```sql
#Query_movie_songs
USE Marvel_team10;
CREATE OR REPLACE VIEW Movie_Songs AS
SELECT movie_name as Movie, songs_name as Songs, CONCAT(composer_lname, ",
", composer_fname) as Composers
FROM songs JOIN movies USING (movie_id) JOIN composers USING (composers_id)
WHERE movie_name != ''
ORDER BY movie_name;
SELECT * from Movie_Songs

#Query_IronMan3_songs
USE Marvel_team10;
CREATE OR REPLACE VIEW Iron_Man3_Songs AS
SELECT songs_name, movie_name
FROM songs JOIN movies USING(movie_id) WHERE movie_name
LIKE "Ir%3";

SELECT * FROM Iron_man_Movies

#Query_Doctor_strange_songs
USE Marvel_team10;
CREATE OR REPLACE VIEW Doctor_Strange_Songs AS
SELECT movie_name, CONCAT(composer_fname, ' ', composer_lname) AS
composer, songs_name
FROM composers JOIN songs USING (composers_id)
JOIN movies USING(movie_id) WHERE movie_name != " " AND movie_name =
"Doctor Strange";

SELECT * FROM Doctor_Strange_Songs

#Query_movies_count
USE Marvel_team10;
CREATE OR REPLACE VIEW movies_count AS
SELECT movie_id, COUNT(movie_id) AS 'movie count', movie_name FROM songs
JOIN movies
USING(movie_id)
WHERE movie_name != ' '
GROUP BY movie_id;

SELECT * from movies_count

#Query_find_a_movie
USE Marvel_team10;
create or replace view find_a_movie as
select hero_name from heroes where actor_id in
(select actor_id from actors where actor_id = 4);
```

```
SELECT * FROM find_a_movie
```