




Virtual base class in C++

Difficulty Level : Medium • Last Updated : 14 Mar, 2019

Virtual base classes are used in virtual inheritance in a way of preventing multiple "instances" of a given class appearing in an inheritance hierarchy when using multiple inheritances.

Need for Virtual Base Classes:

Consider the situation where we have one class **A** .This class is **A** is inherited by two other classes **B** and **C**. Both these class are inherited into another in a new class **D** as shown in figure below.



As we can see from the figure that data members/function of class **A** are inherited twice to class **D**. One through class **B** and second through class **C**.

'hen any data / function member of class **A** is accessed by an object of class ambiguity arises as to which data/function member would be called? One

inherited through ${\bf B}$ or the other inherited through ${\bf C}$. This confuses compiler and it displays error.

Example: To show the need of Virtual Base Class in C++

```
#include <iostream>
using namespace std;
class A {
public:
    void show()
        cout << "Hello form A \n";</pre>
};
class B : public A {
};
class C : public A {
};
class D : public B, public C {
};
int main()
{
    D object;
    object.show();
}
```

Compile Errors:

How to resolve this issue?

To resolve this ambiguity when class **A** is inherited in both class **B** and class **C**, it is declared as **virtual base class** by placing a keyword **virtual** as :

Syntax for Virtual Base Classes:

```
Syntax 1:
class B : virtual public A
{
};

Syntax 2:
class C : public virtual A
{
};
```

Note: virtual can be written before or after the **public**. Now only one copy of data/function member will be copied to class **C** and class **B** and class **A** becomes the virtual base class.

Virtual base classes offer a way to save space and avoid ambiguities in class hierarchies that use multiple inheritances. When a base class is specified as a virtual base, it can act as an indirect base more than once without duplication of its data members. A single copy of its data members is shared by all the base classes that use virtual base.

Example 1

```
#include <iostream>
using namespace std;

class A {
public:
    int a;
    A() // constructor
    {
        a = 10;
    }

class B : public virtual A {
};
```

```
class C : public virtual A {
};

class D : public B, public C {
};

int main()
{
    D object; // object creation of class d
    cout << "a = " << object.a << endl;

    return 0;
}</pre>
```

Output:

```
a = 10
```

Explanation : The class **A** has just one data member **a** which is **public**. This class is virtually inherited in class **B** and class **C**. Now class **B** and class **C** becomes virtual base class and no duplication of data member **a** is done.

Example 2:

```
#include <iostream>
using namespace std;

class A {
public:
    void show()
    {
        cout << "Hello from A \n";
    }
};

class B : public virtual A {
};

class C : public virtual A {
};

class D : public B, public C {

int main()
{</pre>
```


```
D object;
object.show();
}
```

Output:

Hello from A

Want to learn from the best curated videos and practice problems, check out the <u>C++ Foundation Course</u> for Basic to Advanced C++ and <u>C++ STL Course</u> for foundation plus STL. To complete your preparation from learning a language to DS Algo and many more, please refer <u>Complete Interview Preparation</u>

Course.



RECOMMENDED ARTICLES

Behavior of virtual function in the derived class from the base class and abstract class

05, Apr 21

Difference between Virtual function and Pure virtual function in C++

Page: 1 2 3

22, Jan 20

☆

Difference between Base class and Derived class in C++

Publicly inherit a base class but making some of public method