

Web ontwikkeling 3

Lesson 4: XSS

EXAM QUESTIONS...



- ☒ Explain XSS. Use an example and describe in details the solution in order to avoid XSS.
- ☒ What does XSS stand for?
- ☒ ...

XSS

- Cross Site Scripting
 - Security risk
 - Hacker
 - injects **malicious code**
 - into **safe website**
 - Often through script in the browser
- eg. stealing session cookie

LOGIN.JSP

```
<input ... value="{param.username}" />
```



show value again if validation fails

DEMO

afsluiten
value attribute

script

Voornaam

"><script>window.alert('lol')</script>

Familienaam

Voornaam

lol

OK

LOGIN.JSP

```
<input ... value="{param.username}" />
```

```
<input ... value="Mieke" /> → no problem
```

```
<input ... value=""/><script>alert("lol");</script>" />
```

↓
problem!

PROBLEM

- in form
- when reloaded (e.g. after validation errors)
- browser parses previous value
- **if script: executed!**
- example: login.jsp

```
<input ... value="${param.username}" />
```



show value again if validation fails

SOLUTION

- cleanup input
 - convert HTML symbols to **HTML entities**
 - browser: shows them but doesn't interpret it

HTML SPECIAL CHARS

Result	Description	Entity Name	Entity Number
	non-breaking space	 	
<	less than	<	<
>	greater than	>	>
&	ampersand	&	&

JSP

- Use the JSTL
 - `<c: out>` tag OR
 - `{fn:escapeXml()}` function
- for displaying variables
- **escapes HTML/XML tags!**

NOK

```
<form method="post" action="">
  <fieldset>
    <legend>Login</legend>
    <p>
      <label for="username">Username</label>
      <input type="text" id="username" name="username"
        value="${param.username}">
    </p>
  </fieldset>
  <p>
    <input type="submit" id="save" value="Log in">
  </p>
</form>
```

OK

```
<%@taglib prefix="c" uri="http://java.sun.com/jsp/jstl/core" %>
```

```
<form method="post" action="">
  <fieldset>
    <legend>Login</legend>
    <p>
      <label for="username">Username</label>
      <input type="text" id="username" name="username"
        value="<c:out value='${param.username}' />" />
    </p>
  </fieldset>
  <p>
    <input type="submit" id="save" value="Log in" />
  </p>
</form>
```

OK

```
<%@taglib prefix="fn" uri="http://java.sun.com/jsp/jstl/functions" %>
```

```
<form method="post" action="">
  <fieldset>
    <legend>Login</legend>
    <p>
      <label for="username">Username</label>
      <input type="text" id="username" name="username"
        value="${fn:escapeXml(param.username)}">
    </p>
  </fieldset>
  <p>
    <input type="submit" id="save" value="Log in">
  </p>
</form>
```

LOGIN.JSP

```
<input ... value="<c:out value='${param.username}' />" />
```

```
<input ... value="Mieke" /> → no problem
```

```
<input ... value="&#034;/  
&gt;&lt;script&gt;alert(&#034;lol&#034;);&lt;/script&gt;"
```

↓
no problem!