

VULNERABILITY

Puerto	Servicio de Puerto	Version del Servicio
139	Samba	smbd 3.X - 4.X
445	Samba	Smbd 3.0.20-Debian

```
139/tcp open  netbios-ssn syn-ack ttl 64 Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
445/tcp open  netbios-ssn syn-ack ttl 64 Samba smbd 3.0.20-Debian (workgroup: WORKGROUP)
MAC Address: 86:B5:47:52:64:88 (Unknown)

Host script results:
| nbstat: NetBIOS name: VULNERABILITY, NetBIOS user: <unknown>, NetBIOS MAC: <unknown> (unknown)
| Names:
|   VULNERABILITY<00>      Flags: <unique><active>
|   VULNERABILITY<03>      Flags: <unique><active>
|   VULNERABILITY<20>      Flags: <unique><active>
|   WORKGROUP<00>          Flags: <group><active>
|   WORKGROUP<1e>          Flags: <group><active>
| Statistics:
|   00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00
|   00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00
| _ 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00
| smb-os-discovery:
|   OS: Unix (Samba 3.0.20-Debian)
|   Computer name: vulnerability
|   NetBIOS computer name:
|   Domain name:
|   FQDN: vulnerability
| _ System time: 2026-05-08T18:55:08-04:00
| _clock-skew: mean: 1h59m59s, deviation: 2h49m42s, median: 0s
| p2p-conficker:
|   Checking for Conficker.C or higher...
|   Check 1 (port 21783/tcp): CLEAN (Couldn't connect)
|   Check 2 (port 64581/tcp): CLEAN (Couldn't connect)
|   Check 3 (port 58197/udp): CLEAN (Failed to receive data)
```

CVE	Descripción
CVE-2007-2447	Permite ejecución remota de comando Arbitrarios mediante una función SamrChangePassword en la configuración del smb.conf con “username map script” habilitado
CVE-2007-0454	Permite ejecución de código por medio de cadena de formato de sistema de archivos AFS del módulo VFS afsacl.so
CVE-2007-0452	Permite a usuarios autenticados provocar denegación de servicios renombrando un archivo de una forma que previene que una petición sea eliminada de la cola abierta referenciada, esto dispara un bucle infinito