ImgWindow Contrib Library

Modern UI Widgets & Extensions for Dear ImGui in X-Plane Plugins

---

ImGui Contributions in ImgWindow (`contrib/`)

Welcome to the **`contrib/`** directory of **ImgWindow**. This directory houses ImgWindow's bundled library of community-contributed **Dear ImGui (`ImGui::`) extensions and immediate-mode widgets** for X-Plane plugins.

■ Why `contrib/`? (From Debug Menus to Cockpit Instruments)

Pure Dear ImGui is fundamentally an engine designed for game-dev debug menus and developer panels. When flight sim plugin authors try to build user-facing products with it, they immediately hit friction:

- **Tooltips follow the mouse, flicker, and fall off the screen** when moving near the simulator window edges.
- **Help text in tooltips is limited to plain ASCII strings** without headers, bullet lists, bold emphasis, or documentation links.
- **Toggles are clunky checkboxes** rather than tactile, cockpit-grade switches with clear dual-state affordances.
- **Sliders and combos don't respond naturally to the mouse scroll-wheel**, making fine tuning feel clumsy compared to real avionics knobs.
- **There is no standard "revert to default" pattern**, so users fear tweaking settings lest they lose their calibrated values.

Look at the spectrum of UI tasks a flight sim plugin author faces, and how **`contrib/`** covers them today:

Common Cockpit UI Task	Vanilla Dear ImGui Friction	`contrib/` Solution
Interactive Help & Manuals	**`SetTooltip()`** follows the mouse cursor, flickers, and clips outside simulator window boundaries. Limited to plain ASCII strings.	**`ImGui::TimedTooltip`** & **`ImGui::MD`** Stationary anchor after initial delay, low-water wheel reset, smart cursor-avoidance and screen-edge clamping, and full Markdown rendering.
Two-Position Switches	Clunky **`[x]`** checkboxes with no visual state distinction or dual-label tooltips.	**`ImGui::ToggleButton`** Animated physical rocker/toggle switches with font-relative scaling, custom palettes, and automatic dual-state tooltips (**`"Off Hint", "On Hint"`**).
Avionics Dials & Adjusters	Requires click-and-drag. The mouse wheel does nothing, requiring awkward custom tracking.	**`ImGui::MouseWheelSlider`** / **`MouseWheelDrag`** / **`MouseWheelCombo`** Natural mouse-wheel stepping with configurable increments and fine-tune modifier keys.
Fearless Settings Tweaking	No standard "revert to default" pattern; users hesitate to adjust complex tuning parameters.	**`ImGui::AdjustItemOnMouseWheel`** & **Reset Chasers** Inline 1-click restore-to-default icon chaser with instant undo history.
One-Click Clipboard Copying	Requires manual clipboard handling, lacks transient visual feedback, and twitches layout.	**`ImGui::CopyButton`** & **`CopyLastItemButton`** Procedural vector icons (clipboard & checkmark), 1.5s feedback, anti-twitch sizing, and automatic chaser extraction from InputText.

Common Cockpit UI Task	Vanilla Dear ImGui Friction	`contrib/` Solution
Interactive Data Tables	Tables require dozens of manual `TableSetupColumn` / `TableHeadersRow` lines, manual sort callbacks, and custom sizing persistence.	`ImGui::MD` **CommonMark Tables** Standard GFM table syntax with tristate column sorting, divider drag resizing, right-border width grip, A/B toggle memory, and 2-tier comment persistence (`<!-- table-preset: ... -->` / `<!-- table-state: ... -->`).
Universal Vector Icons & Glyphs	Missing glyph diamond boxes (`) when font atlases omit extended Unicode blocks (e.g. ■, ▲, ▼, ✓, ■`).	`ImGui::Icon` **& Procedural Engine** Zero-texture, zero-font procedural vector icon engine. Markdown `<icon ...>`, emoji shortcodes (`:gear:`), fallback link macros (`#[^](ICON_CARET_UP)`), and automatic raw Unicode glyph rescue.
External Docs & Web Links	Raw text URLs or awkward styled buttons with default arrow cursors.	`ImGui::ButtonLink`, `TextLink`, `MenuItemLink` Native OS hand cursors (`ImGuiMouseCursor_Hand`), hover underlines, and one-click browser launch via `XPLMOpenURL`.

■ Quick Start: Just `#include "contrib.h"`

Using `contrib/` requires zero setup or boilerplate. Simply include the master header:

```cpp
#include "contrib.h"
```

> **IMPORTANT**
>
> **macOS Developers: Enable OS Clipboard (`IMGUI_ENABLE_OSX_DEFAULT_CLIPBOARD_FUNCTIONS`)** To enable one-click clipboard copying (`[Copy]` in code blocks) and text selection shortcuts (`Cmd+C`/`Cmd+V`) on macOS: 1. Add `#define IMGUI_ENABLE_OSX_DEFAULT_CLIPBOARD_FUNCTIONS` to your `imconfig.h` (or pass it as a compiler flag). 2. Link `-framework ApplicationServices` in your project linker flags. *(On Windows, clipboard works out of the box via `user32.lib`. On Linux, provide `MarkdownConfig::setClipboardTextFn` or set `ImGui::GetPlatformIO().Platform_SetClipboardTextFn`.)*

All widgets and extensions immediately feel like native Dear ImGui:

```cpp
// 1. Cockpit widgets live directly in ImGui:::
static bool s_HudActive = true;
ImGui::ToggleButton("HUD Active", &amp;s_HudActive);

static float s_Brightness = 0.85f;
ImGui::MouseWheelSlider("Brightness", &amp;s_Brightness, 0.0f, 1.0f, "%.0f%%");

// 2. Extensions mirror standard ImGui text &amp; tooltip vocabulary:
ImGui::Markdown::Text("# Flight Deck\nTelemetry is **active**.");
ImGui::TimedTooltip::Text("Hover-delayed stationary tooltip.");
```

> **TIP**

Forgiving Aliases ("It Just Works") Don't sweat memorizing rigid namespace rules. The library includes transparent aliases so whatever you intuitively reach for compiles cleanly: * Prefer brevity? `ImGui::MD::Text(...)` is an official shorthand alias for `ImGui::Markdown::Text(...)`. * Prefer root access? `ImGui::TextMD(...)` and `ImGui::TextMarkdown(...)` work directly under `ImGui::`. * Combining tooltips and markdown? `ImGui::TimedTooltip::MD::Text` and `ImGui::MD::TimedTooltip::Text` work identically. * Want to skip `ImGui::` completely? `#define CONTRIB_ENABLE_GLOBAL_NAMESPACES` before including `contrib.h` to use `Markdown::`, `MD::`, and `TimedTooltip::` directly in the global scope.

Ecosystem Organization: Multi-Package Container Architecture

The `contrib/` directory serves as an extensible **community container** for Dear ImGui enhancements. Its flagship suite is `ImGee`, an avionics-grade toolkit designed specifically for flight-deck instruments and X-Plane plugin interfaces.

```
ImgWindow/
■■■ contrib.h                              # Master concentrator (-&gt; contrib/includes.h)
■■■ contrib/
    ■■■ includes.h                         # Level-1 Container Switchboard (cascades to packages)
    ■
    ■■■ ImGee/                             # Package 1: ImGee Avionics &amp; UI Toolkit
    ■   ■■■ imgee.h                        # Canonical ImGee master header &amp; IMGEE_* switches
    ■   ■■■ imgee-global.h                 # Opt-in global namespace aliases
    ■   ■■■ docs/
    ■   ■   ■■■ ImGee_User_Guide.md        # Comprehensive User Manual (Publication-ready)
    ■   ■■■ extensions/                    # Subsystems (Typography, Markdown, TimedTooltip)
    ■   ■   ■■■ TimedTooltip/             # Stationary &amp; delayed tooltip engine
    ■   ■   ■■■ Markdown/                 # GFM table parser, column sorter &amp; text renderer
    ■   ■   ■■■ Typography/               # Font roles (ImFontRole) &amp; inline StyledText
    ■   ■■■ widgets/                       # Immediate-mode flight controls &amp; vector icons
    ■       ■■■ imgui_icons.h              # Zero-texture procedural vector icon engine
    ■       ■■■ imgui_knobs.h              # Avionics rotary knobs, dimmer dials &amp; detents
    ■       ■■■ imgui_mouse_wheel_controls.h # Wheel sliders, combos &amp; reset chasers
    ■       ■■■ imgui_badges.h             # Status badges, pills, annunciators &amp; &lt;kbd&gt;
    ■       ■■■ imgui_popup_menus.h        # Directional popups (AboveItem) &amp; pulldowns
    ■       ■■■ imgui_toggle_buttons.h     # Tactile animated rocker/toggle switches
    ■       ■■■ imgui_spinners.h           # Procedural radar sweeps &amp; radial timers
    ■       ■■■ imgui_clickable_links.h    # OS hand cursor links (XPLMOpenURL)
    ■       ■■■ imgui_copy_button.h        # Vector copy buttons with 1.5s visual feedback
    ■       ■■■ imgui_file_dialog.h        # Non-blocking in-sim file dialogs
    ■
    ■■■ extensions/                        # Backward-Compatible Forwarding Headers
    ■■■ widgets/                           # Backward-Compatible Forwarding Headers
```

1. ImGee Suite (`contrib/ImGee/`)

The complete avionics and flight-sim UI design system. See → **ImGee User Guide** and **contrib/ImGee/README.md**.

2. Zero-Breakage Forwarding Shims (`contrib/extensions/`, `contrib/widgets/`)

To guarantee 100% backward compatibility for existing code and downstream CI pipelines, thin forwarding headers remain in `contrib/extensions/` and `contrib/widgets/`, routing cleanly to their canonical locations in `contrib/ImGee/`.

■■ Configuration Reference: Opt-Out Flags

The library provides a hierarchical two-tier configuration matrix:

Tier 1: Master Container & Package Toggles

- `CONTRIB_DISABLE_ALL` (or `DISABLE_CONTRIB`, `IMGWINDOW_DISABLE_CONTRIB`): Completely shuts off the entire `contrib/` ecosystem. Zero contrib code compiled.

- **`IMGEE_DISABLE_ALL`** (or **`CONTRIB_IMGEE_DISABLE_ALL`**): Disables the entire ImGee suite while leaving the container active for future packages.

Tier 2: ImGee Feature & Subsystem Toggles

Uncomment or pass any of these macros to selectively exclude individual ImGee subsystems or widgets:

Canonical Macro Directive	Legacy Alias	Description
`IMGEE_DISABLE_EXTENSIONS`	`CONTRIB_DISABLE_EXTENSIONS`	Excludes all extensions (`Typography`, `Markdown`, `TimedTooltip`).
`IMGEE_DISABLE_WIDGETS`	`CONTRIB_DISABLE_WIDGETS`	Excludes all contributed widgets in `widgets/`.
`IMGEE_DISABLE_ICONS`	`CONTRIB_DISABLE_ICONS`	Excludes procedural vector icon engine and `ImGui::Icon`.
`IMGEE_DISABLE_ICON_BUTTON`	`CONTRIB_DISABLE_ICON_BUTTON`	Excludes `IconButton` and `ButtonIcon` push buttons.
`IMGEE_DISABLE_TYPOGRAPHY`	`CONTRIB_DISABLE_TYPOGRAPHY`	Excludes `ImFontRole` and `ImGui::StyledText`.
`IMGEE_DISABLE_MARKDOWN`	`CONTRIB_DISABLE_MARKDOWN`	Excludes Markdown parser, GFM tables, and callouts.
`IMGEE_DISABLE_TIMED_TOOLTIP`	`CONTRIB_DISABLE_TIMED_TOOLTIP`	Excludes stationary delayed tooltip engine.
`IMGEE_DISABLE_KNOBS`	`CONTRIB_DISABLE_KNOBS`	Excludes avionics rotary knobs, dials, and detents.
`IMGEE_DISABLE_MOUSE_WHEEL_CONTROLS`	`CONTRIB_DISABLE_MOUSE_WHEEL_CONTROLS`	Excludes mouse-wheel sliders, drags, combos, and reset buttons.
`IMGEE_DISABLE_BADGES`	`CONTRIB_DISABLE_BADGES`	Excludes status badges, pills, annunciators, and keycaps.
`IMGEE_DISABLE_POPUP_MENUS`	`CONTRIB_DISABLE_POPUP_MENUS`	Excludes directional anchored popups (`AboveItem`) and pulldowns.
`IMGEE_DISABLE_TOGGLE_BUTTONS`	`CONTRIB_DISABLE_TOGGLE_BUTTONS`	Excludes animated physical toggle switches.
`IMGEE_DISABLE_CLICKABLE_LINKS`	`CONTRIB_DISABLE_CLICKABLE_LINKS`	Excludes OS hand cursor links (`ButtonLink`, `TextLink`).
`IMGEE_DISABLE_SPINNERS`	`CONTRIB_DISABLE_SPINNERS`	Excludes activity spinners and countdown timer dials.
`IMGEE_ENABLE_GLOBAL_NAMESPACES`	`CONTRIB_ENABLE_GLOBAL_NAMESPACES`	Publishes `Markdown::`, `MD::`, and `TimedTooltip::` to global scope.

(Note: Legacy `CONTRIB_DISABLE_*` flags are automatically mapped via an internal alias bridge in `contrib/ImGee/imgee.h` with zero build warnings.)

How to Contribute

We welcome community contributions! Whether porting an existing open-source widget or introducing a new UI component:

1. **Choose the Category:** Determine if your code is a standalone **Widget** (a single control in `widgets/`) or a full **Extension** (a package in `extensions/`).
2. **Namespace Appropriately:** Follow the namespacing rules above.
3. **Keep Dependencies Minimal:** Header-only or clean single-file implementations are strongly preferred.
4. **Document Your Work:** Include a dedicated `README.md` in your extension folder detailing usage, API signatures, and code examples.
5. **Open a PR:** Submit a Pull Request against the repository with a description and sample screenshot or code snippet.

ImGee: Avionics & Flight-Sim UI Toolkit for Dear ImGui

Comprehensive Developer & User Manual (v2.4.0)

1. Executive Architecture & Design Philosophy

`Dear ImGui` is an immediate-mode graphical user interface library built fundamentally for game-engine debugging, tool development, and developer panels. When flight simulator plugin developers attempt to build production-grade avionics interfaces, settings windows, or interactive kneeboards with stock Dear ImGui, they immediately encounter several fundamental architectural gaps:

1. **Missing Glyphs and Font Atlas Friction:** Standard font atlases omit extended Unicode mathematical and symbol blocks (such as ■, ▲, ▼, ✓, ■, or ✍), resulting in missing-glyph diamond boxes (**`?`** or placeholder squares) unless heavy custom icon fonts are baked into VRAM.
2. **Volatile Tooltips:** Vanilla **`ImGui::SetTooltip()`** follows the mouse cursor frame-by-frame, continuously flickering, resetting scroll state, and clipping off-screen when hovering near flight simulator window borders.
3. **Clunky Input Affordances:** Checkboxes look like desktop form controls rather than physical cockpit switches; sliders do not respond naturally to the mouse scroll wheel; and there is no universal "revert to calibrated default" pattern for complex tuning parameters.
4. **Rigid Text Rendering:** Stock text rendering lacks inline semantic sizing, baseline alignment, and formatted Markdown tables with column resizing and persistent sorting.

`ImGee` is an immediate-mode avionics and flight-simulation UI toolkit designed to bridge these gaps. Bundled as the premier package within the **`ImgWindow`** **`contrib/`** ecosystem, ImGee turns Dear ImGui into a cockpit-grade design system with zero mandatory dependencies, zero runtime allocations in hot loops, and complete backward compatibility.

```
ImgWindow/
■■■ contrib.h                          # Master Concentrator (-&gt; contrib/includes.h)
■■■ contrib/
    ■■■ includes.h                     # Level-1 Container Package Switchboard
    ■
    ■■■ ImGee/                         # The ImGee Flight-Deck UI Suite
    ■   ■■■ imgee.h                    # Canonical ImGee Master Header &amp;amp; Opt-Out Toggles
    ■   ■■■ imgee-global.h              # Opt-in Global Scope Aliases
    ■   ■■■ docs/
    ■   ■   ■■■ ImGee_User_Guide.md    # Comprehensive User Manual (this document)
    ■   ■■■ extensions/                 # Subsystems (Typography, Markdown, TimedTooltip)
    ■   ■■■ widgets/                    # Immediate-mode flight controls &amp;amp; vector icons
    ■
    ■■■ extensions/                    # Zero-breakage Forwarding Headers
    ■■■ widgets/                       # Zero-breakage Forwarding Headers
```

2. Integration & Inclusion Models

2.1 The Front Door: `contrib.h`

For standard plugins, integration requires a single line:

```cpp
#include "contrib.h"
```

This single include opens the master package switchboard (**`contrib/includes.h`**), which automatically pulls in **`contrib/ImGee/imgee.h`**. All widgets and extensions are registered under the standard **`ImGui::`** namespace.

2.2 Direct Suite Inclusion: `contrib/ImGee/imgee.h`

If your project manages multiple vendor packages or prefers strict package isolation, you can include ImGee directly:

```cpp
#include "contrib/ImGee/imgee.h"
```

2.3 Container-Level vs. Package-Level Opt-Out Switches

ImGee provides a hierarchical two-tier preprocessor configuration matrix:

Preprocessor Define	Scope	Description
`CONTRIB_DISABLE_ALL`	Container	Completely disables the entire `contrib/` folder. Zero contrib code compiled.
`IMGEE_DISABLE_ALL` (or `CONTRIB_IMGEE_DISABLE_ALL`)	Package	Excludes the entire ImGee suite while allowing other contrib packages.
`IMGEE_DISABLE_EXTENSIONS`	Subsystem	Excludes Typography, Markdown, and TimedTooltip.
`IMGEE_DISABLE_WIDGETS`	Subsystem	Excludes all rotary knobs, sliders, badges, toggles, and popups.
`IMGEE_DISABLE_ICONS`	Feature	Excludes the procedural vector icon rendering engine.
`IMGEE_DISABLE_KNOBS`	Feature	Excludes avionics rotary knobs and dimmer dials.
`IMGEE_DISABLE_MOUSE_WHEEL_CONTROLS`	Feature	Excludes wheel sliders, drags, combos, and reset chasers.
`IMGEE_DISABLE_BADGES`	Feature	Excludes badges, status pills, annunciators, and keycaps.
`IMGEE_DISABLE_POPUP_MENUS`	Feature	Excludes directional anchored popups and pulldowns.
`IMGEE_ENABLE_GLOBAL_NAMESPACES`	Namespaces	Exposes `Markdown::`, `MD::`, and `TimedTooltip::` to global scope.


> **NOTE**
>
> **Legacy Alias Bridge:** For projects written against earlier versions of ImgWindow, legacy switches like `CONTRIB_DISABLE_WIDGETS`, `CONTRIB_DISABLE_BADGES`, and `CONTRIB_DISABLE_MARKDOWN` are automatically mapped to their canonical `IMGEE_*` counterparts with zero build warnings.

---

3. Procedural Vector Icon Engine & Glyphs

Standard Dear ImGui plugins often suffer from missing glyphs when attempting to display symbols like reset arrows (■), sort carets (▲, ▼), checkmarks (✓), gears (■), or airplanes (✈).

ImGee includes a **zero-texture, zero-font procedural vector engine** (`imgui_icons.h`). It submits antialiased geometric primitives (lines, arcs, bezier curves, triangles) directly to Dear ImGui's active `ImDrawList`.



3.1 Icon Catalog & Normalization

The engine understands dozens of canonical aliases, FontAwesome names, emoji shortcodes, and raw UTF-8 glyphs:

- **Reset / Undo:** `"undo"`, `":undo:"`, `"ICON_FA_UNDO"`, `"reset"`, `"\xE2\x86\xBA"` (■)
- **Redo / Restore:** `"redo"`, `":redo:"`, `"\xE2\x86\xBB"` (■)
- **Carets & Navigation:** `"caret-up"` (▲), `"caret-down"` (▼), `"caret-left"` (■), `"caret-right"` (■)
- **Actions:** `"check"` (✓, ✔), `"cross"` (✗, ✘), `"plus"` (+), `"minus"` (-)
- **Cockpit / Utility:** `"gear"` / `"settings"` (■), `"plane"` / `"aircraft"` (✈), `"info"` (■), `"warning"` (■), `"star"` (★), `"search"` (■)

3.2 Submitting Inline Vector Icons

Use `ImGui::Icon()` to draw an icon inline with current text:

```cpp
// Auto-sizes to 90% of active font size, aligned to text baseline
ImGui::Text("Calibrated Heading:");
ImGui::SameLine();
ImGui::Icon("plane");

// Explicit size (24x24 px) with custom status color
ImVec4 warnCol(1.0f, 0.75f, 0.1f, 1.0f);
ImGui::Icon("warning", 24.0f, &amp;warnCol);
```

3.3 Vector Push-Buttons: `IconButton` & `ButtonIcon`

ImGee provides turnkey button helpers that render procedural vector icons without font dependencies:

```cpp
// 1. Square Icon-Only Button with native hand cursor and tooltip
if (ImGui::IconButton("##ResetHdg", "undo", ImVec2(0, 0), "Reset Heading to 360°")) {
    s_Heading = 360.0f;
}

// 2. Icon + Text Button (Icon on Left)
if (ImGui::ButtonIcon("Settings", "gear")) {
    OpenSettingsDialog();
}

// 3. Text + Icon Button (Icon on Right)
if (ImGui::ButtonIcon("Next Waypoint", "caret-right", ImVec2(160, 0), /*icon_on_right=*/true)) {
    AdvanceWaypoint();
}
```

4. Semantic Typography & Inline Sized Text

Cockpit user interfaces require strict typographic hierarchy: primary instruments need large, legible digits; captions and annunciator legends require micro-typography; and datarefs require clear monospaced alignment.

ImGee provides two complimentary typography systems:

1. **Semantic Font Roles (`ImFontRole`):** An 8-slot registry linking logical design roles to loaded rasterized fonts with automatic hierarchical fallbacks.
2. **Inline Styled Text Engine (`ImGui::StyledText`):** Lightweight XML-style tag parsing with baseline alignment and zero Markdown document overhead.

4.1 The `ImFontRole` Registry

```cpp
enum class ImFontRole {
    Regular = 0,        // Slot 0: Primary interface font (e.g. 14px)
    Title,              // Slot 1: Section headers, dialog titles (e.g. 16px)
    Small,              // Slot 2: Captions, annotations, secondary subtext (e.g. 12px)
    Bold,               // Slot 3: Strong emphasis, table headers (e.g. Bold 14px)
    BoldLarge,          // Slot 4: Hero banners, major readouts (e.g. Bold 16px)
    Monospace,          // Slot 5: Datarefs, callsigns, frequencies (e.g. Mono 14px)
    Italic,             // Slot 6: Citations, hints, metadata (e.g. Italic 14px)
    MonospaceMedium,    // Slot 7: Numeric avionics readouts (e.g. Mono Medium 15px)
    Tiny                // Micro subtext, annunciator legends (e.g. 10px / fallback to Small)
};
```

Direct C++ Typography Helpers

Instead of manually pushing and popping fonts from ImGui's font stack, use convenient direct helpers:

```cpp
ImGui::TitleText("Primary Flight Display Configuration");
ImGui::SmallText("Sub-channel frequency: %0.2f MHz", s_Freq);
ImGui::TinyText("ANNUNCIATOR BUS VOLTAGE OK");
ImGui::MonoText("sim/cockpit2/radios/actuators/nav1_frequency_hz");
```

4.2 Inline Sized Text Tags (`ImGui::StyledText`)

`ImGui::StyledText` allows embedding sizing, bolding, colors, and badges directly inside text strings:

```cpp
ImGui::StyledText("Altimeter: &lt;huge color=#38BDF8&gt;29.92&lt;/huge&gt; &lt;small&gt;IN HG&lt;/small&gt;");
ImGui::StyledText("Engine 1: &lt;badge-success&gt;NORMAL&lt;/badge-success&gt; | EGT: &lt;mono&gt;645°C&lt;/mono&gt;");
```

Supported Inline Tags:

- **Sizing Tags:** `<tiny>`, `<small>`, `<regular>`, `<big>`, `<large>`, `<huge>`
- **Style Tags:** `<b>` / `<strong>`, `<i>` / `<em>`, `<mono>` / `<code>`, `<h1>`, `<h2>`, `<h3>`
- **Color Tag:** `<color=#RRGGBB>Text</color>` or `<color=#RGB>`
- **Embedded Badges & Pills:** `<badge>Text</badge>`, `<badge-danger>FAIL</badge-danger>`, `<pill>VFR</pill>`
- **Keycaps:** `<kbd>Ctrl+Alt+P</kbd>`
- **Inline Vector Icons:** `<icon name=gear size=14 color=#94A3B8 />`
- **Named Memory Images:** `<image name=logo width=32 height=32 />`


> **TIP**
>
> **Sub-pixel Baseline Alignment:** When mixing **<huge>** numbers with **<small>** units on the same line, ImGee automatically calculates font ascent offsets, keeping the bottoms of all glyphs locked to a common visual baseline.

---

5. Flight-Deck Avionics Widgets

5.1 Avionics Rotary Knobs & Dimmer Dials (`imgui_knobs.h`)

Standard sliders feel unnatural for cockpit instruments. **`ImGui::Knob`** implements an avionics-grade potentiometer:



Features:

1. **270-Degree "Omega" Arc:** An open deadband at 6 o'clock immediately communicates an interactive dial.
2. **Tactile Two-Step Detente Switch:** Counter-clockwise rotation dims smoothly down to minimum operating value (e.g., 5%). A deliberate extra mouse-wheel click or drag snaps across the detente gap into the powered-down **`"OFF"`** state. Rotating clockwise from **`"OFF"`** snaps instantly back to minimum active power.
3. **Scroll-Wheel Primary:** Hover and roll the wheel with fine-tuning modifiers (**`Shift`** for 10x, **`Alt`**/**`Ctrl`** for 0.1x).

```cpp
[CPP]
static float s_InstrumentLight = 0.75f;

// 1. Standard Knob with perimeter ticks
ImGui::Knob("Panel Light", &amp;s_InstrumentLight, 0.0f, 1.0f,
            ImGuiKnobFlags_ShowTicks | ImGuiKnobFlags_ValueBelow);

// 2. Composite Knob with Reset Chaser
static const float s_DefaultLight = 0.80f;
ImGui::KnobWithReset("Backlight", &amp;s_InstrumentLight, 0.0f, 1.0f,
                     s_DefaultLight, "%.0f%%");
```

5.2 Mouse-Wheel Sliders & Reset Chasers (`imgui_mouse_wheel_controls.h`)

Settings tweaking in flight simulations is fraught with user anxiety: if an author tweaks an aircraft trim or graphic setting, they fear losing their calibrated value.

ImGee solves this with **Inline 1-Click Restore-to-Default Chasers**:

```cpp
[CPP]
static float s_Gamma = 2.2f;
static const float s_DefaultGamma = 2.2f;

// Renders slider with natural mouse-wheel stepping and a ■ button that appears
// whenever s_Gamma differs from s_DefaultGamma. Clicking restores default instantly.
ImGui::SliderWithReset("Display Gamma", &amp;s_Gamma, 1.0f, 3.0f, s_DefaultGamma, "%.2f");
```

Universal Mouse-Wheel Adjuster: `AdjustItemOnMouseWheel`

Want to add scroll-wheel support and a reset chaser to any stock Dear ImGui widget? Use **`AdjustItemOnMouseWheel`**:

```cpp
static float s_Volume = 0.70f;
ImGui::SliderFloat("Master Volume", &amp;s_Volume, 0.0f, 1.0f);
ImGui::AdjustItemOnMouseWheel(&amp;s_Volume, 0.01f, 0.0f, 1.0f, 0.70f);
```

Viewport Scroll Defeat

In stock Dear ImGui, rolling the mouse wheel over a slider inside a scrollable window causes the window to scroll awkwardly instead of adjusting the setting. ImGee features automatic **scroll defeat**: when hovering an interactive wheel control, parent window scrolling is cleanly inhibited.

5.3 Badges, Pills & Annunciators (`imgui_badges.h`)

ImGee provides semantic status indicators with automatic high-contrast text calculation:

```cpp
// 1. Semantic Badges
ImGui::Badge("ONLINE", ImGuiBadgeVariant_Success);
ImGui::SameLine();
ImGui::Badge("CAUTION", ImGuiBadgeVariant_Warning);
ImGui::SameLine();
ImGui::Badge("FAULT", ImGuiBadgeVariant_Danger);

// 2. Rounded Flight Status Pills
ImGui::Pill("AUTOPILOT: NAV", IM_COL32(37, 99, 235, 255));

// 3. Unary Flight-Deck Annunciator Pill (Flash / Invert on Master Warning)
ImGui::AnnunciatorPill("FIRE ENG 1", /*active=*/s_FireWarning, /*caution=*/false);

// 4. Keyboard Shortcut Caps
ImGui::Text("Toggle HUD:");
ImGui::SameLine();
ImGui::Kbd("Ctrl+Shift+H");
```

5.4 Directional Anchored Popups & Pulldowns (`imgui_popup_menus.h`)

Standard Dear ImGui popups appear at the mouse cursor position. For cockpit panels and status bars docked at the bottom of the screen, menus need to blossom **upward** relative to their launcher button.




```cpp
if (ImGui::Button("COM 1 Frequency")) {
    ImGui::OpenPopupAtItem("ComPopup", ImGuiPopupAnchor_AboveItem);
}

if (ImGui::BeginAnchoredPopup("ComPopup", ImGuiPopupAnchor_AboveItem)) {
    if (ImGui::Selectable("118.10 MHz (Tower)")) SetCom1(118100);
    if (ImGui::Selectable("121.90 MHz (Ground)")) SetCom1(121900);
    ImGui::EndAnchoredPopup();
}
```

Muscle-Memory Toggle Safety

Clicking the opener button while an anchored popup is already open cleanly toggles it closed, eliminating the annoying double-open flicker present in vanilla ImGui menus.

5.5 Physical Animated Toggle Switches (`imgui_toggle_buttons.h`)

Replace generic checkboxes with tactile two-position switches:

```cpp
static bool s_PitotHeat = true;
// Renders an animated rocker switch with dual-state hover tooltips
ImGui::ToggleButton("Pitot Heat", &amp;s_PitotHeat, "Heaters OFF (Risk of Icing)", "Heaters ON");
```

6. Rich Markdown Engine & GFM Tables

The ImGee Markdown engine (`imgui_markdown_ext.h`) transforms plain text strings into fully interactive documentation:

```cpp
const char* doc = R"(
# Flight Operations Manual
The **Autopilot Flight Director System** (AFDS) manages aircraft trajectory.

### Status Annunciations
| Mode | Status | Armed | Minimum Speed |
| :--- | :---: | :---: | :--- |
| **LNAV** | &lt;badge-success&gt;ENGAGED&lt;/badge-success&gt; | Yes | `V2 + 15` |
| **VNAV** | &lt;badge-warning&gt;ARMED&lt;/badge-warning&gt; | Yes | `250 KTS` |
| **ILS** | &lt;badge&gt;STANDBY&lt;/badge&gt; | No | `VREF + 5` |

&gt; [!NOTE]
&gt; Ensure barometric altimeters are set to standard pressure (29.92 IN HG / 1013 HPA) when passing transition altitude.
)";

ImGui::Markdown::Text(doc);
```

6.1 GFM Interactive Table Features

- **Tristate Column Sorting:** Click any column header to cycle Ascending $\rightarrow$ Descending $\rightarrow$ Default sort.
- **Interactive Drag Sizing:** Adjust column dividers directly.
- **Persistent Presets:** Save and restore column widths via inline comment tags (`<!-- table-state: ... -->`).
- **Code Block Copy Buttons:** Code blocks automatically include one-click clipboard copying with 1.5s visual feedback.

7. Stationary Anchored Tooltips (`imgui_tooltip_ext.h`)

Vanilla tooltips follow the cursor like a bee, creating visual distraction and clipping out-of-sim. ImGee provides stationary anchored tooltips:

```cpp
// 1. Plain text stationary tooltip
ImGui::Button("Flaps 15");
ImGui::TimedTooltip::Text("Takeoff flap detent. Generates additional lift with moderate drag.");

// 2. Full Markdown stationary tooltip
ImGui::Button("GPWS");
ImGui::TimedTooltip::TextMD(
    "### Ground Proximity Warning System\n"
    "* **Terrain Ahead:** Pull up immediately.\n"
    "* **Glideslope:** Deviation exceeds 1.3 dots."
);
```

Key Tooltip Affordances:

- **Initial Delay:** Prevents accidental popup spam while sweeping the mouse across controls.
- **Stationary Anchor:** Freezes in position once visible, allowing effortless reading.
- **Smart Screen Clamping:** Automatically nudges inside the X-Plane main monitor boundaries.
- **Wheel-Defeat Dismissal:** Rolling the mouse wheel immediately closes the tooltip so it never blocks scrolling views.

---

8. Summary of Preprocessor Configuration Flags

Add any of these defines to your project or **`imconfig.h`** to tailor ImGee to your specific binary footprint requirements:

```cpp
// --- Master Opt-Out ---
#define CONTRIB_DISABLE_ALL                  // Exclude entire contrib container
#define IMGEE_DISABLE_ALL                    // Exclude entire ImGee suite

// --- Subsystem Opt-Outs ---
#define IMGEE_DISABLE_EXTENSIONS             // Exclude Typography, Markdown, Tooltips
#define IMGEE_DISABLE_WIDGETS                // Exclude all cockpit widgets

// --- Granular Feature Opt-Outs ---
#define IMGEE_DISABLE_ICONS                  // Exclude procedural vector icon engine
#define IMGEE_DISABLE_ICON_BUTTON            // Exclude IconButton / ButtonIcon
#define IMGEE_DISABLE_TYPOGRAPHY             // Exclude Font Roles and StyledText
#define IMGEE_DISABLE_MARKDOWN               // Exclude Markdown parser and tables
#define IMGEE_DISABLE_TIMED_TOOLTIP          // Exclude TimedTooltip engine
#define IMGEE_DISABLE_KNOBS                  // Exclude avionics rotary knobs
#define IMGEE_DISABLE_MOUSE_WHEEL_CONTROLS   // Exclude wheel sliders and combo controls
#define IMGEE_DISABLE_BADGES                 // Exclude badges, pills, and keycaps
#define IMGEE_DISABLE_POPUP_MENUS            // Exclude directional anchored popups
#define IMGEE_DISABLE_TOGGLE_BUTTONS         // Exclude animated toggle switches
#define IMGEE_DISABLE_CLICKABLE_LINKS        // Exclude OS link buttons and hand cursors

#define IMGEE_DISABLE_SPINNERS               // Exclude radar spinners and countdowns

// --- Opt-In Features ---
#define IMGEE_ENABLE_GLOBAL_NAMESPACES       // Publish Markdown:: and TimedTooltip:: to global scope
```

Document Version: 2.4.0 • Author: Steven L. Goldberg (@slgoldberg) • ImgWindow Contrib Suite

ImGui Extra Widgets

This directory contains lightweight, reusable, immediate-mode **Widgets** extending Dear ImGui within the **ImgWindow** framework.

Unlike **Extensions** (which manage their own complex background subsystems, registries, and configuration structures), **Widgets** are self-contained immediate-mode controls. They hook directly into Dear ImGui's ambient context (`GImGui`, ID stack, `ImGuiStorage`, and window draw lists) and live directly in the root `ImGui::` namespace to feel completely native.

Architecture & Inclusion Strategy

1. Root `ImGui::` Namespacing

All widgets in this directory are injected directly into `namespace ImGui { ... }`. You call `ImGui::ToggleButton(...)`, `ImGui::SliderWithReset(...)`, `ImGui::PercentSlider(...)`, and `ImGui::ButtonLink(...)` just like Dear ImGui's built-in `ImGui::Checkbox` or `ImGui::SliderFloat`.

2. The 4-Tier Inclusion Model

Pattern	Usage	Benefit
Master Contrib Roll-Up	`#include "ImgWindow/contrib.h"` *(or* `"contrib/includes.h"`*)*	Includes **all** extensions (`TimedTooltip`, `Markdown`) and contributed widgets in guaranteed dependency order.
Widgets Roll-Up	`#include "ImgWindow/contrib/widgets.h"` *(or* `"contrib/widgets/includes.h"`*)*	Instant access to the entire widget collection in one line.
A-la-Carte	`#include "ImgWindow/contrib/widgets/imgui_mouse_wheel_controls.h"`	Include only the specific control family you need.
Opt-Out Macros	`#define CONTRIB_DISABLE_<FEATURE>`	Zero conflict if your project already defines a conflicting identifier.

Opt-Out Configuration Flags

If your project defines a function with the same name, define any of the following canonical macros *before* including `contrib.h` or `widgets.h` (`IMGUI_CONTRIB_DISABLE_*`, `IMGUI_DISABLE_CONTRIB_*`, and legacy `IMGUI_DISABLE_EXTRA_*` macro names are also honored automatically):

```[CPP]
#define CONTRIB_DISABLE_TOGGLE_BUTTONS        // Disables ToggleButton &amp;amp; ToggleButtons
#define CONTRIB_DISABLE_TOGGLE_MOUSE_WHEEL    // Disables mouse-wheel support on ToggleButton &amp;amp; ToggleButtons
#define CONTRIB_DISABLE_MOUSE_WHEEL_CONTROLS  // Disables all wheel sliders, drags, cyclers &amp;amp; combos
#define CONTRIB_DISABLE_CLICKABLE_LINKS       // Disables ButtonLink, TextLink &amp;amp; AttachItemCursor
#define CONTRIB_DISABLE_BADGES                // Disables Badge, Pill &amp;amp; Kbd widgets
#define CONTRIB_DISABLE_SPINNERS              // Disables Spinner, RadialTimer &amp;amp; CountdownTimer
#define CONTRIB_DISABLE_COPY_BUTTON           // Disables CopyButton, CopyLastItemButton &amp;amp; semantic aliases
#define CONTRIB_DISABLE_POPUP_MENUS           // Disables SelectPulldown, OpenPopupAtItem &amp;amp; BeginAnchoredPopup
#define CONTRIB_DISABLE_ICONS                 // Disables procedural vector icon engine &amp;amp; ImGui::Icon
#define CONTRIB_DISABLE_ICON_BUTTON           // Disables IconButton &amp;amp; ButtonIcon push-button widgets
#define CONTRIB_DISABLE_GET_MOUSE_WHEEL       // Disables GetMouseWheel* primitives
#define CONTRIB_DISABLE_ADJUST_MOUSE_WHEEL    // Disables AdjustItemOnMouseWheel()
#define CONTRIB_DISABLE_CYCLE_MOUSE_WHEEL     // Disables CycleItemOnMouseWheel()
#define CONTRIB_DISABLE_PERCENT_SLIDER        // Disables PercentSlider() &amp;amp; SliderPercent()
#define CONTRIB_DISABLE_SLIDER_PERCENT        // Disables only the SliderPercent() alias
#define CONTRIB_DISABLE_MOUSE_WHEEL_COMBO     // Disables MouseWheelCombo &amp;amp; ComboWithReset
#define IMGUI_CONTRIB_DISABLE_RESET_UNDO      // Disables 1-click Reset-with-Undo (restore previous value)

// Optional compile-time icon &amp;amp; chevron style customization:
#define IMGUI_CONTRIB_DEFAULT_RESET_LABEL          ICON_FA_UNDO     // Custom primary reset icon (default:
```

```
#define IMGUI_CONTRIB_DEFAULT_RESET_LABEL_ALT      ICON_FA_REDO     // Custom restore/redo icon (default: v
#define IMGUI_CONTRIB_DEFAULT_COMBO_ARROW_STYLE     ImGui::ComboArrowStyle_RightWhenClosed // Combo chevron
#define IMGUI_CONTRIB_DEFAULT_PULLDOWN_CARET_DOWN  ICON_FA_CHEVRON_DOWN // Custom pulldown down-caret (defa
#define IMGUI_CONTRIB_DEFAULT_PULLDOWN_CARET_UP    ICON_FA_CHEVRON_UP   // Custom pulldown up-caret (defaul
```

Widget Catalog

1. Toggle Controls (`imgui_toggle_buttons.h`)

A. Animated Toggle Switch (`ImGui::ToggleButton`)

A modern, iOS / Material-design rounded pill switch with a smoothly sliding circular thumb. Accepts both `bool*` and `int*` state variables.

```cpp
#include "contrib/widgets/imgui_toggle_buttons.h"

static bool s_ExpertMode = false;
static int  s_SmoothTransitions = 1;

// 1. Standard switch with clickable label on the right:
ImGui::ToggleButton("Expert Mode", &amp;s_ExpertMode);

// 2. Direct reference syntax (no &amp; required):
ImGui::ToggleButton("Expert Mode", s_ExpertMode);

// 3. Compact switch without visible label (uses ID only):
ImGui::ToggleButton("##hud_switch", &amp;s_HudActive);

// 4. Direct dual-string per-state tooltips (Off tooltip, On tooltip):
ImGui::ToggleButton("HUD Overlay", &amp;s_HudActive,
                    "HUD is currently **OFF**.\n- Click to enable overlay.",
                    "HUD is currently **ON**.\n- Click to disable overlay.");

// 5. Array-based per-state tooltips ({ Off tooltip, On tooltip }):

static const char* const kTransitionTooltips[] = {
    "Smooth transitions are **OFF** (instant snap).\n- Click or scroll **up** on the switch to enable.",
    "Smooth transitions are **ON** (animated).\n- Click or scroll **down** on the switch to disable."
};
ImGui::ToggleButton("Smooth Transitions", &amp;s_SmoothTransitions, ImVec2(0, 0), kTransitionTooltips);

// Optional: Customize switch active track &amp; thumb colors globally:
ImGui::SetDefaultToggleButtonColors(ImVec4(0.26f, 0.59f, 0.98f, 1.0f)); // Active track color
// Or via ImU32:
ImGui::SetDefaultToggleButtonColors(ABCIM_COL32(HILITE_COLOR));
```

- **Features:**
- Frame-rate independent sliding animation powered by `io.DeltaTime` and stored per-widget in `ImGuiStorage`.
- **Flexible Types & Syntax:** Accepts `bool*`, `int*`, `bool&`, or `int&` (`0` = Off, non-zero = On).
- **Global Theme Integration (`SetDefaultToggleButtonColors`):** Easily set the switch track/thumb colors globally via `ImVec4` or `ImU32`. Defaults to your theme's active highlight color (`ImGuiCol_ButtonActive`).
- **Built-In Clamped Mouse-Wheel Support (`allow_mouse_wheel = true`):** Spinning the scroll wheel up/right over the pill switch turns it **On** and clamps there; spinning down/left turns it **Off** and clamps there (never wraps). Hovering over the text label does *not* capture the mouse wheel, preventing accidental toggles when scrolling windows.
- **Per-State Tooltips:** Supports both direct dual-string parameters (`off_tooltip`, `on_tooltip`) and 2-element string arrays (`{ off_tooltip, on_tooltip }`) automatically rendered via `TimedTooltip::TextMDProxy` (or standard `SetTooltip` fallback).
- **Responsive Auto-Scaling:** Switch dimensions scale naturally with the ambient font size (0.78x ambient frame height for standard switches, 0.60x for compact switches), looking crisp on standard, Retina, and 4K displays, with support for

explicit `ImVec2 size` overrides.

- Automatic hand pointer cursor (`ImGuiMouseCursor_Hand` by default, customizable via `hover_cursor` or `IMGUI_EXTRA_TOGGLE_DEFAULT_CURSOR`).

B. Segmented Dual-Button Pair (`ImGui::ToggleButtons`)

Joined side-by-side buttons for explicit binary selections (`Off` / `On`, `Solid Opaque` / `Glass Translucent`). Accepts both `int*` and `bool*`.

```cpp
static int s_WindowStyle = 0; // 0 = Solid Opaque, 1 = Glass Translucent

// 1. Compact pair without a right-side label (starts with "##"):
if (ImGui::ToggleButtons("##style_toggle", &amp;s_WindowStyle, "Solid Opaque", "Glass Translucent")) {
    ApplyStyleChange();
}

// 2. With clickable right-side title ("Surface Style") and wheel-latched hover index:
int hovered_idx = -1;
ImGui::ToggleButtons("Surface Style##style_pair", &amp;s_WindowStyle, "Solid Opaque", "Glass Translucent",
                     ImVec2(130.0f, 0.0f), nullptr /* item_tooltips */, &amp;hovered_idx);
```

- **Features:**
- **Optional Right-Side Clickable Title:** Following standard Dear ImGui `"Title##id"` semantics, if `label` contains text before `"##"`, it is drawn to the right of the button pair, shows a Hand cursor on hover, toggles the state on click, and ignores the mouse wheel.
- **Clamped Mouse-Wheel Toggling:** Scrolling up/right over either button selects `1` (`label_on`); scrolling down/left selects `0` (`label_off`).
- **Per-Button Tooltips (`item_tooltips`) & Wheel-Selection Tooltip Latch (`out_hovered_item`):** When the user spins the mouse wheel over either button to change the state, tooltip targeting (and `*out_hovered_item`) automatically latches onto the newly selected button (`0` or `1`)—even if the stationary mouse cursor is still parked over the unselected button—until the mouse moves (`> 1.5px`).

---

2. Mouse-Wheel Sliders, Drag Boxes, Cyclers & Combos (`imgui_mouse_wheel_controls.h`)

A. Core Mouse-Wheel Primitives (`ImGui::GetMouseWheel` / `GetMouseWheelV` / `GetMouseWheelH` / `GetMouseWheelEither`)

Queries vertical (`GetMouseWheel` / `GetMouseWheelV`), horizontal (`GetMouseWheelH`), or either-axis (`GetMouseWheelEither`, alias `GetMouseWheelAny`) scroll-wheel deltas for the current frame. Passing `consume = true` zeroes out `io.MouseWheel` / `io.MouseWheelH` so parent scrollable windows do not scroll while adjusting a hovered control.

```cpp
float clicks = ImGui::GetMouseWheelEither(true /* consume event */);
```

B. Continuous Range Chaser (`ImGui::AdjustItemOnMouseWheel`)

Attaches to **any** preceding continuous range item (`SliderFloat`, `SliderInt`, `DragFloat`, `DragInt`, etc.) via `ImGui::IsItemHovered()`. Overloaded for both `float*` and `int*`, it interprets vertical/horizontal mouse-wheel clicks, consumes the wheel event, and clamps boundaries.

- **Track-Only Cursor Precision:** Switches the cursor to East-West resize arrows (`ImGuiMouseCursor_ResizeEW` by default) strictly when hovering over the physical control track/box, preserving standard arrow cursors over text labels.

```cpp
#include "contrib/widgets/imgui_mouse_wheel_controls.h"

// Attach mouse-wheel adjustment to any standard ImGui slider or drag box:
ImGui::SliderFloat("Text Zoom", &amp;fontZoom, 0.75f, 1.75f);
ImGui::AdjustItemOnMouseWheel(&amp;fontZoom, 0.75f, 1.75f, 0.01f);

ImGui::DragInt("Altitude", &amp;alt, 10.0f, 0, 40000);
ImGui::AdjustItemOnMouseWheel(&amp;alt, 0, 40000, 100.0f);
```

C. Discrete Choice Chaser (`ImGui::CycleItemOnMouseWheel`)

Attaches to **any** preceding widget (`Button`, `Text`, `Combo`, `Selectable`) to step an integer index forward or backward one item per scroll gesture. Overloaded for both `(int* idx, int item_count, ...)` and `(int* idx, int min_idx, int max_idx, ...)`.

- **Clamped by Default (`wrap = false`):** Stops cleanly at the first and last items so a fast flick of the scroll wheel never accidentally wraps from minimum to maximum.
- **Directional Hover Cursor:** Defaults to `ImGuiMouseCursor_ResizeNS` (↕) on hover, and can be overridden per-call (e.g., `ImGuiMouseCursor_ResizeEW` ↔ for horizontal button cycling or `ImGuiMouseCursor_Hand`).

```cpp
// 1. Attach wheel-cycling to a popup-menu opener button with an East-West scroll cursor:
if (ImGui::ButtonLink(kDensityLabels[s_DensityIdx])) {
    ImGui::OpenPopup("##density_menu");
}
if (ImGui::CycleItemOnMouseWheel(&amp;s_DensityIdx, 5 /* item_count */, false /* wrap */,
                                 true /* natural_list_order */, true /* consume */,
                                 ImGuiMouseCursor_ResizeEW)) {
    ApplyDensity(s_DensityIdx);
}

// 2. Standalone wheel-cycled ButtonLink paired with an abutting ResetButton:
//    Evaluating `(is_mod || can_restore) &amp;&amp; static_cast&lt;bool&gt;(btn)` resets/restores on click
//    when actionable, and automatically falls back to click-to-toggle tooltip when idle at default!
const bool is_mod      = (s_DensityIdx != 2);
const bool can_restore = (!is_mod &amp;&amp; s_LastDensityIdx != 2);
auto btn = ImGui::ButtonLink(kDensityLabels[s_DensityIdx], ImVec2(110.0f, 0.0f));
bool btn_clicked = (is_mod || can_restore) &amp;&amp; static_cast&lt;bool&gt;(btn);
if (ImGui::CycleItemOnMouseWheel(&amp;s_DensityIdx, 5, false, true, true, ImGuiMouseCursor_ResizeEW)) {
    if (s_DensityIdx == 2) s_LastDensityIdx = 2;
}

ImGui::SameLine(0.0f, 0.0f);
bool rst_clicked = ImGui::ResetButton("##density_reset", is_mod, 0.0f, true /* abutting */, nullptr, can_restore);
if (btn_clicked || rst_clicked) {
    if (is_mod) { s_LastDensityIdx = s_DensityIdx; s_DensityIdx = 2; }
    else if (can_restore) { s_DensityIdx = s_LastDensityIdx; }
    ImGui::TimedTooltip::ClearActiveTooltip();
}
```

D. Turnkey Mouse-Wheel Sliders & Drag Boxes (`MouseWheelSlider` / `PercentSlider` / `MouseWheelDrag`)

Drop-in replacements for standard sliders and drag boxes that respond to mouse-wheel scrolling out of the box. `MouseWheelSlider` and `MouseWheelDrag` are overloaded for both `float*` and `int*` so you never have to type `Float` or `Int` in the function name!

```cpp
static float s_Heading = 180.0f;
static int   s_Fov     = 80;
ImGui::MouseWheelSlider("Heading", &amp;s_Heading, 0.0f, 360.0f, "%.0f°", 0, 1.0f);
ImGui::MouseWheelSlider("FOV",     &amp;s_Fov,     40,   120,    "%d°",   0, 1.0f);

static float s_PitchOffset = 0.0f;
ImGui::MouseWheelDrag("Pitch Offset", &amp;s_PitchOffset, 0.5f /* speed &amp; default wheel step */, -45.0f
45.0f, "%.1f

static float s_Opacity = 0.85f;
ImGui::PercentSlider("Window Opacity", &amp;s_Opacity, 0.1f, 1.0f); // (alias: ImGui::SliderPercent)
```

E. Composite Sliders & Drag Boxes with Reset & Undo (`SliderWithReset` / `PercentSliderWithReset` / `DragWithReset`)

Full-featured compound controls (overloaded for `float*` and `int*`, also aliased as `ResettableSlider`, `ResettablePercentSlider`, and `ResettableDrag`) with built-in mouse-wheel support, a flush abutting vector undo/reset button (`0`-gap seam), smart width reservation, hover isolation, active input lockout, and **Reset-with-Undo** (1-click A/B toggle between default and previous value).

- Sits cleanly in a single line: `[ Control Track/Box | ■ / ■ ] Label Text`
- **"Reset with Undo" (1-Click A/B Comparison):**
- When modified (`*v != v_default`), clicking the Reset button saves the current non-default value (`last_val`), resets `*v = v_default`, and flips the button into **Restore/Redo Mode** (■ or `IMGUI_CONTRIB_DEFAULT_RESET_LABEL_ALT`).
- Clicking the button again in Restore mode swaps `*v` right back to `last_val`, letting users click back and forth effortlessly to A/B compare their custom setting against the default!
- **Automatic Session Memory + Optional Persistent Pointer (`v_last`):** Works automatically with **zero extra arguments** via internal per-ID session memory (`##reset_undo`), or accepts an optional trailing `float* v_last = nullptr` / `int* v_last = nullptr` pointer if you want to persist the pre-reset value in your own variable/dataref across sessions.
- **Automatic 3-State Default Tooltips:** When `reset_tooltip` is `nullptr`, automatically formats the default and previous values using the control's `format` string:
- **Modified:** `"Click to revert to default (85%)."`
- **After Reset (Restore Mode):** `"At default (85%). Click to restore previous (42%)."`
- **At Default (Idle):** `"Already at default (85%)."` (Clicking the dimmed button or right-side label immediately toggles the status/help `TimedTooltip` ON/OFF!)
- **Dual Icon Configuration (`#define` or Runtime Setter) & Vector Fallback:**
- With zero font configuration, draws crisp, DPI-scaled procedural vector arrows directly in `ImDrawList`: counter-clockwise ■ for Reset, and clockwise ■ for Restore-Previous.
- Or configure custom FontAwesome / icon-font strings at compile time (`#define IMGUI_CONTRIB_DEFAULT_RESET_LABEL ICON_FA_UNDO` and `#define IMGUI_CONTRIB_DEFAULT_RESET_LABEL_ALT ICON_FA_REDO` / `IMGUI_CONTRIB_DEFAULT_REDO_LABEL`) or at runtime via `ImGui::SetDefaultResetButtonLabel(reset_label, restore_label)`. Button width is automatically sized across both glyphs so the control never shifts by 1px when toggling states.
- **Seamless Abutting Frame Borders:** When abutting an active control (`abutting == true`), `ResetButton` automatically suppresses redundant internal frame borders (`FrameBorderSize > 0.0f`), ensuring the control track and reset button share a single clean outer frame without an unwanted vertical box seam between them.

```cpp
static float s_Heading = 180.0f;
static int   s_Fov     = 80;

// Optional: configure custom Reset &amp;amp; Restore/Redo icons globally (or via #define before #include):
// ImGui::SetDefaultResetButtonLabel(ICON_FA_UNDO, ICON_FA_REDO);

// 1-line sliders (float* or int*) with built-in mouse-wheel and Reset-with-Undo:
ImGui::SliderWithReset("Heading", &amp;amp;s_Heading, 180.0f /* default */, 0.0f, 360.0f, "%.0f°");
ImGui::SliderWithReset("FOV",     &amp;amp;s_Fov,     80     /* default */, 40,   120,    "%d°");

static float s_Opacity = 0.85f;
ImGui::PercentSliderWithReset("Opacity", &amp;amp;s_Opacity, 0.85f /* default */, 0.1f, 1.0f);

static float s_PitchOffset = 0.0f;
ImGui::DragWithReset("Pitch Offset", &amp;amp;s_PitchOffset, 0.0f /* default */, 0.5f /* speed */, -45.0f, 45.0
```

F. Turnkey Mouse-Wheel Combos (`MouseWheelCombo` / `ComboWithReset`)

Dropdown combo boxes that work like standard `ImGui::Combo` when clicked, and support live mouse-wheel cycling both when **closed** and while the dropdown popup menu is **open**!

- **Split Preview vs. Chevron `[▼]` Zones:**
- **Preview Text Zone (`[box_min.x .. box_max.x - GetFrameHeight()]`):** Shows `hover_cursor` (`ImGuiMouseCursor_ResizeNS` by default) and cycles items on mouse-wheel without falsely highlighting the right-hand chevron button.
- **Chevron Button Zone (`[box_max.x - GetFrameHeight() .. box_max.x]`):** Shows `ImGuiMouseCursor_Hand`, highlights strictly when the chevron itself is hovered (or when the popup is open), and **ignores mouse-wheel scrolling** so clicking/hovering the opener button feels like a dedicated dropdown button.
- **Configurable Chevron Arrow Polarity (`ImGui::ComboArrowStyle`):**

Configure globally via `#define IMGUI_CONTRIB_DEFAULT_COMBO_ARROW_STYLE` or `ImGui::SetDefaultComboArrowStyle(...)`:

- `ImGui::ComboArrowStyle_DownWhenClosed` (`0`, default): ▼ when closed $\rightarrow$ ▲ when open (or ▼ if the popup flipped upward near the bottom of the screen).
- `ImGui::ComboArrowStyle_RightWhenClosed` (`1`, ABC disclosure style): ■ when closed $\rightarrow$ ▼ (or ▲ if opened upward) when open.
- `ImGui::ComboArrowStyle_UpWhenClosed` (`2`): ▲ when closed $\rightarrow$ ▼ (or ▲ if opened upward) when open.
- `ImGui::ComboArrowStyle_StaticDown` (`3`): Vanilla ImGui's static ▼.
- `ComboWithReset` (also aliased as `ResettableCombo`) pairs the mouse-wheel combo with the flush abutting ■ / ■ reset-with-undo button (with automatic session memory or optional `int* last_item = nullptr` persistence).
- **Per-Item Tooltips (`item_tooltips[]`) & Open-Menu Wheel Tooltip Latch ("Lens UI"):** Pass an optional array of tooltip strings (plain text or Markdown when `contrib.h` is active) to attach a distinct tooltip to each item in the open dropdown list. When the user spins the mouse wheel while the dropdown menu is open, tooltip targeting automatically latches onto the **newly wheel-selected item** (`*current_item`) rather than whichever row the stationary mouse cursor happens to be parked over, and seamlessly returns to normal mouse hover targeting when the mouse moves (`> 6px`).

```cpp
static const char* const kCameraModes[] = { "Cockpit", "Chase", "Circle", "Tower", "Ride-Along" };
static const char* const kCameraModeTooltips[] = {
    "**Cockpit View**: Inside the 3-D flight deck.",
    "**Chase View**: Locked behind the aircraft.",
    "**Circle View**: Free exterior orbit around the aircraft.",
    "**Tower View**: Stationary camera from the nearest ATC tower.",
    "**Ride-Along**: Wing-mount or fuselage camera position."
};
static int s_CamMode = 1; // Default: Chase (1)

// Optional: use disclosure chevron polarity (■ when closed -&gt; ▼ when open):
// ImGui::SetDefaultComboArrowStyle(ImGui::ComboArrowStyle_RightWhenClosed);

// Standard mouse-wheel-enabled dropdown with per-item tooltips:
ImGui::MouseWheelCombo("Camera View", &amp;s_CamMode, kCameraModes, IM_ARRAYSIZE(kCameraModes),
                       -1, false /* wrap */, kCameraModeTooltips);

// Compound mouse-wheel dropdown with abutting Reset-with-Undo (1 = Chase):
ImGui::ComboWithReset("Camera Mode", &amp;s_CamMode, 1 /* default */,
                      kCameraModes, IM_ARRAYSIZE(kCameraModes),

                      -1, false /* wrap */, nullptr /* auto 3-state reset/restore tooltip */,
                      kCameraModeTooltips);
```

G. Mouse-Wheel Checkboxes (`MouseWheelCheckbox` / `ToggleItemOnMouseWheel` / `CycleItemOnMouseWheel(bool*)`)

Allows standard checkboxes to be toggled with the mouse wheel strictly when hovering over the **square `[✓]` box on the left** (`[box_min.x .. box_min.x + GetFrameHeight()]`), while hovering over the **text label** shows `ImGuiMouseCursor_Hand` (still clickable to toggle) and **ignores** the mouse wheel!

- By default (`wrap = false`), scrolling **up/right** checks the box (`true`) and scrolling **down/left** unchecks it (`false`), clamping cleanly at both ends (or pass `wrap = true` to flip on every wheel notch).
- Includes convenience overloads accepting `ImGuiMouseCursor_` directly after `bool* v` so you can customize or suppress the hover cursor (`ImGuiMouseCursor_Hand` or `ImGuiMouseCursor_None`) without passing intermediate boolean parameters.

```cpp
static bool s_AutoZoom = true;

// Option 1: Single-call MouseWheelCheckbox (with optional cursor override right after &amp;v):
ImGui::MouseWheelCheckbox("Enable Auto-Zoom", &amp;s_AutoZoom);
ImGui::MouseWheelCheckbox("Quiet Mode", &amp;s_QuietMode, ImGuiMouseCursor_Hand);

// Option 2: 1-line chaser attached to standard ImGui::Checkbox:
ImGui::Checkbox("Expert Mode", &amp;s_ExpertMode);
ImGui::ToggleItemOnMouseWheel(&amp;s_ExpertMode, ImGuiMouseCursor_None); // or CycleItemOnMouseWheel(&amp;s_ExpertMode)
```

H. Mouse-Wheel Auto-Defeat on Scrollable Viewports

In windows or child panels with active vertical scrolling (`ScrollMax.y > 0.0f`), spinning the mouse wheel to scroll through content could inadvertently adjust sliders, cyclers, or toggle switches if the mouse cursor passes over them.

To protect users against accidental setting changes while navigating long pages:

- **Automatic Detection:** `AdjustItemOnMouseWheel`, `CycleItemOnMouseWheel`, `MouseWheelSlider`, `PercentSlider`, `MouseWheelCombo`, `MouseWheelCheckbox`, and `ToggleButton` inspect the active Dear ImGui window and parent hierarchy for vertical scrollability via `ImGui::Contrib::IsCurrentWindowScrollableY()`.
- **Zero Accidental Adjustments:** When vertical scrolling is active, in-widget mouse-wheel adjustments are **defeated automatically**, and wheel events pass directly through to window scrolling.

- **Smart Cursor Hiding:** Resizing/adjustment hover cursors (`ImGuiMouseCursor_ResizeEW`, `ImGuiMouseCursor_ResizeNS`) are suppressed on scrollable viewports so users are not misled into expecting wheel adjustments.
- **Per-Widget Override:** If you explicitly want mouse-wheel interaction on a widget within a scrollable panel (e.g. an embedded canvas or dedicated map zoomer), pass `bAllowMouseWheelOnScrollable = true` to the widget overload.

---

3. Clickable Link & Item Cursor Affordances (`imgui_clickable_links.h`)

In standard Dear ImGui, buttons, menu items, and clickable text keep the default OS arrow cursor. The `imgui_clickable_links.h` header eliminates the boilerplate of writing `if (IsItemHovered()) SetMouseCursor(ImGuiMouseCursor_Hand);` on every interactive item, while providing automatic **click-to-toggle tooltip** ergonomics and **open-popup wheel-selection tooltip latching**.

- **Ambient Color Preservation on `ImGui::TextLink`:** In Dear ImGui 1.91+, the built-in `ImGui::TextLink(const char*)` forces `ImGuiCol_TextLink` (a bright sky-blue tint) with an underline. Our `imgui_clickable_links.h` overloads preserve your **ambient `ImGuiCol_Text` color** by default (or accept an explicit `const ImVec4* col_override` and `std::string`), while rendering a zero-frame clickable text item with a Hand cursor on hover (with Dear ImGui's native hyperlink preserved as `ImGui::NativeTextLink`).
- **Smart Click-to-Toggle Tooltips (`ImGui::LinkClickResult`): `ButtonLink`, `SmallButtonLink`, `TextLink`, `TextLinkUnformatted`, `MenuItemLink`,** and `MD::TextLink` return `ImGui::LinkClickResult`:
- **Tested in `if (...)` (Action Link):** Evaluating `if (ImGui::ButtonLink("Save"))` invokes `operator bool()`, marking the click as handled by your action block and dismissing any open tooltip on click.
- **Standalone Statement (Info / Help Link):** Calling `ImGui::TextLink("(i) Help");` without testing its return value leaves the click unconsumed, so clicking the widget immediately toggles a trailing `ImGui::TimedTooltip::Text` / `TextMD` ON and OFF (without closing any enclosing `BeginPopup`!).

```[CPP]
#include "contrib/widgets/imgui_clickable_links.h"

// 1. Action button (tested in `if` -&gt; executes action &amp; dismisses tooltip on click):
if (ImGui::ButtonLink("Save Flight Plan")) {
    SavePlan();
}
ImGui::TimedTooltip::TextMD("Saves the active flight plan to disk.");

// 2. Standalone info link (return value ignored -&gt; clicking toggles tooltip ON/OFF!):
ImGui::TextLinkUnformatted("(i) Works with scroll-wheel!");
ImGui::TimedTooltip::TextMD("Spin the **scroll-wheel** over this menu to step through options.");

// 3. Checkboxes, radio buttons, selectables, and menu items with hand cursor:
ImGui::CheckboxLink("Enable Autothrottle", &amp;s_Autothrottle);
ImGui::RadioButtonLink("NAV 1", &amp;s_NavSource, 1);
ImGui::SelectableLink("Row Item", isSelected);
ImGui::MenuItemLink("Compact Density", nullptr, isSelected);
```

Custom `BeginPopup` Menus with Mouse-Wheel Cycling & Per-Item Tooltips

When building custom `ImGui::BeginPopup` menus (with custom titles, separators, or footers), wrap the popup contents in `BeginGroup()` / `EndGroup()`, use `ImGui::MenuItem` (or `ImGui::MenuItemLink` for a Hand cursor on each row) with per-item `TimedTooltip::TextMD` calls, and attach `ImGui::CycleItemOnMouseWheel` after `EndGroup()`:

```cpp
if (ImGui::BeginPopup("#density_menu")) {
    ImGui::BeginGroup();
    if (ImGui::TextLink("Choose tracking list density:")) {
        ImGui::CloseCurrentPopup();
    }
    ImGui::Separator();

    for (int i = 4; i &gt;= 0; --i) {
        bool isActive = (densityIdx == i);
        if (ImGui::MenuItem(menus[i], nullptr, isActive)) {
            gUserLinePadding = 4 + 2 * i;
        }
        ImGui::TimedTooltip::TextMD("Switch table spacing to **%s** density.", tipLabels[i]);
    }

    ImGui::Separator();
    ImGui::TextLinkUnformatted("  (i) Works with scroll-wheel!  ");
    ImGui::TimedTooltip::TextMD("Spin your scroll-wheel over this list to step through options.");
    ImGui::EndGroup();

    // Whole-menu mouse-wheel cycling (automatically latches per-item tooltips to `isActive`!):
    if (ImGui::CycleItemOnMouseWheel(&amp;densityIdx, 0, 4, /*wrap=*/false, /*natural_list_order=*/false,
                                     /*consume=*/true, ImGuiMouseCursor_Hand)) {
        gUserLinePadding = 4 + 2 * densityIdx;
    }
    ImGui::EndPopup();
}
```

- **Automatic Wheel-Selection Tooltip Latch:** **`ImGui::MenuItem`** and **`ImGui::MenuItemLink`** register each item's **`isActive`** state. When the user spins the scroll wheel inside the open popup, **`TimedTooltip`** automatically switches from mouse-hover targeting to showing the tooltip for the **newly wheel-selected item** (**`isActive`**), returning to normal hover targeting as soon as the mouse moves (**`> 6px`**).

Universal Item Hover-Cursor Chaser (`ImGui::AttachItemCursor`):

```cpp
// Attach default Hand cursor to any preceding item:
ImGui::Image(textureId, ImVec2(64, 64));
ImGui::AttachItemCursor();

// Or attach any specific ImGuiMouseCursor on hover:
ImGui::Button("Splitter");
ImGui::AttachItemCursor(ImGuiMouseCursor_ResizeEW);
```

4. Badges, Pills & Key Caps (`imgui_badges.h`)

Sleek, standalone C++ UI indicators designed for status tags, version numbers, notification counters, and keyboard shortcut chips without requiring any Markdown parsing.

```cpp
#include "contrib/widgets/imgui_badges.h"

// 1. Semantic Status Badges (Default, Primary, Success, Warning, Danger, Info):
ImGui::Badge("ONLINE", ImGui::ImGuiBadgeVariant_Success);
ImGui::SameLine();
ImGui::Badge("EXPIRING", ImGui::ImGuiBadgeVariant_Warning);
ImGui::SameLine();
ImGui::Badge("FAULT", ImGui::ImGuiBadgeVariant_Danger);

// 2. Fully-rounded Pills:
ImGui::Pill("v1.92", ImGui::ImGuiBadgeVariant_Primary);
ImGui::SameLine();
ImGui::Pill("PRO", ImVec4(0.85f, 0.40f, 0.10f, 1.0f)); // Custom ImVec4 background

// 3. Custom Hex or ImU32 Backgrounds with Automatic Contrast Calculation:
ImGui::Badge("BETA", ImGui::GetColorU32(ImVec4(0.9f, 0.9f, 0.1f, 1.0f))); // Auto-selects dark text

// 4. Keyboard Key Caps (&lt;kbd&gt;):
ImGui::Text("Press");
ImGui::SameLine();

ImGui::Kbd("Ctrl+Shift+P");
ImGui::SameLine();
ImGui::Text("to open Command Palette.");
```

- **Features:**
- **Pixel-Balanced Rounded Geometry:** Uses TrueType baseline alignment and font-scale compensation so ascenders and descenders ('p', 'g', 'y') stay centered with identical visual margins.
- **Intelligent Auto-Contrast:** Computes ITU-R BT.601 perceptual luminance of the background color and automatically selects crisp dark (**`#000000`**) or light (**`#FFFFFF`**) text when foreground color is omitted.
- **3D Key Caps (`ImGui::Kbd`):** Renders tactile keyboard shortcut chips with rounded borders and a bottom bevel shadow.
- **Zero Markdown Overhead:** Standalone immediate-mode C++ functions usable anywhere in pure ImGui panels. Markdown's **`<badge>`**, **`<pill>`**, and **`<kbd>`** tags delegate directly to these widgets.

---

5. Procedural Spinners & Countdown Dials (`imgui_spinners.h`)

Smooth, procedural immediate-mode activity indicators and radial timers rendered directly via **`ImDrawList`** antialiased paths. No texture assets, no font hacks, and zero memory allocations.

```cpp
#include "contrib/widgets/imgui_spinners.h"

// 1. Organic Activity Spinner (loading / busy state):
ImGui::Spinner("##loading"); // Auto-scales to font size
ImGui::SameLine();
ImGui::Text("Syncing telemetry...");

// With custom radius, thickness, color, and label:
ImGui::Spinner("Downloading airport navdata", 14.0f, 3.0f, IM_COL32(0, 200, 255, 255));

// 2. Radial Countdown Timer (fraction remaining: 0.0f .. 1.0f):
float timeoutRemaining = GetRemainingFraction(); // e.g., 0.65f
ImGui::RadialTimer("Auto-dismiss in 5s", timeoutRemaining);

// 3. Countdown Timer Helper (current seconds vs max duration):
float alertTimeLeft = 3.2f;
float alertMaxTime  = 10.0f;
ImGui::CountdownTimer("Alert Timeout", alertTimeLeft, alertMaxTime);
```

- **Features:**

- **Organic Breathing Arc Animation:** Rather than a rigid rotating stick, `ImGui::Spinner` uses a sinusoidal expansion-and-contraction cycle that mimics modern Material/Apple loading spinners.
- **Clockwise/Counter-Clockwise Dials:** `ImGui::RadialTimer` starts cleanly at 12 o'clock (`-90°`) with an ambient background track ring, sweeping smoothly around to indicate elapsed or remaining time.
- **True Ambient Scaling:** Radius and stroke thickness automatically scale to the ambient font size (`ImGui::GetFontSize()`) when left as `0.0f`, looking sharp on standard and high-DPI displays alike.
- **Built-in Text Label Affordance:** Labels without leading `##` automatically render beside the spinner or dial with standard item alignment and spacing.

---

6. Universal Standalone & Chaser Copy Buttons (`imgui_copy_button.h`)

Tactile, immediate-mode copy buttons featuring procedural vector icons, transient "Copied!" feedback, anti-twitch fixed width layouts, and seamless integration with `TimedTooltip` and `InputText`.

```cpp
#include "contrib/widgets/imgui_copy_button.h"

// 1. Standalone Proxy Form (CopyButton / CopyBufferButton):
// Takes an explicit string, buffer, or std::string to copy to the clipboard:
ImGui::CopyButton("##copy_apikey", myApiKeyString);
// Or use the explicit semantic alias:
ImGui::CopyBufferButton("##copy_buf", textBuffer);

// 2. Chaser Form (CopyLastItemButton / CopyTextFieldButton):
// Placed immediately after an ImGui::InputText / InputTextMultiline:
static char s_LogBuffer[512] = "N450GA clearance delivered...";
ImGui::InputText("Flight Plan", s_LogBuffer, sizeof(s_LogBuffer));
ImGui::SameLine();
ImGui::CopyLastItemButton("##copy_flightplan"); // Automatically copies s_LogBuffer!

// 3. Querying transient state or custom duration:
bool is_copied = false;
if (ImGui::CopyButtonEx("##custom_copy", "Payload", 2.0f /* duration */, ImVec2(0, 0), &amp;is_copied)) {
    // Button was clicked this frame!
}
```

- **Features:**
- **Procedural Vector Icons:** Renders a clean two-sheet overlapping clipboard vector icon that transitions smoothly into a green vector checkmark during the transient `Copied!` confirmation state.
- **Anti-Twitch Fixed Width Layout:** Automatically calculates the maximum bounding width across `"Copy"` and `"Copied!"` labels (`ImMax(normal_w, copied_w)`) so adjacent buttons and toolbars never twitch or jump when toggling states.
- **Independent `ImGuiStorage` Scoping:** Transient copied feedback is keyed to `ImGuiID` in the window's state storage, ensuring multiple copy buttons in the same window maintain their own timers and feedback independently.
- **Zero-Redundancy Chaser Mode (`CopyLastItemButton`):** Automatically queries Dear ImGui's internal `LastItemData` and `InputTextState` to retrieve the buffer pointer of the preceding input field with zero redundant buffer duplication.
- **Semantic Aliases:** Includes `ImGui::CopyBufferButton` and `ImGui::CopyTextFieldButton` to make developer intent clear at a glance.
- **Rich `TimedTooltip` Integration:** Automatically displays `"Copy to Clipboard"` on hover, switching to `"Copied!"` during the feedback duration, with an automatic `ImGuiMouseCursor_Hand` hover cursor.

---

7. Avionics Rotary Knobs & Dimmer Dials (`imgui_knobs.h`)

Turnkey immediate-mode cockpit potentiometers, rotary dials, and lighting dimmer controls featuring an unmistakable 270° "Omega" arc, tactile two-step **`OFF`** detente switches, perimeter graduation ticks, and full mouse-wheel integration.

```
[CPP]

#include "contrib/widgets/imgui_knobs.h"

// 1. Avionics Potentiometer Dimmer with 2-Step OFF Detente:
// Turning CCW dims smoothly from 100% down to 5% (minimum active floor).
// An intentional extra downward notch while resting at 5% snaps across into "OFF"!
// Turning CW from OFF snaps immediately back into active range (5%).
static float s_FloodDimmer = 0.85f;
ImGui::DimmerKnob("Floodlight Dimmer", &amp;s_FloodDimmer, 0.05f /* v_min_active */, 1.0f /* v_max */, 1.0f

// 2. Standard 270° Rotary Knob with 1-Click Vector Reset (■):
static float s_RadioVol = 0.70f;
ImGui::KnobWithReset("Radio Volume", &amp;s_RadioVol, 0.70f /* default */, 0.0f, 1.0f, "%.0f%%", 0.0f, 0.02

// 3. Compact / Percentage Dial:
static float s_HeadingBug = 180.0f;
ImGui::Knob("Heading Bug", &amp;s_HeadingBug, 0.0f, 360.0f, "%.0f°", 14.0f /* radius */);

// 4. Vertical Stacked Avionics Gauge Unit:
static float s_TransponderGain = 0.50f;
ImGui::Knob("XPNDR", &amp;s_TransponderGain, 0.0f, 1.0f, "%.2f", 20.0f, 0.01f, ImGuiKnobFlags_ValueBelow |
```

- **Features:**
- **Unmistakable Omega Potentiometer Geometry:** Features an authentic 270° arc with a 90° open deadband at 6 o'clock and a raised 3D knurled knob hub with a high-contrast rotating index needle/pip. Instantly disambiguated from 360° read-only timers or progress circles.
- **Tactile Two-Step Detente Switch:** Counter-clockwise rotation stops cleanly at the minimum active floor (e.g. 5%), preventing accidental power cutoffs in flight. A deliberate extra scroll step past the stop snaps across the detente gap directly into the powered-down **`OFF`** detente. Clockwise rotation from **`OFF`** snaps immediately back to minimum power.
- **State-Aware Text Readout:** Automatically displays **`"OFF"`** in warning amber when disarmed in detente, or the formatted percentage/value when active.
- **Dual-Mode Input Ergonomics:** Primary mouse-wheel rotation with automatic scroll-defeat prevents scrolling the parent window. Secondary vertical/horizontal click-dragging supports VR/touchscreen use, with **`Shift`** (fine $0.1\times$) and **`Ctrl`** (coarse $2.0\times$) speed modifiers.
- **Default `ResizeEW` (<-->) Cursor:** Shows horizontal range selection cursor by default on hover, confirming interactive status at a glance.
- **Double-Click Reset / Detente Toggle:** Double-clicking the knob restores calibrated baseline default (or toggles between **`OFF`** and default).

---

8. Directional Popup Menus & Select Pulldowns (`imgui_popup_menus.h`)

First-class popup anchoring and selection widgets solving directional placement, muscle-memory toggle protection, font-scale invariant alignment, and closed-state wheel pass-through:

```cpp
#include "contrib/widgets/imgui_popup_menus.h"

// 1. Directional Item Anchoring (Status Bars &amp;amp; HUDs):
// Blossoms UP above the button with sub-pixel precision:
if (ImGui::Button("View Mode")) {
    ImGui::OpenPopupAtItem("##ViewModeMenu", ImGuiPopupAnchor_AboveItem, ImGuiPopupAlign_Auto);
}

// 2. Begin Anchored Popup:
if (ImGui::BeginAnchoredPopup("##ViewModeMenu")) {
    if (ImGui::MenuItem("Circle View")) { SetView(0); }
    if (ImGui::MenuItem("Spot View"))   { SetView(1); }
    if (ImGui::MenuItem("Tower View"))  { SetView(2); }
    ImGui::EndPopup();
}

// 3. Headroom Query for Window Managers / Subclasses (e.g. WidgetImgWindow):
// Returns exact measured height in pixels so XPLM window expansion has zero guessing:
float headroom = ImGui::GetLastPopupHeight("##ViewModeMenu");

// 4. SelectPulldown Widget (Settings Window 1-Line Dataref Selectors):
// Closed: ignores mouse-wheel (smooth parent list scrolling without accidental edits).
// Open: mouse-wheel cycles active selection dynamically without closing menu!
// Caret: automatically renders crisp procedural vector arrows (▼ / ▲) without requiring Unicode font glyphs!
static int s_SelectedCam = 1;
const char* const kCamModes[] = { "Circle", "Spot", "Tower", "Cockpit" };
const char* const kCamTips[]  = { "Follow aircraft", "Fixed distance", "Tower view", "Pilot eye" };
if (ImGui::SelectPulldown("##CameraMode", &amp;amp;s_SelectedCam, kCamModes, 4, kCamTips)) {
    UpdateCamera(s_SelectedCam);
}

// 5. Upward Blossoming Pulldown (Status Bars &amp;amp; Screen-Bottom Docks):
static int s_PowerMode = 0;
const char* const kPowerModes[] = { "Battery", "APU", "External Power" };
if (ImGui::SelectPulldown("##PowerMode", &amp;amp;s_PowerMode, kPowerModes, 3, nullptr, 140.0f, ImGuiPopupAnchor_AboveItem)) {
    UpdatePowerSource(s_PowerMode);
}

// 6. Caret Customization &amp;amp; Procedural Vector Drawing:
// Optional: Configure FontAwesome glyphs or custom ASCII strings globally at runtime:
ImGui::SetDefaultPulldownCaret(ICON_FA_CHEVRON_DOWN, ICON_FA_CHEVRON_UP);

// Or call the procedural vector arrow helper directly in custom controls:
ImGui::DrawPulldownArrow(ImGui::GetWindowDrawList(), arrow_pos, text_col, ImGuiDir_Down, font_size);
```

- **Features:**
- **Procedural Vector Caret Fallback:** Eliminates unmapped Unicode Geometric Shapes (**`U+25BE`**) missing-glyph issues. Defaults to crisp, antialiased procedural vector triangles rendered directly to **`ImDrawList`**, matching **`ResetButton`** vector rendering.
- **Configurable Font Carets & Runtime Setters:** Host apps with FontAwesome can define **`#define IMGUI_CONTRIB_DEFAULT_PULLDOWN_CARET_DOWN`** or call **`ImGui::SetDefaultPulldownCaret(...)`** to use native icon-font glyphs.
- **Directional Blossoming (`ImGuiPopupAnchor`):** Supports **`ImGuiPopupAnchor_AboveItem`** for bottom status bars and docks, dynamically flipping caret directions between open and closed states.
- **Smooth TimedTooltip Integration:** Item hover tooltips automatically use **`ImGui::TimedTooltip`** (with fallback to **`ImGui::SetTooltip`**), preventing cursor jitter.
- **Broad In-Popup Hover Scope:** Mouse-wheel spinning anywhere inside the open popup window (including while hovering individual **`Selectable`** rows) cycles active options smoothly.
- **Font-Scale Invariant Placement:** Uses live **`GetItemRectMin()`** and **`ItemSpacing.y`** bounding geometry from the rendering frame, eliminating magic pixel offsets and text-zoom drift.

- **Muscle-Memory Toggle Safety:** Clicking the opener button while the popup is open cleanly toggles it closed without re-opening flicker.
- **Universal Widget Compatibility:** `OpenPopupAtItem()` anchors cleanly behind any widget: `ImGui::Button`, `ImGui::ButtonLink`, `ImGui::MD::ButtonMD`, `ImGui::Pill`, `ImGui::Badge`, or custom controls.
- **Exact Headroom Reporting:** `GetLastPopupHeight(str_id)` reports the measured pixel height for dynamic XPLM window expansion.
- **Scroll Pass-Through:** `SelectPulldown` never captures the mouse-wheel while closed, preventing unwanted dataref changes while scrolling settings.

---

10. Procedural Vector Icons Engine (`imgui_icons.h`)

A zero-texture, zero-font, zero-dependency procedural vector icon engine that actively renders crisp antialiased vector geometry directly to Dear ImGui's `ImDrawList`.

Completely eliminates missing-glyph diamond replacement characters (`) when host font atlases only bake standard ASCII/Latin-1 (0x20..0xFF) and lack extended Unicode blocks (such as Mathematical arrows U+2190..U+21FF or Geometric shapes U+25A0..U+25FF`).

```cpp
#include "contrib/widgets/imgui_icons.h"

// 1. Direct Immediate-Mode Widget:
// Scales automatically with ambient font size (GetFontSize() * 0.90f) and centers on text baseline:
ImGui::Icon("undo");
ImGui::Icon("caret-up", 18.0f);
ImGui::Icon("gear", 16.0f, &amp;ImVec4(1.0f, 0.6f, 0.0f, 1.0f));

// 2. Procedural Vector Push-Buttons:
// IconButton: square button with centered vector icon, hand cursor, and optional tooltip:
if (ImGui::IconButton("##zoom_up", "caret-up", ImVec2(0, 0), "Zoom In")) {
    ZoomIn();
}

// ButtonIcon: dual icon + text button (or text + icon if icon_on_right = true):
if (ImGui::ButtonIcon("Settings", "gear", ImVec2(0, 0), false, "Open avionics configuration")) {
    OpenSettings();
}
if (ImGui::ButtonIcon("Next Page", "caret-right", ImVec2(0, 0), true)) {
    AdvancePage();
}

// 3. Direct DrawList Procedural Vector Path Rendering:
ImGui::DrawVectorIcon(ImGui::GetWindowDrawList(), pos, size, col_u32, "search");

// 4. Forgiving Name Normalization:
// Accepts any format: "undo", ":undo:", "ICON_FA_UNDO", "ICON_UNDO", "reset", or raw UTF-8:
ImGui::Icon("ICON_FA_UNDO");
ImGui::Icon(":gear:");
ImGui::Icon("\xE2\x86\xBA"); // ■
```

Markdown & Typography Integration

The icon engine is deeply integrated into `ImGui::MarkdownExt` and `ImGui::TextStyled`, offering 5 authoring modes:

1. **Inline HTML Tag:** `<icon caret-up />`, `<icon orange undo />`, `<icon name=gear size=16 />`
2. **Emoji Shortcodes:** `:undo:`, `:reset:`, `:caret_up:`, `:caret-down:`, `:gear:`, `:check:`, `:star:`, `:plane:`
3. **Steven's Raw-Fallback Link Macro:** `#[^](ICON_CARET_UP)` or `#[■](ICON_UNDO)`
4. **Automatic Raw Unicode Glyph Rescue:** Raw symbols like ■, ■, ▲, ▼, ✓, ■ outside code blocks are automatically intercepted and rendered as crisp vector icons with zero missing-glyph diamonds!

5. **Backtick Rescue:** Single symbols wrapped in backticks (` ■ `) are rescued and rendered as vector icons.

Universal Icon Catalog

- **Navigation:** `caret-up` (▲), `caret-down` (▼), `caret-left` (■), `caret-right` (■)
- **History:** `undo` / `reset` (■), `redo` / `restore` (■)
- **Actions & State:** `check` (✓), `cross` (✗), `plus` (+), `minus` (-), `gear` (■), `search` (■)
- **Indicators & Badges:** `info` (■), `warning` (■), `star` (★), `plane` (✈), `circle` (●), `square` (■)

Credits & Upstream Lineage

- **Author & Architect**: Steven L. Goldberg (@slgoldberg)
- **SliderPercent Upstream Inspiration**: Birger Hoppe (LiveTraffic)
- **License**: BSD 3-Clause (see ImgWindow LICENSE)

Markdown Extension

The **Markdown** extension provides rich Markdown parsing and rendering for Dear ImGui within ImgWindow, based on **`enkisoftware/imgui_markdown`** and heavily enhanced for X-Plane plugin user interfaces.

It allows you to embed rich text formatting, headers, links, lists, and custom interactive widgets directly into your ImGui windows, settings panels, and stationary tooltips.

> **Author / Maintainer:** Steven L. Goldberg (@slgoldberg)

> **Original Upstream:** Juliette Foucaut (@juliettef) & Doug Binks (@dougbinks) — Repository: enkisoftware/imgui_markdown

> **License:** BSD 3-Clause (Extension Wrapper; see ImgWindow LICENSE) & zlib (Upstream Parser)

Architectural Overview: Foundation vs. Extension Wrapper

The Markdown system is structured as a clean two-layer architecture:

1. **Base Engine (`imgui_markdown.h`):**

- Upstream parser originally created by Doug Binks and Juliette Foucaut (**`enkisoftware/imgui_markdown`**).
- Responsible for raw character scanning, CommonMark tokenization, AST-like block dispatch, and low-level C-style callbacks (**`formatCallback`**, **`linkCallback`**, **`imageCallback`**, **`tooltipCallback`**).
- Our fork incorporates crucial low-level fixes for CommonMark punctuation lookahead and bullet list token isolation.

2. **ImgWindow Extension Wrapper (`imgui_markdown_ext.h`):**

- High-level, ergonomic C++ layer designed specifically for X-Plane plugins and modern ImGui applications.
- Encapsulates all functionality inside the second-level **`ImGui::Markdown::`** namespace, with **`ImGui::MD::`** provided as an official, zero-overhead namespace alias (**`namespace ImGui { namespace MD = Markdown; }`**).
- Eliminates the upstream symbol collision: Upstream's raw C-style function **`ImGui::Markdown(text, len, config)`** has been moved to **`ImGui::Markdown::Render(...)`** (and **`ImGui::MD::Render(...)`**). This prevents beginners from accidentally invoking the raw unconfigured parser and frees **`ImGui::Markdown`** to be a clean, first-class C++ namespace.
- Introduces an XML/HTML-style inline tag pre-processor (**`<tag>`**, **`<color>`**, **`<backdrop>`**, **`<badge>`**, **`<btn>`**) with custom tag callback registration via **`ImGui::Markdown::RegisterTag`**.
- Solves Dear ImGui layout hurdles: typographic line-wrap lookahead (eliminating mid-word breaks across styles and links), mathematical hanging indents for wrapped multi-line bullets, and ambient font scale inheritance (**`ImGui::GetFontScale()`**).
- Provides non-rendering layout measurement via **`ImGui::Markdown::CalcTextSize`** (defeating ImGui viewport culling to measure exact dimensions for floating windows and stationary tooltips).
- Directly interfaces with the companion **`TimedTooltip`** extension via bidirectional bridges (**`ImGui::TimedTooltip::Markdown::Text`** / **`ImGui::TimedTooltip::MD::Text`** and **`ImGui::Markdown::TimedTooltip::Text`** / **`ImGui::MD::TimedTooltip::Text`**).

Architectural Enhancements over Upstream

- **Collision-Free Canonical Namespace (`ImGui::Markdown::` & `ImGui::MD::`):**
- Primary namespace is **`ImGui::Markdown::Text(...)`** for full clarity.
- Shorthand alias **`ImGui::MD::Text(...)`** is 100% interchangeable.
- Root convenience aliases **`ImGui::TextMD(...)`** / **`ImGui::TextMarkdown(...)`** allow drop-in usage matching **`ImGui::Text(...)`**.

- Opt-in global convenience (`#define CONTRIB_ENABLE_GLOBAL_NAMESPACES` or `#include "contrib/contrib-global.h"`) publishes `Markdown::Text(...)` and `MD::Text(...)` to the global scope for developers seeking minimum boilerplate.
- **CommonMark Backslash Escaping:**
- Escapes any ASCII punctuation character (`\*`, `\#`, `\_`, `\<`, `\>`, `\[`, `\]`, `\(`, `\)`, `\\`, etc.) to render literally without triggering emphasis, headers, HTML tags, or links.
- Ensures clean display of technical expressions like `C\*` or `[X-Plane 12]\(build\)`.
- **Strikethrough & Underline Typography:**
- **Strikethrough:** Full support for GitHub Flavored Markdown `~~deleted text~~` and legacy ABC `$$struck text$$`, as well as HTML tags (`<s>`, `<del>`, `<strike>`).
- **Underline:** Supports CriticMarkup / Markdown Extended `++underlined text++` and HTML tags (`<u>`, `<ins>`) out-of-the-box. Setting `mdConfig.underlineWithUnderscores = true` allows Discord/ABC-style `__underlined text__` to render as underline instead of bold.
- **Pixel-Aligned Rules:** Centered midline for strikethrough and baseline-aligned underline scale cleanly across all display DPIs and custom font sizes.
- **Ordered & Unordered Lists with True Hanging Indents:**
- **Ordered Lists:** Automatically recognizes numbered items (`1.` , `2.` , etc.) and formats the number prefix with a clean hanging indent matching unordered bullets.
- **Unordered Lists:** Replaces cramped upstream bullet spacing with scalable, comfortable breathing room (`bulletSpacing` defaulting to a clean 4px).
- Mathematically maintains true hanging indents across wrapped multi-line list items and continuation lines, keeping all wrapped text cleanly aligned to the text column rather than under the bullet glyph or number.
- Preserves leading space depth across emphasis chunks and links so nested sub-bullets never pop out of alignment.
- Broadens list marker syntax to standard Markdown (`*`, `-`, `+`) with or without leading whitespace, with strict token isolation so bullet glyphs never hijack inline styling into rogue italic runs.
- **Nested Indent Balance:** Accurately unindents when nested lists terminate, preventing indentation from leaking into subsequent paragraphs or blocks.
- **Thematic Breaks / Horizontal Rules (CommonMark 4.1):**
- Full support for thematic breaks via `---`, `***`, or ___ (with optional internal/trailing whitespace).
- Automatically renders clean visual dividers via `ImGui::Separator()`.
- **Smart Spacing & Void Prevention:** Intelligently suppresses redundant vertical margins when separators immediately precede or follow headings, avoiding cavernous whitespace voids.
- **Fenced Code Blocks with Width Clamping & Continuation Soft-Wrapping:**
- Multi-line code blocks (` ` ` and ~~~`) clamp their container width to available window content space (`avail_width`) while guaranteeing minimum toolbar control width.
- Continuation lines soft-wrap naturally without horizontal clipping.
- **CommonMark 4.5 Indentation Stripping:** Code blocks nested inside lists or indented sections automatically strip up to N spaces of leading indentation matching the opening fence, preventing code from being pushed awkwardly to the right inside the container.
- **Indented Closing Fences:** Closing fences indented by ≥ 4 spaces or tabs are properly recognized, preventing list continuation text from being accidentally swallowed.
- **Scoped Copy Button:** Integrated vector copy button with checkmark animation and 1.5s transient visual feedback. Scoped via `ImGuiStorage` to ensure multiple code blocks in the same window maintain their feedback independently.
- **Mode Toggle with Mouse-Wheel Scroll-Defeat:** The animated `Raw [===O] Preview` toggle switch automatically defeats mouse-wheel adjustments when inside scrollable parent viewports, preventing accidental mode switches when

scrolling through documentation.

- **Soft-Wrap Leading Space Suppression:**
- Forced line breaks on wrapped prose cleanly suppress carried-forward leading spaces, ensuring continuation lines align flush against the left text margin.
- **Layout Pre-Calculation (`CalcSize` / `CalcTextSize`):**
- Exposes `ImGui::MD::CalcSize(...)` (aliased as `CalcTextSize`) to pre-measure exact wrapped multi-line Markdown dimensions without rendering to the screen—crucial for sizing OS floating windows, child frames, and stationary tooltips.
- Defeats ImGui viewport culling by employing pass-unique offscreen window hashes.
- **Interactive CommonMark Tables with Sorting & Bi-Directional State Serialization:**
- Parses standard CommonMark pipe tables with column alignment (`:---`, `:---:`, `---:`), natural cell content measurement, and rich inline Markdown/tags inside cells.
- **Tristate Interactive Sorting:** Click any header to cycle Ascending ↑ → Descending ↓ → Unsorted, with responsive hand cursor hover and rendered sort indicator arrows.
- **Column Divider Resizing:** Drag any column boundary separator to customize column widths dynamically.
- **Total Width Border Grip:** Drag the right-border resize handle to stretch or contract table width up to 5x available window width (smooth horizontal scrolling in narrow viewports).
- **A/B Double-Click Toggle Memory:** Double-clicking the right border grip toggles back and forth between the baseline preset and user-modified geometry with 100% memory of column widths and total width.
- **Two-Tier Comment Persistence:** Transparently reads and writes Author Baseline Presets (`<!-- table-preset: ... -->`) and User State (`<!-- table-state: ... -->`) without cluttering rendered output.
- **Turnkey Host Serialization:** Provides `mdConfig.tableStateCallback` and `ImGui::ApplyTableStateToMarkdown(...)` to keep raw markdown editor buffers and persistence files in lockstep with user interactions.
- **Continuous Vertical Baseline Alignment for Inline Tags:**
- In `<pill>`, `<badge>`, and `<kbd>`, text rendering anchors directly to the line's natural font baseline (`CursorPos.y + CurrLineTextBaseOffset`), and the background capsule expands symmetrically above and below. Bare text, bold text, and capsule text share a single unbroken typographic baseline without sagging or vertical drift.
- **Centering Layout Primitives (`<center>` and `-> text <-`):**
- Effortlessly center briefing headers, warnings, and status lines via HTML-style `<center>text</center>` (or `<centre>`) tags or ASCII block-level markers (`-> Centered Text <-` and `= Centered Text =`).
- Dynamically pre-measures line advance width across headers, bold/italics, pills, and badges to ensure true horizontal optical centering.
- **Dynamic Font Scaling:**
- Uses `ImGui::GetFontScale()` to cleanly honor parent window text zoom and high-DPI display scales.
- **Custom Tag Registration:**
- Supports custom XML/HTML-style tags (e.g., `<btn>Label</btn>`, `<badge>OK</badge>`) that execute arbitrary C++ rendering callbacks inline with text flow.
- **Collision-Free Scope (`ImGui::MD::`):**
- Scoped under `ImGui::MD::` to mirror standard ImGui vocabulary (`Text`, `TextWrapped`) without colliding with core ImGui functions.

Quick Start

1. Include the Header

```cpp
#include "contrib/extensions/Markdown/imgui_markdown_ext.h"
// (Or simply: #include "contrib.h")
```

> **IMPORTANT**
>
> **Migrating from Upstream `imgui_markdown`: Remove Old Includes!** If your plugin previously included upstream `imgui_markdown.h` directly: 1. **Remove your old `#include "imgui_markdown.h"`** lines and delete any loose copies of `imgui_markdown.h` from your project's header search paths. 2. **Include `#include "contrib.h"` (or `#include "contrib/extensions/Markdown/imgui_markdown_ext.h"`) instead.** `imgui_markdown_ext.h` automatically includes our modernized, patched engine (`contrib/extensions/Markdown/imgui_markdown.h`) under the hood. Keeping an older upstream copy in your project tree risks compiling against the unpatched upstream engine, which lacks our typographic lookahead, mathematical hanging indents, and `ImGui::MD::` widget suite!

2. Configure Default Styles & Fonts (Optional)

You are responsible for loading your own fonts into your `ImgFontAtlas` during plugin startup (e.g., in `InitializeImGui()`). There is no runtime font synthesization in Dear ImGui—if you want Markdown to render distinct headers, bold text, or italics, you must load those fonts into your atlas.

As demonstrated in `sample-code/InitializeImGui.cpp`, each sequential, non-merged font added increments an index in `ImGui::GetIO().Fonts->Fonts[i]`. We recommend defining macro aliases for these slots:

```cpp
// Example font slot definitions (from sample-code/InitializeImGui.cpp):
#define IM_FONT_SLOT(i)       ImGui::GetIO().Fonts-&gt;Fonts[i]
#define IM_NORMAL_FONT        IM_FONT_SLOT(0) // Regular base font (14px)
#define IMG_TITLE_FONT        IM_FONT_SLOT(1) // Large header font
#define IM_SMALLER_FONT       IM_FONT_SLOT(2) // Compact UI font
#define IM_BOLD_FONT          IM_FONT_SLOT(3) // Bold font
#define IM_BOLD_LARGER_FONT   IM_FONT_SLOT(4) // Bold title font
#define IM_MONO_NORMAL_FONT   IM_FONT_SLOT(5) // Monospace code font
#define IM_ITALIC_FONT        IM_FONT_SLOT(6) // Italic font
```

During plugin startup, configure your Markdown appearance globally using `ImGui::MD::Config`:

```cpp
ImGui::MD::Config mdConfig;

// Configure semantic fonts directly (no cryptic array indices!):
mdConfig.h1Font     = IM_BOLD_LARGER_FONT; // # H1
mdConfig.h2Font     = IMG_TITLE_FONT;      // ## H2
mdConfig.h3Font     = IM_BOLD_FONT;        // ### H3
mdConfig.boldFont   = IM_BOLD_FONT;        // **Bold** / __Bold__
mdConfig.italicFont = IM_ITALIC_FONT;      // *Italic* / _Italic_
mdConfig.monoFont   = IM_MONO_NORMAL_FONT; // `code` / &lt;code&gt; / &lt;mono&gt;

// Configure tight, clean bullet spacing:
mdConfig.bulletSpacing = 4.0f;

// Set globally for the extension:
ImGui::SetDefaultMarkdownConfig(&amp;mdConfig);
```

> **NOTE**

Graceful Font Fallback: If any font pointer is left as `nullptr`, the engine gracefully falls back: * `h1Font`, `h2Font`, `h3Font` fall back to `headingFormats[0..2]` (or the ambient window font). * `boldFont` falls back to `headingFormats[3]` (or the ambient window font). * `italicFont` falls back to `ImGuiCol_TextDisabled` (upstream's dimmed text color). * `monoFont` falls back to the ambient window font.

3. Rendering Markdown in Windows

Simply call `ImGui::Markdown::Text` (or the shorthand `ImGui::MD::Text`):

```cpp
// Standard single-line or multi-line Markdown:
ImGui::Markdown::Text("### System Status\nEngine 1: **Normal** | Fuel: *Sufficient*");

// Paragraph block with automatic word wrapping:
ImGui::Markdown::TextWrapped(
    "Check this option to enable **custom cursors**. "
    "Changes take effect immediately without requiring a simulator restart."
);

// Clickable Markdown text link:
if (ImGui::Markdown::TextLink("Open **Avionics Settings**")) {
    OpenSettings();
}
```

TIP

Forgiving Aliases: Prefer shorter names? `ImGui::MD::Text(...)` is an official shorthand alias for `ImGui::Markdown::Text(...)`. Root shorthands like `ImGui::TextMD(...)` work directly under `ImGui::` as well.

TIP

`#`, `##`, and `###` Are Pure Markdown Headers (Never Swallowed as ImGui IDs!): In standard Dear ImGui widgets (`ImGui::Button`, `ImGui::Checkbox`, `ImGui::CollapsingHeader`, etc.), `"##"` is reserved as an ID separator that hides everything after `"##"`. In `ImGui::MD::Text(...)`, `ImGui::MD::TextWrapped(...)`, and `ImGui::TimedTooltip::TextMD(...)`, text is rendered via `ImGui::TextUnformatted(start, end)`, bypassing ImGui's `"##"` label parser completely. You can freely start strings or lines with `#`, `##`, or `###` for H1/H2/H3 headers without any escaping!

4. Rendering Markdown in Timed Tooltips

When combined with the companion **TimedTooltip** extension (included in either order, or via `#include "contrib/includes.h"`), rich multi-line Markdown tooltips are attached with a single line of code:

```cpp
#include "contrib/includes.h"

ImGui::Button("Accessibility Mode");
ImGui::TimedTooltip::TextMD(
    "### Accessibility Options\n"
    "Enables **larger fonts** and high-contrast styling across all plugin chrome.\n\n"
    "* Fast toggle: `Ctrl+Shift+A`\n"
    "* Requires zero reload."
);
```

Configuration Reference (`ImGui::MD::Config` / `ImGui::MarkdownConfig`)

For clean namespace symmetry with `ImGui::TimedTooltip::Config`, the configuration struct is accessible as both `ImGui::MD::Config` and `ImGui::MarkdownConfig`.

Field	Type	Default	Description
`boldFont`	`ImFont*`	`nullptr`	**[Semantic]** Font used for bold emphasis (`**bold**` / `__bold__`). (Falls back to `headingFormats[3].font`.)
`italicFont`	`ImFont*`	`nullptr`	**[Semantic]** Font used for true italics (`*italic*` / `_italic_`). (Falls back to `ImGuiCol_TextDisabled` if null.)
`monoFont`	`ImFont*`	`nullptr`	**[Semantic]** Font used for monospace code spans (` code ) and **[mono] / [code]**` tags. (Falls back to ambient font if null.)
`h1Font`	`ImFont*`	`nullptr`	**[Semantic]** Font used for H1 headers (`# Header`). (Falls back to `headingFormats[0].font`.)
`h2Font`	`ImFont*`	`nullptr`	**[Semantic]** Font used for H2 headers (`## Header`). (Falls back to `headingFormats[1].font`.)
`h3Font`	`ImFont*`	`nullptr`	**[Semantic]** Font used for H3 headers (`### Header`). (Falls back to `headingFormats[2].font`.)
`bulletSpacing`	`float`	`0.0f` (`4.0f` active)	Horizontal gap in pixels between the bullet circle glyph and the following text.
`codeBlockCallback`	`MarkdownCodeBlockCallback *`	`nullptr`	Optional host callback to customize syntax coloring, lexing, and custom token layout for fenced code blocks.
`codeBlockDescriptionCallback`	`const char* (*)(const char*, size_t, void*)`	`nullptr`	Optional host callback returning tooltip documentation for custom or recognized code block languages.
`setClipboardTextFn`	`void (*)(const char*, void*)`	`nullptr`	Optional host callback to forward code block copies directly to OS-level system clipboards (e.g. macOS NSPasteboard).
`showCodeCopyButton`	`bool`	`true`	When true, renders an interactive one-click `[Copy]` button in the code block header bar.
`tabSize`	`int`	`4`	Column-aligned tabstop expansion width for `\t` characters in code blocks.
`headingFormats`	`HeadingFormat[4]`	`{}`	Upstream array fallback for H1 (`[0]`), H2 (`[1]`), H3 (`[2]`), and Bold (`[3]`).
`linkCallback`	`LinkCallback`	`nullptr`	Upstream hook invoked when the user clicks a markdown `[link](url)`.
`tooltipCallback`	`TooltipCallback`	`nullptr`	Upstream hook invoked when hovering a link with tooltip description.

Field	Type	Default	Description
`imageCallback`	`ImageCallback`	`nullptr`	Upstream hook invoked to render inline markdown `![alt](url)` images.
`formatCallback`	`FormatCallback`	`defaultMarkdownFormatCallback`	Low-level upstream hook invoked when entering/exiting format blocks (headers, lists, bold, italic, code).

> **NOTE**
>
> **Do I Need to Implement the Callbacks?** In 99% of UI tasks, **no**. The callbacks (`linkCallback`, `tooltipCallback`, `imageCallback`, and `formatCallback`) are low-level C-style hooks inherited directly from the upstream `enkisoftware/imgui_markdown` base engine. With the semantic font properties (`boldFont`, `italicFont`, `monoFont`, `h1Font`, etc.) and the high-level tag registration API (`ImGui::MD::RegisterTag`), you do not need to write custom format callbacks.

Emphasis & Monospace Typography: Bold, Italics, and Code

Standard Markdown and CommonMark recognize distinct emphasis and code levels:

- **Level 1 Emphasis (`*italic*` or `_italic_`):** Traditionally rendered as italics (`<em>`).
- **Level 2 Emphasis (`**bold**` or `__bold__`):** Traditionally rendered as bold (`<strong>`).
- **Code Spans (`` ` code ` / [code] / [mono]):** `Rendered in monospace font ([code]`).

1. Bold Emphasis (`**bold**` / `__bold__`)

Bold emphasis automatically uses `mdConfig.boldFont`. If set (e.g. `IM_BOLD_FONT`), all double-delimiter text renders in crisp bold. If left `nullptr`, it checks `headingFormats[3].font` before falling back to the ambient window font.

2. True Italics (`*italic*` / `_italic_`)

In upstream `enkisoftware/imgui_markdown`, there was no field for italics, so single-delimiter text was given a shortcut: tinted with `ImGuiCol_TextDisabled` (a dimmed, half-opacity gray).

With our extension, simply assign your loaded italic font to `mdConfig.italicFont`:

```cpp
mdConfig.italicFont = IM_ITALIC_FONT;
```

When `italicFont` is assigned, `*hello*` and `_hello_` render in true, crisp italic typography rather than dimmed disabled gray. If left `nullptr`, it preserves upstream's disabled-color fallback for compatibility.

3. Monospace Code Spans (`` ` code `) and Code Tags ([code] / [mono]`)

For code identifiers, hotkeys, file paths, and terminal syntax, assign your loaded monospace font to `mdConfig.monoFont`:

```cpp
mdConfig.monoFont = IM_MONO_NORMAL_FONT;
```

You have two complementary options for rendering monospace text:

- **Inline Backtick Spans (`` ` code `):** `Standard CommonMark inline backticks switch cleanly to` mdConfig.monoFont` while preserving the surrounding text color and sentence flow.
- **Code Tags (`<code>foobar</code>` or `<mono>foobar</mono>`):** Switches to `mdConfig.monoFont` and automatically draws a subtle, translucent rounded pill background (`IM_COL32(128, 128, 128, 60)`) behind the text bounding box, providing a sleek styled code badge (similar to GitHub and documentation sites). Accepts optional

background tinting via parameter (e.g. **<code=#334455>foobar</code>**).

4. Multi-Line Fenced Code Blocks (` `lang / ~~~lang `)

For multi-line snippets, function signatures, configuration files, and terminal logs, use standard CommonMark triple backticks (or tildes):

```
void Initialize() {
ImGui::Badge("ONLINE", ImGui::ImGuiBadgeVariant_Success);
}
```

- **Features:**
- **Automatic Monospace Typography:** Uses **mdConfig.monoFont** (or ambient monospace font) line-by-line without word-wrapping or accidental markup parsing.
- **Responsive Width Clamping & Soft-Wrapping:** Dynamically hugs content lines while clamping maximum container width to available window space (**avail_width**). Wrapped continuation lines flow naturally without horizontal overflow.
- **CommonMark 4.5 Indentation Stripping:** When code blocks are nested inside list items or indented sections, leading indentation matching the opening fence is automatically stripped from code content, preventing code from being pushed awkwardly to the right.
- **Indented Closing Fences:** Supports closing fences indented by ≥ 4 spaces or tabs without swallowing subsequent markdown.
- **Language Badge (Steve TextLink):** Renders the language identifier on the left of the header bar. Formats recognized by built-in highlighters (**lua**, **cpp**, **markdown**, **plaintext**) or host callbacks are color-branded (Lua blue, C++ cobalt, Markdown teal, Plain text slate, Custom purple); unrecognized languages are styled in muted neutral charcoal. Hovering triggers **ImGuiMouseCursor_Hand**; clicking toggles an informative persistent tooltip (e.g. **"C++ format (Syntax highlighted)"**).
- **Animated Raw / Preview Toggle:** For **markdown** or **md** containers, renders an animated sliding toggle switch (**Raw [===O] Preview**) with smooth thumb easing, mouse-wheel scrub support, and live re-entrant formatting (including nested child code blocks). In scrollable viewports, mouse-wheel auto-defeat prevents accidental toggles while navigating long documents.
- **One-Click Vector Clipboard Copy:** Integrated procedural vector copy button on the far right with a transient 1.5s **Copied!** visual feedback state, **ImGuiMouseCursor_Hand** hover cursor, and optional host **setClipboardTextFn** forwarding. Scoped via **ImGuiStorage** to ensure multiple code blocks in the same window maintain their feedback independently without cross-talk.
- **Tabstop Expansion:** Universal 4-character column-aligned tabstop expansion (**tabSize = 4**).
- **CommonMark Compliant:** Supports both backticks (` `) and tildes (~~~`) with optional indentation and variable fence lengths.

5. Thematic Breaks / Horizontal Rules (---, *, ___)**

Standard CommonMark 4.1 thematic breaks create visual section dividers:

```
[MARKDOWN]
Section 1 text.
---
Section 2 text.
```

- Recognizes **---**, *******, and ___ with optional spaces between markers or at the end of the line.
- Renders a clean divider using **ImGui::Separator()**.

- Automatically balances spacing so dividers preceding or following headings do not create excessive empty vertical voids or stacked separators.

6. Interactive CommonMark Tables (Sorting, Resizing & Bi-Directional Persistence)

Standard CommonMark pipe tables render as full-featured, interactive Dear ImGui tables:

```
[MARKDOWN]
| Waypoint | Target Alt | Fuel Remaining | Est. Time |
|:---|:---:|---:|:---:|
| **SEA8** | 3,000 ft | 98% | 18:05z |
| **JAWBN** | 8,000 ft | 92% | 18:18z |
| **BTG** | 10,000 ft | 86% | 18:32z |
&lt;!-- table-preset: width=450 sort="Waypoint" asc --&gt;
&lt;!-- table-state: width=329 cols=51,72,94,75 sort="Waypoint" asc --&gt;
```

- **Features:**
- **CommonMark Syntax & Cell Alignment:** Parses headers, separator row, and data rows with cell text alignments (`:---` left, `:---:` center, `---:` right).
- **Rich Cell Content:** Cells support full inline Markdown formatting (bold, italic, code spans, `<pill>`, `<badge>`, etc.).
- **Tristate Header Sorting:** Click any column header to cycle between `Ascending` ↑, `Descending` ↓, and `None` (unsorted). Renders directional arrows and native hand cursor (`ImGuiMouseCursor_Hand`).
- **Internal Column Divider Dragging:** Drag any column boundary separator to adjust relative column widths.
- **Rightmost Width Grip Handle:** An interactive grab-handle on the rightmost edge of the table allows stretching or contracting the overall table width up to 5x available window space.
- **Horizontal Scroll Protection:** If the containing window has `ImGuiWindowFlags_HorizontalScrollbar`, tables retain their natural readable widths without being squished when the host window is narrow.
- **Double-Click A/B Toggle Memory:** Double-clicking the right border grip toggles back and forth between the baseline preset dimensions and the user's customized geometry (`cols=` and `width=`), preserving custom column widths across multi-cycle toggling.

Two-Tier Markdown Directives

Table configuration is persisted directly inside the Markdown text via invisible HTML comment chasers docked immediately beneath the table:

1. **Author Baseline Preset (`<!-- table-preset: ... -->` or `<!-- table: default ... -->`):**

- Placed by document authors to define reference geometry and default sort order:

```
[MARKDOWN]
    &lt;!-- table-preset: width=450 sort="Waypoint" asc --&gt;
```

2. **Active User State (`<!-- table-state: ... -->` or `<!-- table: user ... -->`):**

- Generated automatically when a user modifies column widths, total width, or sort column/direction:

```
[MARKDOWN]
    &lt;!-- table-state: width=329 cols=51,72,94,75 sort="Waypoint" desc --&gt;
```

- When double-clicking to reset to baseline, `width=` and `cols=` are automatically omitted, retaining only non-default sort overrides (e.g. `<!-- table-state: sort="Waypoint" desc -->`).

Bi-Directional Host Synchronization

To synchronize live UI interactions (sorting, resizing) back to your raw Markdown buffer or file storage:

```
[CPP]
ImGui::MD::Config mdConfig;

mdConfig.tableStateCallback = [](const ImGui::MarkdownTableState&amp;amp; state, void* userData) {
    auto* editorBuffer = static_cast&amp;lt;std::string*&amp;gt;(userData);

    // Commit only on user release or definitive clicks:
    if (state.isCommitted) {
        *editorBuffer = ImGui::ApplyTableStateToMarkdown(*editorBuffer, state);
    }
};
mdConfig.userData = &amp;amp;myMarkdownString;
```

7. Built-in Image Services (Tiers 1, 2 & 3)

Images in Markdown (`![alt text](url)`) are resolved automatically via **`ImgWindow`**'s built-in 3-tier image service, requiring zero boilerplate callbacks:

1. **Tier 1: In-Memory Named Textures (`texture://name` or `name`):**

- Pre-register memory textures (cockpit gauges, avionics icons, branding):

```
[CPP]
     ImgWindow::RegisterMarkdownNamedTexture("acme_logo", myTexId, ImVec2(64, 64));
```

- Markdown references like `![Logo](texture://acme_logo)` or `![Logo](acme_logo)` resolve instantly with zero disk I/O.

2. **Tier 2: Local Disk Images:**

- Referenced via relative or absolute paths: `![Airplane](imgui_demo.jpg)` or `![Diagram](./Resources/diagram.png)`.
- Automatically searched relative to the active document directory, the calling plugin's directory, and the X-Plane system root.
- Decoded safely via embedded **`stb_image`** (forcing 4-channel RGBA8 for Metal/Vulkan hardware safety), uploaded via **`ImgWindow::CreateTexture()`**, and cached in VRAM with negative caching to prevent disk thrashing.

3. **Tier 3: Asynchronous Remote Web Images (`http://`, `https://`):**

- Referenced directly via web URLs: `![Badge](https://img.shields.io/badge/X--Plane-12.00+-blue.png)`.
- **Zero-Stall Sim Loop:** Network downloads and CPU image decompression run completely off-thread in the background, keeping the simulation loop running smoothly at 60+ FPS.
- **Main-Thread GPU Upload:** Decoded pixel buffers are handed off to the main render thread and uploaded via **`ImgWindow::CreateTexture()`** without blocking frame rendering.
- **Transient Loading State:** While in flight, the renderer displays a subtle disabled indicator (**`( Loading https://... )`**) which seamlessly converts to the rendered image once ready.
- **Zero External Dependencies:** Dynamically resolves system **`libcurl`** on macOS/Linux and native **`WinINet`** on Windows without requiring any downstream plugins to modify their linker flags or **`CMakeLists.txt`**.
- **Custom Fetch Overrides:** Host plugins with dedicated HTTP managers can register a custom downloader via **`ImgWindow::SetMarkdownRemoteFetchCallback(...)`**.

8. Image Sizing, Auto-Constraints & Treatments

Images in Markdown support rich layout modifiers, responsive viewport constraints, and decorative treatments:

1. **Auto-Constraint to Viewport Width (`max-width: 100%; height: auto`):**

- High-resolution graphics or photos that exceed the current window or column width (**`ImGui::GetContentRegionAvail().x`**) are automatically downscaled proportionally, preventing unwanted

horizontal scrollbars or clipped avionics layouts.

2. **Explicit Pandoc / Extended Markdown URL Sizing:**

• **Explicit Dimensions:** `![Diagram](diagram.png =300x200)` renders at 300x200 px.

• **Proportional Width:** `![Logo](logo.png =150x)` renders at 150px wide with height scaled to preserve natural aspect ratio.

• **Proportional Height:** `![Badge](badge.png =x30)` renders at 30px high with proportional width.

• **Viewport Percentage:** `![Banner](banner.png =50%)` dynamically renders at 50% of available window width with proportional height.

• **Angle-Bracket CommonMark URLs:** `![Banner](<https://example.com/banner.png =50%>)` or `![Pic](<https://example.com/pic.png> =200x150)`.

3. **Pandoc Attribute Block Syntax:**

• Append curly attributes after the image link:

```
[MARKDOWN]
     ![Cockpit](panel.png){ width=250px height=180px border=#4a90e2 }
```

4. **HTML `<img ... />` Element Support:**

• Supports standard HTML tags, self-closing tags, and void elements:

```
[HTML]
     &amp;lt;img src="https://example.com/badge.png" width="180" height="40" border="#00ff00" /&amp;gt;
     &amp;lt;img src="gauge.png" width="50%" border /&amp;gt;
```

5. **Image Treatments (Borders & Frames):**

• Add a border by specifying `border` (subtle default frame), `border=red`, or hex colors `border=#4a90e2` across any syntax variant. Cleanly mapped to `ImGui::Image()`'s native border parameter.

6. **VRAM Texture Cache Deduplication:**

• Sizing and treatment modifiers are parsed and stripped *before* cache lookup and network fetch. Multiple markdown instances referencing the same URL with different sizes or borders reuse the exact same underlying GPU texture in VRAM.

> **IMPORTANT**
>
> **Operating System Clipboard Integration Across Platforms:** * **macOS (`APL=1` / `__APPLE__`):** Upstream Dear ImGui compiles with OS clipboard support disabled unless `#define IMGUI_ENABLE_OSX_DEFAULT_CLIPBOARD_FUNCTIONS` is defined in your `imconfig.h` (and `-framework ApplicationServices` linked). If unconfigured, the `[Copy]` button automatically renders as a disabled button with an on-hover guidance tooltip. * **Windows (`IBM=1` / `_WIN32`):** OS clipboard works out of the box via Dear ImGui's built-in Win32 implementation (`user32.lib`). * **Linux (`LIN=1` / `__linux__`):** Upstream Dear ImGui does not provide an out-of-the-box X11 clipboard implementation. To enable system copying on Linux, assign `MarkdownConfig::setClipboardTextFn` or set `ImGui::GetPlatformIO().Platform_SetClipboardTextFn`.

Per-Call Configuration Overrides

Every rendering function in `ImGui::MD` accepts an optional `const MarkdownConfig*` pointer if a specific widget requires unique fonts, callbacks, or bullet spacing:

```
[CPP]
ImGui::MD::Config customConfig = *ImGui::GetDefaultMarkdownConfig();
customConfig.bulletSpacing = 6.0f;

ImGui::MD::Text(markdownString, &amp;amp;customConfig);
```

Layout Pre-Calculation (`CalcTextSize`)

When building stationary tooltips or sizing dynamic OS windows to fit a block of documentation, you need to know the rendered height *before* drawing:

```
[CPP]
ImGuiID widgetId = ImGui::GetID("doc_section");
float wrapWidth = 400.0f; // Constrain to 400px wide
float fontScale = 0.0f;   // 0.0f = inherit ambient scale

// Pre-calculates exact ImVec2 dimensions without rendering to the screen:
ImVec2 requiredSize = ImGui::MD::CalcTextSize(widgetId, 1, docString, wrapWidth, fontScale);

// Use the size to configure window bounds or child frames:
ImGui::SetNextWindowSize(requiredSize);
```

Markdown Styling Tags (`<tag=param>` / `<tag param>`)

The extension includes a built-in pre-processor that allows you to embed rich, inline styling tags and interactive widgets directly within Markdown text without breaking standard Markdown formatting rules:

```
[MARKDOWN]
This option is &lt;color=red&gt;highly experimental&lt;/color&gt;!
Please verify &lt;backdrop=yellow&gt;active route&lt;/backdrop&gt; before flight.
System status: &lt;badge=danger&gt;FAULT&lt;/badge&gt; | &lt;badge=success&gt;ONLINE&lt;/badge&gt;
```

1. Flexible Tag Syntax

Tags support both HTML-style attributes and key-value formats:

- **Assignment format:** `<tag=red>text</tag>`, `<backdrop=yellow>text</backdrop>`
- **Space-separated format:** `<tag red>text</tag>`, `<color #00FFCC>text</color>`
- **Multi-parameter format:** `<tag=red,bold>text</tag>`, `<tag red bold>text</tag>`

2. Bold, Italic, and Monospace Styling Inside Tags

You can style tag text in two natural ways:

A. Markdown Syntax Inside the Tag (Recommended)

Place standard Markdown delimiters directly inside the tag content:

```
[MARKDOWN]
Check &lt;tag red&gt;**accessibility**&lt;/tag&gt; or options.
Please review &lt;backdrop=yellow&gt;**critical checklist**&lt;/backdrop&gt; before departure.
Click &lt;btn&gt;*more info*&lt;/btn&gt; for details.
&lt;pill orange&gt;` ■ `&lt;/pill&gt;
```

- The engine detects inner Markdown wrappers (`**bold**`, `__bold__`, `*italic*`, `_italic_`, `` ` `` mono `), strips the wrapper characters so delimiters never render literally, and pushes the active bold, italic, or monospace (`mdConfig.monoFont`) font.
- Intentional leading/trailing padding spaces (both outside and inside the delimiters, as well as UTF-8 non-breaking spaces `U+00A0`) are preserved so you can easily pad single-icon pills (e.g., `"<pill orange mono> " ICON_FA_RETWEET " </pill>"` or `"<pill orange>` " ICON_FA_RETWEET " `</pill>"`).
- For `<backdrop>` and `<pill>`, the font is pushed *before* measuring text width, ensuring the pill bounding box fits the styled glyphs.

B. Tag Parameter Flags

You can also specify **bold** (or **b**), **italic** (or **i**), and **mono** (or **monospace**, **code**, **m**) directly in the tag attributes (alongside optional **color=** / **col=** prefixes):

```
[MARKDOWN]
Check &lt;tag red bold&gt;accessibility&lt;/tag&gt; or options.
Check &lt;tag=red,bold&gt;accessibility&lt;/tag&gt; or options.
&lt;pill orange mono&gt; ■ &lt;/pill&gt;
&lt;pill color=0xFFA500, mono&gt; ■ &lt;/pill&gt;
&lt;btn bold&gt;Acknowledge&lt;/btn&gt;
```

NOTE

Why `**<tag>...</tag>**` is not supported: In Markdown and CommonMark, formatting delimiters wrap text spans rather than embedding interactive widgets across boundary tokens. Nesting formatting inside the tag (**<tag>**text**</tag>**) or on the tag (**<tag bold>text</tag>**) follows standard HTML/XML element structure and guarantees correct word wrapping and draw-list grouping.

3. Inline Spacing & Punctuation Flow

Inline tags integrate cleanly into paragraph and sentence flow:

- **Preserved Spaces:** Both inter-word spaces after a closing tag (such as **<tag red>badge</tag> or options**) and intentional padding spaces inside a tag (such as **<pill orange mono> ■ </pill>**) are preserved.
- **Flush Punctuation:** When followed by punctuation without space, such as **<tag red>badge</tag>, options**, the punctuation docks directly flush against the tag border.
- **Automatic Line-Wrap Protection:** If an inline tag, button, or background pill exceeds the remaining horizontal space on the current line, the renderer automatically wraps down to the next line (**EnsureTagFitsOnLine**) to prevent tags from spilling past window borders.

4. Pre-Supplied Built-in Tags (Ready Out-of-the-Box)

The following tags are pre-registered and active by default:

Tag	Syntax Options	Parameters & Variants	Description
color / **col**	**<color=COLOR>text</color>** **<color COLOR [bold] [italic] [mono]>text</color>**	Named colors (**red**, **green**, **blue**, **yellow**, **orange**, **purple**, **violet**, **cyan**, **magenta**, **white**, **black**, **gray**, **gold**, **dark**, **light**) or hex (**#RRGGBB**, **#RRGGBBAA**, **0xRRGGBB**, **0xRRGGBBAA**). Optional flags: **bold**, **italic**, **mono**.	Renders **text** in the specified color and font style.
backdrop / **bg** / **highlight**	**<backdrop=COLOR>text</backdrop>** **<backdrop COLOR [bold] [italic] [mono]>text</backdrop>**	Accepts any named color or hex code. Optional attribute flags: **bold**, **italic**, **mono**.	Renders a rounded background rectangle ("pill") optically centered behind the text bounding box. Backdrops auto-contrast text color against dark backgrounds and never split awkwardly across lines.
badge / **pill** / **tag**	**<badge=VARIANT>text</badge>** **<pill COLOR [bold] [italic] [mono]>text</pill>** **<pill bg=BG fg=FG>text</pill>**	Semantic variants (**danger**, **warning**, **success**, **info**), named colors, or custom hex color. Supports explicit dual-color attributes (**bg=COLOR fg=COLOR**, **color=COLOR text=COLOR**). Optional flags: **bold**, **italic**, **mono**.	Delegates directly to **ImGui::Badge** / **ImGui::Pill** standalone C++ widgets. Renders sleek rounded badges with auto-contrasting text.

Tag	Syntax Options	Parameters & Variants	Description
`kbd` / `key` / `kdb`	`<kbd>Key</kbd>` `<key>Ctrl+C</key>`	Keyboard key or shortcut label (`kdb` is a built-in typo alias).	Delegates directly to `ImGui::Kbd`. Renders a 3D tactile keyboard keycap with bottom bevel/shadow.
`u` / `ins`	`<u>text</u>` `<ins>text</ins>`	Optional color attribute (`<u #FFCC00>`).	Renders text with a pixel-aligned underline rule along the baseline.

`s` / `del` / `strike`	`<s>text</s>`
	`<del>text</del>`
	`<strike>text</strike>`
		Optional color attribute (`<s red>`).	Renders text with a pixel-aligned strikethrough rule across the vertical midline.

`center` / `centre`	`<center>text</center>` `<centre>text</centre>`	Centered block or inline span.	Centers text or multiline blocks horizontally within the available content area. Pre-measures content width across headers, bold/italics, pills, and badges.
`btn`	`<btn=ID>label</btn>` `<btn [bold] [italic] [mono]>label</btn>`	Unique button ID or style flags (`bold`, `italic`, `mono`).	Renders an inline, clickable `ImGui::SmallButton` directly within text flow.
`mono` / `code`	`<mono>text</mono>` `<code [COLOR]>text</code>`	Accepts optional custom background color or hex parameter (and optional `fg=COLOR`).	Renders `text` in monospace (`mdConfig.monoFont`) inside a subtle, translucent rounded background pill.
`small` / `tiny`	`<small>text</small>` `<tiny>micro text</tiny>`	Optional color attribute (`<small #aaa>`).	Renders text using `ImFontRole::Small` (Slot 2, typically 12px) or `ImFontRole::Tiny` (10px micro font or `Small` fallback).
`big` / `large`	`<big>text</big>` `<large>text</large>`	Optional color attribute (`<big orange>`).	Renders text using `ImFontRole::Title` (Slot 1, typically 16px).
`huge`	`<huge>text</huge>`	Optional color attribute (`<huge #ffcc00>`).	Renders text using `ImFontRole::BoldLarge` (Slot 4, typically 16px+ bold).
`regular` / `prop` / `sans`	`<regular>text</regular>` `<sans>text</sans>`	Optional color attribute.	Resets text font back to `ImFontRole::Regular` (Slot 0 base body font) inside mono or heading spans.

(To disable default tags, define `#define IMGUI_DISABLE_MARKDOWN_DEFAULT_TAGS` before including the header.)

Two-Color Pills & Badges (`bg=` and `fg=`)

By default, `<badge>`, `<pill>`, and `<backdrop>` automatically contrast the text color against the background (e.g., using dark text on yellow, light text on dark blue). When you want explicit artistic control over both colors, specify `bg` (background) and `fg` (text/foreground):

```
[MARKDOWN]
Status: &lt;pill bg=warning fg=black&gt;CAUTION&lt;/pill&gt;
Release: &lt;badge bg=#1a3a5a fg=#40c0ff bold&gt;v2.2.1&lt;/badge&gt;
Dual-tone: &lt;pill purple white italic&gt;SPECIAL&lt;/pill&gt;
```

Inner Markdown vs. Tag Attributes

It's helpful to distinguish how formatting reaches your tags:

1. **Inner Markdown (`<tag>**text**</tag>`):**

Works universally across **all** tags (both built-in tags and your own custom registered tags). If you write standard Markdown delimiters inside a tag, the engine automatically pushes the matching bold/italic font and strips the delimiter characters *before* calling the tag callback.

2. **Tag Attributes (`<tag param>text</tag>`):**

Built-in tags (**`badge`**, **`backdrop`**, etc.) inspect the opening tag's attribute string for colors and layout flags. When writing custom tags, the raw parameter string is passed directly into your callback as the second argument (**`param`**), allowing you to build arbitrary domain-specific markup (e.g., **`<item id=42 count=3>Widget</item>`**).

---

5. Custom Tag Registration (`ImGui::MD::RegisterTag`)

You can register your own custom styling tags or widgets using **`ImGui::MD::RegisterTag`** (or **`ImGui::RegisterMarkdownTag`**) with either 1-argument or 2-argument (parameterized) callbacks:

```cpp
// 1. Parameterized tag: &lt;status=critical&gt;Engine 1&lt;/status&gt; or &lt;status ok&gt;Engine 2&lt;/status&gt;
ImGui::MD::RegisterTag("status", [](const std::string&amp; text, const std::string&amp; param) {
    ImVec4 col = (param == "critical") ? ImVec4(1.0f, 0.2f, 0.2f, 1.0f) : ImVec4(0.2f, 0.8f, 0.2f, 1.0f);
    ImGui::PushStyleColor(ImGuiCol_Text, col);
    ImGui::TextUnformatted(text.c_str());
    ImGui::PopStyleColor();
});

// 2. Simple single-argument tag: &lt;notice&gt;Check checklists&lt;/notice&gt;
ImGui::MD::RegisterTag("notice", [](const std::string&amp; text) {
    ImGui::BulletText("%s", text.c_str());
});
```

> **TIP**
>
> **A Friendly Note on C++ Lambdas:** If you are new to modern C++, the `[](const std::string& text, const std::string& param) { ... }` syntax is standard C++11 lambda notation for an inline anonymous function. The lambda receives whatever text was enclosed between `` and `` as `text`, and any parameters or attributes from the opening tag as `param`.

*(Note: **`ImGui::RegisterMarkdownTag`** and **`ImGui::RegisterMarkdownWidget`** are also preserved as direct backward-compatible aliases.)*

API Summary

```cpp
namespace ImGui {

    // Global Configuration &amp;amp; Tag Registry:
    void SetDefaultMarkdownConfig(const MarkdownConfig* config);
    const MarkdownConfig*&amp;amp; GetDefaultMarkdownConfig();
    void RegisterMarkdownTag(const std::string&amp;amp; tag_name, TagCallback callback);
    void RegisterMarkdownWidget(const std::string&amp;amp; tag_name, CustomTagCallback callback);

    namespace MD {
        // Configuration Alias:
        using Config = MarkdownConfig;

        // Custom Tag Registration (Convenience Aliases):
        void RegisterTag(const std::string&amp;amp; tag_name, std::function&amp;lt;void(const std::string&amp;amp; text
        void RegisterTag(const std::string&amp;amp; tag_name, std::function&amp;lt;void(const std::string&amp;amp; text

        // Standard Text Rendering (Mirroring standard ImGui vocabulary):
        // - TextUnformatted / Text: Do not wrap by default (unless wrap_width / wrap_size or PushTextWrapP
        // - TextWrapped: Wraps automatically to GetContentRegionAvail().x (or explicit wrap_width / wrap_s
        void TextUnformatted(const char* text, const char* text_end = nullptr, const MarkdownConfig* config

        void TextUnformatted(const std::string&amp;amp; markdown_text, const MarkdownConfig* config_override =
        void Text(const std::string&amp;amp; markdown_text, const MarkdownConfig* config_override = nullptr);
        void Text(const std::string&amp;amp; markdown_text, float wrap_width, const MarkdownConfig* config_over
        void Text(const std::string&amp;amp; markdown_text, const ImVec2&amp;amp; wrap_size, const MarkdownConfig*
        void TextWrapped(const std::string&amp;amp; markdown_text, const MarkdownConfig* config_override = null
        void TextWrapped(const std::string&amp;amp; markdown_text, float wrap_width, const MarkdownConfig* conf
        void TextWrapped(const std::string&amp;amp; markdown_text, const ImVec2&amp;amp; wrap_size, const MarkdownC

        // Clickable Markdown Text Links (Hand cursor on hover; toggles TimedTooltip on click if return val
        LinkClickResult TextUnformattedLink(const char* text, const char* text_end = nullptr, const Markdow
        LinkClickResult TextUnformattedLink(const std::string&amp;amp; markdown_text, const MarkdownConfig* con
        LinkClickResult TextLink(const std::string&amp;amp; markdown_text, const MarkdownConfig* config_overrid
        LinkClickResult TextLink(const std::string&amp;amp; markdown_text, float wrap_width, const MarkdownConf
        LinkClickResult TextLink(const std::string&amp;amp; markdown_text, const ImVec2&amp;amp; wrap_size, const M
        LinkClickResult TextWrappedLink(const std::string&amp;amp; markdown_text, const MarkdownConfig* config_
        LinkClickResult TextWrappedLink(const std::string&amp;amp; markdown_text, float wrap_width, const Markd
        LinkClickResult TextWrappedLink(const std::string&amp;amp; markdown_text, const ImVec2&amp;amp; wrap_size,

        // Backward-Compatibility Aliases:
        void TextMD(const std::string&amp;amp; markdown_text, const MarkdownConfig* config_override = nullptr);

        void TextWrappedMD(const std::string&amp;amp; markdown_text, const MarkdownConfig* config_override = nu

        // Layout Pre-Measurement:
        ImVec2 CalcSize(ImGuiID id, int pass, const std::string&amp;amp; text, float wrap_width = 0.0f, float f
        ImVec2 CalcTextSize(ImGuiID id, int pass, const std::string&amp;amp; text, float wrap_width = 0.0f, flo
        ImVec2 CalcMarkdownSize(ImGuiID id, int pass, const std::string&amp;amp; text, float wrap_width = 0.0f,

        // Interactive Button with Rich Tooltip &amp;amp; Vector Icon Rendering:
        bool ButtonMD(const std::string&amp;amp; label, const std::string&amp;amp; tooltip_md = "", float tooltip_w
        bool ButtonMD(const std::string&amp;amp; label, const ImVec2&amp;amp; size, const std::string&amp;amp; tooltip_
    }
}

// Top-Level Convenience Aliases (root ImGui:: namespace):
bool ImGui::ButtonMD(const std::string&amp;amp; label, const std::string&amp;amp; tooltip_md = "", float tooltip_wr
bool ImGui::ButtonMD(const std::string&amp;amp; label, const ImVec2&amp;amp; size, const std::string&amp;amp; tooltip_m
```

Interactive Buttons (`ImGui::ButtonMD` / `ImGui::Markdown::ButtonMD`)

`ButtonMD` provides an immediate-mode push button that seamlessly combines Dear ImGui native button styling, procedural vector icon rendering, hand cursor feedback, and rich Markdown tooltips.

- **Vector Icon Button Faces:**

If the button label includes an icon tag (`<icon caret-up />`), an emoji shortcode (`:undo: Reset`), raw Unicode (`▲##up`), or Steven's raw-fallback link macro (`#[^](ICON_CARET_UP)`), `ButtonMD` renders the procedural vector icon directly to `ImDrawList` on the button face.

- **Pure icon buttons** (e.g. `ButtonMD("<icon caret-up />##up")`) default to square geometry matching `ImGui::GetFrameHeight()`.
- **Icon + Text buttons** (e.g. `ButtonMD(":gear: Settings")` or `ButtonMD("<icon undo color=#ff5555 /> Revert")`) auto-size to fit both the icon and text with standard inner item spacing.
- **No font dependencies:** Never displays missing-glyph diamond boxes (`?`).
- **Rich Markdown Tooltips:**

When hovered, renders formatted multi-line Markdown tooltips wrapped to `tooltip_wrap_width` (default 400px).

- **Hand Cursor:**

Automatically activates `ImGuiMouseCursor_Hand` when hovered.

```
[CPP]
// Pure icon button (square, auto-sized to GetFrameHeight()):
if (ImGui::ButtonMD("&lt;icon caret-up /&gt;##scroll_top", "Scroll to top of document")) {
    ScrollToTop();
}

// Raw Unicode rescue:
if (ImGui::ButtonMD("▲##zoom_in", "Increase preview zoom")) {
    ZoomIn();
}

// Icon + Text with custom icon color and Markdown tooltip:
if (ImGui::ButtonMD("&lt;icon undo color=#ff5555 /&gt; Reset All##reset", "**Warning:** Reverts *all* prefe
    ResetDefaults();
}
```

```
---

## Appendix: Real-World Example &amp;amp; Comparison

Below is a complete real-world example illustrating how the **Markdown** and **TimedTooltip** extensions co

### Side-by-Side: Why Use the Extensions?

To appreciate what the extensions handle behind the scenes, consider what is required to build a mixed-form

#### The Hard Way: Vanilla Dear ImGui (Without Extensions)
```

// --

// VANILLA IMGUI: ~70+ lines of low-level boilerplate, manual geometry math,

// and state storage just for a single header, backdrop pill, and timed tooltip!

// --

void RenderSettingsPanelVanilla()

{

ImGui::Begin("Plugin Settings & Reference");

// 1. Header: Manual font push, separator, and manual pop

ImGui::PushFont(IMG_TITLE_FONT);

ImGui::TextUnformatted("Welcome to Avionics Manager");

```
ImGui::PopFont();
ImGui::Separator();
// 2. Mixed Bold Text + Background Highlight Pill:
// In vanilla ImGui, you cannot wrap text across lines if you embed custom drawn rectangles.
// You have to manually calculate draw list coordinates, text sizes, and padding:
ImGui::TextUnformatted("Configure your autopilot, navigation modes, and ");
ImGui::SameLine(0.0f, 0.0f);
ImVec2 p0 = ImGui::GetCursorScreenPos();
ImVec2 text_sz = IM_BOLD_FONT->CalcTextSizeA(IM_BOLD_FONT->FontSize, FLT_MAX, 0.0f, "expert features");
ImVec2 p1 = ImVec2(p0.x + text_sz.x + 8.0f, p0.y + text_sz.y + 2.0f);
// Draw background pill manually:
ImGui::GetWindowDrawList()->AddRectFilled(p0, p1, IM_COL32(255, 230, 60, 255), 4.0f);
// Position text inside pill and draw in dark contrast color:
ImGui::SetCursorScreenPos(ImVec2(p0.x + 4.0f, p0.y + 1.0f));
ImGui::PushFont(IM_BOLD_FONT);
ImGui::PushStyleColor(ImGuiCol_Text, IM_COL32(20, 20, 20, 255));
ImGui::TextUnformatted("expert features");
ImGui::PopStyleColor();
ImGui::PopFont();
// Resume following text:
ImGui::SetCursorScreenPos(ImVec2(p1.x, p0.y));
ImGui::TextUnformatted(" below.");
ImGui::Spacing();
// 3. Bullet List:
// Vanilla ImGui::BulletText does NOT support hanging indents when text wraps.
// Continuation lines wrap directly beneath the bullet circle instead of indenting cleanly.
// Fixing this requires manual ImGui::Indent() / ImGui::Unindent() bookkeeping.
ImGui::Bullet();
ImGui::SameLine(0.0f, 4.0f);
ImGui::TextWrapped("autopilot: Controls automated flight guidance (LNAV, VNAV, FLCH).");
ImGui::Spacing();
// 4. Reset Button with Stationary Clamped Tooltip:
// Vanilla ImGui::SetTooltip moves with the mouse, has no hover delay, and lacks screen clamping.
// Building a stationary tooltip with a 1-second delay and viewport boundary clamping requires
// querying frame counters, ImGuiStorage, and calculating display boundary math:
```

```
ImGui::Button("Reset to Defaults");
static int s_HoverFrames = 0;
if (ImGui::IsItemHovered()) {
s_HoverFrames++;
if (s_HoverFrames > 60) { // ~1.0 second delay
ImVec2 mousePos = ImGui::GetIO().MousePos;
ImVec2 dispSize = ImGui::GetIO().DisplaySize;
ImVec2 tipSize(260.0f, 80.0f); // Guessed height!
// Manual screen boundary clamping:
ImVec2 tipPos = ImVec2(mousePos.x, mousePos.y + 20.0f);
if (tipPos.y + tipSize.y > dispSize.y) tipPos.y = mousePos.y - tipSize.y - 10.0f;
if (tipPos.x + tipSize.x > dispSize.x) tipPos.x = dispSize.x - tipSize.x - 10.0f;
ImGui::SetNextWindowPos(tipPos);
ImGui::PushStyleColor(ImGuiCol_PopupBg, IM_COL32(255, 242, 153, 255));
ImGui::PushStyleColor(ImGuiCol_Text, IM_COL32(0, 0, 0, 255));
if (ImGui::BeginTooltip()) {
ImGui::TextUnformatted("Restores all settings to factory defaults.");
ImGui::EndTooltip();
}
ImGui::PopStyleColor(2);
}
} else {
s_HoverFrames = 0;
}
ImGui::End();
}
```

```
---

#### The Clean Way: With ImgWindow Extensions (`MD` + `TimedTooltip`)
```

```
// ----------------------------------------------------------------------------
// WITH EXTENSIONS: Clean, declarative, expressive code.
// The engine automatically handles dynamic font scaling, lookahead word wrapping,
// hanging bullet indents, draw-list pills, delay timers, and screen docking!
// ----------------------------------------------------------------------------
#include "contrib/extensions/Markdown/imgui_markdown_ext.h"
#include "contrib/extensions/TimedTooltip/imgui_tooltip_ext.h"
```

```
void RenderSettingsPanelExtensions()
{
ImGui::Begin("Plugin Settings & Reference");
// 1. Rich Header and Overview with Custom Backdrop Pill and Tags:
ImGui::MD::TextWrapped(
"### Welcome to Avionics Manager\n"
"Configure your autopilot, navigation modes, and <backdrop=yellow>**expert features**</backdrop> below. "
"Hover over any setting or **[tag red]**tag**[/tag]** for operational manuals."
);
ImGui::Separator();
// 2. Multi-Line List with Nested Bullets, Badges, and Automatic Hanging Indents:
ImGui::MD::TextWrapped(
"* **[tag red]**modes**[/tag]**: *Click* on active tags above to filter the feature catalog.\n"
" * *Important*: Filter queries use exact \"**[tag yellow]**substring**[/tag]**\" matching.\n"
" * Toggle back to preset: __#1__ / \"**Default Nav**\" **[pill green]**Active**[/pill]**.\n"
"* **[tag blue]**autopilot**[/tag]**: Controls automated lateral and vertical flight guidance.\n"
" * Supported modes: **LNAV**, **VNAV**, and **FLCH**.\n"
" * Disconnect shortcut: **Ctrl+Shift+D**."
);
ImGui::Spacing();
// 3. Interactive Widgets with Stationary Clamped Markdown Timed Tooltip:
if (ImGui::Button("Reset to Defaults")) {
// Reset logic...
}
// Automatically binds to the preceding button, manages hover cycle delays,
// isolates styles, clamps to screen borders, and renders rich Markdown:
ImGui::TimedTooltip::TextMD(
"### Reset Configuration\n"
"Restores all plugin settings back to factory defaults.\n\n"
"* **Reversible:** A backup of your current setup is saved automatically.\n"
"* Active theme: #3/\"**Black & White**\" **[pill green]**PG**[/pill]**.\n"
"* *Click to confirm.*"
);
ImGui::End();
}
```

TimedTooltip Extension

The **TimedTooltip** extension provides an advanced, stationary tooltip engine designed specifically for Dear ImGui within X-Plane plugins.

Unlike standard Dear ImGui tooltips which move with the mouse and can flicker, obstruct UI elements, or run off-screen, `TimedTooltip` locks in place, calculates dynamic viewport boundaries, preserves custom interactive cursors, isolates its styling hermetically from parent windows, and supports both plain-text and rich Markdown content.

> **Author / Maintainer:** Steven L. Goldberg (@slgoldberg)

> **License:** BSD 3-Clause (see ImgWindow LICENSE)

Key Features

- **Configurable Delay & Lifetime:**
- **Low Watermark (Hover Delay):** Prevents tooltip spam by waiting for the user to pause over a widget before showing.
- **Active Input Low-Water Reset:** Spinning the mouse wheel (`io.MouseWheel` / `io.MouseWheelH`) or dragging (`IsMouseDragging`) over any widget immediately slams the hover timer back to 0 and dismisses any active tooltip, preventing tooltips from popping up or obstructing adjustments during continuous wheel scrolling or slider interaction.
- **High Watermark (Auto-Dismiss):** Automatically hides tooltips after a readable duration, with adaptive time-scaling for taller/multi-line text.
- **Grace Period:** Forgives micro-slips off the target widget so users don't lose their place.
- **Wiggle Latch:** Micro-mouse movements reset the auto-hide timer so users can continue reading long descriptions.
- **Hermetic Style Isolation:**
- Pushes and pops its own `WindowPadding`, `ItemSpacing`, `FramePadding`, and `IndentSpacing`. Outer parent window style modifications (such as `ItemSpacing.x = 0` in menu bars or compressed button pads) can never distort tooltip typography, and tooltip styles never leak back out.
- Precise vertical line pitch (`item_spacing.y = 0.0f`) preserves the exact 15px native font leading in X-Plane, preventing vertical bloat and screen overrun.
- **Smart Bounds Clamping & Docking:**
- **Cursor-Safe Viewport Clamping (Flip Above Cursor):** If a tooltip would clip off the bottom of the screen (e.g. over a bottom control strip or footer slider), it automatically flips **above the mouse cursor**, ensuring the tooltip never covers the cursor or the widget being manipulated.
- **Leftward Shift:** If a tooltip approaches the right screen border, it automatically shifts leftwards.
- **Adaptive Wrap:** Shrink-wraps tightly around concise text while wrapping paragraphs at a readable width (80% of available viewport width by default).
- **Interactive Cursor Protection & Click-to-Toggle Ergonomics:**
- Preserves and restores custom widget cursors (e.g., `ImGuiMouseCursor_Hand` or `ImGuiMouseCursor_ResizeEW`), and automatically shows a Hand cursor on passive text/labels that have a tooltip attached.
- Clicking passive text, right-side Slider/Drag/Combo labels, dimmed at-default reset buttons, or standalone `*Link` widgets immediately toggles the tooltip ON/OFF without waiting for `hover_delay_cycles`.
- **Multi-`ImGuiContext` & Overlapping-Widget Safety:**
- Isolates tooltip state and wheel-selection latches per `ImGuiContext*` so multiple `ImgWindow` instances rendering in the same X-Plane draw cycle never interfere with one another.
- **Foreground-Widget Hover Priority:** When a button sits on the same line as a full-width background `Selectable(..., ImGuiSelectableFlags_SpanAllColumns)`, `TimedTooltip` automatically gives tooltip priority to the earlier foreground widget on the row without requiring manual hover-suppression flags.

- **Plain Text & Markdown Support (Order-Independent):**
- Native auto-wrapping plain-text via **`Text(...)`**, single-line non-wrapping plain-text via **`TextUnformatted(...)`**, rich auto-wrapping Markdown via **`TextMD(...)`**, and single-line non-wrapping Markdown via **`TextUnformattedMD(...)`**.
- **`imgui_tooltip_ext.h`** and **`imgui_markdown_ext.h`** can be **`#include`**d in **either order** and the **`TextMD`** / **`TextUnformattedMD`** bridge is synthesized automatically.

Quick Start

1. Include the Header

```
[CPP]
#include "contrib/extensions/TimedTooltip/imgui_tooltip_ext.h"
```

2. Basic Usage (Plain Text)

Attach a timed tooltip directly after drawing any ImGui widget:

```
[CPP]
if (ImGui::Button("Save Flight Plan")) {
    SavePlan();
}
// Automatically attaches to the preceding widget:
ImGui::TimedTooltip::Text("Saves the active route to disk as an .fms file.");
```

3. Markdown Tooltips

If using the companion **Markdown** extension, simply call **`TextMD`**:

```
[CPP]
#include "contrib.h"

ImGui::Button("Autopilot Nav");
ImGui::TimedTooltip::TextMD("Arms **LNAV** mode. *Requires active GPS waypoint.*");
```

> **TIP**
>
> **Forgiving Aliases:** Prefer explicit sub-namespaces? **`ImGui::TimedTooltip::Markdown::Text(...)`** and **`ImGui::TimedTooltip::MD::Text(...)`** work too! If you prefer flipping the order (**`ImGui::Markdown::TimedTooltip::Text`**), that works identically. Clickable links inside tooltips are supported via **`TextMDLink(...)`**.

Configuration (**`ImGui::TimedTooltip::Config`**)

The **`TooltipConfig`** (aliased as **`ImGui::TimedTooltip::Config`**) controls timing, dimensions, typography, and colors.

Configuration Fields Reference

Field	Type	Default	Description
`hover_delay_cycles`	`int`	`65`	Frame cycles the mouse must hover before the tooltip appears (~1.0s at 60fps).

Field	Type	Default	Description
`max_display_cycles`	`int`	`504`	Frame cycles before the tooltip auto-dismisses. Set negative to disable auto-hide.
`grace_period_cycles`	`int`	`12`	Allowable frame cycles off the widget before cancelling hover state.
`size_skew_multiplier`	`float`	`0.5f`	Extra cycles added to display timeout per pixel of vertical height.
`enable_wiggle_latch`	`bool`	`true`	When `true`, subtle mouse movements inside the tooltip reset the dismiss timer.
`default_wrap_width`	`float`	`360.0f`	Target comfortable sticky-note width (~50-60 chars). Short text shrink-wraps tightly to its natural size.
`min_wrap_width`	`float`	`240.0f`	Minimum width boundary before forced truncation/overflow.
`max_wrap_width`	`float`	`600.0f`	Maximum width ceiling for wide documentation/manuals.
`padding`	`ImVec2`	`(8.0f, 6.0f)`	Internal window padding around the tooltip contents.
`item_spacing`	`ImVec2`	`(4.0f, 0.0f)`	Item spacing between lines. `y = 0.0f` matches native font leading.
`frame_padding`	`ImVec2`	`(2.0f, 1.0f)`	Internal padding for frame elements inside the tooltip.
`indent_spacing`	`float`	`20.0f`	Standard indent spacing between nested list levels.
`bullet_spacing`	`float`	`4.0f`	**[Markdown Tooltips Only]** Gap in pixels between bullet glyph and following text when rendering rich lists via `TextMD`. (Ignored for plain-text tooltips.)
`font_scale`	`float`	`0.0f`	Window font scale multiplier (`0.0f` = automatically inherit the ambient font scale from the calling parent window; `>0.0f` = explicit scale override).
`bg_color`	`ImVec4`	Solid yellow	Window and popup background color (`#FFF299`, 100% opaque `alpha = 1.0f`).
`border_color`	`ImVec4`	Dark yellow	Tooltip border outline color (`#CCBF66`).
`text_color`	`ImVec4`	Jet black	Tooltip text and separator color (`#000000`).

NOTE

Resolution-Independent Base Dimensions: All dimensional settings (`default_wrap_width`, `min_wrap_width`, `max_wrap_width`, `padding`, `item_spacing`, `frame_padding`, and `indent_spacing`) are defined in **base design boxels** (at 1.0× baseline). The tooltip engine resolves the active ambient scale (`ImGui::GetFontSize() / 14.0f` or explicit `font_scale`) and automatically scales constraints and padding dynamically. Callers do not need to manually multiply configuration values by font zoom factors.

Usage Patterns: Global Setup vs. Per-Call Overrides

Pattern A: Global Setup (Once at Plugin Startup)

For 95% of use cases, configure your desired tooltip personality once during plugin startup or window creation:

```
[CPP]
// In your plugin initialization:
static ImGui::TimedTooltip::Config s_MyTooltipConfig;
s_MyTooltipConfig.hover_delay_cycles = 45;                          // Snappier hover delay
s_MyTooltipConfig.padding            = ImVec2(8.0f, 6.0f);          // Compact padding
s_MyTooltipConfig.item_spacing       = ImVec2(4.0f, 0.0f);          // Tight line pitch
s_MyTooltipConfig.bg_color           = ImVec4(1.0f, 0.95f, 0.6f, 1.0f); // 100% opaque sticky note

ImGui::TimedTooltip::SetDefaultTooltipConfig(&amp;s_MyTooltipConfig);
```

Every subsequent call to **`ImGui::TimedTooltip::Text(...)`** and **`ImGui::TimedTooltip::TextMD(...)`** will automatically use this configuration without needing any per-call arguments.

Pattern B: Per-Call Override (Instant & Dynamic)

If a specific widget needs unique styling—for example, a wider maximum width, distinct background color, or custom padding—you can fetch a copy of the active configuration using **`ImGui::TimedTooltip::GetConfig()`**, tweak the desired fields, and pass it directly to **`Text`** or **`TextMD`**:

```
[CPP]
// Safely copies the active global config (or built-in defaults if no global config was set):
ImGui::TimedTooltip::Config wideConfig = ImGui::TimedTooltip::GetConfig();
wideConfig.max_wrap_width = 800.0f;                       // Allow wider manual formatting
wideConfig.bg_color       = ImVec4(0.15f, 0.15f, 0.20f, 0.95f); // Dark HUD styling
wideConfig.text_color     = ImVec4(1.0f, 1.0f, 1.0f, 1.0f);

ImGui::Button("System Diagnostics");
// Pass custom configuration directly:
ImGui::TimedTooltip::TextMD(&amp;wideConfig, "### System Status\n* Bus 1: **Normal**\n* Bus 2: **Normal**")
```

Pattern C: Low-Level Custom Layout Blocks

For completely custom tooltip content containing arbitrary ImGui widgets, use **`BeginStationaryTooltip`** and **`EndStationaryTooltip`**:

```
[CPP]
ImGui::Button("Engine Monitor");
if (ImGui::TimedTooltip::BeginStationaryTooltip("EngineMonitorTooltip")) {
    ImGui::Text("EGT: 640 C");
    ImGui::ProgressBar(0.75f, ImVec2(150, 15));
    ImGui::TimedTooltip::EndStationaryTooltip("EngineMonitorTooltip");
}
```

Hermetic Style Isolation

In Dear ImGui, child windows and popups can inadvertently inherit active layout styles from their parent windows. If an outer menu bar or custom toolbar has set **`ItemSpacing.x = 0.0f`** or compressed **`FramePadding`** to pack buttons tightly, standard tooltips would inherit those distorted spacing values.

`TimedTooltip` isolates itself completely:

1. When opening a tooltip proxy, **`BeginStationaryTooltipProxy`** pushes:

- **`ImGuiStyleVar_WindowPadding`** (**`config->padding`**)

- `ImGuiStyleVar_ItemSpacing` (`config->item_spacing`)
- `ImGuiStyleVar_FramePadding` (`config->frame_padding`)
- `ImGuiStyleVar_IndentSpacing` (`config->indent_spacing`)

2. When closing, `EndStationaryTooltip` pops all four style variables in exact reverse order.

This guarantees that:

- **No outer window hacks leak inward:** Tooltips always render with crisp, predictable typography regardless of what the calling window modified.
- **No tooltip styles leak outward:** Calling windows retain their exact style state without needing defensive push/pop blocks.

Screen Clamping & Docking

Tooltips automatically check the active display dimensions (`ImGui::GetIO().DisplaySize`):

- **Bottom Edge Protection:** If `render_pos.y + height` exceeds the screen floor, the anchor position automatically shifts upward so the entire tooltip remains visible on screen.
- **Right Edge Protection:** If `render_pos.x + width` exceeds the screen edge, the tooltip shifts leftwards to keep all content in view.

Click Forwarding & Automatic Dismissal

Tooltips attached to interactive or proxy-instrumented widgets (like `ButtonLink`, chevron menus, or `TextProxy` / `TextMDProxy` items) automatically intercept clicks via `ImGui::IsItemClicked()`:

- **Immediate Dismissal:** Clicking an active widget immediately dismisses the active tooltip, preventing tooltips from lingering over open menus or blocking post-click interactions.
- **Toggle on Idle Click:** Clicking an idle/non-actionable widget (such as a dimmed reset button or standalone info link) cleanly toggles the explanation tooltip on/off.

X-Plane 12 Panel Graphics (Linear Blending & Font Scaling)

1. 100% Solid Opacity (`alpha = 1.0f`)

In legacy OpenGL, plugins composited in uncorrected gamma space, where semi-transparent yellow cards (`alpha = 0.95f`) appeared largely solid.

In X-Plane 12's modern **Panel Graphics** pipeline (Metal on macOS, Vulkan on Windows/Linux), compositing is computed in **physically linear color space**. Even a minor 5% transparency allows intense runway lights, aircraft labels, and bright background elements to illuminate the pixels under dark text. Furthermore, linear antialiasing blends 50% edge coverage at $\approx 73\%$ background luminance ($(0.5)^{1/2.2} \approx 0.73$), optically eroding dark letter stems.

To ensure crisp, dark typography without background wash-out, `TooltipConfig::bg_color` defaults to `1.0f` **solid opacity** (`ImVec4(1.0f, 0.95f, 0.6f, 1.0f)`).

2. Automatic Ambient Font Scale Inheritance

When `TooltipConfig::font_scale` is left at `0.0f` (the default), the tooltip engine automatically queries and inherits the ambient window font scale of the calling widget:

- **Custom Window Zoom:** If a child window or floating palette is zoomed to 124%, hovering a widget inside that window renders the tooltip scaled at that exact same 124% factor.

- **Accessibility / Senior Citizen Mode:** If a global or per-window 17pt font mode is active, the tooltip inherits the enlarged scale seamlessly.
- **Pre-Calculation Accuracy:** The 2-pass size pre-calculator (**`MD::CalcMarkdownSize`**) computes wrap boundaries and vertical heights using this exact inherited scale factor, guaranteeing zero text clipping and zero scrollbar flutter.

API Summary

```
[CPP]
namespace ImGui {
    namespace TimedTooltip {
        // High-level Plain Text (auto-wraps to TooltipConfig bounds; returns true when displayed):
        bool Text(const char* fmt, ...);
        bool Text(const TooltipConfig* config, const char* fmt, ...);
        bool Text(const std::string&amp; text, const TooltipConfig* config = nullptr);

        // Single-line / Non-Wrapping Plain Text (mirrors ImGui::TextUnformatted):
        bool TextUnformatted(const char* text, const char* text_end = nullptr, const TooltipConfig* config
        bool TextUnformatted(const std::string&amp; text, const TooltipConfig* config = nullptr);

        // High-level Plain Text Proxy (explicit ID and hover state):
        bool TextProxy(ImGuiID id, bool is_hovered, const char* fmt, ...);
        bool TextProxy(ImGuiID id, bool is_hovered, const TooltipConfig* config, const char* fmt, ...);
        bool TextProxy(ImGuiID id, bool is_hovered, const std::string&amp; text, const TooltipConfig* confi
        bool TextProxy(const char* str_id, bool is_hovered, const char* fmt, ...);
        bool TextProxy(const char* str_id, bool is_hovered, const std::string&amp; text, const TooltipConfi
        bool TextUnformattedProxy(ImGuiID id, bool is_hovered, const char* text, const char* text_end = nul

        // High-level Markdown (requires imgui_markdown_ext.h in either include order; returns true when di

        bool TextMD(const char* fmt, ...);
        bool TextMD(const TooltipConfig* config, const char* fmt, ...);
        bool TextMD(const std::string&amp; markdown_text, const TooltipConfig* config = nullptr);

        // Single-line / Non-Wrapping Markdown (never wraps unless \n or PushTextWrapPos is active):
        bool TextUnformattedMD(const char* text, const char* text_end = nullptr, const TooltipConfig* confi
        bool TextUnformattedMD(const std::string&amp; markdown_text, const TooltipConfig* config = nullptr)

        // High-level Markdown Proxy (explicit ID and hover state):
        bool TextMDProxy(ImGuiID id, bool is_hovered, const char* fmt, ...);
        bool TextMDProxy(ImGuiID id, bool is_hovered, const TooltipConfig* config, const char* fmt, ...);
        bool TextMDProxy(const char* str_id, bool is_hovered, const char* fmt, ...);
        bool TextMDProxy(ImGuiID id, bool is_hovered, const std::string&amp; markdown_text, const TooltipCo
        bool TextMDProxy(const char* str_id, bool is_hovered, const std::string&amp; markdown_text, const T
        bool TextUnformattedMDProxy(ImGuiID id, bool is_hovered, const char* text, const char* text_end = n

        // Explicitly opt the preceding widget into click-to-toggle tooltip behavior for the current frame:
        void ToggleOnClick(bool enable = true);

        // Configuration:

        using Config = TooltipConfig;
        using State  = TooltipState;
        void SetDefaultTooltipConfig(const Config* config);
        const Config*&amp; GetDefaultTooltipConfig();
        const Config&amp; GetCurrentTooltipConfig();
        Config GetConfig();

        // Low-level lifecycle controls:
        bool BeginStationaryTooltipProxy(ImGuiID id, bool is_hovered, const Config* cfg = nullptr);
        bool BeginStationaryTooltip(ImGuiID id, const Config* cfg = nullptr);
        bool BeginStationaryTooltip(const char* str_id, const Config* cfg = nullptr);
        void EndStationaryTooltip(ImGuiID id);
        void EndStationaryTooltip(const char* str_id);
        void ClearActiveTooltip();
    }
}
```