

Understanding SCSS/CSS Properties and Values

SCSS/CSS

SCSS (Sassy CSS) is a way to style your website by controlling colors, fonts, spacing, and layout. This brief tutorial describes some key properties and their descriptions. SCSS files have extension `.scss` and can be saved in `styles/` of your project repo to be referenced by your `_quarto.yml` file. When you open `.scss` files in RStudio, you will see the hexadecimal color code and can adjust accordingly.

Basic Structure

CSS rules follow this pattern:

```
selector {  
  property: value;  
}
```

The selector targets HTML elements, and the properties define how they look.

Selectors Used in Example

- `body`: targets the whole page
- `.navbar`: targets elements with `class="navbar"`
- `.navbar a`: targets `<a>` tags inside navbar elements
- `a:hover`: special state when hovering over links
- `footer, pre`: targets specific HTML elements

Selector Explanations

body: Targets the entire webpage content

```
body {  
  background-color: #FFFFFF;  
  color: #121212;  
  font-family: Arial, sans-serif;  
  line-height: 1.6;  
  margin: 0;  
  padding: 0;  
}
```

Properties:

- background-color: background for the whole page
- color: text color
- font-family: font type
- line-height: space between lines of text
- margin: 0: spacing around page edges
- padding: 0: internal spacing

.navbar a: Styles all links (<a> tags) inside elements with class "navbar"

```
.navbar a {
  color: #6610f2;
  text-decoration: none;
  padding: 5px 10px;
}
```

Properties:

- color: link color
- text-decoration: styles underlines from links
- padding: left/right spacing around links

.navbar a:hover: Styles links when you hover your mouse over them

```
.navbar a:hover {
  color: #FFD700;
  text-decoration: underline;
}
```

Properties:

- color: color change on hover
- text-decoration: underline behavior when hovering

footer: Styles the footer element at the bottom of pages

```
footer {
  background-color: #50fa7b;
  color: #FFFFFF;
  padding: 10px 20px;
  text-align: center;
  position: fixed;
  width: 100%;
  bottom: 0;
  border-top: 2px solid #121212;
}
```

Properties:

- **background-color**: background color
- **color**: font color
- **padding**: spacing inside the footer
- **text-align**: text position
- **position**: footer visibility when scrolling
- **width**: manages width of screen
- **bottom**: positions at bottom of viewport
- **border-top**: border along top edge

pre: Styles pre-formatted text blocks

```
pre {  
  background-color: #1E1E1E;  
  border-color: #121212;  
  border-width: 1px;  
  border-style: solid;  
  padding: 10px;  
  overflow-x: auto;  
}
```

Properties:

- **background-color**: background color
- **border-***: border around the block
- **padding**: inner spacing
- **overflow-x**: manages horizontal scrollbar for long lines