

Module Interface Specification for STEM Moiré GPA

Alexandre Pofelski
macid: pofelska
github: slimpotatoes

November 18, 2017

1 Revision History

Date	Version	Notes
14/11/2017	1.0	First draft

2 Symbols, Abbreviations and Acronyms

The same Symbols, Abbreviations and Acronyms as in the SRS, the TestPlan and the MG (available in [STEM Moiré GPA](#) repository) are used in the Module Interface Specifications document.

addition to document

Contents

1	Revision History	i
2	Symbols, Abbreviations and Acronyms	ii
3	Introduction	1
4	Notation	1
5	Module Decomposition	1
6	MIS of STEM Moiré GPA Control Module (M 2)	3
6.1	Module	3
6.2	Uses	3
6.3	Syntax	3
6.3.1	Exported Access Programs	3
6.4	Semantics	3
6.4.1	State Variables	3
6.4.2	Access Routine Semantics	3
7	MIS of STEM Moiré GPA GUI Module (M 3)	4
7.1	Module	4
7.2	Uses	4
7.3	Syntax	4
7.3.1	Exported Access Programs	4
7.4	Semantics	4
7.4.1	State Variables	4
7.4.2	Access Routine Semantics	5
8	MIS of Input Module (M 4)	5
8.1	Module	5
8.2	Uses	6
8.3	Syntax	6
8.3.1	Exported Access Programs	6
8.4	Semantics	6
8.4.1	State Variables	6
8.4.2	Access Routine Semantics	7
9	MIS of SMH Simulation (M 5)	7
9.1	Module	7
9.2	Uses	7
9.3	Syntax	7
9.3.1	Exported Access Programs	7

9.4	Semantics	7
9.4.1	State Variables	7
9.4.2	Access Routine Semantics	8
10	MIS of GPA Module (M 6)	8
10.1	Module	8
10.2	Uses	8
10.3	Syntax	8
10.3.1	Exported Access Programs	8
10.4	Semantics	9
10.4.1	State Variables	9
10.4.2	Access Routine Semantics	9
11	MIS of Mask Module (M 7)	9
11.1	Module	9
11.2	Uses	9
11.3	Syntax	9
11.3.1	Exported Access Programs	9
11.4	Semantics	10
11.4.1	State Variables	10
11.4.2	Access Routine Semantics	10
12	MIS of Unstrained region (M 8)	10
12.1	Module	10
12.2	Uses	10
12.3	Syntax	10
12.3.1	Exported Access Programs	10
12.4	Semantics	11
12.4.1	State Variables	11
12.4.2	Access Routine Semantics	11
13	MIS of Conversion Module (M 9)	11
13.1	Module	11
13.2	Uses	11
13.3	Syntax	11
13.3.1	Exported Access Programs	11
13.4	Semantics	11
13.4.1	State Variables	11
13.4.2	Access Routine Semantics	11
14	MIS of 2D Strain Tensor Module (M 10)	12
14.1	Module	12
14.2	Uses	12

14.3	Syntax	12
14.3.1	Exported Access Programs	12
14.4	Semantics	12
14.4.1	State Variables	12
14.4.2	Access Routine Semantics	12
15	MIS of Fourier Transform Module (M 11)	12
15.1	Module	12
15.2	Uses	12
15.3	Syntax	13
15.3.1	Exported Access Programs	13
15.4	Semantics	13
15.4.1	State Variables	13
15.4.2	Access Routine Semantics	13
16	MIS of Gradient Module (M 12)	13
16.1	Module	13
16.2	Uses	14
16.3	Syntax	14
16.3.1	Exported Access Programs	14
16.4	Semantics	14
16.4.1	State Variables	14
16.4.2	Access Routine Semantics	14
17	MIS of Least Square Fit Method Module (M 13)	14
17.1	Module	14
17.2	Uses	14
17.3	Syntax	14
17.3.1	Exported Access Programs	14
17.4	Semantics	15
17.4.1	State Variables	15
17.4.2	Access Routine Semantics	15
18	MIS of Phase Operation Module (M 14)	15
18.1	Module	15
18.2	Uses	15
18.3	Syntax	15
18.3.1	Exported Access Programs	15
18.4	Semantics	15
18.4.1	State Variables	15
18.4.2	Access Routine Semantics	15

19 MIS of Data Structure Module (M 15)	16
19.1 Module	16
19.2 Uses	17
19.3 Syntax	17
19.3.1 Exported Access Programs	17
19.4 Semantics	17
19.4.1 State Variables	17
19.4.2 Access Routine Semantics	17
20 MIS of Generic GUI/Plot Module (M 16)	18
20.1 Module	18
20.2 Uses	18
20.3 Syntax	18
20.3.1 Exported Access Programs	18
20.4 Semantics	18
20.4.1 State Variables	18
20.4.2 Access Routine Semantics	18
21 Appendix	19

3 Introduction

The following document details the Module Interface Specifications for STEM Moiré GPA. The full documentation and implementation can be found in [STEM Moiré GPA](#) repository.

4 Notation

The structure of the MIS for modules comes from [?], with the addition that template modules have been adapted from [?]. The mathematical notation comes from Chapter 3 of [?]. For instance, the symbol $:=$ is used for a multiple assignment statement and conditional rules follow the form $(c_1 \Rightarrow r_1 | c_2 \Rightarrow r_2 | \dots | c_n \Rightarrow r_n)$.

The following table summarizes the primitive data types used by STEM Moiré GPA.

Data Type	Notation	Description
character	char	a single symbol or digit
integer	\mathbb{Z}	an integer number
natural number	\mathbb{N}	a natural number
real	\mathbb{R}	a real number

The specification of STEM Moiré GPA uses some derived data types: sequences, strings, and tuples. Sequences are lists filled with elements of the same data type. Strings are sequences of characters. Tuples contain a list of values, potentially of different types. In addition, STEM Moiré GPA uses functions, which are defined by the data types of their inputs and outputs. Local functions are described by giving their type signature followed by their specification.

5 Module Decomposition

The following table is taken directly from the Module Guide document for this project.

Level 1	Level 2
Hardware-Hiding Module	
	Input
	STEM Moiré GPA Control
	STEM Moiré GPA GUI
	User Input
Behaviour-Hiding Module	SMH simulation
	GPA
	Mask
	Unstrained region
	Conversion
	2D strain tensor
	Fourier Transform
	Least square fitting method
Software Decision Module	Phase calculation
	Gradient
	Generic GUI/Plot
	Data structure

Table 1: Module Hierarchy

LIST ALL MIS to refer them in other document

6 MIS of STEM Moiré GPA Control Module (M 2)

6.1 Module

main

6.2 Uses

- STEM Moiré GPA GUI
- Processing modules
 - Unstrained region
 - Conversion
 - SMH Simulation
 - GPA
 - 2D Strain Tensors
- Input

6.3 Syntax

6.3.1 Exported Access Programs

Name	In	Out	Exceptions
main	-	-	-

6.4 Semantics

STEM Moiré GPA is designed to have the different steps of the process flow driven by user directly through GUI_SMG. The STEM Moiré GPA Control Module uses the events in STEM Moiré GPA GUI to use the processing modules in the order defined by the user.

6.4.1 State Variables

6.4.2 Access Routine Semantics

main():

- transition: A reflexir
GUI(): *# Software permanently running until user abort by closing the GUI*
(event_Input()
→ Get the path pathISMH and pathIC from the user \wedge
load_files(pathISMH,pathIC))

```

(event_SimSMH() → SMHsim())
(event_GPA() → gpa())
(event_URef() → ZeroStrain())
(event_Conversion() → conversion())
(event_StrainCalc() → CalcStrain())

```

7 MIS of STEM Moiré GPA GUI Module (M 3)

7.1 Module

GUI_SMG

7.2 Uses

- Generic GUI/Plot
- Data Structure

7.3 Syntax

7.3.1 Exported Access Programs

Name	In	Out	Exceptions
GUI	-	-	-
event_Input()	-	-	-
event_SMHSim()	-	-	-
event_GPA()	-	-	-
event_URef()	-	-	-
event_StrainCalc()	-	-	-
GUI_Mask	-	-	-
GUI_U	-	-	-
GUI_nm	-	-	-

7.4 Semantics

STEM Moiré GPA process flow is driven by user through GUI_SMG. User triggers the events that start the selected processing step.

7.4.1 State Variables

Win_Flow: Window with the following buttons triggering events: button_Input, button_SMHSim, button_GPA, button_URef, button_StrainCalc.

Win_SMHSim: Window with areas to display $\tilde{I}_{SMH_{exp}}$ and $\tilde{I}_{SMH_{sim}}$

Win_Phase: Window with areas to display $\Delta \vec{g}^{M_{\text{exp}}}$ and let the user input the variable U

Win_FTSMH: Window with areas to display $\tilde{I}_{SMH_{\text{exp}}}$ and let the user input the variable.

Win_Conv: Window with entry field to get n and m from the user

7.4.2 Access Routine Semantics

GUI():

- transition: Win_Flow displayed

event_Input():

- transition: Trigger event_Input when button_Input pressed

event_SMHSim():

- transition: Trigger event_SMHSim when button_SMHSim pressed

event_GPA():

- transition: Trigger event_GPA when button_GPA pressed

event_URef():

- transition: Trigger event_URef when button_URef pressed

event_StrainCalc():

- transition: Trigger event_StrainCalc when button_StrainCalc press

event_GUI_Mask():

- transition: Trigger event_StrainCalc when button_StrainCalc press

event_GUI_U():

- transition: Trigger event_StrainCalc when button_StrainCalc press

event_GUI_nm():

- transition: Trigger event_StrainCalc when button_StrainCalc press

8 MIS of Input Module (M 4)

8.1 Module

Input

8.2 Uses

- STEM Moié GPA GUI
- Data Structure

8.3 Syntax

8.3.1 Exported Access Programs

Name	In	Out	Exceptions
load_files	string	-	FilePath
load_mask	GUI object	-	NoMask
load_U	GUI object	-	NoU
load_nm	GUI object	-	NoConv
$I_{SMH_{\text{exp}}}$	-	$f : \mathbb{N}^2 \rightarrow \mathbb{R}$	-
p	-	\mathbb{R}^{+*}	-
$I_{C_{\text{ref}}}$	-	$f : \mathbb{N}^2 \rightarrow \mathbb{R}$	-
p_{ref}	-	\mathbb{R}^{+*}	-
U	-	-	-
M	-	$(x_c, y_c) \in \mathbb{R}^2, R \in \mathbb{R}^{+*}$	-
n	-	\mathbb{Z}	-
m	-	\mathbb{Z}	-

8.4 Semantics

8.4.1 State Variables

For R 1 and IM 1 in the SRS document,

$$I_{SMH_{\text{exp}}} : f : \mathbb{N}^2 \rightarrow \mathbb{R}$$

$$p : \mathbb{R}^{+*}$$

$$I_{C_{\text{ref}}} : f : \mathbb{N}^2 \rightarrow \mathbb{R}$$

$$p_{\text{ref}} : \mathbb{R}^{+*}$$

For R 5 and IM 2 in the SRS document,

$$M : (x_c, y_c) \in \mathbb{R}^2, R \in \mathbb{R}^{+*}$$

For R 8 and IM 3 in the SRS document,

$$U :$$

For R 11 and For IM 4 in the SRS document,

$$n : \mathbb{Z}$$

$$m : \mathbb{Z}$$

8.4.2 Access Routine Semantics

load_files(pathISMH,pathIC):

- transition: pathISMH and pathIC are the file paths for the input files. The following procedure is performed:
 1. The .dm3 files are read and their respective metafiles are collected.
 2. From the metafile, $I_{SMH_{exp}}$, $I_{C_{ref}}$, p and p_{ref} are extracted to modify their respective state variable.
 - 3.
 4. The variables $I_{SMH_{exp}}$, $I_{C_{ref}}$, p and p_{ref} are stored in the data structure using the access program store
- output: $I_{SMH_{exp}}$, $I_{C_{ref}}$, p , p_{ref}
- exception:

9 MIS of SMH Simulation (M 5)

9.1 Module

SMHSimCalc

9.2 Uses

- Fourier Transform
- Input
- Data Structure

9.3 Syntax

9.3.1 Exported Access Programs

Name	In	Out	Exceptions
SMHsim	$I_{SMH_{exp}} : \mathbb{R}^2 \rightarrow \mathbb{R}$ $I_{C_{ref}} : \mathbb{R}^2 \rightarrow \mathbb{R}$, $p \in \mathbb{R}^{+*}$, $p_{ref} \in \mathbb{R}^{+*}$	$\tilde{I}_{SMH_{exp}} : \mathbb{R}^2 \rightarrow \mathbb{C}$ $\tilde{I}_{SMH_{sim}} : \mathbb{R}^2 \rightarrow \mathbb{C}$ $N_{lim} \in \mathbb{N}^*$	Nlim.zero()

9.4 Semantics

9.4.1 State Variables

None

9.4.2 Access Routine Semantics

$\text{SMHsim}(I_{SMH_{\text{exp}}}, I_{C_{\text{ref}}}, p, p_{\text{ref}})$:

- output:

– $\tilde{I}_{SMH_{\text{exp}}}$ such that

$$\tilde{I}_{SMH_{\text{exp}}}(\vec{v}) = \mathcal{FT}[I_{SMH_{\text{exp}}}(\vec{r})]$$

– $\tilde{I}_{SMH_{\text{sim}}}$ such that

$$\tilde{I}_{SMH_{\text{sim}}}(\vec{v}) = \frac{1}{p^2} \sum_{\vec{q} \in Q_{\text{lim}}} \mathcal{FT}[I_{C_{\text{ref}}}(\vec{v} - \frac{\vec{q}}{p})]$$

with $Q_{\text{lim}} = \{\forall(n, m) \in \mathbb{Z}^2 \cap [-N_{\text{lim}}, N_{\text{lim}}]^2, \vec{q} = n\vec{u}_x + m\vec{u}_y\}$

and $N_{\text{lim}} = \Xi(\frac{p}{p_{\text{ref}}})$ with Ξ the floor function

- exception:

10 MIS of GPA Module (M 6)

10.1 Module

GPACalc

10.2 Uses

- Mask
- Fourier Transform
- Phase
- Gradient
- Data Structure

10.3 Syntax

10.3.1 Exported Access Programs

Name	In	Out	Exceptions
gpa	$\tilde{I}_{SMH_{\text{exp}}} : \mathbb{R}^2 \rightarrow \mathbb{C}$, $M : \mathbb{R}^2 \rightarrow \mathbb{R}$, $\vec{g}_0 : \mathbb{R}^2 \rightarrow \mathbb{R}$	$P_{\vec{g}} : \mathbb{R}^2 \rightarrow \mathbb{R}$, $\vec{\Delta g} : \mathbb{R}^2 \rightarrow \mathbb{R}$	-

10.4 Semantics

10.4.1 State Variables

10.4.2 Access Routine Semantics

$\text{gpa}(\tilde{I}_{SMH_{\text{exp}}}, M, \vec{g}_0)$:

- output:

- $P_{\vec{g}}$ such that

$$\forall \vec{r} \in \mathbb{R}^2, P_{\vec{g}}(\vec{r}) = \arg(i\mathcal{FT}[M \times \tilde{I}_{SMH_{\text{exp}}}])$$

- $\vec{\Delta g}$ such that

$$\forall \vec{r} \in \mathbb{R}^2, \Delta \vec{g}(\vec{r}) = \frac{1}{2\pi} \text{grad}(\text{unwrap}(P_{\vec{g}}(\vec{r}))) - \vec{g}_0(\vec{r})$$

- $P_{\Delta \vec{g}}$ such that

$$\forall \vec{r} \in \mathbb{R}^2, P_{\Delta \vec{g}}(\vec{r}) = \text{wrap}(\text{unwrap}[P_{\vec{g}}(\vec{r})] - 2\pi \vec{g}_0(\vec{0}) \cdot \vec{r})$$

- exception:

11 MIS of Mask Module (M 7)

11.1 Module

Mask

11.2 Uses

- Input
- Data structure

11.3 Syntax

11.3.1 Exported Access Programs

Name	In	Out	Exceptions
MCirc	$(x_c, y_c) \in \mathbb{N}^2, R \in \mathbb{R}^{+*}$	$M : \mathbb{R}^2 \rightarrow \mathbb{R}, \vec{g}_0 : \mathbb{R}^2 \rightarrow \mathbb{R}^2$	-

11.4 Semantics

11.4.1 State Variables

11.4.2 Access Routine Semantics

MaskGene(x_c, y_c, R):

- output:

- M such that

$$M(x, y) = \begin{cases} 1, & (x - x_c)^2 + (y - y_c)^2 \leq R^2 \\ 0, & (x - x_c)^2 + (y - y_c)^2 > R^2 \end{cases}$$

- \vec{g}_0 such that

$$\forall \vec{r} \in \mathbb{R}^2, \vec{g}_0(\vec{r}) = \begin{bmatrix} x_c \\ y_c \end{bmatrix}$$

- exception:

12 MIS of Unstrained region (M 8)

12.1 Module

URefCalc

12.2 Uses

- Least Square Fit
- Input
- Data Structure

12.3 Syntax

12.3.1 Exported Access Programs

Name	In	Out	Exceptions
ZeroStrain	$\vec{\Delta g}^M : \mathbb{R}^2 \rightarrow \mathbb{R}^2, bla$	$\vec{\Delta g}^M : \mathbb{R}^2 \rightarrow \mathbb{R}^2$	-

12.4 Semantics

12.4.1 State Variables

12.4.2 Access Routine Semantics

$()$:

- transition:
- output:
- exception:

13 MIS of Conversion Module (M 9)

13.1 Module

MtoCConv

13.2 Uses

- Input
- Data Structure

13.3 Syntax

13.3.1 Exported Access Programs

Name	In	Out	Exceptions
conversion	$p \in \mathbb{R}$, $(n, m) \in \mathbb{N}^2$, $\vec{g}_{\text{uns}}^{M_{\text{exp}}} : \mathbb{R}^2 \rightarrow \mathbb{R}^2$	$\vec{g}_{j_{\text{uns}}}^{C_{\text{exp}}} : \mathbb{R}^2 \rightarrow \mathbb{R}^2$	-

13.4 Semantics

13.4.1 State Variables

13.4.2 Access Routine Semantics

conversion(p , $\vec{g}_{\text{uns}}^{M_{\text{exp}}}$):

- output: $\vec{g}_{\text{uns}}^{M_{\text{exp}}}$ such that

$$\forall \vec{r} \in \mathbb{R}^2, \vec{g}_{j_{\text{uns}}}^{C_{\text{exp}}}(\vec{r}) = \vec{g}_{j_{\text{uns}}}^{M_{\text{exp}}}(\vec{r}) + p \times \begin{bmatrix} n \\ m \end{bmatrix}$$

- exception:

14 MIS of 2D Strain Tensor Module (M 10)

14.1 Module

2D_Strain

14.2 Uses

Data Structure

14.3 Syntax

14.3.1 Exported Access Programs

Name	In	Out	Exceptions
CalcStrain	$g_{1_{\text{uns}}}^{C_{\text{exp}}} : \mathbb{R}^2 \rightarrow \mathbb{R}^2$, $g_{2_{\text{uns}}}^{C_{\text{exp}}} : \mathbb{R}^2 \rightarrow \mathbb{R}^2$, $\Delta g_{1_{\text{uns}}}^{C_{\text{exp}}} : \mathbb{R}^2 \rightarrow \mathbb{R}^2$, $\Delta g_{2_{\text{uns}}}^{C_{\text{exp}}} : \mathbb{R}^2 \rightarrow \mathbb{R}^2$	$T : \mathbb{R}^2 \rightarrow \mathbb{R}^4$	-

14.4 Semantics

14.4.1 State Variables

14.4.2 Access Routine Semantics

CalcStrain($g_{1_{\text{uns}}}^{C_{\text{exp}}}, g_{2_{\text{uns}}}^{C_{\text{exp}}}, \Delta g_{1_{\text{uns}}}^{C_{\text{exp}}}, \Delta g_{2_{\text{uns}}}^{C_{\text{exp}}}$):

- output:
- exception:

15 MIS of Fourier Transform Module (M 11)

2D Fourier transform

15.1 Module

FTCalc

15.2 Uses

Data Structure

15.3 Syntax

15.3.1 Exported Access Programs

Name	In	Out	Exceptions
\mathcal{FT}	$f : \mathbb{R}^2 \rightarrow \mathbb{R}$	$f : \mathbb{R}^2 \rightarrow \mathbb{C}$	-
$\text{i}\mathcal{FT}$	$f : \mathbb{R}^2 \rightarrow \mathbb{C}$	$f : \mathbb{R}^2 \rightarrow \mathbb{R}$	-

15.4 Semantics

15.4.1 State Variables

None

15.4.2 Access Routine Semantics

Calculate the 2D Fourier transform of a function f

$\mathcal{FT}(f(x, y))$:

- output: $\tilde{f}(\nu, \mu)$ such that

$$\forall(\nu, \mu) \in \mathbb{R}^2 \wedge \forall(x, y) \in \mathbb{R}^2, \tilde{f}(\nu, \mu) = \int_{-\infty}^{\infty} \int_{-\infty}^{\infty} f(x, y) e^{-2i\pi(\nu x + \mu y)} dx dy$$

- exception:

Calculate the 2D inverse Fourier transform of a function \tilde{f}

$\text{i}\mathcal{FT}(\tilde{f}(\nu, \mu))$:

- output: $f(x, y)$ such that

$$\forall(x, y) \in \mathbb{R}^2 \wedge \forall(\nu, \mu) \in \mathbb{R}^2, f(x, y) = \int_{-\infty}^{\infty} \int_{-\infty}^{\infty} \tilde{f}(\nu, \mu) e^{2i\pi(\nu x + \mu y)} dx dy$$

- exception:

16 MIS of Gradient Module (M 12)

2D Gradient

16.1 Module

GradCalc

16.2 Uses

Data Structure

16.3 Syntax

16.3.1 Exported Access Programs

Name	In	Out	Exceptions
grad	$f : \mathbb{R}^2 \rightarrow \mathbb{R}$	$f : \mathbb{R}^2 \rightarrow \mathbb{R}^2$	-

16.4 Semantics

16.4.1 State Variables

16.4.2 Access Routine Semantics

Calculate the gradient of a 2D function f

grad(*f*):

- output: $\nabla f(x, y)$ such that

$$\forall (x, y) \in \mathbb{R}^2, \nabla f(x, y) = \begin{bmatrix} \frac{\partial f}{\partial x}(x, y) \\ \frac{\partial f}{\partial y}(x, y) \end{bmatrix}$$

- exception:

17 MIS of Least Square Fit Method Module (M 13)

2D linear least square method to fit a function f

17.1 Module

LSFMCalc

17.2 Uses

Data Structure

17.3 Syntax

17.3.1 Exported Access Programs

Name	In	Out	Exceptions
lsfm	$f : \mathbb{R}^2 \rightarrow \mathbb{R}$	$f : \mathbb{R}^2 \rightarrow \mathbb{R}$	-

17.4 Semantics

17.4.1 State Variables

17.4.2 Access Routine Semantics

Calculate the 2D fit of a function f using the linear least square method on a domain $U = ([x_0, x_1]; [y_0, y_1]) \in \mathbb{R}^2$

lsfm(f,U):

- output: $fit(x, y) = ax + by$ such that

$$\begin{aligned} \forall (x, y) \in U, E(a, b) = \int_{x_0}^{x_1} \int_{y_0}^{y_1} [f(x, y) - fit(x, y)]^2 dx dy \text{ is minimized} \\ \Rightarrow \frac{\partial E}{\partial a} = 0 \wedge \frac{\partial E}{\partial b} = 0 \Rightarrow a = \frac{\int_{x_0}^{x_1} \int_{y_0}^{y_1} x f(x, y) dx dy}{\int_{x_0}^{x_1} \int_{y_0}^{y_1} x^2 dx dy} \wedge b = \frac{\int_{x_0}^{x_1} \int_{y_0}^{y_1} y f(x, y) dx dy}{\int_{x_0}^{x_1} \int_{y_0}^{y_1} y^2 dx dy} \end{aligned}$$

- exception:

18 MIS of Phase Operation Module (M 14)

18.1 Module

PhaseCalc

18.2 Uses

Data Structure

18.3 Syntax

18.3.1 Exported Access Programs

Name	In	Out	Exceptions
unwrap	$f : \mathbb{R}^2 \rightarrow] - \pi, \pi]$	$f : \mathbb{R}^2 \rightarrow \mathbb{R}$	-
wrap	$f : \mathbb{R}^2 \rightarrow \mathbb{R}$	$f : \mathbb{R}^2 \rightarrow] - \pi, \pi]$	-
arg	$z \in \mathbb{C}$	$\phi \in] - \pi, \pi]$	

18.4 Semantics

18.4.1 State Variables

18.4.2 Access Routine Semantics

wrap(f):

- output: g such that

$$\forall (x, y) \in \mathbb{R}^2, \exists k \in \mathbb{Z} | g(x, y) = f(x, y) + 2k\pi \wedge g(x, y) \in] - \pi, \pi]$$

- exception:

$\text{unwrap}(f)$:

- output: g such that

$$\begin{aligned} & \forall (x, y) \in \mathbb{R}^2, \exists k \in \mathbb{Z} | g(x, y) = f(x, y) + 2k\pi \wedge g \text{ is continuous} \\ \Rightarrow & \forall (x, y) \in \mathbb{R}^2, \exists k \in \mathbb{Z} | \lim_{(x, y) \rightarrow (x_0, y_0)} g(x, y) = g(x_0, y_0) = f(x_0, y_0) + 2k\pi \end{aligned}$$

- exception:

$\text{arg}(z)$:

- output: ϕ such that

$$\phi = \arg(z) = \text{atan2}(z) = \text{atan2}\left(\frac{\text{Im}(z)}{\text{Re}(z)}\right)$$

- exception:

19 MIS of Data Structure Module (M 15)

19.1 Module

DataStruct

19.2 Uses

19.3 Syntax

19.3.1 Exported Access Programs

Name	In	Out	Exceptions
store	-	-	-
read	-	-	-
load_FT_SMH_exp	datastruct	-	-
load_Δg_moire	datastruct	-	-
load_g_mask_moire	datastruct	-	-
load_g_uns_moire	datastruct	-	-
load_Δg_moire_cor	datastruct	-	-
$\tilde{I}_{SMH_{exp}}$	-	$f : \mathbb{N}^2 \rightarrow \mathbb{C}$	-
$\Delta \vec{g}^{M_{exp}}$	-	$f : \mathbb{N}^2 \rightarrow \mathbb{R}^2$	-
$\vec{g}^{M_{exp}}$	-	$f : \mathbb{N}^2 \rightarrow \mathbb{R}^2$	-
$\vec{g}_{uns}^{M_{exp}}$	-	$f : \mathbb{N}^2 \rightarrow \mathbb{R}^2$	-
$\Delta \vec{g}_{cor}^{M_{exp}}$	-	$f : \mathbb{N}^2 \rightarrow \mathbb{R}^2$	-
$\vec{g}_{exp}^{C_{exp}}$	-	$f : \mathbb{N}^2 \rightarrow \mathbb{R}^2$	-
$\vec{g}_{1uns}^{C_{exp}}$	-	$f : \mathbb{N}^2 \rightarrow \mathbb{R}^2$	-
$\vec{g}_{2uns}^{C_{exp}}$	-	$f : \mathbb{N}^2 \rightarrow \mathbb{R}^2$	-
$\Delta \vec{g}_{1uns}^{C_{exp}}$	-	$f : \mathbb{N}^2 \rightarrow \mathbb{R}^2$	-
$\Delta \vec{g}_{2uns}^{C_{exp}}$	-	$f : \mathbb{N}^2 \rightarrow \mathbb{R}^2$	-

19.4 Semantics

19.4.1 State Variables

bla
 $\tilde{I}_{SMH_{exp}} : f : \mathbb{N}^2 \rightarrow \mathbb{C}$
 $\Delta \vec{g}^{M_{exp}} : f : \mathbb{N}^2 \rightarrow \mathbb{R}^2$
 $\vec{g}^{M_{exp}} : f : \mathbb{N}^2 \rightarrow \mathbb{R}^2$
 $\vec{g}_{uns}^{M_{exp}} : f : \mathbb{N}^2 \rightarrow \mathbb{R}^2$
 $\Delta \vec{g}_{cor}^{M_{exp}} : f : \mathbb{N}^2 \rightarrow \mathbb{R}^2$
 $\vec{g}_{exp}^{C_{exp}} : f : \mathbb{N}^2 \rightarrow \mathbb{R}^2$
 $\vec{g}_{1uns}^{C_{exp}} : f : \mathbb{N}^2 \rightarrow \mathbb{R}^2$
 $\vec{g}_{2uns}^{C_{exp}} : f : \mathbb{N}^2 \rightarrow \mathbb{R}^2$
 $\Delta \vec{g}_{1uns}^{C_{exp}} : f : \mathbb{N}^2 \rightarrow \mathbb{R}^2$
 $\Delta \vec{g}_{2uns}^{C_{exp}} : f : \mathbb{N}^2 \rightarrow \mathbb{R}^2$

19.4.2 Access Routine Semantics

store():

- transition:
- output:
- exception:

20 MIS of Generic GUI/Plot Module (M 16)

20.1 Module

GUIGene

20.2 Uses

Hardware-Hiding Data Structure

20.3 Syntax

20.3.1 Exported Access Programs

Name	In	Out	Exceptions
	-	-	-

20.4 Semantics

20.4.1 State Variables

20.4.2 Access Routine Semantics

():

- transition:
- output:
- exception:

21 Appendix