


G-4153



## Green Pin® Dee Shackle BN

### Standard dee shackle with safety bolt

- **Material:** bow and pin high tensile steel, grade 6, quenched and tempered
- **Safety Factor:** MBL equals 6 x WLL
- **Standard:** ISO 2415, EN 13889, ASME B30.26 and meets performance requirements of US Fed. Spec. RR-C-271 Type IVB Class 3, grade A
- **Finish:** hot dipped galvanized
- **Temperature Range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC\* DNV 2.7-1\* DNV 2.7-1\* DNV 0378 CE IIA ABS PDA ABS MA
- **Article code:** scan QR code to see article codes

Scan for  
additional  
product  
details



| working<br>load<br>limit | diameter<br>bow | diameter<br>pin | diameter<br>eye | width<br>eye | width<br>inside | length<br>inside | length  | length<br>bolt | thickness<br>nut | weight<br>each |
|--------------------------|-----------------|-----------------|-----------------|--------------|-----------------|------------------|---------|----------------|------------------|----------------|
| t                        | a<br>mm         | b<br>mm         | c<br>mm         | d<br>mm      | e<br>mm         | f<br>mm          | g<br>mm | h<br>mm        | i<br>mm          | kg             |
| 2                        | 13.5            | 16              | 34              | 13           | 22              | 43               | 82      | 80             | 13               | 0.39           |
| 3.25                     | 16              | 19              | 40              | 16           | 27              | 51               | 97      | 98             | 17               | 0.67           |
| 4.75                     | 19              | 22              | 46              | 19           | 31              | 59               | 112     | 115            | 19               | 1.08           |
| 6.5                      | 22              | 25              | 52              | 22           | 36              | 73               | 134     | 130            | 22               | 1.66           |
| 8.5                      | 25              | 28              | 59              | 25           | 43              | 85               | 154     | 150            | 25               | 2.46           |
| 9.5                      | 28              | 32              | 67              | 28           | 47              | 90               | 168     | 166            | 27               | 3.40           |
| 12                       | 32              | 35              | 73              | 32           | 51              | 94               | 180     | 184            | 30               | 4.51           |
| 13.5                     | 35              | 38              | 79              | 35           | 57              | 115              | 209     | 197            | 33               | 6.10           |
| 17                       | 38              | 42              | 88              | 38           | 60              | 127              | 230     | 202            | 19               | 7.63           |
| 25                       | 45              | 50              | 104             | 45           | 74              | 149              | 271     | 243            | 23               | 12.9           |
| 35                       | 50              | 57              | 112             | 50           | 83              | 171              | 306     | 269            | 26               | 17.4           |
| 42.5                     | 57              | 65              | 132             | 57           | 95              | 190              | 346     | 301            | 29               | 25.9           |
| 55                       | 65              | 70              | 145             | 65           | 105             | 203              | 376     | 329            | 32               | 35.3           |
| 85                       | 75              | 83              | 167             | 75           | 127             | 229              | 429     | 381            | 39               | 53             |

CAD RFID INFO



\* For shackles  $\geq$  WLL 2 t