# Modeling of angle ply laminates using artificial neural network

Huiyao Zhang

12-10-2020

Kyoto Institue of Technology

#### Content

- 1. Neural Network
- 2. Genetic Algorithm
- 3. Classic Lamination Theory

#### 2. Neural Work





Figure 1: Neural Network Model

## 2. Genetic Algorithm



# 2. Classic Lamination Theory

$$\begin{array}{c} \theta \\ -\theta \\ \cdots \\ \theta \\ -\theta \end{array}$$

$$\begin{bmatrix} N_{x} \\ N_{y} \\ N_{xy} \end{bmatrix} = \begin{bmatrix} A_{11} & A_{12} & A_{16} \\ A_{12} & A_{22} & A_{26} \\ A_{16} & A_{26} & A_{66} \end{bmatrix} \begin{bmatrix} \varepsilon_{x}^{0} \\ \varepsilon_{y}^{0} \\ \gamma_{xy}^{0} \end{bmatrix} + \begin{bmatrix} B_{11} & B_{12} & B_{16} \\ B_{11} & B_{12} & B_{16} \\ B_{16} & B_{26} & B_{66} \end{bmatrix} \begin{bmatrix} k_{x} \\ k_{y} \\ k_{xy} \end{bmatrix}$$

$$\begin{bmatrix} M_{x} \\ M_{y} \\ M_{xy} \end{bmatrix} = \begin{bmatrix} B_{11} & B_{12} & B_{16} \\ B_{16} & B_{26} & B_{66} \end{bmatrix} \begin{bmatrix} k_{y} \\ k_{xy} \end{bmatrix}$$

$$= \begin{bmatrix} M_{x} \\ B_{12} & B_{12} & B_{16} \\ B_{12} & B_{22} & B_{26} \\ B_{16} & B_{26} & B_{66} \end{bmatrix} \begin{bmatrix} \varepsilon_{x}^{0} \\ \varepsilon_{y}^{0} \\ \gamma_{xy}^{0} \end{bmatrix}$$

$$+ \begin{bmatrix} D_{11} & D_{12} & D_{16} \\ D_{11} & D_{12} & D_{16} \\ D_{16} & D_{26} & D_{66} \end{bmatrix} \begin{bmatrix} k_{x} \\ k_{y} \\ k_{5} / 8 \end{bmatrix}$$

## 2. Methdology




Figure 4: Neural Network Model

# 3. Implementation: Data Preparation

Input			Output		
Load	Laminate Structure	Material Property	Failure Property	MS	Tsai-Wu
120,5,0	10,-10,8,1.27	38.6,8.27,0.26,4.14	1062.0,610.0,31,118,72	0.068	0.062
120,5,0	10,-10,2,1.27	38.6,8.27,0.26,4.14	1062.0,610.0,31,118,72	1.69	2.18
120,5,0	10,-10,134,1.27	38.6,8.27,0.26,4.14	1062.0,610.0,31,118,72	1.70	1.56
120,5,0	10,-10,8,1.27	181,10.3,0.28,7.17	1500.0,1500.0,40,246,68	0.072	0.024

## 4. Implementation: Neural Network

