



HALO:

High-efficiency Autonomous Low-SWaP Operations

Sloan Hatter, Blake Gisclair
Advisor: Dr. Ryan T. White

GOALS AND MOTIVATION

- Current orbital object detection uses Vision Transformer (ViT) neural networks on large computers.
 - This is ***unsustainable for satellites due to space and resource limits.***
 - Smaller devices like Raspberry Pis are better suited
- Typical downsizing method, called “pruning”, removes model layers
 - This ***reduces model size, but also accuracy.***
- Proposed solution: ***compress weights instead of removing layers.***
- Weights are stored as 32-bit floats (in C++)
- I hope to reduce them to 1-bit
 - Prior research has achieved a 1.58-bit representation for ViT.
- Objective: ***develop a true 1-bit quantization method for ViTs*** deployable on satellites to enable autonomous orbital object detection.

APPROACH

- **Accurate Object Detection**
 - The user will be able to detect and identify orbital objects within a given image space.
- **Low-SWaP Hardware Compatibility and Deployability**
 - The user will be able to send smaller, object-detection-capable computers into space that take up less space and resources.
- **Autonomous Operations Abilities**
 - The user will be able to run the computer vision model on satellite hardware and execute autonomous operations.

NOVEL FEATURES

- One-bit representations of weights have been restricted mainly to LLM transformers and have not been explored extensively for vision transformers and vision tasks, such as classification and segmentation.


ALGORITHMS AND TOOLS

- Python
- Jupyter Lab
- Multiple data sets:
 - Hardware In the Loop (HIL)
 - Web Satellite Data (WSD)
 - Digital Twin On-Demand Data
- Neural Networks and Vision Transformers (ViTs)
- Jetson AGX Orin Developer Kit


TECHNICAL CHALLENGES

- Maintaining accuracy as lower bit models are implemented
- Balancing power draw while still adhering to Low-SWaP parameters
- Ensuring the Jetson AGX Orin has the proper infrastructure to effectively run lower bit models

SYSTEM ARCHITECTURE DESIGN - JETSON AGX ORIN



NEURAL NETWORK ARCHITECTURE - VISUAL TRANSFORMER



EVALUATION

- Run Time
- Accuracy
- Power Draw

PROGRESS SUMMARY

Task	Completion	Sloan	To Do
Literature Review	100%	Research	None
Load ViT onto Raspberry Pi	100%	Interface with hardware	None
Hardware Swap	100%	Switch out Pi for Jetson	None
16-bit Representation	100%	Load 16-bit onto Jetson	None

MILESTONE 4

- Implement 8-bit model
- Record metrics for 8-bit model
- Demo 8-bit model
- Implement 4-bit model
- Record metrics for 4-bit model
- Demo 4-bit model

MILESTONE 5

- Implement 2-bit model
- Record metrics for 2-bit model
- Work towards implementing 1-bit model
- Record metrics throughout implementation and testing

MILESTONE 6

- Complete 1-bit model
- Record final metrics for 1-bit model
- Create demo video
- Create showcase poster

TASK VECTOR - MILESTONE 4

Task	Sloan
Implement 8-bit model	100%
Record metrics for 8-bit model	100%
Demo 8-bit model	100%
Implement 4-bit model	100%
Record metrics for 4-bit model	100%
Demo 4-bit model	100%



THANK YOU!
QUESTIONS?