

nRF51 Series Compatibility Matrix

Version 2.1

This document shows the compatibility between the nRF51422 and nRF51822 IC revisions, SDKs, the relevant SoftDevices with corresponding SoftDevice Specifications, and development kits.

This document will be updated on every new nRF51 IC revision release, and on every new release of the SDK or SoftDevice for the nRF51 Series IC.



Revision History

Date	Version	Description
May 2015	2.1	 Updated for SDK v8.1.0 and S130 v1.0 production version. Updated: Table 4 "IC revisions, SDK, and SoftDevice compatibility matrix" on page 6 Table 6 "Qualified Design ID matrix" on page 8
April 2015	2.0	Updated for S130 v1.0 Restructured <i>Table 4</i> , moved the Development HW content into a new <i>Table 5</i> "Development HW compatibility matrix" on page 7. Updated: • Front page, added text about update on every new SoftDevice release • <i>Table 4 "IC revisions, SDK, and SoftDevice compatibility matrix"</i> on page 6 • <i>Table 6 "Qualified Design ID matrix"</i> on page 8
March 2015	1.2	 Updated for SDK v8.0.0 Updated: Table 4 "IC revisions, SDK, and SoftDevice compatibility matrix" on page 6 Table 6 "Qualified Design ID matrix" on page 8
February 2015	1.1	Updated for SDK v7.2.0. Added: • Front page • Revision history Updated: • Table 4 "IC revisions, SDK, and SoftDevice compatibility matrix" on page 6 • Table 6 "Qualified Design ID matrix" on page 8
December 2014	1.0	First release, valid for SDK v7.1.0 and older.



nRF51422 IC revision overview

This table shows the packet and memory variants for each nRF51422 IC revision.

		Device markin					
nRF51422 IC revision	Packet/ Variant	Build code	HWID	Package	Flash [kB]	RAM [kB]	
	QF AA	CA	001E	QFN48			
1	QF AA	C0	0024	QFIV40	256	16	
	CE AA	A0A	0031	WLCSP			
	05.44	DAA	002D		256	16	
2	QF AA	Ex0 ^a	002E	QFN48			
2	QF AB	A00	0061		128	16	
	CE AA	Bx0 ^a	0050	WLCSP	256		
	QF AA	Fx0 ^a	0073		256	16	
	QF AB	Bx0 ^a	007C	QFN48	128	10	
3	QF AC ^b	Ax0 ^a	0085		256	32	
3	CD AB ^c	Ax0 ^a	007E		128	16	
	CE AA	Cx0 ^a	007A	WLCSP	256	10	
	CF AC ^b	Ax0 ^a	0088		256	32	

a. The x in the build code could be A..Z for engineering release, or 0..9 for production release. (HWID is given for x = 0, if $X \neq 0$ the HWID will be different).

Table 1 nRF51422 IC revision overview

b. New chip variant with 256 kB FLASH/32 kB RAM.

c. New packet variant of the 128 kB FLASH/16 kB RAM variant.



nRF51822 IC revision overview

This table shows the packet and memory variants for each nRF51822 IC revision.

		Device markin	g				
nRF51822 IC revision	Packet/ Variant	Build code	HWID	Package	Flash [kB]	RAM [kB]	
	QF AA	CA	001D		256		
	QIAA	C0	001D	QFN48	250		
1	QF AB	AA	0026	QIIV	128	16	
'	QI AD	A0	0027		120		
	CE AA	ВА	0020	WLCSP	256		
	CLAA	В0	002F	WECSI	230		
	QF AA	FA0	002A	QFN48	256		
		GC0	0044				
		Gx0 ^a	003C				
2	QF AB	Bx0 ^a	004C		128	16	
	CE AA	CA0	0040		256		
		DA0	0047	WLCSP			
		Dx0 ^a	004D				
	QF AA	Hx0 ^a	0072		256	- 16	
	QF AB	Cx0 ^a	007B	QFN48	128	10	
3	QF AC ^b	Ax0 ^a	0083		256	32	
	CD AB ^c	Ax0 ^a	007D		128	- 16	
	CE AA	Ex0 ^a	0079	WLCSP	256	10	
	CF AC ^b	Ax0 ^a	0087		250	32	

a. The x in the build code could be A..Z for engineering release, or 0..9 for production release. (HWID is given for x = 0, if $X \ne 0$ the HWID will be different).

Table 2 nRF51822 IC revision overview

b. New chip variant with 256 kB FLASH/32 kB RAM.

c. New packet variant of the 128 kB FLASH/16 kB RAM variant.



nRF51422/nRF51822 documentation and reference design files overview

This table shows the relevant documentation for the nRF51422 and nRF51822 IC revisions.

			Reference design files				
nRF51 IC revision	Chip	Product Specification	Reference Manual	Product Anomaly Notice	Product Change Notification ^a	nRF51x22- QFAx-DF ^b	nRF51x22- CxAx-DF ^c
1	nRF51422	nRF51422 PS v1.2	~ DEE1 DM v.1.1	nRF51422-PAN v2.3			-
	nRF51822	nRF51822 PS v1.3	nRF51 RM v1.1	nRF51822-PAN v2.4		_	
2	nRF51422	nRF51422 PS v2.1	nRF51 RM v2.1	nRF51422-PAN v2.3	PCN-084 v1.0	2.4	1.2
2	nRF51822	nRF51822 PS v2.0	NKF3 I KIVI VZ. I	nRF51822-PAN v2.4	PCN-082 v1.0	2.4	1.3
3	nRF51422	nRF51422 PS v3.1	nRF51 RM v3.0	nRF51422-PAN v3.0	PCN-093 v1.1	2.4	1.3
3	nRF51822	nRF51822 PS v3.1	TIREST RIVI VS.U	nRF51822-PAN v3.0	PCN-092 v1.1	2.4	1.3

- a. The PCNs listed here describe HW changes that affects the chip features or behavior, see www.nordicsemi.com for a complete PCN listing.
- b. nRF51x22-QFAx-DF = nRF51x22 Reference Layout files for the QFN48 packet variants (Old Code: nRF51x22-DF).
- c. nRF51x22-CxAx-DF = nRF51x22 Reference Layout files for the WLCSP Package variants (Old Code: nRF51x22-CEAA-DF).

Table 3 Document and reference design files overview



nRF51422 and nRF51822 IC revisions compatibility with SDK and SoftDevices

Table 4 shows the compatibility between the nRF51422 and nRF51822 IC revisions, the relevant SoftDevices and their corresponding SoftDevice Specifications, and SDKs.

		SoftDevices									
		nRF51422/nRF51822						nRF51422			
nRF51	nRF51	S 1	S110 S120		S130		S210		S310		
IC rev.	SDK	SD	SDS	SD	SDS	SD	SDS	SD	SDS	SD	SDS
1	4.4.2	5.2.1 ^a	1.1	-	-	-	-	2.0.0 ^b	1.0	-	-
	4.4.2	5.2.1	1.1					3.0.0	1.2	-	-
	5.2.0	6.0.0 6.2.1	1.2	-	-	_		3.0.0	1.2	1.0.0	1.0
2	6.1.0	7.0.0 7.1.0	1.3	1.0.1	1.1		-	3.0.0	1.2	1.0.0	1.0
	-	8.0.0	2.0	2.0.0	2.1			4.0.1	2.0	2.0.1	2.0
	6.1.0					-	-	3.0.0	1.2	1.0.0	1.0
	7.0.1	7.1.0	1 2	1 0 1	1 1			4.0.1	2.0	-	-
	7.1.0	7.1.0	1.3	1.0.1	1.1	0.5.0-1 alpha	0.5	401	2.0	201	2.0
3	7.2.0					агрпа		4.0.1	2.0	2.0.1	2.0
	8.0.0	8.0.0	8.0.0 2.0	2.0.0	2.1	0.9.0-1 alpha	0.5	4.0.1	2.0	-	-
	8.1.0					1.0.0	1.0				

a. Valid for nRF51822 only.

Table 4 IC revisions, SDK, and SoftDevice compatibility matrix

b. Preprogrammed in factory.



nRF51422 and nRF51822 IC revisions compatibility with development HW

Table 5 shows the compatibility between the nRF51422 and nRF51822 IC revisions and development kits. When using the Master Control Panel, nRFgo Studio, or nRF51 Tools, use the latest available version.

		Development HW						
nRF51 IC rev.	Chip	nRF51x22 Evaluation Kit ^a	nRF51x22 Development Kit ^a	nRF51 Development Kit ^b	nRF51 Dongle ^b			
1	nRF51422	2.0	2.0					
'	nRF51822	1.0, 2.0	1.0, 2.0	_	-			
2	nRF51422	3.0.0	3.0.0					
2	nRF51822	2.1.0, 2.2.0	2.1.0, 2.2.0	-	-			
2	nRF51422		-	1.0.0	1.0.0			
3	nRF51822	-		1.0.0	1.0.0			

a. The nRF51422/nRF51822 Development and Evaluation kit is using the QFAA variant of the chip.

Table 5 Development HW compatibility matrix

b. The nRF51-DK and nRF51-Dongle is using the nRF51422-QFAC variant of the chip.



nRF51422 and nRF51822 *Bluetooth* low energy QD ID qualification matrix

This table shows you the Qualified Design ID (QD ID) that applies when you use different IC and SoftDevice combinations.

	nRF51422/nRF51822 QD IDs						
SoftDevice	QFAA/QFAB/QFAC	CEAA	CDAB	CFAC			
S110 v5.x.x	44505	49155	-	-			
S110 v6.x.x	51744	51745	-	-			
S110 v7.0.x	58616	58540	-	-			
S110 v7.1.x	62701	62702	62074	62000			
S110 v8.0.0	62791	62792	63874	63880			
S120 v1.x.x	56426	56425	-	-			
S120 v2.0.0	66453	66455	66456	66457			
S130 v1.0.0	68915	68916	68917	68918			
S310 v1.0.0 ^a	51744	51745	-	-			
S310 v2.0.x ^a	62791	62792	-	-			

a. The S310 SoftDevice is only valid for the nRF51422 IC.

Table 6 Qualified Design ID matrix