



רסומנטלס



STATEMENT

We have performed a comparative review of the Deployed Bytecode of the smart contracts identified below against the corresponding Uniswap V3 reference deployments on Ethereum Mainnet.

In addition, we reviewed certain on-chain configuration and administrative state of the reviewed UniswapV3Factory deployment relevant to pool fee-tier configuration and protocol-fee administration.

The review was conducted based on the on-chain state observed at Ethereum Mainnet block height 26,016,048.

CONTRACTS SUBJECT TO COMPARISON

Contract	Reviewed Deployment	Corresponding Uniswap V3 Deployment
UniswapV3Factory	0x00a38533c68327aBE0Cc265436e036066E2D6B38	0x1F98431c8aD98523631AE4a59f267346ea31F984
SwapRouter	0xd53bE749711E7DFf31F4940D42386310b23c4C1E	0xE592427A0AEce92De3Edee1F18E0157C05861564
QuoterV2	0xCC1c929D41106D78D798315AFfFEF6A832eDe90A	0x61fFE014bA17989E743c5F6cB21bF9697530B21e
NonfungiblePositionManager	0xDd2Bf86EFef5C67F16ca43FD2Db63bE63729987a	0xC36442b4a4522E871399CD717aBDD847Ab11FE88
TickLens	0x4a2C8e133Ae07Ced79254d2841Ce7Fd0bb674d8e	0xbfd8137f7d1516D3ea5cA83523914859ec47F573
UniswapInterfaceMulticall	0x4C1A523c249a6718D4C1fE86fD2C2530C81d976D	0x1F98415757620B543A52E61c46B32eB19261F984
Descriptor	0xEe6A57eC80ea46401049E92587E52f5Ec1c24785	0xEe6A57eC80ea46401049E92587E52f5Ec1c24785

SUMMARY OF DEPLOYED BYTECODE COMPARISON

Based on our comparison of the Deployed Bytecode, the reviewed contracts are consistent with their respective Uniswap V3 counterparts in terms of the executable contract logic represented by the deployed runtime bytecode, subject only to the deployment-specific modifications described below.

- **Byte-for-byte identical:**
TickLens, UniswapInterfaceMulticall, and Descriptor.
- **Differences limited solely to fork-required deployment-specific address constants:**

UniswapV3Factory, SwapRouter, QuoterV2, and NonfungiblePositionManager.

For *UniswapV3Factory*, *SwapRouter*, *QuoterV2*, and *NonfungiblePositionManager*, the identified differences in the Deployed Bytecode are confined exclusively to deployment-specific address constants required for the reviewed fork deployment. These differences reflect address substitutions required for the reviewed contracts to reference the corresponding addresses within the fork deployment, including, as applicable, the address of the deployed contract itself and/or the addresses of corresponding contracts within the fork deployment.

No other differences in the Deployed Bytecode were identified for these four contract pairs.

SUMMARY OF FACTORY CONFIGURATION

At Ethereum Mainnet block height 26,016,048, the reviewed UniswapV3Factory deployment (0x00a38533c68327aBE0Cc265436e036066E2D6B38) was configured with the following enabled fee amounts and corresponding tick spacing parameters:

Fee Tier	Tick Spacing	Fee Tier	Tick Spacing
100	1	12,000	240
500	10	13,000	260
1,000	20	14,000	280
2,000	40	15,000	300
3,000	60	16,000	320
4,000	80	17,000	340
5,000	100	18,000	360
6,000	120	19,000	380
7,000	140	20,000	400
8,000	160	30,000	600
9,000	180	40,000	800
10,000	200	50,000	1,000
11,000	220		

At Ethereum Mainnet block height 26,016,048, the owner of the reviewed UniswapV3Factory deployment was the zero address. Factory ownership had been transferred to the zero address through the transaction identified below:

0xa38a059cde03947573e4c9a5858ffecf076d3e4318a7c77d81659649c415635c

Under the reviewed Uniswap V3 contract logic, factory ownership controls owner-restricted administrative functions. Pool-level protocol-fee administration, including the ability to modify protocol-fee parameters and to collect protocol fees, is likewise restricted to the current owner of the corresponding factory.

Because the factory owner has been set to the zero address, no externally controlled account can satisfy these factory-owner authorization checks. Under the reviewed contract logic, ownership cannot be reassigned through the factory owner function, and the owner-restricted administrative functions are therefore no longer exercisable by an externally controlled account.

Accordingly, the reviewed deployment does not retain an administratively exercisable mechanism through which a protocol administrator can subsequently configure, modify, or collect protocol fees.

CONCLUSION

On the basis of the Deployed Bytecode comparison at Ethereum Mainnet block height 26,016,048, the reviewed deployments were found to contain the same executable contract logic as the corresponding Uniswap V3 reference deployments, except solely for the deployment-specific address substitutions identified above.

Where the Deployed Bytecode is not byte-for-byte identical, the identified differences are confined exclusively to address values required for the reviewed fork deployment. Apart from these necessary substitutions, no additional differences in the Deployed Bytecode were identified.

Separately, the reviewed UniswapV3Factory was configured with the expanded fee-tier set described herein and had its ownership set to the zero address. The fee-tier configuration is an on-chain state configuration and does not represent an additional Deployed Bytecode modification.

Accordingly, under the reviewed contract logic and factory ownership state, the deployment does not retain an administrator capable of enabling, modifying, or collecting protocol fees. Pool swap fees remain applicable according to the enabled fee tiers and are distinct from protocol fees.

SCOPE AND LIMITATION

This statement is limited to:

- the comparison of the Deployed Bytecode of the contract addresses identified above against the corresponding Uniswap V3 reference deployments;
- the specific on-chain fee-tier configuration and factory ownership state of the reviewed UniswapV3Factory; and
- the administrative consequences of the factory ownership state under the reviewed contract logic, in each case as observed or assessed with reference to Ethereum Mainnet block height 26,016,048.

Except for the specific on-chain state expressly identified above, this statement does not constitute an assessment or representation regarding source code provenance, constructor inputs except insofar as their effects are reflected in the Deployed Bytecode, unrelated contract storage state, initialization state, external dependencies, referenced third-party contracts, transaction history, economic performance, or any subsequent change in contract state or surrounding protocol configuration.

This statement does not independently enumerate or attest to the historical or current pool-level feeProtocol storage value of every pool created by the reviewed factory. The protocol-fee conclusion stated herein is limited to the absence of an administratively exercisable factory-owner path to set or collect protocol fees under the reviewed contract logic and ownership state.

The conclusions stated herein should therefore be understood solely within the scope of the Deployed Bytecode comparison and specific on-chain configuration review expressly described above.

This statement records the results of a technical comparison and limited on-chain configuration review and is not a smart contract audit report or an assurance opinion on matters outside the scope expressly stated herein.

SlowMist Team

20 September 2026



Official Website

www.slowmist.com



E-mail

team@slowmist.com



Twitter

[@SlowMist_Team](https://twitter.com/SlowMist_Team)



Github

<https://github.com/slowmist>