

Apply filters to SQL queries

Project description

In this project, SQL is used to filter and retrieve relevant data for cybersecurity investigations. By applying specific filters, I can identify suspicious login activity, isolate data from specific departments, and ensure efficient data management to enhance security measures.

Retrieve after hours failed login attempts

To investigate potential unauthorized access after working hours, I used SQL to filter login attempts based on the time of the attempt and the status of the login.

The login_time column in the log_in_attempts table contains information on when login attempts were made. Office hours end at '18:00'.

The success column in the log_in_attempts table contains values of TRUE or FALSE to indicate whether the login was successful. MySQL stores Boolean values as 1 for TRUE, and 0 for FALSE. This means that TRUE is represented as 1, and FALSE represented as 0 in the success column.

```
MariaDB [organization]> select *
-> from log_in_attempts
-> where login_time > '18:00' and success = 0;
```

event_id	username	login_date	login_time	country	ip_address	success
2	apatel	2022-05-10	20:27:27	CAN	192.168.205.12	0
18	pwashing	2022-05-11	19:28:50	US	192.168.66.142	0
20	tshah	2022-05-12	18:56:36	MEXICO	192.168.109.50	0
28	aestrada	2022-05-09	19:28:12	MEXICO	192.168.27.57	0
34	drosas	2022-05-11	21:02:04	US	192.168.45.93	0
42	cgriffin	2022-05-09	23:04:05	US	192.168.4.157	0
52	cjackson	2022-05-10	22:07:07	CAN	192.168.58.57	0
69	wjaffrey	2022-05-11	19:55:15	USA	192.168.100.17	0
82	abernard	2022-05-12	23:38:46	MEX	192.168.234.49	0
87	apatel	2022-05-08	22:38:31	CANADA	192.168.132.153	0
96	ivelasco	2022-05-09	22:36:36	CAN	192.168.84.194	0
104	asundara	2022-05-11	18:38:07	US	192.168.96.200	0
107	bisles	2022-05-12	20:25:57	USA	192.168.116.187	0
111	aestrada	2022-05-10	22:00:26	MEXICO	192.168.76.27	0
127	abellmas	2022-05-09	21:20:51	CANADA	192.168.70.122	0
131	bisles	2022-05-09	20:03:55	US	192.168.113.171	0
155	cgriffin	2022-05-12	22:18:42	USA	192.168.236.176	0
160	jclark	2022-05-10	20:49:00	CANADA	192.168.214.49	0
199	yappiah	2022-05-11	19:34:48	MEXICO	192.168.44.232	0

```
19 rows in set (0.147 sec)
```

Retrieve login attempts on specific dates

To review all login attempts that occurred on **2022-05-09** and **2022-05-08**, I was using the SQL WHERE clause with the OR operator to filter the login_date column for the specific dates. Here is the SQL query and an explanation of how it works:

This query will return all login attempts made on 2022-05-09 and 2022-05-08, providing the necessary information to investigate the suspicious event.

```
MariaDB [organization]> SELECT *  
-> FROM log_in_attempts  
-> WHERE login_date = '2022-05-09' OR login_date = '2022-05-08';
```

event_id	username	login_date	login_time	country	ip_address	success
1	jrafael	2022-05-09	04:56:27	CAN	192.168.243.140	1
3	dkot	2022-05-09	06:47:41	USA	192.168.151.162	1
4	dkot	2022-05-08	02:00:39	USA	192.168.178.71	0
8	bisles	2022-05-08	01:30:17	US	192.168.119.173	0
12	dkot	2022-05-08	09:11:34	USA	192.168.100.158	1
15	lyamamot	2022-05-09	17:17:26	USA	192.168.183.51	0
24	arusso	2022-05-09	06:49:39	MEXICO	192.168.171.192	1
25	sbaelish	2022-05-09	07:04:02	US	192.168.33.137	1
26	apatel	2022-05-08	17:27:00	CANADA	192.168.123.105	1
28	aestrada	2022-05-09	19:28:12	MEXICO	192.168.27.57	0
30	yappiah	2022-05-09	03:22:22	MEX	192.168.124.48	1
32	acook	2022-05-09	02:52:02	CANADA	192.168.142.239	0
36	asundara	2022-05-08	09:00:42	US	192.168.78.151	1
38	sbaelish	2022-05-09	14:40:01	USA	192.168.60.42	1
39	yappiah	2022-05-09	07:56:40	MEXICO	192.168.57.115	1
42	cgriffin	2022-05-09	23:04:05	US	192.168.4.157	0
43	mcouliba	2022-05-08	02:35:34	CANADA	192.168.16.208	0
44	daquino	2022-05-08	07:02:35	CANADA	192.168.168.144	0
47	dkot	2022-05-08	05:06:45	US	192.168.233.24	1
49	asundara	2022-05-08	14:00:01	US	192.168.173.213	0
53	nmason	2022-05-08	11:51:38	CAN	192.168.133.188	1
56	acook	2022-05-08	04:56:30	CAN	192.168.209.130	1
58	ivelasco	2022-05-09	17:20:54	CAN	192.168.57.162	0
61	dtanaka	2022-05-09	09:45:18	USA	192.168.98.221	1
65	aalonso	2022-05-09	23:42:12	MEX	192.168.52.37	1
66	aestrada	2022-05-08	21:58:32	MEX	192.168.67.223	1
67	abernard	2022-05-09	11:53:41	MEX	192.168.118.29	1
68	mrah	2022-05-08	17:16:13	US	192.168.42.248	1
70	tmitchel	2022-05-09	10:55:17	MEXICO	192.168.87.199	1
71	mcouliba	2022-05-09	06:57:42	CAN	192.168.55.169	0
72	alevitsk	2022-05-08	12:09:10	CANADA	192.168.139.176	1
79	abernard	2022-05-09	11:41:15	MEX	192.168.158.170	0
80	cjackson	2022-05-08	02:18:10	CANADA	192.168.33.140	1
83	lrodriqu	2022-05-08	08:10:23	USA	192.168.67.69	1
87	apatel	2022-05-08	22:38:31	CANADA	192.168.132.153	0
90	gesparza	2022-05-09	00:49:05	CANADA	192.168.87.201	0
92	pwashing	2022-05-08	00:36:12	US	192.168.247.219	0

Retrieve login attempts outside of Mexico

To find login attempts that did not originate from Mexico, you can use the NOT and LIKE operators with the matching pattern 'MEX%', which will filter out any logins where the country is either 'MEX' or 'MEXICO'. Here's the query and an explanation of how it works:

WHERE country NOT LIKE 'MEX%': This condition filters out login attempts where the country starts with 'MEX', which includes both 'MEX' and 'MEXICO'. The NOT LIKE ensures that only login attempts from countries other than Mexico are returned.

The pattern 'MEX%' matches any value that starts with 'MEX', and using NOT LIKE excludes those values. Therefore, this query will retrieve all login attempts that did not originate from Mexico.

```
MariaDB [organization]> SELECT *  
-> FROM log_in_attempts  
-> WHERE NOT country LIKE 'MEX%';
```

event_id	username	login_date	login_time	country	ip_address	success
1	jrafael	2022-05-09	04:56:27	CAN	192.168.243.140	1
2	apatel	2022-05-10	20:27:27	CAN	192.168.205.12	0
3	dkot	2022-05-09	06:47:41	USA	192.168.151.162	1
4	dkot	2022-05-08	02:00:39	USA	192.168.178.71	0
5	jrafael	2022-05-11	03:05:59	CANADA	192.168.86.232	0
7	eraab	2022-05-11	01:45:14	CAN	192.168.170.243	1
8	bisles	2022-05-08	01:30:17	US	192.168.119.173	0
10	jrafael	2022-05-12	09:33:19	CANADA	192.168.228.221	0
11	sgilmore	2022-05-11	10:16:29	CANADA	192.168.140.81	0
12	dkot	2022-05-08	09:11:34	USA	192.168.100.158	1
13	mrah	2022-05-11	09:29:34	USA	192.168.246.135	1
14	sbaelish	2022-05-10	10:20:18	US	192.168.16.99	1
15	lyamamot	2022-05-09	17:17:26	USA	192.168.183.51	0
16	mcouliba	2022-05-11	06:44:22	CAN	192.168.172.189	1
17	pwashing	2022-05-11	02:33:02	USA	192.168.81.89	1
18	pwashing	2022-05-11	19:28:50	US	192.168.66.142	0
19	jhill	2022-05-12	13:09:04	US	192.168.142.245	1
21	iuduike	2022-05-11	17:50:00	US	192.168.131.147	1
25	sbaelish	2022-05-09	07:04:02	US	192.168.33.137	1
26	apatel	2022-05-08	17:27:00	CANADA	192.168.123.105	1
29	bisles	2022-05-11	01:21:22	US	192.168.85.186	0
31	acook	2022-05-12	17:36:45	CANADA	192.168.58.232	0
32	acook	2022-05-09	02:52:02	CANADA	192.168.142.239	0
33	zbernal	2022-05-11	02:52:10	US	192.168.72.59	1
34	drosas	2022-05-11	21:02:04	US	192.168.45.93	0
36	asundara	2022-05-08	09:00:42	US	192.168.78.151	1
37	eraab	2022-05-10	06:03:41	CANADA	192.168.152.148	0
38	sbaelish	2022-05-09	14:40:01	USA	192.168.60.42	1

Retrieve employees in Marketing

To retrieve all employees in the Marketing department who are located in the East building, you can create a SQL query using the LIKE keyword to filter for office locations that start with "East-" and the WHERE clause to filter by department. Here's the query and an explanation of how it works:

AND office LIKE 'East-%': Further filters the results to include only those employees whose office is in the East building. The LIKE 'East-%' uses the wildcard % to match any office location that starts with "East-" and can be followed by any number of characters (e.g., East-170, East-320).

```
MariaDB [organization]> SELECT * FROM employees WHERE department = 'Marketing' AND office LIKE 'East%';
```

employee_id	device_id	username	department	office
1000	a320b137c219	elarson	Marketing	East-170
1052	a192b174c940	jdarosa	Marketing	East-195
1075	x573y883z772	fbautist	Marketing	East-267
1088	k865l965m233	rgosh	Marketing	East-157
1103	NULL	randerss	Marketing	East-460
1156	a184b775c707	dellery	Marketing	East-417
1163	h679i515j339	cwilliam	Marketing	East-216

```
7 rows in set (0.001 sec)
```

Retrieve employees in Finance or Sales

WHERE department = 'Finance': This condition filters the results to only include employees who work in the Finance department.

OR department = 'Sales': This condition adds an alternative option, where employees who work in the Sales department are also included. The OR operator ensures that employees from either the Finance or Sales departments are retrieved.

This query will return a list of all employees who belong to either the Finance or Sales department.

```
MariaDB [organization]> SELECT *  
-> FROM employees  
-> WHERE department = 'Finance' OR department = 'Sales';
```

employee_id	device_id	username	department	office
1003	d394e816f943	sgilmore	Finance	South-153
1007	h174i497j413	wjaffrey	Finance	North-406
1008	i858j583k571	abernard	Finance	South-170
1009	NULL	lrodriqu	Sales	South-134
1010	k242l212m542	jlsansky	Finance	South-109
1011	l748m120n401	drosas	Sales	South-292
1015	p611q262r945	jsoto	Finance	North-271
1017	r550s824t230	jclark	Finance	North-188
1018	s310t540u653	abellmas	Finance	North-403
1022	w237x430y567	arusso	Finance	West-465
1024	y976z753a267	iuduike	Sales	South-215
1025	z381a365b233	jhill	Sales	North-115
1029	d336e475f676	ivelasco	Finance	East-156
1035	j236k303l245	bisles	Sales	South-171
1039	n253o917p623	cjackson	Sales	East-378
1041	p929q222r778	cgriffin	Sales	North-208
1044	s429t157u159	tbarnes	Finance	West-415

Retrieve all employees not in IT

WHERE NOT department = 'Information Technology': This condition filters out employees whose department is 'Information Technology'. The NOT operator excludes any rows that match this department, meaning only employees from other departments will be returned.

This query will return all employees from departments **other than** Information Technology. It's useful when you need to focus on employees from different departments and exclude IT-specific staff.

```
MariaDB [organization]> SELECT *  
  -> FROM employees  
  -> WHERE NOT department = 'Information Technology';
```

employee_id	device_id	username	department	office
1000	a320b137c219	elarson	Marketing	East-170
1001	b239c825d303	bmoreno	Marketing	Central-276
1002	c116d593e558	tshah	Human Resources	North-434
1003	d394e816f943	sgilmore	Finance	South-153
1004	e218f877g788	eraab	Human Resources	South-127
1005	f551g340h864	gesparza	Human Resources	South-366
1007	h174i497j413	wjaffrey	Finance	North-406
1008	i858j583k571	abernard	Finance	South-170
1009	NULL	lrodriqu	Sales	South-134
1010	k242l212m542	jlansky	Finance	South-109
1011	l748m120n401	drosas	Sales	South-292
1015	p611q262r945	jsoto	Finance	North-271
1016	q793r736s288	sbaelish	Human Resources	North-229
1017	r550s824t230	jclark	Finance	North-188
1018	s310t540u653	abellmas	Finance	North-403
1020	u899v381w363	arutley	Marketing	South-351
1022	w237x430y567	arusso	Finance	West-465
1024	y976z753a267	iuduike	Sales	South-215
1025	z381a365b233	jhill	Sales	North-115
1026	a998b568c863	apatel	Human Resources	West-320

Summary

This project demonstrates how SQL can be used to apply various filters to extract meaningful data for cybersecurity purposes. From isolating failed login attempts to retrieving department-specific employee data, SQL provides a flexible and powerful tool for managing data in a security context. The queries in this project show practical examples of filtering login attempts by time, location, date, and department, all essential for effective cybersecurity analysis.