

SM-2302 Software for Mathematicians

R3: The tidyverse

Dr. Haziq Jamil

Mathematical Sciences, Faculty of Science, UBD

<https://haziqj.ml>

Semester I 2023/24

Preamble

```
# If not installed yet, install them first  
library(tidyverse)  
library(remotes)  
  
# This may require compilation  
remotes::install_github("rstudio/EDAWR")  
library(EDAWR) # to get the data sets: storms, cases, pollution, tb
```

Note that installing EDAWR package may require compilation. For Windows, check out Rtools42. For Macs, I think minimally you will need to install Xcode. Check out this link.

These slides were adapted from the following YouTube playlist.

- Data wrangling with R and the Tidyverse by Garrett Grolemund, RStudio.

I would recommend that you watch them, but note that the video is based on the old version of tidyverse packages, so some commands may be deprecated or superseded.

Learning objectives

- Spot the **variables** and **observations** within your data
 - Variables = Columns
 - Observations = Rows
- **Reshape** your data into the layout that works best for R
 - Long vs wide data sets
 - Long → wide using `pivot_wider()`
 - Wide → long using `pivot_longer()`
- *Quickly* derive new variables and observations to explore
 - `mutate()` or `summarise()` to add new variables or summarise data
 - `select()`, `filter()`, `slice()`, `arrange()` to focus and/or reveal information
- Perform **group-wise** summaries to explore hidden levels of information within your data
 - `group_by()`
- Join multiple data sets together
 - `left_join()`, `right_join()`, `inner_join()`, `full_join()`

The tidyverse package

The tidyverse is a collection of R packages designed for data science. We're most interested in the following packages:

1. `tibble`
A modern re-imagining of `data.frames`.
2. `tidyr`
Provides a set of functions that help you get to tidy data.
3. `dplyr`
Provides a set of verbs for data manipulation.



TL;DR—Use the cheat sheet!

Have a look at the Data Wrangling cheat sheet from RStudio.

Data Wrangling with dplyr and tidy Cheat Sheet



Syntax - Helpful conventions for wrangling

dplyr::tbl(iris)

Converts data to tbl class. tbl's are easier to examine than data frames. R displays only the data that fits onscreen:

```
Source: local data frame [136 x 5]
  Sepal.Length Sepal.Width Petal.Length
1           5.1           3.5           1.4
2           4.9           3.0           1.4
3           4.7           3.2           1.3
4           4.0           3.1           1.5
5           5.0           3.6           1.4
..          ...
Variables not shown: Petal.Width (dbl),
                     Species (factor)
```

dplyr::glimpse(iris)

Information dense summary of tbl data.

utils::View(iris)

View data set in spreadsheet-like display (note capital V).

```
iris %>% View
#> # A tibble: 136 x 5
#>   Sepal.Length Sepal.Width Petal.Length Species
#>   <dbl>         <dbl>         <dbl> <fctr>
#> 1     5.1         3.5           1.4 setosa
#> 2     4.9         3.0           1.4 setosa
#> 3     4.7         3.2           1.3 setosa
#> 4     4.0         3.1           1.5 setosa
#> 5     5.0         3.6           1.4 setosa
#> 6     5.4         3.9           1.7 setosa
#> 7     4.8         3.4           1.4 versicolour
#> 8     5.1         3.4           1.5 versicolour
```

dplyr::%>%

Passes object on left hand side as first argument (or . argument) of function on right hand side.

```
x %>% f(y) is the same as f(x, y)
y %>% f(x, ., z) is the same as f(x, y, z)
```

"Piping" with %>% makes code more readable, e.g.

```
iris %>%
  group_by(Species) %>%
  summarise(avg = mean(Sepal.Width)) %>%
  arrange(avg)
```

Tidy Data - A foundation for wrangling in R

In a tidy data set:

Each **variable** is saved in its own **column**

Each **observation** is saved in its own **row**

Tidy data complements R's **vectorized operations**. R will automatically preserve observations as you manipulate variables. No other format works as intuitively with R.

M * A → F
M * A

Reshaping Data - Change the layout of a data set

dplyr::gather(cases, "year", "n", 2:4)
Gather columns into rows.

tidyr::separate(storms, date, c("y", "m", "d"))
Separate one column into several.

dplyr::spread(pollution, size, amount)
Spread rows into columns.

tidyr::unite(data, col1, ..., sep)
Unite several columns into one.

dplyr::data_frame(a = 1:3, b = 4:6)
Combine vectors into data frame (optimized).

dplyr::arrange(mtcars, mpg)
Order rows by values of a column (low to high).

dplyr::arrange(mtcars, desc(mpg))
Order rows by values of a column (high to low).

dplyr::rename(tb, y = year)
Rename the columns of a data frame.

Subset Observations (Rows)

dplyr::filter(iris, Sepal.Length > 7)
Extract rows that meet logical criteria.

dplyr::distinct(iris)
Remove duplicate rows.

dplyr::sample_frac(iris, 0.5, replace = TRUE)
Randomly select fraction of rows.

dplyr::sample_n(iris, 10, replace = TRUE)
Randomly select n rows.

dplyr::slice(iris, 10:15)
Select rows by position.

dplyr::top_n(storms, 2, date)
Select and order top n entries (by group if grouped data).

Logic in R - ?Comparison, ?base-Logic			
<	Less than	!=	Not equal to
>	Greater than	%in%	Group membership
==	Equal to	is.na	Is NA
<=	Less than or equal to	is.na	Is not NA
>=	Greater than or equal to	isTRUE, isFALSE, isTRUE, isFALSE	Boolean operators

Subset Variables (Columns)

dplyr::select(iris, Sepal.Width, Petal.Length, Species)
Select columns by name or helper function.

Helper functions for select - ?select

select(iris, contains("l"))
Select columns whose name contains a character string.

select(iris, ends_with("Length"))
Select columns whose name ends with a character string.

select(iris, everything())
Select every column.

select(iris, matches("l"))
Select columns whose name matches a regular expression.

select(iris, num_range("x", 1:3))
Select columns named x1, x2, x3, x4, x5.

select(iris, one_of(c("Species", "Genus")))
Select columns whose names are in a group of names.

select(iris, starts_with("Sepal"))
Select columns whose name starts with a character string.

select(iris, Sepal.Length:Petal.Width)
Select all columns between Sepal.Length and Petal.Width (inclusive).

select(iris, -Species)
Select all columns except Species.

Tidy data

Data comes in various shapes and formats. It's important when you begin your analysis to identify this at the outset.

- What are the variables? How many of them are there?
- What are the observations? How many of them are there?

The goal is to reshape your data into a format that works best in R. The resulting format is called **tidy data**.

Let's have a look at three data sets:

1. `storms` (Wind speed data for six hurricanes)
2. `cases` (Data from the WHO Global Tuberculosis report)
3. `pollution` (Ambient air pollution from WHO)

1. storms data set

```
EDAWR::storms
```

```
##      storm wind pressure      date
## 1 Alberto  110      1007 2000-08-03
## 2   Alex   45      1009 1998-07-27
## 3 Allison  65      1005 1995-06-03
## 4    Ana   40      1013 1997-06-30
## 5  Arlene  50      1010 1999-06-11
## 6  Arthur  45      1010 1996-06-17
```

- Variables: storm, wind, pressure, date
- Observations: 1, 2, 3, 4, 5, 6
- Notice that
 - Each variable is represented by a single column
 - Each row is a single observation

storms

storm	wind	pressure	date
Alberto	110	1007	2000-08-12
Alex	45	1009	1998-07-30
Allison	65	1005	1995-06-04
Ana	40	1013	1997-07-01
Arlene	50	1010	1999-06-13
Arthur	45	1010	1996-06-21

Extracting data by subsetting easily:

- storms\$storm
- storms\$wind
- storms\$pressure
- storms\$date

2. cases data set

Wide format

```
EDAWR: : cases
```

```
##   country 2011 2012 2013
## 1      FR 7000 6900 7000
## 2      DE 5800 6000 6200
## 3      US 15000 14000 13000
```

- Variables: `country, year = c(2011, 2012, 2013), count`
- Observations: $3 \times 3 = 9$
- Notice that
 - Each cell of this data frame corresponds to the count for a given country and year



Extracting data by subsetting (not so easy):

- `cases$country`
- `colnames(cases)[-1]`
- `unlist(cases[1:3, 2:4])`

3. pollution data set

Long format

```
EDAWR::pollution
```

```
##      city size amount
## 1 New York large    23
## 2 New York small    14
## 3 London  large    22
## 4 London  small    16
## 5 Beijing large   121
## 6 Beijing small    56
```

- Variables: city, amount
- Observations: 1, 2, 3, 4, 5, 6
- Notice that
 - Amount of particles for each city is segregated into two groups: large and small.

pollution

city	particle size	amount ($\mu\text{g}/\text{m}^3$)
New York	large	23
New York	small	14
London	large	22
London	small	16
Beijing	large	121
Beijing	small	56

Extracting data by subsetting (hard):

- `pollution$city[c(1, 3, 5)]`
- `pollution$amount[c(1, 3, 5)]`
- `pollution$amount[c(2, 4, 6)]`

Tidy data

The defining characteristics of tidy data are:

Variables in columns, observations in rows, and each type in a table.

This makes variables easy to access and manipulate (while preserving observations).

country	year	cases	population
Afghanistan	1999	745	12257071
Afghanistan	2000	2666	20595360
Brazil	1999	3737	17206362
Brazil	2000	8488	174504898
China	1999	21258	1272015272
China	2000	21666	128042583

variables

country	year	cases	population
Afghanistan	1999	745	12257071
Afghanistan	2000	2666	20595360
Brazil	1999	3737	17206362
Brazil	2000	8488	174504898
China	1999	21258	1272015272
China	2000	21666	128042583

observations

country	year	cases	population
Afghanistan	1999	745	12257071
Afghanistan	2000	2666	20595360
Brazil	1999	3737	17206362
Brazil	2000	8488	174504898
China	1999	21258	1272015272
China	2000	21666	128042583

values

Tidy data

Getting tidy data

```
pivot_longer()  
pivot_wider()  
separate()  
unite()
```

Data wrangling

Pipeline

Group wrangling

Joining data sets

Getting tidy data

There are two main functions that we will use to reshape the layout of tables:


1. `pivot_wider()`
2. `pivot_longer()`

To a lesser degree, these utility functions may be useful too:

1. `separate()`
2. `unite()`

`pivot_longer()`

This converts data from wide format to long format. In the cases data set, ideally we want to have three columns only: country, year, and count; and each row will be an observation.



pivot_longer() (cont.)

```
cases
```

```
## Error in eval(expr, envir, enclos): obj
```

- Select which cols to pivot to longer format. Note that these have to be character vectors.
- `names_to` is the name of the new column to store the old columns
- `values_to` is the name of the new column to store the observations

```
pivot_longer(data = cases,  
             cols = c("2011", "2012", "2013"),  
             names_to = "year",  
             values_to = "count")
```

```
## Error in pivot_longer(data = cases, cols = c("20
```

`pivot_wider()`

This converts data from long format to wide format. In the `pollution` data set, we could instead have a table of city by particle size, and each cell is the amount.

`id_cols = "city"`

`names_from = "size"`

`values_from = "amount"`

city	size	amount
New York	large	23
New York	small	14
London	large	22
London	small	16
Beijing	large	121
Beijing	small	56

`pivot_wider()`



city	large	small
New York	23	14
London	22	16
Beijing	121	56

pivot_longer() (cont.)

```
pollution
```

```
## Error in eval(expr, envir, enclos): object 'pollutio
```

- Select which `id_cols` uniquely identifies each observation
- `names_from` is the name of the column to spread
- `values_from` is the name of column containing the observations

```
pivot_wider(data = pollution,  
            id_cols = "city",  
            names_from = "size",  
            values_from = "amount")
```

```
## Error in pivot_wider(data = pollutio
```


separate()

Turns a single character column into multiple columns.

```
storms

## # A tibble: 19,066 x 13
##   name    year month   day hour   lat  lon tropicalstorm force diameter <int>
##   <chr> <dbl> <dbl> <int> <dbl> <dbl> <dbl> <fct>          <dbl> <int>   <int>
## 1 Amy    1975     6    27     0  27.5 -79 tropical depres~ NA      25    1013
## 2 Amy    1975     6    27     6  28.5 -79 tropical depres~ NA      25    1013
## 3 Amy    1975     6    27    12  29.5 -79 tropical depres~ NA      25    1013
## 4 Amy    1975     6    27    18  30.5 -79 tropical depres~ NA      25    1013
## 5 Amy    1975     6    28     0  31.5 -78.8 tropical depres~ NA      25    1012
## 6 Amy    1975     6    28     6  32.4 -78.7 tropical depres~ NA      25    1012
## 7 Amy    1975     6    28    12  33.3 -78 tropical depres~ NA      25    1011
## 8 Amy    1975     6    28    18  34 -77 tropical depres~ NA      30    1006
## 9 Amy    1975     6    29     0  34.4 -75.8 tropical storm NA      35    1004
## 10 Amy   1975     6    29     6  34 -74.8 tropical storm NA      40    1002
## # i 19,056 more rows
## #> variables: tropicalstorm force diameter <int>,
```

```
separate(data = storms,
          col = "date",
          into = c("year", "month", "day"),
          sep = "-")
```

```
## Error in separate(): NA columns that don't exist.
## ! Can't extract columns that don't exist.
## x Column 'date' doesn't exist.
```

unite()

Paste together multiple columns into one.

```
## Error in `separate()`:  
## ! Can't extract columns that don't exist.  
## x Column `date` doesn't exist.
```

```
storms2
```

```
unite(data = storms2,  
      col = "date",  
        "year", "month", "day",  
        sep = "-")
```

```
## Error in eval(expr, envir, enclos): object 'storms2' not found  
## Error in unite(data = storms2, col = "date", "
```

Tidy data

Getting tidy data

Data wrangling

- `select()`

- `filter()`

- `slice()`

- `mutate()`

- `summarise()`

- `arrange()`

Pipeline

Group wrangling

Joining data sets

Data wrangling

Having obtained a tidy dataset, there are several ways to access information.

1. **Extract** existing variables (columns).
 - `select()`
2. **Extract** existing observations (rows).
 - `filter()` or `slice()`
3. **Derive** new variables (from existing variables).
 - `mutate()`
4. **Change** the unit of analysis.
 - `summarise()`

select()

Select variables in a data frame.

Before

```
storms
```

After

```
select(.data = storms, storm, pressure)
```

```
## # A tibble: 19,066 x 13
```

```
##   name   year month   day  hour   lat  long status category wind pressure
##   <chr> <dbl> <dbl> <int> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl>
## 1 Amy    1975     6    27     0  27.5 -79 tropical depres~ NA    25    1013
## 2 Amy    1975     6    27     6  28.5 -79 tropical depres~ NA    25    1013
## 3 Amy    1975     6    27    12  29.5 -79 tropical depres~ NA    25    1013
## 4 Amy    1975     6    27    18  30.5 -79 tropical depres~ NA    25    1013
## 5 Amy    1975     6    28     0  31.5 -78.8 tropical depres~ NA    25    1012
## 6 Amy    1975     6    28     6  32.4 -78.7 tropical depres~ NA    25    1012
## 7 Amy    1975     6    28    12  33.3 -78 tropical depres~ NA    25    1011
## 8 Amy    1975     6    28    18  34 -77 tropical depres~ NA    30    1006
## 9 Amy    1975     6    29     0  34.4 -75.8 tropical storm NA    35    1004
## 10 Amy   1975     6    29     6  34 -74.8 tropical storm NA    40    1002
## 18 / 53 0 6 more rows
```

```
## Error in `select()`:
## ! Can't subset columns that don't exist.
```

```
## ! Column `storm` doesn't exist.
```

```
## ! Column `storm` doesn't exist.
```

select(): Optionally rename

Optionally rename while selecting.

Before

```
storms
```

After

```
select(.data = storms, STORM = storm,  
       PRESSURE = pressure)
```

```
## # A tibble: 19,066 x 13
```

```
##   name    year month   day  hour   lat  long status category wind pressure  
##   <chr> <dbl> <dbl> <int> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl>  
## 1 Amy    1975     6    27     0  27.5 -79 tropical depress~ NA    25    1013  
## 2 Amy    1975     6    27     6  28.5 -79 tropical depress~ NA    25    1013  
## 3 Amy    1975     6    27    12  29.5 -79 tropical depress~ NA    25    1013  
## 4 Amy    1975     6    27    18  30.5 -79 tropical depress~ NA    25    1013  
## 5 Amy    1975     6    28     0  31.5 -78.8 tropical depress~ NA    25    1012  
## 6 Amy    1975     6    28     6  32.4 -78.7 tropical depress~ NA    25    1012  
## 7 Amy    1975     6    28    12  33.3 -78 tropical depress~ NA    25    1011  
## 8 Amy    1975     6    28    18  34 -77 tropical depress~ NA    30    1006  
## 9 Amy    1975     6    29     0  34.4 -75.8 tropical storm NA    35    1004  
## 10 Amy   1975     6    29     6  34 -74.8 tropical storm NA    40    1002  
## 19 / 53 0 6 more rows
```

select(): Negative subsetting

Deselecting variables.

Before

```
storms
```

After

```
select(.data = storms, -storm)
```

```
## # A tibble: 19,066 x 13
```

```
##   name    year month   day  hour   lat  long status category wind pressure
##   <chr> <dbl> <dbl> <int> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl>
## 1 Amy    1975     6    27     0  27.5 -79 tropical depres~ NA    25    1013
## 2 Amy    1975     6    27     6  28.5 -79 tropical depres~ NA    25    1013
## 3 Amy    1975     6    27    12  29.5 -79 tropical depres~ NA    25    1013
## 4 Amy    1975     6    27    18  30.5 -79 tropical depres~ NA    25    1013
## 5 Amy    1975     6    28     0  31.5 -78.8 tropical depres~ NA    25    1012
## 6 Amy    1975     6    28     6  32.4 -78.7 tropical depres~ NA    25    1012
## 7 Amy    1975     6    28    12  33.3 -78 tropical depres~ NA    25    1011
## 8 Amy    1975     6    28    18  34 -77 tropical depres~ NA    30    1006
## 9 Amy    1975     6    29     0  34.4 -75.8 tropical storm NA    35    1004
## 10 Amy   1975     6    29     6  34 -74.8 tropical storm NA    40    1002
## 20 / 53 0 6 more rows
```

```
## Error in `select()`:
## Can't subset columns that don't exist.
```

```
## #> First Column `storm` doesn't exist.
```

```
## #> First Column `storm` doesn't exist.
```

select(): Selecting a range of consecutive variables

Use : to select a range of consecutive variables

Before

```
storms
```

After

```
select(.data = storms, storm:pressure)
```

```
## # A tibble: 19,066 x 13
```

```
##   name   year month   day  hour   lat  long status category wind pressure
##   <chr> <dbl> <dbl> <int> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl>
## 1 Amy    1975     6    27     0  27.5 -79 tropical depres~ NA    25    1013
## 2 Amy    1975     6    27     6  28.5 -79 tropical depres~ NA    25    1013
## 3 Amy    1975     6    27    12  29.5 -79 tropical depres~ NA    25    1013
## 4 Amy    1975     6    27    18  30.5 -79 tropical depres~ NA    25    1013
## 5 Amy    1975     6    28     0  31.5 -78.8 tropical depres~ NA    25    1012
## 6 Amy    1975     6    28     6  32.4 -78.7 tropical depres~ NA    25    1012
## 7 Amy    1975     6    28    12  33.3 -78 tropical depres~ NA    25    1011
## 8 Amy    1975     6    28    18  34 -77 tropical depres~ NA    30    1006
## 9 Amy    1975     6    29     0  34.4 -75.8 tropical storm NA    35    1004
## 10 Amy   1975     6    29     6  34 -74.8 tropical storm NA    40    1002
## 21 / 53 0 6 more rows
```

```
## Error in `select()`:
## ! Can't subset columns that don't exist.
```

```
## ! Column `storm` doesn't exist.
```

```
## ! Column `storm` doesn't exist.
```


Useful select functions

Call	Use
-	Select everything but
:	Select range
contains()	Select columns whose name contains a character string
starts_with()	Select column whose name starts with a character string
ends_with()	Select columns whose name ends with a string
everything()	Select all columns
matches()	Select columns whose name matches a regular expression
num_range()	Select columns matching a numerical range e.g. x1, x2, etc.
one_of()	Select columns whose names are in a group of names

There are others. See `?select` for further details.

filter()

This is used to subset a data frame, retaining all rows that satisfy your logical tests.

Before

```
storms
```

```
## # A tibble: 19,066 x 13
```

##	name	year	month	day	hour	lat	long	##	name	year	month	day	hour	lat	long
##	<chr>	<dbl>	<dbl>	<int>	<dbl>	<dbl>	<dbl>	##	<chr>	<dbl>	<dbl>	<int>	<int>	<dbl>	<dbl>
##	1 Amy	1975	6	27	0	27.5	-79	##	1 Amy	1975	6	29	25	18	-72.8
##	2 Amy	1975	6	27	6	28.5	-79	##	2 Amy	1975	6	30	25	0	-71.6
##	3 Amy	1975	6	27	12	29.5	-79	##	3 Amy	1975	6	30	25	6	-70.8
##	4 Amy	1975	6	27	18	30.5	-79	##	4 Amy	1975	6	30	25	12	-70.5
##	5 Amy	1975	6	28	0	31.5	-78.8	##	5 Amy	1975	6	30	25	18	-70.2
##	6 Amy	1975	6	28	6	32.4	-78.7	##	6 Amy	1975	7	1	25	0	-69.8
##	7 Amy	1975	6	28	12	33.3	-78	##	7 Amy	1975	7	1	25	6	-69.4
##	8 Amy	1975	6	28	18	34	-77	##	8 Amy	1975	7	1	30	12	-68.3
##	9 Amy	1975	6	29	0	34.4	-75.8	##	9 Amy	1975	7	1	35	18	-67.2
##	10 Amy	1975	6	29	6	34	-74.8	##	10 Amy	1975	7	2	40	0	-66.7

```
## 23 / 53 0 6 more rows
```

After

```
filter(.data = storms, wind >= 50)
```

```
## # A tibble: 8,118 x 13
```

##	name	year	month	day	hour	lat	long	##	name	year	month	day	hour	lat	long
##	<chr>	<dbl>	<dbl>	<int>	<dbl>	<dbl>	<dbl>	##	<chr>	<dbl>	<dbl>	<int>	<int>	<dbl>	<dbl>
##	1 Amy	1975	6	29	25	18	-72.8	##	1 Amy	1975	6	29	25	18	-72.8
##	2 Amy	1975	6	30	25	0	-71.6	##	2 Amy	1975	6	30	25	0	-71.6
##	3 Amy	1975	6	30	25	6	-70.8	##	3 Amy	1975	6	30	25	6	-70.8
##	4 Amy	1975	6	30	25	12	-70.5	##	4 Amy	1975	6	30	25	12	-70.5
##	5 Amy	1975	6	30	25	18	-70.2	##	5 Amy	1975	6	30	25	18	-70.2
##	6 Amy	1975	7	1	25	0	-69.8	##	6 Amy	1975	7	1	25	0	-69.8
##	7 Amy	1975	7	1	25	6	-69.4	##	7 Amy	1975	7	1	25	6	-69.4
##	8 Amy	1975	7	1	30	12	-68.3	##	8 Amy	1975	7	1	30	12	-68.3
##	9 Amy	1975	7	1	35	18	-67.2	##	9 Amy	1975	7	1	35	18	-67.2
##	10 Amy	1975	7	2	40	0	-66.7	##	10 Amy	1975	7	2	40	0	-66.7

```
## # i 8 108 more rows
```

filter() (cont.)

You can combine tests separated by commas.

Before

```
storms
```

```
## # A tibble: 19,066 x 13
```

```
##   name    year month   day  hour   lat  long
```

```
##   <chr> <dbl> <dbl> <int> <dbl> <dbl> <dbl> <dbl> <fct> <dbl> <int> <int>
```

```
## 1 Amy    1975     6    27     0  27.5 -79  tropical cyclone  NA    25    1013
```

```
## 2 Amy    1975     6    27     6  28.5 -79  tropical cyclone  NA    25    1013
```

```
## 3 Amy    1975     6    27    12  29.5 -79  tropical cyclone  NA    25    1013
```

```
## 4 Amy    1975     6    27    18  30.5 -79  tropical cyclone  NA    25    1013
```

```
## 5 Amy    1975     6    28     0  31.5 -78.8 tropical depres~  NA    25    1012
```

```
## 6 Amy    1975     6    28     6  32.4 -78.7 tropical depres~  NA    25    1012
```

```
## 7 Amy    1975     6    28    12  33.3 -78   tropical depres~  NA    25    1011
```

```
## 8 Amy    1975     6    28    18  34    -77   tropical depres~  NA    30    1006
```

```
## 9 Amy    1975     6    29     0  34.4 -75.8 tropical storm    NA    35    1004
```

```
## 10 Amy   1975     6    29     6  34    -74.8 tropical storm    NA    40    1002
```

```
## 24 / 53 0 6 more rows
```

After

```
filter(.data = storms,  
       wind >= 50,  
       storm %in% c("Alberto", "Alex",  
                    "Allison"))
```

Logical tests in R

?Comparison

Test	Usage
<	Less than
>	Greater than
==	Equal to
<=	Less than or equal to
>=	Greater than or equal to
!=	Not equal to
%in%	Group membership
is.na()	Is NA?

?base::Logic

Operator	Usage
&	Boolean and
\	Boolean or
xor	Exactly or
!	Not
any()	Any true
all()	All true

slice()

This lets you index rows by their (integer) locations. Thus, it allows you to select, remove, and duplicate rows.

```
# Before
```

```
storms
```

```
## # A tibble: 19,066 x 13
```

```
##   name    year month   day  hour   lat   long ##   name    year month   day  hour   lat   long
##   <chr> <dbl> <dbl> <int> <dbl> <dbl> <dbl> ##   <chr> <dbl> <dbl> <int> <dbl> <dbl> <dbl>
## 1 Amy    1975     6     27     0  27.5 -79 ## 1 Amy    1975     6     27     0  27.5 -79
## 2 Amy    1975     6     27     6  28.5 -79 ## 2 Amy    1975     6     27     6  28.5 -79
## 3 Amy    1975     6     27    12  29.5 -79 ## 3 Amy    1975     6     27    12  29.5 -79
## 4 Amy    1975     6     27    18  30.5 -79 ## 4 Amy    1975     6     27    18  30.5 -79
## 5 Amy    1975     6     28     0  31.5 -78.8 ## 5 Amy    1975     6     28     0  31.5 -78.8
## 6 Amy    1975     6     28     6  32.4 -78.7 ## 6 Amy    1975     6     28     6  32.4 -78.7
## 7 Amy    1975     6     28    12  33.3 -78 ## 7 Amy    1975     6     28    12  33.3 -78
## 8 Amy    1975     6     28    18  34     -77 ## 8 Amy    1975     6     28    18  34     -77
## 9 Amy    1975     6     29     0  34.4 -75.8 ## 9 Amy    1975     6     29     0  34.4 -75.8
## 10 Amy   1975     6     29     6  34     -74.8 ## 10 Amy   1975     6     29     6  34     -74.8
```

```
# After
```

```
slice(.data = storms, 1:3)
```

```
## # A tibble: 3 x 13
```

```
##   name    year month   day  hour   lat   long ##   name    year month   day  hour   lat   long
##   <chr> <dbl> <dbl> <int> <dbl> <dbl> <dbl> ##   <chr> <dbl> <dbl> <int> <dbl> <dbl> <dbl>
## 1 Amy    1975     6     27     0  27.5 -79 ## 1 Amy    1975     6     27     0  27.5 -79
## 2 Amy    1975     6     27     6  28.5 -79 ## 2 Amy    1975     6     27     6  28.5 -79
## 3 Amy    1975     6     27    12  29.5 -79 ## 3 Amy    1975     6     27    12  29.5 -79
```

```
slice(.data = storms, rep(1, 3))
```

```
##   name    year month   day  hour   lat   long ##   name    year month   day  hour   lat   long
##   <chr> <dbl> <dbl> <int> <dbl> <dbl> <dbl> ##   <chr> <dbl> <dbl> <int> <dbl> <dbl> <dbl>
## 1 Amy    1975     6     27     0  27.5 -79 ## 1 Amy    1975     6     27     0  27.5 -79
## 2 Amy    1975     6     27     6  28.5 -79 ## 2 Amy    1975     6     27     6  28.5 -79
## 3 Amy    1975     6     27    12  29.5 -79 ## 3 Amy    1975     6     27    12  29.5 -79
```

```
## # A tibble: 3 x 13
```

```
##   name    year month   day  hour   lat   long ##   name    year month   day  hour   lat   long
```

slice() (cont.)

Using `which.min()` or `which.max()` (or other functions which return row indices) is quite helpful with `slice()`.

```
# Before
```

```
storms
```

```
## # A tibble: 19,066 x 13
```

```
##   name    year month   day  hour   lat  long status
##   <chr> <dbl> <dbl> <int> <dbl> <dbl> <dbl> <chr>
## 1 Amy    1975     6    27     0  27.5 -79 tropical
## 2 Amy    1975     6    27     6  28.5 -79 tropical
## 3 Amy    1975     6    27    12  29.5 -79 tropical
## 4 Amy    1975     6    27    18  30.5 -79 tropical
## 5 Amy    1975     6    28     0  31.5 -78 tropical
## 6 Amy    1975     6    28     6  32.4 -78 tropical
## 7 Amy    1975     6    28    12  33.3 -78 tropical
## 8 Amy    1975     6    28    18  34    -77 tropical
## 9 Amy    1975     6    29     0  34.4 -75.8 tropical
## 10 Amy   1975     6    29     6  34    -74.8 tropical
```

```
# After
```

```
slice(.data = storms, which.min(pressure))
```

```
## # A tibble: 1 x 13
```

```
##   name    year month   day  hour   lat  long status
##   <chr> <dbl> <dbl> <int> <dbl> <dbl> <dbl> <chr>
## 1 Amy    1975     6    27     0  27.5 -79 tropical
```

```
slice(.data = storms, which.max(wind))
```

```
## # A tibble: 1 x 13
##   name    year month   day  hour   lat  long status
##   <chr> <dbl> <dbl> <int> <dbl> <dbl> <dbl> <chr>
## 1 Amy    1975     6    29    35  34.4 -75.8 tropical
```

mutate()

We may want to **create** new variables from existing variables. Suppose we want to derive a new variable called `ratio` which is defined as

$$\text{ratio} = \frac{\text{pressure}}{\text{wind}}$$

storm	wind	pressure	date
Alberto	110	1007	2000-08-03
Alex	45	1009	1998-07-27
Allison	65	1005	1995-06-03
Ana	40	1013	1997-06-30
Arlene	50	1010	1999-06-11
Arthur	45	1010	1999-06-17

`storms$pressure / storms$wind` → `ratio`

1007 / 110 → 9.16

1009 / 45 → 22.42

1005 / 65 → 15.46

1013 / 40 → 25.33

1010 / 50 → 20.20

1010 / 45 → 22.44

mutate() (cont.)

Using dplyr's mutate() function, we are able to do this easily without having to use \$ all the time.

```
# Before
```

```
storms
```

```
## # A tibble: 19,066 x 13
```

```
##   name    year month   day   hour   lat   long   status category   wind pressure
##   <chr> <dbl> <dbl> <int> <dbl> <dbl> <dbl> <chr> <dbl> <int> <dbl> <dbl>
## 1 Amy    1975     6    27     0  27.5 -79  tropical depress 6 NA 27 25 0 1013 -79
## 2 Amy    1975     6    27     6  28.5 -79  tropical depress 6 NA 27 25 6 1013 -79
## 3 Amy    1975     6    27    12  29.5 -79  tropical depress 6 NA 27 25 12 1013 -79
## 4 Amy    1975     6    27    18  30.5 -79  tropical depress 6 NA 27 25 18 1013 -79
## 5 Amy    1975     6    28     0  31.5 -78.8 tropical depress 6 NA 27 25 18 1013 -79
## 6 Amy    1975     6    28     6  32.4 -78.7 tropical depress 6 NA 28 25 0 1013 -78.8
## 7 Amy    1975     6    28    12  33.3 -78  tropical depress 6 NA 28 25 6 1014 -78.7
## 8 Amy    1975     6    28    18  34 -77  tropical depress 6 NA 28 30 12 1006 -78
## 9 Amy    1975     6    29     0  34.4 -75.8 tropical storm 6 NA 28 35 18 1004 -77
## 10 Amy    1975     6    29     6  34 -74.8 tropical storm 6 NA 29 40 0 1002 -77
```

```
# After
```

```
mutate(.data = storms,
       ratio = pressure / wind)
```


mutate() (cont.)

Keep on adding new columns in the same mutate() call. Just separate them by commas.

```
mutate(.data = storms,  
       ratio = pressure / wind,  
       inverse = ratio ^ (-1))
```

```
## # A tibble: 19,066 x 15
```

##	name	year	month	day	hour	lat	long	status	category	wind	pressure
##	<chr>	<dbl>	<dbl>	<int>	<dbl>	<dbl>	<dbl>	<fct>	<dbl>	<int>	<int>
##	1 Amy	1975	6	27	0	27.5	-79	tropical depres~	NA	25	1013
##	2 Amy	1975	6	27	6	28.5	-79	tropical depres~	NA	25	1013
##	3 Amy	1975	6	27	12	29.5	-79	tropical depres~	NA	25	1013
##	4 Amy	1975	6	27	18	30.5	-79	tropical depres~	NA	25	1013
##	5 Amy	1975	6	28	0	31.5	-78.8	tropical depres~	NA	25	1012
##	6 Amy	1975	6	28	6	32.4	-78.7	tropical depres~	NA	25	1012
##	7 Amy	1975	6	28	12	33.3	-78	tropical depres~	NA	25	1011
##	8 Amy	1975	6	28	18	34	-77	tropical depres~	NA	30	1006
##	9 Amy	1975	6	29	0	34.4	-75.8	tropical storm	NA	35	1004
##	10 Amy	1975	6	29	6	34	-74.8	tropical storm	NA	40	1002

```
## #> 10 more rows
```

Useful mutate() functions

Operator	Usage
<code>pmin()</code> , <code>pmax()</code>	Element-wise min and max
<code>cummin()</code> , <code>cummax()</code>	Cumulative min and max
<code>cumsum()</code> , <code>cumprod()</code>	Cumulative sum and product
<code>between()</code>	Are values between a and b?
<code>cumall()</code> , <code>cumany()</code>	Cumulative <code>all()</code> and <code>any()</code>
<code>cummean()</code>	Cumulative mean
<code>lead()</code> , <code>lag()</code>	Comparing values behind or ahead of current values
<code>ntile()</code>	Bin vector into n buckets
<code>row_number()</code>	Returns row number

Remark

All of these (window) functions take vector values and return vector values of the same length. If using non-window functions, the recycling rule applies.

summarise()

On the other hand, we may want to **condense** the available information. For this, the `summarise()` function returns a new data frame.

```
# Before  
pollution
```

```
## Error in eval(expr, envir, enclos): object
```

```
# After
```

```
summarise(.data = pollution,  
          median = median(amount),  
          variance = var(amount))
```

```
## Error in summarise(.data = pollution, median
```

Useful summarise() functions

Operator	Usage
<code>min()</code> , <code>max()</code>	Minimum and maximum values
<code>mean()</code>	Mean value
<code>median()</code>	Median value
<code>sum()</code>	Sum of values
<code>var()</code> , <code>sd()</code>	Variance and standard deviation of a vector
<code>first()</code> , <code>last()</code>	First or last value in a vector
<code>nth()</code>	Nth value in a vector
<code>n()</code>	The number of values in a vector
<code>n_distinct()</code>	The number of distinct values in a vector

Remark

All of these functions take vector values and return a single value.

Summary (summarise) vs window (mutate) functions



- Functions used with `summarise()` should reduce the length of the input vector to a single value.
- Functions used with `mutate()` should keep the vector length.

arrange()

Sorting rows (in ascending order) in a particular column is done using `arrange()`.

Before

```
storms
```

```
## # A tibble: 19,066 x 13
```

##	name	year	month	day	hour	lat	long	status	name	year	month	day	hour	lat	long
##	<chr>	<dbl>	<dbl>	<int>	<dbl>	<dbl>	<dbl>	<fct>	<chr>	<dbl>	<dbl>	<int>	<dbl>	<dbl>	<dbl>
## 1	Amy	1975	6	27	0	27.5	-79	tropical	Bonnie	1986	NA	25	10	136.5	-9
## 2	Amy	1975	6	27	6	28.5	-79	tropical	Bonnie	1986	NA	25	12	137.2	-9
## 3	Amy	1975	6	27	12	29.5	-79	tropical	Charley	1986	NA	25	12	130.1	-8
## 4	Amy	1975	6	27	18	30.5	-79	tropical	Charley	1986	NA	25	18	130.8	-8
## 5	Amy	1975	6	28	0	31.5	-78.8	tropical	Charley	1986	NA	25	0	131.4	-8
## 6	Amy	1975	6	28	6	32.4	-78.7	tropical	Charley	1986	NA	25	6	132	-8
## 7	Amy	1975	6	28	12	33.3	-78	tropical	Charley	1986	NA	25	12	132.5	-8
## 8	Amy	1975	6	28	18	34	-77	tropical	Charley	1986	NA	25	18	132.4	-8
## 9	Amy	1975	6	29	0	34.4	-75.8	tropical	storm	1987	NA	25	0	130.9	-8
## 10	Amy	1975	6	29	6	34	-74.8	tropical	storm	1987	NA	25	6	131.4	-8

After

```
arrange(.data = storms, wind)
```

```
## # A tibble: 19,066 x 13
```

##	name	year	month	day	hour	lat	long	status	name	year	month	day	hour	lat	long
##	<chr>	<dbl>	<dbl>	<int>	<dbl>	<dbl>	<dbl>	<fct>	<chr>	<dbl>	<dbl>	<int>	<dbl>	<dbl>	<dbl>
## 1	Bonnie	1986	NA	25	10	136.5	-9	tropical	Bonnie	1986	NA	25	10	136.5	-9
## 2	Bonnie	1986	NA	25	12	137.2	-9	tropical	Bonnie	1986	NA	25	12	137.2	-9
## 3	Charley	1986	NA	25	12	130.1	-8	tropical	Charley	1986	NA	25	12	130.1	-8
## 4	Charley	1986	NA	25	18	130.8	-8	tropical	Charley	1986	NA	25	18	130.8	-8
## 5	Charley	1986	NA	25	0	131.4	-8	tropical	Charley	1986	NA	25	0	131.4	-8
## 6	Charley	1986	NA	25	6	132	-8	tropical	Charley	1986	NA	25	6	132	-8
## 7	Charley	1986	NA	25	12	132.5	-8	tropical	Charley	1986	NA	25	12	132.5	-8
## 8	Charley	1986	NA	25	18	132.4	-8	tropical	Charley	1986	NA	25	18	132.4	-8
## 9	storm	1987	NA	25	0	130.9	-8	tropical	storm	1987	NA	25	0	130.9	-8
## 10	storm	1987	NA	25	6	131.4	-8	tropical	storm	1987	NA	25	6	131.4	-8

```
## # i 19,056 more rows
```

arrange() (cont.)

Sorting rows (in descending order) in a particular column is done by applying desc() on the variable.

```
# Before
```

```
storms
```

```
## # A tibble: 19,066 x 13
```

```
##   name    year month   day  hour   lat  long ## status name    year category  wind  pressure  lat  lon
##   <chr> <dbl> <dbl> <int> <dbl> <dbl> <dbl> ## <fct> <chr>    <dbl> <dbl> <int> <dbl> <dbl> <dbl>
## 1 Amy    1975     6    27     0  27.5 -79  ## tropical 1980     NA    25    18 1013.8 -86
## 2 Amy    1975     6    27     6  28.5 -79  ## tropical 1988     NA    25     0 1013.7 -83
## 3 Amy    1975     6    27    12  29.5 -79  ## tropical 2005    10    25    12 1017.3 -82
## 4 Amy    1975     6    27    18  30.5 -79  ## tropical 2019     NA    25    16 1013.5 -77
## 5 Amy    1975     6    28     0  31.5 -78.8 ## tropical 2019     NA    25    18 1013.5 -77
## 6 Amy    1975     6    28     6  32.4 -78.7 ## tropical 1980     NA    25    12 1012.9 -70
## 7 Amy    1975     6    28    12  33.3 -78  ## tropical 1980     NA    25    12 1011    -84
## 8 Amy    1975     6    28    18  34    -77  ## tropical 1980     NA    30     0 1006.2 -87
## 9 Amy    1975     6    29     0  34.4 -75.8 ## tropical 1980     NA    35     6 1004    -94
## 10 Amy    1975     6    29     6  34    -74.8 ## tropical 1980     NA    140    6 1003.2 -94
```

```
# After
```

```
arrange(.data = storms, desc(wind))
```

arrange() (cont.)

You may arrange by multiple columns in order.

Before

```
storms
```

```
## # A tibble: 19,066 x 13
```

```
##   name   year month   day hour   lat   long status category wind pressure
##   <chr> <dbl> <dbl> <int> <dbl> <dbl> <dbl> <dbl> <dbl> <int> <int>
## 1 Amy    1975     6    27     0  27.5 -79 tropical depres~ NA      25      1013
## 2 Amy    1975     6    27     6  28.5 -79 tropical depres~ NA      25      1013
## 3 Amy    1975     6    27    12  29.5 -79 tropical depres~ NA      25      1013
## 4 Amy    1975     6    27    18  30.5 -79 tropical depres~ NA      25      1013
## 5 Amy    1975     6    28     0  31.5 -78.8 tropical depres~ NA      25      1012
## 6 Amy    1975     6    28     6  32.4 -78.7 tropical depres~ NA      25      1012
## 7 Amy    1975     6    28    12  33.3 -78 tropical depres~ NA      25      1011
## 8 Amy    1975     6    28    18  34 -77 tropical depres~ NA      30      1006
## 9 Amy    1975     6    29     0  34.4 -75.8 tropical storm NA      35      1004
## 10 Amy   1975     6    29     6  34 -74.8 tropical storm NA      40      1002
## 37 / 53 0 6 more rows
```

After

```
arrange(.data = storms, wind, date)
```

```
## Error in `arrange()`:
## In argument: category, date, wind, pressure
```

```
## Caused by error: <dbl> <int> <int>
## tropical depres~ must be a vector, not a function.
```


Tidy data

Getting tidy data

Data wrangling

Pipeline

Group wrangling

Joining data sets

Pipeline

Consider the following sequence of actions that describe the process of getting to campus in the morning:

I need to find my key, then unlock my car, then start my car, then drive to school, then park.

Expressed as a set of nested functions in R pseudocode this would look like:

```
park(drive(start_car(find("keys")), to = "campus"))
```

Writing it out using pipes give it a more natural (and easier to read) structure:

```
find("keys") %>%  
  start_car() %>%  
  drive(to = "campus") %>%  
  park()
```

The pipe operator %>%

The pipe operator puts the output of the LHS into the first argument of the function of the RHS.



Therefore, the following code both do the same thing.

```
summarise(storms, mean = mean(wind))
```

```
storms %>% summarise(., mean = mean(wind))
```

```
## # A tibble: 1 x 1
##   mean
##   <dbl>
## 1  50.0
```

```
## # A tibble: 1 x 1
##   mean
##   <dbl>
## 1  50.0
```

In fact, we may drop the `'.'` when the situation is obvious, i.e. `storms %>% summarise(mean = mean(wind))` would give the same thing.

Combining dplyr functions

For data wrangling, it seems more natural to progressively write code in a pipeline path. As an example, consider the `nycflights13::flights` data set. How many flights to LAX did each of the legacy carriers (AA, UA, DL or US) have in May from JFK, and what was their average duration?

```
library(nycflights13)
filtered_flights <-
  filter(.data = flights,
         origin == "JFK", dest == "LAX", month == 5,
         carrier %in% c("AA", "UA", "DL", "US"))
res <- summarise(.data = filtered_flights,
                 n = n(), avg_dur = mean(air_time, na.rm = TRUE))
res
```

```
## # A tibble: 1 x 2
##       n avg_dur
##   <int>   <dbl>
## 1   685   320.
```

Combining dplyr functions (cont.)

In contrast, we can pipe the entire thing:

```
flights %>%  
  # Filter first  
  filter(origin == "JFK", dest == "LAX", month == 5,  
         carrier %in% c("AA", "UA", "DL", "US")) %>%  
  # Then summarise  
  summarise(  
    n = n(),  
    avg_dur = mean(air_time, na.rm = TRUE)  
  )
```

```
## # A tibble: 1 x 2  
##       n avg_dur  
##   <int>   <dbl>  
## 1    685    320.
```

Another example

```
flights %>%  
  # Select all variables containing "delay" in their name  
  select(contains("delay")) %>%  
  # Create a new gain variable  
  mutate(gain = arr_delay - dep_delay) %>%  
  # Drop all rows with NA in them  
  drop_na() %>%  
  # Summarise  
  summarise(  
    min = min(gain),  
    max = max(gain),  
    mean = mean(gain)  
  )
```

```
## # A tibble: 1 x 3  
##   min    max  mean  
##   <dbl> <dbl> <dbl>  
## 1  -109   196 -5.66
```

Tidy data

Getting tidy data

Data wrangling

Pipeline

Group wrangling

Joining data sets

Group wrangling

When we used the `summarise()` function, we were in fact using the **entire data set** to arrive at the summaries.

city	size	amount
New York	large	23
New York	small	14
London	large	22
London	small	16
Beijing	large	121
Beijing	small	56

`summarise()`



sum	n	mean
252	6	42

e.g. `pollution %>% summarise(sum = sum(amount), n = n(), mean = mean(amount))`.

Group wrangling (cont.)

Grouping the observations by some categorical variable allows us to uncover hidden information lying within the groups. We use `group_by()` to do this.

city	size	amount
New York	large	23
New York	small	14

London	large	22
London	small	16

Beijing	large	121
Beijing	small	56

`group_by(city) %>%
summarise()`



sum	n	mean
37	2	18.5

38	2	19
----	---	----

177	2	88.5
-----	---	------

Group wrangling (cont.)

The code to obtain the previous grouped summary table is

```
pollution %>%  
  group_by(city) %>%  
  summarise(  
    sum = sum(amount),  
    n = n(),  
    mean = mean(amount)  
  )
```

```
## Error in group_by(., city): object 'pollution' not found
```

ungroup()

Note that when you group data, this will persist throughout the pipeline. This is indicated by the Groups: city [3] print out below. If, further down the pipeline, you wish to mutate or summarise based on the entire data set, you must first ungroup().

```
pollution %>%  
  group_by(city)
```

```
## Error in group_by(., city): object 'pollution' not found
```

```
pollution %>%  
  group_by(city) %>%  
  ungroup()
```

```
## Error in group_by(., city): object 'pollutio
```

Multiple groups

Multiple groupings are allowed. Let's find the top 3 routes with the smallest departure delay in the flights dataset.

```
flights %>%  
  group_by(origin, dest) %>%  
  summarise(min_delay = min(dep_delay)) %>%  
  arrange(min_delay) %>%  
  print(n = 3)
```

```
## # A tibble: 224 x 3  
## # Groups:   origin [3]  
##   origin dest  min_delay  
##   <chr>  <chr>      <dbl>  
## 1 LGA     EYW         -18  
## 2 JFK     HNL         -16  
## 3 JFK     ACK         -13  
## # i 221 more rows
```

Tidy data

Getting tidy data

Data wrangling

Pipeline

Group wrangling

Joining data sets

- `bind_cols()`

- `bind_rows()`

- `left_join()`

Joining data sets

Here are the functions useful for combining data sets

1. `bind_cols()`
2. `bind_rows()`
3. `*_join()` commands
4. Other set operation functions such as `union()`, `intersect()`, and `setdiff()`

For more details on these functions, please have a look at

<https://github.com/gadenbuie/tidyexplain>--This page contains a helpful information about what the join functions do.

bind_cols()

If you have two or more data frames (or columns) that are meant to go together column-wise, then use `bind_cols()`.

```
x <- storms[, 1:3]  # First 3 columns of storms
y <- storms$date    # The last column of storms
bind_cols(x, y)
```

```
## # A tibble: 19,066 x 3
```

```
##   name    year month
```

```
##   <chr> <dbl> <dbl>
```

```
## 1 Amy    1975     6
```

```
## 2 Amy    1975     6
```

```
## 3 Amy    1975     6
```

```
## 4 Amy    1975     6
```

```
## 5 Amy    1975     6
```

```
## 6 Amy    1975     6
```

```
## 7 Amy    1975     6
```

```
## 8 Amy    1975     6
```

```
## 9 Amy    1975     6
```

```
## 49 / 53 1975     6
```

bind_rows()

Similarly if you wanted to stack two or more data frames on top of each other, then use `bind_rows()`.

```
x <- storms[1:3, ] # First 3 columns of storms
y <- storms[4:6, ] # Last 3 columns of storms
bind_rows(x, y)
```

```
## # A tibble: 6 x 13
```

	name	year	month	day	hour	lat	long	status	category	wind	pressure
	<chr>	<dbl>	<dbl>	<int>	<dbl>	<dbl>	<dbl>	<fct>	<dbl>	<int>	<int>
## 1	Amy	1975	6	27	0	27.5	-79	tropical depress~	NA	25	1013
## 2	Amy	1975	6	27	6	28.5	-79	tropical depress~	NA	25	1013
## 3	Amy	1975	6	27	12	29.5	-79	tropical depress~	NA	25	1013
## 4	Amy	1975	6	27	18	30.5	-79	tropical depress~	NA	25	1013
## 5	Amy	1975	6	28	0	31.5	-78.8	tropical depress~	NA	25	1012
## 6	Amy	1975	6	28	6	32.4	-78.7	tropical depress~	NA	25	1012

```
## # i 2 more variables: tropicalstorm_force_diameter <int>,
```

```
## # hurricane_force_diameter <int>
```


Remark

`bind_rows()`



`bind_cols()`



Warning


`bind_cols()` and `bind_rows()` have no way of checking whether or not the joining is consistent (e.g. is the row-ordering the same between both data frames in `bind_cols()`?)

left_join()

Out of all the `*_join()` functions, this is probably the most frequently used (at least for me anyway). When calling `left_join(x, y)`, this

- adds columns from `y` to `x`;
- matching rows based on the by keys;
- and **includes all rows in `x`** (but possibly not `y`).

`left_join()`



left_join() (cont.)

An example of left_join() on the band members and instruments data sets.

```
band_members
```

```
## # A tibble: 3 x 2
##   name band
##   <chr> <chr>
## 1 Mick  Stones
## 2 John  Beatles
## 3 Paul  Beatles
```

```
band_instruments
```

```
## # A tibble: 3 x 2
##   name plays
##   <chr> <chr>
## 1 John  guitar
## 2 Paul   bass
## 3 Keith guitar
```

```
band_members %>%
  left_join(., band_instruments, by = "name")
```

```
## # A tibble: 3 x 3
##   name band   plays
##   <chr> <chr>   <chr>
## 1 Mick  Stones <NA>
## 2 John  Beatles guitar
## 3 Paul  Beatles bass
```