

Technical Data Sheet PC: 6200

Protex Rust Preventive Oil - 1048

Protex rust preventive oil is special design for rust prevention during assembly, transit, storage, export etc...

FEATURES & BENEFITS

- Excellent product for rust prevention, with user friendly application
- Save labour & material cost
- Prevent degradation of material
- Easy to handle
- Save further process
- Use as multi metal protection system
- After drying can be grinding, chipping & machining work
- Easy to remove

Uses

- Castings, machine surface, plates each and every metal parts
- Foundry, stamping, bearing, auto parts, castings, nut bolts etc...
- Article storage during assembly
- Protection during transit
- Can apply on export articles
- Multiple uses for rust prevention purpose

Why Protex rust preventive oil - 1048 (Benefits)

Protex rust preventive oil contains specialised corrosion inhibitors, hydrophobic additives, moisture resistant materials, provide excellent resistant against rust, so it workable for long time.

The product has following specifications:

Form: Liquid

Density: 0.80 ± 0.50

Flash point: Around $40 \pm 5^{\circ}c$

PH (as it is): Not applicable

Odour: Solvent

Flammable: Highly Flammable

Solubility in Water: Not Soluble

Appearance: Pale yellow to brown in colour

Application Method:

Deep, spray, brush, for best result if possible deep the article

Article temperature must be below 40°c during rust preventive oil application

Remove or further painting:

To remove the rust preventive oil - 1048, clean (wipe with cloth) with any type of petroleum solvent like kerosene, xylene, turpentine, toluene or any petroleum based thinner.

Protex rust preventive oil packing:

Corrosion inhibitor is available in 20 ltr, 50 ltr HDPE carboys and 210 ltr drums.

Storage:

Should be stored in shade area, in a location where the product temperature can be kept between 10 to 35°c, the product contains petroleum solvent, it is flammable, please keep it away from fire, spark or flammable material, Refer to MSDS for detailed information.

Important:

When stored in cool dry condition, unopened container of PROTEX — rust preventive oil - 1048 may be kept for 2 year However, it is advisable to turnover stock on first-in, first-out basis

PROTEX - rust preventive oil - 1048 contains flammable solvents and so it must stored away from fire atmosphere, away from red-hot surface, open flames and in well ventilated area.

All protective cloth including face-mask, respirators, eye-protector, hard-gloves, etc. must be wear by when handling/using PROTEX – rust preventive oil - 1048, please refer MSDS before use.

Handle: The product, PROTEX - rust preventive oil - 1048 contain petroleum oil & solvents so take every precaution handling solvents.

Please shake well before every use.

Note:

No liability is accepted for any accidents or damages arising in handling or use of this product PROTEX - rust preventive oil - 1048, in any circumstances.

All technical data's in this bulletin are based on the test results and are believed to be correct, However since the end use of this product, PROTEX - rust preventive oil - 1048 (and the manner of storing, handling, application, etc,) are beyond our control, we make no warranty express or implied as to the fitness of use. Results to be obtained from or affects use with respect to those materials. Their use shall be solely by the judgment of and at the risk of the users not withstanding any statement contained in this bulletin.

All information is without engagement.

Issue Date: 15th April 2010

Creative Business Systems

07, Agrawal Estate, Beside Bhagirath Est., Gulabnager, Near Swastik Char Rasta, Amraiwadi, Ahmedabad-26 (M) 98250 08956

E-mail: creativeprotex@gmail.com & dhirentricoat@yahoo.com