

### **Technical Data Sheet**

## Protex Oilygo – 100 Oil Remover

Water base oil remover to clean oil from surface

#### **FEATURES**

- Domestic & industrial oil surface cleaner
- Environment friendly material & easily disposable
- Non corrosive
- No heavy particals
- Minimum doses & maximum work
- Cost effective
- User's friendly

#### Uses

Automobile workshop, leth or CMC machine workshops, Transformer manufacturer, Bearing Manufacturer, Automobile or pump assembly units, Food processing, phermaceuticals, sheet metal processing units, oil processers, oil mills etc...

#### PROTEX - Details

PROTEX OILYGO - 100 is specially formulated industrial degreaser for the effective removal of mineral / synthetic oils, tar, grease etc. from work areas of factories, workshops, hotels and restaurants, public areas, office blocks etc. It is a fast wetter for penetrating soils and surfaces. It can hold soil in suspension.

PC: 5400

#### **RECOMMENDED DILUTION**

Normal Soiling: 10 ml in 1 litre of water

Medium Soiling: 20 ml in 1 litre of water

Heavy soiling: 50 ml in 1 litre of water

First time uses: 100 ml in 1 litre of water

#### **Why PROTEX (benefits)**

User's friendly, easy disposable, cost economical, huge area, bulk work through machine is possible with PROTEX OILYGO - 100, Suitable for use with both, wet mopping as well as scrubbing with a machine.

#### **IMPORTANT**

When stored in cool dark condition, unopened container of PROTEX OILYGO - 100 may be kept for 1 year However, it is advisable to turnover stock on first-in, first-out basis.

PROTEX OILYGO - 100 contains flammable solvents and so it must stored in fire-proof atmosphere, away from red-hot surface, open flames and in well ventilated area.

All protective cloth including face-mask, respirators, eye-protector, hard-gloves, etc. must be wear by when handling/using PROTEX OILYGO - 100

The product, PROTEX OILYGO - 100 contain some green emulsifiers so take every precaution handling cleaning material, please refer our MSDS before use.

#### **PRODUCT SPECIFICATIONS**

Colour: Light Yellow

Odour: loral

pH: 8 - 9

Type: Non corrosive material

#### NOTE:

No liability is accepted for any accidents or damages arising in handling or use of this product PROTEX OILYGO - 100 under any circumstances.

All technical data's in this bulletin are based on the test results and are believed to be correct, However since the end use of this product, PROTEX OILYGO - 100 (and the manner of storing, handling, application, etc,) are beyond our control, we make no warranty express or implied as to the fitness of use. Results to be obtained from or affects use with respect to those materials. Their use shall be solely by the judgment of and at the risk of the users not withstanding any statement contained in this bulletin.

All information is without engagement.

Issue Date: 15<sup>th</sup> April 2010

# **Creative Business Systems**

07, Agrawal Estate, Beside Bhagirath Est., Gulabnager, Near Swastik Char Rasta, Amraiwadi, Ahmedabad-26 (M) 98250 08956

E-mail: creativeprotex@gmail.com & dhirentricoat@yahoo.com