



## Technical Data Sheet

PC: 5508

# Protex Water Fill – 932 JAY Rust Preventer

Protex water fill – 932 JAY prevent the water corrosion and heating in equipment during pump storage & working condition

### FEATURES (For Submersible & Mono block Pump)

- Reduce Chock-up or blocking problems because of non rusted inner surface.
  - Help in Maintain temp. During working
  - Long lasting maintenance period because non corrosive inner surface
  - Easy start in low voltage
  - Rust prevention due to water corrosion during storage
  - Decrease the heat during running & product has anti freezing property up to some extent.
  - User friendly material
  - No additional efforts
  - Maintain quality manufacturing product, not only at the time of product mfg. but quality remains same during pump life it Save replacement ratio by 5-6 % & increase brand image of manufacturer
- Recommended for close water system, Water storage equipment must be rust free.

### Uses

- Submersible & mono block pumps
- Water cooling Pipelines, water circulation lines etc..
- Water filling machines higher cooling required

### OPERATING PROCEDURE

Just dose Water fill 932 JAY 1 : 9 R O water (By Volume)

## **Surface preparation**

Surface must be non rusted, free from oil, grease, scale, dust, paint or any other foreign particles, the sand blasted, shot blasted or machine surface give best result.

### **Why Protex water fill – 932 JAY (benefits)**

- Pre-softening of water is generally, not required
- Prevents scale and sludge
- No Chromates
- Inhibits multi-metal system
- Increases life of equipments
- Does not affect non-metals

## **IMPORTANT**

Shake well before every use, When stored in cool dark condition, unopened container of **Protex water fill – 932 JAY** may be kept for 1 year However, it is advisable to turnover stock on first-in, first-out basis.

All protective cloth including face-mask, respirators, eye-protector, hard-gloves, etc. must be wear by when handling/using **Protex water fill – 932 JAY**

Please refer our MSDS before use.

## **NOTE:**

No liability is accepted for any accidents or damages arising in handling or use of this product PROTEX water fill - 932 JAY under any circumstances.

All technical data's in this bulletin are based on the test results and are believed to be correct, However since the end use of this product, PROTEX water fill - 932 JAY (and the manner of storing, handling, application, etc,) are beyond our control, we make no warranty express or implied as to the fitness of use. Results to be obtained from or affects use with respect to those materials. Their use shall be solely by the judgment of and at the risk of the users notwithstanding any statement contained in this bulletin.

For further information please contact on email id: [creativeprotex@gmail.com](mailto:creativeprotex@gmail.com)

All information is without engagement.

**Packing:** 210 Ltrs in plastic carbo or barrel

Issue Date: 15<sup>th</sup> April 2010

# Creative Business Systems

07, Agrawal Estate, Beside Bhagirath Est., Gulabnager, Near Swastik Char Rasta, Amraiwadi,  
Ahmedabad-26 (M) 98250 08956

E-mail: [creativeprotex@gmail.com](mailto:creativeprotex@gmail.com) & [dhirentriccoat@yahoo.com](mailto:dhirentriccoat@yahoo.com)