

SmagerUp Core (SUC) - Updated System Documentation

Overview

SmagerUp Core (SUC) is the central backend platform that securely manages, hosts, and licenses JavaScript modules and libraries used by SmagerUp Studio (SUS).

This document reflects the latest database structure, including the new Content-based modular design.

Core Tables Overview

1. Accounts - Manages user authentication and API keys.
2. LicenseTypes - Defines module license categories (FreeUseNonModifiable, PaidNonModifiable).
3. Contents - Stores raw JS, CSS, HTML, or text code.
4. ContentGroups - Groups related content files together (HTML, CSS, JS per module).
5. Modules - Links to a ContentGroup and LicenseType, representing a full library/module.
6. AccountModules - Tracks module ownership and access per account.

1. Accounts

Columns:

- AccountId (UNIQUEIDENTIFIER): Primary key.
- FirstName, LastName, EmailAdd: User details.
- ApiKey (NVARCHAR(255)): Authentication key.
- CreatedDate (DATETIME): Record creation date.

2. LicenseTypes

Columns:

- LicenseTypeId (INT): Primary key.
- Name (NVARCHAR(50)): Short code (SFUL, SCL).
- Type (NVARCHAR(50)): Classification (FreeUseNonModifiable, PaidNonModifiable).
- BodyContent (NVARCHAR(MAX)): License text.
- CreatedAt (DATETIME): Creation date.

3. Contents

Stores raw code for modules.

Columns:

- ContentId (UNIQUEIDENTIFIER): Primary key.
- ContentBody (NVARCHAR(MAX)): The actual source code.
- ContentType (VARCHAR(5)): Identifies content as js, css, html, txt, etc.
- CreatedAt (DATETIME): Creation timestamp.

4. ContentGroups

Groups content files under a single identifier.

Columns:

- ContentGroupId (UNIQUEIDENTIFIER): Primary key.
- ContentId (INT): FK -> Contents.ContentId.
- CreatedAt (DATETIME): Creation date.

5. Modules

Represents a complete library or module with license and grouped content.

Columns:

- ModuleId (INT): Primary key.
- Name (NVARCHAR(100)): Module name.
- Version (NVARCHAR(20)): Version string.
- LicenseTypeId (INT): FK -> LicenseTypes.LicenseTypeId.
- Price (DECIMAL): Price (0 = Free).
- ContentGroupId (UNIQUEIDENTIFIER): FK -> ContentGroups.ContentGroupId.
- IsActive (BIT): Active flag.
- CreatedAt (DATETIME): Creation date.

6. AccountModules

Tracks which accounts have access to which modules.

Columns:

- AccountModuleId (UNIQUEIDENTIFIER): Primary key.
- AccountId (UNIQUEIDENTIFIER): FK -> Accounts.AccountId.
- ModuleId (INT): FK -> Modules.ModuleId.
- ExpiryDate (DATETIME): License expiry.
- IsActive (BIT): Access status.
- CreatedAt (DATETIME): Record creation date.

Data Flow Example

1. SUS authenticates with SUC using AccountId + ApiKey.
2. SUC returns a JWT token for secure access.
3. SUS requests modules via API (e.g., /api/grid@1.0.0).
4. SUC validates license, retrieves grouped content (HTML, CSS, JS) via ContentGroups -> Contents.
5. Returns compiled response to SUS for rendering.

Entity Relationship Summary

Accounts (1) --< AccountModules (M) >-- (1) Modules

Modules (1) --< LicenseTypes

Modules (1) --< ContentGroups (M) >-- (1) Contents

Author

German Fuentes

Founder & Developer of SmagerUp Ecosystem

Cebu, Philippines