

Project Data Page:





Table of Contents

Cover Page	1
Vessel Design Summary:	2
Nozzle Summary:	5
Nozzle Schedule:	6
Bill of Material:	7
MDMT Summary:	8
Warnings and Errors:	10
Input Echo:	11
XY Coordinate Calculations:	20
Flg Calc [Int P]: FLANGE	21
Flg Calc [Int P]: New Flange	27
Internal Pressure Calculations:	33
Element: Chnl. cover rea	34
Element: Chnl. rear	36
Element: Shell	38
Element: Chnl. front	40
Element: Chnl. front	42
Shop Pressure Test Results:	44
ASME TS Calc: Pressure Test	46
External Pressure Calculations:	59
Element and Detail Weights:	60
Nozzle Flange MAWP:	62
Wind Load Calculation:	64
Earthquake Load Calculation:	66
Center of Gravity Calculation:	68
Saddle Calcs: Operating Case:	69
Saddle Calcs: Test Case:	87
Nozzle Calcs.: N1- Channel inl	102
Nozzle Calcs.: N1- Shell outle	116
Nozzle Calcs.: N2- shell inlet	130
Nozzle Calcs.: N2- Channel out	144
ASME TS Calc: DESIGN CASE	158
Problems/Failures Summary:	173



DESIGN CALCULATION

In Accordance with ASME Section VIII Division 1

ASME Code Version : 2025

Analysis Performed by : SL User

Job File : ...\\401-E-33001-RP.pvdb

Date of Analysis : Aug 12, 2026 9:52am

PV Elite 28, January 2026



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 2 of 173

Vessel Design Summary:

Step: 28 9:52am Aug 12,2026

Vessel Design Summary:

ASME Code, Section VIII Division 1, 2025

Diameter Spec : 600.000 mm ID
Vessel Design Length, Tangent to Tangent 6404.00 mm
Specified Datum Line Distance 76.20 mm
Shell Side Design Temperature 166 °C
Channel Side Design Temperature 77 °C
Shell Side Design Pressure 1549.500 KPa.
Channel Side Design Pressure 1191.500 KPa.
Shop Shell Side Test Pressure 3665.206 KPa.
Shop Channel Side Test Pressure 2385.965 KPa.
Wind Design Code IS 875 (PART 3) Amd. 1&2 (2020)
Earthquake Design Code IS 1893 RSM Amd. 1&2 (2018)

Materials of Construction:

Component Type	Material	Class	Thickness	UNS #	Material Treatment Options
Shell	SA-106 B	...	...	K03006	
Head	SA-234 WPB	...	...	K03006	
Flange	SA-266 2	...	...	K03506	
Nozzle	SA-106 B	...	...	K03006	
Re-Pad	SA-516 70	...	...	K02700	
Nozzle Flg	SA-105	...	...	K03504	
Tubes	SA-179	...	...	K01200	
Tubesheet	SA-266 2	...	...	K03506	
Flg Bolting	SA-193 B7	...	<= 64	G41400	
Hrz Bolting	SA-193 B7	...	<= 64	G41400	
Saddles	SA-516 70	...	...	K02700	

+FG - Fine Grained, +R - rolled, +T - Tempered, +N - Normalized

+Q - quenched, +CBV - Cb & V added, +IT - Impact tested

Element Pressures and MAWP (KPa. & mm):

Element Description or Type	Design Pressure + Stat. head	Ext. Press.	Element M.A.W.P	Total Corrosion Allowance	Str. Flg. Gov.	In Creep Range
Chnl. cover rea	1197.412	0.00	2029.000	3.1750	No	No
Chnl. rear	1197.412	0.00	2437.000	3.1750	N/A	No
Chnl. flange rer	1191.500	0.00	1921.000	3.1750	N/A	No
Shell	1549.796	0.00	2913.000	3.1750	N/A	No
Chnl. flange frnt	1191.500	0.00	1921.000	3.1750	N/A	No
Chnl. front	1197.412	0.00	2437.000	3.1750	N/A	No
Chnl. front	1197.412	0.00	2029.000	3.1750	No	No

Liquid Level: 600.00 mm Dens.: 0.001 kg./cm³ Sp. Gr.: 1.000

Element Types and Properties:

Element Type	"To" Elev mm	Element Length mm	Nominal Thickness mm	Finished Thickness mm	Reqd Thk Internal mm	Reqd Thk External mm	Long Eff	Circ Eff
--------------	--------------	-------------------	----------------------	-----------------------	----------------------	----------------------	----------	----------



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 3 of 173

Vessel Design Summary:

Step: 28 9:52am Aug 12,2026

Ellipse	0.0	76.2	9.5	8.3	6.2	...	1.00	1.00
Cylinder	600.0	600.0	9.5	9.5	6.3	...	1.00	1.00
Body Flg	678.8	74.3	68.0	60.0	54.8	54.8	1.00	1.00
Cylinder	5520.8	4790.0	9.5	9.5	6.5	...	1.00	1.00
Body Flg	5651.6	74.3	68.0	60.0	54.8	54.8	1.00	1.00
Cylinder	6251.6	600.0	9.5	9.5	6.3	...	1.00	1.00
Ellipse	6327.8	76.2	9.5	8.3	6.2	...	1.00	1.00

Local Stress Analysis Results:

Description	Analysis Type	Max Stress Ratio	High Stress Location	Pass Fail
N1- Channel in	WRC-297	0.483	Shell	Passed
N1- Shell outl	WRC-297	0.526	Shell	Passed
N2- shell inle	WRC-297	0.526	Shell	Passed
N2- Channel ou	WRC-297	0.483	Shell	Passed


Foundation/Support Summary

Saddle Parameters:

Saddle Width	204.000 mm
Saddle Bearing Angle	120.000 deg.
Centerline Dimension	560.000 mm
Wear Pad Width	225.000 mm
Wear Pad Thickness	12.000 mm
Wear Pad Bearing Angle	132.000 deg.
Distance from Saddle to Tangent	960.000 mm

Baseplate Length	550.000 mm
Baseplate Thickness	16.000 mm
Baseplate Width	150.000 mm
Number of Ribs (including outside ribs)	3
Rib Thickness	16.000 mm
Web Thickness	16.000 mm
Height of Center Web	306.000 mm
Number of Bolts in Baseplate	2

Baseplate Sketch



Maximum Tensile Bolt Load

15. Kgf

Summary of Maximum Saddle Loads, Operating Case, Un-Factored:



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 4 of 173

Vessel Design Summary: Step: 28 9:52am Aug 12,2026

Maximum Vertical Saddle Load	4001.17	Kgf
Maximum Transverse Saddle Shear Load	531.40	Kgf
Maximum Longitudinal Saddle Shear Load	404.22	Kgf

Summary of Maximum Saddle Loads, Pressure Test Case:

Maximum Vertical Saddle Load	3379.04	Kgf
Maximum Transverse Saddle Shear Load	175.36	Kgf
Maximum Longitudinal Saddle Shear Load	31.84	Kgf

Weights:

Fabricated - Bare w/o removable internals	3992.7	kg.
Shop Test - Fabricated + water (full)	5604.4	kg.
Shipping - Fab. + rem. intls.+ shipping app.	4060.2	kg.
Erected - Fab. + rem. intls.+ insul. (etc)	4060.2	kg.
Empty - Fab. + intls. + details + wghts.	4060.2	kg.
Operating - Empty + operating liquid (no ca)	4819.2	kg.

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 5 of 173

Nozzle Summary:

Step: 26 9:52am Aug 12,2026

Nozzle Calculation Summary (KPa. & mm):

Description	MAWP	Ext	MAPNC	UG-45	[tr]	Weld Path	Areas or Stresses
N1- Channel inl	2437	...	...	OK	6.27	OK	Passed
N1- Shell outle	2913	...	...	OK	6.53	OK	Passed
N2- shell inlet	2819	...	...	OK	6.53	OK	Passed
N2- Channel out	2437	...	...	OK	6.26	OK	Passed

Nozzle MAWP Summary:

Minimum MAWP Nozzles : 2819 Nozzle : N2- shell inlet [Shellside]
 Minimum MAWP Nozzles : 2437 Nozzle : N1- Channel inl [Tubeside]

Note: MAWPs (Internal Case) shown above are at the High Point.

Multiple output lines for the same nozzle indicates required Code calculations in both the longitudinal and circumferential planes of reinforcement where applicable.

Check the spatial relationship between the nozzles:

From Node	Nozzle Description	X Coordinate mm	Layout Angle deg	Dia. Limit mm
20	N1- Channel inle	376.200	90.000	305.359
40	N1- Shell outlet	1306.999	270.000	498.450
40	N2- shell inlet	4806.999	270.000	590.601
60	N2- Channel outl	6027.799	270.000	305.359

The nozzle spacing is computed by the following:

$$= \sqrt{ll^2 + lc^2} \text{ where}$$

ll - Arc length along the inside vessel surface in the long. direction.

lc - Arc length along the inside vessel surface in the circ. direction

If any interferences/violations are found, they will be noted below.

No interference violations have been detected!

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 6 of 173

Nozzle Schedule:

Step: 25 9:52am Aug 12,2026

Nozzle Schedule:

Description	Nominal or Actual Size	Schd or FVC Type	Flg Type	Nozzle O/Dia in	Wall Thk mm	Reinforcing Pad Diameter	Pad Thk mm	Cut Length mm	Flg Class
N1- Channel inle	6.000 in	80	WNF	6.625	10.973	308.27	10.00	271.57	150
N2- Channel outl	6.000 in	80	WNF	6.625	10.973	308.27	10.00	271.57	150
N1- Shell outlet	10.000 in	80	WNF	10.750	15.088	413.05	10.00	292.40	300
N2- shell inlet	12.000 in	80	WNF	12.750	17.450	463.85	10.00	306.98	300

General Notes for the above table:

The cut length is the outside projection + inside projection + drop + in-plane shell thickness. This value does not include weld gaps, nor does it account for shrinkage.

In the case of oblique nozzles, the outside diameter must be increased. The re-pad width around the nozzle is calculated as follows:

Width of Pad = (Pad Outside Dia. (per above) - Nozzle Outside Dia.)/2

For hub nozzles, the thickness and diameter shown are those of the smaller and thinner section.

Nozzle Material and Weld Fillet Leg Size Details (mm):

Description	Material	Shl Grve Weld	Noz Shl/Pad Weld	Pad OD Weld	Pad Grve Weld	Inside Weld
N1- Channel	SA-106 B	9.530	30.000	8.000	10.000	...
N2- Channel	SA-106 B	9.530	30.000	8.000	10.000	...
N1- Shell o	SA-106 B	9.530	10.000	8.000	10.000	...
N2- shell i	SA-106 B	9.530	10.000	8.000	10.000	...

Note: The Outside projections below do not include the flange thickness.

Nozzle Miscellaneous Data:

Description	Elev/Distance From Datum mm	Layout Angle deg	Proj Outside mm	Proj Inside mm	Installed in Component
N1- Channel inle	300.000	90.0	250.00	0.00	Chnl. rear
N2- Channel outl	5951.599	270.0	250.00	0.00	Chnl. front
N1- Shell outlet	1230.799	270.0	250.00	0.00	Shell
N2- shell inlet	4730.799	270.0	250.00	0.00	Shell

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 7 of 173

Bill of Material:

Step: 24 9:52am Aug 12,2026

Bill of Materials:

QTY	DESCRIPTION	MATERIAL
2	ELLIPTICAL HEAD: 2.0 X 1, 9.5mm THK X 600.0mm ID X 76.2mm	SA-234 WPB
2	WELD NECK FLANGE: 68.0mm THK X 740.0mm OD	SA-266 2
8	BAFFLES: 580.0mm DIA X 6.0mm THK	SA-516 70
2	TUBESHEET: 740.0mm X 52.0mm THK	SA-266 2
534	TUBES: 4877.0mm X 15.9mm DIA X 2.1mm THK	SA-179
2	SADDLE: 204.0mm X 120 DEG	SA-516 70
1	INSULATION: 4790mm X 45mm THK	Hot
2	GASKET: 655.0mm OD X 629.0mm ID	...
56	BODY FLANGE BOLTS: 19.0mm DIA	SA-193 B7
56	NUTS FOR BODY FLANGE BOLTS: 19.0mm DIA	...
2	CYLINDRICAL SEGMENT 9.5mm THK X 748.7mm X 600.0mm	SA-106 B
1	CYLINDRICAL SEGMENT 9.5mm THK X 387.5mm X 600.0mm	SA-106 B
1	CYLINDRICAL SEGMENT 9.5mm THK X 1513.2mm X 4790.0mm	SA-106 B
1	CYLINDRICAL SEGMENT 9.5mm THK X 371.7mm X 4790.0mm	SA-106 B
1	CYLINDRICAL SEGMENT 9.5mm THK X 371.7mm X 600.0mm	SA-106 B
1	CYLINDRICAL SEGMENT 9.5mm THK X 1513.2mm X 600.0mm	SA-106 B
1	NAMEPLATE	...

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 8 of 173

MDMT Summary:

Step: 27 9:52am Aug 12,2026

Minimum Design Metal Temperature Results Summary (°C):

Description	Curve	Basic MDMT	Reduced MDMT	UG-20(f) MDMT	Thickness ratio	Gov Thk mm	E*	PWHT reqd
Notes								
Shell [8]	B	-29	-48	-29	0.416	9.530	1.00	No
Left Saddle [24]	B	-29	-38	-29	0.844	9.530	1.00	No
Right saddle [24]	B	-29	-38	-29	0.844	9.530	1.00	No
N1- Shell outl[1]	B	-29	-48	-29	0.462	10.000	1.00	No
Nozzle Flg [5]	A	-18	-104					
N2- shell inle[1]	B	-29	-48	-29	0.462	10.000	1.00	No
Nozzle Flg [5]	A	-18	-104					
Tubesheet: SS[13]	B	-21	-48	-29	0.510	13.000	1.00	No
Warmest MDMT:		-18	-38					
Chnl. flange [11]	B	-29	-43	-29	0.751	9.530	1.00	No
Chnl. flange [11]	B	-29	-43	-29	0.751	9.530	1.00	No
Chnl. cover r[10]	B	-29	-34	-29	0.902	8.340	1.00	No
Chnl. cover re[7]	B	-29	-43	-29	0.749	9.530	1.00	No
Chnl. rear [8]	B	-29	-48	-29	0.455	8.340	1.00	No
Chnl. front [8]	B	-29	-48	-29	0.370	9.530	1.00	No
Chnl. front [10]	B	-29	-34	-29	0.902	8.340	1.00	No
Chnl. front [7]	B	-29	-43	-29	0.749	9.530	1.00	No
N1- Channel in[1]	B	-29	-48	-29	0.487	9.530	1.00	No
Nozzle Flg [5]	A	-18	-39					
N2- Channel ou[1]	B	-29	-48	-29	0.485	9.530	1.00	No
Nozzle Flg [5]	A	-18	-40					
Tubesheet: CS[14]	B	-21	-48	-29	0.510	13.000	1.00	No
Bolting [21]		-48						
Bolting [21]		-48						
Warmest MDMT:		-18	-34					

Exchanger Side	Computed MDMT	Required MDMT	Pass/Fail
Shell	-38.0	11.4	Pass
Channel/Tube	-34.0	11.4	Pass

Notes:

- [!] - This was an impact tested material.
- [1] - Governing Nozzle Weld.
- [4] - ASME Flange MDMT Calcs; Thickness ratio per UCS-66(b)(1)(-c).
- [5] - ASME Flange MDMT Calcs; Thickness ratio per UCS-66(b)(1)(-b).
- [6] - MDMT Calculations at the Shell/Head Joint.
- [7] - MDMT Calculations for the Straight Flange.
- [8] - Cylinder/Cone/Flange Junction MDMT.
- [9] - Calculations in the Spherical Portion of the Head.
- [10] - Calculations in the Knuckle Portion of the Head.
- [11] - Calculated (Body Flange) Flange MDMT.
- [12] - Calculated Flat Head MDMT per UCS-66.3
- [13] - Tubesheet MDMT, shell side, if applicable
- [14] - Tubesheet MDMT, tube side, if applicable
- [15] - Nozzle Material
- [16] - Shell or Head Material
- [17] - Impact Testing required
- [18] - Impact Testing not required, see UCS-66(b)(3)
- [20] - Cylinder/Cone Junction MDMT based on Longitudinal Stress considerations
- [21] - Body Flange Bolting Material
- [22] - Nozzle Flange Bolting Material
- [23] - Stiffening Ring to Shell Weld
- [24] - Saddle to Shell Weld



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 9 of 173

MDMT Summary:

Step: 27 9:52am Aug 12, 2026

UG-84(b)(2) was not considered.

UCS-66(g) was not considered.

UCS-66(i) was not considered.

Notes:

Impact test temps were not entered in and not considered in the analysis.

UCS-66(i) applies to impact tested materials not by specification and

UCS-66(g) applies to materials impact tested per UG-84.1 General Note (c).

The Basic MDMT includes the (30F) PWHT credit if applicable.

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 10 of 173

Warnings and Errors:

Step: 0 9:52am Aug 12,2026

Class From To : Basic Element Checks.

Class From To: Check of Additional Element Data

Warning:

There is a flange in this model connected to an element whose temperature is different. The bolt allowable stress is based on it's parent design temperature. You may need to manually adjust the operating bolt allowable stress to a value based upon a representative maximum temperature the bolts will be subject to.

There were no geometry errors or warnings.

PV Elite performs all calculations internally in Imperial Units to remain compliant with the ASME Code and any built in assumptions in the ASME Code formulas. The finalized results are reflected to show the set of selected units for this analysis.

Information Regarding Nozzle Loads

Please note that nozzle loadings, if included, are assumed to be local in nature and will not contribute to or create a net section bending moment. Therefore, the addition of nozzle loads will not affect the support load calculation. If you wish to create a load on the support(s) from nozzle loads, you can enable that feature in tools->configuration->Job Specific Settings.



The level of precision is set to a value of less than 3. At this level you may not obtain proper resolution on some results. This value can be changed in Tools->Set Configuration Parameters->Default Values->Level of Precision.



The ASME Code Section VIII Division 1 does not explicitly require stresses on elements to be computed under test conditions. Please see interpretation VIII-1-10-12 for more information. PV Elite also computes weight due to test fluid and uses the weight in various calculations such as saddle and leg loads. PV Elite also computes static pressure due to operating and test liquids. The static pressure is used in conjunction with the design and test pressures to determine a total pressure in the determination of required thickness, MAWP etc. This ensures compliance with UG-22 requirements.

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 11 of 173

Input Echo:

Step: 1 9:52am Aug 12,2026

Units used in this Analysis (MM):

Name	System Unit	Constant	User Unit
Length	Feet	304.8000	mm
Force	Pounds	0.4536	Kgf
Mass	Pounds	0.4536	kg.
Area	sq. inches	6.4516	cm ²
Moment	ft. lbs.	0.1383	Kg-m.
Stress	lbs./sq.in.	0.0069	N./mm ²
Temperature	Degrees F	0.5556	°C
Pressure	psig	6.8946	KPa.
Elast. Modulus	lbs./sq.in.	6.8946	KPa.
Pipe Density	lbs./cu.in.	0.0277	kg./cm ³
Ins. Density	lbs./cu.ft.	0.1600E-04	kg./cm ³
Fluid Density	lbs./cu.ft.	0.1600E-04	kg./cm ³
Wind Speed	miles/hr	1.6093	Km/hr
Tray Weight	lbs./sq.ft.	0.0005	Kgs/cm ²
Inertia	in.4	41.6231	cm4
G Load	G's	1.0000	g's
Wind Load	lbs./sq.ft.	4.8825	Kgs/m ²
Elevation	Feet	304.8000	mm
Volume	in.3	16.3900	cm ³
Diameter	inches	25.4000	mm
Thickness	inches	25.4000	mm

PV Elite Vessel Analysis Program: Input Data

Exchanger Design Pressures and Temperatures

Shell Side Design Pressure	1549.5	KPa.
Channel Side Design Pressure	1191.5	KPa.
Shell Side Design Temperature	165.6	°C
Channel Side Design Temperature	76.7	°C
Radiography, Shell Side	RT-1	
Radiography, Channel Side	RT-1	
Service Type, Shell Side	Air/Water/Steam	
Service Type, Channel Side	Air/Water/Steam	
MDMT (CET), Shell Side	11.4	°C
MDMT (CET), Tube Side	11.4	°C
User defined MAWP, Shell Side	0	KPa.
User defined MAWP, Channel Side	0	KPa.
User defined MAPnc, Shell Side	0	KPa.
User defined MAPnc, Channel Side	0	KPa.
User defined Test Pres., Shell Side	0	KPa.
User defined Test Pres., Channel Side	0	KPa.

Projection of Nozzle from Vessel Top	0	mm
Projection of Nozzle from Vessel Bottom	0	mm
Type of Construction	Welded	
Use Higher Longitudinal Stresses (Flag)	Y	
Select t for Internal Pressure (Flag)	N	
Select t for External Pressure (Flag)	N	
Select t for Axial Stress (Flag)	N	
Select Location for Stiff. Rings (Flag)	N	

User Spectrum Data points specified for increments of Time Period

Time Period	Sa/g
0.010	0.070



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 12 of 173

Input Echo:

Step: 1 9:52am Aug 12,2026

0.050	0.117
0.100	0.175
0.130	0.175
0.200	0.175
0.270	0.175
0.300	0.175
0.400	0.175
0.500	0.140
0.550	0.127
0.600	0.117
0.670	0.105
0.800	0.087
1.000	0.070
1.200	0.058
1.400	0.050
1.600	0.044
1.800	0.039
2.000	0.035
2.400	0.029
0.000	0.000

Consider Vortex Shedding

N

Shop Pressure Test:

Type of Pressure Test

UG-99(b)

Pressure Test Position

Horizontal

Test Performed in Corroded Condition

No

Load Case 1	NP+EW+WI+FW+BW
Load Case 2	NP+EW+EE+FS+BS
Load Case 3	NP+OW+WI+FW+BW
Load Case 4	NP+OW+EQ+FS+BS
Load Case 5	NP+HW+HI
Load Case 6	NP+HW+HE
Load Case 7	IP+OW+WI+FW+BW
Load Case 8	IP+OW+EQ+FS+BS
Load Case 9	EP+OW+WI+FW+BW
Load Case 10	EP+OW+EQ+FS+BS
Load Case 11	HP+HW+HI
Load Case 12	HP+HW+HE
Load Case 13	IP+WE+EW
Load Case 14	IP+WF+CW
Load Case 15	IP+VO+OW
Load Case 16	IP+VE+EW
Load Case 17	NP+VO+OW
Load Case 18	FS+BS+IP+OW
Load Case 19	FS+BS+EP+OW
Load Case 20	BL+IP+OW

Wind Design Code	IS 875 (PART 3):2015-2020	
Basic Wind Speed for IS-875	180	Km/hr
Wind Zone Number	5	
Base Elevation	300	mm
Percent Wind for Hydrotest	33.0	
Risk Factor	[k1] 1.0	
Terrain Category	2	
Equipment Class	Class A	
Topography Factor	[k3] 1.0	
Importance Factor	[k4] 1.15	
Damping Factor (Beta) for Wind (Ope)	0.0100	
Damping Factor (Beta) for Wind (Empty)	0.0000	
Damping Factor (Beta) for Wind (Filled)	0.0000	

Seismic Design Code	IS 1893-RSM
Importance Factor for IS-1893	2.000



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 13 of 173

Input Echo: Step: 1 9:52am Aug 12,2026

Soil Factor	1.000
Zone Number	2.000
Percent Seismic for Hydrotest	0.000
Period of Vibration (User defined) Sec	0.000
Damping Factor	2.000

User Spectrum Data points specified for increments of Time Period

Time Period	Sa/g
0.010	0.070
0.050	0.117
0.100	0.175
0.130	0.175
0.200	0.175
0.270	0.175
0.300	0.175
0.400	0.175
0.500	0.140
0.550	0.127
0.600	0.117
0.670	0.105
0.800	0.087
1.000	0.070
1.200	0.058
1.400	0.050
1.600	0.044
1.800	0.039
2.000	0.035
2.400	0.029
0.000	0.000

Consider Vertical Acceleration	Yes
Design Pressure + Static Head	Y
Consider MAP New and Cold in Noz. Design	N
Consider External Loads for Nozzle Des.	Y
Use ASME VIII-1 Appendix 1-9	N
Perform Blast Load Analysis	No
Material Database Year	Current w/Addenda or Code Year

Configuration Directives:

g0 is taken as min(g0, attached shell thk)	Yes
Do not use Nozzle MDMT Interpretation VIII-1 01-37	No
Use Table G instead of exact equation for "A"	Yes
Shell Head Joints are Tapered	Yes
Compute "K" in corroded condition	Yes
Use Code Case 2286	No
Use the MAWP to compute the MDMT	Yes
For thickness ratios <= 0.35, MDMT will be -155F (-104C)	Yes
For PWHT & P1 Materials the MDMT can be < -55F (-48C)	No
Using Metric Material Databases, ASME II D	Yes
Calculate B31.3 type stress for Nozzles with Loads	Yes
Reduce the MDMT due to lower membrane stress	Yes
Consider Longitudinal Stress in MDMT Calculations	Yes

Complete Listing of Vessel Elements and Details:

Element#	1/7
Element From Node	10
Element To Node	20
Element Type	Elliptical



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 14 of 173

Input Echo:

Step: 1 9:52am Aug 12,2026

Description	Chnl. cover rea	
Distance "FROM" to "TO"	76.2	mm
Inside Diameter	600	mm
Element Thickness	8.34	mm
Internal Corrosion Allowance	3.175	mm
Nominal Thickness	9.53	mm
External Corrosion Allowance	0	mm
Design Internal Pressure	1191.5	KPa.
Design Temperature Internal Pressure	77	°C
Design External Pressure	0	KPa.
Design Temperature External Pressure	40	°C
Effective Diameter Multiplier	1.2	
Material Name	SA-234 WPB	
Allowable Stress, Ambient	118	N./mm ²
Allowable Stress, Operating	118	N./mm ²
Allowable Stress, Hydrotest	153.4	N./mm ²
Material Density	0.00775	kg./cm ³
P Number Thickness	32.004	mm
Yield Stress, Operating	224.66	N./mm ²
UCS-66 Chart Curve Designation	B	
External Pressure Chart Name	CS-2	
UNS Number	K03006	
Product Form	Smls. & wld. fittings	
Efficiency, Longitudinal Seam	1.0	
Efficiency, Circumferential Seam	1.0	
Elliptical Head Factor	2.0	
Weld is pre-Heated	No	
Element From Node	10	
Detail Type	Liquid	
Detail ID	Liquid: 10	
Dist. from "FROM" Node / Offset dist	0	mm
Height/Length of Liquid	600	mm
Liquid Density	0.0009984	kg./cm ³

Element#	2/7
Element From Node	20
Element To Node	30
Element Type	Cylinder
Description	Chnl. rear
Distance "FROM" to "TO"	600 mm
Inside Diameter	600 mm
Element Thickness	9.53 mm
Internal Corrosion Allowance	3.175 mm
Nominal Thickness	9.53 mm
External Corrosion Allowance	0 mm
Design Internal Pressure	1191.5 KPa.
Design Temperature Internal Pressure	77 °C
Design External Pressure	0 KPa.
Design Temperature External Pressure	40 °C
Effective Diameter Multiplier	1.2
Material Name	SA-106 B
Allowable Stress, Ambient	118 N./mm ²
Allowable Stress, Operating	118 N./mm ²
Allowable Stress, Hydrotest	153.4 N./mm ²
Material Density	0.00775 kg./cm ³
P Number Thickness	32.004 mm
Yield Stress, Operating	224.66 N./mm ²
UCS-66 Chart Curve Designation	B
External Pressure Chart Name	CS-2
UNS Number	K03006
Product Form	Smls. pipe
Efficiency, Longitudinal Seam	1.0



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 15 of 173

Input Echo:

Step: 1 9:52am Aug 12,2026

Efficiency, Circumferential Seam	1.0
Weld is pre-Heated	No
Element From Node	20
Detail Type	Liquid
Detail ID	Liquid: 30
Dist. from "FROM" Node / Offset dist	0 mm
Height/Length of Liquid	600 mm
Liquid Density	0.0009984 kg./cm ³
Element From Node	20
Detail Type	Nozzle
Detail ID	N1- Channel inle
Dist. from "FROM" Node / Offset dist	300 mm
Nozzle Diameter	6 in.
Nozzle Schedule	80
Nozzle Class	150
Layout Angle	90.0
Blind Flange (Y/N)	N
Weight of Nozzle (Used if > 0)	27.062 Kgf
Grade of Attached Flange	GR 1.1
Nozzle Matl	SA-106 B

Element#	3/7
Element From Node	30
Element To Node	40
Element Type	Flange
Description	Chnl. flange rer
Distance "FROM" to "TO"	74.3 mm
Flange Inside Diameter	600 mm
Element Thickness	60 mm
Internal Corrosion Allowance	3.175 mm
Nominal Thickness	68 mm
External Corrosion Allowance	0 mm
Design Internal Pressure	1191.5 KPa.
Design Temperature Internal Pressure	77 °C
Design External Pressure	0 KPa.
Design Temperature External Pressure	40 °C
Effective Diameter Multiplier	1.2
Material Name	SA-266 2
Allowable Stress, Ambient	138 N./mm ²
Allowable Stress, Operating	138 N./mm ²
Allowable Stress, Hydrotest	179.4 N./mm ²
Material Density	0.00775 kg./cm ³
P Number Thickness	32.004 mm
Yield Stress, Operating	231 N./mm ²
UCS-66 Chart Curve Designation	B
External Pressure Chart Name	CS-2
UNS Number	K03506
Product Form	Forgings
Perform Flange Stress Calculation (Y/N)	Y
Weld is pre-Heated	No

Element#	4/7
Element From Node	40
Element To Node	50
Element Type	Cylinder
Description	Shell
Distance "FROM" to "TO"	4790 mm
Inside Diameter	600 mm
Element Thickness	9.53 mm



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 16 of 173

Input Echo:

Step: 1 9:52am Aug 12,2026

Internal Corrosion Allowance	3.175	mm
Nominal Thickness	9.53	mm
External Corrosion Allowance	0	mm
Design Internal Pressure	1549.5	KPa.
Design Temperature Internal Pressure	166	°C
Design External Pressure	0	KPa.
Design Temperature External Pressure	40	°C
Effective Diameter Multiplier	1.2	
Material Name	SA-106 B	
Allowable Stress, Ambient	161	N./mm ²
Allowable Stress, Operating	140.75	N./mm ²
Allowable Stress, Hydrotest	228	N./mm ²
Material Density	0.00775	kg./cm ³
P Number Thickness	0	mm
Yield Stress, Operating	211.51	N./mm ²
UCS-66 Chart Curve Designation	B	
External Pressure Chart Name	CS-2	
UNS Number	K03006	
Product Form	Smls. pipe	
Efficiency, Longitudinal Seam	1.0	
Efficiency, Circumferential Seam	1.0	
Weld is pre-Heated	No	

Element From Node	40	
Detail Type	Saddle	
Detail ID	Left Saddle	
Dist. from "FROM" Node / Offset dist	960	mm
Width of Saddle	204	mm
Height of Saddle at Bottom	560	mm
Saddle Contact Angle	120.0	
Height of Composite Ring Stiffener	0	mm
Width of Wear Plate	225	mm
Thickness of Wear Plate	12	mm
Contact Angle, Wear Plate (degrees)	132.0	
Friction coefficient	0.0	
Moment Factor	3.0	
Dimension E at base (optional)	0	mm
Circumferential Eff. over Saddle	1.0	
Circumferential Eff. at Midspan	1.0	
Tangent to Tangent dist. (optional)	0	mm

Element From Node	40	
Detail Type	Saddle	
Detail ID	Right saddle	
Dist. from "FROM" Node / Offset dist	3830	mm
Width of Saddle	204	mm
Height of Saddle at Bottom	560	mm
Saddle Contact Angle	120.0	
Height of Composite Ring Stiffener	0	mm
Width of Wear Plate	225	mm
Thickness of Wear Plate	12	mm
Contact Angle, Wear Plate (degrees)	132.0	
Friction coefficient	0.5	
Moment Factor	3.0	
Dimension E at base (optional)	0	mm
Circumferential Eff. over Saddle	1.0	
Circumferential Eff. at Midspan	1.0	
Tangent to Tangent dist. (optional)	0	mm

Element From Node	40	
Detail Type	Liquid	
Detail ID	Liquid: 40	
Dist. from "FROM" Node / Offset dist	0	mm
Height/Length of Liquid	600	mm
Liquid Density	0.49920E-04	kg./cm ³



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 17 of 173

Input Echo:

Step: 1 9:52am Aug 12,2026

Element From Node	40
Detail Type	Insulation
Detail ID	Hot insulation
Dist. from "FROM" Node / Offset dist	0 mm
Height/Length of Insulation	4790 mm
Thickness of Insulation	45 mm
Density	0.00015 kg./cm ³

Element From Node	40
Detail Type	Nozzle
Detail ID	N1- Shell outlet
Dist. from "FROM" Node / Offset dist	500 mm
Nozzle Diameter	10 in.
Nozzle Schedule	80
Nozzle Class	300
Layout Angle	270.0
Blind Flange (Y/N)	N
Weight of Nozzle (Used if > 0)	78.846 Kg
Grade of Attached Flange	GR 1.1
Nozzle Matl	SA-106 B

Element From Node	40
Detail Type	Nozzle
Detail ID	N2- shell inlet
Dist. from "FROM" Node / Offset dist	4000 mm
Nozzle Diameter	12 in.
Nozzle Schedule	80
Nozzle Class	300
Layout Angle	270.0
Blind Flange (Y/N)	N
Weight of Nozzle (Used if > 0)	110.13 Kg
Grade of Attached Flange	GR 1.1
Nozzle Matl	SA-106 B

Element#	5/7
Element From Node	50
Element To Node	60
Element Type	Flange
Description	Chnl. flange frnt
Distance "FROM" to "TO"	74.3 mm
Flange Inside Diameter	600 mm
Element Thickness	60 mm
Internal Corrosion Allowance	3.175 mm
Nominal Thickness	68 mm
External Corrosion Allowance	0 mm
Design Internal Pressure	1191.5 KPa.
Design Temperature Internal Pressure	77 °C
Design External Pressure	0 KPa.
Design Temperature External Pressure	40 °C
Effective Diameter Multiplier	1.2
Material Name	SA-266 2
Allowable Stress, Ambient	138 N./mm ²
Allowable Stress, Operating	138 N./mm ²
Allowable Stress, Hydrotest	179.4 N./mm ²
Material Density	0.00775 kg./cm ³
P Number Thickness	32.004 mm
Yield Stress, Operating	231 N./mm ²
UCS-66 Chart Curve Designation	B
External Pressure Chart Name	CS-2
UNS Number	K03506
Product Form	Forgings
Perform Flange Stress Calculation (Y/N)	Y



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 18 of 173

Input Echo:

Step: 1 9:52am Aug 12,2026

Weld is pre-Heated

No

Element#	6/7
Element From Node	60
Element To Node	70
Element Type	Cylinder
Description	Chnl. front
Distance "FROM" to "TO"	600 mm
Inside Diameter	600 mm
Element Thickness	9.53 mm
Internal Corrosion Allowance	3.175 mm
Nominal Thickness	9.53 mm
External Corrosion Allowance	0 mm
Design Internal Pressure	1191.5 KPa.
Design Temperature Internal Pressure	77 °C
Design External Pressure	0 KPa.
Design Temperature External Pressure	40 °C
Effective Diameter Multiplier	1.2
Material Name	SA-106 B
Allowable Stress, Ambient	118 N./mm ²
Allowable Stress, Operating	118 N./mm ²
Allowable Stress, Hydrotest	153.4 N./mm ²
Material Density	0.00775 kg./cm ³
P Number Thickness	32.004 mm
Yield Stress, Operating	224.66 N./mm ²
UCS-66 Chart Curve Designation	B
External Pressure Chart Name	CS-2
UNS Number	K03006
Product Form	Smls. pipe
Efficiency, Longitudinal Seam	1.0
Efficiency, Circumferential Seam	1.0
Weld is pre-Heated	No

Element From Node	60
Detail Type	Liquid
Detail ID	Liquid: 50
Dist. from "FROM" Node / Offset dist	0 mm
Height/Length of Liquid	600 mm
Liquid Density	0.0009984 kg./cm ³

Element From Node	60
Detail Type	Nozzle
Detail ID	N2- Channel outl
Dist. from "FROM" Node / Offset dist	300 mm
Nozzle Diameter	6 in.
Nozzle Schedule	80
Nozzle Class	150
Layout Angle	270.0
Blind Flange (Y/N)	N
Weight of Nozzle (Used if > 0)	27.062 Kg
Grade of Attached Flange	GR 1.1
Nozzle Matl	SA-106 B

Element#	7/7
Element From Node	70
Element To Node	80
Element Type	Elliptical
Description	Chnl. front
Distance "FROM" to "TO"	76.2 mm
Inside Diameter	600 mm
Element Thickness	8.34 mm



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 19 of 173

Input Echo:

Step: 1 9:52am Aug 12,2026

Internal Corrosion Allowance	3.175	mm
Nominal Thickness	9.53	mm
External Corrosion Allowance	0	mm
Design Internal Pressure	1191.5	KPa.
Design Temperature Internal Pressure	77	°C
Design External Pressure	0	KPa.
Design Temperature External Pressure	40	°C
Effective Diameter Multiplier	1.2	
Material Name	SA-234	WPB
Allowable Stress, Ambient	118	N./mm ²
Allowable Stress, Operating	118	N./mm ²
Allowable Stress, Hydrotest	153.4	N./mm ²
Material Density	0.00775	kg./cm ³
P Number Thickness	32.004	mm
Yield Stress, Operating	224.66	N./mm ²
UCS-66 Chart Curve Designation	B	
External Pressure Chart Name	CS-2	
UNS Number	K03006	
Product Form	Smls. & wld. fittings	
Efficiency, Longitudinal Seam	1.0	
Efficiency, Circumferential Seam	1.0	
Elliptical Head Factor	2.0	
Weld is pre-Heated	No	
Element From Node	70	
Detail Type	Liquid	
Detail ID	Liquid: 70	
Dist. from "FROM" Node / Offset dist	0	mm
Height/Length of Liquid	600	mm
Liquid Density	0.0009984	kg./cm ³

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 20 of 173

XY Coordinate Calculations: Step: 2 9:52am Aug 12,2026

XY Coordinate Calculations:

From	To	X (Horiz.) mm	Y (Vert.) mm	DX (Horiz.) mm	DY (Vert.) mm
Chnl. cover rea		76.2	...	76.2	...
Chnl. rear		676.2	...	600	...
Chnl. flange re		755	...	74.3	...
Shell		5597	...	4790	...
Chnl. flange fr		5727.8	...	74.3	...
Chnl. front		6327.8	...	600	...
Chnl. front		6404	...	76.2	...

The calculated dimensions are based on the given element lengths. Due to variability in manufacturing (weld gaps etc.), the Tangent to Tangent length may not be exact. The length includes gasket thicknesses and raised face heights.

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 21 of 173

Flg Calc [Int P]: FLANGE


Flng: 5 9:52am Aug 12,2026

Flange Input Data Values

Description: FLANGE :

Chnl. flange rer

Flange Type	Integral Weld Neck		
Design Pressure	P	1191.50	KPa.
Design Temperature		77	°C
Internal Corrosion Allowance	ci	3.1750	mm
External Corrosion Allowance	ce	0.0000	mm
Use Corrosion Allowance in Thickness Calcs.		Yes	
Flange Inside Diameter	B	600.000	mm
Flange Outside Diameter	A	740.000	mm
Flange Thickness	t	60.0000	mm
Thickness of Hub at Small End	go	9.5300	mm
Thickness of Hub at Large End	gl	13.0000	mm
Length of Hub	h	14.3000	mm
Flange Material		SA-266 2	
Flange Material UNS number		K03506	
Flange Allowable Stress At Temperature	Sfo	138.00	N./mm ²
Flange Allowable Stress At Ambient	Sfa	138.00	N./mm ²
Bolt Material		SA-193 B7	
Bolt Allowable Stress At Temperature	Sb	172.00	N./mm ²
Bolt Allowable Stress At Ambient	Sa	172.00	N./mm ²
Diameter of Bolt Circle	C	690.000	mm
Nominal Bolt Diameter	a	19.0500	mm
Type of Threads	TEMA Thread Series		
Number of Bolts		28	
Flange Face Outside Diameter	Fod	666.000	mm
Flange Face Inside Diameter	Fid	600.000	mm
Flange Facing Sketch		Sketch 1a	
Gasket Outside Diameter	Go	655.000	mm
Gasket Inside Diameter	Gi	629.000	mm
Gasket Factor	m	3.0000	
Gasket Design Seating Stress	y	68.95	N./mm ²
Gasket Thickness	tg	4.5000	mm
Raised face depth	Fd	0.0000	mm





PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 22 of 173

Flg Calc [Int P]: FLANGE

Flng: 5 9:52am Aug 12, 2026

ASME Code, Section VIII Division 1, 2025

Hub Small End Required Thickness due to Internal Pressure:

$$= (P \cdot (D/2 + Ca)) / (S \cdot E - 0.6 \cdot P) \text{ per UG-27 (c)(1)}$$

$$= (1191.5 \cdot (600.0/2 + 3.175)) / (138.0 \cdot 1.0 - 0.6 \cdot 1191.5) + Ca$$

$$= 5.8065 \text{ mm}$$

Small End Hub MAWP:

$$= (S \cdot E \cdot t) / (R + 0.6 \cdot t) \text{ per UG-27 (c)(1)}$$

$$= (138.0 \cdot 1.0 \cdot 6.355) / (303.175 + 0.6 \cdot 6.355)$$

$$= 2856.539 \text{ KPa.}$$

Hub Small End Hub MAPnc:

$$= (Sa \cdot E \cdot t) / (R + 0.6 \cdot t) \text{ per UG-27 (c)(1)}$$

$$= (138.0 \cdot 1.0 \cdot 9.53) / (300.0 + 0.6 \cdot 9.53)$$

$$= 4301.480 \text{ KPa.}$$

Corroded Flange Thickness, $t_c = T - c_i$	56.825 mm
Corroded Flange ID, $B_{cor} = B + 2 \cdot c_i$	606.350 mm
Corroded Large Hub, $g1_{cor} = g1 - c_i$	9.825 mm
Corroded Small Hub, $g0_{cor} = g0 - c_i$	6.355 mm
Code R Dimension, $R = ((C - B_{cor})/2) - g1_{cor}$	32.000 mm

Gasket Contact Width, $N = (G_o - G_i)/2$	13.000 mm
Basic Gasket Width, $bo = N/2$	6.500 mm
Effective Gasket Width, $b = Cb \cdot \sqrt{bo}$	6.425 mm
Gasket Reaction Diameter, $G = G_o - 2 \cdot b$	642.151 mm

Basic Flange and Bolt Loads:

Hydrostatic End Load due to Pressure [H or Wo,1]:

$$= \pi/4 \cdot G^2 \cdot P$$

$$= \pi/4 \cdot 642.1509^2 \cdot 1191.5$$

$$= 39350.895 \text{ Kgf}$$

Contact Load on Gasket Surfaces [Hp or Wo,2]:

$$= 2 \cdot b \cdot \pi \cdot G \cdot m \cdot P$$

$$= 2 \cdot 6.4246 \cdot \pi \cdot 642.1509 \cdot 3.0 \cdot 1191.5$$

$$= 9448.699 \text{ Kgf}$$

Hydrostatic End Load at Flange ID [Hd]:

$$= \pi/4 \cdot B_{cor}^2 \cdot P$$

$$= \pi/4 \cdot 606.35^2 \cdot 1191.5$$

$$= 35085.465 \text{ Kgf}$$

Pressure Force on Flange Face [Ht]:

$$= H - Hd$$

$$= 39351 - 35085$$

$$= 4265.428 \text{ Kgf}$$

Design Bolt Load for the Operating Condition [Wo]:

$$= \max(Wo,1 + Wo,2 + H'p, 0)$$

$$= \max(39351 + 9449 + 0, 0)$$

$$= 48799.594 \text{ Kgf}$$

Design Bolt Load for the Gasket Seating Condition [Wg]:

$$= y \cdot b \cdot \pi \cdot G + y_{Part} \cdot b_{Part} \cdot l_p$$

$$= 68.95 \cdot 6.4246 \cdot \pi \cdot 642.151 + 0.0 \cdot 0.0 \cdot 0.0$$

$$= 91124.641 \text{ Kgf}$$

Required Bolt Area [Am]:

$$= \max((Wo + Fa + 4Me/G)/Sb, Wg/Sa)$$

$$= \max((48800 + 0 + 4 \cdot 0/642.15)/172, 91125/172)$$

$$= 51.957 \text{ cm}^2$$



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 23 of 173

Flg Calc [Int P]: FLANGE

Flng: 5 9:52am Aug 12,2026

ASME Maximum Circumferential Spacing between Bolts, Table 4.16.11 [Bsmax]:

$$= 2a + 6t/(m + 0.5)$$

$$= 2 \cdot 19.05 + 6 \cdot 56.825/(3.0 + 0.5)$$

$$= 135.514 \text{ mm}$$

Actual Circumferential Bolt Spacing [Bs]:

$$= C \cdot \sin(\pi / n)$$

$$= 690.0 \cdot \sin(\pi/28)$$

$$= 77.255 \text{ mm}$$

ASME Moment Multiplier for Bolt Spacing per Table 4.16.11 [Bsc]:

$$= \max(\sqrt{Bs/(2a + t)}, 1)$$

$$= \max(\sqrt{77.255/(2 \cdot 19.05 + 56.825)}, 1)$$

$$= 1.0000$$

Bolting Information for TEMA Imperial Thread Series (Non Mandatory):

	Minimum	Actual	Maximum
Bolt Area:	51.957	54.555	
Radial Distance between Hub and Bolts:	28.575	32.000	
Radial Distance between Bolts and Edge:	20.637	25.000	
Circ. Spacing between the Bolts:	44.450	77.255	135.514

Min. Gasket Contact Width (Brownell Young) [Not an ASME Calc] [Nmin]:

$$= Ab \cdot Sa / (y \cdot \pi(Go + Gi))$$

$$= 54.555 \cdot 172.0 / (68.95 \cdot \pi(655.0 + 629.0))$$

$$= 3.374 \text{ mm}$$

Flange Design Bolt Load, Gasket Seating [W or Wgs]:

$$= Sa(Am + Ab) / 2$$

$$= 172.0(51.957 + 54.5547) / 2$$

$$= 93402.66 \text{ Kgf}$$

Gasket Load for the Operating Condition [HG]:

$$= Wo - H$$

$$= 48800 - 39351$$

$$= 9448.70 \text{ Kgf}$$

Moment Arm Calculations:

Distance to Gasket Load Reaction [hg]:

$$= (C - G) / 2$$

$$= (690.0 - 642.1509) / 2$$

$$= 23.9246 \text{ mm}$$

Distance to Face Pressure Reaction [ht]:

$$= 0.5((C - B) / 2 + hg)$$

$$= 0.5((690.0 - 606.35) / 2 + 23.9246)$$

$$= 32.8748 \text{ mm}$$

Distance to End Pressure Reaction [hd]:

$$= (C - B - g1) / 2$$

$$= (690.0 - 606.35 - 9.825) / 2$$

$$= 36.9125 \text{ mm}$$

Summary of Moments for Internal Pressure: (Kg-m.)

Loading	Force	Distance	Bolt Corr	Moment
End Pressure, Md	35085.	36.9125	1.0000	1295.
Face Pressure, Mt	4265.	32.8748	1.0000	140.
Gasket Load, Mg	9449.	23.9246	1.0000	226.
Gasket Seating, Matm	93403.	23.9246	1.0000	2235.



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 24 of 173

Flg Calc [Int P]: FLANGE

Flng: 5 9:52am Aug 12, 2026

Total Moment for Operation, Mo 1661. Kg-m.
Total Moment for Gasket seating, Mg 2235. Kg-m.

Effective Hub Length, ho = sqrt(Bcor*goCor) 62.075 mm
Hub Ratio, h/h0 = HL / H0 0.230
Thickness Ratio, g1/g0 = (g1Cor/goCor) 1.546

Flange Factors for Integral Flange:

Factor F per 4.16.5 0.894
Factor V per 4.16.5 0.391
Factor f per 4.16.5 1.483

Stress factor from Table 4.16.4 [K]:

= A / B
= 740.0/606.35
= 1.220

Stress factor from Table 4.16.4 [Y]:

= (0.66845 + (5.7169(K² • log10(K))) / (K² - 1))/(K - 1)
= (0.66845 + (5.7169(1.22² • log10(1.22))) / (1.22² - 1))/(1.22 - 1)
= 9.861

Stress factor from Table 4.16.4 [T]:

= (K²(1 + 8.55246 • log10(K)) - 1) / ((1.0472 + 1.9448 • K²) • (K - 1))
= (1.22²(1 + 8.55246 • log10(1.22)) - 1) / ((1.0472 + 1.9448 • 1.22²) • (1.22 - 1))
= 1.831

Stress factor from Table 4.16.4 [U]:

= (K²(1 + 8.55246 • log10(K)) - 1) / (1.36136(K² - 1) • (K - 1))
= (1.22²(1 + 8.55246 • log10(1.22)) - 1) / (1.36136(1.22² - 1) • (1.22 - 1))
= 10.836

Stress factor from Table 4.16.4 [Z]:

= (K² + 1) / (K² - 1)
= (1.22² + 1) / (1.22² - 1)
= 5.086

Stress factor from Table 4.16.4 for integral flanges [d]:

= U • g0² • h0 / V
= 10.836 • 6.355² • 62.075 / 0.391
= 69423.953 mm³

Stress factor from Table 4.16.4 for integral flanges [e]:

= F / h0
= 0.894/62.075
= 0.014 1/mm

Stress factor from Table 4.16.4 [L]:

= (t • e + 1) / T + t³/d
= (56.825 • 0.014 + 1) / 1.831 + 56.825³/69423.953
= 3.636

Flange Stresses

Longitudinal Hub Stress, Operating [SHo]:

= (f • Mop / Bcor) / (L • g1²)
= (1.4827•1661/606.35)/(3.6363•9.825²)
= 113.50 N./mm²

Longitudinal Hub Stress, Seating [SHa]:

= (f • Matm / Bcor) / (L • g1²)
= (1.4827•2235/606.35)/(3.6363•9.825²)
= 152.67 N./mm²



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 25 of 173

Flg Calc [Int P]: FLANGE

Flng: 5 9:52am Aug 12, 2026

Radial Flange Stress, Operating [SRo]:

$$= (\beta \cdot Mop / Bcor) / (L \cdot t^2)$$

$$= (2.091 \cdot 1661 / 606.35) / (3.6363 \cdot 56.825^2)$$

$$= 4.79 \text{ N./mm}^2$$

Radial Flange Stress, Seating [SRa]:

$$= (\beta \cdot Matm / Bcor) / (L \cdot t^2)$$

$$= (2.091 \cdot 2235 / 606.35) / (3.6363 \cdot 56.825^2)$$

$$= 6.44 \text{ N./mm}^2$$

Tangential Flange Stress, Operating [STo]:

$$= (Y \cdot Mo / (t^2 \cdot Bcor)) - Z \cdot SRo$$

$$= (9.8609 \cdot 1661 / (56.825^2 \cdot 606.35)) - 5.0865 \cdot 5$$

$$= 57.72 \text{ N./mm}^2$$

Tangential Flange Stress, Seating [STa]:

$$= (y \cdot Matm / (t^2 \cdot Bcor)) - Z \cdot SRa$$

$$= (9.8609 \cdot 2235 / (56.825^2 \cdot 606.35)) - 5.0865 \cdot 6$$

$$= 77.63 \text{ N./mm}^2$$

Average Flange Stress, Operating [SAo]:

$$= (SHo + \max(SRo, STo)) / 2$$

$$= (114 + \max(5, 58)) / 2$$

$$= 85.61 \text{ N./mm}^2$$

Average Flange Stress, Seating [SAa]:

$$= (SHa + \max(SRa, STa)) / 2$$

$$= (153 + \max(6, 78)) / 2$$

$$= 115.15 \text{ N./mm}^2$$

Bolt Stress, Operating [BSo]:

$$= Wm1 / Ab$$

$$= 48800 / 54.5547$$

$$= 87.72 \text{ N./mm}^2$$

Bolt Stress, Seating [BSa]:

$$= (Wm2 / Ab)$$

$$= (91125 / 54.5547)$$

$$= 163.81 \text{ N./mm}^2$$

Flange Stress Analysis Results: N./mm²

	Actual	Operating Allowed	Gasket Actual	Seating Allowed
Longitudinal Hub	113.50	207.00	152.67	207.00
Radial Flange	4.79	138.00	6.44	138.00
Tangential Flange	57.72	138.00	77.63	138.00
Maximum Average	85.61	138.00	115.15	138.00
Bolting	87.72	172.00	163.81	172.00

Minimum Required Flange Thickness 54.839 mm

Estimated M.A.W.P. (Operating) 1921 KPa.

Estimated Finished Weight of Flange at given Thk. 70.9 kg.

Estimated Unfinished Weight of Forging at given Thk 84.8 kg.

Flange rigidity based on required thickness [ASME]:

Flange Rigidity Criterion, Seating per Table 4.16.10 [Jg]:

$$= 52.14 \cdot Ma / Bsc \cdot Cnvfac \cdot V / (\lambda \cdot Eamb \cdot go^2 \cdot ho \cdot Ki)$$

$$= 52.14 \cdot 2234.7 / 1.0 \cdot 9806.637 \cdot 0.391 / (2.936 \cdot 202713 \cdot 6.355^2 \cdot 62.075 \cdot 0.3)$$

$$= 0.998 \text{ (should be } \leq 1)$$

Flange Rigidity Criterion, Operating per Table 4.16.10 [Jo]:



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 26 of 173

Flg Calc [Int P]: FLANGE

Flng: 5 9:52am Aug 12,2026

$$= 52.14 \cdot Mo / Bsc \cdot Cnvfac \cdot V / (\lambda \cdot Eop \cdot goc^2 \cdot ho \cdot Ki)$$

$$= 52.14 \cdot 1661.4 / 1.0 \cdot 9806.637 \cdot 0.391 / (2.936 \cdot 199531 \cdot 6.355^2 \cdot 62.075 \cdot 0.3)$$

$$= 0.754 \text{ (should be } \leq 1)$$

Flange rigidity based on given thickness [ASME]:

Flange Rigidity Criterion, Seating per Table 4.16.10 [Jg]:

$$= 52.14 \cdot Ma / Bsc \cdot Cnvfac \cdot V / (\lambda \cdot Eamb \cdot go^2 \cdot ho \cdot Ki)$$

$$= 52.14 \cdot 2234.7 / 1.0 \cdot 9806.637 \cdot 0.391 / (3.636 \cdot 202713 \cdot 6.355^2 \cdot 62.075 \cdot 0.3)$$

$$= 0.806 \text{ (should be } \leq 1)$$

Flange Rigidity Criterion, Operating per Table 4.16.10 [Jo]:

$$= 52.14 \cdot Mo / Bsc \cdot Cnvfac \cdot V / (\lambda \cdot Eop \cdot goc^2 \cdot ho \cdot Ki)$$

$$= 52.14 \cdot 1661.4 / 1.0 \cdot 9806.637 \cdot 0.391 / (3.636 \cdot 199531 \cdot 6.355^2 \cdot 62.075 \cdot 0.3)$$

$$= 0.609 \text{ (should be } \leq 1)$$

Minimum Design Metal Temperature Results:

Thickness Ratio = 0.751, Temperature Reduction per Fig. UCS 66.1 = 14 °C

Min Metal Temp. w/o impact per UCS-66, Curve B -29 °C

Min Metal Temp. at Required thickness (UCS 66.1) -43 °C

Note: UCS-66(b)(-c) was considered in the flange MDMT calculation.

Per ASME VIII-2, 4.16.2.3, Perform Calculations in the New Condition:

Flange Stress Analysis Results: N./mm²

	Actual	Operating Allowed	Gasket Actual	Seating Allowed
Longitudinal Hub	93.27	207.00	121.11	207.00
Radial Flange	6.69	138.00	8.69	138.00
Tangential Flange	40.90	138.00	53.10	138.00
Maximum Average	67.08	138.00	87.11	138.00
Bolting	87.72	172.00	163.81	172.00

Minimum Req'd Thickness, ambient, no Corrosion: 43.307 mm

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 27 of 173

Flg Calc [Int P]: New Flange


Flng: 6 9:52am Aug 12,2026

Flange Input Data Values

Description: New Flange :

Chnl. flange frnt

Flange Type	Integral Weld Neck		
Design Pressure	P	1191.50	KPa.
Design Temperature		77	°C
Internal Corrosion Allowance	ci	3.1750	mm
External Corrosion Allowance	ce	0.0000	mm
Use Corrosion Allowance in Thickness Calcs.		Yes	
Flange Inside Diameter	B	600.000	mm
Flange Outside Diameter	A	740.000	mm
Flange Thickness	t	60.0000	mm
Thickness of Hub at Small End	go	9.5300	mm
Thickness of Hub at Large End	gl	13.0000	mm
Length of Hub	h	14.3000	mm
Flange Material		SA-266 2	
Flange Material UNS number		K03506	
Flange Allowable Stress At Temperature	Sfo	138.00	N./mm ²
Flange Allowable Stress At Ambient	Sfa	138.00	N./mm ²
Bolt Material		SA-193 B7	
Bolt Allowable Stress At Temperature	Sb	172.00	N./mm ²
Bolt Allowable Stress At Ambient	Sa	172.00	N./mm ²
Diameter of Bolt Circle	C	690.000	mm
Nominal Bolt Diameter	a	19.0500	mm
Type of Threads	TEMA Thread Series		
Number of Bolts		28	
Flange Face Outside Diameter	Fod	666.000	mm
Flange Face Inside Diameter	Fid	600.000	mm
Flange Facing Sketch		Sketch 1a	
Gasket Outside Diameter	Go	655.000	mm
Gasket Inside Diameter	Gi	629.000	mm
Gasket Factor	m	3.0000	
Gasket Design Seating Stress	y	68.95	N./mm ²
Gasket Thickness	tg	4.5000	mm
Raised face depth	Fd	0.0000	mm





PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 28 of 173

Flg Calc [Int P]: New Flange

Flng: 6 9:52am Aug 12, 2026

ASME Code, Section VIII Division 1, 2025

Hub Small End Required Thickness due to Internal Pressure:

$$= (P \cdot (D/2 + Ca)) / (S \cdot E - 0.6 \cdot P) \text{ per UG-27 (c)(1)}$$

$$= (1191.5 \cdot (600.0/2 + 3.175)) / (138.0 \cdot 1.0 - 0.6 \cdot 1191.5) + Ca$$

$$= 5.8065 \text{ mm}$$

Small End Hub MAWP:

$$= (S \cdot E \cdot t) / (R + 0.6 \cdot t) \text{ per UG-27 (c)(1)}$$

$$= (138.0 \cdot 1.0 \cdot 6.355) / (303.175 + 0.6 \cdot 6.355)$$

$$= 2856.539 \text{ KPa.}$$

Hub Small End Hub MAPnc:

$$= (Sa \cdot E \cdot t) / (R + 0.6 \cdot t) \text{ per UG-27 (c)(1)}$$

$$= (138.0 \cdot 1.0 \cdot 9.53) / (300.0 + 0.6 \cdot 9.53)$$

$$= 4301.480 \text{ KPa.}$$

Corroded Flange Thickness, $t_c = T - c_i$	56.825 mm
Corroded Flange ID, $B_{cor} = B + 2 \cdot c_i$	606.350 mm
Corroded Large Hub, $g1_{cor} = g1 - c_i$	9.825 mm
Corroded Small Hub, $g0_{cor} = g0 - c_i$	6.355 mm
Code R Dimension, $R = ((C - B_{cor})/2) - g1_{cor}$	32.000 mm

Gasket Contact Width, $N = (G_o - G_i)/2$	13.000 mm
Basic Gasket Width, $bo = N/2$	6.500 mm
Effective Gasket Width, $b = Cb \cdot \sqrt{bo}$	6.425 mm
Gasket Reaction Diameter, $G = G_o - 2 \cdot b$	642.151 mm

Basic Flange and Bolt Loads:

Hydrostatic End Load due to Pressure [H or Wo,1]:

$$= \pi/4 \cdot G^2 \cdot P$$

$$= \pi/4 \cdot 642.1509^2 \cdot 1191.5$$

$$= 39350.895 \text{ Kgf}$$

Contact Load on Gasket Surfaces [Hp or Wo,2]:

$$= 2 \cdot b \cdot \pi \cdot G \cdot m \cdot P$$

$$= 2 \cdot 6.4246 \cdot \pi \cdot 642.1509 \cdot 3.0 \cdot 1191.5$$

$$= 9448.699 \text{ Kgf}$$

Hydrostatic End Load at Flange ID [Hd]:

$$= \pi/4 \cdot B_{cor}^2 \cdot P$$

$$= \pi/4 \cdot 606.35^2 \cdot 1191.5$$

$$= 35085.465 \text{ Kgf}$$

Pressure Force on Flange Face [Ht]:

$$= H - Hd$$

$$= 39351 - 35085$$

$$= 4265.428 \text{ Kgf}$$

Design Bolt Load for the Operating Condition [Wo]:

$$= \max(Wo,1 + Wo,2 + H'p, 0)$$

$$= \max(39351 + 9449 + 0, 0)$$

$$= 48799.594 \text{ Kgf}$$

Design Bolt Load for the Gasket Seating Condition [Wg]:

$$= y \cdot b \cdot \pi \cdot G + y_{Part} \cdot b_{Part} \cdot l_p$$

$$= 68.95 \cdot 6.4246 \cdot \pi \cdot 642.151 + 0.0 \cdot 0.0 \cdot 0.0$$

$$= 91124.641 \text{ Kgf}$$

Required Bolt Area [Am]:

$$= \max((Wo + Fa + 4Me/G)/Sb, Wg/Sa)$$

$$= \max((48800 + 0 + 4 \cdot 0/642.15)/172, 91125/172)$$

$$= 51.957 \text{ cm}^2$$



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 29 of 173

Flg Calc [Int P]: New Flange

Flng: 6 9:52am Aug 12,2026

ASME Maximum Circumferential Spacing between Bolts, Table 4.16.11 [Bsmax]:

$$= 2a + 6t/(m + 0.5)$$

$$= 2 \cdot 19.05 + 6 \cdot 56.825/(3.0 + 0.5)$$

$$= 135.514 \text{ mm}$$

Actual Circumferential Bolt Spacing [Bs]:

$$= C \cdot \sin(\pi / n)$$

$$= 690.0 \cdot \sin(\pi/28)$$

$$= 77.255 \text{ mm}$$

ASME Moment Multiplier for Bolt Spacing per Table 4.16.11 [Bsc]:

$$= \max(\sqrt{Bs/(2a + t)}, 1)$$

$$= \max(\sqrt{77.255/(2 \cdot 19.05 + 56.825)}, 1)$$

$$= 1.0000$$

Bolting Information for TEMA Imperial Thread Series (Non Mandatory):

	Minimum	Actual	Maximum
Bolt Area:	51.957	54.555	
Radial Distance between Hub and Bolts:	28.575	32.000	
Radial Distance between Bolts and Edge:	20.637	25.000	
Circ. Spacing between the Bolts:	44.450	77.255	135.514

Min. Gasket Contact Width (Brownell Young) [Not an ASME Calc] [Nmin]:

$$= Ab \cdot Sa / (y \cdot \pi(Go + Gi))$$

$$= 54.555 \cdot 172.0 / (68.95 \cdot \pi(655.0 + 629.0))$$

$$= 3.374 \text{ mm}$$

Flange Design Bolt Load, Gasket Seating [W or Wgs]:

$$= Sa(Am + Ab) / 2$$

$$= 172.0(51.957 + 54.5547) / 2$$

$$= 93402.66 \text{ Kg}$$

Gasket Load for the Operating Condition [HG]:

$$= Wo - H$$

$$= 48800 - 39351$$

$$= 9448.70 \text{ Kg}$$

Moment Arm Calculations:

Distance to Gasket Load Reaction [hg]:

$$= (C - G) / 2$$

$$= (690.0 - 642.1509) / 2$$

$$= 23.9246 \text{ mm}$$

Distance to Face Pressure Reaction [ht]:

$$= 0.5((C - B) / 2 + hg)$$

$$= 0.5((690.0 - 606.35) / 2 + 23.9246)$$

$$= 32.8748 \text{ mm}$$

Distance to End Pressure Reaction [hd]:

$$= (C - B - g1) / 2$$

$$= (690.0 - 606.35 - 9.825) / 2$$

$$= 36.9125 \text{ mm}$$

Summary of Moments for Internal Pressure: (Kg-m.)

Loading	Force	Distance	Bolt Corr	Moment
End Pressure, Md	35085.	36.9125	1.0000	1295.
Face Pressure, Mt	4265.	32.8748	1.0000	140.
Gasket Load, Mg	9449.	23.9246	1.0000	226.
Gasket Seating, Matm	93403.	23.9246	1.0000	2235.



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 30 of 173

Flg Calc [Int P]: New Flange

Flng: 6 9:52am Aug 12, 2026

Total Moment for Operation, Mo 1661. Kg-m.
Total Moment for Gasket seating, Mg 2235. Kg-m.

Effective Hub Length, ho = sqrt(Bcor*goCor) 62.075 mm
Hub Ratio, h/h0 = HL / H0 0.230
Thickness Ratio, g1/g0 = (g1Cor/goCor) 1.546

Flange Factors for Integral Flange:

Factor F per 4.16.5 0.894
Factor V per 4.16.5 0.391
Factor f per 4.16.5 1.483

Stress factor from Table 4.16.4 [K]:

= A / B
= 740.0/606.35
= 1.220

Stress factor from Table 4.16.4 [Y]:

= (0.66845 + (5.7169(K² • log10(K)) / (K² - 1)) / (K - 1)
= (0.66845 + (5.7169(1.22² • log10(1.22)) / (1.22² - 1)) / (1.22 - 1)
= 9.861

Stress factor from Table 4.16.4 [T]:

= (K²(1 + 8.55246 • log10(K)) - 1) / ((1.0472 + 1.9448 • K²) • (K - 1))
= (1.22²(1 + 8.55246 • log10(1.22)) - 1) / ((1.0472 + 1.9448 • 1.22²) • (1.22 - 1))
= 1.831

Stress factor from Table 4.16.4 [U]:

= (K²(1 + 8.55246 • log10(K)) - 1) / (1.36136(K² - 1) • (K - 1))
= (1.22²(1 + 8.55246 • log10(1.22)) - 1) / (1.36136(1.22² - 1) • (1.22 - 1))
= 10.836

Stress factor from Table 4.16.4 [Z]:

= (K² + 1) / (K² - 1)
= (1.22² + 1) / (1.22² - 1)
= 5.086

Stress factor from Table 4.16.4 for integral flanges [d]:

= U • g0² • h0 / V
= 10.836 • 6.355² • 62.075 / 0.391
= 69423.953 mm³

Stress factor from Table 4.16.4 for integral flanges [e]:

= F / h0
= 0.894/62.075
= 0.014 1/mm

Stress factor from Table 4.16.4 [L]:

= (t • e + 1) / T + t³/d
= (56.825 • 0.014 + 1) / 1.831 + 56.825³/69423.953
= 3.636

Flange Stresses

Longitudinal Hub Stress, Operating [SHo]:

= (f • Mop / Bcor) / (L • g1²)
= (1.4827•1661/606.35)/(3.6363•9.825²)
= 113.50 N./mm²

Longitudinal Hub Stress, Seating [SHa]:

= (f • Matm / Bcor) / (L • g1²)
= (1.4827•2235/606.35)/(3.6363•9.825²)
= 152.67 N./mm²



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 31 of 173

Flg Calc [Int P]: New Flange

Flng: 6 9:52am Aug 12, 2026

Radial Flange Stress, Operating [SRo]:

$$= (\beta \cdot Mop / Bcor) / (L \cdot t^2)$$

$$= (2.091 \cdot 1661 / 606.35) / (3.6363 \cdot 56.825^2)$$

$$= 4.79 \text{ N./mm}^2$$

Radial Flange Stress, Seating [SRa]:

$$= (\beta \cdot Matm / Bcor) / (L \cdot t^2)$$

$$= (2.091 \cdot 2235 / 606.35) / (3.6363 \cdot 56.825^2)$$

$$= 6.44 \text{ N./mm}^2$$

Tangential Flange Stress, Operating [STo]:

$$= (Y \cdot Mo / (t^2 \cdot Bcor)) - Z \cdot SRo$$

$$= (9.8609 \cdot 1661 / (56.825^2 \cdot 606.35)) - 5.0865 \cdot 5$$

$$= 57.72 \text{ N./mm}^2$$

Tangential Flange Stress, Seating [STa]:

$$= (y \cdot Matm / (t^2 \cdot Bcor)) - Z \cdot SRa$$

$$= (9.8609 \cdot 2235 / (56.825^2 \cdot 606.35)) - 5.0865 \cdot 6$$

$$= 77.63 \text{ N./mm}^2$$

Average Flange Stress, Operating [SAo]:

$$= (SHo + \max(SRo, STo)) / 2$$

$$= (114 + \max(5, 58)) / 2$$

$$= 85.61 \text{ N./mm}^2$$

Average Flange Stress, Seating [SAa]:

$$= (SHa + \max(SRa, STa)) / 2$$

$$= (153 + \max(6, 78)) / 2$$

$$= 115.15 \text{ N./mm}^2$$

Bolt Stress, Operating [BSo]:

$$= Wm1 / Ab$$

$$= 48800 / 54.5547$$

$$= 87.72 \text{ N./mm}^2$$

Bolt Stress, Seating [BSa]:

$$= (Wm2 / Ab)$$

$$= (91125 / 54.5547)$$

$$= 163.81 \text{ N./mm}^2$$

Flange Stress Analysis Results: N./mm²

	Actual	Operating Allowed	Gasket Actual	Seating Allowed
Longitudinal Hub	113.50	207.00	152.67	207.00
Radial Flange	4.79	138.00	6.44	138.00
Tangential Flange	57.72	138.00	77.63	138.00
Maximum Average	85.61	138.00	115.15	138.00
Bolting	87.72	172.00	163.81	172.00

Minimum Required Flange Thickness 54.839 mm

Estimated M.A.W.P. (Operating) 1921 KPa.

Estimated Finished Weight of Flange at given Thk. 70.9 kg.

Estimated Unfinished Weight of Forging at given Thk 84.8 kg.

Flange rigidity based on required thickness [ASME]:

Flange Rigidity Criterion, Seating per Table 4.16.10 [Jg]:

$$= 52.14 \cdot Ma / Bsc \cdot Cnvfac \cdot V / (\lambda \cdot Eamb \cdot go^2 \cdot ho \cdot Ki)$$

$$= 52.14 \cdot 2234.7 / 1.0 \cdot 9806.637 \cdot 0.391 / (2.936 \cdot 202713 \cdot 6.355^2 \cdot 62.075 \cdot 0.3)$$

$$= 0.998 \text{ (should be } \leq 1)$$

Flange Rigidity Criterion, Operating per Table 4.16.10 [Jo]:



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 32 of 173

Flg Calc [Int P]: New Flange

Flng: 6 9:52am Aug 12,2026

$$= 52.14 \cdot Mo / Bsc \cdot Cnvfac \cdot V / (\lambda \cdot Eop \cdot goc^2 \cdot ho \cdot Ki)$$

$$= 52.14 \cdot 1661.4 / 1.0 \cdot 9806.637 \cdot 0.391 / (2.936 \cdot 199531 \cdot 6.355^2 \cdot 62.075 \cdot 0.3)$$

$$= 0.754 \text{ (should be } \leq 1)$$

Flange rigidity based on given thickness [ASME]:

Flange Rigidity Criterion, Seating per Table 4.16.10 [Jg]:

$$= 52.14 \cdot Ma / Bsc \cdot Cnvfac \cdot V / (\lambda \cdot Eamb \cdot go^2 \cdot ho \cdot Ki)$$

$$= 52.14 \cdot 2234.7 / 1.0 \cdot 9806.637 \cdot 0.391 / (3.636 \cdot 202713 \cdot 6.355^2 \cdot 62.075 \cdot 0.3)$$

$$= 0.806 \text{ (should be } \leq 1)$$

Flange Rigidity Criterion, Operating per Table 4.16.10 [Jo]:

$$= 52.14 \cdot Mo / Bsc \cdot Cnvfac \cdot V / (\lambda \cdot Eop \cdot goc^2 \cdot ho \cdot Ki)$$

$$= 52.14 \cdot 1661.4 / 1.0 \cdot 9806.637 \cdot 0.391 / (3.636 \cdot 199531 \cdot 6.355^2 \cdot 62.075 \cdot 0.3)$$

$$= 0.609 \text{ (should be } \leq 1)$$

Minimum Design Metal Temperature Results:

Thickness Ratio = 0.751, Temperature Reduction per Fig. UCS 66.1 = 14 °C

Min Metal Temp. w/o impact per UCS-66, Curve B -29 °C

Min Metal Temp. at Required thickness (UCS 66.1) -43 °C

Note: UCS-66(b)(-c) was considered in the flange MDMT calculation.

Per ASME VIII-2, 4.16.2.3, Perform Calculations in the New Condition:

Flange Stress Analysis Results: N./mm²

	Actual	Operating Allowed	Gasket Actual	Seating Allowed
Longitudinal Hub	93.27	207.00	121.11	207.00
Radial Flange	6.69	138.00	8.69	138.00
Tangential Flange	40.90	138.00	53.10	138.00
Maximum Average	67.08	138.00	87.11	138.00
Bolting	87.72	172.00	163.81	172.00

Minimum Req'd Thickness, ambient, no Corrosion: 43.307 mm

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 33 of 173

Internal Pressure Calculations: Step: 5 9:52am Aug 12,2026

Internal Pressure Results Summary:

Element Thickness, Pressure, Diameter and Allowable Stress :

From	To	Int. Press + Liq. Hd KPa.	Nominal Thickness mm	Total Corr Allowance mm	Element Diameter mm	Allowable Stress(SE) N./mm ²	Element#
Chnl. cover rea		1197.4	9.53	3.175	600	118	1
Chnl. rear		1197.4	9.53	3.175	600	118	2
Chnl. flange rer		1191.5	68	3.175	600	138	3
Shell		1549.8	9.53	3.175	600	140.75	4
Chnl. flange frn		1191.5	68	3.175	600	138	5
Chnl. front		1197.4	9.53	3.175	600	118	6
Chnl. front		1197.4	9.53	3.175	600	118	7

Element Required Thickness and MAWP :

From	To	Design Pressure KPa.	M.A.W.P. Corroded KPa.	M.A.P. New & Cold KPa.	Minimum Thickness mm	Required Thickness mm	Element#
Chnl. cover rea		1191.5	2028.73	3271.06	8.34	6.21251	1
Chnl. rear		1191.5	2436.64	3678.08	9.53	6.27057	2
Chnl. flange rer		1191.5	1920.61	2336.16	60	54.8386	3
Shell		1549.5	2913.3	5018.39	9.53	6.53556	4
Chnl. flange frn		1191.5	1920.61	2336.16	60	54.8386	5
Chnl. front		1191.5	2436.64	3678.08	9.53	6.27057	6
Chnl. front		1191.5	2028.73	3271.06	8.34	6.21251	7

Warning: Channel Side MAWP governed by a standard Flange!

Summary of Heat Exchanger Maximum Allowable Working Pressures :

Note:

For Exchanger designs, the following values include MAWPs that consider the tubesheet, tubes, tube/tubesheet joint etc. These values were determined by iteration. Review the tubesheet analysis report for more information.

Shell Side MAWP = 2819 KPa.
 Shell Side MAPnc = 5018 KPa.
 Channel Side MAWP = 1835 KPa.
 Channel Side MAPnc = 1960 KPa.


Elements Suitable for Design Internal Pressure.

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



Internal Pressure Calculation Results:

ASME Code, Section VIII Division 1, 2025



Internal Pressure Results for: Chnl. cover rea

Elliptical Head Design Information:			
Design Pressure P	1197.412 KPa.	Int. Design Temperature	77 °C
Material	SA-234 WPB	Ext. Design Temperature	40 °C
Length	76.200 mm	External Pressure Chart	CS-2
		UNS Number	K03006
Int. Corr. All. c	3.1750 mm	Allowable Stress (ope) S	118.0 N./mm ²
Ext. Corr. All. ce	0.0000 mm	Allowable Stress (amb) Sa	118.0 N./mm ²
Inside Diameter Di	600.000 mm	Actual Stress	69.4 N./mm ²
Spec. Min. Thk t _e , or sa	8.3400 mm	Spec. Nominal Thk.	9.530 mm
Surface Area	5636.2 cm ²	SG of Contents	1.000
Element Volume	49828.3 cm ³	Weight of Contents	49.8 Kg
Empty Weight	43.6 Kg	Operating Weight	93.4 Kg
		Comp. All. Ope. Stress	125.7 N./mm ²
		Aspect Ratio	2.00

Radiography Information:			
User Defined		User Defined	
Circ. Joint Efficiency	100 %	Long. Joint Eff. E or v	100 %

Tolerance for Formed Heads per UG-81(a):

Head inner surface maximum deviation outside the specified shape, 1.25% of D: 7.500 mm

Head inner surface maximum deviation inside the specified shape, 0.625% of D: 3.750 mm

Required Thickness due to Internal Pressure [tr]:

$$= (P \cdot D \cdot K_{cor}) / (2 \cdot S \cdot E - 0.2 \cdot P) \text{ Appendix 1-4(c)}$$

$$= (1197.412 \cdot 606.35 \cdot 0.986) / (2 \cdot 118.0 \cdot 1.0 - 0.2 \cdot 1197.412)$$

$$= 3.0375 + 3.1750 = 6.2125 \text{ mm}$$

Max. Allowable Working Pressure at given Thickness, corroded [MAWP]:

Less Operating Hydrostatic Head Pressure of 5.912 KPa.

$$= (2 \cdot S \cdot E \cdot t) / (K_{cor} \cdot D + 0.2 \cdot t) \text{ per Appendix 1-4 (c)}$$

$$= (2 \cdot 118.0 \cdot 1.0 \cdot 5.165) / (0.986 \cdot 606.35 + 0.2 \cdot 5.165)$$

$$= 2035 - 6 = 2029 \text{ KPa.}$$

Maximum Allowable Pressure, New and Cold [MAPNC]:

$$= (2 \cdot S \cdot E \cdot t) / (K \cdot D + 0.2 \cdot t) \text{ per Appendix 1-4 (c)}$$

$$= (2 \cdot 118.0 \cdot 1.0 \cdot 8.34) / (1.0 \cdot 600.0 + 0.2 \cdot 8.34)$$

$$= 3271 \text{ KPa.}$$



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 35 of 173

Element: Chnl. cover rea

Step: 6 9:52am Aug 12,2026

Actual stress at given pressure and thickness, corroded [Sact]:

$$= (P \cdot (K_{cor} \cdot D + 0.2 \cdot t)) / (2 \cdot E \cdot t)$$

$$= (1197.412 \cdot (0.986 \cdot 606.35 + 0.2 \cdot 5.165)) / (2 \cdot 1.0 \cdot 5.165)$$

$$= 69.443 \text{ N./mm}^2$$

Straight Flange Required Thickness:

$$= (P \cdot R) / (S \cdot E - 0.6 \cdot P) + c \text{ per UG-27 (c)(1)}$$

$$= (1197.412 \cdot 303.175) / (118.0 \cdot 1.0 - 0.6 \cdot 1197.412) + 3.175$$

$$= 6.271 \text{ mm}$$

Straight Flange Maximum Allowable Working Pressure:

[Less Operating Hydrostatic Head Pressure of 5.912 KPa.](#)

$$= (S \cdot E \cdot t) / (R + 0.6 \cdot t) \text{ per UG-27 (c)(1)}$$

$$= (118.0 \cdot 1.0 \cdot 6.355) / (303.175 + 0.6 \cdot 6.355)$$

$$= 2443 - 6 = 2437 \text{ KPa.}$$

Factor K, corroded condition [Kcor]:

$$= (2 + (\text{Inside Diameter} / (2 \cdot \text{Inside Head Depth}))^2) / 6$$

$$= (2 + (606.35 / (2 \cdot 153.175))^2) / 6$$

$$= 0.986253$$

MDMT Calculations in the Knuckle Portion:

Govrn. thk, tg = 8.34, tr = 4.658, c = 3.175 mm, E* = 1.0

Thickness Ratio = tr * E* / (tg - c) = 0.902, Temp. Reduction = 5 °C

Min Metal Temp. w/o impact per UCS-66, Curve B -29 °C
Min Metal Temp. at Required thickness (UCS 66.1) -34 °C

MDMT Calculations in the Head Straight Flange:

Govrn. thk, tg = 9.53, tr = 4.76, c = 3.175 mm, E* = 1.0

Thickness Ratio = tr * E* / (tg - c) = 0.749, Temp. Reduction = 14 °C

Min Metal Temp. w/o impact per UCS-66, Curve B -29 °C
Min Metal Temp. at Required thickness (UCS 66.1) -43 °C

MDMT Design Information:			
MDMT Curve	B	Press. at MDMT	1835.358 KPa.
UCS-66(b) red.	Yes	Min. Des. Mtl. Temp.	11 °C
Governing Thk.	9.530 mm	Basic MDMT	-29 °C
Stress/Thk. Ratio	0.749	Temperature Difference	14 °C
UCS-66(c) red.	No	Computed Min. Temp.	-43 °C
		MDMT per UG-20(f)	-29 °C
		Joint Efficiency E*	100 %

Note: Temperature values displayed above are for the location with the highest basic MDMT

Tolerance for Formed Heads per UG-81(a):

Head inner surface maximum deviation outside the specified shape, 1.25% of D: 7.500 mm

Head inner surface maximum deviation inside the specified shape, 0.625% of D: 3.750 mm

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP


Page 36 of 173

Element: Chnl. rear

Step: 7 9:52am Aug 12,2026

Internal Pressure Calculation Results:

ASME Code, Section VIII Division 1, 2025



Internal Pressure Results for: Chnl. rear

Cylindrical Shell Design Information:			
Design Pressure P	1197.412 KPa.	Int. Design Temperature	77 °C
Material	SA-106 B	Ext. Design Temperature	40 °C
Length	600.000 mm	External Pressure Chart	CS-2
		UNS Number	K03006
Int. Corr. All. c	3.1750 mm	Allowable Stress (ope) S	118.0 N./mm ²
Ext. Corr. All. ce	0.0000 mm	Allowable Stress (amb) Sa	118.0 N./mm ²
Inside Diameter Di	600.000 mm	Actual Stress	57.8 N./mm ²
Spec. Min. Thk t,e, or sa	9.5300 mm	Spec. Nominal Thk.	9.530 mm
Surface Area	11669.0 cm ²	SG of Contents	1.000
Element Volume	169676.4 cm ³	Weight of Contents	169.6 Kg
Empty Weight	84.9 Kg	Operating Weight	254.4 Kg
		Comp. All. Ope. Stress	130.8 N./mm ²

Radiography Information:			
User Defined		User Defined	
Circ. Joint Efficiency	100 %	Long. Joint Eff.	E or v 100 %

Required Thickness due to Internal Pressure [tr]:

$$\begin{aligned}
 &= (P \cdot R) / (S \cdot E - 0.6 \cdot P) \text{ per UG-27 (c)(1)} \\
 &= (1197.412 \cdot 303.175) / (118.0 \cdot 1.0 - 0.6 \cdot 1197.412) \\
 &= 3.0956 + 3.1750 = 6.2706 \text{ mm}
 \end{aligned}$$

Max. Allowable Working Pressure at given Thickness, corroded [MAWP]:

$$\begin{aligned}
 &\text{Less Operating Hydrostatic Head Pressure of 5.912 KPa.} \\
 &= (S \cdot E \cdot t) / (R + 0.6 \cdot t) \text{ per UG-27 (c)(1)} \\
 &= (118.0 \cdot 1.0 \cdot 6.355) / (303.175 + 0.6 \cdot 6.355) \\
 &= 2443 - 6 = 2437 \text{ KPa.}
 \end{aligned}$$

Maximum Allowable Pressure, New and Cold [MAPNC]:

$$\begin{aligned}
 &= (S \cdot E \cdot t) / (R + 0.6 \cdot t) \text{ per UG-27 (c)(1)} \\
 &= (118.0 \cdot 1.0 \cdot 9.53) / (300.0 + 0.6 \cdot 9.53) \\
 &= 3678 \text{ KPa.}
 \end{aligned}$$

Actual stress at given pressure and thickness, corroded [Sact]:

$$\begin{aligned}
 &= (P \cdot (R + 0.6 \cdot t)) / (E \cdot t) \\
 &= (1197.412 \cdot (303.175 + 0.6 \cdot 6.355)) / (1.0 \cdot 6.355) \\
 &= 57.846 \text{ N./mm}^2
 \end{aligned}$$



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 37 of 173

Element: Chnl. rear

Step: 7 9:52am Aug 12,2026

Minimum Design Metal Temperature Results:

Govrn. thk, tg = 8.34, tr = 2.351, c = 3.175 mm, E* = 1.0
Thickness Ratio = $tr * E*/(tg - c) = 0.455$, Temp. Reduction = 39 °C

Min Metal Temp. w/o impact per UCS-66, Curve B -29 °C
Min Metal Temp. at Required thickness (UCS 66.1) -48 °C


MDMT Design Information:			
MDMT Curve	B	Press. at MDMT	1835.358 KPa.
UCS-66(b) red.	Yes	Min. Des. Mtl. Temp.	11 °C
Governing Thk.	8.340 mm	Basic MDMT	-29 °C
Stress/Thk. Ratio	0.455	Temperature Difference	19 °C
UCS-66(c) red.	No	Computed Min. Temp.	-48 °C
		MDMT per UG-20(f)	-29 °C
		Joint Efficiency E*	100 %

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



Internal Pressure Calculation Results:

ASME Code, Section VIII Division 1, 2025



Internal Pressure Results for: Shell

Cylindrical Shell Design Information:			
Design Pressure P	1549.796 KPa.	Int. Design Temperature	166 °C
Material	SA-106 B	Ext. Design Temperature	40 °C
Length	4790.000 mm	External Pressure Chart	CS-2
		UNS Number	K03006
Int. Corr. All. c	3.1750 mm	Allowable Stress (ope) S	140.8 N./mm ²
Ext. Corr. All. ce	0.0000 mm	Allowable Stress (amb) Sa	161.0 N./mm ²
Inside Diameter Di	600.000 mm	Actual Stress	74.9 N./mm ²
Spec. Min. Thk t _e , or sa	9.5300 mm	Spec. Nominal Thk.	9.530 mm
Surface Area	93157.6 cm ²	SG of Contents	0.050
Element Volume	848208.5 cm ³	Weight of Contents	42.4 Kg
Empty Weight	677.5 Kg	Operating Weight	719.9 Kg
		Comp. All. Ope. Stress	126.1 N./mm ²

Radiography Information:			
User Defined		User Defined	
Circ. Joint Efficiency	100 %	Long. Joint Eff.	E or v 100 %

Required Thickness due to Internal Pressure [tr]:

$$\begin{aligned}
 &= (P \cdot R) / (S \cdot E - 0.6 \cdot P) \text{ per UG-27 (c)(1)} \\
 &= (1549.796 \cdot 303.175) / (140.75 \cdot 1.0 - 0.6 \cdot 1549.796) \\
 &= 3.3606 + 3.1750 = 6.5356 \text{ mm}
 \end{aligned}$$

Max. Allowable Working Pressure at given Thickness, corroded [MAWP]:

$$\begin{aligned}
 &\text{Less Operating Hydrostatic Head Pressure of 0.296 KPa.} \\
 &= (S \cdot E \cdot t) / (R + 0.6 \cdot t) \text{ per UG-27 (c)(1)} \\
 &= (140.75 \cdot 1.0 \cdot 6.355) / (303.175 + 0.6 \cdot 6.355) \\
 &= 2914 - 0 = 2913 \text{ KPa.}
 \end{aligned}$$

Maximum Allowable Pressure, New and Cold [MAPNC]:

$$\begin{aligned}
 &= (S \cdot E \cdot t) / (R + 0.6 \cdot t) \text{ per UG-27 (c)(1)} \\
 &= (161.0 \cdot 1.0 \cdot 9.53) / (300.0 + 0.6 \cdot 9.53) \\
 &= 5018 \text{ KPa.}
 \end{aligned}$$

Actual stress at given pressure and thickness, corroded [Sact]:

$$\begin{aligned}
 &= (P \cdot (R + 0.6 \cdot t)) / (E \cdot t) \\
 &= (1549.796 \cdot (303.175 + 0.6 \cdot 6.355)) / (1.0 \cdot 6.355) \\
 &= 74.870 \text{ N./mm}^2
 \end{aligned}$$



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 39 of 173

Element: Shell

Step: 8 9:52am Aug 12,2026

Minimum Design Metal Temperature Results:

Govrn. thk, tg = 9.53, tr = 2.645, c = 3.175 mm, E* = 1.0
Thickness Ratio = $tr * E* / (tg - c) = 0.416$, Temp. Reduction = 47 °C

Min Metal Temp. w/o impact per UCS-66, Curve B -29 °C
Min Metal Temp. at Required thickness (UCS 66.1) -48 °C

MDMT Design Information:			
MDMT Curve	B	Press. at MDMT	2819.390 KPa.
UCS-66(b) red.	Yes	Min. Des. Mtl. Temp.	11 °C
Governing Thk.	9.530 mm	Basic MDMT	-29 °C
Stress/Thk. Ratio	0.416	Temperature Difference	19 °C
UCS-66(c) red.	No	Computed Min. Temp.	-48 °C
		MDMT per UG-20(f)	-29 °C
		Joint Efficiency E*	100 %

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP


Page 40 of 173

Element: Chnl. front

Step: 9 9:52am Aug 12,2026

Internal Pressure Calculation Results:

ASME Code, Section VIII Division 1, 2025



Internal Pressure Results for: Chnl. front

Cylindrical Shell Design Information:			
Design Pressure P	1197.412 KPa.	Int. Design Temperature	77 °C
Material	SA-106 B	Ext. Design Temperature	40 °C
Length	600.000 mm	External Pressure Chart	CS-2
		UNS Number	K03006
Int. Corr. All. c	3.1750 mm	Allowable Stress (ope) S	118.0 N./mm ²
Ext. Corr. All. ce	0.0000 mm	Allowable Stress (amb) Sa	118.0 N./mm ²
Inside Diameter Di	600.000 mm	Actual Stress	57.8 N./mm ²
Spec. Min. Thk t,e, or sa	9.5300 mm	Spec. Nominal Thk.	9.530 mm
Surface Area	11669.0 cm ²	SG of Contents	1.000
Element Volume	169676.4 cm ³	Weight of Contents	169.6 Kg
Empty Weight	84.9 Kg	Operating Weight	254.4 Kg
		Comp. All. Ope. Stress	130.8 N./mm ²

Radiography Information:			
User Defined		User Defined	
Circ. Joint Efficiency	100 %	Long. Joint Eff.	E or v 100 %

Required Thickness due to Internal Pressure [tr]:

$$\begin{aligned}
 &= (P \cdot R) / (S \cdot E - 0.6 \cdot P) \text{ per UG-27 (c)(1)} \\
 &= (1197.412 \cdot 303.175) / (118.0 \cdot 1.0 - 0.6 \cdot 1197.412) \\
 &= 3.0956 + 3.1750 = 6.2706 \text{ mm}
 \end{aligned}$$

Max. Allowable Working Pressure at given Thickness, corroded [MAWP]:

Less Operating Hydrostatic Head Pressure of 5.912 KPa.

$$\begin{aligned}
 &= (S \cdot E \cdot t) / (R + 0.6 \cdot t) \text{ per UG-27 (c)(1)} \\
 &= (118.0 \cdot 1.0 \cdot 6.355) / (303.175 + 0.6 \cdot 6.355) \\
 &= 2443 - 6 = 2437 \text{ KPa.}
 \end{aligned}$$

Maximum Allowable Pressure, New and Cold [MAPNC]:

$$\begin{aligned}
 &= (S \cdot E \cdot t) / (R + 0.6 \cdot t) \text{ per UG-27 (c)(1)} \\
 &= (118.0 \cdot 1.0 \cdot 9.53) / (300.0 + 0.6 \cdot 9.53) \\
 &= 3678 \text{ KPa.}
 \end{aligned}$$

Actual stress at given pressure and thickness, corroded [Sact]:

$$\begin{aligned}
 &= (P \cdot (R + 0.6 \cdot t)) / (E \cdot t) \\
 &= (1197.412 \cdot (303.175 + 0.6 \cdot 6.355)) / (1.0 \cdot 6.355) \\
 &= 57.846 \text{ N./mm}^2
 \end{aligned}$$

PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 41 of 173

Element: Chnl. front

Step: 9 9:52am Aug 12, 2026

Minimum Design Metal Temperature Results:

Govrn. thk, $t_g = 9.53$, $t_r = 2.351$, $c = 3.175$ mm, $E^* = 1.0$

Thickness Ratio = $tr * E^*/(tg - c) = 0.37$, Temp. Reduction = 63 °C

Min Metal Temp. w/o impact per UCS-66, Curve B -29 °C


Min Metal Temp. at Required thickness (UCS 66.1) -48 °C

MDMT Design Information:			
MDMT Curve	B	Press. at MDMT	1835.358 KPa.
UCS-66(b) red.	Yes	Min. Des. Mtl. Temp.	11 °C
Governing Thk.	9.530 mm	Basic MDMT	-29 °C
Stress/Thk. Ratio	0.370	Temperature Difference	19 °C
UCS-66(c) red.	No	Computed Min. Temp.	-48 °C
		MDMT per UG-20(f)	-29 °C
		Joint Efficiency E*	100 %



Internal Pressure Calculation Results:

ASME Code, Section VIII Division 1, 2025



Internal Pressure Results for: Chnl. front

Elliptical Head Design Information:			
Design Pressure P	1197.412 KPa.	Int. Design Temperature	77 °C
Material	SA-234 WPB	Ext. Design Temperature	40 °C
Length	76.200 mm	External Pressure Chart	CS-2
		UNS Number	K03006
Int. Corr. All. c	3.1750 mm	Allowable Stress (ope) S	118.0 N./mm ²
Ext. Corr. All. ce	0.0000 mm	Allowable Stress (amb) Sa	118.0 N./mm ²
Inside Diameter Di	600.000 mm	Actual Stress	69.4 N./mm ²
Spec. Min. Thk t,e, or sa	8.3400 mm	Spec. Nominal Thk.	9.530 mm
Surface Area	5636.2 cm ²	SG of Contents	1.000
Element Volume	49828.3 cm ³	Weight of Contents	49.8 Kg
Empty Weight	43.6 Kg	Operating Weight	93.4 Kg
		Comp. All. Ope. Stress	130.8 N./mm ²
		Aspect Ratio	2.00

Radiography Information:			
User Defined		User Defined	
Circ. Joint Efficiency	100 %	Long. Joint Eff. E or v	100 %

Tolerance for Formed Heads per UG-81(a):

Head inner surface maximum deviation outside the specified shape, 1.25% of D: 7.500 mm

Head inner surface maximum deviation inside the specified shape, 0.625% of D: 3.750 mm

Required Thickness due to Internal Pressure [tr]:

$$= (P \cdot D \cdot K_{cor}) / (2 \cdot S \cdot E - 0.2 \cdot P) \text{ Appendix 1-4(c)}$$

$$= (1197.412 \cdot 606.35 \cdot 0.986) / (2 \cdot 118.0 \cdot 1.0 - 0.2 \cdot 1197.412)$$

$$= 3.0375 + 3.1750 = 6.2125 \text{ mm}$$

Max. Allowable Working Pressure at given Thickness, corroded [MAWP]:

Less Operating Hydrostatic Head Pressure of 5.912 KPa.

$$= (2 \cdot S \cdot E \cdot t) / (K_{cor} \cdot D + 0.2 \cdot t) \text{ per Appendix 1-4 (c)}$$

$$= (2 \cdot 118.0 \cdot 1.0 \cdot 5.165) / (0.986 \cdot 606.35 + 0.2 \cdot 5.165)$$

$$= 2035 - 6 = 2029 \text{ KPa.}$$

Maximum Allowable Pressure, New and Cold [MAPNC]:

$$= (2 \cdot S \cdot E \cdot t) / (K \cdot D + 0.2 \cdot t) \text{ per Appendix 1-4 (c)}$$

$$= (2 \cdot 118.0 \cdot 1.0 \cdot 8.34) / (1.0 \cdot 600.0 + 0.2 \cdot 8.34)$$

$$= 3271 \text{ KPa.}$$



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 43 of 173

Element: Chnl. front

Step: 10 9:52am Aug 12,2026

Actual stress at given pressure and thickness, corroded [Sact]:

$$= (P \cdot (K_{cor} \cdot D + 0.2 \cdot t)) / (2 \cdot E \cdot t)$$

$$= (1197.412 \cdot (0.986 \cdot 606.35 + 0.2 \cdot 5.165)) / (2 \cdot 1.0 \cdot 5.165)$$

$$= 69.443 \text{ N./mm}^2$$

Straight Flange Required Thickness:

$$= (P \cdot R) / (S \cdot E - 0.6 \cdot P) + c \text{ per UG-27 (c)(1)}$$

$$= (1197.412 \cdot 303.175) / (118.0 \cdot 1.0 - 0.6 \cdot 1197.412) + 3.175$$

$$= 6.271 \text{ mm}$$

Straight Flange Maximum Allowable Working Pressure:

[Less Operating Hydrostatic Head Pressure of 5.912 KPa.](#)

$$= (S \cdot E \cdot t) / (R + 0.6 \cdot t) \text{ per UG-27 (c)(1)}$$

$$= (118.0 \cdot 1.0 \cdot 6.355) / (303.175 + 0.6 \cdot 6.355)$$

$$= 2443 - 6 = 2437 \text{ KPa.}$$

Factor K, corroded condition [Kcor]:

$$= (2 + (\text{Inside Diameter} / (2 \cdot \text{Inside Head Depth})))^2 / 6$$

$$= (2 + (606.35 / (2 \cdot 153.175)))^2 / 6$$

$$= 0.986253$$

MDMT Calculations in the Knuckle Portion:

Govrn. thk, tg = 8.34, tr = 4.658, c = 3.175 mm, E* = 1.0

Thickness Ratio = tr * E* / (tg - c) = 0.902, Temp. Reduction = 5 °C

Min Metal Temp. w/o impact per UCS-66, Curve B -29 °C
Min Metal Temp. at Required thickness (UCS 66.1) -34 °C

MDMT Calculations in the Head Straight Flange:

Govrn. thk, tg = 9.53, tr = 4.76, c = 3.175 mm, E* = 1.0

Thickness Ratio = tr * E* / (tg - c) = 0.749, Temp. Reduction = 14 °C

Min Metal Temp. w/o impact per UCS-66, Curve B -29 °C
Min Metal Temp. at Required thickness (UCS 66.1) -43 °C

MDMT Design Information:			
MDMT Curve	B	Press. at MDMT	1835.358 KPa.
UCS-66(b) red.	Yes	Min. Des. Mtl. Temp.	11 °C
Governing Thk.	9.530 mm	Basic MDMT	-29 °C
Stress/Thk. Ratio	0.749	Temperature Difference	14 °C
UCS-66(c) red.	No	Computed Min. Temp.	-43 °C
		MDMT per UG-20(f)	-29 °C
		Joint Efficiency E*	100 %

Note: Temperature values displayed above are for the location with the highest basic MDMT

Tolerance for Formed Heads per UG-81(a):

Head inner surface maximum deviation outside the specified shape, 1.25% of D: 7.500 mm

Head inner surface maximum deviation inside the specified shape, 0.625% of D: 3.750 mm

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 44 of 173

Shop Pressure Test Results: Step: 11 9:52am Aug 12,2026

Hydrostatic Test Pressure Results:

Exchanger Shell Side Hydrostatic Test Pressures:

UG99(b)	= 1.30 * M.A.W.P. * Sa/S	3665.206 KPa.
UG99b(b)(35)	= 1.30 * Design Pres * Sa/S	2014.350 KPa.
UG99(c)	= 1.30 * M.A.P. - Head(Hyd)	6518.030 KPa.
UG100	= 1.10 * M.A.W.P. * Sa/S	3101.329 KPa.
PED	= max(1.43*DP, 1.25*DP*ratio)	2215.785 KPa.
PED&UG99(b)(35)	= max(1.43*DP, 1.3*DP*ratio)	2215.785 KPa.
App 27-4	= M.A.W.P.	2819.390 KPa.

Exchanger Channel Side Hydrostatic Test Pressures:

UG99(b)	= 1.30 * M.A.W.P. * Sa/S	2385.965 KPa.
UG99b(b)(35)	= 1.30 * Design Pres * Sa/S	1548.950 KPa.
UG99(c)	= 1.30 * M.A.P. - Head(Hyd)	2548.008 KPa.
UG100	= 1.10 * M.A.W.P. * Sa/S	2018.894 KPa.
PED	= max(1.43*DP, 1.25*DP*ratio)	1703.845 KPa.
PED&UG99(b)(35)	= max(1.43*DP, 1.3*DP*ratio)	1703.845 KPa.
App 27-4	= M.A.W.P.	1835.358 KPa.

Horizontal Test performed per: UG-99b

Please note that Nozzle, Shell, Head, Flange, etc MAWPs are all considered when determining the hydrotest pressure for those test types that are based on the MAWP of the vessel.

Stresses on Elements due to Test Pressure (N./mm² & KPa.):

From To	Stress	Allowable	Ratio	Pressure
Chnl. cover rea	86.3	153.4	0.562	2391.85
Chnl. rear	76.7	153.4	0.500	2391.85
Shell	117.8	228.0	0.517	3671.09
Chnl. front	76.7	153.4	0.500	2391.85
Chnl. front	86.3	153.4	0.562	2391.85

Stress ratios for Nozzle and Pad Materials (N./mm²):

Description	Pad/Nozzle	Ambient	Operating	Ratio
N1- Channel inle	Nozzle	118.00	118.00	1.000
N1- Channel inle	Pad	138.00	138.00	1.000
N1- Shell outlet	Nozzle	118.00	118.00	1.000
N1- Shell outlet	Pad	138.00	138.00	1.000
N2- shell inlet	Nozzle	118.00	118.00	1.000
N2- shell inlet	Pad	138.00	138.00	1.000
N2- Channel outl	Nozzle	118.00	118.00	1.000
N2- Channel outl	Pad	138.00	138.00	1.000

Minimum

1.000

Stress ratios for Pressurized Vessel Elements (N./mm²):

Description	Ambient	Operating	Ratio
Chnl. cover rea	118.00	118.00	1.000
Chnl. rear	118.00	118.00	1.000
Chnl. flange rer	138.00	138.00	1.000
Shell	161.00	140.75	1.144
Chnl. flange frnt	138.00	138.00	1.000
Chnl. front	118.00	118.00	1.000



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 45 of 173

Shop Pressure Test Results: Step: 11 9:52am Aug 12, 2026

Chnl. front	118.00	118.00	1.000
-------------	--------	--------	-------

Minimum	1.000
---------	-------

Stress ratios for Exchanger Materials (N./mm²):

Description	Ambient	Operating	Ratio
Tube Material	92.40	92.40	1.000
Tubesheet Material	138.00	138.00	1.000

Minimum	1.000
---------	-------

Hoop Stress in Nozzle Wall during Pressure Test (N./mm²):

Description	Ambient	Operating	Ratio
N1- Channel inle	17.38	153.40	0.113
N1- Shell outlet	31.75	153.40	0.207
N2- shell inlet	32.60	153.40	0.213
N2- Channel outl	17.38	153.40	0.113

Elements Suitable for Test Pressure.

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 46 of 173

ASME TS Calc: Pressure Test

Case: 1 9:52a Aug 12, 2026

Input Echo, Tubesheet Number 1, Description: Fixed tubesheet

Shell Data:

Main Shell Description: Shell

Shell Test Pressure		3665.21 KPa.
Shell Thickness	ts	9.5300 mm
Shell Internal Corrosion Allowance	cas	0.0000 mm
Shell External Corrosion Allowance	casext	0.0000 mm
Inside Diameter of Shell	Ds	600.000 mm
Shell Circumferential Joint Efficiency	Esw	1.000
Shell Temperature for Internal Pressure	Ts	21.11 °C
Shell Material		SA-106 B

See ASME VIII Div. 1, UG-23(e), for determination of the SPS allowable.

Shell Material UNS Number		K03006
Shell Allowable Stress at Temperature	Ss	118.00 N./mm ²
Shell Allowable Stress at Ambient		118.00 N./mm ²

Channel Data:

Channel Description: Chnl. rear

Channel Type:		Cylinder
Channel Test Pressure		2385.97 KPa.
Channel Thickness	tc	9.5300 mm
Channel Internal Corrosion Allowance	cac	0.0000 mm
Channel External Corrosion Allowance	cacext	0.0000 mm
Inside Diameter of Channel	Dc	600.000 mm
Channel Design Temperature	TEMPC	21.11 °C
Channel Flange Matl		SA-106 B

See ASME VIII Div. 1, UG-23(e), for determination of the SPS allowable.

Channel Material UNS Number		K03006
Channel Allowable Stress at Temperature	Sc	118.00 N./mm ²
Channel Allowable Stress at Ambient		118.00 N./mm ²

Tube Data:

Number of Tube Holes	Nt	534
Tube Wall Thickness	et	2.1080 mm
Tube Outside Diameter	D	15.8750 mm
Total Straight Tube Length	Lt	4877.00 mm
Straight Tube Length (bet. inner tubsht faces) L		4773.00 mm
Design Temperature of the Tubes		21.11 °C
Tube Material		SA-179
Tube Material UNS Number		K01200
Is this a Welded Tube		No
Tube Material Specification used		Smls. tube
Tube Allowable Stress at Temperature		92.40 N./mm ²
Tube Allowable Stress At Ambient		92.40 N./mm ²
Tube Yield Stress At design Temperature	Syt	180.00 N./mm ²
Tube Pitch (Center to Center Spacing)	P	19.8440 mm
Tube Layout Pattern		Triangular

Fillet Weld Leg	af	2.0000 mm
Groove Weld Leg	ag	2.0000 mm
Tube-Tubesheet Joint Weld Type		Full Strength
Method for Tube-Tubesheet Jt. Allowable		UW-20.3
Is the Tube Inset		No

Radius to Outermost Tube Hole Center	ro	284.388 mm
Largest Center-to-Center Tube Distance	Ul	0.0000 mm
Length of Expanded Portion of Tube	ltx	0.0000 mm
Tube-side pass partition groove depth	hg	0.0000 mm
Area of Tube Layout	Ap	1676.2 cm ²



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 47 of 173

ASME TS Calc: Pressure Test

Case: 1 9:52a Aug 12,2026

Perimeter of Tube Layout Cp 1676.1 mm

Tubesheet Data:

Tubesheet TYPE: Fixed Tubesheet Exchanger, Conf B

Tubesheet Design Metal Temperature T 21.11 °C
Tubesheet Material SA-266 2

See ASME VIII Div. 1, UG-23(e), for determination of the SPS allowable.

Tubesheet Material UNS Number		K03506
Tubesheet Allowable Stress at Temperature	S	138.00 N./mm ²
Tubesheet Allowable Stress at Ambient	Tt	138.00 N./mm ²
Thickness of Tubesheet	h	52.0000 mm
Tubesheet Corr. Allowance (Shell side)	Cats	0.0000 mm
Tubesheet Corr. Allowance (Channel side)	Catc	0.0000 mm
Tubesheet Outside Diameter	A	740.000 mm

Additional Data for Stepped Tubesheets:

Is the Tubesheet Stepped?		Yes
Is the Tubesheet Flat on Tubeside?		No
Step 1 Diameter on the Tubeside	dt1	663.00 mm
Step 1 Depth on the Tubeside	ht1	8.00 mm
Step 2 Diameter on the Tubeside	dt2	597.00 mm
Step 2 Depth on the Tubeside	ht2	8.00 mm
Is the Tubesheet Flat on Shellside?		No
Calculated Tubesheet Diameter per Div 2, 4.18.4		663.00 mm

Note: Tubesheet diameter is now: 663.000 mm Div 2, 4.18.4.

Area of the Untubed Lanes AL 0.0 cm²

Additional Data for Fixed/Floating Tubesheet Exchangers:

Unsupported Tube Span under consideration	l	0.000 mm
Tube End condition corresponding to Span (l)	k	0.00
Ignore Radial Thermal Exp. effects (4.18.8/4.18.9)		Yes
Perform Differential Pressure Design		No
Run Multiple Load Cases		Yes
Mean Shell Metal Temp. along Shell len.	Tsm	21.11 °C
Mean Tube Metal Temp. along Tube length	Ttm	21.11 °C
Junction Stress Reduction option		Perform Plastic Calculation

Additional Data for Gasketed Tubesheets:

Tubesheet Gasket on which Side		Channel
Flange Outside Diameter	A	740.000 mm
Flange Inside Diameter	B	600.000 mm
Flange Face Outside Diameter	Fod	666.000 mm
Flange Face Inside Diameter	Fid	600.000 mm
Gasket Outside Diameter	Go	655.000 mm
Gasket Inside Diameter	Gi	629.000 mm
Small end Hub thk.	g0	9.5300 mm
Large end Hub thk.	g1	13.0000 mm
Gasket Factor,	m	3.00
Gasket Design Seating Stress	y	68.95 N./mm ²
Flange Facing Sketch		Code Sketch 1a
Gasket Thickness	tg	4.5000 mm
Full face Gasket Flange Option		Program Selects

Bolting Information:

Diameter of Bolt Circle	C	690.000 mm
Nominal Bolt Diameter	dB	19.0500 mm
Thread Series		TEMA Thread Series



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 48 of 173

ASME TS Calc: Pressure Test


Case: 1 9:52a Aug 12, 2026

Number of Bolts	n	28
Bolt Material		SA-193 B7
Bolt Allowable Stress At Temperature	Sb	172.00 N./mm ²
Bolt Allowable Stress At Ambient	Sa	172.00 N./mm ²
Weld between Flange and Shell/Channel		0.0000 mm

Tubesheet Integral with		Shell
Tubesheet Extended as Flange		Yes
Thickness of Extended Portion of Tubesheet	Tf	36.0000 mm
Is Bolt Load Transferred to the Tubesheet		Yes

Is Exchanger in Creep range (skip EP, Use 3S for Sps) No

Tubesheet Integral w/Shell, Gasketed w/Channel, Extended as a Flange



Configuration b:

Messages regarding the Tubesheet & Exchanger Input Data:

Warning - Tube end condition k should be bet 0 - 1 (.00).

ASME TubeSheet Results per Part UHX/4.18, 2025

Elasticity/Expansion Material Properties:

Shell - TE-1 Carbon & Low Alloy Steels, Group 1
Shell - TM-1 Carbon Steels with C<= 0.3%

Th. Exp. Coeff. Metal Temp. along Len	21.1 °C	0.0000115191 /°C
Elastic Mod. at Design Temperature	21.1 °C	0.20270E+09 KPa.
Th. Exp. Coeff. Metal Temp. at Tubsht	21.1 °C	0.0000115191 /°C
Elastic Mod. at Metal Temp. along Len	21.1 °C	0.20270E+09 KPa.
Elastic Mod. at Ambient Temperature	21.1 °C	0.20270E+09 KPa.

Channel - TE-1 Carbon & Low Alloy Steels, Group 1
Channel - TM-1 Carbon Steels with C<= 0.3%

Th. Exp. Coeff. Metal Temp. at Tubsht	21.1 °C	0.0000115191 /°C
Elastic Mod. at Design Temperature	21.1 °C	0.20270E+09 KPa.
Elastic Mod. at Ambient Temperature	21.1 °C	0.20270E+09 KPa.



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 49 of 173

ASME TS Calc: Pressure Test

Case: 1 9:52a Aug 12, 2026

Tubes - TE-1 Carbon & Low Alloy Steels, Group 1
Tubes - TM-1 Carbon Steels with C<= 0.3%

Th. Exp. Coeff. Metal Temp. along Len	21.1 °C	0.0000115191 /°C
Elastic Mod. at Design Temperature	21.1 °C	0.20270E+09 KPa.
Elastic Mod. at Metal Temp. along Len	21.1 °C	0.20270E+09 KPa.
Elastic Mod. at Tubsht. Design Temp.	21.1 °C	0.20270E+09 KPa.
Elastic Mod. at Ambient Temperature	21.1 °C	0.20270E+09 KPa.

TubeSheet - TE-1 Carbon & Low Alloy Steels, Group 1
TubeSheet - TM-1 Carbon Steels with C<= 0.3%

Elastic Mod. at Design Temperature	21.1 °C	0.20270E+09 KPa.
Elastic Mod. at Ambient Temperature	21.1 °C	0.20270E+09 KPa.

Note:

The Elasticity and Alpha values are taken from Tables in ASME II D.

Please insure these properties are consistent with the type of Material for the tubes, shell, channel etc.

Tube Required Thickness under Internal Pressure (Tubeside pressure):

Thickness Due to Internal Pressure:

$$= (P \cdot (D/2 - CAE)) / (S \cdot E + 0.4 \cdot P) \text{ per Appendix 1-1 (a)(1)}$$

$$= (2385.97 \cdot (15.875/2 - 0)) / (92.4 \cdot 1.0 + 0.4 \cdot 2385.97)$$

$$= 0.2029 + 0.0000 = 0.2029 \text{ mm}$$

Tube Required Thickness under External Pressure (Shellside pressure) :

External Pressure Chart CS-1 at 21.11 °C
Elastic Modulus for Material 199943392.00 KPa.

Results for Max. Allowable External Pressure (Emawp):

TCA	ODCA	SLEN	D/T	L/D	Factor A	B
2.1080	15.88	4773.00	7.53	50.0000	0.0193957	95.84

EMAWP = $(2.167 / (D/T) - 0.0833) \cdot B = 19593.4844 \text{ KPa.}$

Results for Req'd Thickness for Ext. Pressure (Tca):

TCA	ODCA	SLEN	D/T	L/D	Factor A	B
0.5412	15.88	4773.00	29.33	50.0000	0.0012784	80.65

EMAWP = $(4 \cdot B) / (3 \cdot (D/T)) = (4 \cdot 80.6473) / (3 \cdot 29.3337) = 3665.5273 \text{ KPa.}$

Summary of Tube Required Thickness Results:

Total Required Thickness including Corrosion all.	0.5412 mm
Allowable Internal Pressure at Corroded thickness	27453.64 KPa.
Required Internal Design Pressure	2385.97 KPa.
Allowable External Pressure at Corroded thickness	19593.48 KPa.
Required External Design Pressure	3665.21 KPa.
Required Thickness due to Shell Side pressure	0.5412 mm

Detailed Results for load Case D3 un-corr. (Psd,max + Ptd,max)

Intermediate Calculations For Tubesheets Extended As Flanges:

ASME Code, Section VIII Division 1, 2025

Gasket Contact Width,	$N = (Goc - Gic) / 2$	13.000 mm
Basic Gasket Width,	$b0 = N / 2$	6.500 mm
Effective Gasket Width,	$b = \text{sqrt}(b0) \cdot 2.5$	6.422 mm
Gasket Reaction Diameter,	$G = Go - 2.0 \cdot b$	642.156 mm

Warning: Available bolt area, 54.555 cm² for the flange is < required 55.715 cm²



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 50 of 173

ASME TS Calc: Pressure Test

Case: 1 9:52a Aug 12, 2026

Note that for the pressure test case, ASME VIII-2 paragraph 4.18.13 (c)(9) does not require that the bolt area requirement be met.

Results for ASME Fixed Tubesheet Calculations for Configuration b:

Results for Tubesheet Calculations Original Thickness:

ASME Section VIII-2 Part 4.18.8.4 Step 1:

Tube expansion depth ratio [ρ]:

= l_{tx} / h (modified for corrosion if present)

= 0/52.0

= 0.0000 (must be $0 \leq \rho \leq 1$)

Effective tube hole diameter [d^*]:

= $\max(dt - 2 \cdot tt(EtT/E) \cdot (StT/S) \cdot (\rho); dt - 2 \cdot tt)$

= $\max(15.875 - 2 \cdot 2.108 (0.20270E+09/.20270E+09) \cdot (92/137) \cdot (0); 15.875 - 2 \cdot 2.108)$

= 15.8750 mm

Equivalent outer tube limit circle diameter [Do]:

= $2 \cdot r_o + dt$

= $2 \cdot 284.388 + 15.875$

= 584.651 mm

Determine the basic ligament efficiency for shear [μ]:

= $(p - dt) / p$

= $(19.844 - 15.875) / 19.844$

= 0.200

Equivalent outer tube limit radius [ao]:

= $Do / 2$

= $584.651 / 2$

= 292.3255 mm

Effective tube pitch [p^*]:

= $p / \sqrt{ (1 - 4 \cdot \min(AL \cdot CNVfactor; 4 \cdot Do \cdot p) / (\pi \cdot Do^2)) }$

= $19.844 / \sqrt{ (1 - 4 \cdot \min(0 \cdot 100.0; 4 \cdot 584.651 \cdot 19.844) / (\pi \cdot 584.651^2)) }$

= 19.8440 mm

Effective ligament efficiency for bending [μ^*]:

= $(p^* - d^*) / p^*$

= $(19.844 - 15.875) / 19.844$

= 0.2000

Ratio [ρ_s]:

= a_s / a_o

= $300.0 / 292.3255$

= 1.0263

Ratio [ρ_c]:

= a_c / a_o

= $321.0778 / 292.3255$

= 1.0984

Compute parameter [xt]:

= $1 - Nt((dt - 2 \cdot tt) / (2 \cdot a_o))^2$

= $1 - 534 ((15.875 - 2 \cdot 2.108) / (2 \cdot 292.3255))^2$

= 0.7876

Determine parameter [xs]:

= $1 - Nt(dt / (2 \cdot a_o))^2$

= $1 - 534 (15.875 / (2 \cdot 292.3255))^2$



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 51 of 173

ASME TS Calc: Pressure Test

Case: 1 9:52a Aug 12, 2026

= 0.6063

Determine the value [h'g]:

= max((hg - CATC); 0) (For pressure only cases)

= max((0 - 0); 0)

= 0.000 mm

ASME Section VIII-2 Part 4.18.8.4 Step 2:

Axial Shell Stiffness [Ks]:

= $\pi \cdot ts (Ds + ts) Es / L$

= $\pi \cdot 9.53 (600.0 + 9.53) \cdot 2.0270E+09 / 4773.0$

= 79031.3438 Kgf/mm

Axial Tube Stiffness [Kt]:

= $\pi \cdot tt (Dt - tt) Et / L$

= $\pi \cdot 2.108 (15.875 - 2.108) \cdot 2.0270E+09 / 4773.0$

= 394.8401 Kgf/mm

Stiffness Factor [Ks,t]:

= $Ks / (Nt \cdot Kt)$

= $79031.344 / (534 \cdot 394.84)$

= 0.37483

Rigidity Ratio [J]:

= $1 / (1 + Ks/Kj)$

= $1 / (1 + 79031.344/0)$

= 1.0000 (= 1 if No Exp. Jt.)

Shell coefficient [β_s]:

= $((12(1 - vs^2))^{1/4}) / ((Ds + ts)ts)$

= $((12(1 - 0.3^2))^{1/4}) / ((600.0 + 9.53)9.53)$

= 0.0239 1/mm

Shell coefficient [ks]:

= $\beta_s \cdot Es \cdot ts^3 / (6(1 - vs^2))$

= $0.024 \cdot 0.20270E+09 \cdot 9.53^3 / (6(1 - 0.3^2))$

= 766397568.0000 KPa.·mm²

Shell coefficient [λ_s]:

= $6(Ds + ts) \cdot ks / h^3 \cdot (1 + h \cdot \beta_s + (h \cdot \beta_s)^2/2)$

= $6(600.0 + 9.53) \cdot 0.76640E+09 / 52.0^3 \cdot (1 + 52.0 \cdot 0.024 + (52.0 \cdot 0.024)^2/2)$

= 59988764.0000 KPa.

Shell coefficient [δ_s]:

= $Ds^2 / (4 \cdot Es \cdot ts) \cdot (1 - Ds \cdot vs / (2(Ds + ts)))$

= $600.0^2 / (4 \cdot 0.20270E+09 \cdot 9.53) \cdot (1 - 600.0 \cdot 0.3 / (2(600.0 + 9.53)))$

= 0.39709E-01 mm/N./mm²

Intermediate parameters for Tubesheet Gasketed on the Channel Side:

β_C , k_C , λ_C , δ_C are all = 0

ASME Section VIII-2 Part 4.18.8.4 Step 3:

$h/p = 2.620440$; $\mu^* = 0.200010$; $E^* = 31491868$ KPa.

$E^*/E = 0.155361$; $\nu^* = 0.458557$

Note: As h/p (2.620) is > 2, data values for $h/p = 2$ were used.

Tube Bundle Stiffness Factor [X_a]:

= $((24(1 - \nu^*)Nt \cdot Et \cdot tt(dt - tt)ao^2) / (E^* \cdot L \cdot H^3))^{1/4}$

= $((24(1 - 0.459^2)534 \cdot 0.20270E+09 \cdot 2.108$

$(15.875 - 2.108)292.3255^2) / (31491868 \cdot 4773.0 \cdot 52.0^3))^{1/4}$

= 3.9390



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 52 of 173

ASME TS Calc: Pressure Test

Case: 1 9:52a Aug 12, 2026

Values from Table 4.18.3

$$\begin{aligned} Z_d &= 0.024674 ; Z_v = 0.062813 ; Z_m = 0.361181 \\ Z_a &= 0.658639E+01 ; Z_w = 0.062813 \end{aligned}$$

ASME Section VIII-2 Part 4.18.8.4 Step 4:

Diameter ratio [K]:

$$\begin{aligned} &= A / D_o \\ &= 663.0/584.651 \\ &= 1.1340 \end{aligned}$$

Compute coefficient [F]:

$$\begin{aligned} &= (1 - v^*) / E^* \cdot (\lambda_s + \lambda_c + E \cdot \ln(K)) \\ &= (1 - 0.46) / 31491868 \cdot (59988764 + 0 + 0.20270E+09 \cdot \ln(1.13)) \\ &= 1.4697 \end{aligned}$$

Compute parameter [φ]:

$$\begin{aligned} &= (1 + v^*) F \\ &= (1 + 0.4586) 1.4697 \\ &= 2.1436 \end{aligned}$$

Compute parameter [Q1]:

$$\begin{aligned} &= (\psi_s - 1 - \phi \cdot Z_v) / (1 + \phi \cdot Z_m) \\ &= (1.0263 - 1 - 2.1436 \cdot 0.0628) / (1 + 2.1436 \cdot 0.3612) \\ &= -0.061093 \end{aligned}$$

Compute Parameter [Qz1]:

$$\begin{aligned} &= (Z_d + Q1 \cdot Z_w) / 2 \cdot X_a^4 \\ &= (0.02467 + -0.06109 \cdot 0.06281) / 2 \cdot 3.93897^4 \\ &= 2.5080 \end{aligned}$$

Compute parameter [Qz2]:

$$\begin{aligned} &= (Z_v + Q1 \cdot Z_m) / 2 \cdot X_a^4 \\ &= (0.06281 + -0.06109 \cdot 0.36118) / 2 \cdot 3.93897^4 \\ &= 4.9045 \end{aligned}$$

Compute parameter [U]:

$$\begin{aligned} &= (Z_w + (\psi_s - 1) Z_m) X_a^4 / (1 + \phi \cdot Z_m) \\ &= (0.0628 + (1.0263 - 1) 0.3612) 3.93897^4 / (1 + 2.1436 \cdot 0.3612) \\ &= 9.8091 \end{aligned}$$

ASME Section VIII-2 Part 4.18.8.4 Step 5:

Determine factor [γb]:

$$\begin{aligned} &= (G_c - C) / D_o \text{ (config b)} \\ &= (642.1556 - 690.0) / 584.651 = -0.08183 \end{aligned}$$

Compute Parameter [γ]:

$$= 0.000 \text{ mm (For Pressure only cases)}$$

Calculate parameter [ωs]:

$$\begin{aligned} &= \psi_s \cdot k_s \cdot \beta_s \cdot \delta S (1 + h \cdot \beta_s) \\ &= 1.0263 \cdot 0.76640E+09 \cdot 0.0239 \cdot 0.039709 (1 + 52.0 \cdot 0.0239) \\ &= 1668.8943 \text{ mm}^2 \end{aligned}$$

Calculate parameter [ω*s]:

$$\begin{aligned} &= a o^2 (\psi_s^2 - 1) \cdot (\psi_s - 1) / 4 - \omega_s \\ &= 292.326^2 (1.026^2 - 1) \cdot (1.026 - 1) / 4 - 1668.894 \\ &= -1639.0586 \text{ mm}^2 \end{aligned}$$

Parameter [ωc]:

$$\begin{aligned} &= \rho_c \cdot k_c [\delta C (C_m \theta_{\text{Theta}} \cdot \beta_C + C_q \Delta \cdot h \cdot \beta_C^2) - \zeta_c (C_m \theta_{\text{Theta}} + h \cdot C_q \theta_{\text{Theta}} \cdot h \cdot \beta_C / 2)] \\ &= 1.098 \cdot 0 [0 (0 + 0 \cdot 0 \cdot 52.0) - \end{aligned}$$



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 53 of 173

ASME TS Calc: Pressure Test

Case: 1 9:52a Aug 12, 2026

$$0 (0/52.0 + 0 \cdot 0/2)) \\ = 0.0000 \text{ mm}^2$$

Parameter [$\omega \cdot c$]:

$$= a_o^2 [(p_c^2 + 1) \cdot (p_c - 1) / 4 - (p_s - 1) / 2] - \omega c \\ = 292.3255^2 [(1.09836^2 + 1) \cdot (1.09836 - 1) / 4 - (1.02625 - 1) / 2] - 0 \\ = 3514.4580 \text{ mm}^2$$

Pressure [$P \cdot S$]:

$$= 0 \text{ For Pressure only cases or Configurations d,e,f,A,B,C,D}$$

Pressure [$P \cdot C$]:

$$= 0 \text{ For Pressure only cases or Configurations b,c,d,B,C,D}$$

ASME Section VIII-2 Part 4.18.8.4 Step 6:

Pressure [$P's$]:

$$= P_s \{ x_s + 2(1 - x_s) v_t + [2/Kst \cdot (D_s/D_o)^2] v_s - \\ [(p_s^2 - 1) / (J \cdot Kst)] - [(1 - J) / (2J \cdot Kst)] [(D_j^2 - (D_s)^2) / D_o^2] \} \\ = 3665.206 \{ 0.606 + 2(1 - 0.606) 0.3 + [2/0.375 \cdot \\ (600.0/584.651)^2] 0.3 - [(1.026^2 - 1) / (1.0 \cdot 0.375)] - \\ [(1 - 1.0) / (2 \cdot 1.0 \cdot 0.375)] [(0^2 - (600.0)^2) / 584.651^2] \} \\ = 8746.8877 \text{ KPa.}$$

Pressure [$P't$]:

$$= [x_t + 2(1 - x_t) v_t + 1 / (J \cdot Kst)] P_t \\ = [0.788 + 2(1 - 0.788) 0.3 + 1 / (1. \cdot 0.375)] 2385.965 \\ = 8548.7168 \text{ KPa.}$$

Pressure [P_y]:

$$= N_t \cdot K_t \cdot \gamma / (\pi \cdot a_o^2) \\ = 534 \cdot 394.84 \cdot 0 / (3.142 \cdot 292.326^2) \\ = 0.0000 \text{ KPa.}$$

Pressure [P_w]:

$$= -\gamma_b \cdot U \cdot W \cdot / (2 \cdot \pi \cdot a_o^2) \\ = -0.082 \cdot 9.809 \cdot 97715.02 / (2 \cdot \pi \cdot 292.326^2) \\ = 1432.5645 \text{ KPa.}$$

Calculate the pressure [$Prim$]:

$$= - (U/a_o^2) \cdot (\omega \cdot s \cdot P_s - \omega \cdot c \cdot P_t) \\ = - (9.809/292.326^2) \cdot (-1639.059 \cdot 3665.206 - 3514.458 \cdot 2385.965) \\ = 1652.1196 \text{ KPa.}$$

Calculate the pressure [P_w]:

$$= (U/a_o^2) \cdot (\omega \cdot s \cdot P \cdot s - \omega \cdot c \cdot P \cdot c) \\ = (9.809/292.326^2) \cdot (1668.8943 \cdot 0 - 0 \cdot 0) \\ = 0.0000 \text{ KPa.}$$

Determine the effective pressure [Pe]:

$$= J \cdot Kst / (1 + J \cdot Kst(Qz1 + (p_s - 1) Qz2)) \cdot \\ (P's - P't + P_y + P_w + P_w + Prim) \\ = 0.1000E+01 \cdot 0.375 / (1 + 1.0 \cdot 0.375 (2.508 + (1.026 - \\ 1) 4.905)) \cdot (8746.888 - 8548.717 + 0 + 0 + 1432.564 + 1652.12) \\ = 618.8653 \text{ KPa.}$$

ASME Section VIII-2 Part 4.18.8.4 Step 7:

Determine factor [$Q2$]:

$$= [((\omega \cdot s \cdot P_s - \omega \cdot c \cdot P_t) - (\omega \cdot s \cdot P \cdot s - \omega \cdot c \cdot P \cdot c)) + \\ W \cdot \gamma_b / (2 \cdot \pi)] / (1 + \phi \cdot Z_m) \\ = [((-1639.059 \cdot 3665.206 - 3514.458 \cdot 2385.965) - \\ (1668.894 \cdot 0 - 0 \cdot 0)) \cdot 0. + \\ 97715.0 \cdot -0.082 / (2 \cdot \pi)] / (1 + 2.1436 \cdot 0.36118) \\ = -1544.5541 \text{ Kg}$$



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 54 of 173

ASME TS Calc: Pressure Test

Case: 1 9:52a Aug 12, 2026

Calculate factor [Q3]:

$$= Q1 + 2 \cdot Q2 / (Pe \cdot ao^2)$$

$$= -0.061 + 2 \cdot -1544.554 / (618.865 \cdot 292.326^2)$$

$$= -0.63390$$

Fm Value from Table 4.18.3 = 0.316949

Tubesheet Bending Stress - original thickness [σ]:

$$= (1.5 \cdot Fm / \mu \cdot) \cdot (2 \cdot ao / (h - h'g))^2 \cdot Pe$$

$$= (1.5 \cdot 0.3169 / 0.2) \cdot (2 \cdot 292.3255 / (52.0 - 0))^2 \cdot 618.87$$

$$= 185.9674 \text{ N./mm}^2$$

Allowable Tubesheet Bending Stress [σ allowed]:

$$= 1.5 \cdot \beta T \cdot Sy = 1.5 \cdot 0.95 \cdot 250.0 = 356.24 \text{ N./mm}^2, 4.18.233$$

Tubesheet Bending Stress - final thickness [σ]:

$$= (1.5 \cdot Fm / \mu \cdot) \cdot (2 \cdot ao / (h - h'g))^2 \cdot Pe$$

$$= (1.5 \cdot 0.2032 / 0.2) \cdot (2 \cdot 292.3255 / (34.487 - 0))^2 \cdot 813.23$$

$$= 356.2395 \text{ N./mm}^2$$

Reqd Tubesheet Thickness, for Bending Stress (including CA) [HReqB]:

$$= h + Cats + Catc$$

$$= 34.4874 + 0 + 0$$

$$= 34.4874 \text{ mm}$$

ASME Section VIII-2 Part 4.18.8.4 Step 8:

Shear Stress check [τ limit]:

$$= (2 \cdot \mu \cdot h / ao) \cdot (0.8 \cdot \beta T \cdot Sy)$$

$$= (2 \cdot 0.2 \cdot 52.0 / 292.326) \cdot 189.997$$

$$= 13.5196 \text{ N./mm}^2$$

Shear Stress is not required to be computed; [Pe] <= τ limit

Tubesheet Shear Stress is probably low, use the following req. thk:

$$\text{Tubesheet thickness (Incl. Corr.)} = 3.8100 \text{ mm}$$

$$\text{Tubesheet Shear Stress} = 67.5122 \text{ N./mm}^2$$

Reqd Tubesheet Thickness for Given Loadings (including CA) [Hreqd]:

$$= \max(HreqB; HreqS)$$

$$= \max(34.4874; 3.81)$$

$$= 34.4874 \text{ mm}$$

ASME Section VIII-2 Part 4.18.8.4 Step 9:

The Ftmin and Ftmax Coefficients from Table 4.18.4:

$$Ftmin = -1.8227, Ftmax = 1.9883$$

First Extreme Tube Axial Stress from among all the tubes [σ t1]:

$$= ((Ps \cdot xs - Pt \cdot xt) - Pe \cdot Ftmin) / (Xt - Xs)$$

$$= ((3665.21 \cdot 0.6063 - 2385.97 \cdot 0.7876) - (618.865) \cdot -1.823) /$$

$$(0.7876 - 0.6063)$$

$$= 8.1111 \text{ N./mm}^2$$

Second Extreme value of Tube Axial Stress from among all the tubes [σ t2]:

$$= ((Ps \cdot xs - Pt \cdot xt) - Pe \cdot Ftmax) / (Xt - Xs)$$

$$= ((3665.21 \cdot 0.6063 - 2385.97 \cdot 0.7876) - (618.865) \cdot 1.988) /$$

$$(0.7876 - 0.6063)$$

$$= -4.8948 \text{ N./mm}^2$$

Maximum Tube Axial Stress [σ t,max]:

$$= \max(|\sigma_{t,1}|; |\sigma_{t,2}|) = 8.111 \text{ N./mm}^2$$



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 55 of 173

ASME TS Calc: Pressure Test

Case: 1 9:52a Aug 12, 2026

Allowable Tube Stress [σ_t, A]:
 $= \beta T \cdot S_{y,t} = 170.9969 \text{ N./mm}^2$

Check for Buckling as some of the tubes are in compression.

Determine the Factor of Safety [Fs]:
 $= \max((3.25 - 0.25(Z_d + Q_3 \cdot Z_w) X_a^4); 1.25)$
 $= \max((3.25 - 0.25(0.025 + -0.634 \cdot 0.063) 3.939^4); 1.25)$
 $= 1.2500 \text{ (Should be } \leq 2 \text{)}$

Determine the factor [rt]:
 $= (\sqrt{ dt^2 + (dt - 2 \cdot tt)^2 }) / 4$
 $= (\sqrt{ 15.875^2 + (15.875 - 2 \cdot 2.108)^2 }) / 4$
 $= 4.9241 \text{ mm}$

Determine the factor [Ct]:
 $= \sqrt{ (2 \cdot \pi^2 \cdot Et / S_{yt})}$
 $= \sqrt{ (2 \cdot \pi^2 \cdot 0.20270E+09 / 179)}$
 $= 156.4208$

Determine the factor [Ft]:
 $= k \cdot L / r$
 $= 0 \cdot 0 / 4.924$
 $= 0.0000$

Buckling Allowable Stress [Stb]:
 $= (S_{y,t} / F_s) \cdot (1 - F_t / (2 \cdot C_t))$
 $= (179 / 1.25) \cdot (1 - 0 / (2 \cdot 156.421))$
 $= 170.997 \text{ N./mm}^2 \text{ (Never greater than } S_{ot} \text{)}$

Note: The Axial Compressive stress in tubes is within limits.

Largest tube-to-tubesheet Joint Load [Wt]:
 $= \sigma_{t,max} \cdot \text{Tube Area}$
 $= 8.11 \cdot 0.9117$
 $= 75.41 \text{ Kg}$

Tube Metal Area [At]:
 $= \pi (d_o - t) t$
 $= \pi (15.875 - 2.108) 2.108$
 $= 0.912 \text{ cm}^2$

Tube Weld Size Results per UW-20.3:

Tube Strength [Ft]:
 $= \pi \cdot t (d_o - t) S$
 $= \pi \cdot 2.108 (15.875 - 2.108) 170.997$
 $= 1589.716 \text{ Kg}$

Groove Weld Strength [Fg]:
 $= 0.85 \cdot \pi \cdot a_g (d_o + 0.67 \cdot a_g) S_w \text{ (but not } > F_t \text{)}$
 $= 0.85 \cdot \pi \cdot 2.0 (15.875 + 0.67 \cdot 2.0) 171.0$
 $= 1589.7156 \text{ Kg}$

Weld Strength Factor [fw]:
 $= S / S_w \text{ where } S_w = \min(S \text{ and } S_t)$
 $= 170.997 / 170.997$
 $= 1.000$

Design Strength Ratio [fd]:
 $= 1 \text{ for full strength welds}$

Fillet Weld Strength [Ff]:
 $= 0.55 \cdot \pi \cdot a_f (d_o + 0.67 \cdot a_f) S_w \text{ (but not } > F_t \text{)}$
 $= 0.55 \cdot \pi \cdot 2.0 (15.875 + 0.67 \cdot 2.0) 171.0$



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 56 of 173

ASME TS Calc: Pressure Test

Case: 1 9:52a Aug 12, 2026

= 1037.3115 Kgf

Minimum Length of Weld [ar]:

$$= 2 \left(\sqrt{((0.75 \cdot do)^2 + 1.07 \cdot t \cdot (do - t) \cdot fw \cdot fd) - 0.75 \cdot do} \right) - 0.75 \cdot 15.875$$

$$= 2 \left(\sqrt{((0.75 \cdot 15.875)^2 + 1.07 \cdot 2.108 \cdot (15.875 - 2.108) \cdot 1.0 \cdot 1.0)} - 0.75 \cdot 15.875 \right)$$

$$= 2.479 \text{ mm}$$

Minimum Required Fillet Weld Leg [afr]: 1.2648 mm

Minimum Required Groove Weld Leg [agr]: 1.2648 mm

Tube-Tubesheet Jt allowable, 1589.72 is >= tube strength 1589.72 Kgf

Note: This tube-tubesheet joint is a Full Strength joint

ASME Section VIII-2 Part 4.18.8.4 Step 10:

Shell Axial Membrane Allowable Stress:

$$= \beta T \cdot S_{y,s} = 0.95 \cdot 240.0 = 341.99 \text{ N./mm}^2$$

Axial Membrane Stress in Shell [σ_s, m]:

$$= a o^2 / ((D_s + t_s) t_s) \cdot [P_e + (p_s^2 - 1)(P_s - P_t)] + a s^2 \cdot P_t / ((D_s + t_s) t_s)$$

$$= 292.326^2 / ((600.0 + 9.53) 9.53) \cdot [618.87 + (1.026^2 - 1)(3665.21 - 2385.97)] + 300.0^2 \cdot 2385.97 / ((600.0 + 9.53) 9.53)$$

$$= 47.0754 \text{ N./mm}^2$$

ASME Section VIII-2 Part 4.18.8.4 Step 11:

Note:

For a given Shell thickness of 9.53 mm, the minimum Shell length adjacent to the tubesheet should be 136.111 mm

Computations completed for ASME tubesheet configuration: b

Stress/Force Summary for Loadcase D3 un-corr. (Psd,max + Ptd,max):

Stress Description	Actual	Allowable	Pass/Fail
Tubesheet Bend. Stress	186.0 <=	356.2 N./mm ²	Pass
Tubesheet Shear Stress	6.0 <=	190.0 N./mm ²	Pass
Maximum Tube Stress	8.1 <=	171.0 N./mm ²	Pass
Minimum Tube Stress (Buckling)	-4.9 <=	-171.0 N./mm ²	Pass
Maximum Force on any one Tube	75.4 <=	1589.7 Kgf	Pass
Axial Membrane Stress in Shell	47.1 <=	342.0 N./mm ²	Pass

Thickness Results for Loadcase D3 un-corr. (Psd,max + Ptd,max):

Thickness (mm)	Required	Actual	P/F
Tubesheet Thickness :	34.487	52.000	Ok
Tube-Tubesheet Fillet Weld Leg :	1.265	2.000	Ok
Tube-Tubesheet Groove Weld Leg :	1.265	2.000	Ok

Fixed Tubesheet results per ASME Div. 2 Part 4.18.8 2025

Results for 3 Load Cases:

Case#	--Reqd. Thk. + CA Tbsht Extnsn	----	Tubesheet Bend	Stresses Allwd	Shear	Allwd	Case Type	Pass/ Fail
D1uc	24.451	16.900	144	356	11	190	Ps+Pt-Th	D1 Ok
D2uc	19.121	...	89	356	17	190	Ps+Pt-Th	D2 Ok
D3uc	34.487	...	186	356	6	190	Ps+Pt-Th	D3 Ok



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 57 of 173

ASME TS Calc: Pressure Test

Case: 1 9:52a Aug 12,2026

Max: 34.4874 16.900 mm 0.522 0.090 (Str. Ratio)

Load Case Definitions:

[Ps & Pt]:

Shell-side and Tube-side Design or Operating Pressures
derived from Psd,min Ptd,max, Psox,min, Ptox,max etc. per the
Load Case Tables

[(+)-Th]:

With or Without Thermal Expansion, Tt,mx & Ts,mx

[c]:

With or Without Corrosion Allowance

[D1, D2, D3]:

Design Load Cases using the Maximum and Minimum Design Pressures

[D4]:

Design Load Case using the Minimum (Vacuum) Pressures (if specified)

[O1, O2, O3, O4]:

Operating Load Cases using the Maximum and Minimum Operating Pressures and
Operating Temperatures

Shell Axial Membrane Stress Summary:

---- Shell Stresses ----					:	---- Shell Band Stress ----					:	Pass
Case#	Ten	Allwd	Cmp	Allwd	:	Ten	Allwd	Cmp	Allwd	:		Fail
D1uc	18	341	...	...	:	...	...	...	...	:		Ok
D2uc	29	341	...	...	:	...	...	...	...	:		Ok
D3uc	47	341	...	...	:	...	...	...	...	:		Ok
Max RATIO	0.138		...	...	:	...	...	...	...	:		

Tube, Shell and Channel Stress Summary:

---- Tube Stresses ----					Tube Loads		Shell Stress		Channel Stress		Pass
Case#	Ten	Allwd	Cmp	Allwd	Ld	Allwd	Stress	Allwd	Stress	Allwd	Fail
D1uc	19	170	-19	-170	175	1589	...	341	...	...	Ok
D2uc	15	170	-9	-170	143	1589	...	341	...	...	Ok
D3uc	8	170	-5	-170	75	1589	...	341	...	...	Ok
Max RATIO	0.110		0.110		0.110		...	...	...	...	

Summary of Thickness Comparisons for 3 Load Cases:

Thickness (mm)	Required	Actual	P/F
Tubesheet thickness :	34.487	52.000	Ok
Tubesheet thickness flanged extension :	16.900	36.000	Ok
Tube thickness :	0.541	2.108	Ok
Tube-tubesheet fillet weld leg :	1.265	2.000	Ok
Tube-tubesheet groove weld leg :	1.265	2.000	Ok

Min Shell length of thk, (9.530) adj. to tubesheet: 136.111 mm

Note: This is a full strength Tube to Tubesheet Joint.

Summary of Axial Differential Expansion between Shell and Tubes :

Due to Thermal Expansion Shell Extends by : +.000 mm

Due to Pressure Shell Compresses by : -0.090 mm



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 58 of 173

ASME TS Calc: Pressure Test

Case: 1 9:52a Aug 12, 2026

Due to Pressure + Thermal Shell Compresses by : -0.090 mm

Summary of Exchanger Pressure and Thermal Displacements: (mm)

Load Case#	Due to Pressure		Due to Thermal Exp.		Computed Delta Ms	
	UnCorroded	Corroded	UnCorroded	Corroded	UnCorroded	Corroded
1	0.0108	...	...	...	...	...
2	-0.0899	...	...	...	...	...
3	-0.0791	...	...	...	...	...
4	...	...	...	...	...	...
5	...	...	...	...	...	...
6	...	...	...	...	...	...
7	...	...	...	...	...	...
8	...	...	...	...	...	...

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 59 of 173

External Pressure Calculations: Step: 12 9:52am Aug 12,2026

External Pressure Calculation Results Summary:

ASME Code, Section VIII Division 1, 2025

External Pressure Calculations:

From	To	Section Length mm	Outside Diameter mm	Corroded Thickness mm	Factor A	Factor B N./mm ²
10	20	No Calc	616.68	5.165	0.0011633	89.8136
20	30	726.2	619.06	6.355	0.0011829	90.2975
30	40	No Calc	...	56.825	No Calc	No Calc
40	50	4790	619.06	6.355	0.00015459	15.456
50	60	No Calc	...	56.825	No Calc	No Calc
60	70	726.2	619.06	6.355	0.0011829	90.2975
70	80	No Calc	616.68	5.165	0.0011633	89.8136

External Pressure Calculations:

From	To	External Actual T. mm	External Required T. mm	External Design Pressure KPa.	External M.A.W.P. KPa.
10	20	8.34	No Calc	...	835.766
20	30	9.53	No Calc	...	1235.87
30	40	60	54.8386	...	No Calc
40	50	9.53	No Calc	...	211.541
50	60	60	54.8386	...	No Calc
60	70	9.53	No Calc	...	1235.87
70	80	8.34	No Calc	...	835.766

Minimum

212

External Pressure Calculations:

From	To	Actual Length Bet. Stiffeners mm	Allowable Length Bet. Stiffeners mm	Ring Inertia Required cm ⁴	Ring Inertia Available cm ⁴
10	20	No Calc	No Calc	No Calc	No Calc
20	30	726.2	No Calc	No Calc	No Calc
30	40	No Calc	No Calc	No Calc	No Calc
40	50	4790	No Calc	No Calc	No Calc
50	60	No Calc	No Calc	No Calc	No Calc
60	70	726.2	No Calc	No Calc	No Calc
70	80	No Calc	No Calc	No Calc	No Calc

Elements Suitable for External Pressure.

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 60 of 173

Element and Detail Weights:

Step: 13

9:52am Aug 12,2026

Element and Detail Weights:

From	To	Element Metal Wgt. kg.	Element ID Volume cm ³	Corroded Metal Wgt. kg.	Corroded ID Volume cm ³	Extra due Misc % kg.
10	20	43.6214	49828.3	29.0886	51194.2	4.36214
20	30	84.863	169676	56.8849	173287	8.4863
30	40	80.0512	23683.1	76.2136	23769.2	8.00512
40	50	677.49	848208	454.132	877032	67.749
50	60	80.0512	23683.1	76.2136	23769.2	8.00512
60	70	84.863	169676	56.8849	173287	8.4863
70	80	43.6214	49828.3	29.0886	51194.2	4.36214
Total		1094	1334584.25	778	1373532.88	109



For elements specified as shell side elements, the volume(s) shown above for those elements, reflects the displacement of the tubes.

Weight of Details:

From	Type	Weight of Detail kg.	X Offset, Dtl. Cent. mm	Y Offset, Dtl. Cent. mm	Z Offset Dtl. Cent. mm	Description
10	Liqd	49.7979	-50	...	...	Liquid: 10
20	Liqd	169.573	300	...	...	Liquid: 30
20	Nozl	29.7678	300	-384.137	...	N1- Channel inle
40	Sadl	82.383	960	419.235	...	Left Saddle
40	Sadl	82.383	3830	419.235	...	Right saddle
40	Liqd	42.3846	2395	...	...	Liquid: 40
40	Insl	67.5312	2395	...	...	Hot insulation
40	Nozl	86.7305	500	436.525	...	N1- Shell outlet
40	Nozl	121.14	4000	461.925	...	N2- shell inlet
60	Liqd	169.573	300	...	...	Liquid: 50
60	Nozl	29.7678	300	384.137	...	N2- Channel outl
70	Liqd	49.7979	126.2	...	...	Liquid: 70
30	FTsh	143.811	104.8	...	...	Fixed tubesheet
30	Tube	2024.31	2517.3	...	...	Tubes
30	RTsh	143.811	4929.8	...	...	Tubesheet
40	Bafl	5.56857	598.51	...	...	Baffles
40	Bafl	5.56857	1197.02	...	...	Baffles
40	Bafl	5.56857	1795.53	...	...	Baffles
40	Bafl	5.56857	2394.04	...	...	Baffles
40	Bafl	5.56857	2992.55	...	...	Baffles
40	Bafl	5.56857	3591.06	...	...	Baffles
40	Bafl	5.56857	4189.57	...	...	Baffles
40	Bafl	5.56857	4788.08	...	...	Baffles

Total Weight of Each Detail Type:

Saddles	164.8
Liquid	481.1
Insulation	67.5
Nozzles	267.4
Exchanger Components	2356.5
Liquid in Tubes	277.9

Sum of the Detail Weights 3615.2 kg.

Weight Summation Results: (kg.)



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 61 of 173

Element and Detail Weights:

Step: 13 9:52am Aug 12,2026

	Fabricated	Shop Test	Shipping	Erected	Empty	Operating
Main Elements	1204.0	1204.0	1204.0	1204.0	1204.0	1204.0
Saddles	164.8	164.8	164.8	164.8	164.8	164.8
Nozzles	267.4	267.4	267.4	267.4	267.4	267.4
Exchanger	2356.5	2356.5	2356.5	2356.5	2356.5	2356.5
Insulation	...	...	67.5	67.5	67.5	67.5
Ope. Liquid	...	...	...	...	...	481.1
Tube Ope Lqd	...	...	...	...	...	277.9
Test Liquid	...	1333.8	...	...	...	...
Tube Tst Lqd	...	277.9	...	...	...	...
Totals	3992.7	5604.4	4060.2	4060.2	4060.2	4819.2

Field Installation Options:

Miscellaneous Weight Percent: 10.0 %

Note that the above value for the miscellaneous weight percent has been applied to the shells/heads/flange/tubesheets/tubes etc. in the weight calculations for metallic components.

Weight Summary:

Fabricated Wt.	- Bare weight without removable internals	3992.7 kg.
Shop Test Wt.	- Fabricated weight + water (full)	5604.4 kg.
Shipping Wt.	- Fab. weight + removable intls.+ shipping app.	4060.2 kg.
Erected Wt.	- Fab. wt + or - loose items (trays,platforms etc.)	4060.2 kg.
Ope. Wt. no Liq	- Fab. weight + internals. + details + weights	4060.2 kg.
Operating Wt.	- Empty weight + operating liq. uncorroded	4819.2 kg.
Oper. Wt. + CA	- Corr wt. + operating liquid	4471.6 kg.

Exchanger Tube Data

Volume of Exchanger tubes :	278089.3 cm ³
Weight of Ope Liq in tubes :	277.9 kg.
Weight of Water in tubes :	277.9 kg.

The Corroded Weight and thickness are used in the Horizontal Vessel Analysis (Ope Case) and Earthquake Load Calculations.

Surface Areas of Elements:

From	To	Outside Surface Area cm ²	Inside Surface Area cm ²
10	20	5636.18	5338.68
20	30	11669	11309.7
30	40	3335.49	1551.32
40	50	93157.6	90289.4
50	60	3335.49	1551.32
60	70	11669	11309.7
70	80	5636.18	5338.68

Total	134438.9	126688.9 cm ²
Total	144.7	136.4 ft ²

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 62 of 173

Nozzle Flange MAWP:

Step: 14 9:52am Aug 12,2026

Nozzle Flange MAWP Results: (KPa. & °C)

Nozzle Description	Flange Rating Ope.	Flange Rating Ambient	Des. Temp	Class	Grade/Group	Equiv. Press	UG-44	Max Pressure 50%	DNV
N1- Channel in	1835.4	1960.0	77	150	GR 1.1	135.5	1835.4	1835.4	1835.4
N1- Shell outl	4469.6	5100.0	166	300	GR 1.1	95.6	4469.6	4469.6	4469.6
N2- shell inle	4469.6	5100.0	166	300	GR 1.1	82.8	4469.6	4469.6	4469.6
N2- Channel ou	1835.4	1960.0	77	150	GR 1.1	135.5	1835.4	1835.4	1835.4

Shellside Flange Rating

Lowest Flange Pressure Rating was (Ope)[ShellSide]: 4469.575 KPa.

Lowest Flange Pressure Rating was (Amb)[ShellSide]: 5100.005 KPa.

Channelside Flange Rating

Lowest Flange Pressure Rating was (Ope)[TubeSide]: 1835.358 KPa.

Lowest Flange Pressure Rating was (Amb)[TubeSide]: 1960.006 KPa.

Selected Method for Derating ASME B16.5 Flange MAWP: ASME UG-44(b)

The UG-44(b) Method is based on the paper PVP 2013-97814. PV Elite uses the maximum loads from each load category to determine ME and FE. In many cases, the computed maximum allowable pressure will be greater than the flange rating. In these cases, the minimum of the rating from the table and the UG-44(b) method will be used. SA-193 B8 Cl. 2 bolts or ones with higher allowable stresses at the specified bolt size shall be used.

The axial force FE must put the nozzle in tension (-P for 107/297; +Fr for PD 5500 AnnexG) to be considered.

Nozzle Description	Gasket Dimension G mm	Fm Value	Resolved Moment ME Kg-m.	Axial Force FE Kgf	MAWP PD KPa.	Maximum Pressure Pmax KPa.	Pass Fail
N1- Channel inle	196.088	1.20	0	408	1835.4	1835.4	Pass
N1- Shell outlet	302.387	0.50	1	683	2819.4	4469.6	Pass
N2- shell inlet	357.251	0.50	2	826	2819.4	4469.6	Pass
N2- Channel outl	196.088	1.20	0	408	1835.4	1835.4	Pass

Evaluating Flange on Nozzle [N1- Channel inle]:

$$= 16 \cdot ME + 4 \cdot FE \cdot G \leq \pi \cdot G^3 [((PR - PD) + FM \cdot PR)]$$

$$= 16(0) + 4 \cdot \text{abs}(408)196.088 \leq \pi \cdot 196.088^3 [(1835.358 - 1835.358) + 1.200 \cdot 1835.358]$$

$$= 0.32729E+03 \leq 0.53200E+04 \text{ Check Passes}$$

Maximum Pressure for Flange on Nozzle N1- Channel inle [Pmax]:

$$= \min(PR, FM \cdot PR + PR - (16 \cdot ME + 4 \cdot FE \cdot G) / (\pi \cdot G^3))$$

$$= \min(1835.358, 1.200 \cdot 1835.358 + 1835.358 - 327.3 / (\pi \cdot 196.088^3))$$

$$= \min(1835.358, 3902.291)$$

$$= 1835.358 \text{ KPa.}$$

Evaluating Flange on Nozzle [N1- Shell outlet]:

$$= 16 \cdot ME + 4 \cdot FE \cdot G \leq \pi \cdot G^3 [((PR - PD) + FM \cdot PR)]$$

$$= 16(1) + 4 \cdot \text{abs}(683)302.387 \leq \pi \cdot 302.387^3 [(4469.575 - 2819.390) + 0.500 \cdot 4469.575]$$

$$= 0.84683E+03 \leq 0.34414E+05 \text{ Check Passes}$$

Maximum Pressure for Flange on Nozzle N1- Shell outlet [Pmax]:

$$= \min(PR, FM \cdot PR + PR - (16 \cdot ME + 4 \cdot FE \cdot G) / (\pi \cdot G^3))$$

$$= \min(4469.575, 0.500 \cdot 4469.575 + 4469.575 - 846.8 / (\pi \cdot 302.387^3))$$

$$= \min(4469.575, 6608.764)$$

$$= 4469.575 \text{ KPa.}$$

Evaluating Flange on Nozzle [N2- shell inlet]:



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 63 of 173

Nozzle Flange MAWP:

Step: 14 9:52am Aug 12, 2026

$$\begin{aligned}
 &= 16 \cdot ME + 4 \cdot FE \cdot G \leq \pi \cdot G^3 [(PR - PD) + FM \cdot PR] \\
 &= 16(2) + 4 \cdot \text{abs}(826) 357.251 \leq \pi \cdot 357.251^3 [(4469.575 - 2819.390) + 500 \cdot 4469.575] \\
 &= 0.12098E+04 \leq 0.56750E+05 \text{ Check Passes}
 \end{aligned}$$

Maximum Pressure for Flange on Nozzle N2- shell inlet [Pmax]:

$$\begin{aligned}
 &= \min(PR, FM \cdot PR + PR - (16 \cdot ME + 4 \cdot FE \cdot G) / (\pi \cdot G^3)) \\
 &= \min(4469.575, 0.500 \cdot 4469.575 + 4469.575 - 1209.8 / (\pi \cdot 357.251^3)) \\
 &= \min(4469.575, 6621.543) \\
 &= 4469.575 \text{ KPa.}
 \end{aligned}$$

Evaluating Flange on Nozzle [N2- Channel outl]:

$$\begin{aligned}
 &= 16 \cdot ME + 4 \cdot FE \cdot G \leq \pi \cdot G^3 [(PR - PD) + FM \cdot PR] \\
 &= 16(0) + 4 \cdot \text{abs}(408) 196.088 \leq \pi \cdot 196.088^3 [(1835.358 - 1835.358) + 1.200 \cdot 1835.358] \\
 &= 0.32729E+03 \leq 0.53200E+04 \text{ Check Passes}
 \end{aligned}$$

Maximum Pressure for Flange on Nozzle N2- Channel outl [Pmax]:

$$\begin{aligned}
 &= \min(PR, FM \cdot PR + PR - (16 \cdot ME + 4 \cdot FE \cdot G) / (\pi \cdot G^3)) \\
 &= \min(1835.358, 1.200 \cdot 1835.358 + 1835.358 - 327.3 / (\pi \cdot 196.088^3)) \\
 &= \min(1835.358, 3902.291) \\
 &= 1835.358 \text{ KPa.}
 \end{aligned}$$

Flange Pressure Ratings are per ASME B16.5 2025 Metric Edition

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 64 of 173

Wind Load Calculation:

Step: 15 9:52am Aug 12,2026

Wind Load Calculation Results:

Wind Load Calculations per India Std. IS 875 (PART 3):2015, Amd. 1&2 (2020):

Input Values:

Wind Design Code	IS 875 (PART 3):2015-2020
Basic Wind Speed for IS-875	180 Km/hr
Wind Zone Number	5
Base Elevation	300 mm
Percent Wind for Hydrotest	33.0
Risk Factor	[k1] 1.0
Terrain Category	2
Equipment Class	Class A
Topography Factor	[k3] 1.0
Importance Factor	[k4] 1.15
Damping Factor (Beta) for Wind (Ope)	0.0100
Damping Factor (Beta) for Wind (Empty)	0.0000
Damping Factor (Beta) for Wind (Filled)	0.0000
Use Gust Response Factor (Dynamic Analysis)	No

Calculated Values:

Vessel Length to Diameter ratio: 9.723

Design Wind Speed [Vz]:

= Basic Wind Speed • k1 • k2,1 • k3 • k4 (for the 1st element)

= 50.0 • 1.0 • 1.0 • 1.0 • 1.15

= 57.496 meters/s

Design Wind Pressure per 4.5.2 [pd]:

= max(0.7 • pz, Kd • Ka • Kc • 0.6 • Vz²)

= max(0.7 • 1983.503, 1.0 • 1.0 • 1.0 • 0.6 • 57.5²)

= 1983.5 N/m²

Element Wind Load (operating condition):

= Wind Area • Cf • pd

= 0.1 • 0.894 • 1983.503

= 236.1 N

From	Height mm	k1	k2	k3	Vz m/sec	Cf
10	860.00	1.0000	1.0000	1.0000	57.50	0.8945
20	860.00	1.0000	1.0000	1.0000	57.50	0.8945
30	860.00	1.0000	1.0000	1.0000	57.50	0.8945
40	860.00	1.0000	1.0000	1.0000	57.50	0.8945
50	860.00	1.0000	1.0000	1.0000	57.50	0.8945
60	860.00	1.0000	1.0000	1.0000	57.50	0.8945
70	860.00	1.0000	1.0000	1.0000	57.50	0.8945

Wind Load Calculation:

From	To	Wind Height mm	Wind Diameter mm	Wind Area cm²	Wind Pressure Kgs/m²	Element Wind Load Kgf
10	20	860	740.016	1330.8	202.347	26.4851
20	30	860	742.872	4457.23	202.347	88.7067
30	40	860	720	534.96	202.347	10.6466
40	50	860	850.872	40756.8	202.347	811.131
50	60	860	720	534.96	202.347	10.6466
60	70	860	742.872	4457.23	202.347	88.7067
70	80	860	740.016	1330.8	202.347	26.4851



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 65 of 173

Wind Load Calculation:

Step: 15 9:52am Aug 12, 2026

The Wind Loads calculated and printed in the Wind Load calculation report have been factored by the input scalar/load reduction factor of: 1.100.

Be sure the wind speed is in accordance with the specified wind design code.

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 66 of 173

Earthquake Load Calculation: Step: 16 9:52am Aug 12,2026

Earthquake Load Calculation Results:

Seismic Analysis Results per IS 1893 (Part 4): 2024

Input Data:

Importance Factor as Entered by User	I	2.0000
Zone Number		2
Soil Type	Rocky or Hard Soil	
Response reduction factor (Force factor)	R	2.0000
Time Period of Vibration (program or user)		0.0303 Seconds
Value of Sa/g from user Spectrum Data		0.0939
Percent Damping		2.0 %
Considering MCE for load determination		No

Calculated results:

Horizontal Seismic Coefficient per 7.3.1 [Ah]:

$$= (Sa/g)_{ss} \cdot DampVal) \cdot (I / R)$$

$$= (0.0939 \cdot 1.0) \cdot 1.0$$

$$= 0.094$$

User Spectrum Data points specified for increments of Time Period

Time Period	Sa/g
0.010	0.070
0.050	0.117
0.100	0.175
0.130	0.175
0.200	0.175
0.270	0.175
0.300	0.175
0.400	0.175
0.500	0.140
0.550	0.127
0.600	0.117
0.670	0.105
0.800	0.087
1.000	0.070
1.200	0.058
1.400	0.050
1.600	0.044
1.800	0.039
2.000	0.035
2.400	0.029
0.000	0.000

Actual Time Period = 0.0303 secs

Computed Sa/g = 0.0939

Note:

It was indicated to ignore the damping factor, assuming that the Site Spectrum specified is per the actual damping value of this vessel.

The value of "DampVal" has been set to 1 (not used).

Earthquake Element Load, for the first Element:

$$= \text{Earthquake Weight} \cdot Ah \cdot \text{Scalar}$$

$$= 478.54 \cdot 0.0939 \cdot 1.0$$

$$= 44.9 \text{ Kgf}$$

Vertical load per 8.4:

$$= 2/3 \cdot Ah \cdot W \cdot \text{Scalar}$$

$$= 2/3 \cdot 0.0939 \cdot 4307 \cdot 1.0$$



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 67 of 173

Earthquake Load Calculation:

Step: 16

9:52am Aug 12, 2026

= 269.5 Kgf

Earthquake Load Calculation:

From	To	Earthquake Height mm	Earthquake Weight Kgf	Element Ope Load Kgf
10	20	300	478.535	44.9134
20	30	300	478.535	44.9134
30	40	300	478.535	44.9134
40	Sad1	300	478.535	44.9134
Sad1	50	300	478.535	44.9134
40	50	300	478.535	44.9134
50	60	300	478.535	44.9134
60	70	300	478.535	44.9134
70	80	300	478.535	44.9134

The Earthquake Weight does not include the weight of the saddles.

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 68 of 173

Center of Gravity Calculation: Step: 17 9:52am Aug 12,2026

Shop/Field Installation Options :

Insulation is installed in the Shop.

Note : The CG is computed from the first Element From Node

Center of Gravity of the Saddles	3202.000 mm
Center of Gravity of the Liquid	3202.000 mm
Center of Gravity of the Insulation	3201.999 mm
Center of Gravity of the Nozzles	3314.469 mm
Center of Gravity of the Tubesheet(s)	3193.500 mm
Center of Gravity of the Tubes	3193.500 mm
Center of Gravity of the Baffles	3500.294 mm
Center of Gravity of Bare Shell New and Cold	3201.999 mm
Center of Gravity of Bare Shell Corroded	3201.999 mm
Vessel CG in the Operating Condition	3206.774 mm
Vessel CG in the Fabricated (Shop/Empty) Condition	3207.840 mm
Vessel CG in the Test Condition	3205.763 mm

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 69 of 173

Saddle Calcs: Operating Case: Step: 18 9:52am Aug 12,2026

ASME VIII Division 2 Horizontal Vessel Analysis, Left Saddle:

Horizontal Vessel Stress Calculations : Operating Case

Note:

Wear Pad Width (225.00) is less than $1.56 \cdot \sqrt{r_m \cdot t}$
and less than $2a$. The wear plate will be ignored.

Minimum Wear Plate Width to be considered in analysis [b1]:


$$= \min(b + 1.56 \cdot \sqrt{R_m \cdot t}, 2a)$$

$$= \min(204.0 + 1.56 \cdot \sqrt{306.3525 \cdot 6.355}, 2 \cdot 960.0)$$

$$= 272.8324 \text{ mm}$$

Input and Calculated Values:

Vessel Mean Radius	Rm	306.35	mm
Shell Thickness used in this Case	t	9.530	mm
Stiffened Vessel Length per 4.15.6	L	4790.00	mm
Distance from Saddle to Vessel tangent	a1 or a	960.00	mm
Saddle Width	b1 or b	204.00	mm
Saddle Bearing Angle	delta or theta	120.00	degrees
Shell Allowable Stress used in Calculation		140.75	N./mm ²
Head Allowable Stress used in Calculation		138.00	N./mm ²
Circumferential Efficiency in Plane of Saddle		1.00	
Circumferential Efficiency at Mid-Span		1.00	
Distance from Saddle Base to Centerline	B	560.00	mm
Coefficient of Friction	mu	0.00	



Results for Horizontal Vessel Analysis:

Saddle Force Q, Operating Case		3903.91	Kgf
Pressure used in Analysis	P	1549.647	KPa.

Horizontal Vessel Analysis Results:	Actual N./mm ²	Allowable N./mm ²
Long. Stress at Top of Midspan	32.30	140.75
Long. Stress at Bottom of Midspan	42.41	140.75
Long. Stress at Top of Saddles	72.35	140.75
Long. Stress at Bottom of Saddles	17.96	140.75



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 70 of 173

Saddle Calcs: Operating Case: Step: 18 9:52am Aug 12,2026

Tangential Shear in Shell	13.79	112.60
Circ. Stress at Horn of Saddle	80.67	175.94
Circ. Compressive Stress in Shell	1.68	140.75

Intermediate Results: Saddle Reaction Q due to Wind or Seismic:

Transverse Saddle Reaction Force [Fwt]:

$$= Ftr(Ft/Num of Saddles + Z Force Load) \cdot B / E$$

$$= 3.0(1062.8/2 + 0) \cdot 560.0/550.0$$

$$= 1623.2 \text{ Kgf}$$

Longitudinal Saddle Reaction Force [Fwl]:

$$= \max(Fl,wind; \text{Sum of X Forces}) \cdot B / Ls$$

$$= \max(96.47, 0) \cdot 560.0/2870.0$$

$$= 18.8 \text{ Kgf}$$

Saddle Reaction Force due to Earthquake Fl [Fsl]:

$$= \max(Fl,eq; \text{Sum of X Forces}) \cdot B / Ls$$

$$= \max(404.22, 0) \cdot 560.0/2870.0$$

$$= 78.9 \text{ Kgf}$$

Saddle Reaction Force due to Earthquake Ft [Fst]:

$$= Ftr(Ft/Num of Saddles + Z Force Load) \cdot B / E$$

$$= 3.0(404/2 + 0) \cdot 560.0/550.0$$

$$= 617.4 \text{ Kgf}$$

Load Combination Results for Q + Wind or Seismic [Q]:

$$= \text{Saddle Load} + \max(Fwl, Fwt, Fsl, Fst)$$

$$= 2281 + \max(19, 1623, 79, 617)$$

$$= 3903.9 \text{ Kgf}$$

Longitudinal Wind Force [Fl]:

$$= \text{WindScalar} \cdot \text{WindPress}(\text{Platform Area} + (\pi/4(OD \cdot \text{WindDiaMult})^2))$$

$$= 1.1 \cdot 1984.306(0.0 + \pi/4(0.619 \cdot 1.2)^2)$$

$$= 946.068 \text{ N}$$

Summary of Loads at the Base of this Saddle:

Vertical Load (including saddle weight)	3986.29	Kgf
Transverse Shear Load	531.40	Kgf
Longitudinal Shear Load	404.22	Kgf

Note: Wear Plate is Welded to the Shell, k = 0.1

Saddle Dimension [E]:

$$= \text{Baseplate Length}$$

$$= 550.000 \text{ mm}$$

The Computed K values from Table 4.15.1:

K1 = 0.1066	K2 = 1.1707	K3 = 0.8799	K4 = 0.4011
K5 = 0.7603	K6 = 0.0529	K7 = 0.0529	K8 = 0.3405
K9 = 0.2711	K10 = 0.0581	K1* = 0.1923	

Note: Dimension a is greater than or equal to Rm/2.

Moment per Equation 4.15.1 [M1]:

$$= -Q \cdot a [1 - (1 - a/L + (Rm^2 - hm^2)/(2a \cdot L)) / (1 + (4hm^2)/3L)]$$

$$= -3904 \cdot 960.0 [1 - (1 - 960.0/4790.0 + (306.352^2 - 0.0^2) / (2 \cdot 960.0 \cdot 4790.0)) / (1 + (4 \cdot 0.0) / (3 \cdot 4790.0))]$$

$$= -712.9 \text{ Kg-m.}$$

Moment per Equation 4.15.2 [M2]:

$$= Q \cdot L / 4 ((1 + 2(Rm^2 - hm^2)/(L^2)) / (1 + (4hm^2)/(3L)) - 4a/L)$$

$$= 3904 \cdot 4790 / 4 ((1 + 2(306^2 - 0^2)/(4790^2)) / (1 + (4 \cdot 0) / (3 \cdot 4790)) - 4 \cdot 960 / 4790)$$



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 71 of 173

Saddle Calcs: Operating Case: Step: 18 9:52am Aug 12, 2026

$$(3 \cdot 4790) - 4 \cdot 960 / 4790 \\ = 965.4 \text{ Kg-m.}$$

$$\text{Longitudinal Stress at Top of Shell (4.15.4) } [\sigma_1]: \\ = P \cdot R_m / (2t) - M_2 / (\pi \cdot R_m^2 \cdot t) \\ = 1549.647 \cdot 306.352 / (2 \cdot 6.355) - 965.4 / (\pi \cdot 306.4^2 \cdot 6.355) \\ = 32.30 \text{ N./mm}^2$$

$$\text{Longitudinal Stress at Bottom of Shell (4.15.5) } [\sigma_2]: \\ = P \cdot R_m / (2t) + M_2 / (\pi \cdot R_m^2 \cdot t) \\ = 1549.647 \cdot 306.352 / (2 \cdot 6.355) + 965.4 / (\pi \cdot 306.4^2 \cdot 6.355) \\ = 42.41 \text{ N./mm}^2$$

$$\text{Longitudinal Stress at Top of Shell at Support (4.15.8) } [\sigma_3]: \\ = P \cdot R_m / (2t) - M_1 / (K_1 \cdot \pi \cdot R_m^2 \cdot t) \\ = 1549.647 \cdot 306.352 / (2 \cdot 6.355) - 712.9 / (0.1066 \cdot \pi \cdot 306.4^2 \cdot 6.355) \\ = 72.35 \text{ N./mm}^2$$

$$\text{Longitudinal Stress at Bottom of Shell at Support (4.15.9) } [\sigma_4]: \\ = P \cdot R_m / (2t) + M_1 / (K_1 \cdot \pi \cdot R_m^2 \cdot t) \\ = 1549.647 \cdot 306.352 / (2 \cdot 6.355) + 712.9 / (0.1923 \cdot \pi \cdot 306.4^2 \cdot 6.355) \\ = 17.96 \text{ N./mm}^2$$

$$\text{Maximum Shear Force in the Saddle (4.15.3) } [T]: \\ = Q(L - 2a) / (L + (4 \cdot h_m / 3)) \\ = 3904(4790.0 - 2 \cdot 960.0) / (4790.0 + (4 \cdot 0.0 / 3)) \\ = 2339.1 \text{ Kg}$$

$$\text{Shear Stress in the shell no rings, not stiffened (4.15.12) } [\tau_2]: \\ = K_2 \cdot T / (R_m \cdot t) \\ = 1.1707 \cdot 2339.08 / (306.3525 \cdot 6.355) \\ = 13.79 \text{ N./mm}^2$$

$$\text{Decay Length (4.15.20) } [x_1, x_2]: \\ = 0.78 \cdot \sqrt{R_m \cdot t} \\ = 0.78 \cdot \sqrt{306.352 \cdot 6.355} \\ = 34.416 \text{ mm}$$

$$\text{Circumferential Stress in shell, no rings (4.15.21) } [\sigma_6]: \\ = -K_5 \cdot Q \cdot k / (t(b + X_1 + X_2)) \\ = -0.7603 \cdot 3904 \cdot 0.1 / (6.355(204.0 + 34.42 + 34.42)) \\ = -1.68 \text{ N./mm}^2$$

$$\text{Circ. Comp. Stress at Horn of Saddle, } L \geq 8R_m \text{ (4.15.22) } [\sigma_7]: \\ = -Q / (4 \cdot t(b + X_1 + X_2)) - 3 \cdot K_7 \cdot Q / (2 \cdot t^2) \\ = -3904 / (4 \cdot 6.355(204.0 + 34.416 + 34.416)) - \\ 3 \cdot 0.0529 \cdot 3904 / (2 \cdot 6.355^2) \\ = -80.67 \text{ N./mm}^2$$

$$\text{Effective reinforcing plate width (4.15.24) } [B_1]: \\ = \min(b + 1.56 \cdot \sqrt{R_m \cdot t}, 2a) \\ = \min(204.0 + 1.56 \cdot \sqrt{306.352 \cdot 6.355}, 2 \cdot 960.0) \\ = 272.83 \text{ mm}$$

$$\text{Distance between Saddle Supports } [L_s]: \\ = 2870.0 \text{ mm}$$

$$\text{Free Un-Restrained Thermal Expansion between the Saddles } [\text{Exp}]: \\ = \alpha \cdot L_s (\text{Design Temperature} - \text{Ambient Temperature}) \\ = 0.000013 \cdot 2870.0 (165.6 - 21.1) \\ = 5.193 \text{ mm}$$

Results for Vessel Ribs, Web and Base:

Baseplate Length	Bplen	550.0000	mm
Baseplate Thickness	Bpthk	16.0000	mm



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 72 of 173

Saddle Calcs: Operating Case: Step: 18 9:52am Aug 12,2026

Baseplate Width	Bpwid	150.0000	mm
Number of Ribs (inc. outside ribs)	Nribs	3	
Rib Thickness	Ribtk	16.0000	mm
Web Thickness	Webtk	16.0000	mm
Web Location	Webloc	Side	
Saddle Design Temperature		21.1	°C
Saddle Yield Stress	Sy	262.0	N./mm ²
Height of Web at Center	Hw,c	306.0	mm
Friction Coefficient	mu	0.000	

Moment of Inertia of Saddle - Transverse Direction (90 degrees to long axis)

Inertia of Shell [ShellInertia]:

$$= ((1.56 \cdot \sqrt{(R \cdot t)} + \text{WearPlateWidth})t^3)/12$$

$$= ((1.56 \cdot \sqrt{(303.175 \cdot 6.355)} + 225.0)6.355^3)/12$$

$$= 0.628 \text{ cm}^4$$

Resolved Inertia for the Shell [I,shell]:

$$= \text{ShellInertia} + A_{\text{Shell}}(C1 - Y)^2$$

$$= 0.628 + 18.65(104.303 - 3.177)^2$$

$$= 1907.877 \text{ cm}^4$$

	B mm	D mm	Y mm	A cm ²	AY mm ³	I + AD ⁽²⁾ cm ⁴
Shell	293.5	6.4	3.2	18.7	5926.1	0.191E+04
Wearplate	225.0	12.0	12.4	27.0	33358.5	0.229E+04
Web	16.0	222.5	129.6	35.6	461278.3	0.170E+04
BasePlate	150.0	16.0	248.8	24.0	597180.1	0.502E+04
Totals	...	...	...	105.2	1097743.0	0.109E+05

Distance to Centroid [C1]:

$$= AY / A$$

$$= 1097743/105.246$$

$$= 104.303 \text{ mm}$$

Angle [β]:

$$= 180 - \text{Saddle Angle}/2$$

$$= 180 - 120.0/2$$

$$= 120.0$$

Saddle Splitting Coefficient [K1]:

$$= (1 + \cos(\beta) - 0.5 \cdot \sin(\beta)^2) / (\pi - \beta + \sin(\beta)\cos(\beta))$$

$$= (1 + \cos(120.0) - 0.5 \cdot \sin(120.0)^2) / (\pi - 2.094 + \sin(120.0)\cos(120.0))$$

$$= 0.2035$$

Saddle Splitting Force [Fh]:

$$= K1 \cdot Q$$

$$= 0.204 \cdot 3903.905$$

$$= 794.5294 \text{ Kgf}$$

Tension Stress, St = (Fh/As)	=	0.8998	N./mm ²
Allowed Stress, Sa = 0.6 * Yield Str	=	157.1972	N./mm ²

Saddle Splitting Dimension [d]:

$$= B - R \cdot \sin(\text{theta}/2) / (\text{theta}/2 \text{ in radians})$$

$$= 560.0 - 303.17 \cdot \sin(120.0/2) / 1.0472$$

$$= 309.276 \text{ mm}$$

Bending Moment, M = Fh * d	=	245.7340	Kg-m.
----------------------------	---	----------	-------

Bending Stress, Sb = (M * C1 / I)	=	2.3044	N./mm ²
Allowed Stress, Sa = 2/3 * Yield Str	=	174.6635	N./mm ²

Minimum Thickness of Baseplate per Moss:



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 73 of 173

Saddle Calcs: Operating Case: Step: 18 9:52am Aug 12, 2026

$$= \sqrt{(3(Q + \text{SaddleWt}) \cdot \text{BasePlateWidth}) / (2 \cdot \text{BasePlateLength} \cdot \text{AllStress}))}$$

$$= \sqrt{(3(3904 + 82)150.0 / (2 \cdot 550.0 \cdot 174.663))}$$

$$= 9.569 \text{ mm}$$

Calculation of Axial Load, Intermediate Values and Compressive Stress:

Web Length Dimension [Web Length]:

$$= 2 \cdot \cos(90 - \text{Saddle Angle}/2) (\text{Inside Radius} + \text{Shell Thk} + \text{Wear Plate Thk})$$

$$= 2 \cdot \cos(90 - 120.0/2) (300.0 + 9.53 + 12.0)$$

$$= 556.906 \text{ mm}$$

Distance between Ribs [e]:

$$= \text{Web Length} / (\text{Nr ribs} - 1)$$

$$= 556.9062 / (3 - 1)$$

$$= 278.453 \text{ mm}$$

Baseplate Pressure Area [Ap]:

$$= e \cdot \text{Bpwid} / 2$$

$$= 278.4531 \cdot 150.0 / 2$$

$$= 208.840 \text{ cm}^2$$

Bearing Pressure [Bp]:

$$= (Q + \text{SaddleWt}) / (\text{BasePlateLength} \cdot \text{BasePlateWidth})$$

$$= 3986.288 / (550.0 \cdot 150.0)$$

$$= 4.832 \text{ Kg/cm}^2$$

Axial Load [P]:

$$= \text{Ap} \cdot \text{Bp}$$

$$= 208.8 \cdot 4.83$$

$$= 1009.086 \text{ Kg}$$

Area of the Rib and Web [Ar]:

$$= \text{Rib Area} + \text{Web Area}$$

$$= 30.08 + 22.276$$

$$= 52.356 \text{ cm}^2$$

Compressive Stress [Sc]:

$$= P / \text{Ar}$$

$$= 1009.1 / 52.3563$$

$$= 1.890 \text{ N./mm}^2$$

Check of Outside Ribs:

Inertia of Saddle, Outer Ribs - Longitudinal Direction

	B	D	Y	A	AY	Io
Rib	16.0	188.0	110.0	30.1	330880.0	0.145E+04
Web	139.2	16.0	8.0	22.3	17821.0	770.
Totals	...	...	...	52.4	348700.9	0.222E+04

Rib dimension [D]:

$$= \text{Saddle Width} - \text{Web Thickness}$$

$$= 204.0 - 16.0$$

$$= 188.000 \text{ mm}$$

Distance to Centroid from Datum [ytot]:

$$= \text{AY} / \text{A}$$

$$= 348700.938 / 52.356$$

$$= 66.602 \text{ mm}$$

Distance to Centroid [C1]:

$$= \max(\text{ytot}, \text{Saddle Width} - \text{ytot})$$

$$= \max(66.602, 204.0 - 66.602)$$

$$= 137.398 \text{ mm}$$



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 74 of 173

Saddle Calcs: Operating Case: Step: 18 9:52am Aug 12,2026

Radius of Gyration [r]:

$$= \sqrt{\text{Total Inertia} / \text{Total Area}}$$

$$= \sqrt{2222.2/52.356}$$

$$= 65.150 \text{ mm}$$

Length of Outer Rib, step 1, [Lv]:

$$= \text{Saddle Height} - \cos(\text{saddle bearing angle} / 2) (\text{radius} + \text{shlthk} + \text{wpdthk}) - \text{bpthk}$$

$$= 560.0 - \cos(120.0/2) (300.0 + 9.53 + 12.0) - 16.0$$

$$= 383.235 \text{ mm}$$

Length of Outer Rib, step 2, [Lw]:

$$= 2 \cdot \sin(\text{saddle bearing angle} / 2) (\text{radius} + \text{shlthk} + \text{wpdthk})$$

$$= 2 \cdot \sin(120.0/2) (300.0 + 9.53 + 12.0)$$

$$= 556.906 \text{ mm}$$

Length of Outer Rib, step 3, [Bd]:

$$= \text{Baseplate length} - \text{clearance}$$

$$= 550.0 - 50.8$$

$$= 499.200 \text{ mm}$$

Length of Outer Rib, step 4, [Dd]:

$$= (\text{Lw} - \text{Bd}) / 2$$

$$= (556.906 - 499.2) / 2$$

$$= 28.853 \text{ mm}$$

Length of Outer Rib [L]:

$$= \sqrt{\text{Lv}^2 + \text{Dd}^2}$$

$$= \sqrt{383.235^2 + 28.853^2}$$

$$= 384.320 \text{ mm}$$

Intermediate Term [Cc]:

$$= \sqrt{(2 \cdot \pi^2 \cdot \text{Elastic Modulus} / \text{Yield Stress})}$$

$$= \sqrt{(2 \cdot \pi^2 \cdot 0.20270\text{E}+09/262.0)}$$

$$= 123.583$$

Slenderness ratio [KL/r]:

$$= \text{KL}/r$$

$$= 1 \cdot 384.32/65.15$$

$$= 5.899$$

Bending Moment [Rm]:

$$= \text{Fl} / (2 \cdot \text{Bplen}) \cdot e \cdot L / 2$$

$$= 404.2 / (2 \cdot 550.0) \cdot 278.453 \cdot 384.32/2$$

$$= 19.663 \text{ Kg-m.}$$

Compressive Allowable, $\text{KL}/r < \text{Cc}$ ($5.899 < 123.583$) per AISC E2-1 [Sca]:

$$= (1 - (\text{KL}/r)^2 / (2 \cdot \text{Cc}^2)) \text{Fy} / (5/3 + 3 \cdot (\text{KL}/r) / (8 \cdot \text{Cc}) - (\text{KL}/r)^3 / (8 \cdot \text{Cc}^3))$$

$$= (1 - (5.9)^2 / (2 \cdot 123.58^2)) 262 / (5/3 + 3 \cdot (5.9) / (8 \cdot 123.58) - (5.9)^3 / (8 \cdot 123.58^3))$$

$$= 155.4 \text{ N/mm}^2$$

AISC Unity Check of Outside Ribs (must be ≤ 1)

$$= \text{Sc}/\text{Sca} + (\text{Rm} \cdot \text{C1} / \text{I}) / \text{Sba}$$

$$= 1.89/155.35 + (19.66 \cdot 137.398/22222406) / 174.66$$

$$= 0.019$$

Check of Inside Ribs:

Inertia of Saddle, Inner Ribs - Axial Direction

	B	D	Y	A	AY	Io
Rib	16.0	188.0	110.0	30.1	330880.0	0.200E+04
Web	278.5	16.0	8.0	44.6	35642.0	762.
Totals	...	...	...	74.6	366522.0	0.276E+04



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 75 of 173

Saddle Calcs: Operating Case: Step: 18 9:52am Aug 12,2026

Distance to Centroid from Datum [ytot]:

$$= AY / A$$

$$= 366521.969/74.632$$

$$= 49.110 \text{ mm}$$

Distance to Centroid [C1]:

$$= \max(ytot, \text{abs}(\text{Saddle Width} - ytot))$$

$$= \max(49.11, \text{abs}(204.0 - 49.11))$$

$$= 154.890 \text{ mm}$$

Length of Inner Rib [L]:

$$= \text{Saddle Height} - \text{Outside Radius} - \text{Bpthk}$$

$$= 560.0 - \cos(321.53/2) (16.0 + 0.0 + 0.0) - 0.0$$

$$= 222.470 \text{ mm}$$

Radius of Gyration [r]:

$$= \sqrt{ (\text{Total Inertia} / \text{Total Area}) }$$

$$= \sqrt{ (2763.7/74.632) }$$

$$= 60.852 \text{ mm}$$

Slenderness ratio [KL/r]:

$$= KL/r$$

$$= 1 \cdot 222.47/60.852$$

$$= 3.656$$

Unit Force [Force,u]:

$$= FI / (2 \cdot \text{Baseplate Length})$$

$$= 404.221/(2 \cdot 550.0)$$

$$= 0.367 \text{ Kgf/mm}$$

Moment at base of inner Rib [Mbase,c]:

$$= \text{Unit Force} \cdot e \cdot L$$

$$= 0.367 \cdot 278.453 \cdot 222.47$$

$$= 22.764 \text{ Kg-m.}$$

Bending Stress due to Transverse Force and Weight Load [σ_B ,base,c]:

$$= \text{Bending Moment} / \text{Section Modulus}$$

$$= 22.764/178427.25$$

$$= 1.251 \text{ N./mm}^2$$

Compressive Allowable, $KL/r < C_c$ ($3.6559 < 123.583$) per AISC E2-1 [Sca]:

$$= (1 - (KL/r)^2 / (2 \cdot C_c^2)) F_y / (5/3 + 3 \cdot (KL/r) / (8 \cdot C_c) - (KL/r)^3 / (8 \cdot C_c^3))$$

$$= (1 - (3.66)^2 / (2 \cdot 123.58^2)) 262 / (5/3 + 3 \cdot (3.66) / (8 \cdot 123.58) - (3.66^3) / (8 \cdot 123.58^3))$$

$$= 156.1 \text{ N./mm}^2$$

AISC Unity Check of Inside Ribs (must be ≤ 1)

$$= Sc/Sca + (M_{base,c} \cdot C1/I) / Sba$$

$$= 3.2/156.09 + (22.76 \cdot 154.89/2763.653) / 174.66$$

$$= 0.028$$

Input Data for Base Plate Bolting Calculations:

Total Number of Bolts per BasePlate	Nbolts	2
Total Number of Bolts in Tension/Baseplate	Nbt	1
Bolt Design Temperature		21.1 °C
Bolt Material Specification		SA-193 B7
Bolt Allowable Stress	Stba	137.29 N./mm ²
Bolt Corrosion Allowance	Bca	1.5 mm
Distance from Bolts to Edge	Edgedis	50.0 mm
Nominal Bolt Diameter	Bnd	24.0000 mm
Thread Series	Series	TEMA Metric
BasePlate Allowable Stress	S	138.00 N./mm ²
Area Available in a Single Bolt	BlArea	2.2586 cm ²



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 76 of 173

Saddle Calcs: Operating Case: Step: 18 9:52am Aug 12, 2026

Saddle Load Q0 (Weight)	Q0	2363.1 Kgf
Saddle Load QL (Wind/Seismic contribution)	QL	78.9 Kgf
Maximum Transverse Force	Ft	531.4 Kgf
Maximum Longitudinal Force	F1	404.2 Kgf
Saddle Bolted to Steel Foundation		No

Friction force due to thermal growth, [Ff]:
= 1189.0 Kgf

Shear Stress in a Single Bolt, Longitudinal Direction [rb,l]:
= $\max(Ff, F1) / (\text{Bolt Area} \cdot \text{Number of Bolts})$
= $1189.0 / (2.259 \cdot 2)$
= 25.8 N./mm². Must be less than 107.9 N./mm².

Shear Stress in a Single Bolt, Transverse Direction [rb,t]:
= $Ft / (\text{Bolt Area} \cdot \text{Number of Bolts})$
= $531.4 / (2.259 \cdot 2)$
= 11.5 N./mm². Must be less than 107.9 N./mm².

Bolt Area Calculation per Dennis R. Moss

Bolt Area Requirement Due to Longitudinal Load [Bltarearl]:
= 0.0 (Q0 > QL --> No Uplift in Longitudinal direction)

Bolt Area due to Shear Load [Bltarears]:
= $F1 / (\text{BoltShearAllowable} \cdot \text{Nbols})$
= $404.22 / (107.87 \cdot 2.0)$
= 0.1837 cm²

Bolt Area due to Transverse Load:

Moment on Baseplate Due to Transverse Load [Rmom]:
= $B \cdot Ft + \text{Sum of X Moments}$
= $560.0 \cdot 531.4 + 0.0$
= 297.59 Kg-m.

Eccentricity (e):
= $Rmom / Q0$
= $297.59 / 2363.09$
= 125.93 mm > Bplen/6 --> Uplift in Transverse direction

f = $Bplen / 2 - Edgedis$
= $550.0 / 2 - 50.01$
= 224.99 mm

Modular Ratio Of Steel/Concrete (n1):
= ES / EC
= $203402.5 / 21526.32$
= 9.45

K1 = $3 \cdot (e - 0.5 \cdot Bplen)$
= $3 \cdot (125.93 - 0.5 \cdot 550.0)$
= -447.21 mm

K2 = $6 \cdot n1 \cdot At / Bpwid \cdot (f + e)$
= $6 \cdot 9.45 \cdot 2.26 / 150.0 \cdot (224.99 + 125.93)$
= 29955.93 mm²

K3 = $-K2 \cdot (0.5 \cdot Bplen + f)$
= $-29955.93 \cdot (0.5 \cdot 550.0 + 224.99)$
= -14977589.27 mm³

Iteratively Solving for the Effective Bearing Length:

$$Y^3 + K1 \cdot Y^2 + K2 \cdot Y + K3 = 0$$

$$Y^3 + -447.21 \cdot Y^2 + 29955.93 \cdot Y + -0.1E+08 = 0$$



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 77 of 173

Saddle Calcs: Operating Case: Step: 18 9:52am Aug 12, 2026

$$Y = 453.91 \text{ mm}$$

$$\begin{aligned} \text{Num} &= (\text{Bplen} / 2 - Y / 3 - e) \\ &= (550.0 / 2 - 453.91 / 3 - 125.93) \\ &= -2.23 \end{aligned}$$

$$\begin{aligned} \text{Denom} &= (\text{Bplen} / 2 - Y / 3 + f) \\ &= (550.0 / 2 - 453.91 / 3 + 224.99) \\ &= 348.68 \end{aligned}$$

$$\begin{aligned} \text{Total Bolt Tension Force [Tforce]:} \\ &= -\text{QO} \cdot \text{Num} / \text{Denom} \\ &= -2363.09 \cdot -2.23 / 348.68 \\ &= 15.14 \text{ Kgf} \end{aligned}$$

$$\begin{aligned} \text{Bolt Area Required due to Transverse Load [Bltareart]:} \\ &= \text{Tforce} / (\text{Stba} \cdot \text{Nbt}) \\ &= 15.14 / (137.29 \cdot 1.0) \\ &= 0.0108 \text{ cm}^2 \end{aligned}$$

$$\begin{aligned} \text{Required Area of a Single Bolt [Bltarear]:} \\ &= \max[\text{Bltarearl}, \text{Bltarears}, \text{Bltareart}] \\ &= \max[0.0, 0.1837, 0.0108] \\ &= 0.1837 \text{ cm}^2 \end{aligned}$$

Baseplate Thickness Calculation per D. Moss:

$$\begin{aligned} \text{Bearing Pressure (fc)} \\ &= 2(\text{QO} + \text{Tforce}) / (Y \cdot \text{Bpwid}) \\ &= 2(2363.09 + 15.14) / (453.91 \cdot 150.0) \\ &= 685.06 \text{ KPa.} \end{aligned}$$

$$\begin{aligned} \text{Distance from Baseplate Edge to the Web [ADIST]:} \\ &= (\text{Bplen} - \text{WebLength}) / 2 \\ &= (550.0 - 499.2) / 2 \\ &= 25.4000 \text{ mm} \end{aligned}$$

$$\begin{aligned} \text{Overturning Moment due To Bolt Tension [Mt]:} \\ &= \text{Tforce} \cdot \text{Adist} \\ &= 15.14 \cdot 25.4 \\ &= 0.38 \text{ Kg-m.} \end{aligned}$$

$$\begin{aligned} \text{Equivalent Bearing Pressure (f1):} \\ &= \text{fc} \cdot (Y - \text{Adist}) / Y \\ &= 685.06 \cdot (453.91 - 25.4) / 453.91 \\ &= 646.72 \text{ KPa.} \end{aligned}$$

$$\begin{aligned} \text{Overturning Moment due to Bearing Pressure [Mc]:} \\ &= (\text{Adist}^2 \cdot \text{Bpwid} / 6) \cdot (f1 + 2 \cdot \text{fc}) \\ &= (25.4^2 \cdot 150.0 / 6) \cdot (646.72 + 2 \cdot 685.06) \\ &= 3.32 \text{ Kg-m.} \end{aligned}$$

$$\begin{aligned} \text{Baseplate Required Thickness [Treq]:} \\ &= \sqrt{(6 \cdot \max(\text{Mt}, \text{Mc}) / (\text{Bpwid} \cdot \text{Sba}))} \\ &= \sqrt{(6 \cdot \max(0.38, 3.32) / (150.0 \cdot 207.0))} \\ &= 2.5073 \text{ mm} \end{aligned}$$

MDMT Calculations for: Left Saddle, Saddle to Wearplate Junction, Curve: B

Govrn. thk, tg = 9.53, tr = 5.366, c = 3.175 mm, E* = 1.0
Thickness Ratio = tr * E* / (tg - c) = 0.844, Temp. Reduction = 9 °C

Min Metal Temp. w/o impact per UCS-66, Curve B

-29 °C



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 78 of 173

Saddle Calcs: Operating Case: Step: 18 9:52am Aug 12, 2026

Min Metal Temp. at Required thickness (UCS 66.1) -38 °C

ASME VIII Division 2 Horizontal Vessel Analysis, Right Saddle:

Note:

Wear Pad Width (225.00) is less than $1.56 \cdot \sqrt{r_m \cdot t}$
and less than 2a. The wear plate will be ignored.

Minimum Wear Plate Width to be considered in analysis [b1]:

$$= \min(b + 1.56 \cdot \sqrt{R_m \cdot t}, 2a)$$

$$= \min(204.0 + 1.56 \cdot \sqrt{306.3525 \cdot 6.355}, 2 \cdot 960.0)$$

$$= 272.8324 \text{ mm}$$

Input and Calculated Values:

Vessel Mean Radius	Rm	306.35	mm
Shell Thickness used in this Case	t	9.530	mm
Stiffened Vessel Length per 4.15.6	L	4790.00	mm
Distance from Saddle to Vessel tangent	a1 or a	960.00	mm
Saddle Width	b1 or b	204.00	mm
Saddle Bearing Angle	delta or theta	120.00	degrees
Shell Allowable Stress used in Calculation		140.75	N./mm ²
Head Allowable Stress used in Calculation		138.00	N./mm ²
Circumferential Efficiency in Plane of Saddle		1.00	
Circumferential Efficiency at Mid-Span		1.00	
Distance from Saddle Base to Centerline	B	560.00	mm
Coefficient of Friction	mu	0.50	

Results for Horizontal Vessel Analysis:

Saddle Force Q, Operating Case		3918.78	Kgf
Pressure used in Analysis	P	1549.647	KPa.

Horizontal Vessel Analysis Results:	Actual N./mm ²	Allowable N./mm ²
Long. Stress at Top of Midspan	32.28	140.75
Long. Stress at Bottom of Midspan	42.43	140.75
Long. Stress at Top of Saddles	72.48	140.75
Long. Stress at Bottom of Saddles	17.88	140.75
Tangential Shear in Shell	13.85	112.60
Circ. Stress at Horn of Saddle	80.98	175.94
Circ. Compressive Stress in Shell	1.69	140.75

Intermediate Results: Saddle Reaction Q due to Wind or Seismic:

Transverse Saddle Reaction Force [Fwt]:

$$= F_{tr} (F_t / \text{Num of Saddles} + Z \text{ Force Load}) \cdot B / E$$

$$= 3.0 (1062.8/2 + 0) \cdot 560.0/550.0$$

$$= 1623.2 \text{ Kgf}$$

Longitudinal Saddle Reaction Force [Fwl]:

$$= \max(F_{l, \text{wind}}, \text{Sum of X Forces}) \cdot B / L_s$$

$$= \max(96.47, 0) \cdot 560.0/2870.0$$

$$= 18.8 \text{ Kgf}$$

Saddle Reaction Force due to Earthquake FI [Fsl]:

$$= \max(F_{l, \text{eq}}, \text{Sum of X Forces}) \cdot B / L_s$$

$$= \max(404.22, 0) \cdot 560.0/2870.0$$

$$= 78.9 \text{ Kgf}$$



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 79 of 173

Saddle Calcs: Operating Case: Step: 18 9:52am Aug 12, 2026

Saddle Reaction Force due to Earthquake Ft [Fst]:

$$= Ftr(Ft/Num of Saddles + Z Force Load) \cdot B / E$$

$$= 3.0(404/2 + 0) \cdot 560.0/550.0$$

$$= 617.4 \text{ Kg}$$

Load Combination Results for Q + Wind or Seismic [Q]:

$$= \text{Saddle Load} + \max(Fwl, Fwt, Fsl, Fst)$$

$$= 2296 + \max(19, 1623, 79, 617)$$

$$= 3918.8 \text{ Kg}$$

Longitudinal Wind Force [FI]:

$$= \text{WindScalar} \cdot \text{WindPress}(\text{Platform Area} + (\pi/4(\text{OD} \cdot \text{WindDiaMult})^2))$$

$$= 1.1 \cdot 1984.306(0.0 + \pi/4(0.619 \cdot 1.2)^2)$$

$$= 946.068 \text{ N}$$

Summary of Loads at the Base of this Saddle:

Vertical Load (including saddle weight)	4001.17	Kgf
Transverse Shear Load	531.40	Kgf
Longitudinal Shear Load	404.22	Kgf

Note: Wear Plate is Welded to the Shell, $k = 0.1$

Saddle Dimension [E]:

$$= \text{Baseplate Length}$$

$$= 550.000 \text{ mm}$$

The Computed K values from Table 4.15.1:

K1 = 0.1066	K2 = 1.1707	K3 = 0.8799	K4 = 0.4011
K5 = 0.7603	K6 = 0.0529	K7 = 0.0529	K8 = 0.3405
K9 = 0.2711	K10 = 0.0581	K1* = 0.1923	

Note: Dimension a is greater than or equal to $Rm/2$.

Moment per Equation 4.15.1 [M1]:

$$= -Q \cdot a [1 - (1 - a/L + (Rm^2 - hm^2)/(2a \cdot L)) / (1 + (4hm)/3L)]$$

$$= -3919 \cdot 960.0 [1 - (1 - 960.0/4790.0 + (306.352^2 - 0.0^2) /$$

$$(2 \cdot 960.0 \cdot 4790.0) / (1 + (4 \cdot 0.0) / (3 \cdot 4790.0))]$$

$$= -715.6 \text{ Kg-m.}$$

Moment per Equation 4.15.2 [M2]:

$$= Q \cdot L/4 ((1 + 2(Rm^2 - hm^2)/(L^2)) / (1 + (4hm^2)/(3L)) - 4a/L)$$

$$= 3919 \cdot 4790/4 ((1 + 2(306^2 - 0^2)/(4790^2)) / (1 + (4 \cdot 0) /$$

$$(3 \cdot 4790)) - 4 \cdot 960/4790)$$

$$= 969.1 \text{ Kg-m.}$$

Longitudinal Stress at Top of Shell (4.15.4) [σ_1]:

$$= P \cdot Rm/(2t) - M2/(\pi \cdot Rm^2 t)$$

$$= 1549.647 \cdot 306.352/(2 \cdot 6.355) - 969.1/(\pi \cdot 306.4^2 \cdot 6.355)$$

$$= 32.28 \text{ N./mm}^2$$

Longitudinal Stress at Bottom of Shell (4.15.5) [σ_2]:

$$= P \cdot Rm/(2t) + M2/(\pi \cdot Rm^2 \cdot t)$$

$$= 1549.647 \cdot 306.352/(2 \cdot 6.355) + 969.1/(\pi \cdot 306.4^2 \cdot 6.355)$$

$$= 42.43 \text{ N./mm}^2$$

Longitudinal Stress at Top of Shell at Support (4.15.8) [σ_3]:

$$= P \cdot Rm/(2t) - M1/(K1 \cdot \pi \cdot Rm^2 t)$$

$$= 1549.647 \cdot 306.352/(2 \cdot 6.355) - 715.6/(0.1066 \cdot \pi \cdot 306.4^2 \cdot 6.355)$$

$$= 72.48 \text{ N./mm}^2$$

Longitudinal Stress at Bottom of Shell at Support (4.15.9) [σ_4]:

$$= P \cdot Rm/(2t) + M1/(K1* \cdot \pi \cdot Rm^2 \cdot t)$$

$$= 1549.647 \cdot 306.352/(2 \cdot 6.355) + 715.6/(0.1923 \cdot \pi \cdot 306.4^2 \cdot 6.355)$$

$$= 17.88 \text{ N./mm}^2$$



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 80 of 173

Saddle Calcs: Operating Case: Step: 18 9:52am Aug 12,2026

Maximum Shear Force in the Saddle (4.15.3) [T]:

$$= Q(L-2a)/(L+(4 \cdot hm/3))$$

$$= 3919(4790.0 - 2 \cdot 960.0)/(4790.0 + (4 \cdot 0.0/3))$$

$$= 2348.0 \text{ Kg}$$

Shear Stress in the shell no rings, not stiffened (4.15.12) [τ_2]:

$$= K2 \cdot T / (Rm \cdot t)$$

$$= 1.1707 \cdot 2348.0 / (306.3525 \cdot 6.355)$$

$$= 13.85 \text{ N./mm}^2$$

Decay Length (4.15.20) [x1,x2]:

$$= 0.78 \cdot \sqrt{(Rm \cdot t)}$$

$$= 0.78 \cdot \sqrt{(306.352 \cdot 6.355)}$$

$$= 34.416 \text{ mm}$$

Circumferential Stress in shell, no rings (4.15.21) [σ_6]:

$$= -K5 \cdot Q \cdot k / (t(b + X1 + X2))$$

$$= -0.7603 \cdot 3919 \cdot 0.1 / (6.355(204.0 + 34.42 + 34.42))$$

$$= -1.69 \text{ N./mm}^2$$

Circ. Comp. Stress at Horn of Saddle, $L \geq 8Rm$ (4.15.22) [σ_7]:

$$= -Q/(4 \cdot t(b + X1 + X2)) - 3 \cdot K7 \cdot Q / (2 \cdot t^2)$$

$$= -3919 / (4 \cdot 6.355(204.0 + 34.416 + 34.416)) - 3 \cdot 0.0529 \cdot 3919 / (2 \cdot 6.355^2)$$

$$= -80.98 \text{ N./mm}^2$$

Effective reinforcing plate width (4.15.24) [B1]:

$$= \min(b + 1.56 \cdot \sqrt{(Rm \cdot t)}, 2a)$$

$$= \min(204.0 + 1.56 \cdot \sqrt{(306.352 \cdot 6.355)}, 2 \cdot 960.0)$$

$$= 272.83 \text{ mm}$$

Results for Vessel Ribs, Web and Base:

Baseplate Length	Bplen	550.0000	mm
Baseplate Thickness	Bpthk	16.0000	mm
Baseplate Width	Bpwid	150.0000	mm
Number of Ribs (inc. outside ribs)	Nribs	3	
Rib Thickness	Ribtk	16.0000	mm
Web Thickness	Webtk	16.0000	mm
Web Location	Webloc	Side	
Saddle Design Temperature		21.1	°C
Saddle Yield Stress	Sy	262.0	N./mm ²
Height of Web at Center	Hw,c	306.0	mm
Friction Coefficient	mu	0.500	

Moment of Inertia of Saddle - Transverse Direction (90 degrees to long axis)

Inertia of Shell [ShellInertia]:

$$= ((1.56 \cdot \sqrt{(R \cdot t)} + \text{WearPlateWidth})t^3)/12$$

$$= ((1.56 \cdot \sqrt{(303.175 \cdot 6.355)} + 225.0)6.355^3)/12$$

$$= 0.628 \text{ cm}^4$$

Resolved Inertia for the Shell [I,shell]:

$$= \text{ShellInertia} + A_{\text{Shell}}(C1 - Y)^2$$

$$= 0.628 + 18.65(104.303 - 3.177)^2$$

$$= 1907.877 \text{ cm}^4$$

	B mm	D mm	Y mm	A cm ²	AY mm ³	I + AD ⁽²⁾ cm ⁴
Shell	293.5	6.4	3.2	18.7	5926.1	0.191E+04
Wearplate	225.0	12.0	12.4	27.0	33358.5	0.229E+04
Web	16.0	222.5	129.6	35.6	461278.3	0.170E+04
BasePlate	150.0	16.0	248.8	24.0	597180.1	0.502E+04



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 81 of 173

Saddle Calcs: Operating Case: Step: 18 9:52am Aug 12, 2026

Totals	...	...	...	105.2	1097743.0	0.109E+05
--------	-----	-----	-----	-------	-----------	-----------

Distance to Centroid [C1]:

$$= AY / A$$

$$= 1097743/105.246$$

$$= 104.303 \text{ mm}$$

Angle [β]:

$$= 180 - \text{Saddle Angle}/2$$

$$= 180 - 120.0/2$$

$$= 120.0$$

Saddle Splitting Coefficient [K1]:

$$= (1 + \cos(\beta) - 0.5 \cdot \sin(\beta)^2) / (\pi - \beta + \sin(\beta) \cos(\beta))$$

$$= (1 + \cos(120.0) - 0.5 \cdot \sin(120.0)^2) / (\pi - 2.094 + \sin(120.0) \cos(120.0))$$

$$= 0.2035$$

Saddle Splitting Force [Fh]:

$$= K1 \cdot Q$$

$$= 0.204 \cdot 3918.784$$

$$= 797.5575 \text{ Kgf}$$

$$\text{Tension Stress, } St = (Fh / As) = 0.9032 \text{ N./mm}^2$$

$$\text{Allowed Stress, } Sa = 0.6 \cdot \text{Yield Str} = 157.1972 \text{ N./mm}^2$$

Saddle Splitting Dimension [d]:

$$= B - R \cdot \sin(\theta/2) / (\theta/2 \text{ in radians})$$

$$= 560.0 - 303.17 \cdot \sin(120.0/2) / 1.0472$$

$$= 309.276 \text{ mm}$$

$$\text{Bending Moment, } M = Fh \cdot d = 246.6705 \text{ Kg-m.}$$

$$\text{Bending Stress, } Sb = (M \cdot C1 / I) = 2.3132 \text{ N./mm}^2$$

$$\text{Allowed Stress, } Sa = 2/3 \cdot \text{Yield Str} = 174.6635 \text{ N./mm}^2$$

Minimum Thickness of Baseplate per Moss:

$$= \sqrt{(3(Q + \text{SaddleWt}) \text{BasePlateWidth}) / (2 \cdot \text{BasePlateLength} \cdot \text{AllStress}))}$$

$$= \sqrt{(3(3919 + 82)150.0) / (2 \cdot 550.0 \cdot 174.663)} = 9.587 \text{ mm}$$

Calculation of Axial Load, Intermediate Values and Compressive Stress:

Web Length Dimension [Web Length]:

$$= 2 \cdot \cos(90 - \text{Saddle Angle}/2) (\text{Inside Radius} + \text{Shell Thk} + \text{Wear Plate Thk})$$

$$= 2 \cdot \cos(90 - 120.0/2) (300.0 + 9.53 + 12.0)$$

$$= 556.906 \text{ mm}$$

Distance between Ribs [e]:

$$= \text{Web Length} / (\text{Nr ribs} - 1)$$

$$= 556.9062 / (3 - 1)$$

$$= 278.453 \text{ mm}$$

Baseplate Pressure Area [Ap]:

$$= e \cdot \text{Bpwid} / 2$$

$$= 278.4531 \cdot 150.0/2$$

$$= 208.840 \text{ cm}^2$$

Bearing Pressure [Bp]:

$$= (Q + \text{SaddleWt}) / (\text{BasePlateLength} \cdot \text{BasePlateWidth})$$

$$= 4001.167 / (550.0 \cdot 150.0)$$

$$= 4.850 \text{ Kgf/cm}^2$$

Axial Load [P]:

$$= Ap \cdot Bp$$

$$= 208.8 \cdot 4.85$$



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 82 of 173

Saddle Calcs: Operating Case: Step: 18 9:52am Aug 12,2026

= 1012.852 Kgf

Area of the Rib and Web [Ar]:

= Rib Area + Web Area

= 30.08 + 22.276

= 52.356 cm²

Compressive Stress [Sc]:

= P/Ar

= 1012.9/52.3563

= 1.897 N./mm²

Check of Outside Ribs:

Inertia of Saddle, Outer Ribs - Longitudinal Direction

	B	D	Y	A	AY	Io
Rib	16.0	188.0	110.0	30.1	330880.0	0.145E+04
Web	139.2	16.0	8.0	22.3	17821.0	770.
Totals	...	...	...	52.4	348700.9	0.222E+04

Rib dimension [D]:

= Saddle Width - Web Thickness

= 204.0 - 16.0

= 188.000 mm

Distance to Centroid from Datum [ytot]:

= AY / A

= 348700.938/52.356

= 66.602 mm

Distance to Centroid [C1]:

= max(ytot, Saddle Width - ytot)

= max(66.602, 204.0 - 66.602)

= 137.398 mm

Radius of Gyration [r]:

= $\sqrt{\text{Total Inertia} / \text{Total Area}}$

= $\sqrt{2222.2/52.356}$

= 65.150 mm

Length of Outer Rib, step 1, [Lv]:

= Saddle Height - cos(saddle bearing angle / 2)(radius + shlthk + wpdthk) - bpthk

= 560.0 - cos(120.0/2)(300.0 + 9.53 + 12.0) - 16.0

= 383.235 mm

Length of Outer Rib, step 2, [Lw]:

= 2 • sin(saddle bearing angle / 2)(radius + shlthk + wpdthk)

= 2 • sin(120.0/2)(300.0 + 9.53 + 12.0)

= 556.906 mm

Length of Outer Rib, step 3, [Bd]:

= Baseplate length - clearance

= 550.0 - 50.8

= 499.200 mm

Length of Outer Rib, step 4, [Dd]:

= (Lw - Bd)/2

= (556.906 - 499.2)/2

= 28.853 mm

Length of Outer Rib [L]:

= $\sqrt{Lv^2 + Dd^2}$

= $\sqrt{383.235^2 + 28.853^2}$



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 83 of 173

Saddle Calcs: Operating Case: Step: 18 9:52am Aug 12,2026

= 384.320 mm

Intermediate Term [Cc]:

= $\sqrt{(2 \cdot \pi^2 \cdot \text{Elastic Modulus} / \text{Yield Stress})}$

= $\sqrt{(2 \cdot \pi^2 \cdot 0.20270\text{E}+09 / 262.0)}$

= 123.583

Slenderness ratio [KL/r]:

= KL/r

= 1 • 384.32/65.15

= 5.899

Bending Moment [Rm]:

= FI / (2 • Bplen) • e • L / 2

= 404.2 / (2 • 550.0) • 278.453 • 384.32 / 2

= 19.663 Kg-m.

Compressive Allowable, KL/r < Cc (5.899 < 123.583) per AISC E2-1 [Sca]:

= (1 - (KL/r)² / (2 • Cc²)) Fy / (5/3 + 3 • (KL/r) / (8 • Cc) - (KL/r)³ / (8 • Cc³))

= (1 - (5.9)² / (2 • 123.58²)) 262 /

(5/3 + 3 • (5.9) / (8 • 123.58) - (5.9³) / (8 • 123.58³))

= 155.4 N./mm²

AISC Unity Check of Outside Ribs (must be ≤ 1)

= Sc/Sca + (Rm • C1 / I) / Sba

= 1.9/155.35 + (19.66 • 137.398/22222406) / 174.66

= 0.019

Check of Inside Ribs:

Inertia of Saddle, Inner Ribs - Axial Direction

	B	D	Y	A	AY	Io
Rib	16.0	188.0	110.0	30.1	330880.0	0.200E+04
Web	278.5	16.0	8.0	44.6	35642.0	762.
Totals	...	...	...	74.6	366522.0	0.276E+04

Distance to Centroid from Datum [ytot]:

= AY / A

= 366521.969/74.632

= 49.110 mm

Distance to Centroid [C1]:

= max(ytot, abs(Saddle Width - ytot))

= max(49.11, abs(204.0 - 49.11))

= 154.890 mm

Length of Inner Rib [L]:

= Saddle Height - Outside Radius - Bpthk

= 560.0 - cos(321.53/2) (16.0 + 0.0 + 0.0) - 0.0

= 222.470 mm

Radius of Gyration [r]:

= $\sqrt{(\text{Total Inertia} / \text{Total Area})}$

= $\sqrt{(2763.7 / 74.632)}$

= 60.852 mm

Slenderness ratio [KL/r]:

= KL/r

= 1 • 222.47/60.852

= 3.656

Unit Force [Force,u]:

= FI / (2 • Baseplate Length)

= 404.221 / (2 • 550.0)



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 84 of 173

Saddle Calcs: Operating Case: Step: 18 9:52am Aug 12,2026

= 0.367 Kg/mm

Moment at base of inner Rib [Mbase,c]:

= Unit Force • e • L

= 0.367 • 278.453 • 222.47

= 22.764 Kg-m.

Bending Stress due to Transverse Force and Weight Load [σ_B ,base,c]:

= Bending Moment / Section Modulus

= 22.764/178427.25

= 1.251 N./mm²

Compressive Allowable, $KL/r < C_c$ (3.6559 < 123.583) per AISC E2-1 [Sca]:

= (1-(KL/r)²/(2• C_c ²)) F_y /(5/3+3•(KL/r)/(8• C_c)-(KL/r)³)/(8• C_c ³)

= (1-(3.66)²/(2 • 123.58²))262/

(5/3+3•(3.66)/(8• 123.58)-(3.66³)/(8•123.58³)

= 156.1 N./mm²

AISC Unity Check of Inside Ribs (must be ≤ 1)

= $S_c/S_{ca} + (M_{base,c} \cdot C_{1/I})/S_{ba}$

= 3.21/156.09 + (22.76 • 154.89/2763.653)/174.66

= 0.028

Input Data for Base Plate Bolting Calculations:

Total Number of Bolts per BasePlate	Nbolts	2
Total Number of Bolts in Tension/Baseplate	Nbt	1
Bolt Design Temperature		21.1 °C
Bolt Material Specification	SA-193 B7	
Bolt Allowable Stress	Stba	137.29 N./mm ²
Bolt Corrosion Allowance	Bca	1.5 mm
Distance from Bolts to Edge	Edgedis	50.0 mm
Nominal Bolt Diameter	Bnd	24.0000 mm
Thread Series	Series	TEMA Metric
BasePlate Allowable Stress	S	138.00 N./mm ²
Area Available in a Single Bolt	BlArea	2.2586 cm ²
Saddle Load Q0 (Weight)	Q0	2378.0 Kg
Saddle Load QL (Wind/Seismic contribution)	QL	78.9 Kg
Maximum Transverse Force	Ft	531.4 Kg
Maximum Longitudinal Force	F1	404.2 Kg
Saddle Bolted to Steel Foundation		No

Shear Stress in a Single Bolt, Longitudinal Direction [τ_b ,l]:

= $F_l / (\text{Bolt Area} \cdot \text{Number of Bolts})$

= 404.2/(2.259 • 2)

= 8.8 N./mm². Must be less than 107.9 N./mm².

Shear Stress in a Single Bolt, Transverse Direction [τ_b ,t]:

= $F_t / (\text{Bolt Area} \cdot \text{Number of Bolts})$

= 531.4/(2.259 • 2)

= 11.5 N./mm². Must be less than 107.9 N./mm².

Bolt Area Calculation per Dennis R. Moss

Bolt Area Requirement Due to Longitudinal Load [Bltarearl]:

= 0.0 (Q0 > QL --> No Uplift in Longitudinal direction)

Bolt Area due to Shear Load [Bltarears]:

= $F_l / (\text{BoltShearAllowable} \cdot \text{Nbolts})$

= 404.22/(107.87 • 2.0)

= 0.1837 cm²

Bolt Area due to Transverse Load:

Moment on Baseplate Due to Transverse Load [Rmom]:



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 85 of 173

Saddle Calcs: Operating Case: Step: 18 9:52am Aug 12, 2026

$$\begin{aligned}
 &= B \cdot Ft + \text{Sum of X Moments} \\
 &= 560.0 \cdot 531.4 + 0.0 \\
 &= 297.59 \text{ Kg-m.}
 \end{aligned}$$

$$\begin{aligned}
 &\text{Eccentricity (e):} \\
 &= R_{\text{mom}} / QO \\
 &= 297.59 / 2377.97 \\
 &= 125.14 \text{ mm} > B_{\text{plen}} / 6 \rightarrow \text{Uplift in Transverse direction}
 \end{aligned}$$

$$\begin{aligned}
 f &= B_{\text{plen}} / 2 - \text{Edgedis} \\
 &= 550.0 / 2 - 50.01 \\
 &= 224.99 \text{ mm}
 \end{aligned}$$

$$\begin{aligned}
 &\text{Modular Ratio Of Steel/Concrete (n1):} \\
 &= E_S / E_C \\
 &= 203402.5 / 21526.32 \\
 &= 9.45
 \end{aligned}$$

$$\begin{aligned}
 K1 &= 3 (e - 0.5 \cdot B_{\text{plen}}) \\
 &= 3 (125.14 - 0.5 \cdot 550.0) \\
 &= -449.57 \text{ mm}
 \end{aligned}$$

$$\begin{aligned}
 K2 &= 6 \cdot n1 \cdot A_t / B_{\text{pwid}} \cdot (f + e) \\
 &= 6 \cdot 9.45 \cdot 2.26 / 150.0 \cdot (224.99 + 125.14) \\
 &= 29888.67 \text{ mm}^2
 \end{aligned}$$

$$\begin{aligned}
 K3 &= -K2 \cdot (0.5 \cdot B_{\text{plen}} + f) \\
 &= -29888.67 \cdot (0.5 \cdot 550.0 + 224.99) \\
 &= -14943959.32 \text{ mm}^3
 \end{aligned}$$

$$\begin{aligned}
 &\text{Iteratively Solving for the Effective Bearing Length:} \\
 &Y^3 + K1 \cdot Y^2 + K2 \cdot Y + K3 = 0 \\
 &Y^3 + -449.57 \cdot Y^2 + 29888.67 \cdot Y + -0.1E+08 = 0 \\
 &Y = 455.91 \text{ mm}
 \end{aligned}$$

$$\begin{aligned}
 \text{Num} &= (B_{\text{plen}} / 2 - Y / 3 - e) \\
 &= (550.0 / 2 - 455.91 / 3 - 125.14) \\
 &= -2.11
 \end{aligned}$$

$$\begin{aligned}
 \text{Denom} &= (B_{\text{plen}} / 2 - Y / 3 + f) \\
 &= (550.0 / 2 - 455.91 / 3 + 224.99) \\
 &= 348.02
 \end{aligned}$$

$$\begin{aligned}
 &\text{Total Bolt Tension Force [Tforce]:} \\
 &= -QO \cdot \text{Num} / \text{Denom} \\
 &= -2377.97 \cdot -2.11 / 348.02 \\
 &= 14.44 \text{ Kg}
 \end{aligned}$$

$$\begin{aligned}
 &\text{Bolt Area Required due to Transverse Load [Bltareart]:} \\
 &= T_{\text{force}} / (S_{\text{tba}} \cdot N_{\text{bt}}) \\
 &= 14.44 / (137.29 \cdot 1.0) \\
 &= 0.103 \text{ cm}^2
 \end{aligned}$$

$$\begin{aligned}
 &\text{Required Area of a Single Bolt [Bltarear]:} \\
 &= \max[\text{Bltarearl}, \text{Bltarears}, \text{Bltareart}] \\
 &= \max[0.0, 0.1837, 0.103] \\
 &= 0.1837 \text{ cm}^2
 \end{aligned}$$

Baseplate Thickness Calculation per D. Moss:

$$\begin{aligned}
 &\text{Bearing Pressure (fc)} \\
 &= 2(QO + T_{\text{force}}) / (Y \cdot B_{\text{pwid}}) \\
 &= 2(2377.97 + 14.44) / (455.91 \cdot 150.0) \\
 &= 686.12 \text{ KPa.}
 \end{aligned}$$



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 86 of 173

Saddle Calcs: Operating Case: Step: 18 9:52am Aug 12,2026

Distance from Baseplate Edge to the Web [ADIST]:

$$= (B_{plen} - WebLength) / 2$$

$$= (550.0 - 499.2) / 2$$

$$= 25.4000 \text{ mm}$$

Overturning Moment due To Bolt Tension [Mt]:

$$= T_{force} \cdot A_{dist}$$

$$= 14.44 \cdot 25.4$$

$$= 0.37 \text{ Kg-m.}$$

Equivalent Bearing Pressure (f1):

$$= f_c \cdot (Y - A_{dist}) / Y$$

$$= 686.12 \cdot (455.91 - 25.4) / 455.91$$

$$= 647.89 \text{ KPa.}$$

Overturning Moment due to Bearing Pressure [Mc]:

$$= (A_{dist}^2 \cdot B_{pwid} / 6) \cdot (f1 + 2 \cdot f_c)$$

$$= (25.4^2 \cdot 150.0 / 6) \cdot (647.89 + 2 \cdot 686.12)$$

$$= 3.32 \text{ Kg-m.}$$

Baseplate Required Thickness [Treq]:

$$= \sqrt{(6 \cdot \max(Mt, Mc) / (B_{pwid} \cdot S_{ba}))}$$

$$= \sqrt{(6 \cdot \max(0.37, 3.32) / (150.0 \cdot 207.0))}$$

$$= 2.5093 \text{ mm}$$

MDMT Calculations for: Right saddle, Saddle to Wearplate Junction, Curve: B

Govrn. thk, tg = 9.53, tr = 5.366, c = 3.175 mm, E* = 1.0

Thickness Ratio = tr * E* / (tg - c) = 0.844, Temp. Reduction = 9 °C

Min Metal Temp. w/o impact per UCS-66, Curve B -29 °C

Min Metal Temp. at Required thickness (UCS 66.1) -38 °C

Review notes about nozzle loadings and supports in the Warnings report.

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 87 of 173

Saddle Calcs: Test Case:

Step: 19 9:52am Aug 12,2026

ASME VIII Division 2 Horizontal Vessel Analysis, Left Saddle:

Horizontal Vessel Stress Calculations : Test Case

Note:

Wear Pad Width (225.00) is less than $1.56 \cdot \sqrt{r_m \cdot t}$
and less than $2a$. The wear plate will be ignored.

Minimum Wear Plate Width to be considered in analysis [b1]:


$$= \min(b + 1.56 \cdot \sqrt{R_m \cdot t}, 2a)$$

$$= \min(204.0 + 1.56 \cdot \sqrt{304.765 \cdot 9.53}, 2 \cdot 960.0)$$

$$= 288.0724 \text{ mm}$$

Input and Calculated Values:

Vessel Mean Radius	Rm	304.76	mm
Shell Thickness used in this Case	t	9.530	mm
Stiffened Vessel Length per 4.15.6	L	4790.00	mm
Distance from Saddle to Vessel tangent	a1 or a	960.00	mm
Saddle Width	b1 or b	204.00	mm
Saddle Bearing Angle	delta or theta	120.00	degrees
Shell Allowable Stress used in Calculation		228.00	N./mm ²
Head Allowable Stress used in Calculation		228.00	N./mm ²
Circumferential Efficiency in Plane of Saddle		1.00	
Circumferential Efficiency at Mid-Span		1.00	
Distance from Saddle Base to Centerline	B	560.00	mm
Coefficient of Friction	mu	0.00	



Results for Horizontal Vessel Analysis:

Saddle Force Q, Test Case, no Ext. Forces		3281.78	Kgf
Pressure used in Analysis	P	3668.193	KPa.

Horizontal Vessel Analysis Results:	Actual N./mm ²	Allowable N./mm ²
Long. Stress at Top of Midspan	55.80	228.00
Long. Stress at Bottom of Midspan	61.52	228.00
Long. Stress at Top of Saddles	78.49	228.00
Long. Stress at Bottom of Saddles	47.66	228.00



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 88 of 173

Saddle Calcs: Test Case:

Step: 19 9:52am Aug 12, 2026

Tangential Shear in Shell	7.77	127.92
Circ. Stress at Horn of Saddle	31.02	341.99
Circ. Compressive Stress in Shell	0.89	228.00

Intermediate Results: Saddle Reaction Q due to Wind or Seismic:

Transverse Saddle Reaction Force [Fwt]:

$$= \text{Ftr}(\text{Ft/Num of Saddles} + \text{Z Force Load}) \cdot B / E$$

$$= 3.0(350.7/2 + 0) \cdot 560.0/550.0$$

$$= 535.7 \text{ Kgf}$$

Longitudinal Saddle Reaction Force [Fwl]:

$$= \max(\text{Fl,wind}; \text{Sum of X Forces}) \cdot B / Ls$$

$$= \max(31.84, 0) \cdot 560.0/2870.0$$

$$= 6.2 \text{ Kgf}$$

Load Combination Results for Q + Wind or Seismic [Q]:

$$= \text{Saddle Load} + \max(\text{Fwl}, \text{Fwt}, \text{Fsl}, \text{Fst})$$

$$= 2746 + \max(6, 536, 0, 0)$$

$$= 3281.8 \text{ Kgf}$$

Longitudinal Wind Force [Fl]:

$$= \text{WindScalar} \cdot \text{WindPress}(\text{Platform Area} + (\pi/4(\text{OD} \cdot \text{WindDiaMult})^2))$$

$$= 1.1 \cdot 1984.306(0.0 + \pi/4(0.619 \cdot 1.2)^2)$$

$$= 946.068 \text{ N}$$

Summary of Loads at the Base of this Saddle:

Vertical Load (including saddle weight)	3364.16	Kgf
Transverse Shear Load	175.36	Kgf
Longitudinal Shear Load	31.84	Kgf

Note: Wear Plate is Welded to the Shell, k = 0.1

Saddle Dimension [E]:

$$= \text{Baseplate Length}$$

$$= 550.000 \text{ mm}$$

The Computed K values from Table 4.15.1:

K1 = 0.1066	K2 = 1.1707	K3 = 0.8799	K4 = 0.4011
K5 = 0.7603	K6 = 0.0529	K7 = 0.0529	K8 = 0.3405
K9 = 0.2711	K10 = 0.0581	K1* = 0.1923	

Note: Dimension a is greater than or equal to Rm/2.

Moment per Equation 4.15.1 [M1]:

$$= -Q \cdot a [1 - (1 - a/L + (Rm^2 - hm^2)/(2a \cdot L))/(1 + (4hm)/3L)]$$

$$= -3282 \cdot 960.0 [1 - (1 - 960.0/4790.0 + (304.765^2 - 0.0^2)/(2 \cdot 960.0 \cdot 4790.0))/(1 + (4 \cdot 0.0)/(3 \cdot 4790.0))]$$

$$= -599.6 \text{ Kg-m.}$$

Moment per Equation 4.15.2 [M2]:

$$= Q \cdot L/4((1 + 2(Rm^2 - hm^2)/(L^2))/(1 + (4hm^2)/(3L)) - 4a/L)$$

$$= 3282 \cdot 4790/4((1 + 2(305^2 - 0^2)/(4790^2))/(1 + (4 \cdot 0)/(3 \cdot 4790)) - 4 \cdot 960/4790)$$

$$= 811.3 \text{ Kg-m.}$$

Longitudinal Stress at Top of Shell (4.15.4) [σ_1]:

$$= P \cdot Rm/(2t) - M2/(\pi \cdot Rm^2 t)$$

$$= 3668.193 \cdot 304.765/(2 \cdot 9.53) - 811.3/(\pi \cdot 304.8^2 \cdot 9.53)$$

$$= 55.80 \text{ N/mm}^2$$

Longitudinal Stress at Bottom of Shell (4.15.5) [σ_2]:

$$= P \cdot Rm/(2t) + M2/(\pi \cdot Rm^2 \cdot t)$$



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 89 of 173

Saddle Calcs: Test Case:

Step: 19 9:52am Aug 12, 2026

$$= 3668.193 \cdot 304.765 / (2 \cdot 9.53) + 811.3 / (\pi \cdot 304.8^2 \cdot 9.53)$$

$$= 61.52 \text{ N./mm}^2$$

Longitudinal Stress at Top of Shell at Support (4.15.8) [σ_3]:

$$= P \cdot R_m / (2t) - M1 / (K1 \cdot \pi \cdot R_m^2 t)$$

$$= 3668.193 \cdot 304.765 / (2 \cdot 9.53) - 599.6 / (0.1066 \cdot \pi \cdot 304.8^2 \cdot 9.53)$$

$$= 78.49 \text{ N./mm}^2$$

Longitudinal Stress at Bottom of Shell at Support (4.15.9) [σ_4]:

$$= P \cdot R_m / (2t) + M1 / (K1 \cdot \pi \cdot R_m^2 \cdot t)$$

$$= 3668.193 \cdot 304.765 / (2 \cdot 9.53) + 599.6 / (0.1923 \cdot \pi \cdot 304.8^2 \cdot 9.53)$$

$$= 47.66 \text{ N./mm}^2$$

Maximum Shear Force in the Saddle (4.15.3) [T]:

$$= Q(L-2a) / (L + (4 \cdot h_m / 3))$$

$$= 3282(4790.0 - 2 \cdot 960.0) / (4790.0 + (4 \cdot 0.0 / 3))$$

$$= 1966.3 \text{ Kg}$$

Shear Stress in the shell no rings, not stiffened (4.15.12) [τ_2]:

$$= K2 \cdot T / (R_m \cdot t)$$

$$= 1.1707 \cdot 1966.33 / (304.765 \cdot 9.53)$$

$$= 7.77 \text{ N./mm}^2$$

Decay Length (4.15.20) [x_1, x_2]:

$$= 0.78 \cdot \sqrt{(R_m \cdot t)}$$

$$= 0.78 \cdot \sqrt{(304.765 \cdot 9.53)}$$

$$= 42.036 \text{ mm}$$

Circumferential Stress in shell, no rings (4.15.21) [σ_6]:

$$= -K5 \cdot Q \cdot k / (t(b + X1 + X2))$$

$$= -0.7603 \cdot 3282 \cdot 0.1 / (9.53(204.0 + 42.04 + 42.04))$$

$$= -0.89 \text{ N./mm}^2$$

Circ. Comp. Stress at Horn of Saddle, $L \geq 8R_m$ (4.15.22) [σ_7]:

$$= -Q / (4 \cdot t(b + X1 + X2)) - 3 \cdot K7 \cdot Q / (2 \cdot t^2)$$

$$= -3282 / (4 \cdot 9.53(204.0 + 42.036 + 42.036)) -$$

$$3 \cdot 0.0529 \cdot 3282 / (2 \cdot 9.53^2)$$

$$= -31.02 \text{ N./mm}^2$$

Effective reinforcing plate width (4.15.24) [B1]:

$$= \min(b + 1.56 \cdot \sqrt{(R_m \cdot t)}, 2a)$$

$$= \min(204.0 + 1.56 \cdot \sqrt{(304.765 \cdot 9.53)}, 2 \cdot 960.0)$$

$$= 288.07 \text{ mm}$$

Results for Vessel Ribs, Web and Base:

Baseplate Length	Bplen	550.0000	mm
Baseplate Thickness	Bpthk	16.0000	mm
Baseplate Width	Bpwid	150.0000	mm
Number of Ribs (inc. outside ribs)	Nribs	3	
Rib Thickness	Ribtk	16.0000	mm
Web Thickness	Webtk	16.0000	mm
Web Location	Webloc	Side	
Saddle Yield Stress	Sy	260.0	N./mm ²
Height of Web at Center	Hw,c	306.0	mm
Friction Coefficient	mu	0.000	

Moment of Inertia of Saddle - Transverse Direction (90 degrees to long axis)

Inertia of Shell [ShellInertia]:

$$= ((1.56 \cdot \sqrt{(R \cdot t)} + \text{WearPlateWidth})^3) / 12$$

$$= ((1.56 \cdot \sqrt{(300.0 \cdot 9.53)} + 225.0)^3) / 12$$

$$= 2.224 \text{ cm}^4$$

Resolved Inertia for the Shell [I,shell]:

$$= \text{ShellInertia} + A_{\text{Shell}}(C1 - Y)^2$$



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 90 of 173

Saddle Calcs: Test Case:

Step: 19 9:52am Aug 12,2026

$$= 2.224 + 29.392(97.711 - 4.765)^2$$

$$= 2541.343 \text{ cm}^4$$

	B mm	D mm	Y mm	A cm ²	AY mm ³	I + AD ² cm ⁴
Shell	308.4	9.5	4.8	29.4	14005.2	0.254E+04
Wearplate	225.0	12.0	15.5	27.0	41931.0	0.183E+04
Web	16.0	222.5	132.8	35.6	472579.8	0.191E+04
BasePlate	150.0	16.0	252.0	24.0	604800.1	0.572E+04
Totals	...	...	...	116.0	1133316.0	0.120E+05

Distance to Centroid [C1]:

$$= AY / A$$

$$= 1133316/115.987$$

$$= 97.711 \text{ mm}$$

Angle [β]:

$$= 180 - \text{Saddle Angle}/2$$

$$= 180 - 120.0/2$$

$$= 120.0$$

Saddle Splitting Coefficient [K1]:

$$= (1 + \cos(\beta) - 0.5 \cdot \sin(\beta)^2) / (\pi - \beta + \sin(\beta) \cos(\beta))$$

$$= (1 + \cos(120.0) - 0.5 \cdot \sin(120.0)^2) / (\pi - 2.094 + \sin(120.0) \cos(120.0))$$

$$= 0.2035$$

Saddle Splitting Force [Fh]:

$$= K1 \cdot Q$$

$$= 0.204 \cdot 3281.776$$

$$= 667.9127 \text{ Kg}$$

$$\text{Tension Stress, } St = (Fh / As) = 0.7564 \text{ N./mm}^2$$

$$\text{Allowed Stress, } Sa = 0.6 \cdot \text{Yield Str} = 155.9972 \text{ N./mm}^2$$

Saddle Splitting Dimension [d]:

$$= B - R \cdot \sin(\theta/2) / (\theta/2 \text{ in radians})$$

$$= 560.0 - 300.0 \cdot \sin(120.0/2) / 1.0472$$

$$= 311.902 \text{ mm}$$

$$\text{Bending Moment, } M = Fh \cdot d = 208.3274 \text{ Kg-m.}$$

$$\text{Bending Stress, } Sb = (M \cdot C1 / I) = 1.6646 \text{ N./mm}^2$$

$$\text{Allowed Stress, } Sa = 2/3 \cdot \text{Yield Str} = 173.3302 \text{ N./mm}^2$$

Minimum Thickness of Baseplate per Moss:

$$= \sqrt{(3(Q + \text{SaddleWt}) \cdot \text{BasePlateWidth}) / (2 \cdot \text{BasePlateLength} \cdot \text{AllStress})}$$

$$= \sqrt{(3(3282 + 82)150.0 / (2 \cdot 550.0 \cdot 173.33))}$$

$$= 8.824 \text{ mm}$$

Calculation of Axial Load, Intermediate Values and Compressive Stress:

Web Length Dimension [Web Length]:

$$= 2 \cdot \cos(90 - \text{Saddle Angle}/2) (\text{Inside Radius} + \text{Shell Thk} + \text{Wear Plate Thk})$$

$$= 2 \cdot \cos(90 - 120.0/2) (300.0 + 9.53 + 12.0)$$

$$= 556.906 \text{ mm}$$

Distance between Ribs [e]:

$$= \text{Web Length} / (N_{\text{ribs}} - 1)$$

$$= 556.9062 / (3 - 1)$$

$$= 278.453 \text{ mm}$$

Baseplate Pressure Area [Ap]:

$$= e \cdot \text{Bpwid} / 2$$

$$= 278.4531 \cdot 150.0/2$$



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 91 of 173

Saddle Calcs: Test Case:

Step: 19 9:52am Aug 12,2026

$$= 208.840 \text{ cm}^2$$

Bearing Pressure [Bp]:

$$= (Q + \text{SaddleWt}) / (\text{BasePlateLength} \cdot \text{BasePlateWidth})$$

$$= 3364.159 / (550.0 \cdot 150.0)$$

$$= 4.078 \text{ Kg/cm}^2$$

Axial Load [P]:

$$= A_p \cdot B_p$$

$$= 208.8 \cdot 4.08$$

$$= 851.601 \text{ Kg}$$

Area of the Rib and Web [Ar]:

$$= \text{Rib Area} + \text{Web Area}$$

$$= 30.08 + 22.276$$

$$= 52.356 \text{ cm}^2$$

Compressive Stress [Sc]:

$$= P / A_r$$

$$= 851.6 / 52.3563$$

$$= 1.595 \text{ N/mm}^2$$

Check of Outside Ribs:

Inertia of Saddle, Outer Ribs - Longitudinal Direction

	B	D	Y	A	AY	Io
Rib	16.0	188.0	110.0	30.1	330880.0	0.145E+04
Web	139.2	16.0	8.0	22.3	17821.0	770.
Totals	...	...	...	52.4	348700.9	0.222E+04

Rib dimension [D]:

$$= \text{Saddle Width} - \text{Web Thickness}$$

$$= 204.0 - 16.0$$

$$= 188.000 \text{ mm}$$

Distance to Centroid from Datum [ytot]:

$$= AY / A$$

$$= 348700.938 / 52.356$$

$$= 66.602 \text{ mm}$$

Distance to Centroid [C1]:

$$= \max(\text{ytot}, \text{Saddle Width} - \text{ytot})$$

$$= \max(66.602, 204.0 - 66.602)$$

$$= 137.398 \text{ mm}$$

Radius of Gyration [r]:

$$= \sqrt{(\text{Total Inertia} / \text{Total Area})}$$

$$= \sqrt{(2222.2 / 52.356)}$$

$$= 65.150 \text{ mm}$$

Length of Outer Rib, step 1, [Lv]:

$$= \text{Saddle Height} - \cos(\text{saddle bearing angle} / 2) (\text{radius} + \text{shlthk} + \text{wpdthk}) - \text{bpthk}$$

$$= 560.0 - \cos(120.0 / 2) (300.0 + 9.53 + 12.0) - 16.0$$

$$= 383.235 \text{ mm}$$

Length of Outer Rib, step 2, [Lw]:

$$= 2 \cdot \sin(\text{saddle bearing angle} / 2) (\text{radius} + \text{shlthk} + \text{wpdthk})$$

$$= 2 \cdot \sin(120.0 / 2) (300.0 + 9.53 + 12.0)$$

$$= 556.906 \text{ mm}$$

Length of Outer Rib, step 3, [Bd]:

$$= \text{Baseplate length} - \text{clearance}$$

$$= 550.0 - 50.8$$



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 92 of 173

Saddle Calcs: Test Case:

Step: 19 9:52am Aug 12, 2026

= 499.200 mm

Length of Outer Rib, step 4, [Dd]:

= (Lw - Bd)/2

= (556.906 - 499.2)/2

= 28.853 mm

Length of Outer Rib [L]:

= $\sqrt{(Lv^2 + Dd^2)}$

= $\sqrt{(383.235^2 + 28.853^2)}$

= 384.320 mm

Intermediate Term [Cc]:

= $\sqrt{(2 \cdot \pi^2 \cdot \text{Elastic Modulus} / \text{Yield Stress})}$

= $\sqrt{(2 \cdot \pi^2 \cdot 0.20270\text{E}+09/260.0)}$

= 124.057

Slenderness ratio [KL/r]:

= KL/r

= 1 • 384.32/65.15

= 5.899

Bending Moment [Rm]:

= FI / (2 • Bplen) • e • L / 2

= 31.8 / (2 • 550.0) • 278.453 • 384.32/2

= 1.549 Kg-m.

Compressive Allowable, KL/r < Cc (5.899 < 124.0574) per AISC E2-1 [Sca]:

= (1 - (KL/r)² / (2 • Cc²)) Fy / (5/3 + 3 • (KL/r) / (8 • Cc) - (KL/r)³ / (8 • Cc³))

= (1 - (5.9)² / (2 • 124.06²)) 260 /

(5/3 + 3 • (5.9) / (8 • 124.06) - (5.9³) / (8 • 124.06³))

= 154.2 N./mm²

AISC Unity Check of Outside Ribs (must be ≤ 1)

= Sc/Sca + (Rm • C1 / I) / Sba

= 1.6/154.17 + (1.55 • 137.398/22222406) / 173.33

= 0.011

Check of Inside Ribs:

Inertia of Saddle, Inner Ribs - Axial Direction

	B	D	Y	A	AY	Io
Rib	16.0	188.0	110.0	30.1	330880.0	0.200E+04
Web	278.5	16.0	8.0	44.6	35642.0	762.
Totals	...	...	...	74.6	366522.0	0.276E+04

Distance to Centroid from Datum [ytot]:

= AY / A

= 366521.969/74.632

= 49.110 mm

Distance to Centroid [C1]:

= max(ytot, abs(Saddle Width - ytot))

= max(49.11, abs(204.0 - 49.11))

= 154.890 mm

Length of Inner Rib [L]:

= Saddle Height - Outside Radius - Bpthk

= 560.0 - cos(321.53/2) (16.0 + 0.0 + 0.0) - 0.0

= 222.470 mm

Radius of Gyration [r]:

= $\sqrt{(\text{Total Inertia} / \text{Total Area})}$

= $\sqrt{(2763.7/74.632)}$



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 93 of 173

Saddle Calcs: Test Case:

Step: 19 9:52am Aug 12, 2026

= 60.852 mm

Slenderness ratio [KL/r]:

= KL/r

= 1 • 222.47/60.852

= 3.656

Unit Force [Force,u]:

= FI / (2 • Baseplate Length)

= 31.836/(2 • 550.0)

= 0.029 Kg/mm

Moment at base of inner Rib [Mbase,c]:

= Unit Force • e • L

= 0.029 • 278.453 • 222.47

= 1.793 Kg-m.

Bending Stress due to Transverse Force and Weight Load [σ_B ,base,c]:

= Bending Moment / Section Modulus

= 1.793/178427.25

= 0.099 N./mm²

Compressive Allowable, KL/r < Cc (3.6559 < 124.0574) per AISC E2-1 [Sca]:

= (1-(KL/r)²/(2•Cc²))Fy/(5/3+3•(KL/r)/(8•Cc)-(KL/r)³/(8•Cc³))

= (1-(3.66)²/(2 • 124.06²))260/

(5/3+3•(3.66)/(8• 124.06)-(3.66³)/(8•124.06³))

= 154.9 N./mm²

AISC Unity Check of Inside Ribs (must be ≤ 1)

= Sc/Sca + (Mbase,c • C1/I)/Sba

= 2.7/154.9 + (1.79 • 154.89/2763.653)/173.33

= 0.018

Input Data for Base Plate Bolting Calculations:

Total Number of Bolts per BasePlate	Nbolts	2
Total Number of Bolts in Tension/Baseplate	Nbt	1
Bolt Material Specification		SA-193 B7
Bolt Allowable Stress	Stba	172.00 N./mm ²
Bolt Corrosion Allowance	Bca	1.5 mm
Distance from Bolts to Edge	Edgedis	50.0 mm
Nominal Bolt Diameter	Bnd	24.0000 mm
Thread Series	Series	TEMA Metric
BasePlate Allowable Stress	S	138.00 N./mm ²
Area Available in a Single Bolt	BltArea	2.2586 cm ²
Saddle Load QO (Weight)	QO	2828.5 Kg
Saddle Load QL (Wind/Seismic contribution)	QL	6.2 Kg
Maximum Transverse Force	Ft	175.4 Kg
Maximum Longitudinal Force	F1	31.8 Kg
Saddle Bolted to Steel Foundation		No

Shear Stress in a Single Bolt, Longitudinal Direction [τ_b ,l]:

= FI / (Bolt Area • Number of Bolts)

= 31.8/(2.259 • 2)

= 0.7 N./mm². Must be less than 103.2 N./mm².

Shear Stress in a Single Bolt, Transverse Direction [τ_b ,t]:

= Ft / (Bolt Area • Number of Bolts)

= 175.4/(2.259 • 2)

= 3.8 N./mm². Must be less than 103.2 N./mm².

Bolt Area Calculation per Dennis R. Moss

Bolt Area Requirement Due to Longitudinal Load [Bltarearl]:

= 0.0 (QO > QL --> No Uplift in Longitudinal direction)



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 94 of 173

Saddle Calcs: Test Case:

Step: 19 9:52am Aug 12,2026

Bolt Area due to Shear Load [Bltarears]:

= $F_l / (\text{BoltShearAllowable} \cdot N_{\text{bolts}})$

= $31.84 / (103.2 \cdot 2.0)$

= 0.0151 cm²

Bolt Area due to Transverse Load:

Moment on Baseplate Due to Transverse Load [Rmom]:

= $B \cdot F_t + \text{Sum of X Moments}$

= $560.0 \cdot 175.36 + 0.0$

= 98.21 Kg-m.

Eccentricity (e):

= R_{mom} / QO

= $98.21 / 2828.5$

= 34.72 mm < $B_{\text{plen}}/6$ --> No Uplift in Transverse direction

Bolt Area due to Transverse Load [Bltareart]:

= 0 (No Uplift)

Required Area of a Single Bolt [Bltarear]:

= $\max[B_{\text{tarearl}}, B_{\text{tarears}}, B_{\text{tareart}}]$

= $\max[0.0, 0.0151, 0.0]$

= 0.0151 cm²

ASME VIII Division 2 Horizontal Vessel Analysis, Right Saddle:

Note:

Wear Pad Width (225.00) is less than $1.56 \cdot \sqrt{r_m \cdot t}$
and less than 2a. The wear plate will be ignored.

Minimum Wear Plate Width to be considered in analysis [b1]:

= $\min(b + 1.56 \cdot \sqrt{R_m \cdot t}, 2a)$

= $\min(204.0 + 1.56 \cdot \sqrt{304.765 \cdot 9.53}, 2 \cdot 960.0)$

= 288.0724 mm

Input and Calculated Values:

Vessel Mean Radius	Rm	304.76	mm
Shell Thickness used in this Case	t	9.530	mm
Stiffened Vessel Length per 4.15.6	L	4790.00	mm
Distance from Saddle to Vessel tangent	a1 or a	960.00	mm
Saddle Width	b1 or b	204.00	mm
Saddle Bearing Angle	delta or theta	120.00	degrees
Shell Allowable Stress used in Calculation		228.00	N./mm ²
Head Allowable Stress used in Calculation		228.00	N./mm ²
Circumferential Efficiency in Plane of Saddle		1.00	
Circumferential Efficiency at Mid-Span		1.00	
Distance from Saddle Base to Centerline	B	560.00	mm
Coefficient of Friction	mu	0.50	

Results for Horizontal Vessel Analysis:

Saddle Force Q, Test Case, no Ext. Forces		3296.65	Kgf
Pressure used in Analysis	P	3668.193	KPa.

Horizontal Vessel Analysis Results:		Actual	Allowable
		N./mm ²	N./mm ²
Long. Stress at Top	of Midspan	55.78	228.00



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 95 of 173

Saddle Calcs: Test Case: Step: 19 9:52am Aug 12, 2026

Long. Stress at Bottom of Midspan	61.53	228.00
Long. Stress at Top of Saddles	78.58	228.00
Long. Stress at Bottom of Saddles	47.61	228.00
Tangential Shear in Shell	7.81	127.92
Circ. Stress at Horn of Saddle	31.16	341.99
Circ. Compressive Stress in Shell	0.90	228.00

Intermediate Results: Saddle Reaction Q due to Wind or Seismic:

Transverse Saddle Reaction Force [Fwt]:

$$= Ftr(Ft/Num of Saddles + Z Force Load) \cdot B / E$$

$$= 3.0(350.7/2 + 0) \cdot 560.0/550.0$$

$$= 535.7 \text{ Kgf}$$

Longitudinal Saddle Reaction Force [Fwl]:

$$= \max(F_{l,wind}; \text{Sum of X Forces}) \cdot B / L_s$$

$$= \max(31.84, 0) \cdot 560.0/2870.0$$

$$= 6.2 \text{ Kgf}$$

Load Combination Results for Q + Wind or Seismic [Q]:

$$= \text{Saddle Load} + \max(F_{wl}, F_{wt}, F_{sl}, F_{st})$$

$$= 2761 + \max(6, 536, 0, 0)$$

$$= 3296.7 \text{ Kgf}$$

Longitudinal Wind Force [FI]:

$$= \text{WindScalar} \cdot \text{WindPress} (\text{Platform Area} + (\pi/4 (\text{OD} \cdot \text{WindDiaMult})^2))$$

$$= 1.1 \cdot 1984.306 (0.0 + \pi/4 (0.619 \cdot 1.2)^2)$$

$$= 946.068 \text{ N}$$

Summary of Loads at the Base of this Saddle:

Vertical Load (including saddle weight)	3379.04	Kgf
Transverse Shear Load	175.36	Kgf
Longitudinal Shear Load	31.84	Kgf

Note: Wear Plate is Welded to the Shell, $k = 0.1$

Saddle Dimension [E]:

$$= \text{Baseplate Length}$$

$$= 550.000 \text{ mm}$$

The Computed K values from Table 4.15.1:

K1 = 0.1066	K2 = 1.1707	K3 = 0.8799	K4 = 0.4011
K5 = 0.7603	K6 = 0.0529	K7 = 0.0529	K8 = 0.3405
K9 = 0.2711	K10 = 0.0581	K1* = 0.1923	

Note: Dimension a is greater than or equal to $R_m/2$.

Moment per Equation 4.15.1 [M1]:

$$= -Q \cdot a [1 - (1 - a/L + (R_m^2 - h_m^2)/(2a \cdot L)) / (1 + (4h_m)/3L)]$$

$$= -3297 \cdot 960.0 [1 - (1 - 960.0/4790.0 + (304.765^2 - 0.0^2) / (2 \cdot 960.0 \cdot 4790.0)) / (1 + (4 \cdot 0.0) / (3 \cdot 4790.0))]$$

$$= -602.3 \text{ Kg-m.}$$

Moment per Equation 4.15.2 [M2]:

$$= Q \cdot L / 4 ((1 + 2(R_m^2 - h_m^2)/(L^2)) / (1 + (4h_m^2)/(3L)) - 4a/L)$$

$$= 3297 \cdot 4790 / 4 ((1 + 2(305^2 - 0^2)/(4790^2)) / (1 + (4 \cdot 0) / (3 \cdot 4790)) - 4 \cdot 960 / 4790)$$

$$= 814.9 \text{ Kg-m.}$$

Longitudinal Stress at Top of Shell (4.15.4) [σ_1]:

$$= P \cdot R_m / (2t) - M_2 / (\pi \cdot R_m^2 t)$$

$$= 3668.193 \cdot 304.765 / (2 \cdot 9.53) - 814.9 / (\pi \cdot 304.8^2 \cdot 9.53)$$

$$= 55.78 \text{ N./mm}^2$$



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 96 of 173

Saddle Calcs: Test Case:

Step: 19 9:52am Aug 12, 2026

Longitudinal Stress at Bottom of Shell (4.15.5) [σ_2]:

$$= P \cdot R_m / (2t) + M_2 / (\pi \cdot R_m^2 \cdot t)$$

$$= 3668.193 \cdot 304.765 / (2 \cdot 9.53) + 814.9 / (\pi \cdot 304.8^2 \cdot 9.53)$$

$$= 61.53 \text{ N./mm}^2$$

Longitudinal Stress at Top of Shell at Support (4.15.8) [σ_3]:

$$= P \cdot R_m / (2t) - M_1 / (K_1 \cdot \pi \cdot R_m^2 \cdot t)$$

$$= 3668.193 \cdot 304.765 / (2 \cdot 9.53) - 602.3 / (0.1066 \cdot \pi \cdot 304.8^2 \cdot 9.53)$$

$$= 78.58 \text{ N./mm}^2$$

Longitudinal Stress at Bottom of Shell at Support (4.15.9) [σ_4]:

$$= P \cdot R_m / (2t) + M_1 / (K_1 \cdot \pi \cdot R_m^2 \cdot t)$$

$$= 3668.193 \cdot 304.765 / (2 \cdot 9.53) + 602.3 / (0.1923 \cdot \pi \cdot 304.8^2 \cdot 9.53)$$

$$= 47.61 \text{ N./mm}^2$$

Maximum Shear Force in the Saddle (4.15.3) [T]:

$$= Q(L-2a) / (L + (4 \cdot h_m / 3))$$

$$= 3297(4790.0 - 2 \cdot 960.0) / (4790.0 + (4 \cdot 0.0 / 3))$$

$$= 1975.2 \text{ Kgf}$$

Shear Stress in the shell no rings, not stiffened (4.15.12) [τ_2]:

$$= K_2 \cdot T / (R_m \cdot t)$$

$$= 1.1707 \cdot 1975.24 / (304.765 \cdot 9.53)$$

$$= 7.81 \text{ N./mm}^2$$

Decay Length (4.15.20) [x_1, x_2]:

$$= 0.78 \cdot \sqrt{(R_m \cdot t)}$$

$$= 0.78 \cdot \sqrt{(304.765 \cdot 9.53)}$$

$$= 42.036 \text{ mm}$$

Circumferential Stress in shell, no rings (4.15.21) [σ_6]:

$$= -K_5 \cdot Q \cdot k / (t(b + X_1 + X_2))$$

$$= -0.7603 \cdot 3297 \cdot 0.1 / (9.53(204.0 + 42.04 + 42.04))$$

$$= -0.90 \text{ N./mm}^2$$

Circ. Comp. Stress at Horn of Saddle, $L \geq 8R_m$ (4.15.22) [σ_7]:

$$= -Q / (4 \cdot t(b + X_1 + X_2)) - 3 \cdot K_7 \cdot Q / (2 \cdot t^2)$$

$$= -3297 / (4 \cdot 9.53(204.0 + 42.036 + 42.036)) - 3 \cdot 0.0529 \cdot 3297 / (2 \cdot 9.53^2)$$

$$= -31.16 \text{ N./mm}^2$$

Effective reinforcing plate width (4.15.24) [B1]:

$$= \min(b + 1.56 \cdot \sqrt{(R_m \cdot t)}, 2a)$$

$$= \min(204.0 + 1.56 \cdot \sqrt{(304.765 \cdot 9.53)}, 2 \cdot 960.0)$$

$$= 288.07 \text{ mm}$$

Results for Vessel Ribs, Web and Base:

Baseplate Length	Bplen	550.0000	mm
Baseplate Thickness	Bpthk	16.0000	mm
Baseplate Width	Bpwid	150.0000	mm
Number of Ribs (inc. outside ribs)	Nribs	3	
Rib Thickness	Ribtk	16.0000	mm
Web Thickness	Webtk	16.0000	mm
Web Location	Webloc	Side	
Saddle Yield Stress	Sy	260.0	N./mm ²
Height of Web at Center	Hw,c	306.0	mm
Friction Coefficient	mu	0.500	

Moment of Inertia of Saddle - Transverse Direction (90 degrees to long axis)

Inertia of Shell [ShellInertia]:

$$= ((1.56 \cdot \sqrt{(R \cdot t)} + \text{WearPlateWidth})t^3) / 12$$

$$= ((1.56 \cdot \sqrt{(300.0 \cdot 9.53)} + 225.0)9.53^3) / 12$$



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 97 of 173

Saddle Calcs: Test Case:

Step: 19 9:52am Aug 12,2026

$$= 2.224 \text{ cm}^4$$

Resolved Inertia for the Shell [I,shell]:

$$= \text{ShellInertia} + A_{\text{Shell}}(C1 - Y)^2$$

$$= 2.224 + 29.392(97.711 - 4.765)^2$$

$$= 2541.343 \text{ cm}^4$$

	B mm	D mm	Y mm	A cm ²	AY mm ³	I + AD ² (2) cm ⁴
Shell	308.4	9.5	4.8	29.4	14005.2	0.254E+04
Wearplate	225.0	12.0	15.5	27.0	41931.0	0.183E+04
Web	16.0	222.5	132.8	35.6	472579.8	0.191E+04
BasePlate	150.0	16.0	252.0	24.0	604800.1	0.572E+04
Totals	...	...	...	116.0	1133316.0	0.120E+05

Distance to Centroid [C1]:

$$= AY / A$$

$$= 1133316/115.987$$

$$= 97.711 \text{ mm}$$

Angle [β]:

$$= 180 - \text{Saddle Angle}/2$$

$$= 180 - 120.0/2$$

$$= 120.0$$

Saddle Splitting Coefficient [K1]:

$$= (1 + \cos(\beta) - 0.5 \cdot \sin(\beta)^2) / (\pi - \beta + \sin(\beta) \cos(\beta))$$

$$= (1 + \cos(120.0) - 0.5 \cdot \sin(120.0)^2) / (\pi - 2.094 + \sin(120.0) \cos(120.0))$$

$$= 0.2035$$

Saddle Splitting Force [Fh]:

$$= K1 \cdot Q$$

$$= 0.204 \cdot 3296.655$$

$$= 670.9407 \text{ Kg}$$

$$\text{Tension Stress, } St = (Fh / As) = 0.7598 \text{ N./mm}^2$$

$$\text{Allowed Stress, } Sa = 0.6 \cdot \text{Yield Str} = 155.9972 \text{ N./mm}^2$$

Saddle Splitting Dimension [d]:

$$= B - R \cdot \sin(\text{theta}/2) / (\text{theta}/2 \text{ in radians})$$

$$= 560.0 - 300.0 \cdot \sin(120.0/2) / 1.0472$$

$$= 311.902 \text{ mm}$$

$$\text{Bending Moment, } M = Fh \cdot d = 209.2719 \text{ Kg-m.}$$

$$\text{Bending Stress, } Sb = (M \cdot C1 / I) = 1.6722 \text{ N./mm}^2$$

$$\text{Allowed Stress, } Sa = 2/3 \cdot \text{Yield Str} = 173.3302 \text{ N./mm}^2$$

Minimum Thickness of Baseplate per Moss:

$$= \sqrt{(3(Q + \text{SaddleWt}) \cdot \text{BasePlateWidth}) / (2 \cdot \text{BasePlateLength} \cdot \text{AllStress})}$$

$$= \sqrt{(3(3297 + 82)150.0) / (2 \cdot 550.0 \cdot 173.33)}$$

$$= 8.844 \text{ mm}$$

Calculation of Axial Load, Intermediate Values and Compressive Stress:

Web Length Dimension [Web Length]:

$$= 2 \cdot \cos(90 - \text{Saddle Angle}/2) (\text{Inside Radius} + \text{Shell Thk} + \text{Wear Plate Thk})$$

$$= 2 \cdot \cos(90 - 120.0/2) (300.0 + 9.53 + 12.0)$$

$$= 556.906 \text{ mm}$$

Distance between Ribs [e]:

$$= \text{Web Length} / (N_{\text{ribs}} - 1)$$

$$= 556.9062 / (3 - 1)$$

$$= 278.453 \text{ mm}$$



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 98 of 173

Saddle Calcs: Test Case:

Step: 19 9:52am Aug 12,2026

Baseplate Pressure Area [Ap]:

$$= e \cdot Bpwid / 2$$

$$= 278.4531 \cdot 150.0 / 2$$

$$= 208.840 \text{ cm}^2$$

Bearing Pressure [Bp]:

$$= (Q + SaddleWt) / (BasePlateLength \cdot BasePlateWidth)$$

$$= 3379.037 / (550.0 \cdot 150.0)$$

$$= 4.096 \text{ Kg/cm}^2$$

Axial Load [P]:

$$= Ap \cdot Bp$$

$$= 208.8 \cdot 4.1$$

$$= 855.367 \text{ Kg}$$

Area of the Rib and Web [Ar]:

$$= Rib \text{ Area} + Web \text{ Area}$$

$$= 30.08 + 22.276$$

$$= 52.356 \text{ cm}^2$$

Compressive Stress [Sc]:

$$= P / Ar$$

$$= 855.4 / 52.3563$$

$$= 1.602 \text{ N./mm}^2$$

Check of Outside Ribs:

Inertia of Saddle, Outer Ribs - Longitudinal Direction

	B	D	Y	A	AY	Io
Rib	16.0	188.0	110.0	30.1	330880.0	0.145E+04
Web	139.2	16.0	8.0	22.3	17821.0	770.
Totals	...	...	...	52.4	348700.9	0.222E+04

Rib dimension [D]:

$$= Saddle \text{ Width} - Web \text{ Thickness}$$

$$= 204.0 - 16.0$$

$$= 188.000 \text{ mm}$$

Distance to Centroid from Datum [ytot]:

$$= AY / A$$

$$= 348700.938 / 52.356$$

$$= 66.602 \text{ mm}$$

Distance to Centroid [C1]:

$$= \max(ytot, Saddle \text{ Width} - ytot)$$

$$= \max(66.602, 204.0 - 66.602)$$

$$= 137.398 \text{ mm}$$

Radius of Gyration [r]:

$$= \sqrt{ (Total \text{ Inertia} / Total \text{ Area}) }$$

$$= \sqrt{ (2222.2 / 52.356) }$$

$$= 65.150 \text{ mm}$$

Length of Outer Rib, step 1, [Lv]:

$$= Saddle \text{ Height} - \cos(saddle \text{ bearing angle} / 2) (radius + shlthk + wpdthk) - bpthk$$

$$= 560.0 - \cos(120.0 / 2) (300.0 + 9.53 + 12.0) - 16.0$$

$$= 383.235 \text{ mm}$$

Length of Outer Rib, step 2, [Lw]:

$$= 2 \cdot \sin(saddle \text{ bearing angle} / 2) (radius + shlthk + wpdthk)$$

$$= 2 \cdot \sin(120.0 / 2) (300.0 + 9.53 + 12.0)$$

$$= 556.906 \text{ mm}$$



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 99 of 173

Saddle Calcs: Test Case:

Step: 19 9:52am Aug 12, 2026

Length of Outer Rib, step 3, [Bd]:

$$= \text{Baseplate length} - \text{clearance}$$

$$= 550.0 - 50.8$$

$$= 499.200 \text{ mm}$$

Length of Outer Rib, step 4, [Dd]:

$$= (L_w - B_d) / 2$$

$$= (556.906 - 499.2) / 2$$

$$= 28.853 \text{ mm}$$

Length of Outer Rib [L]:

$$= \sqrt{(L_v^2 + D_d^2)}$$

$$= \sqrt{(383.235^2 + 28.853^2)}$$

$$= 384.320 \text{ mm}$$

Intermediate Term [Cc]:

$$= \sqrt{(2 \cdot \pi^2 \cdot \text{Elastic Modulus} / \text{Yield Stress})}$$

$$= \sqrt{(2 \cdot \pi^2 \cdot 0.20270\text{E}+09 / 260.0)}$$

$$= 124.057$$

Slenderness ratio [KL/r]:

$$= KL / r$$

$$= 1 \cdot 384.32 / 65.15$$

$$= 5.899$$

Bending Moment [Rm]:

$$= F_l / (2 \cdot B_{plen}) \cdot e \cdot L / 2$$

$$= 31.8 / (2 \cdot 550.0) \cdot 278.453 \cdot 384.32 / 2$$

$$= 1.549 \text{ Kg-m.}$$

Compressive Allowable, $KL/r < C_c$ ($5.899 < 124.0574$) per AISC E2-1 [Sca]:

$$= (1 - (KL/r)^2 / (2 \cdot C_c^2)) F_y / (5/3 + 3 \cdot (KL/r) / (8 \cdot C_c) - (KL/r)^3 / (8 \cdot C_c^3))$$

$$= (1 - (5.9)^2 / (2 \cdot 124.06^2)) 260 /$$

$$(5/3 + 3 \cdot (5.9) / (8 \cdot 124.06) - (5.9^3) / (8 \cdot 124.06^3))$$

$$= 154.2 \text{ N./mm}^2$$

AISC Unity Check of Outside Ribs (must be ≤ 1)

$$= S_c / S_{ca} + (R_m \cdot C_1 / I) / S_{ba}$$

$$= 1.6 / 154.17 + (1.55 \cdot 137.398 / 22222406) / 173.33$$

$$= 0.011$$

Check of Inside Ribs:

Inertia of Saddle, Inner Ribs - Axial Direction

	B	D	Y	A	AY	Io
Rib	16.0	188.0	110.0	30.1	330880.0	0.200E+04
Web	278.5	16.0	8.0	44.6	35642.0	762.
Totals	...	...	...	74.6	366522.0	0.276E+04

Distance to Centroid from Datum [ytot]:

$$= AY / A$$

$$= 366521.969 / 74.632$$

$$= 49.110 \text{ mm}$$

Distance to Centroid [C1]:

$$= \max(y_{tot}, \text{abs}(\text{Saddle Width} - y_{tot}))$$

$$= \max(49.11, \text{abs}(204.0 - 49.11))$$

$$= 154.890 \text{ mm}$$

Length of Inner Rib [L]:

$$= \text{Saddle Height} - \text{Outside Radius} - B_{pthk}$$

$$= 560.0 - \cos(321.53/2) (16.0 + 0.0 + 0.0) - 0.0$$

$$= 222.470 \text{ mm}$$



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 100 of 173

Saddle Calcs: Test Case:

Step: 19 9:52am Aug 12,2026

Radius of Gyration [r]:

$$= \sqrt{\text{Total Inertia} / \text{Total Area}}$$

$$= \sqrt{2763.7/74.632}$$

$$= 60.852 \text{ mm}$$

Slenderness ratio [KL/r]:

$$= KL/r$$

$$= 1 \cdot 222.47/60.852$$

$$= 3.656$$

Unit Force [Force,u]:

$$= FI / (2 \cdot \text{Baseplate Length})$$

$$= 31.836/(2 \cdot 550.0)$$

$$= 0.029 \text{ Kg/mm}$$

Moment at base of inner Rib [Mbase,c]:

$$= \text{Unit Force} \cdot e \cdot L$$

$$= 0.029 \cdot 278.453 \cdot 222.47$$

$$= 1.793 \text{ Kg-m.}$$

Bending Stress due to Transverse Force and Weight Load [σ_B ,base,c]:

$$= \text{Bending Moment} / \text{Section Modulus}$$

$$= 1.793/178427.25$$

$$= 0.099 \text{ N./mm}^2$$

Compressive Allowable, $KL/r < C_c$ ($3.6559 < 124.0574$) per AISC E2-1 [Sca]:

$$= (1 - (KL/r)^2 / (2 \cdot C_c^2)) F_y / (5/3 + 3 \cdot (KL/r) / (8 \cdot C_c) - (KL/r)^3 / (8 \cdot C_c^3))$$

$$= (1 - (3.66)^2 / (2 \cdot 124.06^2)) 260 /$$

$$(5/3 + 3 \cdot (3.66) / (8 \cdot 124.06) - (3.66^3) / (8 \cdot 124.06^3))$$

$$= 154.9 \text{ N./mm}^2$$

AISC Unity Check of Inside Ribs (must be ≤ 1)

$$= S_c / S_{ca} + (M_{base,c} \cdot C_{1/I}) / S_{ba}$$

$$= 2.71/154.9 + (1.79 \cdot 154.89/2763.653) / 173.33$$

$$= 0.018$$

Input Data for Base Plate Bolting Calculations:

Total Number of Bolts per BasePlate	Nbolts	2
Total Number of Bolts in Tension/Baseplate	Nbt	1
Bolt Material Specification		SA-193 B7
Bolt Allowable Stress	Stba	172.00 N./mm ²
Bolt Corrosion Allowance	Bca	1.5 mm
Distance from Bolts to Edge	Edgedis	50.0 mm
Nominal Bolt Diameter	Bnd	24.0000 mm
Thread Series	Series	TEMA Metric
BasePlate Allowable Stress	S	138.00 N./mm ²
Area Available in a Single Bolt	BltArea	2.2586 cm ²
Saddle Load Q0 (Weight)	Q0	2843.4 Kg
Saddle Load QL (Wind/Seismic contribution)	QL	6.2 Kg
Maximum Transverse Force	Ft	175.4 Kg
Maximum Longitudinal Force	F1	31.8 Kg
Saddle Bolted to Steel Foundation	No	

Shear Stress in a Single Bolt, Longitudinal Direction [τ_b ,l]:

$$= FI / (\text{Bolt Area} \cdot \text{Number of Bolts})$$

$$= 31.8/(2.259 \cdot 2)$$

$$= 0.7 \text{ N./mm}^2. \text{ Must be less than } 103.2 \text{ N./mm}^2.$$

Shear Stress in a Single Bolt, Transverse Direction [τ_b ,t]:

$$= Ft / (\text{Bolt Area} \cdot \text{Number of Bolts})$$

$$= 175.4/(2.259 \cdot 2)$$

$$= 3.8 \text{ N./mm}^2. \text{ Must be less than } 103.2 \text{ N./mm}^2.$$



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 101 of 173

Saddle Calcs: Test Case:

Step: 19 9:52am Aug 12, 2026

Bolt Area Calculation per Dennis R. Moss

Bolt Area Requirement Due to Longitudinal Load [Bltarearl]:
= 0.0 (QO > QL --> No Uplift in Longitudinal direction)

Bolt Area due to Shear Load [Bltarears]:
= $F_l / (\text{BoltShearAllowable} \cdot \text{Nbols})$
= $31.84 / (103.2 \cdot 2.0)$
= 0.0151 cm²

Bolt Area due to Transverse Load:

Moment on Baseplate Due to Transverse Load [Rmom]:
= $B \cdot F_t + \text{Sum of X Moments}$
= $560.0 \cdot 175.36 + 0.0$
= 98.21 Kg-m.

Eccentricity (e):
= R_{mom} / QO
= $98.21 / 2843.38$
= 34.54 mm < Bplen/6 --> No Uplift in Transverse direction

Bolt Area due to Transverse Load [Bltareart]:
= 0 (No Uplift)

Required Area of a Single Bolt [Bltarear]:
= $\max[\text{Bltarearl}, \text{Bltarears}, \text{Bltareart}]$
= $\max[0.0, 0.0151, 0.0]$
= 0.0151 cm²

Review notes about nozzle loadings and supports in the Warnings report.

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 102 of 173

Nozzle Calcs.: N1- Channel inl

Nozl: 9 9:52am Aug 12,2026

Input, Nozzle Desc: N1- Channel inlet

From: 20

Pressure for Reinforcement Calculations	P	1197.381	KPa.
Temperature for Internal Pressure	Temp	77	°C
Parent Material		SA-106 B	
Parent Allowable Stress at Temperature	Sv	118.00	N./mm ²
Parent Allowable Stress At Ambient	Sva	118.00	N./mm ²
Inside Diameter of Cylindrical Shell	D	600.00	mm
Shell Finished (Minimum) Thickness	t	9.5300	mm
Shell Internal Corrosion Allowance	c	3.1750	mm
Shell External Corrosion Allowance	co	0.0000	mm
Distance from Bottom/Left Tangent		376.20	mm
User Entered Minimum Design Metal Temperature		11.40	°C

Type of Element Connected to the Parent : Nozzle

Material		SA-106 B	
Material UNS Number		K03006	
Material Specification/Type		Smls. pipe	
Allowable Stress at Temperature	Sn	118.00	N./mm ²
Allowable Stress At Ambient	Sna	118.00	N./mm ²
Diameter Basis (for tr calc only)		Outside	
Layout Angle		90.00	deg
Diameter		6.0000	in.
Size and Thickness Basis		Nominal	
Nominal Thickness		80	
Flange Material		SA-105	
Flange Type		Weld Neck Flange	
Corrosion Allowance	can	3.1750	mm
Joint Efficiency of Shell Seam at Nozzle	E1	1.00	
Joint Efficiency of Nozzle Neck	En	1.00	
Outside Projection	ho	250.0000	mm
Weld leg size between Nozzle and Pad/Shell	Wo	30.0000	mm
Groove weld depth between Nozzle and Vessel	Wgnv	9.5300	mm
Inside Projection	h	0.0000	mm
Weld leg size, Inside Element to Shell	Wi	0.0000	mm
Pad Material		SA-516 70	
Pad Allowable Stress at Temperature	Sp	138.00	N./mm ²
Pad Allowable Stress At Ambient	Spa	138.00	N./mm ²
Diameter of Pad along vessel surface	Dp	308.2750	mm
Thickness of Pad	te	10.0000	mm
Weld leg size between Pad and Shell	Wp	8.0000	mm
Groove weld depth between Pad and Nozzle	Wgpn	10.0000	mm
Reinforcing Pad Width		70.0000	mm
Flange Class		150	
Flange Grade		GR 1.1	

The Pressure Design option was Design Pressure + static head.




PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 103 of 173

Nozzle Calcs.: N1- Channel inl

Nozl: 9 9:52am Aug 12,2026



Reinforcement CALCULATION, Description: N1- Channel inlet

ASME Code, Section VIII, Div. 1, UG-37 to UG-45

Actual Outside Diameter Used in Calculation	6.625 in.
Actual Thickness Used in Calculation	0.432 in.

Nozzle input data check completed without errors.

Reqd thk per UG-37(a) of Cylindrical Shell, tr [Int. Press]
 $= P \cdot R / (S_v \cdot E - 0.6 \cdot P)$ per UG-27 (c)(1)
 $= 1197.38 \cdot 303.175 / (118 \cdot 1.0 - 0.6 \cdot 1197.38)$
 $= 3.0955 \text{ mm}$

Reqd thk per UG-37(a) of Nozzle Wall, trn [Int. Press]
 $= P \cdot R_o / (S_n \cdot E + 0.4 \cdot P)$ per Appendix 1-1 (a)(1)
 $= 1197.38 \cdot 84.1375 / (118 \cdot 1.0 + 0.4 \cdot 1197.38)$
 $= 0.8504 \text{ mm}$

UG-40, Limits of Reinforcement: [Internal Pressure]

Parallel to Vessel Wall (Diameter Limit)	D1	305.3588 mm
Parallel to Vessel Wall, opening length	d	152.6794 mm
Normal to Vessel Wall (Thickness Limit), pad side Tlwp		15.8875 mm

The Pad diameter is greater than the Diameter Limit. The excess will not be considered.

Weld Strength Reduction Factor [fr1]:
 $= \min(1, S_n / S_v)$
 $= \min(1, 118.0 / 118.0)$
 $= 1.000$

Weld Strength Reduction Factor [fr2]:
 $= \min(1, S_n / S_v)$
 $= \min(1, 118.0 / 118.0)$
 $= 1.000$

Weld Strength Reduction Factor [fr4]:
 $= \min(1, S_p / S_v)$
 $= \min(1, 138.0 / 118.0)$
 $= 1.000$

Weld Strength Reduction Factor [fr3]:
 $= \min(fr2, fr4)$
 $= \min(1.0, 1.0)$
 $= 1.000$



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 104 of 173

Nozzle Calcs.: N1- Channel in1

Noz1: 9 9:52am Aug 12,2026




Figure UG 37.1 Nozzle Areas

Results of Nozzle Reinforcement Area Calculations: (cm²)

AREA AVAILABLE, A1 to A5		Design	External	Mapnc
Area Required	Ar	4.726	NA	NA
Area in Shell	A1	4.977	NA	NA
Area in Nozzle Wall	A2	2.208	NA	NA
Area in Inward Nozzle	A3	0.000	NA	NA
Area in Welds	A41+A42+A43	3.186	NA	NA
Area in Element	A5	13.708	NA	NA
TOTAL AREA AVAILABLE	Atot	24.078	NA	NA

The Internal Pressure Case Governs the Analysis.

Nozzle Angle Used in Area Calculations

90.00 degs.

The area available without a pad is Sufficient.

The area available with the given pad is Sufficient.

Area Required [A]:

$$\begin{aligned}
 &= (d \cdot tr \cdot F + 2 \cdot tn \cdot tr \cdot F \cdot (1 - fr1)) \text{ UG-37(c)} \\
 &= (152.6794 \cdot 3.0955 \cdot 1.0 + 2 \cdot 7.7978 \cdot 3.0955 \cdot 1.0 \cdot (1 - 1.0)) \\
 &= 4.726 \text{ cm}^2
 \end{aligned}$$

Reinforcement Areas per Figure UG-37.1

Area Available in Shell [A1]:

$$\begin{aligned}
 &= d(E1 \cdot t - F \cdot tr) - 2 \cdot tn(E1 \cdot t - F \cdot tr) \cdot (1 - fr1) \\
 &= 152.679(1.0 \cdot 6.355 - 1.0 \cdot 3.095) - 2 \cdot 7.798 \\
 &\quad (1.0 \cdot 6.355 - 1.0 \cdot 3.095) \cdot (1 - 1.0) \\
 &= 4.977 \text{ cm}^2
 \end{aligned}$$

Area Available in Nozzle Wall Projecting Outward [A2]:

$$\begin{aligned}
 &= (2 \cdot Tlwp) \cdot (tn - trn) \cdot fr2 \\
 &= (2 \cdot 15.89) \cdot (7.8 - 0.85) \cdot 1.0
 \end{aligned}$$



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 105 of 173

Nozzle Calcs.: N1- Channel inl Nozl: 9 9:52am Aug 12,2026

= 2.208 cm²

Area Available in Welds [A41 + A42 + A43]:

= (Wo² - Ar Lost)•Fr3+((Wi-can/0.707)² - Ar Lost)•fr2 + Wp²•fr4

= (3.1859) • 1.0 + (0.0) • 1.0 + 0.0² • 1.0

= 3.186 cm²

Area Available in Element [A5]:

= (min(Dp,DL)-(Nozzle OD))•(min(tp,Tlwp,te)) • fr4

= (305.3588 - 168.275) • 10.0 • 1.0

= 13.708 cm²

UG-45 Minimum Nozzle Neck Thickness Requirement: [Int. Press.]

Wall Thickness for Internal/External pressures ta = 4.0254 mm

Wall Thickness per UG16(b), tr16b = 5.6750 mm

Wall Thickness, shell/head, internal pressure trb1 = 6.2705 mm

Wall Thickness tb1 = max(trb1, tr16b) = 6.2705 mm

Wall Thickness tb2 = max(trb2, tr16b) = 5.6750 mm

Wall Thickness per table UG-45 tb3 = 9.3950 mm

Determine Nozzle Thickness candidate [tb]:

= min[tb3, max(tb1,tb2)]

= min[9.395, max(6.2705, 5.675)]

= 6.2705 mm

Minimum Wall Thickness of Nozzle Necks [tUG-45]:

= max(ta, tb)

= max(4.0254, 6.2705)

= 6.2705 mm

Available Nozzle Neck Thickness = 0.875 * 10.973 = 9.601 mm -> OK

Stresses on Nozzle due to External and Pressure Loads per the ASME B31.3 Piping Code, (see 319.4.4 and 302.3.5):

Sustained	:	4.6,	Allowable	:	118.0 N./mm ²	Passed
Expansion	:	0.0,	Allowable	:	290.4 N./mm ²	Passed
Occasional	:	5.6,	Allowable	:	156.9 N./mm ²	Passed
Shear	:	4.6,	Allowable	:	82.6 N./mm ²	Passed

The number of cycles on this nozzle was assumed to be 7000 or less for the determination of the expansion stress allowable.

Nozzle Junction Minimum Design Metal Temperature (MDMT) Calculations:

Nozzle Neck to Flange Weld, min(Curve:B, Curve:A)

Govrn. thk, tg = 9.601, tr = 0.85, c = 3.175 mm, E* = 1.0

Thickness Ratio = tr * E*/(tg - c) = 0.132, Temp. Reduction = 78 °C

Min Metal Temp. w/o impact per UCS-66, Curve A -8 °C

Min Metal Temp. at Required thickness (UCS 66.1) -104 °C

Min Metal Temp. w/o impact per UG-20(f) -29 °C

Nozzle Neck to Pad Weld for the Nozzle, Curve: B

Govrn. thk, tg = 9.601, tr = 0.85, c = 3.175 mm, E* = 1.0

Thickness Ratio = tr * E*/(tg - c) = 0.132, Temp. Reduction = 78 °C

Min Metal Temp. w/o impact per UCS-66, Curve B -29 °C

Min Metal Temp. at Required thickness (UCS 66.1) -104 °C

Nozzle Neck to Pad Weld for Reinforcement pad, Curve: B

Govrn. thk, tg = 9.601, tr = 0.85, c = 3.175 mm, E* = 1.0



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 106 of 173

Nozzle Calcs.: N1- Channel inl Nozl: 9 9:52am Aug 12,2026

Thickness Ratio = $tr * E^* / (tg - c) = 0.132$, Temp. Reduction = 78 °C

Min Metal Temp. w/o impact per UCS-66, Curve B -29 °C
Min Metal Temp. at Required thickness (UCS 66.1) -104 °C

Shell to Pad Weld Junction at Pad OD, Curve: B

Govrn. thk, $tg = 9.53$, $tr = 3.095$, $c = 3.175$ mm, $E^* = 1.0$
Thickness Ratio = $tr * E^* / (tg - c) = 0.487$, Temp. Reduction = 34 °C

Min Metal Temp. w/o impact per UCS-66, Curve B -29 °C
Min Metal Temp. at Required thickness (UCS 66.1) -48 °C

Nozzle-Shell/Head Weld (UCS-66(a)(b)), Curve: B

Govrn. thk, $tg = 9.53$, $tr = 3.095$, $c = 3.175$ mm, $E^* = 1.0$
Thickness Ratio = $tr * E^* / (tg - c) = 0.487$, Temp. Reduction = 34 °C

Min Metal Temp. w/o impact per UCS-66, Curve B -29 °C
Min Metal Temp. at Required thickness (UCS 66.1) -48 °C

Gov. MDMT of the Nozzle : -48 °C
Gov. MDMT of the Reinforcement Pad : -48 °C
Gov. MDMT of the nozzle to shell joint welded assembly : -48 °C

Flange MDMT including Temperature reduction per UCS-66.1:

Unadjusted MDMT of ASME B16.5/47 flanges per UCS-66(c) -18 °C
Flange MDMT with Temp reduction per UCS-66(b)(1)(-b) -39 °C

Where the Stress Reduction Ratio per UCS-66(b)(1)(-b) is :
Design Pressure/Ambient Rating = $1197.38 / 1960.01 = 0.611$

Weld Size Calculations, Description: N1- Channel inl

Intermediate Calc. for nozzle/shell Welds T_{min} 7.7978 mm
Intermediate Calc. for pad/shell Welds T_{minPad} 6.3550 mm

Results Per UW-16.1:

	Required Thickness	Actual Thickness
Nozzle Weld	$5.4585 = 0.7 * t_{min}$	$21.2100 = 0.7 * W_o$ mm
Pad Weld	$3.1775 = 0.5 * T_{minPad}$	$5.6560 = 0.7 * W_p$ mm

Weld Strength and Weld Loads per UG-41.1, Sketch (a) or (b)

Weld Load [W]:
= $\max(0, (A - A1 + 2 \cdot t_n \cdot fr1 \cdot (E1 \cdot t - tr)) \cdot Sv)$
= $\max(0, (4.7262 - 4.9766 + 2 \cdot 7.7978 \cdot 1.0 \cdot (1.0 \cdot 6.355 - 3.0955)) \cdot 118)$
= 310.33 Kgf

Note: F is always set to 1.0 throughout the calculation.

Weld Load [W1]:
= $(A2 + A5 + A4 - (Wi - Can / .707)^2 \cdot fr2) \cdot Sv$
= $(2.2075 + 13.7084 + 3.1859 - 0.0 \cdot 1.0) \cdot 118$
= 22983.69 Kgf

Weld Load [W2]:
= $(A2 + A3 + A4 + (2 \cdot t_n \cdot t \cdot fr1)) \cdot Sv$
= $(2.2075 + 0.0 + 7.0084 + (0.9911)) \cdot 118$
= 12281.30 Kgf

Weld Load [W3]:
= $(A2 + A3 + A4 + A5 + (2 \cdot t_n \cdot t \cdot fr1)) \cdot S$



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 107 of 173

Nozzle Calcs.: N1- Channel inl Nozl: 9 9:52am Aug 12,2026

$$= (2.2075 + 0.0 + 3.1859 + 13.7084 + (0.9911)) \cdot 118$$

$$= 24176.20 \text{ Kgf}$$

Strength of Connection Elements for Failure Path Analysis

Shear, Outward Nozzle Weld [Sonw]:

$$= (\pi/2) \cdot Dlo \cdot Wo \cdot 0.49 \cdot Snw$$

$$= (3.1416/2.0) \cdot 168.275 \cdot 30.0 \cdot 0.49 \cdot 118$$

$$= 46752. \text{ Kgf}$$

Shear, Pad Element Weld [Spew]:

$$= (\pi/2) \cdot DP \cdot WP \cdot 0.49 \cdot SEW$$

$$= (3.1416/2.0) \cdot 308.275 \cdot 8.0 \cdot 0.49 \cdot 118$$

$$= 22840. \text{ Kgf}$$

Shear, Nozzle Wall [Snw]:

$$= (\pi \cdot (Dlr + Dlo)/4) \cdot (Thk - Can) \cdot 0.7 \cdot Sn$$

$$= (3.1416 \cdot 80.2386) \cdot (10.9728 - 3.175) \cdot 0.7 \cdot 118$$

$$= 16556. \text{ Kgf}$$

Tension, Pad Groove Weld [Tpgw]:

$$= (\pi/2) \cdot Dlo \cdot Wgpn \cdot 0.74 \cdot Seg$$

$$= (3.1416/2) \cdot 168.275 \cdot 10.0 \cdot 0.74 \cdot 138$$

$$= 27524. \text{ Kgf}$$

Tension, Shell Groove Weld [Tngw]:

$$= (\pi/2) \cdot Dlo \cdot (T - cas) \cdot 0.74 \cdot Sng$$

$$= (3.1416/2.0) \cdot 168.275 \cdot (9.53 - 3.175) \cdot 0.74 \cdot 118$$

$$= 14957. \text{ Kgf}$$

See UG-41 and UW-15 for clarification of allowable stresses.

Strength of Failure Paths:

Failure Path [Path 1-1]:

$$= (SPEW + SNW) = (22840 + 16556) = 39395 \text{ Kgf}$$

Failure Path [Path 2-2]:

$$= (Sonw + Tpgw + Tngw + Sinw)$$

$$= (46752 + 27524 + 14957 + 0) = 89233 \text{ Kgf}$$

Failure Path [Path 3-3]:

$$= (Spew + Tngw + Sinw)$$

$$= (22840 + 14957 + 0) = 37796 \text{ Kgf}$$

Summary of Failure Path Calculations:

Path 1-1 = 39395	Kgf, must exceed W = 310 Kgf	or W1 = 22983 Kgf
Path 2-2 = 89232	Kgf, must exceed W = 310 Kgf	or W2 = 12281 Kgf
Path 3-3 = 37796	Kgf, must exceed W = 310 Kgf	or W3 = 24176 Kgf

Maximum Allowable Pressure for this Nozzle at this Location:

Converged Maximum Allowable Pressure in the Operating case: 2437 KPa.

Note: The MAWP of this junction was limited by the parent Shell/Head.

The Drop for this Nozzle is : 12.0402 mm

The Cut Length for this Nozzle is, Drop + Ho + H + T : 271.5701 mm

Input Echo, WRC297 Item 1, Description: N1- Channel in:

Diameter Basis for Cylindrical Shell	ID
Shell Internal Corrosion Allowance	3.1750 mm
Shell External Corrosion Allowance	0.0000 mm
Shell Diameter	600.000 mm
Shell Thickness	9.5300 mm



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 108 of 173

Nozzle Calcs.: N1- Channel inl Nozl: 9 9:52am Aug 12,2026

Shell Stress Concentration Factor		1.000	
Vessel Material		SA-106 B	
Vessel Cold S.I. Allowable	Smc	118.00	N./mm ²
Vessel Hot S.I. Allowable	Smh	118.00	N./mm ²

See ASME VIII Div. 2, 4.1.6.3, for determination of the SPS allowable.

Diameter Basis for Nozzle		OD	
Nozzle Corrosion Allowance		3.1750	mm
Nozzle Diameter		168.275	mm
Nozzle Thickness		10.9728	mm
Nozzle Stress Concentration Factor		1.000	
Nozzle Material		SA-106 B	
Nozzle Cold S.I. Allowable	SNmc	118.00	N./mm ²
Nozzle Hot S.I. Allowable	SNmh	118.00	N./mm ²

See ASME VIII Div. 2, 4.1.6.3, for determination of the SPS allowable.

Diameter of Reinforcing Pad	308.275	mm
Thickness of Reinforcing Pad	10.0000	mm

Note:

External Forces and Moments in WRC 107/537 Convention:

These loads are assumed to be SUSained loads.

Design Internal Pressure	Dp	1197.38	KPa.
Radial Load	P	-407.91	Kgf
Circumferential Shear	Vc	611.87	Kgf
Longitudinal Shear	Vl	611.87	Kgf
Circumferential Moment	Mc	0.28	Kg-m.
Longitudinal Moment	Ml	0.37	Kg-m.
Torsional Moment	Mt	0.46	Kg-m.

Include Axial Pressure Thrust	No
Include Pressure Stress Indices per Div. 2	No
Local Loads applied at end of Nozzle/Attachment	No

Stress Computations at the Edge of the Nozzle:

Stress Attenuation Diameter (for Insert Plates) per WRC 297:

$$= \text{NozzleOD} + 2 \cdot 1.65 \cdot \sqrt{(R_{\text{mean}}(t - ca))}$$

$$= 168.275 + 2 \cdot 1.65 \cdot \sqrt{(311.353(9.53 - 3.175))}$$

$$= 315.065 \text{ mm}$$

WRC 297 Curve Access Parameters:

Vessel Mean Diameter	(D) =	622.705	mm
Nozzle Outside Diameter	(d) =	168.275	mm
Vessel Thickness used	(T) =	16.355	mm
Nozzle Thickness used	(t) =	7.798	mm
T / t	=	2.097	
d / t	=	21.580	

$$\lambda = [(d/D) \cdot \sqrt{(D/T)}] = 1.667$$

Nr/P	=	0.077
Mr/P	=	0.087
M0/P	=	0.053
N0/P	=	0.154
MrD/Mc	=	0.196
NrDL/Mc	=	0.131
M0d/Mc	=	0.142



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 109 of 173

Nozzle Calcs.: N1- Channel inl Nozl: 9 9:52am Aug 12,2026

NØDL/Mc = 0.151
MrD/Ml = 0.134
NrDL/Ml = 0.085
MØD/Ml = 0.093
NØDL/Ml = 0.266

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Stresses Normal to longitudinal plane)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Outplane Membrane (P)	2	2	2	2
Outplane Bending (P)	4	-4	4	-4
Outplane Membrane (Mc)	0	0	0	0
Outplane Bending (Mc)	0	0	0	0
Outplane Membrane (ML)	0	0	0	0
Outplane Bending (ML)	0	0	0	0
Normal Pressure Stress	21	22	21	22
Outplane Stress Summary	28	20	28	20

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Stresses parallel to longitudinal plane)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Inplane Membrane (P)	1	1	1	1
Inplane Bending (P)	7	-7	7	-7
Inplane Membrane (Mc)	0	0	0	0
Inplane Bending (Mc)	0	0	0	0
Inplane Membrane (ML)	0	0	0	0
Inplane Bending (ML)	0	0	0	0
Inplane Pressure Stress	10	10	10	10
Inplane Stress Summary	19	4	19	4

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Shear stress normal to longitudinal plane)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Outplane Shear (Vc)	1	1	-1	-1
Outplane Shear (Vl)	0	0	0	0
Outplane Shear (Mt)	0	0	0	0
Shear Stress Summary	1	1	-1	-1

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Stress Intensities)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Two * Max Shear Stress	28	20	28	20

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Stresses Normal to circumferential plane)	Cu Left Outside	Cl Left Inside	Du Right Outside	Dl Right Inside
Outplane Membrane (P)	2	2	2	2
Outplane Bending (P)	4	-4	4	-4
Outplane Membrane (Mc)	0	0	0	0
Outplane Bending (Mc)	0	0	0	0
Outplane Membrane (ML)	0	0	0	0
Outplane Bending (ML)	0	0	0	0



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 110 of 173

Nozzle Calcs.: N1- Channel inl Nozl: 9 9:52am Aug 12,2026

Normal Pressure Stress	10	10	10	10
------------------------	----	----	----	----

Outplane Stress Summary	17	8	17	8
-------------------------	----	---	----	---

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Stresses parallel to circumferential plane)	Cu Left Outside	Cl Left Inside	Du Right Outside	Dl Right Inside
--	-----------------------	----------------------	------------------------	-----------------------

Inplane Membrane (P)	1	1	1	1
Inplane Bending (P)	7	-7	7	-7
Inplane Membrane (Mc)	0	0	0	0
Inplane Bending (Mc)	0	0	0	0
Inplane Membrane (ML)	0	0	0	0
Inplane Bending (ML)	0	0	0	0
Inplane Pressure Stress	21	22	21	22

Inplane Stress Summary	30	16	30	16
------------------------	----	----	----	----

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Shear stress normal to circumferential plane)	Cu Left Outside	Cl Left Inside	Du Right Outside	Dl Right Inside
--	-----------------------	----------------------	------------------------	-----------------------

Outplane Shear (Vc)	0	0	0	0
Outplane Shear (Vl)	-1	-1	1	1
Torsional Shear (Mt)	0	0	0	0

Shear Stress Summary	-1	-1	1	1
----------------------	----	----	---	---

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Stress Intensities)	Cu Left Outside	Cl Left Inside	Du Right Outside	Dl Right Inside
---	-----------------------	----------------------	------------------------	-----------------------

Two * Max Shear Stress	30	16	30	16
------------------------	----	----	----	----

Nozzle Stresses (N./mm²):

LONGITUDINAL PLANE (Stresses in the hoop direction)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
---	----------------------	---------------------	-------------------------	------------------------

Hoop Membrane (P)	2	2	2	2
Hoop Bending (P)	0	0	0	0
Hoop Membrane (Mc)	0	0	0	0
Hoop Bending (Mc)	0	0	0	0
Hoop Membrane (ML)	0	0	0	0
Hoop Bending (ML)	0	0	0	0
Hoop Pressure Stress	13	14	13	14

Hoop Stress Summary	15	17	15	17
---------------------	----	----	----	----

Nozzle Stresses (N./mm²):

LONGITUDINAL PLANE (Stresses Normal to pipe cross-section)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
--	----------------------	---------------------	-------------------------	------------------------

Axial Membrane (P)	1	1	1	1
Axial Bending (P)	19	-19	19	-19
Axial Membrane (Mc)	0	0	0	0
Axial Bending (Mc)	0	0	0	0
Axial Membrane (ML)	0	0	0	0
Axial Bending (ML)	0	0	0	0
Axial Pressure Stress	6	6	6	6



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 111 of 173

Nozzle Calcs.: N1- Channel inl Nozl: 9 9:52am Aug 12,2026

Axial Stress Summary	26	-11	27	-11
----------------------	----	-----	----	-----

Nozzle Stresses (N./mm²):

LONGITUDINAL PLANE	Au	Al	Bu	B1
(Shear stress)	Outside	Inside	Outside	Inside

Shear due to (Vc)	2	2	-2	-2
Shear due to (Vl)	0	0	0	0
Shear due to Torsion	0	0	0	0

Shear Stress Summary	2	2	-2	-2
----------------------	---	---	----	----

Nozzle Stresses (N./mm²):

LONGITUDINAL PLANE	Au	Al	Bu	B1
(Stress Intensities	Outside	Inside	Outside	Inside

Two * Max Shear Stress	27	29	27	29
------------------------	----	----	----	----

Nozzle Stresses (N./mm²):

CIRCUMFERENTIAL PLANE	Cu	Cl	Du	D1
(Stresses in the	Left	Left	Right	Right
hoop direction)	Outside	Inside	Outside	Inside

Hoop Membrane (P)	2	2	2	2
Hoop Bending (P)	0	0	0	0
Hoop Membrane (Mc)	0	0	0	0
Hoop Bending (Mc)	0	0	0	0
Hoop Membrane (ML)	0	0	0	0
Hoop Bending (ML)	0	0	0	0
Hoop Pressure Stress	13	14	13	14

Hoop Stress Summary	15	17	15	17
---------------------	----	----	----	----

Nozzle Stresses (N./mm²):

CIRCUMFERENTIAL PLANE	Cu	Cl	Du	D1
(Stresses Normal to	Left	Left	Right	Right
pipe cross-section)	Outside	Inside	Outside	Inside

Axial Membrane (P)	1	1	1	1
Axial Bending (P)	19	-19	19	-19
Axial Membrane (Mc)	0	0	0	0
Axial Bending (Mc)	0	0	0	0
Axial Membrane (ML)	0	0	0	0
Axial Bending (ML)	0	0	0	0
Axial Pressure Stress	6	6	6	6

Axial Stress Summary	26	-11	27	-11
----------------------	----	-----	----	-----

Nozzle Stresses (N./mm²):

CIRCUMFERENTIAL PLANE	Cu	Cl	Du	D1
(Shear stress)	Outside	Inside	Outside	Inside

Shear due to (Vc)	0	0	0	0
Shear due to (Vl)	-2	-2	2	2
Shear due to Torsion	0	0	0	0

Shear Stress Summary	-2	-2	2	2
----------------------	----	----	---	---

Nozzle Stresses (N./mm²):

CIRCUMFERENTIAL PLANE	Cu	Cl	Du	D1
(Stress Intensities	Outside	Inside	Outside	Inside

Two * Max Shear Stress	27	29	27	29
------------------------	----	----	----	----



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 112 of 173

Nozzle Calcs.: N1- Channel inl Nozl: 9 9:52am Aug 12,2026

Stress Computations at the Edge of the Reinforcing Pad:

Stress Attenuation Diameter (for Insert Plates) per WRC 297:

$$= \text{NozzleOD} + 2 \cdot 1.65 \cdot \sqrt{R_{\text{mean}}(t - c_a)}$$

$$= 168.275 + 2 \cdot 1.65 \cdot \sqrt{306.352(9.53 - 3.175)}$$

$$= 313.882 \text{ mm}$$

WRC 297 Curve Access Parameters:

Vessel Mean Diameter	(D) =	612.705 mm
Nozzle Outside Diameter	(d) =	308.275 mm
Vessel Thickness used	(T) =	6.355 mm
Nozzle Thickness used	(t) =	77.798 mm
T / t	=	0.082
d / t	=	10.000

$$\lambda = [(d/D) \cdot \sqrt{(D/T)}] = 4.940$$

Note: Re-pad thickness is added to nozzle thickness to simulate the Re-pad.

Nr/P	=	0.045
Mr/P	=	0.071
M0/P	=	0.020
N0/P	=	0.027
MrD/Mc	=	0.241
NrDL/Mc	=	0.099
M0d/Mc	=	0.072
N0DL/Mc	=	0.053
MrD/M1	=	0.050
NrDL/M1	=	0.048
M0D/M1	=	0.015
N0DL/M1	=	0.027

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Stresses Normal to longitudinal plane)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Outplane Membrane (P)	2	2	2	2
Outplane Bending (P)	11	-11	11	-11
Outplane Membrane (Mc)	0	0	0	0
Outplane Bending (Mc)	0	0	0	0
Outplane Membrane (ML)	0	0	0	0
Outplane Bending (ML)	0	0	0	0
Normal Pressure Stress	56	57	56	57
Outplane Stress Summary	70	48	70	48

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Stresses parallel to longitudinal plane)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Inplane Membrane (P)	4	4	4	4
Inplane Bending (P)	41	-41	41	-41
Inplane Membrane (Mc)	0	0	0	0
Inplane Bending (Mc)	0	0	0	0
Inplane Membrane (ML)	0	0	0	0
Inplane Bending (ML)	0	0	0	0
Inplane Pressure Stress	28	28	28	28
Inplane Stress Summary	74	-9	74	-9

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE	Au	Al	Bu	Bl
--------------------	----	----	----	----



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 113 of 173

Nozzle Calcs.: N1- Channel inl Nozl: 9 9:52am Aug 12,2026

(Shear stress normal to longitudinal plane)			Top Outside	Top Inside	Bottom Outside	Bottom Inside
Outplane Shear (Vc)			1	1	-1	-1
Outplane Shear (Vl)			0	0	0	0
Outplane Shear (Mt)			0	0	0	0
Shear Stress Summary			1	1	-1	-1

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Stress Intensities)		Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Two * Max Shear Stress		75	58	75	58

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Stresses Normal to circumferential plane)		Cu Left Outside	Cl Left Inside	Du Right Outside	Dl Right Inside
Outplane Membrane (P)		2	2	2	2
Outplane Bending (P)		11	-11	11	-11
Outplane Membrane (Mc)		0	0	0	0
Outplane Bending (Mc)		0	0	0	0
Outplane Membrane (ML)		0	0	0	0
Outplane Bending (ML)		0	0	0	0
Normal Pressure Stress		28	28	28	28
Outplane Stress Summary		42	19	42	19

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Stresses parallel to circumferential plane)		Cu Left Outside	Cl Left Inside	Du Right Outside	Dl Right Inside
Inplane Membrane (P)		4	4	4	4
Inplane Bending (P)		41	-41	41	-41
Inplane Membrane (Mc)		0	0	0	0
Inplane Bending (Mc)		0	0	0	0
Inplane Membrane (ML)		0	0	0	0
Inplane Bending (ML)		0	0	0	0
Inplane Pressure Stress		56	57	56	57
Inplane Stress Summary		102	20	103	20

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Shear stress normal to circumferential plane)		Cu Left Outside	Cl Left Inside	Du Right Outside	Dl Right Inside
Outplane Shear (Vc)		0	0	0	0
Outplane Shear (Vl)		-1	-1	1	1
Torsional Shear (Mt)		0	0	0	0
Shear Stress Summary		-1	-1	1	1

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Stress Intensities)		Cu Left Outside	Cl Left Inside	Du Right Outside	Dl Right Inside
Two * Max Shear Stress		102	22	103	21



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 114 of 173

Nozzle Calcs.: N1- Channel inl Nozl: 9 9:52am Aug 12,2026

WRC 297 Stress Summations per ASME Sec. VIII Div. 2:

Vessel Stress Summation at Vessel-Nozzle Junction (N./mm²):

Type of Stress Int. Location	Stress Values at							
	Au	Al	Bu	Bl	Cu	Cl	Du	Dl
Circ. Pm (SUS)	21	22	21	22	21	22	21	22
Circ. Pl (SUS)	2	2	2	2	1	1	1	1
Circ. Q (SUS)	4	-4	4	-4	7	-7	7	-7
Long. Pm (SUS)	10	10	10	10	10	10	10	10
Long. Pl (SUS)	1	1	1	1	2	2	2	2
Long. Q (SUS)	7	-7	7	-7	4	-4	4	-4
Shear Pm (SUS)	0	0	0	0	0	0	0	0
Shear Pl (SUS)	1	1	-1	-1	-1	-1	1	1
Shear Q (SUS)	0	0	0	0	0	0	0	0
Pm (SUS)	21.0	22.0	21.0	22.0	21.0	22.0	21.0	22.0
Pm+Pl (SUS)	23.1	24.1	23.1	24.1	22.1	23.1	22.1	23.1
Pm+Pl+Q (Total)	27.1	20.1	27.1	20.1	29.1	16.1	29.1	16.1

Vessel Stress Summation Comparison (N./mm²):

Type of Stress Int.	Max. S.I.	S.I. Allowable	Result
Pm (SUS)	22.00	118.00	Passed
Pm+Pl (SUS)	24.08	177.00	Passed
Pm+Pl+Q (TOTAL)	29.08	353.99	Passed

Because only sustained loads were specified, the Pm+Pl+Q allowable was 3 * Smh.

WRC 297 Stress Summations per ASME Sec. VIII Div. 2:

Vessel Stress Summation at Reinforcing Pad Edge (N./mm²):

Type of Stress Int. Location	Stress Values at							
	Au	Al	Bu	Bl	Cu	Cl	Du	Dl
Circ. Pm (SUS)	56	57	56	57	56	57	56	57
Circ. Pl (SUS)	2	2	2	2	4	4	4	4
Circ. Q (SUS)	11	-11	11	-11	41	-41	41	-41
Long. Pm (SUS)	28	28	28	28	28	28	28	28
Long. Pl (SUS)	4	4	4	4	2	2	2	2
Long. Q (SUS)	41	-41	41	-41	11	-11	11	-11
Shear Pm (SUS)	0	0	0	0	0	0	0	0
Shear Pl (SUS)	1	1	-1	-1	-1	-1	1	1
Shear Q (SUS)	0	0	0	0	0	0	0	0
Pm (SUS)	56.0	57.0	56.0	57.0	56.0	57.0	56.0	57.0
Pm+Pl (SUS)	58.0	59.0	58.0	59.0	60.0	61.0	60.0	61.0
Pm+Pl+Q (Total)	73.2	57.0	73.2	57.0	101.0	20.6	101.0	20.6

Vessel Stress Summation Comparison (N./mm²):



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 115 of 173

Nozzle Calcs.: N1- Channel in1 Nozl: 9 9:52am Aug 12,2026

Type of Stress Int.	Max. S.I.	S.I. Allowable	Result
Pm (SUS)	57.00	118.00	Passed
Pm+P1 (SUS)	61.03	177.00	Passed
Pm+P1+Q (TOTAL)	101.02	353.99	Passed

Because only sustained loads were specified, the Pm+P1+Q allowable was 3 * Smh.

WRC 297 Stress Summations per ASME Sec. VIII Div. 2:

Nozzle Stress Summation at Vessel-Nozzle Junction (N./mm²):

Type of Stress Int. Location	Stress Values at							
	Au	Al	Bu	Bl	Cu	Cl	Du	Dl
Circ. Pm (SUS)	13	14	13	14	13	14	13	14
Circ. P1 (SUS)	2	2	2	2	2	2	2	2
Circ. Q (SUS)	0	0	0	0	0	0	0	0
Long. Pm (SUS)	6	6	6	6	6	6	6	6
Long. P1 (SUS)	1	1	1	1	1	1	1	1
Long. Q (SUS)	19	-19	19	-19	19	-19	19	-19
Shear Pm (SUS)	0	0	0	0	0	0	0	0
Shear P1 (SUS)	2	2	-2	-2	-2	-2	2	2
Shear Q (SUS)	0	0	0	0	0	0	0	0
Pm (SUS)	13.0	14.0	13.0	14.0	13.0	14.0	13.0	14.0
Pm+P1 (SUS)	15.5	16.4	15.5	16.4	15.5	16.4	15.5	16.4
Pm+P1+Q (Total)	26.4	28.3	26.4	28.3	26.4	28.3	26.4	28.3

Nozzle Stress Summation Comparison (N./mm²):

Type of Stress Int.	Max. S.I.	S.I. Allowable	Result
Pm (SUS)	14.00	118.00	Passed
Pm+P1 (SUS)	16.42	177.00	Passed
Pm+P1+Q (TOTAL)	28.28	353.99	Passed

Because only sustained loads were specified, the Pm+P1+Q allowable was 3 * Smh.

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 116 of 173

Nozzle Calcs.: N1- Shell outle

Nozl: 10 9:52am Aug 12,2026

Input, Nozzle Desc: N1- Shell outlet

From: 40

Pressure for Reinforcement Calculations	P	1549.500	KPa.
Temperature for Internal Pressure	Temp	166	°C
Parent Material		SA-106 B	
Parent Allowable Stress at Temperature	Sv	140.75	N./mm ²
Parent Allowable Stress At Ambient	Sva	161.00	N./mm ²
Inside Diameter of Cylindrical Shell	D	600.00	mm
Shell Finished (Minimum) Thickness	t	9.5300	mm
Shell Internal Corrosion Allowance	c	3.1750	mm
Shell External Corrosion Allowance	co	0.0000	mm
Distance from Bottom/Left Tangent		1307.00	mm
User Entered Minimum Design Metal Temperature		11.40	°C

Type of Element Connected to the Parent : Nozzle

Material		SA-106 B	
Material UNS Number		K03006	
Material Specification/Type		Smls. pipe	
Allowable Stress at Temperature	Sn	118.00	N./mm ²
Allowable Stress At Ambient	Sna	118.00	N./mm ²
Diameter Basis (for tr calc only)		Outside	
Layout Angle		270.00	deg
Diameter		10.0000	in.
Size and Thickness Basis		Nominal	
Nominal Thickness		80	
Flange Material		SA-105	
Flange Type		Weld Neck Flange	
Corrosion Allowance	can	3.1750	mm
Joint Efficiency of Shell Seam at Nozzle	E1	1.00	
Joint Efficiency of Nozzle Neck	En	1.00	
Outside Projection	ho	250.0000	mm
Weld leg size between Nozzle and Pad/Shell	Wo	10.0000	mm
Groove weld depth between Nozzle and Vessel	Wgnv	9.5300	mm
Inside Projection	h	0.0000	mm
Weld leg size, Inside Element to Shell	Wi	0.0000	mm
Pad Material		SA-516 70	
Pad Allowable Stress at Temperature	Sp	138.00	N./mm ²
Pad Allowable Stress At Ambient	Spa	138.00	N./mm ²
Diameter of Pad along vessel surface	Dp	413.0500	mm
Thickness of Pad	te	10.0000	mm
Weld leg size between Pad and Shell	Wp	8.0000	mm
Groove weld depth between Pad and Nozzle	Wgpn	10.0000	mm
Reinforcing Pad Width		70.0000	mm
Flange Class		300	
Flange Grade		GR 1.1	

The Pressure Design option was Design Pressure + static head.




PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 117 of 173

Nozzle Calcs.: N1- Shell outlet

Nozl: 10 9:52am Aug 12,2026



Reinforcement CALCULATION, Description: N1- Shell outlet

ASME Code, Section VIII, Div. 1, UG-37 to UG-45

Actual Outside Diameter Used in Calculation	10.750 in.
Actual Thickness Used in Calculation	0.594 in.

Nozzle input data check completed without errors.

Reqd thk per UG-37(a) of Cylindrical Shell, tr [Int. Press]
 $= P \cdot R / (S_v \cdot E - 0.6 \cdot P)$ per UG-27 (c)(1)
 $= 1549.5 \cdot 303.175 / (141 \cdot 1.0 - 0.6 \cdot 1549.5)$
 $= 3.3599 \text{ mm}$

Reqd thk per UG-37(a) of Nozzle Wall, trn [Int. Press]
 $= P \cdot R_o / (S_n \cdot E + 0.4 \cdot P)$ per Appendix 1-1 (a)(1)
 $= 1549.5 \cdot 136.525 / (118 \cdot 1.0 + 0.4 \cdot 1549.5)$
 $= 1.7835 \text{ mm}$

UG-40, Limits of Reinforcement: [Internal Pressure]

Parallel to Vessel Wall (Diameter Limit)	D1	498.4496 mm
Parallel to Vessel Wall, opening length	d	249.2248 mm
Normal to Vessel Wall (Thickness Limit), pad side Tlwp		15.8875 mm

Weld Strength Reduction Factor [fr1]:
 $= \min(1, S_n / S_v)$
 $= \min(1, 118.0 / 140.8)$
 $= 0.838$

Weld Strength Reduction Factor [fr2]:
 $= \min(1, S_n / S_v)$
 $= \min(1, 118.0 / 140.8)$
 $= 0.838$

Weld Strength Reduction Factor [fr4]:
 $= \min(1, S_p / S_v)$
 $= \min(1, 138.0 / 140.8)$
 $= 0.980$

Weld Strength Reduction Factor [fr3]:
 $= \min(fr2, fr4)$
 $= \min(0.838, 0.98)$
 $= 0.838$



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 118 of 173

Nozzle Calcs.: N1- Shell outle

Nozl: 10 9:52am Aug 12,2026




Figure UG 37.1 Nozzle Areas

Results of Nozzle Reinforcement Area Calculations: (cm²)

AREA AVAILABLE, A1 to A5		Design	External	Mapnc
Area Required	Ar	8.503	NA	NA
Area in Shell	A1	7.349	NA	NA
Area in Nozzle Wall	A2	2.698	NA	NA
Area in Inward Nozzle	A3	0.000	NA	NA
Area in Welds	A41+A42+A43	1.324	NA	NA
Area in Element	A5	13.726	NA	NA
TOTAL AREA AVAILABLE	Atot	25.097	NA	NA

The Internal Pressure Case Governs the Analysis.

Nozzle Angle Used in Area Calculations

90.00 degs.

The area available without a pad is Sufficient.

The area available with the given pad is Sufficient.

Area Required [A]:

$$\begin{aligned}
 &= (d \cdot tr \cdot F + 2 \cdot tn \cdot tr \cdot F \cdot (1 - fr1)) \text{ UG-37(c)} \\
 &= (249.2248 \cdot 3.3599 \cdot 1.0 + 2 \cdot 11.9126 \cdot 3.3599 \cdot 1.0 \cdot (1 - 0.84)) \\
 &= 8.503 \text{ cm}^2
 \end{aligned}$$

Reinforcement Areas per Figure UG-37.1

Area Available in Shell [A1]:

$$\begin{aligned}
 &= d(E1 \cdot t - F \cdot tr) - 2 \cdot tn(E1 \cdot t - F \cdot tr) \cdot (1 - fr1) \\
 &= 249.225(1.0 \cdot 6.355 - 1.0 \cdot 3.36) - 2 \cdot 11.913 \\
 &\quad (1.0 \cdot 6.355 - 1.0 \cdot 3.3599) \cdot (1 - 0.838) \\
 &= 7.349 \text{ cm}^2
 \end{aligned}$$

Area Available in Nozzle Wall Projecting Outward [A2]:

$$\begin{aligned}
 &= (2 \cdot Tlwp) \cdot (tn - trn) \cdot fr2 \\
 &= (2 \cdot 15.89) \cdot (11.91 - 1.78) \cdot 0.8383
 \end{aligned}$$



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 119 of 173

Nozzle Calcs.: N1- Shell outle Nozl: 10 9:52am Aug 12,2026

= 2.698 cm²

Area Available in Welds [A41 + A42 + A43]:

= (Wo² - Ar Lost)•Fr3+((Wi-can/0.707)² - Ar Lost)•fr2 + Wp²•fr4

= (0.8309) • 0.84 + (0.0) • 0.84 + 8.0² • 0.98

= 1.324 cm²

Area Available in Element [A5]:

= (min(Dp,DL)-(Nozzle OD))•(min(tp,Tlwp,te)) • fr4

= (413.05 - 273.05) • 10.0 • 0.9804

= 13.726 cm²

UG-45 Minimum Nozzle Neck Thickness Requirement: [Int. Press.]

Wall Thickness for Internal/External pressures ta = 4.9585 mm

Wall Thickness per UG16(b), tr16b = 5.6750 mm

Wall Thickness, shell/head, internal pressure trb1 = 6.5349 mm

Wall Thickness tb1 = max(trb1, tr16b) = 6.5349 mm

Wall Thickness tb2 = max(trb2, tr16b) = 5.6750 mm

Wall Thickness per table UG-45 tb3 = 11.2776 mm

Determine Nozzle Thickness candidate [tb]:

= min[tb3, max(tb1,tb2)]

= min[11.278, max(6.5349, 5.675)]

= 6.5349 mm

Minimum Wall Thickness of Nozzle Necks [tUG-45]:

= max(ta, tb)

= max(4.9585, 6.5349)

= 6.5349 mm

Available Nozzle Neck Thickness = 0.875 * 15.088 = 13.202 mm -> OK

Stresses on Nozzle due to External and Pressure Loads per the ASME B31.3 Piping Code, (see 319.4.4 and 302.3.5):

Sustained	:	7.1,	Allowable	:	118.0 N./mm ²	Passed
Expansion	:	0.0,	Allowable	:	287.9 N./mm ²	Passed
Occasional	:	7.7,	Allowable	:	156.9 N./mm ²	Passed
Shear	:	3.0,	Allowable	:	82.6 N./mm ²	Passed

The number of cycles on this nozzle was assumed to be 7000 or less for the determination of the expansion stress allowable.

Nozzle Junction Minimum Design Metal Temperature (MDMT) Calculations:

Nozzle Neck to Flange Weld, min(Curve:B, Curve:A)

Govrn. thk, tg = 13.202, tr = 1.784, c = 3.175 mm, E* = 1.0

Thickness Ratio = tr * E*/(tg - c) = 0.178, Temp. Reduction = 78 °C

Min Metal Temp. w/o impact per UCS-66, Curve A 0 °C

Min Metal Temp. at Required thickness (UCS 66.1) -104 °C

Nozzle Neck to Pad Weld for the Nozzle, Curve: B

Govrn. thk, tg = 10.0, c = 3.175 mm, E* = 1.0

Thickness Ratio = tr * E*/(tg - c) = 0.462, Temp. Reduction = 38 °C

Attachment governing, Attachment stress = Shell stress per Code

Min Metal Temp. w/o impact per UCS-66, Curve B -29 °C

Min Metal Temp. at Required thickness (UCS 66.1) -48 °C

Nozzle Neck to Pad Weld for Reinforcement pad, Curve: B

Govrn. thk, tg = 10.0, c = 3.175 mm, E* = 1.0



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 120 of 173

Nozzle Calcs.: N1- Shell outle Nozl: 10 9:52am Aug 12,2026

Thickness Ratio = $tr \cdot E^* / (tg - c) = 0.462$, Temp. Reduction = 38 °C
Attachment governing, Attachment stress = Shell stress per Code

Min Metal Temp. w/o impact per UCS-66, Curve B -29 °C
Min Metal Temp. at Required thickness (UCS 66.1) -48 °C

Shell to Pad Weld Junction at Pad OD, Curve: B

Govrn. thk, $tg = 9.53$, $tr = 2.935$, $c = 3.175$ mm, $E^* = 1.0$
Thickness Ratio = $tr \cdot E^* / (tg - c) = 0.462$, Temp. Reduction = 38 °C

Min Metal Temp. w/o impact per UCS-66, Curve B -29 °C
Min Metal Temp. at Required thickness (UCS 66.1) -48 °C

Nozzle-Shell/Head Weld (UCS-66(a)(b)), Curve: B

Govrn. thk, $tg = 9.53$, $tr = 2.935$, $c = 3.175$ mm, $E^* = 1.0$
Thickness Ratio = $tr \cdot E^* / (tg - c) = 0.462$, Temp. Reduction = 38 °C

Min Metal Temp. w/o impact per UCS-66, Curve B -29 °C
Min Metal Temp. at Required thickness (UCS 66.1) -48 °C

Gov. MDMT of the Nozzle : -48 °C
Gov. MDMT of the Reinforcement Pad : -48 °C
Gov. MDMT of the nozzle to shell joint welded assembly : -48 °C

Flange MDMT including Temperature reduction per UCS-66.1:

Unadjusted MDMT of ASME B16.5/47 flanges per UCS-66(c) -18 °C
Flange MDMT with Temp reduction per UCS-66(b)(1)(-b) -104 °C

Where the Stress Reduction Ratio per UCS-66(b)(1)(-b) is :
Design Pressure/Ambient Rating = $1549.50 / 5100.00 = 0.304$

Weld Size Calculations, Description: N1- Shell outle

Intermediate Calc. for nozzle/shell Welds Tmin 10.0000 mm
Intermediate Calc. for pad/shell Welds TminPad 6.3550 mm

Results Per UW-16.1:

	Required Thickness	Actual Thickness
Nozzle Weld	$6.0000 = \text{Min per Code}$	$7.0700 = 0.7 \cdot W_o \text{ mm}$
Pad Weld	$3.1775 = 0.5 \cdot \text{TminPad}$	$5.6560 = 0.7 \cdot W_p \text{ mm}$

Weld Strength and Weld Loads per UG-41.1, Sketch (a) or (b)

Weld Load [W]:
 $= \max(0, (A - A1 + 2 \cdot tn \cdot fr1 \cdot (E1 \cdot t - tr)) \cdot Sv)$
 $= \max(0, (8.5032 - 7.3491 + 2 \cdot 11.9126 \cdot 0.8383 \cdot (1.0 \cdot 6.355 - 3.3599)) \cdot 141)$
 $= 2514.94 \text{ Kg}$

Note: F is always set to 1.0 throughout the calculation.

Weld Load [W1]:
 $= (A2 + A5 + A4 - (Wi - Can / .707)^2 \cdot fr2) \cdot Sv$
 $= (2.6982 + 13.7258 + 1.324 - 0.0 \cdot 0.84) \cdot 141$
 $= 25473.08 \text{ Kg}$

Weld Load [W2]:
 $= (A2 + A3 + A4 + (2 \cdot tn \cdot t \cdot fr1)) \cdot Sv$
 $= (2.6982 + 0.0 + 0.8383 + (1.2693)) \cdot 141$
 $= 6897.59 \text{ Kg}$

Weld Load [W3]:



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 121 of 173

Nozzle Calcs.: N1- Shell outle Nozl: 10 9:52am Aug 12,2026

$$= (A2+A3+A4+A5+(2 \cdot t_n \cdot t \cdot f r_1)) \cdot S$$

$$= (2.6982 + 0.0 + 1.324 + 13.7258 + (1.2693)) \cdot 141$$

$$= 27294.87 \text{ Kg}$$

Strength of Connection Elements for Failure Path Analysis

Shear, Outward Nozzle Weld [Sonw]:

$$= (\pi/2) \cdot D_{lo} \cdot W_o \cdot 0.49 \cdot S_{nw}$$

$$= (3.1416/2.0) \cdot 273.05 \cdot 10.0 \cdot 0.49 \cdot 118$$

$$= 25287. \text{ Kg}$$

Shear, Pad Element Weld [Spew]:

$$= (\pi/2) \cdot D_P \cdot W_P \cdot 0.49 \cdot S_{EW}$$

$$= (3.1416/2.0) \cdot 413.05 \cdot 8.0 \cdot 0.49 \cdot 138$$

$$= 35789. \text{ Kg}$$

Shear, Nozzle Wall [Snw]:

$$= (\pi \cdot (D_{lr} + D_{lo})/4) \cdot (Thk - Can) \cdot 0.7 \cdot S_n$$

$$= (3.1416 \cdot 130.5687) \cdot (15.0876 - 3.175) \cdot 0.7 \cdot 118$$

$$= 41157. \text{ Kg}$$

Tension, Pad Groove Weld [Tpgw]:

$$= (\pi/2) \cdot D_{lo} \cdot W_{gpn} \cdot 0.74 \cdot S_{eg}$$

$$= (3.1416/2) \cdot 273.05 \cdot 10.0 \cdot 0.74 \cdot 138$$

$$= 44662. \text{ Kg}$$

Tension, Shell Groove Weld [Tngw]:

$$= (\pi/2) \cdot D_{lo} \cdot (T - cas) \cdot 0.74 \cdot S_{ng}$$

$$= (3.1416/2.0) \cdot 273.05 \cdot (9.53 - 3.175) \cdot 0.74 \cdot 141$$

$$= 28949. \text{ Kg}$$

See UG-41 and UW-15 for clarification of allowable stresses.

Strength of Failure Paths:

Failure Path [Path 1-1]:

$$= (S_{PEW} + S_{NW}) = (35789 + 41157) = 76946 \text{ Kg}$$

Failure Path [Path 2-2]:

$$= (S_{onw} + T_{pgw} + T_{ngw} + S_{inw})$$

$$= (25287 + 44662 + 28949 + 0) = 98899 \text{ Kg}$$

Failure Path [Path 3-3]:

$$= (S_{pew} + T_{ngw} + S_{inw})$$

$$= (35789 + 28949 + 0) = 64739 \text{ Kg}$$

Summary of Failure Path Calculations:

Path 1-1 = 76945	Kgf, must exceed W = 2514 Kg	or W1 = 25473 Kg
Path 2-2 = 98898	Kgf, must exceed W = 2514 Kg	or W2 = 6897 Kg
Path 3-3 = 64738	Kgf, must exceed W = 2514 Kg	or W3 = 27294 Kg

Maximum Allowable Pressure for this Nozzle at this Location:

Converged Maximum Allowable Pressure in the Operating case: 2913 KPa.

Note: The MAWP of this junction was limited by the parent Shell/Head.

The Drop for this Nozzle is : 32.8654 mm

The Cut Length for this Nozzle is, Drop + Ho + H + T : 292.3954 mm

Input Echo, WRC297 Item 1, Description: N1- Shell outl:

Diameter Basis for Cylindrical Shell	ID
Shell Internal Corrosion Allowance	3.1750 mm
Shell External Corrosion Allowance	0.0000 mm
Shell Diameter	600.000 mm



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 122 of 173

Nozzle Calcs.: N1- Shell outle Nozl: 10 9:52am Aug 12,2026

Shell Thickness		9.5300	mm
Shell Stress Concentration Factor		1.000	
Vessel Material		SA-106 B	
Vessel Cold S.I. Allowable	Smc	161.00	N./mm ²
Vessel Hot S.I. Allowable	Smh	140.75	N./mm ²
Diameter Basis for Nozzle		OD	
Nozzle Corrosion Allowance		3.1750	mm
Nozzle Diameter		273.050	mm
Nozzle Thickness		15.0876	mm
Nozzle Stress Concentration Factor		1.000	
Nozzle Material		SA-106 B	
Nozzle Cold S.I. Allowable	SNmc	118.00	N./mm ²
Nozzle Hot S.I. Allowable	SNmh	118.00	N./mm ²

See ASME VIII Div. 2, 4.1.6.3, for determination of the SPS allowable.

Diameter of Reinforcing Pad	413.050	mm
Thickness of Reinforcing Pad	10.0000	mm

Note:

External Forces and Moments in WRC 107/537 Convention:
These loads are assumed to be SUSained loads.

Design Internal Pressure	Dp	1549.50	KPa.
Radial Load	P	-683.25	Kgf
Circumferential Shear	Vc	1019.78	Kgf
Longitudinal Shear	Vl	1019.78	Kgf
Circumferential Moment	Mc	0.76	Kg-m.
Longitudinal Moment	Ml	1.02	Kg-m.
Torsional Moment	Mt	1.27	Kg-m.

Include Axial Pressure Thrust	No
Include Pressure Stress Indices per Div. 2	No
Local Loads applied at end of Nozzle/Attachment	No

Stress Computations at the Edge of the Nozzle:

Stress Attenuation Diameter (for Insert Plates) per WRC 297:

$$= \text{NozzleOD} + 2 \cdot 1.65 \cdot \sqrt{R_{\text{mean}}(t - ca)}$$

$$= 273.05 + 2 \cdot 1.65 \cdot \sqrt{311.353(9.53 - 3.175)}$$

$$= 419.840 \text{ mm}$$

WRC 297 Curve Access Parameters:

Vessel Mean Diameter	(D) =	622.705	mm
Nozzle Outside Diameter	(d) =	273.050	mm
Vessel Thickness used	(T) =	16.355	mm
Nozzle Thickness used	(t) =	11.913	mm
T / t	=	1.373	
d / t	=	22.921	

$$\lambda = [(d/D) \cdot \sqrt{(D/T)}] = 2.706$$

Nr/P	=	0.058
Mr/P	=	0.092
M0/P	=	0.037
N0/P	=	0.126
MrD/Mc	=	0.222
NrDL/Mc	=	0.104
M0d/Mc	=	0.102
N0DL/Mc	=	0.130
MrD/Ml	=	0.108



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 123 of 173

Nozzle Calcs.: N1- Shell outle

Nozl: 10 9:52am Aug 12,2026

NrDL/M1 = 0.054
MØD/M1 = 0.050
NØDL/M1 = 0.190

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Stresses Normal to longitudinal plane)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Outplane Membrane (P)	3	3	3	3
Outplane Bending (P)	5	-5	5	-5
Outplane Membrane (Mc)	0	0	0	0
Outplane Bending (Mc)	0	0	0	0
Outplane Membrane (ML)	0	0	0	0
Outplane Bending (ML)	0	0	0	0
Normal Pressure Stress	27	29	27	29
Outplane Stress Summary	36	27	36	27

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Stresses parallel to longitudinal plane)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Inplane Membrane (P)	1	1	1	1
Inplane Bending (P)	13	-13	13	-13
Inplane Membrane (Mc)	0	0	0	0
Inplane Bending (Mc)	0	0	0	0
Inplane Membrane (ML)	0	0	0	0
Inplane Bending (ML)	0	0	0	0
Inplane Pressure Stress	13	13	13	13
Inplane Stress Summary	29	1	29	1

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Shear stress normal to longitudinal plane)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Outplane Shear (Vc)	1	1	-1	-1
Outplane Shear (Vl)	0	0	0	0
Outplane Shear (Mt)	0	0	0	0
Shear Stress Summary	1	1	-1	-1

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Stress Intensities)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Two * Max Shear Stress	36	27	37	27

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Stresses Normal to circumferential plane)	Cu Left Outside	Cl Left Inside	Du Right Outside	Dl Right Inside
Outplane Membrane (P)	3	3	3	3
Outplane Bending (P)	5	-5	5	-5
Outplane Membrane (Mc)	0	0	0	0
Outplane Bending (Mc)	0	0	0	0
Outplane Membrane (ML)	0	0	0	0
Outplane Bending (ML)	0	0	0	0
Normal Pressure Stress	13	13	13	13



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 124 of 173

Nozzle Calcs.: N1- Shell outle Nozl: 10 9:52am Aug 12,2026

Outplane Stress Summary	22	11	22	11
-------------------------	----	----	----	----

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE	Cu	Cl	Du	Dl
(Stresses parallel to	Left	Left	Right	Right
circumferential plane)	Outside	Inside	Outside	Inside

Inplane Membrane (P)	1	1	1	1
Inplane Bending (P)	13	-13	13	-13
Inplane Membrane (Mc)	0	0	0	0
Inplane Bending (Mc)	0	0	0	0
Inplane Membrane (ML)	0	0	0	0
Inplane Bending (ML)	0	0	0	0
Inplane Pressure Stress	27	29	27	29

Inplane Stress Summary	43	17	43	16
------------------------	----	----	----	----

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE	Cu	Cl	Du	Dl
(Shear stress normal to	Left	Left	Right	Right
circumferential plane)	Outside	Inside	Outside	Inside

Outplane Shear (Vc)	0	0	0	0
Outplane Shear (Vl)	-1	-1	1	1
Torsional Shear (Mt)	0	0	0	0

Shear Stress Summary	-1	-1	1	1
----------------------	----	----	---	---

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE	Cu	Cl	Du	Dl
(Stress Intensities	Left	Left	Right	Right
	Outside	Inside	Outside	Inside

Two * Max Shear Stress	43	17	43	17
------------------------	----	----	----	----

Nozzle Stresses (N./mm²):

LONGITUDINAL PLANE	Au	Al	Bu	Bl
(Stresses in the	Top	Top	Bottom	Bottom
hoop direction)	Outside	Inside	Outside	Inside

Hoop Membrane (P)	3	3	3	3
Hoop Bending (P)	0	0	0	0
Hoop Membrane (Mc)	0	0	0	0
Hoop Bending (Mc)	0	0	0	0
Hoop Membrane (ML)	0	0	0	0
Hoop Bending (ML)	0	0	0	0
Hoop Pressure Stress	18	20	18	20

Hoop Stress Summary	21	23	21	23
---------------------	----	----	----	----

Nozzle Stresses (N./mm²):

LONGITUDINAL PLANE	Au	Al	Bu	Bl
(Stresses Normal to	Top	Top	Bottom	Bottom
pipe cross-section)	Outside	Inside	Outside	Inside

Axial Membrane (P)	0	0	0	0
Axial Bending (P)	17	-17	17	-17
Axial Membrane (Mc)	0	0	0	0
Axial Bending (Mc)	0	0	0	0
Axial Membrane (ML)	0	0	0	0
Axial Bending (ML)	0	0	0	0
Axial Pressure Stress	9	9	9	9

Axial Stress Summary	27	-7	28	-8
----------------------	----	----	----	----



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 125 of 173

Nozzle Calcs.: N1- Shell outle

Nozl: 10 9:52am Aug 12,2026

Nozzle Stresses (N./mm²):

LONGITUDINAL PLANE (Shear stress)	Au	Al	Bu	B1
	Outside	Inside	Outside	Inside
Shear due to (Vc)	1	1	-1	-1
Shear due to (Vl)	0	0	0	0
Shear due to Torsion	0	0	0	0
Shear Stress Summary	1	1	-1	-1

Nozzle Stresses (N./mm²):

LONGITUDINAL PLANE (Stress Intensities	Au	Al	Bu	B1
	Outside	Inside	Outside	Inside
Two * Max Shear Stress	28	31	28	31

Nozzle Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Stresses in the hoop direction)	Cu	Cl	Du	D1
	Left Outside	Left Inside	Right Outside	Right Inside
Hoop Membrane (P)	3	3	3	3
Hoop Bending (P)	0	0	0	0
Hoop Membrane (Mc)	0	0	0	0
Hoop Bending (Mc)	0	0	0	0
Hoop Membrane (ML)	0	0	0	0
Hoop Bending (ML)	0	0	0	0
Hoop Pressure Stress	18	20	18	20
Hoop Stress Summary	21	23	21	23

Nozzle Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Stresses Normal to pipe cross-section)	Cu	Cl	Du	D1
	Left Outside	Left Inside	Right Outside	Right Inside
Axial Membrane (P)	0	0	0	0
Axial Bending (P)	17	-17	17	-17
Axial Membrane (Mc)	0	0	0	0
Axial Bending (Mc)	0	0	0	0
Axial Membrane (ML)	0	0	0	0
Axial Bending (ML)	0	0	0	0
Axial Pressure Stress	9	9	9	9
Axial Stress Summary	27	-7	28	-8

Nozzle Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Shear stress)	Cu	Cl	Du	D1
	Outside	Inside	Outside	Inside
Shear due to (Vc)	0	0	0	0
Shear due to (Vl)	-1	-1	1	1
Shear due to Torsion	0	0	0	0
Shear Stress Summary	-1	-1	1	1

Nozzle Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Stress Intensities	Cu	Cl	Du	D1
	Outside	Inside	Outside	Inside
Two * Max Shear Stress	28	31	28	32

Stress Computations at the Edge of the Reinforcing Pad:



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 126 of 173

Nozzle Calcs.: N1- Shell outle Nozl: 10 9:52am Aug 12,2026

Stress Attenuation Diameter (for Insert Plates) per WRC 297:

$$= \text{NozzleOD} + 2 \cdot 1.65 \cdot \sqrt{R_{\text{mean}}(t - c_a)}$$

$$= 273.05 + 2 \cdot 1.65 \cdot \sqrt{306.352(9.53 - 3.175)}$$

$$= 418.657 \text{ mm}$$

WRC 297 Curve Access Parameters:

Vessel Mean Diameter (D) = 612.705 mm
 Nozzle Outside Diameter (d) = 413.050 mm
 Vessel Thickness used (T) = 6.355 mm
 Nozzle Thickness used (t) = 81.913 mm
 T / t = 0.078
 d / t = 10.000

$$\lambda = [(d/D) \cdot \sqrt{(D/T)}] = 6.619$$

Note: Re-pad thickness is added to nozzle thickness to simulate the Re-pad.

Nr/P = 0.045
 Mr/P = 0.071
 M0/P = 0.019
 N0/P = 0.027
 MrD/Mc = 0.239
 NrDL/Mc = 0.092
 M0d/Mc = 0.067
 N0DL/Mc = 0.049
 MrD/Ml = 0.039
 NrDL/Ml = 0.036
 M0D/Ml = 0.012
 N0DL/Ml = 0.022

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Stresses Normal to longitudinal plane)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Outplane Membrane (P)	4	4	4	4
Outplane Bending (P)	19	-19	19	-19
Outplane Membrane (Mc)	0	0	0	0
Outplane Bending (Mc)	0	0	0	0
Outplane Membrane (ML)	0	0	0	0
Outplane Bending (ML)	0	0	0	0
Normal Pressure Stress	73	74	73	74
Outplane Stress Summary	96	59	96	59

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Stresses parallel to longitudinal plane)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Inplane Membrane (P)	7	7	7	7
Inplane Bending (P)	70	-70	70	-70
Inplane Membrane (Mc)	0	0	0	0
Inplane Bending (Mc)	0	0	0	0
Inplane Membrane (ML)	0	0	0	0
Inplane Bending (ML)	0	0	0	0
Inplane Pressure Stress	36	36	36	36
Inplane Stress Summary	114	-26	114	-26

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Shear stress normal to longitudinal plane)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
--	----------------------	---------------------	-------------------------	------------------------



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 127 of 173

Nozzle Calcs.: N1- Shell outle Nozl: 10 9:52am Aug 12,2026

Outplane Shear (Vc)	2	2	-2	-2
Outplane Shear (Vl)	0	0	0	0
Outplane Shear (Mt)	0	0	0	0

Shear Stress Summary	2	2	-2	-2
----------------------	---	---	----	----

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE	Au	Al	Bu	Bl
(Stress Intensities	Top	Top	Bottom	Bottom
	Outside	Inside	Outside	Inside

Two * Max Shear Stress	114	86	114	86
------------------------	-----	----	-----	----

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE	Cu	Cl	Du	Dl
(Stresses Normal to	Left	Left	Right	Right
circumferential plane)	Outside	Inside	Outside	Inside

Outplane Membrane (P)	4	4	4	4
Outplane Bending (P)	19	-19	19	-19
Outplane Membrane (Mc)	0	0	0	0
Outplane Bending (Mc)	0	0	0	0
Outplane Membrane (ML)	0	0	0	0
Outplane Bending (ML)	0	0	0	0
Normal Pressure Stress	36	36	36	36

Outplane Stress Summary	60	21	60	21
-------------------------	----	----	----	----

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE	Cu	Cl	Du	Dl
(Stresses parallel to	Left	Left	Right	Right
circumferential plane)	Outside	Inside	Outside	Inside

Inplane Membrane (P)	7	7	7	7
Inplane Bending (P)	70	-70	70	-70
Inplane Membrane (Mc)	0	0	0	0
Inplane Bending (Mc)	0	0	0	0
Inplane Membrane (ML)	0	0	0	0
Inplane Bending (ML)	0	0	0	0
Inplane Pressure Stress	73	74	73	74

Inplane Stress Summary	150	12	151	11
------------------------	-----	----	-----	----

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE	Cu	Cl	Du	Dl
(Shear stress normal to	Left	Left	Right	Right
circumferential plane)	Outside	Inside	Outside	Inside

Outplane Shear (Vc)	0	0	0	0
Outplane Shear (Vl)	-2	-2	2	2
Torsional Shear (Mt)	0	0	0	0

Shear Stress Summary	-2	-2	2	2
----------------------	----	----	---	---

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE	Cu	Cl	Du	Dl
(Stress Intensities	Left	Left	Right	Right
	Outside	Inside	Outside	Inside

Two * Max Shear Stress	150	22	151	22
------------------------	-----	----	-----	----



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 128 of 173

Nozzle Calcs.: N1- Shell outle

Nozl: 10 9:52am Aug 12,2026

Vessel Stress Summation at Vessel-Nozzle Junction (N./mm²):

Type of Stress Int. Location	Stress Values at							
	Au	Al	Bu	Bl	Cu	Cl	Du	Dl
Circ. Pm (SUS)	27	29	27	29	27	29	27	29
Circ. Pl (SUS)	3	3	3	3	1	1	1	1
Circ. Q (SUS)	5	-5	5	-5	13	-13	13	-13
Long. Pm (SUS)	13	13	13	13	13	13	13	13
Long. Pl (SUS)	1	1	1	1	3	3	3	3
Long. Q (SUS)	13	-13	13	-13	5	-5	5	-5
Shear Pm (SUS)	0	0	0	0	0	0	0	0
Shear Pl (SUS)	1	1	-1	-1	-1	-1	1	1
Shear Q (SUS)	0	0	0	0	0	0	0	0
Pm (SUS)	27.0	29.0	27.0	29.0	27.0	29.0	27.0	29.0
Pm+Pl (SUS)	30.1	32.1	30.1	32.1	28.1	30.1	28.1	30.1
Pm+Pl+Q (Total)	35.1	27.0	35.1	27.0	41.0	17.2	41.0	17.2

Vessel Stress Summation Comparison (N./mm²):

Type of Stress Int.	Max. S.I.	S.I. Allowable	Result
Pm (SUS)	29.00	140.75	Passed
Pm+Pl (SUS)	32.06	211.13	Passed
Pm+Pl+Q (TOTAL)	41.05	422.26	Passed

Because only sustained loads were specified, the Pm+Pl+Q allowable was 3 * Smh.

WRC 297 Stress Summations per ASME Sec. VIII Div. 2:

Vessel Stress Summation at Reinforcing Pad Edge (N./mm²):

Type of Stress Int. Location	Stress Values at							
	Au	Al	Bu	Bl	Cu	Cl	Du	Dl
Circ. Pm (SUS)	73	74	73	74	73	74	73	74
Circ. Pl (SUS)	4	4	4	4	7	7	7	7
Circ. Q (SUS)	19	-19	19	-19	70	-70	70	-70
Long. Pm (SUS)	36	36	36	36	36	36	36	36
Long. Pl (SUS)	7	7	7	7	4	4	4	4
Long. Q (SUS)	70	-70	70	-70	19	-19	19	-19
Shear Pm (SUS)	0	0	0	0	0	0	0	0
Shear Pl (SUS)	2	2	-2	-2	-2	-2	2	2
Shear Q (SUS)	0	0	0	0	0	0	0	0
Pm (SUS)	73.0	74.0	73.0	74.0	73.0	74.0	73.0	74.0
Pm+Pl (SUS)	77.1	78.1	77.1	78.1	80.1	81.1	80.1	81.1
Pm+Pl+Q (Total)	113.2	86.1	113.2	86.1	150.0	21.4	150.0	21.4

Vessel Stress Summation Comparison (N./mm²):

Type of Stress Int.	Max. S.I.	S.I. Allowable	Result
---------------------	-----------	----------------	--------



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 129 of 173

Nozzle Calcs.: N1- Shell outle Nozl: 10 9:52am Aug 12,2026

Pm (SUS)	74.00	140.75	Passed
Pm+Pl (SUS)	81.10	211.13	Passed
Pm+Pl+Q (TOTAL)	150.04	422.26	Passed

Because only sustained loads were specified, the Pm+Pl+Q allowable was 3 * Smh.

WRC 297 Stress Summations per ASME Sec. VIII Div. 2:

Nozzle Stress Summation at Vessel-Nozzle Junction (N./mm²):

Type of Stress Int. Location	Stress Values at							
	Au	Al	Bu	Bl	Cu	Cl	Du	Dl
Circ. Pm (SUS)	18	20	18	20	18	20	18	20
Circ. Pl (SUS)	3	3	3	3	3	3	3	3
Circ. Q (SUS)	0	0	0	0	0	0	0	0
Long. Pm (SUS)	9	9	9	9	9	9	9	9
Long. Pl (SUS)	0	0	0	0	0	0	0	0
Long. Q (SUS)	17	-17	17	-17	17	-17	17	-17
Shear Pm (SUS)	0	0	0	0	0	0	0	0
Shear Pl (SUS)	1	1	-1	-1	-1	-1	1	1
Shear Q (SUS)	0	0	0	0	0	0	0	0
Pm (SUS)	18.0	20.0	18.0	20.0	18.0	20.0	18.0	20.0
Pm+Pl (SUS)	21.1	23.1	21.1	23.1	21.1	23.1	21.1	23.1
Pm+Pl+Q (Total)	26.2	31.1	26.2	31.1	26.2	31.1	26.2	31.1

Nozzle Stress Summation Comparison (N./mm²):

Type of Stress Int.	Max. S.I.	S.I. Allowable	Result
Pm (SUS)	20.00	118.00	Passed
Pm+Pl (SUS)	23.07	177.00	Passed
Pm+Pl+Q (TOTAL)	31.06	353.99	Passed

Because only sustained loads were specified, the Pm+Pl+Q allowable was 3 * Smh.

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 130 of 173

Nozzle Calcs.: N2- shell inlet

Nozl: 11 9:52am Aug 12,2026

Input, Nozzle Desc: N2- shell inlet

From: 40

Pressure for Reinforcement Calculations	P	1549.500	KPa.
Temperature for Internal Pressure	Temp	166	°C
Parent Material		SA-106 B	
Parent Allowable Stress at Temperature	Sv	140.75	N./mm ²
Parent Allowable Stress At Ambient	Sva	161.00	N./mm ²
Inside Diameter of Cylindrical Shell	D	600.00	mm
Shell Finished (Minimum) Thickness	t	9.5300	mm
Shell Internal Corrosion Allowance	c	3.1750	mm
Shell External Corrosion Allowance	co	0.0000	mm
Distance from Bottom/Left Tangent		4807.00	mm
User Entered Minimum Design Metal Temperature		11.40	°C

Type of Element Connected to the Parent : Nozzle

Material		SA-106 B	
Material UNS Number		K03006	
Material Specification/Type		Smls. pipe	
Allowable Stress at Temperature	Sn	118.00	N./mm ²
Allowable Stress At Ambient	Sna	118.00	N./mm ²
Diameter Basis (for tr calc only)		Outside	
Layout Angle		270.00	deg
Diameter		12.0000	in.
Size and Thickness Basis		Nominal	
Nominal Thickness		80	
Flange Material		SA-105	
Flange Type		Weld Neck Flange	
Corrosion Allowance	can	3.1750	mm
Joint Efficiency of Shell Seam at Nozzle	E1	1.00	
Joint Efficiency of Nozzle Neck	En	1.00	
Outside Projection	ho	250.0000	mm
Weld leg size between Nozzle and Pad/Shell	Wo	10.0000	mm
Groove weld depth between Nozzle and Vessel	Wgnv	9.5300	mm
Inside Projection	h	0.0000	mm
Weld leg size, Inside Element to Shell	Wi	0.0000	mm
Pad Material		SA-516 70	
Pad Allowable Stress at Temperature	Sp	138.00	N./mm ²
Pad Allowable Stress At Ambient	Spa	138.00	N./mm ²
Diameter of Pad along vessel surface	Dp	463.8500	mm
Thickness of Pad	te	10.0000	mm
Weld leg size between Pad and Shell	Wp	8.0000	mm
Groove weld depth between Pad and Nozzle	Wgpn	10.0000	mm
Reinforcing Pad Width		70.0000	mm
Flange Class		300	
Flange Grade		GR 1.1	

The Pressure Design option was Design Pressure + static head.




PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 131 of 173

Nozzle Calcs.: N2- shell inlet

Nozl: 11 9:52am Aug 12,2026



Reinforcement CALCULATION, Description: N2- shell inlet

ASME Code, Section VIII, Div. 1, UG-37 to UG-45

Actual Outside Diameter Used in Calculation	12.750 in.
Actual Thickness Used in Calculation	0.687 in.

Nozzle input data check completed without errors.

Reqd thk per UG-37(a) of Cylindrical Shell, tr [Int. Press]
 $= P \cdot R / (S_v \cdot E - 0.6 \cdot P)$ per UG-27 (c)(1)
 $= 1549.5 \cdot 303.175 / (141 \cdot 1.0 - 0.6 \cdot 1549.5)$
 $= 3.3599 \text{ mm}$

Reqd thk per UG-37(a) of Nozzle Wall, trn [Int. Press]
 $= P \cdot R_o / (S_n \cdot E + 0.4 \cdot P)$ per Appendix 1-1 (a)(1)
 $= 1549.5 \cdot 161.925 / (118 \cdot 1.0 + 0.4 \cdot 1549.5)$
 $= 2.1153 \text{ mm}$

UG-40, Limits of Reinforcement: [Internal Pressure]

Parallel to Vessel Wall (Diameter Limit)	D1	590.6008 mm
Parallel to Vessel Wall, opening length	d	295.3004 mm
Normal to Vessel Wall (Thickness Limit), pad side Tlwp		15.8875 mm

Weld Strength Reduction Factor [fr1]:
 $= \min(1, S_n / S_v)$
 $= \min(1, 118.0 / 140.8)$
 $= 0.838$

Weld Strength Reduction Factor [fr2]:
 $= \min(1, S_n / S_v)$
 $= \min(1, 118.0 / 140.8)$
 $= 0.838$

Weld Strength Reduction Factor [fr4]:
 $= \min(1, S_p / S_v)$
 $= \min(1, 138.0 / 140.8)$
 $= 0.980$

Weld Strength Reduction Factor [fr3]:
 $= \min(fr2, fr4)$
 $= \min(0.838, 0.98)$
 $= 0.838$



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 132 of 173

Nozzle Calcs.: N2- shell inlet

Nozl: 11 9:52am Aug 12,2026




Figure UG 37.1 Nozzle Areas

Results of Nozzle Reinforcement Area Calculations: (cm²)

AREA AVAILABLE, A1 to A5		Design	External	Mapnc
Area Required	Ar	10.077	NA	NA
Area in Shell	A1	8.706	NA	NA
Area in Nozzle Wall	A2	3.239	NA	NA
Area in Inward Nozzle	A3	0.000	NA	NA
Area in Welds	A41+A42+A43	1.324	NA	NA
Area in Element	A5	13.726	NA	NA
TOTAL AREA AVAILABLE	Atot	26.995	NA	NA

The Internal Pressure Case Governs the Analysis.

Nozzle Angle Used in Area Calculations

90.00 degs.

The area available without a pad is Sufficient.

The area available with the given pad is Sufficient.

Area Required [A]:

$$\begin{aligned}
 &= (d \cdot tr \cdot F + 2 \cdot tn \cdot tr \cdot F \cdot (1 - fr1)) \text{ UG-37(c)} \\
 &= (295.3004 \cdot 3.3599 \cdot 1.0 + 2 \cdot 14.2748 \cdot 3.3599 \cdot 1.0 \cdot (1 - 0.84)) \\
 &= 10.077 \text{ cm}^2
 \end{aligned}$$

Reinforcement Areas per Figure UG-37.1

Area Available in Shell [A1]:

$$\begin{aligned}
 &= d(E1 \cdot t - F \cdot tr) - 2 \cdot tn(E1 \cdot t - F \cdot tr) \cdot (1 - fr1) \\
 &= 295.3(1.0 \cdot 6.355 - 1.0 \cdot 3.36) - 2 \cdot 14.275 \\
 &\quad (1.0 \cdot 6.355 - 1.0 \cdot 3.3599) \cdot (1 - 0.838) \\
 &= 8.706 \text{ cm}^2
 \end{aligned}$$

Area Available in Nozzle Wall Projecting Outward [A2]:

$$\begin{aligned}
 &= (2 \cdot Tlwp) \cdot (tn - trn) \cdot fr2 \\
 &= (2 \cdot 15.89) \cdot (14.27 - 2.12) \cdot 0.8383
 \end{aligned}$$



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 133 of 173

Nozzle Calcs.: N2- shell inlet Nozl: 11 9:52am Aug 12,2026

= 3.239 cm²

Area Available in Welds [A41 + A42 + A43]:

= (Wo² - Ar Lost)•Fr3+((Wi-can/0.707)² - Ar Lost)•fr2 + Wp²•fr4
 = (0.8309) • 0.84 + (0.0) • 0.84 + 8.0² • 0.98
 = 1.324 cm²

Area Available in Element [A5]:

= (min(Dp,DL)-(Nozzle OD))•(min(tp,Tlwp,te)) • fr4
 = (463.8501 - 323.85) • 10.0 • 0.9804
 = 13.726 cm²

UG-45 Minimum Nozzle Neck Thickness Requirement: [Int. Press.]

Wall Thickness for Internal/External pressures ta = 5.2903 mm
 Wall Thickness per UG16(b), tr16b = 5.6750 mm
 Wall Thickness, shell/head, internal pressure trb1 = 6.5349 mm
 Wall Thickness tb1 = max(trb1, tr16b) = 6.5349 mm
 Wall Thickness tb2 = max(trb2, tr16b) = 5.6750 mm
 Wall Thickness per table UG-45 tb3 = 11.5062 mm

Determine Nozzle Thickness candidate [tb]:

= min[tb3, max(tb1,tb2)]
 = min[11.506, max(6.5349, 5.675)]
 = 6.5349 mm

Minimum Wall Thickness of Nozzle Necks [tUG-45]:

= max(ta, tb)
 = max(5.2903, 6.5349)
 = 6.5349 mm

Available Nozzle Neck Thickness = 0.875 * 17.450 = 15.269 mm -> OK

Stresses on Nozzle due to External and Pressure Loads per the ASME B31.3 Piping Code, (see 319.4.4 and 302.3.5):

Sustained	:	7.1,	Allowable	:	118.0 N./mm ²	Passed
Expansion	:	0.0,	Allowable	:	287.9 N./mm ²	Passed
Occasional	:	7.6,	Allowable	:	156.9 N./mm ²	Passed
Shear	:	2.6,	Allowable	:	82.6 N./mm ²	Passed

The number of cycles on this nozzle was assumed to be 7000 or less for the determination of the expansion stress allowable.

Nozzle Junction Minimum Design Metal Temperature (MDMT) Calculations:

Nozzle Neck to Flange Weld, min(Curve:B, Curve:A)

Govrn. thk, tg = 15.269, tr = 2.115, c = 3.175 mm, E* = 1.0
 Thickness Ratio = tr * E*/(tg - c) = 0.175, Temp. Reduction = 78 °C

Min Metal Temp. w/o impact per UCS-66, Curve A	4 °C
Min Metal Temp. at Required thickness (UCS 66.1)	-104 °C

Nozzle Neck to Pad Weld for the Nozzle, Curve: B

Govrn. thk, tg = 10.0, c = 3.175 mm, E* = 1.0
 Thickness Ratio = tr * E*/(tg - c) = 0.462, Temp. Reduction = 38 °C
 Attachment governing, Attachment stress = Shell stress per Code

Min Metal Temp. w/o impact per UCS-66, Curve B	-29 °C
Min Metal Temp. at Required thickness (UCS 66.1)	-48 °C

Nozzle Neck to Pad Weld for Reinforcement pad, Curve: B

Govrn. thk, tg = 10.0, c = 3.175 mm, E* = 1.0



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 134 of 173

Nozzle Calcs.: N2- shell inlet Nozl: 11 9:52am Aug 12,2026

Thickness Ratio = $tr \cdot E^* / (tg - c) = 0.462$, Temp. Reduction = 38 °C
Attachment governing, Attachment stress = Shell stress per Code

Min Metal Temp. w/o impact per UCS-66, Curve B -29 °C
Min Metal Temp. at Required thickness (UCS 66.1) -48 °C

Shell to Pad Weld Junction at Pad OD, Curve: B

Govrn. thk, $tg = 9.53$, $tr = 2.935$, $c = 3.175$ mm, $E^* = 1.0$
Thickness Ratio = $tr \cdot E^* / (tg - c) = 0.462$, Temp. Reduction = 38 °C

Min Metal Temp. w/o impact per UCS-66, Curve B -29 °C
Min Metal Temp. at Required thickness (UCS 66.1) -48 °C

Nozzle-Shell/Head Weld (UCS-66(a)(b)), Curve: B

Govrn. thk, $tg = 9.53$, $tr = 2.935$, $c = 3.175$ mm, $E^* = 1.0$
Thickness Ratio = $tr \cdot E^* / (tg - c) = 0.462$, Temp. Reduction = 38 °C

Min Metal Temp. w/o impact per UCS-66, Curve B -29 °C
Min Metal Temp. at Required thickness (UCS 66.1) -48 °C

Gov. MDMT of the Nozzle : -48 °C
Gov. MDMT of the Reinforcement Pad : -48 °C
Gov. MDMT of the nozzle to shell joint welded assembly : -48 °C

Flange MDMT including Temperature reduction per UCS-66.1:

Unadjusted MDMT of ASME B16.5/47 flanges per UCS-66(c) -18 °C
Flange MDMT with Temp reduction per UCS-66(b)(1)(-b) -104 °C

Where the Stress Reduction Ratio per UCS-66(b)(1)(-b) is :
Design Pressure/Ambient Rating = $1549.50 / 5100.00 = 0.304$

Weld Size Calculations, Description: N2- shell inlet

Intermediate Calc. for nozzle/shell Welds $T_{min} = 10.0000$ mm
Intermediate Calc. for pad/shell Welds $T_{minPad} = 6.3550$ mm

Results Per UW-16.1:

	Required Thickness	Actual Thickness
Nozzle Weld	$6.0000 = \text{Min per Code}$	$7.0700 = 0.7 \cdot W_o$ mm
Pad Weld	$3.1775 = 0.5 \cdot T_{minPad}$	$5.6560 = 0.7 \cdot W_p$ mm

Weld Strength and Weld Loads per UG-41.1, Sketch (a) or (b)

Weld Load [W]:
 $= \max(0, (A - A1 + 2 \cdot tn \cdot fr1 \cdot (E1 \cdot t - tr)) \cdot Sv)$
 $= \max(0, (10.0769 - 8.7063 + 2 \cdot 14.2748 \cdot 0.8383 \cdot (1.0 \cdot 6.355 - 3.3599)) \cdot 141)$
 $= 2996.12$ Kg

Note: F is always set to 1.0 throughout the calculation.

Weld Load [W1]:
 $= (A2 + A5 + A4 - (Wi - Can / .707)^2 \cdot fr2) \cdot Sv$
 $= (3.239 + 13.7259 + 1.324 - 0.0 \cdot 0.84) \cdot 141$
 $= 26249.36$ Kg

Weld Load [W2]:
 $= (A2 + A3 + A4 + (2 \cdot tn \cdot t \cdot fr1)) \cdot Sv$
 $= (3.239 + 0.0 + 0.8383 + (1.521)) \cdot 141$
 $= 8035.10$ Kg

Weld Load [W3]:



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 135 of 173

Nozzle Calcs.: N2- shell inlet Nozl: 11 9:52am Aug 12,2026

$$= (A2+A3+A4+A5+(2 \cdot t_n \cdot t_{fr1})) \cdot S$$

$$= (3.239 + 0.0 + 1.324 + 13.7259 + (1.521)) \cdot 141$$

$$= 28432.40 \text{ Kgf}$$

Strength of Connection Elements for Failure Path Analysis

Shear, Outward Nozzle Weld [Sonw]:

$$= (\pi/2) \cdot D_{lo} \cdot W_o \cdot 0.49 \cdot S_{nw}$$

$$= (3.1416/2.0) \cdot 323.85 \cdot 10.0 \cdot 0.49 \cdot 118$$

$$= 29992. \text{ Kgf}$$

Shear, Pad Element Weld [Spew]:

$$= (\pi/2) \cdot D_P \cdot W_P \cdot 0.49 \cdot S_{EW}$$

$$= (3.1416/2.0) \cdot 463.85 \cdot 8.0 \cdot 0.49 \cdot 138$$

$$= 40191. \text{ Kgf}$$

Shear, Nozzle Wall [Snw]:

$$= (\pi \cdot (D_{lr} + D_{lo})/4) \cdot (Thk - Can) \cdot 0.7 \cdot S_n$$

$$= (3.1416 \cdot 154.7876) \cdot (17.4498 - 3.175) \cdot 0.7 \cdot 118$$

$$= 58465. \text{ Kgf}$$

Tension, Pad Groove Weld [Tpgw]:

$$= (\pi/2) \cdot D_{lo} \cdot W_{gpn} \cdot 0.74 \cdot S_{eg}$$

$$= (3.1416/2) \cdot 323.85 \cdot 10.0 \cdot 0.74 \cdot 138$$

$$= 52971. \text{ Kgf}$$

Tension, Shell Groove Weld [Tngw]:

$$= (\pi/2) \cdot D_{lo} \cdot (T - cas) \cdot 0.74 \cdot S_{ng}$$

$$= (3.1416/2.0) \cdot 323.85 \cdot (9.53 - 3.175) \cdot 0.74 \cdot 141$$

$$= 34335. \text{ Kgf}$$

See UG-41 and UW-15 for clarification of allowable stresses.

Strength of Failure Paths:

Failure Path [Path 1-1]:

$$= (S_{PEW} + S_{NW}) = (40191 + 58465) = 98656 \text{ Kgf}$$

Failure Path [Path 2-2]:

$$= (S_{onw} + T_{pgw} + T_{ngw} + S_{inw})$$

$$= (29992 + 52971 + 34335 + 0) = 117298 \text{ Kgf}$$

Failure Path [Path 3-3]:

$$= (S_{pew} + T_{ngw} + S_{inw})$$

$$= (40191 + 34335 + 0) = 74526 \text{ Kgf}$$

Summary of Failure Path Calculations:

Path 1-1 = 98656	Kgf, must exceed W = 2996 Kgf	or W1 = 26249 Kgf
Path 2-2 = 117298	Kgf, must exceed W = 2996 Kgf	or W2 = 8035 Kgf
Path 3-3 = 74526	Kgf, must exceed W = 2996 Kgf	or W3 = 28432 Kgf

Maximum Allowable Pressure for this Nozzle at this Location:

Converged Maximum Allowable Pressure in the Operating case: 2819 KPa.

The Drop for this Nozzle is : 47.4524 mm

The Cut Length for this Nozzle is, Drop + Ho + H + T : 306.9824 mm

Input Echo, WRC297 Item 1, Description: N2- shell inle:

Diameter Basis for Cylindrical Shell	ID
Shell Internal Corrosion Allowance	3.1750 mm
Shell External Corrosion Allowance	0.0000 mm
Shell Diameter	600.000 mm
Shell Thickness	9.5300 mm
Shell Stress Concentration Factor	1.000



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 136 of 173

Nozzle Calcs.: N2- shell inlet Nozl: 11 9:52am Aug 12,2026

Vessel Material		SA-106 B	
Vessel Cold S.I. Allowable	Smc	161.00	N./mm ²
Vessel Hot S.I. Allowable	Smh	140.75	N./mm ²
Diameter Basis for Nozzle		OD	
Nozzle Corrosion Allowance		3.1750	mm
Nozzle Diameter		323.850	mm
Nozzle Thickness		17.4498	mm
Nozzle Stress Concentration Factor		1.000	
Nozzle Material		SA-106 B	
Nozzle Cold S.I. Allowable	SNmc	118.00	N./mm ²
Nozzle Hot S.I. Allowable	SNmh	118.00	N./mm ²

See ASME VIII Div. 2, 4.1.6.3, for determination of the SPS allowable.

Diameter of Reinforcing Pad	463.850	mm
Thickness of Reinforcing Pad	10.0000	mm

Note:

External Forces and Moments in WRC 107/537 Convention:
These loads are assumed to be SUSained loads.

Design Internal Pressure	Dp	1549.50	KPa.
Radial Load	P	-826.02	Kgf
Circumferential Shear	Vc	1223.74	Kgf
Longitudinal Shear	Vl	1223.74	Kgf
Circumferential Moment	Mc	1.10	Kg-m.
Longitudinal Moment	Ml	1.47	Kg-m.
Torsional Moment	Mt	1.83	Kg-m.

Include Axial Pressure Thrust	No
Include Pressure Stress Indices per Div. 2	No
Local Loads applied at end of Nozzle/Attachment	No

Warning - The ratio, Dn/Dv (.523) is > 0.5
check the Limitations of WRC bulletin 297.

Stress Computations at the Edge of the Nozzle:

Stress Attenuation Diameter (for Insert Plates) per WRC 297:

$$= \text{NozzleOD} + 2 \cdot 1.65 \cdot \sqrt{R_{\text{mean}}(t - ca)}$$

$$= 323.85 + 2 \cdot 1.65 \cdot \sqrt{311.353(9.53 - 3.175)}$$

$$= 470.640 \text{ mm}$$

WRC 297 Curve Access Parameters:

Vessel Mean Diameter	(D) =	622.705	mm
Nozzle Outside Diameter	(d) =	323.850	mm
Vessel Thickness used	(T) =	16.355	mm
Nozzle Thickness used	(t) =	14.275	mm
T / t	=	1.146	
d / t	=	22.687	

$$\lambda = [(d/D) \cdot \sqrt{(D/T)}] = 3.209$$

Nr/P	=	0.052
Mr/P	=	0.090
M0/P	=	0.032
N0/P	=	0.119
MrD/Mc	=	0.229
NrDL/Mc	=	0.096
M0d/Mc	=	0.090
N0DL/Mc	=	0.117
MrD/Ml	=	0.099



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 137 of 173

Nozzle Calcs.: N2- shell inlet

Nozl: 11 9:52am Aug 12,2026

NrDL/M1 = 0.045

MØD/M1 = 0.039

NØDL/M1 = 0.152

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Stresses Normal to longitudinal plane)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Outplane Membrane (P)	3	3	3	3
Outplane Bending (P)	5	-5	5	-5
Outplane Membrane (Mc)	0	0	0	0
Outplane Bending (Mc)	0	0	0	0
Outplane Membrane (ML)	0	0	0	0
Outplane Bending (ML)	0	0	0	0
Normal Pressure Stress	27	29	27	29
Outplane Stress Summary	37	27	37	27

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Stresses parallel to longitudinal plane)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Inplane Membrane (P)	1	1	1	1
Inplane Bending (P)	16	-16	16	-16
Inplane Membrane (Mc)	0	0	0	0
Inplane Bending (Mc)	0	0	0	0
Inplane Membrane (ML)	0	0	0	0
Inplane Bending (ML)	0	0	0	0
Inplane Pressure Stress	13	13	13	13
Inplane Stress Summary	31	0	31	0

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Shear stress normal to longitudinal plane)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Outplane Shear (Vc)	1	1	-1	-1
Outplane Shear (Vl)	0	0	0	0
Outplane Shear (Mt)	0	0	0	0
Shear Stress Summary	1	1	-1	-1

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Stress Intensities)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Two * Max Shear Stress	37	28	37	28

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Stresses Normal to circumferential plane)	Cu Left Outside	Cl Left Inside	Du Right Outside	Dl Right Inside
Outplane Membrane (P)	3	3	3	3
Outplane Bending (P)	5	-5	5	-5
Outplane Membrane (Mc)	0	0	0	0
Outplane Bending (Mc)	0	0	0	0
Outplane Membrane (ML)	0	0	0	0
Outplane Bending (ML)	0	0	0	0
Normal Pressure Stress	13	13	13	13



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 138 of 173

Nozzle Calcs.: N2- shell inlet Nozl: 11 9:52am Aug 12,2026

Outplane Stress Summary	23	11	23	11
-------------------------	----	----	----	----

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE	Cu	Cl	Du	Dl
(Stresses parallel to	Left	Left	Right	Right
circumferential plane)	Outside	Inside	Outside	Inside

Inplane Membrane (P)	1	1	1	1
Inplane Bending (P)	16	-16	16	-16
Inplane Membrane (Mc)	0	0	0	0
Inplane Bending (Mc)	0	0	0	0
Inplane Membrane (ML)	0	0	0	0
Inplane Bending (ML)	0	0	0	0
Inplane Pressure Stress	27	29	27	29

Inplane Stress Summary	45	14	46	14
------------------------	----	----	----	----

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE	Cu	Cl	Du	Dl
(Shear stress normal to	Left	Left	Right	Right
circumferential plane)	Outside	Inside	Outside	Inside

Outplane Shear (Vc)	0	0	0	0
Outplane Shear (Vl)	-1	-1	1	1
Torsional Shear (Mt)	0	0	0	0

Shear Stress Summary	-1	-1	1	1
----------------------	----	----	---	---

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE	Cu	Cl	Du	Dl
(Stress Intensities	Left	Left	Right	Right
	Outside	Inside	Outside	Inside

Two * Max Shear Stress	45	15	46	15
------------------------	----	----	----	----

Nozzle Stresses (N./mm²):

LONGITUDINAL PLANE	Au	Al	Bu	Bl
(Stresses in the	Top	Top	Bottom	Bottom
hoop direction)	Outside	Inside	Outside	Inside

Hoop Membrane (P)	3	3	3	3
Hoop Bending (P)	0	0	0	0
Hoop Membrane (Mc)	0	0	0	0
Hoop Bending (Mc)	0	0	0	0
Hoop Membrane (ML)	0	0	0	0
Hoop Bending (ML)	0	0	0	0
Hoop Pressure Stress	18	20	18	20

Hoop Stress Summary	21	23	21	23
---------------------	----	----	----	----

Nozzle Stresses (N./mm²):

LONGITUDINAL PLANE	Au	Al	Bu	Bl
(Stresses Normal to	Top	Top	Bottom	Bottom
pipe cross-section)	Outside	Inside	Outside	Inside

Axial Membrane (P)	0	0	0	0
Axial Bending (P)	15	-15	15	-15
Axial Membrane (Mc)	0	0	0	0
Axial Bending (Mc)	0	0	0	0
Axial Membrane (ML)	0	0	0	0
Axial Bending (ML)	0	0	0	0
Axial Pressure Stress	9	9	9	9

Axial Stress Summary	24	-5	25	-5
----------------------	----	----	----	----



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 139 of 173

Nozzle Calcs.: N2- shell inlet

Nozl: 11 9:52am Aug 12,2026

Nozzle Stresses (N./mm²):

LONGITUDINAL PLANE (Shear stress)	Au Outside	Al Inside	Bu Outside	Bl Inside
Shear due to (Vc)	1	1	-1	-1
Shear due to (Vl)	0	0	0	0
Shear due to Torsion	0	0	0	0
Shear Stress Summary	1	1	-1	-1

Nozzle Stresses (N./mm²):

LONGITUDINAL PLANE (Stress Intensities	Au Outside	Al Inside	Bu Outside	Bl Inside
Two * Max Shear Stress	25	29	25	29

Nozzle Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Stresses in the hoop direction)	Cu Left Outside	Cl Left Inside	Du Right Outside	Dl Right Inside
Hoop Membrane (P)	3	3	3	3
Hoop Bending (P)	0	0	0	0
Hoop Membrane (Mc)	0	0	0	0
Hoop Bending (Mc)	0	0	0	0
Hoop Membrane (ML)	0	0	0	0
Hoop Bending (ML)	0	0	0	0
Hoop Pressure Stress	18	20	18	20
Hoop Stress Summary	21	23	21	23

Nozzle Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Stresses Normal to pipe cross-section)	Cu Left Outside	Cl Left Inside	Du Right Outside	Dl Right Inside
Axial Membrane (P)	0	0	0	0
Axial Bending (P)	15	-15	15	-15
Axial Membrane (Mc)	0	0	0	0
Axial Bending (Mc)	0	0	0	0
Axial Membrane (ML)	0	0	0	0
Axial Bending (ML)	0	0	0	0
Axial Pressure Stress	9	9	9	9
Axial Stress Summary	24	-5	25	-5

Nozzle Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Shear stress)	Cu Outside	Cl Inside	Du Outside	Dl Inside
Shear due to (Vc)	0	0	0	0
Shear due to (Vl)	-1	-1	1	1
Shear due to Torsion	0	0	0	0
Shear Stress Summary	-1	-1	1	1

Nozzle Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Stress Intensities	Cu Outside	Cl Inside	Du Outside	Dl Inside
Two * Max Shear Stress	25	29	25	29

Stress Computations at the Edge of the Reinforcing Pad:



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 140 of 173

Nozzle Calcs.: N2- shell inlet Nozl: 11 9:52am Aug 12,2026

Stress Attenuation Diameter (for Insert Plates) per WRC 297:

$$= \text{NozzleOD} + 2 \cdot 1.65 \cdot \sqrt{R_{\text{mean}}(t - c_a)}$$

$$= 323.85 + 2 \cdot 1.65 \cdot \sqrt{306.352(9.53 - 3.175)}$$

$$= 469.457 \text{ mm}$$

WRC 297 Curve Access Parameters:

Vessel Mean Diameter (D) = 612.705 mm
 Nozzle Outside Diameter (d) = 463.850 mm
 Vessel Thickness used (T) = 6.355 mm
 Nozzle Thickness used (t) = 84.275 mm
 T / t = 0.075
 d / t = 10.000

$$\lambda = [(d/D) \cdot \sqrt{(D/T)}] = 7.434$$

Note: Re-pad thickness is added to nozzle thickness to simulate the Re-pad.

Nr/P = 0.045
 Mr/P = 0.071
 M0/P = 0.019
 N0/P = 0.026
 MrD/Mc = 0.239
 NrDL/Mc = 0.091
 M0d/Mc = 0.067
 N0DL/Mc = 0.048
 MrD/Ml = 0.037
 NrDL/Ml = 0.035
 M0D/Ml = 0.012
 N0DL/Ml = 0.022

Vessel Stresses (N/mm²):

LONGITUDINAL PLANE (Stresses Normal to longitudinal plane)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Outplane Membrane (P)	5	5	5	5
Outplane Bending (P)	23	-23	23	-23
Outplane Membrane (Mc)	0	0	0	0
Outplane Bending (Mc)	0	0	0	0
Outplane Membrane (ML)	0	0	0	0
Outplane Bending (ML)	0	0	0	0
Normal Pressure Stress	73	74	73	74
Outplane Stress Summary	101	56	101	56

Vessel Stresses (N/mm²):

LONGITUDINAL PLANE (Stresses parallel to longitudinal plane)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Inplane Membrane (P)	9	9	9	9
Inplane Bending (P)	84	-84	84	-84
Inplane Membrane (Mc)	0	0	0	0
Inplane Bending (Mc)	0	0	0	0
Inplane Membrane (ML)	0	0	0	0
Inplane Bending (ML)	0	0	0	0
Inplane Pressure Stress	36	36	36	36
Inplane Stress Summary	130	-39	130	-39

Vessel Stresses (N/mm²):

LONGITUDINAL PLANE (Shear stress normal to longitudinal plane)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
--	----------------------	---------------------	-------------------------	------------------------



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 141 of 173

Nozzle Calcs.: N2- shell inlet

Nozl: 11 9:52am Aug 12,2026

Outplane Shear (Vc)	2	2	-2	-2
Outplane Shear (Vl)	0	0	0	0
Outplane Shear (Mt)	0	0	0	0

Shear Stress Summary	2	2	-2	-2
----------------------	---	---	----	----

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE	Au	Al	Bu	Bl
(Stress Intensities	Top	Top	Bottom	Bottom
	Outside	Inside	Outside	Inside

Two * Max Shear Stress	130	96	131	96
------------------------	-----	----	-----	----

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE	Cu	Cl	Du	Dl
(Stresses Normal to	Left	Left	Right	Right
circumferential plane)	Outside	Inside	Outside	Inside

Outplane Membrane (P)	5	5	5	5
Outplane Bending (P)	23	-23	23	-23
Outplane Membrane (Mc)	0	0	0	0
Outplane Bending (Mc)	0	0	0	0
Outplane Membrane (ML)	0	0	0	0
Outplane Bending (ML)	0	0	0	0
Normal Pressure Stress	36	36	36	36

Outplane Stress Summary	64	18	65	18
-------------------------	----	----	----	----

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE	Cu	Cl	Du	Dl
(Stresses parallel to	Left	Left	Right	Right
circumferential plane)	Outside	Inside	Outside	Inside

Inplane Membrane (P)	9	9	9	9
Inplane Bending (P)	84	-84	84	-84
Inplane Membrane (Mc)	0	0	0	0
Inplane Bending (Mc)	0	0	0	0
Inplane Membrane (ML)	0	0	0	0
Inplane Bending (ML)	0	0	0	0
Inplane Pressure Stress	73	74	73	74

Inplane Stress Summary	166	0	168	-2
------------------------	-----	---	-----	----

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE	Cu	Cl	Du	Dl
(Shear stress normal to	Left	Left	Right	Right
circumferential plane)	Outside	Inside	Outside	Inside

Outplane Shear (Vc)	0	0	0	0
Outplane Shear (Vl)	-2	-2	2	2
Torsional Shear (Mt)	0	0	0	0

Shear Stress Summary	-2	-2	2	2
----------------------	----	----	---	---

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE	Cu	Cl	Du	Dl
(Stress Intensities	Left	Left	Right	Right
	Outside	Inside	Outside	Inside

Two * Max Shear Stress	166	20	168	21
------------------------	-----	----	-----	----



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 142 of 173

Nozzle Calcs.: N2- shell inlet

Nozl: 11 9:52am Aug 12,2026

Vessel Stress Summation at Vessel-Nozzle Junction (N./mm²):

Type of Stress Int. Location	Stress Values at							
	Au	Al	Bu	Bl	Cu	Cl	Du	Dl
Circ. Pm (SUS)	27	29	27	29	27	29	27	29
Circ. Pl (SUS)	3	3	3	3	1	1	1	1
Circ. Q (SUS)	5	-5	5	-5	16	-16	16	-16
Long. Pm (SUS)	13	13	13	13	13	13	13	13
Long. Pl (SUS)	1	1	1	1	3	3	3	3
Long. Q (SUS)	16	-16	16	-16	5	-5	5	-5
Shear Pm (SUS)	0	0	0	0	0	0	0	0
Shear Pl (SUS)	1	1	-1	-1	-1	-1	1	1
Shear Q (SUS)	0	0	0	0	0	0	0	0
Pm (SUS)	27.0	29.0	27.0	29.0	27.0	29.0	27.0	29.0
Pm+Pl (SUS)	30.1	32.1	30.1	32.1	28.1	30.1	28.1	30.1
Pm+Pl+Q (Total)	35.2	29.1	35.2	29.1	44.0	14.3	44.0	14.3

Vessel Stress Summation Comparison (N./mm²):

Type of Stress Int.	Max. S.I.	S.I. Allowable	Result
Pm (SUS)	29.00	140.75	Passed
Pm+Pl (SUS)	32.06	211.13	Passed
Pm+Pl+Q (TOTAL)	44.04	422.26	Passed

Because only sustained loads were specified, the Pm+Pl+Q allowable was 3 * Smh.

WRC 297 Stress Summations per ASME Sec. VIII Div. 2:

Vessel Stress Summation at Reinforcing Pad Edge (N./mm²):

Type of Stress Int. Location	Stress Values at							
	Au	Al	Bu	Bl	Cu	Cl	Du	Dl
Circ. Pm (SUS)	73	74	73	74	73	74	73	74
Circ. Pl (SUS)	5	5	5	5	9	9	9	9
Circ. Q (SUS)	23	-23	23	-23	84	-84	84	-84
Long. Pm (SUS)	36	36	36	36	36	36	36	36
Long. Pl (SUS)	9	9	9	9	5	5	5	5
Long. Q (SUS)	84	-84	84	-84	23	-23	23	-23
Shear Pm (SUS)	0	0	0	0	0	0	0	0
Shear Pl (SUS)	2	2	-2	-2	-2	-2	2	2
Shear Q (SUS)	0	0	0	0	0	0	0	0
Pm (SUS)	73.0	74.0	73.0	74.0	73.0	74.0	73.0	74.0
Pm+Pl (SUS)	78.1	79.1	78.1	79.1	82.1	83.1	82.1	83.1
Pm+Pl+Q (Total)	129.1	95.1	129.1	95.1	166.0	19.4	166.0	19.4

Vessel Stress Summation Comparison (N./mm²):

Type of Stress Int.	Max. S.I.	S.I. Allowable	Result
---------------------	-----------	----------------	--------



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 143 of 173

Nozzle Calcs.: N2- shell inlet

Nozl: 11

9:52am Aug 12,2026

Pm (SUS)	74.00	140.75	Passed
Pm+Pl (SUS)	83.10	211.13	Passed
Pm+Pl+Q (TOTAL)	166.04	422.26	Passed

Because only sustained loads were specified, the Pm+Pl+Q allowable was 3 * Smh.

WRC 297 Stress Summations per ASME Sec. VIII Div. 2:

Nozzle Stress Summation at Vessel-Nozzle Junction (N./mm²):

Type of Stress Int. Location	Stress Values at							
	Au	Al	Bu	Bl	Cu	Cl	Du	Dl
Circ. Pm (SUS)	18	20	18	20	18	20	18	20
Circ. Pl (SUS)	3	3	3	3	3	3	3	3
Circ. Q (SUS)	0	0	0	0	0	0	0	0
Long. Pm (SUS)	9	9	9	9	9	9	9	9
Long. Pl (SUS)	0	0	0	0	0	0	0	0
Long. Q (SUS)	15	-15	15	-15	15	-15	15	-15
Shear Pm (SUS)	0	0	0	0	0	0	0	0
Shear Pl (SUS)	1	1	-1	-1	-1	-1	1	1
Shear Q (SUS)	0	0	0	0	0	0	0	0
Pm (SUS)	18.0	20.0	18.0	20.0	18.0	20.0	18.0	20.0
Pm+Pl (SUS)	21.1	23.1	21.1	23.1	21.1	23.1	21.1	23.1
Pm+Pl+Q (Total)	24.3	29.1	24.3	29.1	24.3	29.1	24.3	29.1

Nozzle Stress Summation Comparison (N./mm²):

Type of Stress Int.	Max. S.I.	S.I. Allowable	Result
Pm (SUS)	20.00	118.00	Passed
Pm+Pl (SUS)	23.07	177.00	Passed
Pm+Pl+Q (TOTAL)	29.07	353.99	Passed

Because only sustained loads were specified, the Pm+Pl+Q allowable was 3 * Smh.

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 144 of 173

Nozzle Calcs.: N2- Channel out

Nozl: 12

9:52am Aug 12,2026

Input, Nozzle Desc: N2- Channel outlet

From: 60

Pressure for Reinforcement Calculations	P	1191.500	KPa.
Temperature for Internal Pressure	Temp	77	°C
Parent Material		SA-106 B	
Parent Allowable Stress at Temperature	Sv	118.00	N./mm ²
Parent Allowable Stress At Ambient	Sva	118.00	N./mm ²
Inside Diameter of Cylindrical Shell	D	600.00	mm
Shell Finished (Minimum) Thickness	t	9.5300	mm
Shell Internal Corrosion Allowance	c	3.1750	mm
Shell External Corrosion Allowance	co	0.0000	mm
Distance from Bottom/Left Tangent		6027.80	mm
User Entered Minimum Design Metal Temperature		11.40	°C

Type of Element Connected to the Parent : Nozzle

Material		SA-106 B	
Material UNS Number		K03006	
Material Specification/Type		Smls. pipe	
Allowable Stress at Temperature	Sn	118.00	N./mm ²
Allowable Stress At Ambient	Sna	118.00	N./mm ²
Diameter Basis (for tr calc only)		Outside	
Layout Angle		270.00	deg
Diameter		6.0000	in.
Size and Thickness Basis		Nominal	
Nominal Thickness		80	
Flange Material		SA-105	
Flange Type		Weld Neck Flange	
Corrosion Allowance	can	3.1750	mm
Joint Efficiency of Shell Seam at Nozzle	E1	1.00	
Joint Efficiency of Nozzle Neck	En	1.00	
Outside Projection	ho	250.0000	mm
Weld leg size between Nozzle and Pad/Shell	Wo	30.0000	mm
Groove weld depth between Nozzle and Vessel	Wgnv	9.5300	mm
Inside Projection	h	0.0000	mm
Weld leg size, Inside Element to Shell	Wi	0.0000	mm
Pad Material		SA-516 70	
Pad Allowable Stress at Temperature	Sp	138.00	N./mm ²
Pad Allowable Stress At Ambient	Spa	138.00	N./mm ²
Diameter of Pad along vessel surface	Dp	308.2750	mm
Thickness of Pad	te	10.0000	mm
Weld leg size between Pad and Shell	Wp	8.0000	mm
Groove weld depth between Pad and Nozzle	Wgpn	10.0000	mm
Reinforcing Pad Width		70.0000	mm
Flange Class		150	
Flange Grade		GR 1.1	

The Pressure Design option was Design Pressure + static head.




PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 145 of 173

Nozzle Calcs.: N2- Channel out

Noz1: 12 9:52am Aug 12,2026



Reinforcement CALCULATION, Description: N2- Channel outlet

ASME Code, Section VIII, Div. 1, UG-37 to UG-45

Actual Outside Diameter Used in Calculation	6.625 in.
Actual Thickness Used in Calculation	0.432 in.

Nozzle input data check completed without errors.

Reqd thk per UG-37(a) of Cylindrical Shell, tr [Int. Press]
 $= P \cdot R / (S_v \cdot E - 0.6 \cdot P)$ per UG-27 (c)(1)
 $= 1191.5 \cdot 303.175 / (118 \cdot 1.0 - 0.6 \cdot 1191.5)$
 $= 3.0802 \text{ mm}$

Reqd thk per UG-37(a) of Nozzle Wall, trn [Int. Press]
 $= P \cdot R_o / (S_n \cdot E + 0.4 \cdot P)$ per Appendix 1-1 (a)(1)
 $= 1191.5 \cdot 84.1375 / (118 \cdot 1.0 + 0.4 \cdot 1191.5)$
 $= 0.8462 \text{ mm}$

UG-40, Limits of Reinforcement: [Internal Pressure]

Parallel to Vessel Wall (Diameter Limit)	D1	305.3588 mm
Parallel to Vessel Wall, opening length	d	152.6794 mm
Normal to Vessel Wall (Thickness Limit), pad side Tlwp		15.8875 mm

The Pad diameter is greater than the Diameter Limit. The excess will not be considered.

Weld Strength Reduction Factor [fr1]:
 $= \min(1, S_n / S_v)$
 $= \min(1, 118.0 / 118.0)$
 $= 1.000$

Weld Strength Reduction Factor [fr2]:
 $= \min(1, S_n / S_v)$
 $= \min(1, 118.0 / 118.0)$
 $= 1.000$

Weld Strength Reduction Factor [fr4]:
 $= \min(1, S_p / S_v)$
 $= \min(1, 138.0 / 118.0)$
 $= 1.000$

Weld Strength Reduction Factor [fr3]:
 $= \min(fr2, fr4)$
 $= \min(1.0, 1.0)$
 $= 1.000$



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 146 of 173

Nozzle Calcs.: N2- Channel out

Noz1: 12 9:52am Aug 12,2026




Figure UG 37.1 Nozzle Areas

Results of Nozzle Reinforcement Area Calculations: (cm²)

AREA AVAILABLE, A1 to A5		Design	External	Mapnc
Area Required	Ar	4.703	NA	NA
Area in Shell	A1	5.000	NA	NA
Area in Nozzle Wall	A2	2.209	NA	NA
Area in Inward Nozzle	A3	0.000	NA	NA
Area in Welds	A41+A42+A43	3.186	NA	NA
Area in Element	A5	13.708	NA	NA
TOTAL AREA AVAILABLE	Atot	24.103	NA	NA

The Internal Pressure Case Governs the Analysis.

Nozzle Angle Used in Area Calculations

90.00 degs.

The area available without a pad is Sufficient.

The area available with the given pad is Sufficient.

Area Required [A]:

$$\begin{aligned}
 &= (d \cdot tr \cdot F + 2 \cdot tn \cdot tr \cdot F \cdot (1 - fr1)) \text{ UG-37(c)} \\
 &= (152.6794 \cdot 3.0802 \cdot 1.0 + 2 \cdot 7.7978 \cdot 3.0802 \cdot 1.0 \cdot (1 - 1.0)) \\
 &= 4.703 \text{ cm}^2
 \end{aligned}$$

Reinforcement Areas per Figure UG-37.1

Area Available in Shell [A1]:

$$\begin{aligned}
 &= d(E1 \cdot t - F \cdot tr) - 2 \cdot tn(E1 \cdot t - F \cdot tr) \cdot (1 - fr1) \\
 &= 152.679(1.0 \cdot 6.355 - 1.0 \cdot 3.08) - 2 \cdot 7.798 \\
 &\quad (1.0 \cdot 6.355 - 1.0 \cdot 3.0802) \cdot (1 - 1.0) \\
 &= 5.000 \text{ cm}^2
 \end{aligned}$$

Area Available in Nozzle Wall Projecting Outward [A2]:

$$\begin{aligned}
 &= (2 \cdot Tlwp) \cdot (tn - trn) \cdot fr2 \\
 &= (2 \cdot 15.89) \cdot (7.8 - 0.85) \cdot 1.0
 \end{aligned}$$



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 147 of 173

Nozzle Calcs.: N2- Channel out Nozl: 12 9:52am Aug 12,2026

= 2.209 cm²

Area Available in Welds [A41 + A42 + A43]:

= (Wo² - Ar Lost)•Fr3+((Wi-can/0.707)² - Ar Lost)•fr2 + Wp²•fr4

= (3.1859) • 1.0 + (0.0) • 1.0 + 0.0² • 1.0

= 3.186 cm²

Area Available in Element [A5]:

= (min(Dp,DL)-(Nozzle OD))•(min(tp,Tlwp,te)) • fr4

= (305.3588 - 168.275) • 10.0 • 1.0

= 13.708 cm²

UG-45 Minimum Nozzle Neck Thickness Requirement: [Int. Press.]

Wall Thickness for Internal/External pressures ta = 4.0212 mm

Wall Thickness per UG16(b), tr16b = 5.6750 mm

Wall Thickness, shell/head, internal pressure trb1 = 6.2552 mm

Wall Thickness tb1 = max(trb1, tr16b) = 6.2552 mm

Wall Thickness tb2 = max(trb2, tr16b) = 5.6750 mm

Wall Thickness per table UG-45 tb3 = 9.3950 mm

Determine Nozzle Thickness candidate [tb]:

= min[tb3, max(tb1,tb2)]

= min[9.395, max(6.2552, 5.675)]

= 6.2552 mm

Minimum Wall Thickness of Nozzle Necks [tUG-45]:

= max(ta, tb)

= max(4.0212, 6.2552)

= 6.2552 mm

Available Nozzle Neck Thickness = 0.875 * 10.973 = 9.601 mm -> OK

Stresses on Nozzle due to External and Pressure Loads per the ASME B31.3 Piping Code, (see 319.4.4 and 302.3.5):

Sustained : 4.6, Allowable : 118.0 N./mm² Passed

Expansion : 0.0, Allowable : 290.4 N./mm² Passed

Occasional : 5.5, Allowable : 156.9 N./mm² Passed

Shear : 4.6, Allowable : 82.6 N./mm² Passed

The number of cycles on this nozzle was assumed to be 7000 or less for the determination of the expansion stress allowable.

Nozzle Junction Minimum Design Metal Temperature (MDMT) Calculations:

Nozzle Neck to Flange Weld, min(Curve:B, Curve:A)

Govrn. thk, tg = 9.601, tr = 0.846, c = 3.175 mm, E* = 1.0

Thickness Ratio = tr * E*/(tg - c) = 0.132, Temp. Reduction = 78 °C

Min Metal Temp. w/o impact per UCS-66, Curve A -8 °C

Min Metal Temp. at Required thickness (UCS 66.1) -104 °C

Min Metal Temp. w/o impact per UG-20(f) -29 °C

Nozzle Neck to Pad Weld for the Nozzle, Curve: B

Govrn. thk, tg = 9.601, tr = 0.846, c = 3.175 mm, E* = 1.0

Thickness Ratio = tr * E*/(tg - c) = 0.132, Temp. Reduction = 78 °C

Min Metal Temp. w/o impact per UCS-66, Curve B -29 °C

Min Metal Temp. at Required thickness (UCS 66.1) -104 °C

Nozzle Neck to Pad Weld for Reinforcement pad, Curve: B

Govrn. thk, tg = 9.601, tr = 0.846, c = 3.175 mm, E* = 1.0



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 148 of 173

Nozzle Calcs.: N2- Channel out Nozl: 12 9:52am Aug 12,2026

Thickness Ratio = $tr * E^* / (tg - c) = 0.132$, Temp. Reduction = 78 °C

Min Metal Temp. w/o impact per UCS-66, Curve B -29 °C
Min Metal Temp. at Required thickness (UCS 66.1) -104 °C

Shell to Pad Weld Junction at Pad OD, Curve: B

Govrn. thk, $tg = 9.53$, $tr = 3.08$, $c = 3.175$ mm, $E^* = 1.0$
Thickness Ratio = $tr * E^* / (tg - c) = 0.485$, Temp. Reduction = 34 °C

Min Metal Temp. w/o impact per UCS-66, Curve B -29 °C
Min Metal Temp. at Required thickness (UCS 66.1) -48 °C

Nozzle-Shell/Head Weld (UCS-66(a)(b)), Curve: B

Govrn. thk, $tg = 9.53$, $tr = 3.08$, $c = 3.175$ mm, $E^* = 1.0$
Thickness Ratio = $tr * E^* / (tg - c) = 0.485$, Temp. Reduction = 34 °C

Min Metal Temp. w/o impact per UCS-66, Curve B -29 °C
Min Metal Temp. at Required thickness (UCS 66.1) -48 °C

Gov. MDMT of the Nozzle : -48 °C
Gov. MDMT of the Reinforcement Pad : -48 °C
Gov. MDMT of the nozzle to shell joint welded assembly : -48 °C

Flange MDMT including Temperature reduction per UCS-66.1:

Unadjusted MDMT of ASME B16.5/47 flanges per UCS-66(c) -18 °C
Flange MDMT with Temp reduction per UCS-66(b)(1)(-b) -40 °C

Where the Stress Reduction Ratio per UCS-66(b)(1)(-b) is :
Design Pressure/Ambient Rating = $1191.50 / 1960.01 = 0.608$

Weld Size Calculations, Description: N2- Channel out

Intermediate Calc. for nozzle/shell Welds T_{min} 7.7978 mm
Intermediate Calc. for pad/shell Welds T_{minPad} 6.3550 mm

Results Per UW-16.1:

	Required Thickness	Actual Thickness
Nozzle Weld	$5.4585 = 0.7 * t_{min}$	$21.2100 = 0.7 * W_o$ mm
Pad Weld	$3.1775 = 0.5 * T_{minPad}$	$5.6560 = 0.7 * W_p$ mm

Weld Strength and Weld Loads per UG-41.1, Sketch (a) or (b)

Weld Load [W]:
= $\max(0, (A - A1 + 2 \cdot tn \cdot fr1 \cdot (E1 \cdot t - tr)) \cdot Sv)$
= $\max(0, (4.7028 - 5.0 + 2 \cdot 7.7978 \cdot 1.0 \cdot (1.0 \cdot 6.355 - 3.0802)) \cdot 118)$
= 256.99 Kgf

Note: F is always set to 1.0 throughout the calculation.

Weld Load [W1]:
= $(A2 + A5 + A4 - (Wi - Can / .707)^2 \cdot fr2) \cdot Sv$
= $(2.2089 + 13.7084 + 3.1859 - 0.0 \cdot 1.0) \cdot 118$
= 22985.28 Kgf

Weld Load [W2]:
= $(A2 + A3 + A4 + (2 \cdot tn \cdot t \cdot fr1)) \cdot Sv$
= $(2.2089 + 0.0 + 7.0084 + (0.9911)) \cdot 118$
= 12282.89 Kgf

Weld Load [W3]:
= $(A2 + A3 + A4 + A5 + (2 \cdot tn \cdot t \cdot fr1)) \cdot S$



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 149 of 173

Nozzle Calcs.: N2- Channel out Nozl: 12 9:52am Aug 12,2026

$$= (2.2089 + 0.0 + 3.1859 + 13.7084 + (0.9911)) \cdot 118$$

$$= 24177.79 \text{ Kgf}$$

Strength of Connection Elements for Failure Path Analysis

Shear, Outward Nozzle Weld [Sonw]:

$$= (\pi/2) \cdot Dlo \cdot Wo \cdot 0.49 \cdot Snw$$

$$= (3.1416/2.0) \cdot 168.275 \cdot 30.0 \cdot 0.49 \cdot 118$$

$$= 46752. \text{ Kgf}$$

Shear, Pad Element Weld [Spew]:

$$= (\pi/2) \cdot DP \cdot WP \cdot 0.49 \cdot SEW$$

$$= (3.1416/2.0) \cdot 308.275 \cdot 8.0 \cdot 0.49 \cdot 118$$

$$= 22840. \text{ Kgf}$$

Shear, Nozzle Wall [Snw]:

$$= (\pi \cdot (Dlr + Dlo)/4) \cdot (Thk - Can) \cdot 0.7 \cdot Sn$$

$$= (3.1416 \cdot 80.2386) \cdot (10.9728 - 3.175) \cdot 0.7 \cdot 118$$

$$= 16556. \text{ Kgf}$$

Tension, Pad Groove Weld [Tpgw]:

$$= (\pi/2) \cdot Dlo \cdot Wgpn \cdot 0.74 \cdot Seg$$

$$= (3.1416/2) \cdot 168.275 \cdot 10.0 \cdot 0.74 \cdot 138$$

$$= 27524. \text{ Kgf}$$

Tension, Shell Groove Weld [Tngw]:

$$= (\pi/2) \cdot Dlo \cdot (T - cas) \cdot 0.74 \cdot Sng$$

$$= (3.1416/2.0) \cdot 168.275 \cdot (9.53 - 3.175) \cdot 0.74 \cdot 118$$

$$= 14957. \text{ Kgf}$$

See UG-41 and UW-15 for clarification of allowable stresses.

Strength of Failure Paths:

Failure Path [Path 1-1]:

$$= (SPEW + SNW) = (22840 + 16556) = 39395 \text{ Kgf}$$

Failure Path [Path 2-2]:

$$= (Sonw + Tpgw + Tngw + Sinw)$$

$$= (46752 + 27524 + 14957 + 0) = 89233 \text{ Kgf}$$

Failure Path [Path 3-3]:

$$= (Spew + Tngw + Sinw)$$

$$= (22840 + 14957 + 0) = 37796 \text{ Kgf}$$

Summary of Failure Path Calculations:

Path 1-1 = 39395	Kgf, must exceed W = 256 Kgf	or W1 = 22985 Kgf
Path 2-2 = 89232	Kgf, must exceed W = 256 Kgf	or W2 = 12282 Kgf
Path 3-3 = 37796	Kgf, must exceed W = 256 Kgf	or W3 = 24177 Kgf

Maximum Allowable Pressure for this Nozzle at this Location:

Converged Maximum Allowable Pressure in the Operating case: 2437 KPa.

Note: The MAWP of this junction was limited by the parent Shell/Head.

The Drop for this Nozzle is : 12.0402 mm

The Cut Length for this Nozzle is, Drop + Ho + H + T : 271.5701 mm

Input Echo, WRC297 Item 1, Description: N2- Channel ou:

Diameter Basis for Cylindrical Shell	ID
Shell Internal Corrosion Allowance	3.1750 mm
Shell External Corrosion Allowance	0.0000 mm
Shell Diameter	600.000 mm
Shell Thickness	9.5300 mm



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 150 of 173

Nozzle Calcs.: N2- Channel out Nozl: 12 9:52am Aug 12,2026

Shell Stress Concentration Factor		1.000	
Vessel Material		SA-106 B	
Vessel Cold S.I. Allowable	Smc	118.00	N./mm ²
Vessel Hot S.I. Allowable	Smh	118.00	N./mm ²

See ASME VIII Div. 2, 4.1.6.3, for determination of the SPS allowable.

Diameter Basis for Nozzle		OD	
Nozzle Corrosion Allowance		3.1750	mm
Nozzle Diameter		168.275	mm
Nozzle Thickness		10.9728	mm
Nozzle Stress Concentration Factor		1.000	
Nozzle Material		SA-106 B	
Nozzle Cold S.I. Allowable	SNmc	118.00	N./mm ²
Nozzle Hot S.I. Allowable	SNmh	118.00	N./mm ²

See ASME VIII Div. 2, 4.1.6.3, for determination of the SPS allowable.

Diameter of Reinforcing Pad	308.275	mm
Thickness of Reinforcing Pad	10.0000	mm

Note:

External Forces and Moments in WRC 107/537 Convention:

These loads are assumed to be SUSained loads.

Design Internal Pressure	Dp	1191.50	KPa.
Radial Load	P	-407.91	Kgf
Circumferential Shear	Vc	611.87	Kgf
Longitudinal Shear	Vl	611.87	Kgf
Circumferential Moment	Mc	0.28	Kg-m.
Longitudinal Moment	Ml	0.37	Kg-m.
Torsional Moment	Mt	0.46	Kg-m.

Include Axial Pressure Thrust	No
Include Pressure Stress Indices per Div. 2	No
Local Loads applied at end of Nozzle/Attachment	No

Stress Computations at the Edge of the Nozzle:

Stress Attenuation Diameter (for Insert Plates) per WRC 297:

$$= \text{NozzleOD} + 2 \cdot 1.65 \cdot \sqrt{(R_{\text{mean}}(t - ca))}$$

$$= 168.275 + 2 \cdot 1.65 \cdot \sqrt{(311.353(9.53 - 3.175))}$$

$$= 315.065 \text{ mm}$$

WRC 297 Curve Access Parameters:

Vessel Mean Diameter	(D) =	622.705	mm
Nozzle Outside Diameter	(d) =	168.275	mm
Vessel Thickness used	(T) =	16.355	mm
Nozzle Thickness used	(t) =	7.798	mm
T / t	=	2.097	
d / t	=	21.580	

$$\lambda = [(d/D) \cdot \sqrt{(D/T)}] = 1.667$$

Nr/P	=	0.077
Mr/P	=	0.087
M0/P	=	0.053
N0/P	=	0.154
MrD/Mc	=	0.196
NrDL/Mc	=	0.131
M0d/Mc	=	0.142



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 151 of 173

Nozzle Calcs.: N2- Channel out

Nozl: 12 9:52am Aug 12,2026

NØDL/Mc = 0.151
MrD/Ml = 0.134
NrDL/Ml = 0.085
MØD/Ml = 0.093
NØDL/Ml = 0.266

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Stresses Normal to longitudinal plane)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Outplane Membrane (P)	2	2	2	2
Outplane Bending (P)	4	-4	4	-4
Outplane Membrane (Mc)	0	0	0	0
Outplane Bending (Mc)	0	0	0	0
Outplane Membrane (ML)	0	0	0	0
Outplane Bending (ML)	0	0	0	0
Normal Pressure Stress	21	22	21	22
Outplane Stress Summary	28	20	28	20

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Stresses parallel to longitudinal plane)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Inplane Membrane (P)	1	1	1	1
Inplane Bending (P)	7	-7	7	-7
Inplane Membrane (Mc)	0	0	0	0
Inplane Bending (Mc)	0	0	0	0
Inplane Membrane (ML)	0	0	0	0
Inplane Bending (ML)	0	0	0	0
Inplane Pressure Stress	10	10	10	10
Inplane Stress Summary	19	4	19	4

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Shear stress normal to longitudinal plane)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Outplane Shear (Vc)	1	1	-1	-1
Outplane Shear (Vl)	0	0	0	0
Outplane Shear (Mt)	0	0	0	0
Shear Stress Summary	1	1	-1	-1

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Stress Intensities)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Two * Max Shear Stress	28	20	28	20

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Stresses Normal to circumferential plane)	Cu Left Outside	Cl Left Inside	Du Right Outside	Dl Right Inside
Outplane Membrane (P)	2	2	2	2
Outplane Bending (P)	4	-4	4	-4
Outplane Membrane (Mc)	0	0	0	0
Outplane Bending (Mc)	0	0	0	0
Outplane Membrane (ML)	0	0	0	0
Outplane Bending (ML)	0	0	0	0



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 152 of 173

Nozzle Calcs.: N2- Channel out Nozl: 12 9:52am Aug 12,2026

Normal Pressure Stress	10	10	10	10
------------------------	----	----	----	----

Outplane Stress Summary	17	8	17	8
-------------------------	----	---	----	---

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Stresses parallel to circumferential plane)	Cu Left Outside	Cl Left Inside	Du Right Outside	Dl Right Inside
--	-----------------------	----------------------	------------------------	-----------------------

Inplane Membrane (P)	1	1	1	1
Inplane Bending (P)	7	-7	7	-7
Inplane Membrane (Mc)	0	0	0	0
Inplane Bending (Mc)	0	0	0	0
Inplane Membrane (ML)	0	0	0	0
Inplane Bending (ML)	0	0	0	0
Inplane Pressure Stress	21	22	21	22

Inplane Stress Summary	30	16	30	15
------------------------	----	----	----	----

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Shear stress normal to circumferential plane)	Cu Left Outside	Cl Left Inside	Du Right Outside	Dl Right Inside
--	-----------------------	----------------------	------------------------	-----------------------

Outplane Shear (Vc)	0	0	0	0
Outplane Shear (Vl)	-1	-1	1	1
Torsional Shear (Mt)	0	0	0	0

Shear Stress Summary	-1	-1	1	1
----------------------	----	----	---	---

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Stress Intensities)	Cu Left Outside	Cl Left Inside	Du Right Outside	Dl Right Inside
---	-----------------------	----------------------	------------------------	-----------------------

Two * Max Shear Stress	30	16	30	16
------------------------	----	----	----	----

Nozzle Stresses (N./mm²):

LONGITUDINAL PLANE (Stresses in the hoop direction)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
---	----------------------	---------------------	-------------------------	------------------------

Hoop Membrane (P)	2	2	2	2
Hoop Bending (P)	0	0	0	0
Hoop Membrane (Mc)	0	0	0	0
Hoop Bending (Mc)	0	0	0	0
Hoop Membrane (ML)	0	0	0	0
Hoop Bending (ML)	0	0	0	0
Hoop Pressure Stress	13	14	13	14

Hoop Stress Summary	15	17	15	17
---------------------	----	----	----	----

Nozzle Stresses (N./mm²):

LONGITUDINAL PLANE (Stresses Normal to pipe cross-section)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
--	----------------------	---------------------	-------------------------	------------------------

Axial Membrane (P)	1	1	1	1
Axial Bending (P)	19	-19	19	-19
Axial Membrane (Mc)	0	0	0	0
Axial Bending (Mc)	0	0	0	0
Axial Membrane (ML)	0	0	0	0
Axial Bending (ML)	0	0	0	0
Axial Pressure Stress	6	6	6	6



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 153 of 173

Nozzle Calcs.: N2- Channel out Nozl: 12 9:52am Aug 12,2026

Axial Stress Summary	26	-11	27	-11
----------------------	----	-----	----	-----

Nozzle Stresses (N./mm²):

LONGITUDINAL PLANE	Au	Al	Bu	B1
(Shear stress)	Outside	Inside	Outside	Inside

Shear due to (Vc)	2	2	-2	-2
Shear due to (Vl)	0	0	0	0
Shear due to Torsion	0	0	0	0

Shear Stress Summary	2	2	-2	-2
----------------------	---	---	----	----

Nozzle Stresses (N./mm²):

LONGITUDINAL PLANE	Au	Al	Bu	B1
(Stress Intensities	Outside	Inside	Outside	Inside

Two * Max Shear Stress	27	28	27	29
------------------------	----	----	----	----

Nozzle Stresses (N./mm²):

CIRCUMFERENTIAL PLANE	Cu	Cl	Du	D1
(Stresses in the	Left	Left	Right	Right
hoop direction)	Outside	Inside	Outside	Inside

Hoop Membrane (P)	2	2	2	2
Hoop Bending (P)	0	0	0	0
Hoop Membrane (Mc)	0	0	0	0
Hoop Bending (Mc)	0	0	0	0
Hoop Membrane (ML)	0	0	0	0
Hoop Bending (ML)	0	0	0	0
Hoop Pressure Stress	13	14	13	14

Hoop Stress Summary	15	17	15	17
---------------------	----	----	----	----

Nozzle Stresses (N./mm²):

CIRCUMFERENTIAL PLANE	Cu	Cl	Du	D1
(Stresses Normal to	Left	Left	Right	Right
pipe cross-section)	Outside	Inside	Outside	Inside

Axial Membrane (P)	1	1	1	1
Axial Bending (P)	19	-19	19	-19
Axial Membrane (Mc)	0	0	0	0
Axial Bending (Mc)	0	0	0	0
Axial Membrane (ML)	0	0	0	0
Axial Bending (ML)	0	0	0	0
Axial Pressure Stress	6	6	6	6

Axial Stress Summary	26	-11	27	-11
----------------------	----	-----	----	-----

Nozzle Stresses (N./mm²):

CIRCUMFERENTIAL PLANE	Cu	Cl	Du	D1
(Shear stress)	Outside	Inside	Outside	Inside

Shear due to (Vc)	0	0	0	0
Shear due to (Vl)	-2	-2	2	2
Shear due to Torsion	0	0	0	0

Shear Stress Summary	-2	-2	2	2
----------------------	----	----	---	---

Nozzle Stresses (N./mm²):

CIRCUMFERENTIAL PLANE	Cu	Cl	Du	D1
(Stress Intensities	Outside	Inside	Outside	Inside

Two * Max Shear Stress	27	28	27	29
------------------------	----	----	----	----



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 154 of 173

Nozzle Calcs.: N2- Channel out

Nozl: 12 9:52am Aug 12,2026

Stress Computations at the Edge of the Reinforcing Pad:

Stress Attenuation Diameter (for Insert Plates) per WRC 297:

$$= \text{NozzleOD} + 2 \cdot 1.65 \cdot \sqrt{R_{\text{mean}}(t - ca)}$$

$$= 168.275 + 2 \cdot 1.65 \cdot \sqrt{306.352(9.53 - 3.175)}$$

$$= 313.882 \text{ mm}$$

WRC 297 Curve Access Parameters:

Vessel Mean Diameter (D) = 612.705 mm
 Nozzle Outside Diameter (d) = 308.275 mm
 Vessel Thickness used (T) = 6.355 mm
 Nozzle Thickness used (t) = 77.798 mm
 T / t = 0.082
 d / t = 10.000

$$\lambda = [(d/D) \cdot \sqrt{(D/T)}] = 4.940$$

Note: Re-pad thickness is added to nozzle thickness to simulate the Re-pad.

Nr/P = 0.045
 Mr/P = 0.071
 M0/P = 0.020
 N0/P = 0.027
 MrD/Mc = 0.241
 NrDL/Mc = 0.099
 M0d/Mc = 0.072
 N0DL/Mc = 0.053
 MrD/M1 = 0.050
 NrDL/M1 = 0.048
 M0D/M1 = 0.015
 N0DL/M1 = 0.027

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Stresses Normal to longitudinal plane)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Outplane Membrane (P)	2	2	2	2
Outplane Bending (P)	11	-11	11	-11
Outplane Membrane (Mc)	0	0	0	0
Outplane Bending (Mc)	0	0	0	0
Outplane Membrane (ML)	0	0	0	0
Outplane Bending (ML)	0	0	0	0
Normal Pressure Stress	56	57	56	57
Outplane Stress Summary	70	48	70	48

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Stresses parallel to longitudinal plane)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Inplane Membrane (P)	4	4	4	4
Inplane Bending (P)	41	-41	41	-41
Inplane Membrane (Mc)	0	0	0	0
Inplane Bending (Mc)	0	0	0	0
Inplane Membrane (ML)	0	0	0	0
Inplane Bending (ML)	0	0	0	0
Inplane Pressure Stress	28	28	28	28
Inplane Stress Summary	74	-9	74	-9

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE	Au	Al	Bu	Bl
--------------------	----	----	----	----



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 155 of 173

Nozzle Calcs.: N2- Channel out Nozl: 12 9:52am Aug 12,2026

(Shear stress normal to longitudinal plane)			Top Outside	Top Inside	Bottom Outside	Bottom Inside
Outplane Shear (Vc)			1	1	-1	-1
Outplane Shear (Vl)			0	0	0	0
Outplane Shear (Mt)			0	0	0	0
Shear Stress Summary			1	1	-1	-1

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Stress Intensities)		Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Two * Max Shear Stress		75	57	75	57

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Stresses Normal to circumferential plane)		Cu Left Outside	Cl Left Inside	Du Right Outside	Dl Right Inside
Outplane Membrane (P)		2	2	2	2
Outplane Bending (P)		11	-11	11	-11
Outplane Membrane (Mc)		0	0	0	0
Outplane Bending (Mc)		0	0	0	0
Outplane Membrane (ML)		0	0	0	0
Outplane Bending (ML)		0	0	0	0
Normal Pressure Stress		28	28	28	28
Outplane Stress Summary		42	19	42	19

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Stresses parallel to circumferential plane)		Cu Left Outside	Cl Left Inside	Du Right Outside	Dl Right Inside
Inplane Membrane (P)		4	4	4	4
Inplane Bending (P)		41	-41	41	-41
Inplane Membrane (Mc)		0	0	0	0
Inplane Bending (Mc)		0	0	0	0
Inplane Membrane (ML)		0	0	0	0
Inplane Bending (ML)		0	0	0	0
Inplane Pressure Stress		56	57	56	57
Inplane Stress Summary		102	20	102	19

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Shear stress normal to circumferential plane)		Cu Left Outside	Cl Left Inside	Du Right Outside	Dl Right Inside
Outplane Shear (Vc)		0	0	0	0
Outplane Shear (Vl)		-1	-1	1	1
Torsional Shear (Mt)		0	0	0	0
Shear Stress Summary		-1	-1	1	1

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Stress Intensities)		Cu Left Outside	Cl Left Inside	Du Right Outside	Dl Right Inside
Two * Max Shear Stress		102	21	103	21



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 156 of 173

Nozzle Calcs.: N2- Channel out

Nozl: 12 9:52am Aug 12,2026

WRC 297 Stress Summations per ASME Sec. VIII Div. 2:

Vessel Stress Summation at Vessel-Nozzle Junction (N./mm²):

Type of Stress Int. Location	Stress Values at							
	Au	Al	Bu	Bl	Cu	Cl	Du	Dl
Circ. Pm (SUS)	21	22	21	22	21	22	21	22
Circ. Pl (SUS)	2	2	2	2	1	1	1	1
Circ. Q (SUS)	4	-4	4	-4	7	-7	7	-7
Long. Pm (SUS)	10	10	10	10	10	10	10	10
Long. Pl (SUS)	1	1	1	1	2	2	2	2
Long. Q (SUS)	7	-7	7	-7	4	-4	4	-4
Shear Pm (SUS)	0	0	0	0	0	0	0	0
Shear Pl (SUS)	1	1	-1	-1	-1	-1	1	1
Shear Q (SUS)	0	0	0	0	0	0	0	0
Pm (SUS)	21.0	22.0	21.0	22.0	21.0	22.0	21.0	22.0
Pm+Pl (SUS)	23.1	24.1	23.1	24.1	22.1	23.1	22.1	23.1
Pm+Pl+Q (Total)	27.1	20.1	27.1	20.1	29.1	16.1	29.1	16.1

Vessel Stress Summation Comparison (N./mm²):

Type of Stress Int.	Max. S.I.	S.I. Allowable	Result
Pm (SUS)	22.00	118.00	Passed
Pm+Pl (SUS)	24.08	177.00	Passed
Pm+Pl+Q (TOTAL)	29.08	353.99	Passed

Because only sustained loads were specified, the Pm+Pl+Q allowable was 3 * Smh.

WRC 297 Stress Summations per ASME Sec. VIII Div. 2:

Vessel Stress Summation at Reinforcing Pad Edge (N./mm²):

Type of Stress Int. Location	Stress Values at							
	Au	Al	Bu	Bl	Cu	Cl	Du	Dl
Circ. Pm (SUS)	56	57	56	57	56	57	56	57
Circ. Pl (SUS)	2	2	2	2	4	4	4	4
Circ. Q (SUS)	11	-11	11	-11	41	-41	41	-41
Long. Pm (SUS)	28	28	28	28	28	28	28	28
Long. Pl (SUS)	4	4	4	4	2	2	2	2
Long. Q (SUS)	41	-41	41	-41	11	-11	11	-11
Shear Pm (SUS)	0	0	0	0	0	0	0	0
Shear Pl (SUS)	1	1	-1	-1	-1	-1	1	1
Shear Q (SUS)	0	0	0	0	0	0	0	0
Pm (SUS)	56.0	57.0	56.0	57.0	56.0	57.0	56.0	57.0
Pm+Pl (SUS)	58.0	59.0	58.0	59.0	60.0	61.0	60.0	61.0
Pm+Pl+Q (Total)	73.2	57.0	73.2	57.0	101.0	20.6	101.0	20.6

Vessel Stress Summation Comparison (N./mm²):



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 157 of 173

Nozzle Calcs.: N2- Channel out

Nozl: 12

9:52am Aug 12,2026

Type of Stress Int.	Max. S.I.	S.I. Allowable	Result
Pm (SUS)	57.00	118.00	Passed
Pm+Pl (SUS)	61.03	177.00	Passed
Pm+Pl+Q (TOTAL)	101.02	353.99	Passed

Because only sustained loads were specified, the Pm+Pl+Q allowable was 3 * Smh.

WRC 297 Stress Summations per ASME Sec. VIII Div. 2:

Nozzle Stress Summation at Vessel-Nozzle Junction (N./mm²):

Type of Stress Int. Location	Stress Values at							
	Au	Al	Bu	Bl	Cu	Cl	Du	Dl
Circ. Pm (SUS)	13	14	13	14	13	14	13	14
Circ. Pl (SUS)	2	2	2	2	2	2	2	2
Circ. Q (SUS)	0	0	0	0	0	0	0	0
Long. Pm (SUS)	6	6	6	6	6	6	6	6
Long. Pl (SUS)	1	1	1	1	1	1	1	1
Long. Q (SUS)	19	-19	19	-19	19	-19	19	-19
Shear Pm (SUS)	0	0	0	0	0	0	0	0
Shear Pl (SUS)	2	2	-2	-2	-2	-2	2	2
Shear Q (SUS)	0	0	0	0	0	0	0	0
Pm (SUS)	13.0	14.0	13.0	14.0	13.0	14.0	13.0	14.0
Pm+Pl (SUS)	15.5	16.4	15.5	16.4	15.5	16.4	15.5	16.4
Pm+Pl+Q (Total)	26.4	28.3	26.4	28.3	26.4	28.3	26.4	28.3

Nozzle Stress Summation Comparison (N./mm²):

Type of Stress Int.	Max. S.I.	S.I. Allowable	Result
Pm (SUS)	14.00	118.00	Passed
Pm+Pl (SUS)	16.42	177.00	Passed
Pm+Pl+Q (TOTAL)	28.28	353.99	Passed

Because only sustained loads were specified, the Pm+Pl+Q allowable was 3 * Smh.

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 158 of 173

ASME TS Calc: DESIGN CASE

Case: 1 9:52a Aug 12, 2026

Input Echo, Tubesheet Number 1, Description: Fixed tubesheet

Shell Data:

Main Shell Description: Shell

Shell Maximum Design Pressure	Psd,max	1549.50 KPa.
Shell Maximum Operating Pressure	Psox,max	1549.50 KPa.
Shell Minimum Operating Pressure	Psox,min	0.00 KPa.
Shell Thickness	ts	9.5300 mm
Shell Internal Corrosion Allowance	cas	3.1750 mm
Shell External Corrosion Allowance	casext	0.0000 mm
Inside Diameter of Shell	Ds	600.000 mm
Shell Circumferential Joint Efficiency	Esw	1.000
Shell Temperature for Internal Pressure	Ts	165.56 °C
Shell Material		SA-106 B

See ASME VIII Div. 1, UG-23(e), for determination of the SPS allowable.

Shell Material UNS Number		K03006
Shell Allowable Stress at Temperature	Ss	118.00 N./mm ²
Shell Allowable Stress at Ambient		118.00 N./mm ²

Channel Data:

Channel Description: Chnl. rear

Channel Type:		Cylinder
Channel Maximum Design Pressure	Ptd,max	1191.50 KPa.
Channel Maximum Operating Pressure	Ptox,max	1191.50 KPa.
Channel Minimum Operating Pressure	Ptox,min	0.00 KPa.
Channel Thickness	tc	9.5300 mm
Channel Internal Corrosion Allowance	cac	3.1750 mm
Channel External Corrosion Allowance	cacext	0.0000 mm
Inside Diameter of Channel	Dc	600.000 mm
Channel Design Temperature	TEMPC	76.67 °C
Channel Flange Matl		SA-106 B

See ASME VIII Div. 1, UG-23(e), for determination of the SPS allowable.

Channel Material UNS Number		K03006
Channel Allowable Stress at Temperature	Sc	118.00 N./mm ²
Channel Allowable Stress at Ambient		118.00 N./mm ²

Tube Data:

Number of Tube Holes	Nt	534
Tube Wall Thickness	et	2.1080 mm
Tube Outside Diameter	D	15.8750 mm
Total Straight Tube Length	Lt	4877.00 mm
Straight Tube Length (bet. inner tubsht faces) L		4773.00 mm
Design Temperature of the Tubes		165.56 °C
Tube Material		SA-179
Tube Material UNS Number		K01200
Is this a Welded Tube		No
Tube Material Specification used	Smls. tube	
Tube Allowable Stress at Temperature		92.40 N./mm ²
Tube Allowable Stress At Ambient		92.40 N./mm ²
Tube Yield Stress At design Temperature	Syt	156.75 N./mm ²
Tube Pitch (Center to Center Spacing)	P	19.8440 mm
Tube Layout Pattern		Triangular
Fillet Weld Leg	af	2.0000 mm
Groove Weld Leg	ag	2.0000 mm
Tube-Tubesheet Joint Weld Type		Full Strength
Method for Tube-Tubesheet Jt. Allowable		UW-20.3
Is the Tube Inset		No
Radius to Outermost Tube Hole Center	ro	284.388 mm



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 159 of 173

ASME TS Calc: DESIGN CASE

Case: 1 9:52a Aug 12, 2026

Largest Center-to-Center Tube Distance	U1	0.0000 mm
Length of Expanded Portion of Tube	ltx	0.0000 mm
Tube-side pass partition groove depth	hg	0.0000 mm
Area of Tube Layout	Ap	1676.2 cm ²
Perimeter of Tube Layout	Cp	1676.1 mm

Tubesheet Data:

Tubesheet TYPE: Fixed Tubesheet Exchanger, Conf B

Tubesheet Design Metal Temperature	T	165.56 °C
Tubesheet Material		SA-266 2

See ASME VIII Div. 1, UG-23(e), for determination of the SPS allowable.

Tubesheet Material UNS Number		K03506
Tubesheet Allowable Stress at Temperature	S	138.00 N./mm ²
Tubesheet Allowable Stress at Ambient	Tt	138.00 N./mm ²
Thickness of Tubesheet	h	52.0000 mm
Tubesheet Corr. Allowance (Shell side)	Cats	3.1750 mm
Tubesheet Corr. Allowance (Channel side)	Catc	3.1750 mm
Tubesheet Outside Diameter	A	740.000 mm

Additional Data for Stepped Tubesheets:

Is the Tubesheet Stepped?		Yes
Is the Tubesheet Flat on Tubeside?		No
Step 1 Diameter on the Tubeside	dt1	663.00 mm
Step 1 Depth on the Tubeside	ht1	8.00 mm
Step 2 Diameter on the Tubeside	dt2	597.00 mm
Step 2 Depth on the Tubeside	ht2	8.00 mm
Is the Tubesheet Flat on Shellside?		No
Calculated Tubesheet Diameter per Div 2, 4.18.4		663.00 mm

Note: Tubesheet diameter is now: 663.000 mm Div 2, 4.18.4.

Area of the Untubed Lanes	AL	0.0 cm ²
---------------------------	----	---------------------

Additional Data for Fixed/Floating Tubesheet Exchangers:

Unsupported Tube Span under consideration	l	0.000 mm
Tube End condition corresponding to Span (l)	k	0.00
Ignore Radial Thermal Exp. effects (4.18.8/4.18.9)		Yes
Perform Differential Pressure Design		No
Run Multiple Load Cases		Yes
Mean Shell Metal Temp. along Shell len.	Tsm	70.70 °C
Mean Tube Metal Temp. along Tube length	Ttm	49.64 °C
Junction Stress Reduction option		Perform Plastic Calculation

Additional Data for Gasketed Tubesheets:

Tubesheet Gasket on which Side		Channel
Flange Outside Diameter	A	740.000 mm
Flange Inside Diameter	B	600.000 mm
Flange Face Outside Diameter	Fod	666.000 mm
Flange Face Inside Diameter	Fid	600.000 mm
Gasket Outside Diameter	Go	655.000 mm
Gasket Inside Diameter	Gi	629.000 mm
Small end Hub thk.	g0	9.5300 mm
Large end Hub thk.	g1	13.0000 mm
Gasket Factor,	m	3.00
Gasket Design Seating Stress	y	68.95 N./mm ²
Flange Facing Sketch		Code Sketch 1a
Gasket Thickness	tg	4.5000 mm
Full face Gasket Flange Option		Program Selects



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 160 of 173

ASME TS Calc: DESIGN CASE

Case: 1 9:52a Aug 12, 2026


Bolting Information:

Diameter of Bolt Circle	C	690.000 mm
Nominal Bolt Diameter	dB	19.0500 mm
Thread Series	TEMA Thread Series	
Number of Bolts	n	28
Bolt Material	SA-193 B7	
Bolt Allowable Stress At Temperature	Sb	172.00 N./mm ²
Bolt Allowable Stress At Ambient	Sa	172.00 N./mm ²
Weld between Flange and Shell/Channel		0.0000 mm

Tubesheet Integral with	Shell	
Tubesheet Extended as Flange	Yes	
Thickness of Extended Portion of Tubesheet	Tf	36.0000 mm
Is Bolt Load Transferred to the Tubesheet	Yes	

Is Exchanger in Creep range (skip EP, Use 3S for Sps) No

Tubesheet Integral w/Shell, Gasketed w/Channel, Extended as a Flange



Configuration b:

Messages regarding the Tubesheet & Exchanger Input Data:

Warning - Tube end condition k should be bet 0 - 1 (.00).

ASME TubeSheet Results per Part UHX/4.18, 2025

Elasticity/Expansion Material Properties:

Shell - TE-1 Carbon & Low Alloy Steels, Group 1
Shell - TM-1 Carbon Steels with C<= 0.3%

Th. Exp. Coeff. Metal Temp. along Len	70.7 °C	0.0000119123 /°C
Elastic Mod. at Design Temperature	165.6 °C	0.19429E+09 KPa.
Th. Exp. Coeff. Metal Temp. at Tubsht	21.1 °C	0.0000115190 /°C
Elastic Mod. at Metal Temp. along Len	70.7 °C	0.19986E+09 KPa.
Elastic Mod. at Ambient Temperature	21.1 °C	0.20270E+09 KPa.

Channel - TE-1 Carbon & Low Alloy Steels, Group 1
Channel - TM-1 Carbon Steels with C<= 0.3%



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 161 of 173

ASME TS Calc: DESIGN CASE

Case: 1 9:52a Aug 12, 2026

Th. Exp. Coeff. Metal Temp. at Tubsht	21.1 °C	0.0000115190 /°C
Elastic Mod. at Design Temperature	76.7 °C	0.19952E+09 KPa.
Elastic Mod. at Ambient Temperature	21.1 °C	0.20270E+09 KPa.

Tubes - TE-1 Carbon & Low Alloy Steels, Group 1
Tubes - TM-1 Carbon Steels with C<= 0.3%

Th. Exp. Coeff. Metal Temp. along Len	49.6 °C	0.0000117759 /°C
Elastic Mod. at Design Temperature	165.6 °C	0.19429E+09 KPa.
Elastic Mod. at Metal Temp. along Len	49.6 °C	0.20107E+09 KPa.
Elastic Mod. at Tubsht. Design Temp.	165.6 °C	0.19429E+09 KPa.
Elastic Mod. at Ambient Temperature	21.1 °C	0.20270E+09 KPa.

TubeSheet - TE-1 Carbon & Low Alloy Steels, Group 1
TubeSheet - TM-1 Carbon Steels with C<= 0.3%

Elastic Mod. at Design Temperature	165.6 °C	0.19429E+09 KPa.
Elastic Mod. at Ambient Temperature	21.1 °C	0.20270E+09 KPa.

Note:

The Elasticity and Alpha values are taken from Tables in ASME II D.
Please insure these properties are consistent with the
type of Material for the tubes, shell, channel etc.

Tube Required Thickness under Internal Pressure (Tubeside pressure):

Thickness Due to Internal Pressure:

$$= (P \cdot (D/2 - CAE)) / (S \cdot E + 0.4 \cdot P)$$
 per Appendix 1-1 (a)(1)

$$= (1191.5 \cdot (15.875/2 - 0)) / (92.4 \cdot 1.0 + 0.4 \cdot 1191.5)$$

$$= 0.1018 + 0.0000 = 0.1018 \text{ mm}$$

Tube Required Thickness under External Pressure (Shellside pressure) :

External Pressure Chart CS-1 at 165.56 °C
Elastic Modulus for Material 197876288.00 KPa.

Results for Max. Allowable External Pressure (Emawp):

TCA	ODCA	SLEN	D/T	L/D	Factor A	B
2.1080	15.88	4773.00	7.53	50.0000	0.0193957	95.01

EMAWP = $(2.167 / (D/T) - 0.0833) \cdot B = 19424.4336 \text{ KPa.}$

Results for Req'd Thickness for Ext. Pressure (Tca):

TCA	ODCA	SLEN	D/T	L/D	Factor A	B
0.3496	15.88	4773.00	45.41	50.0000	0.0005334	52.78

EMAWP = $(4 \cdot B) / (3 \cdot (D/T)) = (4 \cdot 52.7777) / (3 \cdot 45.4115) = 1549.5249 \text{ KPa.}$

Summary of Tube Required Thickness Results:

Total Required Thickness including Corrosion all.	0.3496 mm
Allowable Internal Pressure at Corroded thickness	27453.64 KPa.
Required Internal Design Pressure	1191.50 KPa.
Allowable External Pressure at Corroded thickness	19424.43 KPa.
Required External Design Pressure	1549.50 KPa.
Required Thickness due to Shell Side pressure	0.3496 mm

Detailed Results for load Case D3 un-corr. (Psd,max + Ptd,max)

Intermediate Calculations For Tubesheets Extended As Flanges:

ASME Code, Section VIII Division 1, 2025

Gasket Contact Width,	$N = (Goc - Gic) / 2$	13.000 mm
Basic Gasket Width,	$b0 = N / 2$	6.500 mm



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 162 of 173

ASME TS Calc: DESIGN CASE

Case: 1 9:52a Aug 12, 2026

Effective Gasket Width, $b = \sqrt{b_0} \cdot 2.5$ 6.422 mm
 Gasket Reaction Diameter, $G = G_0 - 2.0 \cdot b$ 642.156 mm

Results for ASME Fixed Tubesheet Calculations for Configuration b:

Results for Tubesheet Calculations Original Thickness:

ASME Section VIII-2 Part 4.18.8.4 Step 1:

Tube expansion depth ratio $[\rho]$:

= l_{tx} / h (modified for corrosion if present)

= 0/52.0

= 0.0000 (must be $0 \leq \rho \leq 1$)

Effective tube hole diameter $[d^*]$:

= $\max(dt - 2 \cdot tt(E_t T / E) \cdot (S_t T / S) \cdot (\rho); dt - 2 \cdot tt)$

= $\max(15.875 - 2 \cdot 2.108 (0.19429E+09 / 0.19429E+09) \cdot (92/137) \cdot (0); 15.875 - 2 \cdot 2.108)$

= 15.8750 mm

Equivalent outer tube limit circle diameter $[Do]$:

= $2 \cdot r_o + dt$

= $2 \cdot 284.388 + 15.875$

= 584.651 mm

Determine the basic ligament efficiency for shear $[\mu]$:

= $(p - dt) / p$

= $(19.844 - 15.875) / 19.844$

= 0.200

Equivalent outer tube limit radius $[ao]$:

= $Do / 2$

= 584.651/2

= 292.3255 mm

Effective tube pitch $[p^*]$:

= $p / \sqrt{ 1 - 4 \cdot \min(AL \cdot CNVfactor; 4 \cdot Do \cdot p) / (\pi \cdot Do^2) }$

= $19.844 / \sqrt{ 1 - 4 \cdot \min(0 \cdot 100.0 ; 4 \cdot 584.651 \cdot 19.844) / (\pi \cdot 584.651^2) }$

= 19.8440 mm

Effective ligament efficiency for bending $[\mu^*]$:

= $(p^* - d^*) / p^*$

= $(19.844 - 15.875) / 19.844$

= 0.2000

Ratio $[ps]$:

= as / ao

= 300.0/292.3255

= 1.0263

Ratio $[pc]$:

= ac / ao

= 321.0778/292.3255

= 1.0984

Compute parameter $[xt]$:

= $1 - Nt((dt - 2 \cdot tt) / (2 \cdot ao))^2$

= $1 - 534 ((15.875 - 2 \cdot 2.108) / (2 \cdot 292.3255))^2$

= 0.7876

Determine parameter $[xs]$:

= $1 - Nt(dt / (2 \cdot ao))^2$

= $1 - 534 (15.875 / (2 \cdot 292.3255))^2$

= 0.6063



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 163 of 173

ASME TS Calc: DESIGN CASE

Case: 1 9:52a Aug 12, 2026

Determine the value [h'g]:

$$= \max((h_g - CATC); 0) \text{ (For pressure only cases)}$$

$$= \max((0 - 0); 0)$$

$$= 0.000 \text{ mm}$$

ASME Section VIII-2 Part 4.18.8.4 Step 2:

Axial Shell Stiffness [Ks]:

$$= \pi \cdot ts(D_s + ts)E_s/L$$

$$= \pi \cdot 9.53 (600.0 + 9.53) \cdot 1.9429E+09/4773.0$$

$$= 75752.0000 \text{ Kg/mm}$$

Axial Tube Stiffness [Kt]:

$$= \pi \cdot tt(D_t - tt)E_t/L$$

$$= \pi \cdot 2.108 (15.875 - 2.108) \cdot 1.9429E+09/4773.0$$

$$= 378.4566 \text{ Kg/mm}$$

Stiffness Factor [Ks,t]:

$$= K_s / (N_t \cdot K_t)$$

$$= 75752.0 / (534 \cdot 378.457)$$

$$= 0.37483$$

Rigidity Ratio [J]:

$$= 1 / (1 + K_s/K_j)$$

$$= 1 / (1 + 75752.0/0)$$

$$= 1.0000 (= 1 \text{ if No Exp. Jt.})$$

Shell coefficient [βs]:

$$= ((12(1 - v_s^2))^{1/4}) / ((D_s + ts) ts)$$

$$= ((12(1 - 0.3^2))^{1/4}) / ((600.0 + 9.53) 9.53)$$

$$= 0.0239 \text{ 1/mm}$$

Shell coefficient [ks]:

$$= \beta_s \cdot E_s \cdot ts^3 / (6(1 - v_s^2))$$

$$= 0.024 \cdot 0.19429E+09 \cdot 9.53^3 / (6(1 - 0.3^2))$$

$$= 734596544.0000 \text{ KPa} \cdot \text{mm}^2$$

Shell coefficient [λs]:

$$= 6(D_s + ts) \cdot ks/h^3 \cdot (1 + h \cdot \beta_s + (h \cdot \beta_s)^2/2)$$

$$= 6(600.0 + 9.53) \cdot 0.73460E+09/52.0^3 \cdot (1 + 52.0 \cdot 0.024 + (52.0 \cdot 0.024)^2/2)$$

$$= 57499576.0000 \text{ KPa}$$

Shell coefficient [δs]:

$$= D_s^2 / (4 \cdot E_s \cdot ts) \cdot (1 - D_s \cdot v_s / (2(D_s + ts)))$$

$$= 600.0^2 / (4 \cdot 0.19429E+09 \cdot 9.53) \cdot (1 - 600.0 \cdot 0.3 / (2(600.0 + 9.53)))$$

$$= 0.41428E-01 \text{ mm/N./mm}^2$$

Intermediate parameters for Tubesheet Gasketed on the Channel Side:

βC, kc, λC, δC are all = 0

ASME Section VIII-2 Part 4.18.8.4 Step 3:

h/p = 2.620440 ; μ* = 0.200010 ; E* = 30185138 KPa.

E*/E = 0.155361 ; ν* = 0.458557

Note: As h/p (2.620) is > 2, data values for h/p = 2 were used.

Tube Bundle Stiffness Factor [Xa]:

$$= ((24(1 - \nu^{*2}) N_t \cdot E_t \cdot tt(d_t - tt) a_o^2) / (E^* \cdot L \cdot H^3))^{1/4}$$

$$= ((24(1 - 0.459^2) 534 \cdot 0.19429E+09 \cdot 2.108$$

$$(15.875 - 2.108) 292.3255^2) / (30185138 \cdot 4773.0 \cdot 52.0^3))^{1/4}$$

$$= 3.9390$$

Values from Table 4.18.3



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 164 of 173

ASME TS Calc: DESIGN CASE

Case: 1 9:52a Aug 12, 2026

Zd = 0.024674 ; Zv = 0.062813 ; Zm = 0.361181
Za = 0.658639E+01 ; Zw = 0.062813

ASME Section VIII-2 Part 4.18.8.4 Step 4:

Diameter ratio [K]:

= A / Do
= 663.0/584.651
= 1.1340

Compute coefficient [F]:

= (1 - v*) / E* * (λs + λc + E * ln(K))
= (1 - 0.46) / 30185138 * (57499576 + 0 +
0.19429E+09 * ln(1.13))
= 1.4697

Compute parameter [φ]:

= (1 + v*) F
= (1 + 0.4586) 1.4697
= 2.1436

Compute parameter [Q1]:

= (ps - 1 - φ * Zv) / (1 + φ * Zm)
= (1.0263 - 1 - 2.1436 * 0.0628) / (1 + 2.1436 * 0.3612)
= -0.061093

Compute Parameter [Qz1]:

= (Zd + Q1 * Zw) / 2 * Xa⁴
= (0.02467 + -0.06109 * 0.06281) / 2 * 3.93897⁴
= 2.5080

Compute parameter [Qz2]:

= (Zv + Q1 * Zm) / 2 * Xa⁴
= (0.06281 + -0.06109 * 0.36118) / 2 * 3.93897⁴
= 4.9045

Compute parameter [U]:

= (Zw + (ps - 1) Zm) Xa⁴ / (1 + φ * Zm)
= (0.0628 + (1.0263 - 1) 0.3612) 3.93897⁴ / (1 + 2.1436 * 0.3612)
= 9.8091

ASME Section VIII-2 Part 4.18.8.4 Step 5:

Determine factor [yb]:

= (Gc - C) / Do (config b)
= (642.1556 - 690.0) / 584.651 = -0.08183

Compute Parameter [γ]:

= 0.000 mm (For Pressure only cases)

Calculate parameter [ws]:

= ps * ks * βs * δS (1 + h * βs)
= 1.0263 * 0.73460E+09 * 0.0239 * 0.041428 (1 + 52.0 * 0.0239)
= 1668.8942 mm²

Calculate parameter [ω*s]:

= ao² (ps² - 1) * (ps - 1) / 4 - ωs
= 292.326² (1.026² - 1) * (1.026 - 1) / 4 - 1668.894
= -1639.0583 mm²

Parameter [ωc]:

= pc * kc [δC (CmTheta * βC + CqΔ * h * βC²) -
ζc (CmTheta + h * CqTheta * h * βC / 2))
= 1.098 * 0 [0 (0 + 0 * 0 * 52.0) -
0 (0/52.0 + 0 * 0/2))



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 165 of 173

ASME TS Calc: DESIGN CASE

Case: 1 9:52a Aug 12, 2026

$$= 0.0000 \text{ mm}^2$$

Parameter [$\omega \cdot c$]:

$$\begin{aligned} &= a_o^2 [(p_c^2 + 1) \cdot (p_c - 1)/4 - (p_s - 1)/2] - \omega c \\ &= 292.3255^2 [(1.09836^2 + 1) \cdot (1.09836 - 1)/4 - (1.02625 - 1)/2] - 0 \\ &= 3514.4580 \text{ mm}^2 \end{aligned}$$

Pressure [$P \cdot S$]:

$$= 0 \text{ For Pressure only cases or Configurations d,e,f,A,B,C,D}$$

Pressure [$P \cdot C$]:

$$= 0 \text{ For Pressure only cases or Configurations b,c,d,B,C,D}$$

ASME Section VIII-2 Part 4.18.8.4 Step 6:

Pressure [$P's$]:

$$\begin{aligned} &= P_s \{ x_s + 2(1 - x_s) v_t + [2/Kst \cdot (D_s/D_o)^2] v_s - \\ &\quad [(p_s^2 - 1) / (J \cdot Kst)] - [(1 - J) / (2J \cdot Kst)] [(D_j)^2 - (D_s)^2 / D_o^2] \} \\ &= 1549.5 \{ 0.606 + 2(1 - 0.606) 0.3 + [2/0.375 \cdot \\ &\quad (600.0/584.651)^2] 0.3 - [(1.026^2 - 1) / (1.0 \cdot 0.375)] - \\ &\quad [(1 - 1.0) / (2 \cdot 1.0 \cdot 0.375)] [(0^2 - (600.0)^2 / 584.651^2)] \} \\ &= 3697.8281 \text{ KPa.} \end{aligned}$$

Pressure [$P't$]:

$$\begin{aligned} &= [x_t + 2(1 - x_t) v_t + 1/(J \cdot Kst)] P_t \\ &= [0.788 + 2(1 - 0.788) 0.3 + 1/(1.0 \cdot 0.375)] 1191.5 \\ &= 4269.0459 \text{ KPa.} \end{aligned}$$

Pressure [P_y]:

$$\begin{aligned} &= N_t \cdot K_t \cdot \gamma / (\pi \cdot a_o^2) \\ &= 534 \cdot 378.457 \cdot 0 / (3.142 \cdot 292.326^2) \\ &= 0.0000 \text{ KPa.} \end{aligned}$$

Pressure [P_w]:

$$\begin{aligned} &= -\gamma_b \cdot U \cdot W \cdot / (2 \cdot \pi \cdot a_o^2) \\ &= -0.082 \cdot 9.809 \cdot 48796.79 / (2 \cdot \pi \cdot 292.326^2) \\ &= 715.3920 \text{ KPa.} \end{aligned}$$

Calculate the pressure [$Prim$]:

$$\begin{aligned} &= - (U/a_o^2) \cdot (\omega \cdot s \cdot P_s - \omega \cdot c \cdot P_t) \\ &= - (9.809/292.326^2) \cdot (-1639.058 \cdot 1549.5 - 3514.458 \cdot 1191.5) \\ &= 772.1977 \text{ KPa.} \end{aligned}$$

Calculate the pressure [$P\omega$]:

$$\begin{aligned} &= (U/a_o^2) \cdot (\omega \cdot s \cdot P \cdot s - \omega \cdot c \cdot P \cdot c) \\ &= (9.809/292.326^2) \cdot (1668.8942 \cdot 0 - 0 \cdot 0) \\ &= 0.0000 \text{ KPa.} \end{aligned}$$

Determine the effective pressure [Pe]:

$$\begin{aligned} &= J \cdot Kst / (1 + J \cdot Kst(Qz1 + (p_s - 1) Qz2)) \cdot \\ &\quad (P's - P't + P_y + P\omega + P_w + Prim) \\ &= 0.1000E+01 \cdot 0.375 / (1 + 1.0 \cdot 0.375 (2.508 + (1.026 - \\ &\quad 1) 4.905)) \cdot (3697.828 - 4269.046 + 0 + 0 + 715.392 + 772.198) \\ &= 172.7493 \text{ KPa.} \end{aligned}$$

ASME Section VIII-2 Part 4.18.8.4 Step 7:

Determine factor [$Q2$]:

$$\begin{aligned} &= [((\omega \cdot s \cdot P_s - \omega \cdot c \cdot P_t) - (\omega \cdot s \cdot P \cdot s - \omega \cdot c \cdot P \cdot c)) + \\ &\quad W \cdot \gamma_b / (2 \cdot \pi)] / (1 + \phi \cdot Z_m) \\ &= [((-1639.058 \cdot 1549.5 - 3514.458 \cdot 1191.5) - \\ &\quad (1668.894 \cdot 0 - 0 \cdot 0)) \cdot 0 + \\ &\quad 48796.8 \cdot -0.082 / (2 \cdot \pi)] / (1 + 2.1436 \cdot 0.36118) \\ &= -744.8615 \text{ Kg} \end{aligned}$$



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 166 of 173

ASME TS Calc: DESIGN CASE

Case: 1 9:52a Aug 12, 2026

Calculate factor [Q3]:

$$\begin{aligned}
 &= Q1 + 2 \cdot Q2 / (Pe \cdot a_o^2) \\
 &= -0.061 + 2 \cdot -744.862 / (172.749 \cdot 292.326^2) \\
 &= -1.05069
 \end{aligned}$$

Fm Value from Table 4.18.3 = 0.525346

Tubesheet Bending Stress - original thickness [σ]:

$$\begin{aligned}
 &= (1.5 \cdot F_m / \mu \cdot) \cdot (2 \cdot a_o / (H - h'g))^2 \cdot Pe \\
 &= (1.5 \cdot 0.5253 / 0.2) \cdot (2 \cdot 292.3255 / (52.0 - 0))^2 \cdot 172.75 \\
 &= 86.0425 \text{ N./mm}^2
 \end{aligned}$$

Allowable Tubesheet Bending Stress [σ allowed]:

$$= 1.5 \cdot S = 1.5 \cdot 138.0 = 207.0 \text{ N./mm}^2$$

Tubesheet Bending Stress - final thickness [σ_f]:

$$\begin{aligned}
 &= (1.5 \cdot F_m / \mu \cdot) \cdot (2 \cdot a_o / (h - h'g))^2 \cdot Pe \\
 &= (1.5 \cdot 0.2211 / 0.2) \cdot (2 \cdot 292.3255 / (29.633 - 0))^2 \cdot 320.64 \\
 &= 206.9905 \text{ N./mm}^2
 \end{aligned}$$

Reqd Tubesheet Thickness, for Bending Stress (including CA) [HReqB]:

$$\begin{aligned}
 &= h + C_{ats} + C_{atc} \\
 &= 29.6332 + 0 + 0 \\
 &= 29.6332 \text{ mm}
 \end{aligned}$$

ASME Section VIII-2 Part 4.18.8.4 Step 8:

Shear Stress check [τ_{limit}]:

$$\begin{aligned}
 &= (2 \cdot \mu \cdot h / a_o) \cdot \min(0.8S; 0.533S_y) \\
 &= (2 \cdot 0.2 \cdot 52.0 / 292.326) \cdot 110.398 \\
 &= 7.8556 \text{ N./mm}^2
 \end{aligned}$$

Shear Stress is not required to be computed; [Pe] <= τ_{limit}

Tubesheet Shear Stress is probably low, use the following req. thk:

$$\begin{aligned}
 \text{Tubesheet thickness (Incl. Corr.)} &= 3.8100 \text{ mm} \\
 \text{Tubesheet Shear Stress} &= 26.1565 \text{ N./mm}^2
 \end{aligned}$$

Reqd Tubesheet Thickness for Given Loadings (including CA) [Hreqd]:

$$\begin{aligned}
 &= \max(H_{reqB}; H_{reqS}) \\
 &= \max(29.6332; 3.81) \\
 &= 29.6332 \text{ mm}
 \end{aligned}$$

ASME Section VIII-2 Part 4.18.8.4 Step 9:

The F_{tmin} and F_{tmax} Coefficients from Table 4.18.4:

$$F_{tmin} = -4.9738, F_{tmax} = 3.3859$$

First Extreme Tube Axial Stress from among all the tubes [σ_{t1}]:

$$\begin{aligned}
 &= ((P_s \cdot x_s - P_t \cdot x_t) - Pe \cdot F_{tmin}) / (X_t - X_s) \\
 &= ((1549.5 \cdot 0.6063 - 1191.5 \cdot 0.7876) - (172.749) \cdot -4.974) / \\
 &\quad (0.7876 - 0.6063) \\
 &= 4.7436 \text{ N./mm}^2
 \end{aligned}$$

Second Extreme value of Tube Axial Stress from among all the tubes [σ_{t2}]:

$$\begin{aligned}
 &= ((P_s \cdot x_s - P_t \cdot x_t) - Pe \cdot F_{tmax}) / (X_t - X_s) \\
 &= ((1549.5 \cdot 0.6063 - 1191.5 \cdot 0.7876) - (172.749) \cdot 3.386) / \\
 &\quad (0.7876 - 0.6063) \\
 &= -3.2201 \text{ N./mm}^2
 \end{aligned}$$

Maximum Tube Axial Stress [$\sigma_{t,max}$]:

$$= \max(|\sigma_{t,1}|; |\sigma_{t,2}|) = 4.744 \text{ N./mm}^2$$

Allowable Tube Stress [$\sigma_{t,A}$]:



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 167 of 173

ASME TS Calc: DESIGN CASE

Case: 1 9:52a Aug 12, 2026

$$= Sot = 92.3983 \text{ N./mm}^2$$

Check for Buckling as some of the tubes are in compression.

Determine the Factor of Safety [Fs]:

$$= \max((3.25 - 0.25(Z_d + Q_3 \cdot Z_w)X_{a^4}); 1.25)$$

$$= \max((3.25 - 0.25(0.025 + -1.051 \cdot 0.063)3.939^4); 1.25)$$

$$= 2.0000 \text{ (Should be } \leq 2 \text{)}$$

Determine the factor [rt]:

$$= (\sqrt{ (dt^2 + (dt - 2 \cdot tt)^2) }) / 4$$

$$= (\sqrt{ (15.875^2 + (15.875 - 2 \cdot 2.108)^2) }) / 4$$

$$= 4.9241 \text{ mm}$$

Determine the factor [Ct]:

$$= \sqrt{ (2 \cdot \pi^2 \cdot Et / Syt)}$$

$$= \sqrt{ (2 \cdot \pi^2 \cdot 0.19429E+09 / 156)}$$

$$= 156.4208$$

Determine the factor [Ft]:

$$= k \cdot L / r$$

$$= 0 \cdot 0 / 4.924$$

$$= 0.0000$$

Buckling Allowable Stress [Stb]:

$$= (Sy_t / Fs) \cdot (1 - Ft / (2 \cdot Ct))$$

$$= (156 / 2.0) \cdot (1 - 0 / (2 \cdot 156.421))$$

$$= 78.377 \text{ N./mm}^2 \text{ (Never greater than Sot)}$$

Note: The Axial Compressive stress in tubes is within limits.

Largest tube-to-tubesheet Joint Load [Wt]:

$$= \sigma_{t,max} \cdot \text{Tube Area}$$

$$= 4.74 \cdot 0.9117$$

$$= 44.10 \text{ Kgf}$$

Tube Metal Area [At]:

$$= \pi (do - t) t$$

$$= \pi (15.875 - 2.108) 2.108$$

$$= 0.912 \text{ cm}^2$$

Tube Weld Size Results per UW-20.3:

Tube Strength [Ft]:

$$= \pi \cdot t (do - t) S$$

$$= \pi \cdot 2.108 (15.875 - 2.108) 92.398$$

$$= 859.004 \text{ Kgf}$$

Groove Weld Strength [Fg]:

$$= 0.85 \cdot \pi \cdot a_g (do + 0.67 \cdot a_g) S_w \text{ (but not } > Ft \text{)}$$

$$= 0.85 \cdot \pi \cdot 2.0 (15.875 + 0.67 \cdot 2.0) 92.4$$

$$= 859.0042 \text{ Kgf}$$

Weld Strength Factor [fw]:

$$= S / S_w \text{ where } S_w = \min(S \text{ and } S_t)$$

$$= 92.398 / 92.398$$

$$= 1.000$$

Design Strength Ratio [fd]:

$$= 1 \text{ for full strength welds}$$

Fillet Weld Strength [Ff]:

$$= 0.55 \cdot \pi \cdot a_f (do + 0.67 \cdot a_f) S_w \text{ (but not } > Ft \text{)}$$

$$= 0.55 \cdot \pi \cdot 2.0 (15.875 + 0.67 \cdot 2.0) 92.4$$

$$= 560.5122 \text{ Kgf}$$



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 168 of 173

ASME TS Calc: DESIGN CASE

Case: 1 9:52a Aug 12, 2026

Minimum Length of Weld [ar]:

$$= 2 \left(\sqrt{(0.75 \cdot do)^2 + 1.07 \cdot t \cdot (do - t) \cdot fw \cdot fd} - 0.75 \cdot do \right)$$

$$= 2 \left(\sqrt{(0.75 \cdot 15.875)^2 + 1.07 \cdot 2.108 \cdot (15.875 - 2.108) \cdot 1.0 \cdot 1.0} - 0.75 \cdot 15.875 \right)$$

$$= 2.479 \text{ mm}$$

Minimum Required Fillet Weld Leg [afr]: 1.2648 mm

Minimum Required Groove Weld Leg [agr]: 1.2648 mm

Tube-Tubesheet Jt allowable, 859.0 is >= tube strength 859.0 Kgf

Note: This tube-tubesheet joint is a Full Strength joint

ASME Section VIII-2 Part 4.18.8.4 Step 10:

Shell Axial Membrane Allowable Stress:

$$= S_s \cdot E_{sw} = 118.0 \cdot 1.0 = 118.0 \text{ N./mm}^2$$

Axial Membrane Stress in Shell [σ_s, m]:

$$= a_o^2 / (D_s + t_s) \cdot [P_e + (p_s^2 - 1)(P_s - P_t)] + a_s^2 \cdot P_t / (D_s + t_s) \cdot t_s$$

$$= 292.326^2 / (600.0 + 9.53) \cdot 9.53 + [172.75 + (1.026^2 - 1) \cdot (1549.5 - 1191.5)] + 300.0^2 \cdot 1191.5 / ((600.0 + 9.53) \cdot 9.53)$$

$$= 21.2834 \text{ N./mm}^2$$

ASME Section VIII-2 Part 4.18.8.4 Step 11:

Note:

For a given Shell thickness of 9.53 mm, the minimum Shell length adjacent to the tubesheet should be 136.111 mm

Shell Membrane Stress due to Joint Interaction [σ_s, m]:

$$= a_o^2 / ((D_s + t_s) \cdot t_s) \cdot [P_e + (p_s^2 - 1)(P_s - P_t)] + a_s^2 \cdot P_t / ((D_s + t_s) \cdot t_s)$$

$$= 292.326^2 / ((600.0 + 9.53) \cdot 9.53) + [172.75 + (1.026^2 - 1) \cdot (1549.5 - 1191.5)] + 300.0^2 \cdot 1191.5 / ((600.0 + 9.53) \cdot 9.53)$$

$$= 21.2834 \text{ N./mm}^2$$

Shell Bending Stress due to Joint Interaction [σ_s, b]:

$$= 6 \cdot k_s / t_s^2 \cdot \{ \beta_s [\delta_s \cdot P_s + a_s^2 \cdot P \cdot s / (E \cdot t_s)] + 6(1 - \nu^2) / (E \cdot h) \cdot (a_o / h)^3 [1 + h \cdot \beta_s / 2] [P_e (Z_v + Z_m \cdot Q_1) + 2 / a_o^2 \cdot Z_m \cdot Q_2] \}$$

$$= 6 \cdot 0.73460 \text{E}+09 / 9.53^2 \cdot \{ 0.024 [0.041428 \cdot 1549.5 + 300.0^2 \cdot 0 / (1.8516 \text{E}+1)] + 6(1 - 0.46^2) / (30185138) \cdot (292.33 / 52.0)^3 [1 + 52.0 \cdot 0.02 / 2] [172.7 (0.063 + 0.361 \cdot -0.061) + 2 / 292.33^2 \cdot 0.361 \cdot -744.862] \}$$

$$= -45.6516 \text{ N./mm}^2$$

Shell Stress Summation vs. Allowable

$$\therefore | \sigma_{s, m} | + | \sigma_{s, b} | \leq 1.5 \cdot S_s$$

$$\therefore | 21.28 | + | -45.65 | \leq 177.0 \text{ N./mm}^2$$

$$\therefore 66.93, \text{ must be } \leq 177.0 \text{ N./mm}^2$$

Computations completed for ASME tubesheet configuration: b

Stress/Force Summary for Loadcase D3 un-corr. (Psd,max + Ptd,max):

Stress Description	Actual	Allowable	Pass/Fail
Tubesheet Bend. Stress	86.0 <=	207.0 N./mm ²	Pass
Tubesheet Shear Stress	1.7 <=	110.4 N./mm ²	Pass
Maximum Tube Stress	4.7 <=	92.4 N./mm ²	Pass
Minimum Tube Stress (Buckling)	-3.2 <=	-78.4 N./mm ²	Pass
Maximum Force on any one Tube	44.1 <=	859.0 Kgf	Pass
Axial Membrane Stress in Shell	21.3 <=	118.0 N./mm ²	Pass



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 169 of 173

ASME TS Calc: DESIGN CASE

Case: 1 9:52a Aug 12, 2026

Shell Stress (jt. inter.) 66.9 <= 177.0 N./mm² Pass

Thickness Results for Loadcase D3 un-corr. (Psd,max + Ptd,max):

Thickness (mm)	Required	Actual	P/F
Tubesheet Thickness :	29.633	52.000	Ok
Tube-Tubesheet Fillet Weld Leg :	1.265	2.000	Ok
Tube-Tubesheet Groove Weld Leg :	1.265	2.000	Ok

Fixed Tubesheet results per ASME Div. 2 Part 4.18.8 2025

Results for 14 Load Cases:

Case#	--Reqd. Tbsht	Thk. + CA Extnsn	----	Tubesheet Bend	Allwd	Stresses Shear	Allwd	Case Type	Pass/ Fail	
D1uc	20.678	21.674		72	207	6	110	Ps+Pt-Th	D1	Ok
D2uc	14.907	...		38	207	7	110	Ps+Pt-Th	D2	Ok
D3uc	29.633	...		86	207	2	110	Ps+Pt-Th	D3	Ok
O1uc	7.886	...		155	434	21	110	Ps+Pt+Th	O1	Ok
O2uc	6.707	...		96	434	7	110	Ps+Pt+Th	O2	Ok
O3uc	7.123	...		140	434	13	110	Ps+Pt+Th	O3	Ok
O4uc	4.745	...		109	434	14	110	Ps+Pt+Th	O4	Ok
D1c	36.289	21.674		109	207	6	110	Ps+Pt-Th-c	D1	Ok
D2c	18.110	...		33	207	8	110	Ps+Pt-Th-c	D2	Ok
D3c	39.084	...		115	207	2	110	Ps+Pt-Th-c	D3	Ok
O1c	32.302	...		207	434	18	110	Ps+Pt+Th-c	O1	Ok
O2c	28.691	...		134	434	3	110	Ps+Pt+Th-c	O2	Ok
O3c	32.345	...		189	434	10	110	Ps+Pt+Th-c	O3	Ok
O4c	26.585	...		143	434	10	110	Ps+Pt+Th-c	O4	Ok
Max:	39.0845	21.674	mm		0.554		0.187	(Str. Ratio)		

Load Case Definitions:

[Ps & Pt]:

Shell-side and Tube-side Design or Operating Pressures derived from Psd,min Ptd,max, Psox,min, Ptox,max etc. per the Load Case Tables

[(+)-Th]:

With or Without Thermal Expansion, Tt,mx & Ts,mx

[c]:

With or Without Corrosion Allowance

[D1, D2, D3]:

Design Load Cases using the Maximum and Minimum Design Pressures

[D4]:

Design Load Case using the Minimum (Vacuum) Pressures (if specified)

[O1, O2, O3, O4]:

Operating Load Cases using the Maximum and Minimum Operating Pressures and Operating Temperatures

Shell Axial Membrane Stress Summary:

---- Shell Stresses ----					:	---- Shell Band Stress ----					:	Pass
Case#	Ten	Allwd	Cmp	Allwd	:	Ten	Allwd	Cmp	Allwd	:	Fail	
D1uc	9	117	...	...	:	...	...	...	...	:	Ok	



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 170 of 173

ASME TS Calc: DESIGN CASE

Case: 1 9:52a Aug 12,2026

D2uc	12	117	...	...	...	...	...	...	Ok
D3uc	21	117	...	...	...	...	...	...	Ok
O1uc	14	423	-14	-111	...	...	...	...	Ok
O2uc	9	423	-9	-111	...	...	...	...	Ok
O3uc	2	423	-2	-111	...	...	...	...	Ok
O4uc	21	423	-21	-111	...	...	...	...	Ok
D1c	14	117	...	...	...	...	...	...	Ok
D2c	18	117	...	...	...	...	...	...	Ok
D3c	32	117	...	...	...	...	...	...	Ok
O1c	10	423	-10	-105	...	...	...	...	Ok
O2c	3	423	-3	-105	...	...	...	...	Ok
O3c	8	423	...	...	...	...	...	...	Ok
O4c	21	423	-21	-105	...	...	...	...	Ok

Max RATIO 0.270 0.196 ...

Tube, Shell and Channel Stress Summary:

		---- Tube Stresses		Tube Loads		Shell Stress		Channel Stress		Stress Pass	
Case#	Ten	Allwd	Cmp	Allwd	Ld	Allwd	Stress	Allwd	Stress	Allwd	Fail
D1uc	9	92	-9	-92	88	859	170	176	...	...	Ok
D2uc	6	92	-4	-78	60	859	127	176	...	...	Ok
D3uc	5	92	-3	-78	44	859	67	176	...	...	Ok
O1uc	33	184	-15	-92	311	1718	374	423	...	...	Ok
O2uc	23	184	...	-92	210	1718	147	423	...	...	Ok
O3uc	30	184	-9	-92	275	1718	247	423	...	...	Ok
O4uc	26	184	-7	-92	245	1718	274	423	...	...	Ok
D1c	12	92	-10	-92	112	859	216	423	...	...	Ok
D2c	7	92	-5	-81	66	859	189	423	...	...	Ok
D3c	7	92	-4	-78	64	859	63	176	...	...	Ok
O1c	35	184	-15	-92	323	1718	419	423	...	...	Ok
O2c	20	184	...	...	186	1718	107	423	...	...	Ok
O3c	30	184	-8	-92	275	1718	246	423	...	...	Ok
O4c	25	184	-7	-92	234	1718	296	423	...	...	Ok

Max RATIO 0.188 0.164 0.188 0.990 ...

Summary of Thickness Comparisons for 14 Load Cases:

Thickness (mm)	Required	Actual	P/F
Tubesheet thickness :	39.084	52.000	Ok
Tubesheet thickness flanged extension :	21.674	36.000	Ok
Tube thickness :	0.350	2.108	Ok
Tube-tubesheet fillet weld leg :	1.265	2.000	Ok
Tube-tubesheet groove weld leg :	1.265	2.000	Ok

Min Shell length of thk, (9.530) adj. to tubesheet: 136.111 mm

Note: This is a full strength Tube to Tubesheet Joint.

Summary of Axial Differential Expansion between Shell and Tubes :

Due to Thermal Expansion Shell Compresses by : -1.218 mm
 Due to Pressure Shell Compresses by : -0.040 mm
 Due to Pressure + Thermal Shell Compresses by : -1.257 mm

Tubesheet MAWP used to Compute Hydrotest Pressure:

Stress / Force Condition	Tubeside MAWP	Ø shellside Stress Rat.	Shellside MAWP	Ø tubeside Stress Rat.
Tubesheet Bending Stress	2142.85	1.000	8516.37	1.000
Tubesheet Shear Stress	16870.84	1.000	22165.90	1.000
Tube Tensile Stress	9166.19	1.000	20022.29	1.000



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 171 of 173

ASME TS Calc: DESIGN CASE

Case: 1 9:52a Aug 12, 2026

Tube Compressive Stress	4591.32	0.444	24537.83	1.000
Tube-Tubesheet Joint load	9166.19	1.000	20022.29	1.000
Shell Stress (Axial, Junction)	1230.27	0.999	3468.74	1.000
Tube Pressure Stress	27453.63	1.000	19424.42	1.000
Tubesheet Extension Stress	2336.28	...	No Calc	No Calc
Minimum MAWP	1230.27		3468.74	

Tubesheet MAPnc used to Compute Hydrotest Pressure:

Stress / Force Condition	Tubeside MAPnc	Ø shellside Stress Rat.	Shellside MAPnc	Ø tubeside Stress Rat.
Tubesheet Bending Stress	3435.28	1.000	8516.37	1.000
Tubesheet Shear Stress	23614.01	1.000	23655.11	1.000
Tube Tensile Stress	11694.03	1.000	22036.03	1.000
Tube Compressive Stress	11694.03	1.000	36469.16	1.000
Tube-Tubesheet Joint load	11694.03	1.000	22036.02	1.000
Shell Stress (Axial, Junction)	3114.69	1.000	5844.64	1.000
Tube Pressure Stress	27453.63	1.000	19593.47	1.000
Tubesheet Extension Stress	2336.28	...	No Calc	No Calc
Minimum MAPnc	2336.28		5844.64	

(*) Only the design load cases were analyzed to compute the MAWP for determining the test pressure.

Summary of Exchanger Pressure and Thermal Displacements: (mm)

Load Case#	Due to Pressure		Due to Thermal Exp.		Computed Delta Ms	
	UnCorroded	Corroded	UnCorroded	Corroded	UnCorroded	Corroded
1	0.0056	0.0056	...	...	...	...
2	-0.0396	-0.0397	...	...	...	...
3	-0.0340	-0.0341	...	...	...	...
4	...	...	...	...	...	...
5	0.0056	0.0056	-1.2160	-1.2176	...	...
6	-0.0396	-0.0397	-1.2160	-1.2176	...	...
7	-0.0340	-0.0341	-1.2160	-1.2176	...	...
8	...	...	-1.2160	-1.2176	...	...

Tubesheet MDMT Calculations:

Shell Side MDMT calculation:

Governing thickness on the shell side per figure UCS-66.3 (e):
= max(tubesheet thk/4, min(tubesheet thk, shell thickness))
= max(52.0/4, min(52.0, 9.53))
= 13.000 mm

Thickness Ratio = 0.51, Temperature Reduction per Fig. UCS 66.1 = 31 °C

Min Metal Temp. w/o impact per UCS-66, Curve B -21 °C
Min Metal Temp. at Required thickness (UCS 66.1) -48 °C
Min Metal Temp. w/o impact per UG-20(f) -29 °C

Channel Side MDMT calculation:

Governing thickness for the channel side:
= tubesheet thickness/4
= 52.0/4
= 13.000 mm

Thickness Ratio = 0.51, Temperature Reduction per Fig. UCS 66.1 = 31 °C

Min Metal Temp. w/o impact per UCS-66, Curve B -21 °C



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 172 of 173

ASME TS Calc: DESIGN CASE

Case: 1 9:52a Aug 12, 2026

Min Metal Temp. at Required thickness (UCS 66.1) -48 °C

Min Metal Temp. w/o impact per UG-20(f) -29 °C

where the MDMT reduction ratio per UCS 66 (b)(1)(b) is:

= max(pt/Tubeside MAPnc, ps/Shellside MAPnc), must be ≤ 1

= max(1191.5/2336.28, 1549.5/5844.64)

= 0.510

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 401-E-33001-RP

Page 173 of 173

Problems/Failures Summary:

Step: 29 9:52am Aug 12, 2026

Noted issues for the current model:

Listed below are the known problem areas for the current design. If one or more of the design flags are turned on, please re-run the analysis. Some of these issues may be resolved when using updated input values.

**** Warning: A standard flange seems to be governing the Channelside MAWP!**

Please review all reports carefully!

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite[®] Pressure Vessel Design Notes

Project Information	
Project Number	
Client	
Date	
Designer	
Design Code	
Additional Standards	

Design Conditions		
Internal Design Pressure:		
External Design Pressure:		
Design Int. Temperature:		
Design Ext. Temperature:		
Corrosion Allowance:		

Vessel Geometry		
Vessel Type		
Diameter		
Tangent-to-Tangent Length		
Head Type		
Number of Segments		

Material Specifications	
Shell:	
Head:	
Nozzle:	

Nozzle/Opening Details	ID/OD	Size	Rating	Matl.	Reinf.

Miscellaneous		
Support Type		
Number of Supports		
Support Material		
Seismic Code		
Wind Code		
Insulation		
Pressure Test		
Radiography		
Fatigue Analysis		

Analysis Notes: