

Project Data Page:






Table of Contents

Cover Page	1
Vessel Design Summary:	2
Nozzle Summary:	5
Nozzle Schedule:	6
Bill of Material:	7
MDMT Summary:	8
Warnings and Errors:	10
Input Echo:	11
XY Coordinate Calculations:	22
Flg Calc [Int P]: New Flange	23
Flg Calc [Int P]: New Flange	31
Internal Pressure Calculations:	39
Element: LHS dish end	40
Element: LHS Ch Shell	43
Element: Main Shell	45
Element: RHS Ch Shell	48
Element: RHS Dish End	50
Shop Pressure Test Results:	53
Field Pressure Test Results:	55
ASME TS Calc: Pressure Test	57
External Pressure Calculations:	70
Element and Detail Weights:	74
Nozzle Flange MAWP:	77
Wind Load Calculation:	79
Earthquake Load Calculation:	81
Center of Gravity Calculation:	83
Saddle Calcs: Road Transport:	84
Saddle Calcs: Operating Case:	98
Saddle Calcs: Test Case:	114
Saddle Calcs: Ext. Pressure:	128
Nozzle Calcs.: N1-Tube Inlet	141
Nozzle Calcs.: N3-Shell inlet	153
Nozzle Calcs.: N4-Shell outlet	165
Nozzle Calcs.: N2-Tube Outlet	177
ASME TS Calc:	189
Problems/Failures Summary:	204



DESIGN CALCULATION

In Accordance with ASME Section VIII Division 1

ASME Code Version : 2025

Analysis Performed by : SL User

Job File : ...\\161-C1-C2 Stack.pvdb

Date of Analysis : Sep 9, 2026 9:40am

PV Elite 28, January 2026



PV Elite 28 Licensee: SL User
 FileName : 161-C1-C2 _(Stack) Page 2 of 204
 Vessel Design Summary: Step: 31 9:40am Sep 9,2026

Vessel Design Summary:

ASME Code, Section VIII Division 1, 2025

Diameter Spec : 188.951 mm ID
 Vessel Design Length, Tangent to Tangent 6786.95 mm
 Specified Datum Line Distance 50.80 mm
 Shell Side Design Temperature 260 °C
 Channel Side Design Temperature 270 °C
 Shell Side Design Pressure 2400.000 KPa.
 Channel Side Design Pressure 2400.000 KPa.
 Shop Shell Side Test Pressure 13260.004 KPa.
 Field Shell Side Test Pressure 3120.000 KPa.
 Shop Channel Side Test Pressure 10387.897 KPa.
 Field Channel Side Test Pressure 3120.000 KPa.
 Wind Design Code ASCE/SEI 7-16
 Earthquake Design Code ASCE/SEI 7-16

Materials of Construction:

Component Type	Material	Class	Thickness	UNS #	Material Treatment Options
Shell	SA-106 B	...	...	K03006	
Head	SA-516 70	...	...	K02700	
Flange	SA-105	...	...	K03504	
Nozzle	SA-106 B	...	...	K03006	
Re-Pad	SA-516 70	...	...	K02700	
Nozzle Flg	SA-105	...	...	K03504	
Rings	SA-516 70	...	...	K02700	
Tubes	SA-179	...	...	K01200	
Tubesheet	SA-266 2	...	...	K03506	
Flg Bolting	SA-193 B7	...	<= 64	G41400	
Hrz Bolting	SA-307 A	...	6 <= t <= 100		
Saddles	SA-516 70	...	...	K02700	

+FG - Fine Grained, +R - rolled, +T - Tempered, +N - Normalized
 +Q - quenched, +CBV - Cb & V added, +IT - Impact tested

Element Pressures and MAWP (KPa. & mm):

Element Description or Type	Design Pressure + Stat. head	Ext. Press.	Element M.A.W.P	Total Corrosion Allowance	Str. Flg. Gov.	In Creep Range
LHS dish end	2401.843	103.42	14749.000	3.0000	No	No
LHS Ch Shell	2401.843	103.42	11594.000	3.0000	N/A	No
LHS Ch Flange	2401.911	103.42	10275.000	3.0000	N/A	No
Main Shell	2401.843	103.42	11594.000	3.0000	N/A	No
RHS Ch Flg	2401.911	103.42	4588.000	3.0000	N/A	No
RHS Ch Shell	2401.843	103.42	11594.000	3.0000	N/A	No
RHS Dish End	2401.843	103.42	8765.000	3.0000	No	No

Liquid Level: 195.00 mm Dens.: 0.001 kg./cm³ Sp. Gr.: 1.000

Stiffener Ring Specifications:

Elevation mm Selected Type Ring Description



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)

Page 3 of 204

Vessel Design Summary:

Step: 31 9:40am Sep 9,2026

1655.17 Bar 21.5 x 20.0 Ring R1 Fr40
5105.17 Bar 21.5 x 20.0 Ring R2 Fr40

Element Types and Properties:

Element Type	"To" Elev mm	Element Length mm	Nominal Thickness mm	Finished Thickness mm	Reqd Thk Internal mm	Reqd Thk External mm	Long Eff	Circ Eff
Ellipse	0.0	50.8	15.1	13.2	4.6	...	1.00	1.00
Cylinder	300.0	300.0	15.1	13.2	5.0	...	1.00	1.00
Body Flg	385.2	82.0	68.0	56.0	48.4	...	1.00	1.00
Cylinder	6240.2	5785.0	15.1	13.2	5.0	...	1.00	1.00
Body Flg	6385.4	72.0	64.0	56.0	49.4	...	1.00	1.00
Cylinder	6685.4	300.0	15.1	13.2	5.0	...	1.00	1.00
Ellipse	6736.2	50.8	10.3	9.0	4.6	...	1.00	1.00

External Pressure Calculations:

From	To	External Actual T. mm	External Required T. mm	External Design Pressure KPa.	External M.A.W.P. KPa.
10	20	13.1794	3.58017	103.419	4980
20	30	13.1794	3.88937	103.419	6142
30	40	56	48.387	103.419	No Calc
40	Ring	13.1794	4.47193	103.419	5273
Ring	Ring	13.1794	4.93071	103.419	5197
Ring	50	13.1794	4.43819	103.419	5285
50	60	56	49.403	103.419	No Calc
60	70	13.1794	3.88937	103.419	6142
70	80	9.02335	3.55778	103.419	2842

External Pressure Calculations:

From	To	Actual Length Bet. Stiffeners mm	Allowable Length Bet. Stiffeners mm	Ring Inertia Required cm^4	Ring Inertia Available cm^4
10	20	No Calc	No Calc	No Calc	No Calc
20	30	366.546	19863.5	No Calc	No Calc
30	40	No Calc	No Calc	No Calc	No Calc
40	Ring	1200	60676.8	No Calc	No Calc
Ring	Ring	3450	173184	0.17742	8.05941
Ring	50	1135	57460.5	0.17494	8.05941
50	60	No Calc	No Calc	No Calc	No Calc
60	70	366.546	19863.5	No Calc	No Calc
70	80	No Calc	No Calc	No Calc	No Calc

Local Stress Analysis Results:

Description	Analysis Type	Max Stress Ratio	High Stress Location	Pass Fail
N1-Tube Inlet	WRC-297	0.656	Shell	Passed
N3-Shell inlet	WRC-297	0.656	Shell	Passed
N4-Shell outle	WRC-297	0.656	Shell	Passed
N2-Tube Outlet	WRC-297	0.656	Shell	Passed

Foundation/Support Summary

Saddle Parameters:



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)


Page 4 of 204

Vessel Design Summary:

Step: 31 9:40am Sep 9, 2026

Saddle Width	275.000	mm
Saddle Bearing Angle	120.000	deg.
Centerline Dimension	535.000	mm
Wear Pad Width	335.000	mm
Wear Pad Thickness	14.000	mm
Wear Pad Bearing Angle	132.000	deg.
Distance from Saddle to Tangent	1200.000	mm
Baseplate Length	600.000	mm
Baseplate Thickness	20.000	mm
Baseplate Width	300.000	mm
Number of Ribs (including outside ribs)	3	
Rib Thickness	14.000	mm
Web Thickness	14.000	mm
Height of Center Web	440.000	mm
Number of Bolts in Baseplate	4	

Baseplate Sketch



Maximum Tensile Bolt Load 150. Kgf

Summary of Maximum Saddle Loads, Operating Case, Un-Factored:

Maximum Vertical Saddle Load	10757.13	Kgf
Maximum Transverse Saddle Shear Load	1153.83	Kgf
Maximum Longitudinal Saddle Shear Load	300.00	Kgf

Summary of Maximum Saddle Loads, Pressure Test Case:

Maximum Vertical Saddle Load	2053.47	Kgf
Maximum Transverse Saddle Shear Load	41.65	Kgf
Maximum Longitudinal Saddle Shear Load	8.38	Kgf

Weights:

Fabricated - Bare w/o removable internals	3005.8	kg.
Shop Test - Fabricated + water (full)	3462.9	kg.
Shipping - Fab. + rem. intls.+ shipping app.	3005.8	kg.
Erected - Fab. + rem. intls.+ insul. (etc)	3005.8	kg.
Empty - Fab. + intls. + details + wghts.	3250.7	kg.
Operating - Empty + operating liquid (no ca)	3807.7	kg.
Field Test - Empty weight + test medium (full)	3604.9	kg.



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 5 of 204

Nozzle Summary:

Step: 29 9:40am Sep 9,2026

Nozzle Calculation Summary (KPa. & mm):

Description	MAWP	Ext	MAPNC	UG-45	[tr]	Weld Path	Areas or Stresses
N1-Tube Inlet	11594	...	...	OK	5.01	OK	No Calc[*]
N3-Shell inlet	11594	...	...	OK	5.01	OK	No Calc[*]
N4-Shell outlet	11594	...	...	OK	5.01	OK	No Calc[*]
N2-Tube Outlet	11594	...	...	OK	5.01	OK	No Calc[*]

Nozzle MAWP Summary:

Minimum MAWP Nozzles : 11594 Nozzle : N3-Shell inlet [Shellside]
 Minimum MAWP Nozzles : 11594 Nozzle : N1-Tube Inlet [Tubeside]

[*] - This was a small opening and the areas were not computed.

Note: MAWPs (Internal Case) shown above are at the High Point.

Multiple output lines for the same nozzle indicates required Code calculations in both the longitudinal and circumferential planes of reinforcement where applicable.

Check the spatial relationship between the nozzles:

From Node	Nozzle Description	X Coordinate mm	Layout Angle deg	Dia. Limit mm
20	N1-Tube Inlet	200.800	90.000	146.000
40	N3-Shell inlet	1105.975	90.000	146.000
40	N4-Shell outlet	5755.975	270.000	146.000
60	N2-Tube Outlet	6586.150	270.000	146.000

The nozzle spacing is computed by the following:

$$= \sqrt{ll^2 + lc^2} \text{ where}$$

ll - Arc length along the inside vessel surface in the long. direction.

lc - Arc length along the inside vessel surface in the circ. direction

If any interferences/violations are found, they will be noted below.

No interference violations have been detected!

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 6 of 204

Nozzle Schedule:

Step: 28 9:40am Sep 9,2026

Nozzle Schedule:

Description	Nominal or Actual Size	Schd or FVC Type	Flg Type	Nozzle O/Dia mm	Wall Thk mm	Reinforcing Pad Diameter	Pad Thk mm	Cut Length mm	Flg Class
N1-Tube Inlet	89 mm	Actual	WNF	89.0	11.000	129.00	14.00	224	600
N3-Shell inlet	89 mm	Actual	WNF	89.0	11.000	129.00	12.00	224	600
N4-Shell outlet	89 mm	Actual	WNF	89.0	11.000	129.00	12.00	224	600
N2-Tube Outlet	89 mm	Actual	WNF	89.0	11.000	129.00	12.00	224	600

General Notes for the above table:

The cut length is the outside projection + inside projection + drop + in-plane shell thickness. This value does not include weld gaps, nor does it account for shrinkage.

In the case of oblique nozzles, the outside diameter must be increased. The re-pad width around the nozzle is calculated as follows:

Width of Pad = (Pad Outside Dia. (per above) - Nozzle Outside Dia.)/2

For hub nozzles, the thickness and diameter shown are those of the smaller and thinner section.

Nozzle Material and Weld Fillet Leg Size Details (mm):

Description	Material	Shl Grve Weld	Noz Shl/Pad Weld	Pad OD Weld	Pad Grve Weld	Inside Weld
N1-Tube Inl	SA-106 B	10.000	12.000	10.000	14.000	...
N3-Shell in	SA-106 B	11.000	10.000	10.000	12.000	...
N4-Shell ou	SA-106 B	11.000	10.000	10.000	12.000	...
N2-Tube Out	SA-106 B	11.000	10.000	10.000	12.000	...

Note: The Outside projections below do not include the flange thickness.

Nozzle Miscellaneous Data:

Description	Elev/Distance From Datum mm	Layout Angle deg	Proj Outside mm	Proj Inside mm	Installed in Component
N1-Tube Inlet	150.000	90.0	200.00	0.00	LHS Ch Shell
N3-Shell inlet	1055.175	90.0	200.00	0.00	Main Shell
N4-Shell outlet	5705.175	270.0	200.00	0.00	Main Shell
N2-Tube Outlet	6535.350	270.0	200.00	0.00	RHS Ch Shell

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 7 of 204

Bill of Material:

Step: 27

9:40am

Sep 9,2026

Bill of Materials:

QTY	DESCRIPTION	MATERIAL
1	ELLIPTICAL HEAD: 2.0 X 1, 15.1mm THK X 189.0mm ID X 50.8mm	SA-516 70
2	CYLINDER: 15.1mm THK X 189.0mm ID X 300.0mm	SA-106 B
1	WELD NECK FLANGE: 68.0mm THK X 360.0mm OD	SA-105
1	CYLINDER: 15.1mm THK X 189.0mm ID X 5785.0mm	SA-106 B
1	WELD NECK FLANGE: 64.0mm THK X 360.0mm OD	SA-105
1	ELLIPTICAL HEAD: 2.0 X 1, 10.3mm THK X 189.0mm ID X 50.8mm	SA-516 70
2	INSULATION: 50mm X 100mm THK	Hot Insulation
2	INSULATION: 300mm X 100mm THK	Hot Insulation
1	INSULATION: 81mm X 100mm THK	Hot Insulation
10	BAFFLES: 204.0mm DIA X 6.0mm THK	SA-516 70
4	TIE RODS: 10mm DIA X 5000mm	SA-193 B7M
2	TUBESHEET: 360.0mm X 70.0mm THK	SA-266 2
81	TUBES: 6000.0mm X 12.7mm DIA X 2.1mm THK	SA-179
2	SADDLE: 275.0mm X 120 DEG	SA-516 70
1	INSULATION: 5780mm X 100mm THK	Hot Insulation
2	BAR RING STIFFENER: 215.3mm ID X 258.4mm OD X 20.0mm	SA-516 70
1	INSULATION: 83mm X 100mm THK	Hot Insulation
1	GASKET: 247.0mm OD X 221.0mm ID	...
24	BODY FLANGE BOLTS: 25.4mm DIA	SA-193 B7
24	NUTS FOR BODY FLANGE BOLTS: 25.4mm DIA	...
1	GASKET: 260.7mm OD X 234.7mm ID	...
1	NAMEPLATE	...



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 8 of 204

MDMT Summary:

Step: 30 9:40am Sep 9,2026

Minimum Design Metal Temperature Results Summary (°C):

Description	Curve	Basic MDMT	Reduced MDMT	UG-20(f) MDMT	Thickness ratio	Gov Thk mm	E*	PWHT reqd
Notes								
Main Shell [8]	B	-20	-104	-29	0.201	13.179	1.00	No
Ring R1 Fr40 [23]	B	-20	-48	-29	0.417	13.179	1.00	No
Ring R2 Fr40 [23]	B	-20	-48	-29	0.417	13.179	1.00	No
LH floating s[24]	B	-20	-48	-29	0.417	13.179	1.00	No
RH fixed sadd[24]	B	-20	-48	-29	0.417	13.179	1.00	No
N3-Shell inlet[1]	B	-5	-104	-29	0.112	11.000	1.00	No
Nozzle Flg [5]	A	-18	-104					
N4-Shell outle[1]	B	-5	-104	-29	0.112	11.000	1.00	No
Nozzle Flg [5]	A	-18	-104					
Tubesheet: SS[13]	B	-11	-104	-29	0.234	17.500	1.00	No
Warmest MDMT:		-5	-48					
LHS Ch Flange[11]	A	0	-104		0.338	13.179	1.00	No
RHS Ch Flg [11]	A	-8	-104	-29	0.338	7.156	1.00	No
LHS dish end [10]	B	-20	-104	-29	0.307	13.179	1.00	No
LHS dish end [7]	B	-16	-104	-29	0.274	15.062	1.00	No
LHS Ch Shell [8]	B	-20	-104	-29	0.185	13.179	1.00	No
RHS Ch Shell [8]	B	-20	-104	-29	0.185	13.179	1.00	No
RHS Dish End [10]	B	-29	-48	-29	0.519	9.023	1.00	No
RHS Dish End [7]	B	-28	-48	-29	0.452	10.312	1.00	No
N1-Tube Inlet [1]	B	-5	-104	-29	0.112	11.000	1.00	No
Nozzle Flg [5]	A	-18	-104					
N2-Tube Outlet[1]	B	-5	-104	-29	0.112	11.000	1.00	No
Nozzle Flg [5]	A	-18	-104					
Tubesheet: CS[14]	B	-11	-104	-29	0.234	17.500	1.00	No
Bolting [21]		-48						
Bolting [21]		-48						
Warmest MDMT:		0	-48					

Exchanger Side	Computed MDMT	Required MDMT	Pass/Fail
Shell	-48.0	-12.0	Pass
Channel/Tube	-48.0	-12.0	Pass

Notes:

- [!] - This was an impact tested material.
- [1] - Governing Nozzle Weld.
- [4] - ASME Flange MDMT Calcs; Thickness ratio per UCS-66(b)(1)(-c).
- [5] - ASME Flange MDMT Calcs; Thickness ratio per UCS-66(b)(1)(-b).
- [6] - MDMT Calculations at the Shell/Head Joint.
- [7] - MDMT Calculations for the Straight Flange.
- [8] - Cylinder/Cone/Flange Junction MDMT.
- [9] - Calculations in the Spherical Portion of the Head.
- [10] - Calculations in the Knuckle Portion of the Head.
- [11] - Calculated (Body Flange) Flange MDMT.
- [12] - Calculated Flat Head MDMT per UCS-66.3
- [13] - Tubesheet MDMT, shell side, if applicable
- [14] - Tubesheet MDMT, tube side, if applicable
- [15] - Nozzle Material
- [16] - Shell or Head Material
- [17] - Impact Testing required
- [18] - Impact Testing not required, see UCS-66(b)(3)
- [20] - Cylinder/Cone Junction MDMT based on Longitudinal Stress considerations
- [21] - Body Flange Bolting Material
- [22] - Nozzle Flange Bolting Material



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 9 of 204

MDMT Summary:

Step: 30 9:40am Sep 9, 2026

[23] - Stiffening Ring to Shell Weld

[24] - Saddle to Shell Weld

UG-84(b)(2) was not considered.

UCS-66(g) was not considered.

UCS-66(i) was not considered.

Notes:

Impact test temps were not entered in and not considered in the analysis.

UCS-66(i) applies to impact tested materials not by specification and

UCS-66(g) applies to materials impact tested per UG-84.1 General Note (c).

The Basic MDMT includes the (30F) PWHT credit if applicable.

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 10 of 204

Warnings and Errors:

Step: 0 9:40am Sep 9,2026

Class From To : Basic Element Checks.

Class From To: Check of Additional Element Data

Warning:

There is a flange in this model connected to an element whose temperature is different. The bolt allowable stress is based on it's parent design temperature. You may need to manually adjust the operating bolt allowable stress to a value based upon a representative maximum temperature the bolts will be subject to.

There were no geometry errors or warnings.

PV Elite performs all calculations internally in Imperial Units to remain compliant with the ASME Code and any built in assumptions in the ASME Code formulas. The finalized results are reflected to show the set of selected units for this analysis.

Information Regarding Nozzle Loads

Please note that nozzle loadings, if included, are assumed to be local in nature and will not contribute to or create a net section bending moment. Therefore, the addition of nozzle loads will not affect the support load calculation. If you wish to create a load on the support(s) from nozzle loads, you can enable that feature in tools->configuration->Job Specific Settings.



One or more nozzles in this model was specified using the actual thickness basis and a standard flange is also specified. In many cases a matching nominal diameter cannot be determined and the weight of the flange and optional blind flange cannot be determined. When actual thickness basis is specified, you must calculate the weight of the assembly (by hand) and enter it into the 'Overriding Weight' field in the nozzle dialog when there is a standard flange specified. However, for FVC nozzles that have their nominal diameter specified in the FVC dialog, entering the overriding weight for that nozzle is not required.



The ASME Code Section VIII Division 1 does not explicitly require stresses on elements to be computed under test conditions. Please see interpretation VIII-1-10-12 for more information. PV Elite also computes weight due to test fluid and uses the weight in various calculations such as saddle and leg loads. PV Elite also computes static pressure due to operating and test liquids. The static pressure is used in conjunction with the design and test pressures to determine a total pressure in the determination of required thickness, MAWP etc. This ensures compliance with UG-22 requirements.

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 11 of 204

Input Echo:

Step: 1

9:40am

Sep 9, 2026

Units used in this Analysis (MM):

Name	System Unit	Constant	User Unit
Length	Feet	304.8000	mm
Force	Pounds	0.4536	Kgf
Mass	Pounds	0.4536	kg.
Area	sq. inches	6.4516	cm ²
Moment	ft. lbs.	0.1383	Kg-m.
Stress	lbs./sq.in.	0.0069	N./mm ²
Temperature	Degrees F	0.5556	°C
Pressure	psig	6.8946	KPa.
Elast. Modulus	lbs./sq.in.	6.8946	KPa.
Pipe Density	lbs./cu.in.	0.0277	kg./cm ³
Ins. Density	lbs./cu.ft.	0.1600E-04	kg./cm ³
Fluid Density	lbs./cu.ft.	0.1600E-04	kg./cm ³
Wind Speed	miles/hr	1.6093	Km/hr
Tray Weight	lbs./sq.ft.	0.0005	Kgs/cm ²
Inertia	in.4	41.6231	cm4
G Load	G's	1.0000	g's
Wind Load	lbs./sq.ft.	4.8825	Kgs/m ²
Elevation	Feet	304.8000	mm
Volume	in.3	16.3900	cm ³
Diameter	inches	25.4000	mm
Thickness	inches	25.4000	mm

PV Elite Vessel Analysis Program: Input Data

Exchanger Design Pressures and Temperatures

Shell Side Design Pressure	2400	KPa.
Channel Side Design Pressure	2400	KPa.
Shell Side Design Temperature	260.0	°C
Channel Side Design Temperature	270.0	°C
Radiography, Shell Side	RT-1	
Radiography, Channel Side	RT-1	
Service Type, Shell Side	None	
Service Type, Channel Side	None	
MDMT (CET), Shell Side	-12.0	°C
MDMT (CET), Tube Side	-12.0	°C
User defined MAWP, Shell Side	0	KPa.
User defined MAWP, Channel Side	0	KPa.
User defined MAPnc, Shell Side	0	KPa.
User defined MAPnc, Channel Side	0	KPa.
User defined Test Pres., Shell Side	0	KPa.
User defined Test Pres., Channel Side	0	KPa.

Projection of Nozzle from Vessel Top	0	mm
Projection of Nozzle from Vessel Bottom	0	mm
Type of Construction	Welded	
Use Higher Longitudinal Stresses (Flag)	Y	
Select t for Internal Pressure (Flag)	N	
Select t for External Pressure (Flag)	N	
Select t for Axial Stress (Flag)	N	
Select Location for Stiff. Rings (Flag)	N	
Consider Vortex Shedding	N	

Shop Pressure Test:

Type of Pressure Test	UG-99(c)
Pressure Test Position	Horizontal
Test Performed in Corroded Condition	Yes



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 12 of 204

Input Echo:

Step: 1 9:40am Sep 9,2026

Field Pressure Test:

Type of Pressure Test UG-99(b) Note [35]
 Pressure Test Position Horizontal
 Test Performed in Corroded Condition Yes

Load Case 1	NP+EW+WI+FW+BW
Load Case 2	NP+EW+EE+FS+BS
Load Case 3	NP+OW+WI+FW+BW
Load Case 4	NP+OW+EQ+FS+BS
Load Case 5	NP+HW+HI
Load Case 6	NP+HW+HE
Load Case 7	IP+OW+WI+FW+BW
Load Case 8	IP+OW+EQ+FS+BS
Load Case 9	EP+OW+WI+FW+BW
Load Case 10	EP+OW+EQ+FS+BS
Load Case 11	HP+HW+HI
Load Case 12	HP+HW+HE
Load Case 13	IP+WE+EW
Load Case 14	IP+WF+CW
Load Case 15	IP+VO+OW
Load Case 16	IP+VE+EW
Load Case 17	NP+VO+OW
Load Case 18	FS+BS+IP+OW
Load Case 19	FS+BS+EP+OW
Load Case 20	BL+IP+OW

Wind Design Code	ASCE/SEI 7-16	
Wind Load Reduction Scale Factor	1.100	
Basic Wind Speed	97.2	Km/hr
Surface Roughness Category	C: Open Terrain	
Type of Surface	Moderately Smooth	
Base Elevation	300	mm
Percent Wind for Hydrotest	50.0	
Using User defined Wind Press. Vs Elev.	N	
Height of Hill or Escarpment	0	mm
Distance Upwind of Crest	0	mm
Distance from Crest to the Vessel	0	mm
Type of Terrain (Hill, Escarpment)	Flat	
Damping Factor (Beta) for Wind (Ope)	0.0100	
Damping Factor (Beta) for Wind (Empty)	0.0000	
Damping Factor (Beta) for Wind (Filled)	0.0000	
Site Elevation above Sea Level	0	mm

Seismic Design Code	ASCE/SEI 7-16	
Seismic Load Reduction Scale Factor	1.000	
Importance Factor	1.250	
Table Value Fa	1.600	
Table Value Fv	2.400	
Max. Mapped Res. Acceleration	0.147	[Ss]
Max. Eff. Ground Acceleration	0.065	[S]
Force Modification Factor R	3.000	
Site Class	D	
Component Elevation Ratio	0.000	z/h
Amplification Factor	1.000	Ap
Force Factor	0.000	
Consider Vertical Acceleration	Yes	
Minimum Acceleration Multiplier	0.000	
User Value of Sds (used if > 0)	0.000	
User Value of Sd1 (used if > 0)	0.000	
Moment Reduction Factor Tau	1.000	

Design Pressure + Static Head	Y
Consider MAP New and Cold in Noz. Design	N
Consider External Loads for Nozzle Des.	Y



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 13 of 204

Input Echo:

Step: 1 9:40am Sep 9, 2026

Use ASME VIII-1 Appendix 1-9 N

Perform Blast Load Analysis No

Material Database Year Current w/Addenda or Code Year

Configuration Directives:

g0 is taken as min(g0, attached shell thk) Yes

Do not use Nozzle MDMT Interpretation VIII-1 01-37 No

Use Table G instead of exact equation for "A" Yes

Shell Head Joints are Tapered Yes

Compute "K" in corroded condition Yes

Use Code Case 2286 No

Use the MAWP to compute the MDMT Yes

For thickness ratios <= 0.35, MDMT will be -155F (-104C) Yes

For PWHT & P1 Materials the MDMT can be < -55F (-48C) No

Using Metric Material Databases, ASME II D Yes

Calculate B31.3 type stress for Nozzles with Loads Yes

Reduce the MDMT due to lower membrane stress Yes

Consider Longitudinal Stress in MDMT Calculations Yes

Complete Listing of Vessel Elements and Details:

Element#	1/7	
Element From Node	10	
Element To Node	20	
Element Type	Elliptical	
Description	LHS dish end	
Distance "FROM" to "TO"	50.8	mm
Inside Diameter	188.95	mm
Element Thickness	13.179	mm
Internal Corrosion Allowance	3	mm
Nominal Thickness	15.062	mm
External Corrosion Allowance	0	mm
Design Internal Pressure	2400	KPa.
Design Temperature Internal Pressure	270	°C
Design External Pressure	103.42	KPa.
Design Temperature External Pressure	270	°C
Effective Diameter Multiplier	1.2	
Material Name	SA-516 70	
Allowable Stress, Ambient	138	N./mm ²
Allowable Stress, Operating	137.2	N./mm ²
Allowable Stress, Hydrotest	234	N./mm ²
Material Density	0.00775	kg./cm ³
P Number Thickness	32.004	mm
Yield Stress, Operating	211.2	N./mm ²
UCS-66 Chart Curve Designation	B	
External Pressure Chart Name	CS-2	
UNS Number	K02700	
Product Form	Plate	
Efficiency, Longitudinal Seam	1.0	
Efficiency, Circumferential Seam	1.0	
Elliptical Head Factor	2.0	
Weld is pre-Heated	No	
Element From Node	10	
Detail Type	Liquid	
Detail ID	Liquid: 10	
Dist. from "FROM" Node / Offset dist	0	mm
Height/Length of Liquid	185	mm
Liquid Density	0.0009984	kg./cm ³
Element From Node	10	
Detail Type	Insulation	



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 14 of 204

Input Echo:

Step: 1 9:40am Sep 9,2026

Detail ID	Insulation
Dist. from "FROM" Node / Offset dist	0 mm
Height/Length of Insulation	50.8 mm
Thickness of Insulation	100 mm
Density	0.000352 kg./cm ³

Element#	2/7
Element From Node	20
Element To Node	30
Element Type	Cylinder
Description	LHS Ch Shell
Distance "FROM" to "TO"	300 mm
Inside Diameter	188.95 mm
Element Thickness	13.179 mm
Internal Corrosion Allowance	3 mm
Nominal Thickness	15.062 mm
External Corrosion Allowance	0 mm
Design Internal Pressure	2400 KPa.
Design Temperature Internal Pressure	270 °C
Design External Pressure	103.42 KPa.
Design Temperature External Pressure	270 °C
Effective Diameter Multiplier	1.2
Material Name	SA-106 B
Allowable Stress, Ambient	118 N./mm ²
Allowable Stress, Operating	118 N./mm ²
Allowable Stress, Hydrotest	216 N./mm ²
Material Density	0.00775 kg./cm ³
P Number Thickness	32.004 mm
Yield Stress, Operating	194.8 N./mm ²
UCS-66 Chart Curve Designation	B
External Pressure Chart Name	CS-2
UNS Number	K03006
Product Form	Smls. pipe
Efficiency, Longitudinal Seam	1.0
Efficiency, Circumferential Seam	1.0
Weld is pre-Heated	No

Element From Node	20
Detail Type	Liquid
Detail ID	Liquid: 20
Dist. from "FROM" Node / Offset dist	0 mm
Height/Length of Liquid	185 mm
Liquid Density	0.0009984 kg./cm ³

Element From Node	20
Detail Type	Insulation
Detail ID	Insulation
Dist. from "FROM" Node / Offset dist	0 mm
Height/Length of Insulation	300 mm
Thickness of Insulation	100 mm
Density	0.000352 kg./cm ³

Element From Node	20
Detail Type	Nozzle
Detail ID	N1-Tube Inlet
Dist. from "FROM" Node / Offset dist	150 mm
Nozzle Diameter	89 mm
Nozzle Schedule	160
Nozzle Class	600
Layout Angle	90.0
Blind Flange (Y/N)	N
Weight of Nozzle (Used if > 0)	23.851 Kg
Grade of Attached Flange	GR 1.1



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 15 of 204

Input Echo:

Step: 1 9:40am Sep 9,2026

Nozzle Matl

SA-106 B

Element#	3/7
Element From Node	30
Element To Node	40
Element Type	Flange
Description	LHS Ch Flange
Distance "FROM" to "TO"	82 mm
Flange Inside Diameter	188.95 mm
Element Thickness	56 mm
Internal Corrosion Allowance	3 mm
Nominal Thickness	68 mm
External Corrosion Allowance	0 mm
Design Internal Pressure	2400 KPa.
Design Temperature Internal Pressure	270 °C
Design External Pressure	103.42 KPa.
Design Temperature External Pressure	270 °C
Effective Diameter Multiplier	1.2
Material Name	SA-105
Allowable Stress, Ambient	138 N./mm ²
Allowable Stress, Operating	133.2 N./mm ²
Allowable Stress, Hydrotest	225 N./mm ²
Material Density	0.00775 kg./cm ³
P Number Thickness	32.004 mm
Yield Stress, Operating	200 N./mm ²
UCS-66 Chart Curve Designation	A
External Pressure Chart Name	CS-2
UNS Number	K03504
Product Form	Forgings
Perform Flange Stress Calculation (Y/N)	Y
Weld is pre-Heated	No

Element From Node	30
Detail Type	Liquid
Detail ID	Liquid: 30
Dist. from "FROM" Node / Offset dist	0 mm
Height/Length of Liquid	195 mm
Liquid Density	0.0009984 kg./cm ³

Element From Node	30
Detail Type	Insulation
Detail ID	Insulation
Dist. from "FROM" Node / Offset dist	0 mm
Height/Length of Insulation	82 mm
Thickness of Insulation	100 mm
Density	0.000352 kg./cm ³

Element From Node	30
Detail Type	For./Mom.
Detail ID	TOP HE FORCE
Dist. from "FROM" Node / Offset dist	155.17 mm
Force in X Direction	25 Kg
Force in Y Direction	0 Kg
Force in Z Direction	245 Kg
Moment about X Axis	0 Kg-m.
Moment about Y Axis	0 Kg-m.
Moment about Z Axis	0 Kg-m.
Force/Moment Combination Method	SRSS

Element From Node	30
Detail Type	For./Mom.
Detail ID	TOP HE FORCE
Dist. from "FROM" Node / Offset dist	155.17 mm



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 16 of 204

Input Echo:

Step: 1 9:40am Sep 9, 2026

Force in X Direction	150	Kgf
Force in Y Direction	0	Kgf
Force in Z Direction	150	Kgf
Moment about X Axis	0	Kg-m.
Moment about Y Axis	0	Kg-m.
Moment about Z Axis	0	Kg-m.
Force/Moment Combination Method	SRSS	

Element From Node	30	
Detail Type	For./Mom.	
Detail ID	TOP HE FORCE	
Dist. from "FROM" Node / Offset dist	155.17	mm
Force in X Direction	25	Kgf
Force in Y Direction	0	Kgf
Force in Z Direction	245	Kgf
Moment about X Axis	0	Kg-m.
Moment about Y Axis	0	Kg-m.
Moment about Z Axis	0	Kg-m.
Force/Moment Combination Method	SRSS	

Element From Node	30	
Detail Type	For./Mom.	
Detail ID	TOP HE FORCE	
Dist. from "FROM" Node / Offset dist	155.17	mm
Force in X Direction	150	Kgf
Force in Y Direction	0	Kgf
Force in Z Direction	150	Kgf
Moment about X Axis	0	Kg-m.
Moment about Y Axis	0	Kg-m.
Moment about Z Axis	0	Kg-m.
Force/Moment Combination Method	SRSS	

Element#	4/7
Element From Node	40
Element To Node	50
Element Type	Cylinder
Description	Main Shell
Distance "FROM" to "TO"	5785 mm
Inside Diameter	188.95 mm
Element Thickness	13.179 mm
Internal Corrosion Allowance	3 mm
Nominal Thickness	15.062 mm
External Corrosion Allowance	0 mm
Design Internal Pressure	2400 KPa.
Design Temperature Internal Pressure	260 °C
Design External Pressure	103.42 KPa.
Design Temperature External Pressure	260 °C
Effective Diameter Multiplier	1.2
Material Name	SA-106 B
Allowable Stress, Ambient	118 N./mm ²
Allowable Stress, Operating	118 N./mm ²
Allowable Stress, Hydrotest	216 N./mm ²
Material Density	0.00775 kg./cm ³
P Number Thickness	32.004 mm
Yield Stress, Operating	196.4 N./mm ²
UCS-66 Chart Curve Designation	B
External Pressure Chart Name	CS-2
UNS Number	K03006
Product Form	Smls. pipe
Efficiency, Longitudinal Seam	1.0
Efficiency, Circumferential Seam	1.0
Weld is pre-Heated	No



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 17 of 204

Input Echo:

Step: 1 9:40am Sep 9,2026

Element From Node	40
Detail Type	Saddle
Detail ID	LH floating sad
Dist. from "FROM" Node / Offset dist	1200 mm
Width of Saddle	275 mm
Height of Saddle at Bottom	535 mm
Saddle Contact Angle	120.0
Height of Composite Ring Stiffener	0 mm
Width of Wear Plate	335 mm
Thickness of Wear Plate	14 mm
Contact Angle, Wear Plate (degrees)	132.0
Friction coefficient	0.3000001
Moment Factor	3.0
Dimension E at base (optional)	0 mm
Circumferential Eff. over Saddle	1.0
Circumferential Eff. at Midspan	1.0
Tangent to Tangent dist. (optional)	0 mm

Element From Node	40
Detail Type	Saddle
Detail ID	RH fixed saddle
Dist. from "FROM" Node / Offset dist	4650 mm
Width of Saddle	275 mm
Height of Saddle at Bottom	535 mm
Saddle Contact Angle	120.0
Height of Composite Ring Stiffener	0 mm
Width of Wear Plate	335 mm
Thickness of Wear Plate	14 mm
Contact Angle, Wear Plate (degrees)	132.0
Friction coefficient	0.0
Moment Factor	3.0
Dimension E at base (optional)	0 mm
Circumferential Eff. over Saddle	1.0
Circumferential Eff. at Midspan	1.0
Tangent to Tangent dist. (optional)	0 mm

Element From Node	40
Detail Type	Liquid
Detail ID	Liquid: 50
Dist. from "FROM" Node / Offset dist	0 mm
Height/Length of Liquid	185 mm
Liquid Density	0.0009984 kg./cm³

Element From Node	40
Detail Type	Insulation
Detail ID	Insulation
Dist. from "FROM" Node / Offset dist	0 mm
Height/Length of Insulation	5780 mm
Thickness of Insulation	100 mm
Density	0.000352 kg./cm³

Element From Node	40
Detail Type	Ring
Detail ID	Ring R1 Fr40
Dist. from "FROM" Node / Offset dist	1200 mm
Inside Diameter of Ring	215.31 mm
Thickness of Ring	20 mm
Outside Diameter of Ring	258.37 mm
Material Name	SA-516 70
Height of Section Ring	0 mm
Using Custom Stiffener Section	No

Element From Node	40
Detail Type	Ring
Detail ID	Ring R2 Fr40



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 18 of 204

Input Echo:

Step: 1 9:40am Sep 9,2026

Dist. from "FROM" Node / Offset dist	4650	mm
Inside Diameter of Ring	215.31	mm
Thickness of Ring	20	mm
Outside Diameter of Ring	258.37	mm
Material Name	SA-516 70	
Height of Section Ring	0	mm
Using Custom Stiffener Section	No	

Element From Node	40	
Detail Type	Nozzle	
Detail ID	N3-Shell inlet	
Dist. from "FROM" Node / Offset dist	600	mm
Nozzle Diameter	89	mm
Nozzle Schedule	160	
Nozzle Class	600	
Layout Angle	90.0	
Blind Flange (Y/N)	N	
Weight of Nozzle (Used if > 0)	23.851	Kgf
Grade of Attached Flange	GR 1.1	
Nozzle Matl	SA-106 B	

Element From Node	40	
Detail Type	Nozzle	
Detail ID	N4-Shell outlet	
Dist. from "FROM" Node / Offset dist	5250	mm
Nozzle Diameter	89	mm
Nozzle Schedule	160	
Nozzle Class	600	
Layout Angle	270.0	
Blind Flange (Y/N)	N	
Weight of Nozzle (Used if > 0)	23.851	Kgf
Grade of Attached Flange	GR 1.1	
Nozzle Matl	SA-106 B	

Element From Node	40	
Detail Type	Weight	
Detail ID	TOP HE EMPTY	
Dist. from "FROM" Node / Offset dist	2944.8	mm
Miscellaneous Weight	1500	Kgf
Offset from Element Centerline	1070	mm

Element From Node	40	
Detail Type	Weight	
Detail ID	TOP HE OPERATIN	
Dist. from "FROM" Node / Offset dist	2943.5	mm
Miscellaneous Weight	400	Kgf
Offset from Element Centerline	1070	mm

Element From Node	40	
Detail Type	Weight	
Detail ID	TOP HE TEST	
Dist. from "FROM" Node / Offset dist	2945.7	mm
Miscellaneous Weight	300	Kgf
Offset from Element Centerline	1070	mm

Element#	5/7	
Element From Node	50	
Element To Node	60	
Element Type	Flange	
Description	RHS Ch Flg	
Distance "FROM" to "TO"	72	mm
Flange Inside Diameter	202.72	mm
Element Thickness	56	mm



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 19 of 204

Input Echo:

Step: 1 9:40am Sep 9,2026

Internal Corrosion Allowance	3	mm
Nominal Thickness	64	mm
External Corrosion Allowance	0	mm
Design Internal Pressure	2400	KPa.
Design Temperature Internal Pressure	260	°C
Design External Pressure	103.42	KPa.
Design Temperature External Pressure	260	°C
Effective Diameter Multiplier	1.2	
Material Name	SA-105	
Allowable Stress, Ambient	138	N./mm ²
Allowable Stress, Operating	134.6	N./mm ²
Allowable Stress, Hydrotest	225	N./mm ²
Material Density	0.00775	kg./cm ³
P Number Thickness	32.004	mm
Yield Stress, Operating	202	N./mm ²
UCS-66 Chart Curve Designation	A	
External Pressure Chart Name	CS-2	
UNS Number	K03504	
Product Form	Forgings	
Perform Flange Stress Calculation (Y/N)	Y	
Weld is pre-Heated	No	

Element From Node	50
Detail Type	Liquid
Detail ID	Liquid: 60
Dist. from "FROM" Node / Offset dist	0 mm
Height/Length of Liquid	195 mm
Liquid Density	0.0009984 kg./cm ³

Element From Node	50
Detail Type	Insulation
Detail ID	Insulation
Dist. from "FROM" Node / Offset dist	0 mm
Height/Length of Insulation	83 mm
Thickness of Insulation	100 mm
Density	0.000352 kg./cm ³

Element#	6/7
Element From Node	60
Element To Node	70
Element Type	Cylinder
Description	RHS Ch Shell
Distance "FROM" to "TO"	300 mm
Inside Diameter	188.95 mm
Element Thickness	13.179 mm
Internal Corrosion Allowance	3 mm
Nominal Thickness	15.062 mm
External Corrosion Allowance	0 mm
Design Internal Pressure	2400 KPa.
Design Temperature Internal Pressure	270 °C
Design External Pressure	103.42 KPa.
Design Temperature External Pressure	270 °C
Effective Diameter Multiplier	1.2
Material Name	SA-106 B
Allowable Stress, Ambient	118 N./mm ²
Allowable Stress, Operating	118 N./mm ²
Allowable Stress, Hydrotest	216 N./mm ²
Material Density	0.00775 kg./cm ³
P Number Thickness	32.004 mm
Yield Stress, Operating	194.8 N./mm ²
UCS-66 Chart Curve Designation	B
External Pressure Chart Name	CS-2
UNS Number	K03006



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 20 of 204

Input Echo:

Step: 1 9:40am Sep 9,2026

Product Form	Smls. pipe
Efficiency, Longitudinal Seam	1.0
Efficiency, Circumferential Seam	1.0
Weld is pre-Heated	No
Element From Node	60
Detail Type	Liquid
Detail ID	Liquid: 80
Dist. from "FROM" Node / Offset dist	0 mm
Height/Length of Liquid	185 mm
Liquid Density	0.0009984 kg./cm ³
Element From Node	60
Detail Type	Insulation
Detail ID	Insulation
Dist. from "FROM" Node / Offset dist	0 mm
Height/Length of Insulation	300 mm
Thickness of Insulation	100 mm
Density	0.000352 kg./cm ³
Element From Node	60
Detail Type	Nozzle
Detail ID	N2-Tube Outlet
Dist. from "FROM" Node / Offset dist	150 mm
Nozzle Diameter	89 mm
Nozzle Schedule	160
Nozzle Class	600
Layout Angle	270.0
Blind Flange (Y/N)	N
Weight of Nozzle (Used if > 0)	23.851 Kg
Grade of Attached Flange	GR 1.1
Nozzle Matl	SA-106 B

Element#	7/7
Element From Node	70
Element To Node	80
Element Type	Elliptical
Description	RHS Dish End
Distance "FROM" to "TO"	50.8 mm
Inside Diameter	188.95 mm
Element Thickness	9.0233 mm
Internal Corrosion Allowance	3 mm
Nominal Thickness	10.312 mm
External Corrosion Allowance	0 mm
Design Internal Pressure	2400 KPa.
Design Temperature Internal Pressure	270 °C
Design External Pressure	103.42 KPa.
Design Temperature External Pressure	270 °C
Effective Diameter Multiplier	1.2
Material Name	SA-516 70
Allowable Stress, Ambient	138 N./mm ²
Allowable Stress, Operating	137.2 N./mm ²
Allowable Stress, Hydrotest	234 N./mm ²
Material Density	0.00775 kg./cm ³
P Number Thickness	32.004 mm
Yield Stress, Operating	211.2 N./mm ²
UCS-66 Chart Curve Designation	B
External Pressure Chart Name	CS-2
UNS Number	K02700
Product Form	Plate
Efficiency, Longitudinal Seam	1.0
Efficiency, Circumferential Seam	1.0
Elliptical Head Factor	2.0



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 21 of 204

Input Echo:

Step: 1 9:40am Sep 9,2026

Weld is pre-Heated	No
Element From Node	70
Detail Type	Liquid
Detail ID	Liquid: 90
Dist. from "FROM" Node / Offset dist	0 mm
Height/Length of Liquid	185 mm
Liquid Density	0.0009984 kg./cm ³
Element From Node	70
Detail Type	Insulation
Detail ID	Insulation
Dist. from "FROM" Node / Offset dist	0 mm
Height/Length of Insulation	50.8 mm
Thickness of Insulation	100 mm
Density	0.000352 kg./cm ³

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 22 of 204

XY Coordinate Calculations:

Step: 2 9:40am

Sep 9, 2026

XY Coordinate Calculations:

From	To	X (Horiz.) mm	Y (Vert.) mm	DX (Horiz.) mm	DY (Vert.) mm
LHS dish end		50.8	...	50.8	...
LHS Ch Shell		350.8	...	300	...
LHS Ch Flange		435.975	...	82	...
Main Shell		6290.98	...	5785	...
RHS Ch Flg		6436.15	...	72	...
RHS Ch Shell		6736.15	...	300	...
RHS Dish End		6786.95	...	50.8	...

The calculated dimensions are based on the given element lengths. Due to variability in manufacturing (weld gaps etc.), the Tangent to Tangent length may not be exact. The length includes gasket thicknesses and raised face heights.

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 23 of 204

Flg Calc [Int P]: New Flange


Flng: 5 9:40am Sep 9,2026

Flange Input Data Values

Description: New Flange :

LHS Ch Flange

Flange Type	Integral Weld Neck		
Design Pressure	P	2401.91	KPa.
Design Temperature		270	°C
Internal Corrosion Allowance	ci	3.0000	mm
External Corrosion Allowance	ce	0.0000	mm
Use Corrosion Allowance in Thickness Calcs.		Yes	
Flange Inside Diameter	B	188.951	mm
Flange Outside Diameter	A	360.000	mm
Flange Thickness	t	56.0000	mm
Thickness of Hub at Small End	go	13.1794	mm
Thickness of Hub at Large End	g1	20.0000	mm
Length of Hub	h	26.0000	mm
Flange Material		SA-105	
Flange Material UNS number		K03504	
Flange Allowable Stress At Temperature	Sfo	133.20	N./mm ²
Flange Allowable Stress At Ambient	Sfa	138.00	N./mm ²
Bolt Material		SA-193 B7	
Bolt Allowable Stress At Temperature	Sb	172.00	N./mm ²
Bolt Allowable Stress At Ambient	Sa	172.00	N./mm ²
Diameter of Bolt Circle	C	300.000	mm
Nominal Bolt Diameter	a	25.4000	mm
Type of Threads	UNC Thread Series		
Number of Bolts		12	
Flange Face Outside Diameter	Fod	257.951	mm
Flange Face Inside Diameter	Fid	188.951	mm
Flange Facing Sketch		Sketch 1a	
Gasket Outside Diameter	Go	246.951	mm
Gasket Inside Diameter	Gi	220.951	mm
Gasket Factor	m	3.0000	
Gasket Design Seating Stress	y	68.95	N./mm ²
Gasket Thickness	tg	3.1750	mm
Raised face depth	Fd	0.0000	mm





PV Elite 28 Licensee: SL User
 FileName : 161-C1-C2 _(Stack) Page 24 of 204
 Flg Calc [Int P]: New Flange Flng: 5 9:40am Sep 9,2026

ASME Code, Section VIII Division 1, 2025

Hub Small End Required Thickness due to Internal Pressure:

$$= (P \cdot (D/2 + Ca)) / (S \cdot E - 0.6 \cdot P) \text{ per UG-27 (c)(1)}$$

$$= (2402 \cdot (189/2 + 3)) / (118 \cdot 1 - 0.6 \cdot 2402) + Ca$$

$$= 5.0088 \text{ mm}$$

Small End Hub MAWP:

$$= (S \cdot E \cdot t) / (R + 0.6 \cdot t) \text{ per UG-27 (c)(1)}$$

$$= (118 \cdot 1 \cdot 10.2) / (97.5 + 0.6 \cdot 10.2)$$

$$= 11595.303 \text{ KPa.}$$

Hub Small End Hub MAPnc:

$$= (Sa \cdot E \cdot t) / (R + 0.6 \cdot t) \text{ per UG-27 (c)(1)}$$

$$= (118 \cdot 1 \cdot 13.2) / (94.5 + 0.6 \cdot 13.2)$$

$$= 15188.544 \text{ KPa.}$$

Corroded Flange Thickness, $t_c = T - c_i$	53.000 mm
Corroded Flange ID, $B_{cor} = B + 2 \cdot c_i$	194.951 mm
Corroded Large Hub, $g1_{cor} = g1 - c_i$	17.000 mm
Corroded Small Hub, $g0_{cor} = g0 - c_i$	10.179 mm
Code R Dimension, $R = ((C - B_{cor})/2) - g1_{cor}$	35.525 mm

Gasket Contact Width, $N = (G_o - G_i)/2$	13.000 mm
Basic Gasket Width, $b_o = N/2$	6.500 mm
Effective Gasket Width, $b = C_b \cdot \sqrt{b_o}$	6.425 mm
Gasket Reaction Diameter, $G = G_o - 2 \cdot b$	234.102 mm

Basic Flange and Bolt Loads:

Hydrostatic End Load due to Pressure [H or Wo,1]:

$$= \pi/4 \cdot G^2 \cdot P$$

$$= \pi/4 \cdot 234^2 \cdot 2402$$

$$= 10542.734 \text{ Kgf}$$

Contact Load on Gasket Surfaces [Hp or Wo,2]:

$$= 2 \cdot b \cdot \pi \cdot G \cdot m \cdot P$$

$$= 2 \cdot 6.42 \cdot \pi \cdot 234 \cdot 3 \cdot 2402$$

$$= 6943.897 \text{ Kgf}$$

Hydrostatic End Load at Flange ID [Hd]:

$$= \pi/4 \cdot B_{cor}^2 \cdot P$$

$$= \pi/4 \cdot 195^2 \cdot 2402$$

$$= 7311.295 \text{ Kgf}$$

Pressure Force on Flange Face [Ht]:

$$= H - H_d$$

$$= 10543 - 7311$$

$$= 3231.438 \text{ Kgf}$$

Design Bolt Load for the Operating Condition [Wo]:

$$= \max(W_o,1 + W_o,2 + H'p, 0)$$

$$= \max(10543 + 6944 + 0, 0)$$

$$= 17487.631 \text{ Kgf}$$

Design Bolt Load for the Gasket Seating Condition [Wg]:

$$= y \cdot b \cdot \pi \cdot G + y_{Part} \cdot b_{Part} \cdot l_p$$

$$= 68.9 \cdot 6.42 \cdot \pi \cdot 234 + 0 \cdot 0$$

$$= 33220.336 \text{ Kgf}$$

Required Bolt Area [Am]:

$$= \max((W_o + Fa + 4Me/G)/S_b, W_g/S_a)$$

$$= \max((17487 + 0 + 4 \cdot 0/234)/172, 33220/172)$$

$$= 18.941 \text{ cm}^2$$



PV Elite 28 Licensee: SL User
 FileName : 161-C1-C2 _(Stack) Page 25 of 204
 Flg Calc [Int P]: New Flange Flng: 5 9:40am Sep 9,2026

ASME Maximum Circumferential Spacing between Bolts, Table 4.16.11 [Bsmax]:

$$= 2a + 6t/(m + 0.5)$$

$$= 2 \cdot 25.4 + 6 \cdot 53/(3 + 0.5)$$

$$= 141.657 \text{ mm}$$

Actual Circumferential Bolt Spacing [Bs]:

$$= C \cdot \sin(\pi / n)$$

$$= 300 \cdot \sin(\pi/12)$$

$$= 77.646 \text{ mm}$$

ASME Moment Multiplier for Bolt Spacing per Table 4.16.11 [Bsc]:

$$= \max(\sqrt{Bs/(2a + t)}, 1)$$

$$= \max(\sqrt{77.6/(2 \cdot 25.4 + 53)}, 1)$$

$$= 1.0000$$

Bolting Information for UNC Thread Series (Non Mandatory):

	Minimum	Actual	Maximum
Bolt Area:	18.941	42.658	
Radial Distance between Hub and Bolts:	34.925	35.525	
Radial Distance between Bolts and Edge:	26.987	30.000	
Circ. Spacing between the Bolts:	57.150	77.646	141.657

Min. Gasket Contact Width (Brownell Young) [Not an ASME Calc] [Nmin]:

$$= Ab \cdot Sa / (y \cdot \pi(Go + Gi))$$

$$= 42.7 \cdot 172 / (68.9 \cdot \pi(247 + 221))$$

$$= 7.239 \text{ mm}$$

Flange Design Bolt Load, Gasket Seating [W or Wgs]:

$$= Sa \cdot Ab$$

$$= 172 \cdot 42.7$$

$$= 74815.61 \text{ Kg}$$

Gasket Load for the Operating Condition [HG]:

$$= Wo - H$$

$$= 17487 - 10543$$

$$= 6943.90 \text{ Kg}$$

Moment Arm Calculations:

Distance to Gasket Load Reaction [hg]:

$$= (C - G) / 2$$

$$= (300 - 234) / 2$$

$$= 32.9491 \text{ mm}$$

Distance to Face Pressure Reaction [ht]:

$$= 0.5((C - B) / 2 + hg)$$

$$= 0.5((300 - 195) / 2 + 32.9)$$

$$= 42.7368 \text{ mm}$$

Distance to End Pressure Reaction [hd]:

$$= (C - B - g1) / 2$$

$$= (300 - 195 - 17) / 2$$

$$= 44.0245 \text{ mm}$$

Summary of Moments for Internal Pressure: (Kg-m.)

Loading	Force	Distance	Bolt Corr	Moment
End Pressure, Md	7311.	44.0245	1.0000	322.
Face Pressure, Mt	3231.	42.7368	1.0000	138.
Gasket Load, Mg	6944.	32.9491	1.0000	229.
Gasket Seating, Matm	74816.	32.9491	1.0000	2465.



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)

Page 26 of 204

Flg Calc [Int P]: New Flange

Flng: 5 9:40am Sep 9, 2026

Total Moment for Operation, Mo 689. Kg-m.
Total Moment for Gasket seating, Mg 2465. Kg-m.

Effective Hub Length, ho = sqrt(Bcor*goCor) 44.548 mm
Hub Ratio, h/h0 = HL / H0 0.584
Thickness Ratio, g1/g0 = (g1Cor/goCor) 1.670

Flange Factors for Integral Flange:

Factor F per 4.16.5 0.823
Factor V per 4.16.5 0.259
Factor f per 4.16.5 1.000

Stress factor from Table 4.16.4 [K]:

= A / B
= 360/195
= 1.847

Stress factor from Table 4.16.4 [Y]:

= (0.66845 + (5.7169(K² • log10(K))) / (K² - 1))/(K - 1)
= (0.66845 + (5.7169(1.85² • log10(1.85))) / (1.85² - 1))/(1.85 - 1)
= 3.335

Stress factor from Table 4.16.4 [T]:

= (K²(1 + 8.55246 • log10(K)) - 1) / ((1.0472 + 1.9448 • K²) • (K - 1))
= (1.85²(1 + 8.55246 • log10(1.85)) - 1) / ((1.0472 + 1.9448 • 1.85²) • (1.85 - 1))
= 1.566

Stress factor from Table 4.16.4 [U]:

= (K²(1 + 8.55246 • log10(K)) - 1) / (1.36136(K² - 1) • (K - 1))
= (1.85²(1 + 8.55246 • log10(1.85)) - 1) / (1.36136(1.85² - 1) • (1.85 - 1))
= 3.664

Stress factor from Table 4.16.4 [Z]:

= (K² + 1) / (K² - 1)
= (1.85² + 1) / (1.85² - 1)
= 1.830

Stress factor from Table 4.16.4 for integral flanges [d]:

= U • g0² • h0 / V
= 3.66 • 10.2² • 44.5 / 0.26
= 65359.688 mm³

Stress factor from Table 4.16.4 for integral flanges [e]:

= F / h0
= 0.82/44.5
= 0.018 1/mm

Stress factor from Table 4.16.4 [L]:

= (t • e + 1) / T + t³/d
= (53 • 0.018 + 1) / 1.57 + 53³/65360
= 3.542

Flange Stresses

Longitudinal Hub Stress, Operating [SHo]:

= (f • Mop / Bcor) / (L • g1²)
= (1•689/195)/(3.54•17²)
= 33.85 N./mm²

Longitudinal Hub Stress, Seating [SHa]:

= (f • Matm / Bcor) / (L • g1²)
= (1•2465/195)/(3.54•17²)
= 121.15 N./mm²



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 27 of 204

Flg Calc [Int P]: New Flange

Flng: 5 9:40am

Sep 9, 2026

Radial Flange Stress, Operating [SRo]:

$$= (\beta \cdot Mop / Bcor) / (L \cdot t^2)$$

$$= (2.31 \cdot 689 / 195) / (3.54 \cdot 53^2)$$

$$= 8.03 \text{ N./mm}^2$$

Radial Flange Stress, Seating [SRa]:

$$= (\beta \cdot Matm / Bcor) / (L \cdot t^2)$$

$$= (2.31 \cdot 2465 / 195) / (3.54 \cdot 53^2)$$

$$= 28.73 \text{ N./mm}^2$$

Tangential Flange Stress, Operating [STo]:

$$= (Y \cdot Mo / (t^2 \cdot Bcor)) - Z \cdot SRo$$

$$= (3.33 \cdot 689 / (53^2 \cdot 195)) - 1.83 \cdot 8.03$$

$$= 26.44 \text{ N./mm}^2$$

Tangential Flange Stress, Seating [STa]:

$$= (y \cdot Matm / (t^2 \cdot Bcor)) - Z \cdot SRa$$

$$= (3.33 \cdot 2465 / (53^2 \cdot 195)) - 1.83 \cdot 28.7$$

$$= 94.63 \text{ N./mm}^2$$

Average Flange Stress, Operating [SAo]:

$$= (SHo + \max(SRo, STo)) / 2$$

$$= (33.8 + \max(8.03, 26.4)) / 2$$

$$= 30.15 \text{ N./mm}^2$$

Average Flange Stress, Seating [SAa]:

$$= (SHa + \max(SRa, STa)) / 2$$

$$= (121 + \max(28.7, 94.6)) / 2$$

$$= 107.89 \text{ N./mm}^2$$

Bolt Stress, Operating [BSo]:

$$= Wm1 / Ab$$

$$= 17487 / 42.7$$

$$= 40.20 \text{ N./mm}^2$$

Bolt Stress, Seating [BSa]:

$$= (Wm2 / Ab)$$

$$= (33220 / 42.7)$$

$$= 76.37 \text{ N./mm}^2$$

Flange Stress Analysis Results: N./mm²

	Actual	Operating Allowed	Gasket Actual	Seating Allowed
Longitudinal Hub	33.85	199.80	121.15	207.00
Radial Flange	8.03	133.20	28.73	138.00
Tangential Flange	26.44	133.20	94.63	138.00
Maximum Average	30.15	133.20	107.89	138.00
Bolting	40.20	172.00	76.37	172.00

Minimum Required Flange Thickness 48.387 mm

Estimated M.A.W.P. (Operating) 10276 KPa.

Estimated Finished Weight of Flange at given Thk. 34.2 kg.

Estimated Unfinished Weight of Forging at given Thk 46.9 kg.

Flange Stress results per WRC-538 at computed Sfmax (N./mm²):

	Actual	Operating Allowed	stress ratio	Gasket Actual	Seating Allowed	stress ratio
Longitudinal Hub Sh	384.99	457.15	0.842	384.99	499.99	0.770



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)

Page 28 of 204

Flg Calc [Int P]: New Flange

Flng: 5 9:40am

Sep 9, 2026

Tangential Flange	St	300.73	342.86	0.877	300.73	374.99	0.802
Tangential Flange	Sto	142.05	228.57	0.621	142.05	250.00	0.568
Combined	Sh/f + St	685.72	685.72	1.000	685.72	749.99	0.914
Combined	Sr + St	392.04	685.72	0.572	392.04	749.99	0.523
Combined	Sh + Sto	527.04	685.72	0.769	527.04	749.99	0.703
Radial Flange	Sr	91.31	457.15	0.200	91.31	499.99	0.183
Maximum Stress Ratio				1.000			0.914

Coefficients for f and f2

	<i>f</i>	<i>f2</i>	<i>f3</i>
<i>a</i>	-0.71375912	-0.01447638	-0.06456312
<i>b</i>	-0.12846279	-0.27814745	-0.08232239
<i>c</i>	1.08037907	0.01035395	0.13691677
<i>d</i>	0.99766848	1.37984158	-0.77879888
<i>e</i>	1.21823466	-0.34346764	0.14909019
<i>f</i>	0.01024612	0.02536192	0.00660062
<i>g</i>	0.4262313	-0.0014508	0.0616252
<i>h</i>	1.4204976	2.25543162	0.74639834
<i>i</i>	-0.70278181	-0.60889597	-0.079595
<i>j</i>	-0.02483937	-0.15735462	0.09851673
<i>k</i>	-1.59460436	1.22516062	-0.1121436

$$f_n = \frac{\left[a + c \left(\frac{g1}{g0} \right) + e \left(\frac{h}{h0} \right) + g \left(\frac{g1}{g0} \right)^2 + i \left(\frac{h}{h0} \right)^2 + k \left(\frac{g1}{g0} \right) \left(\frac{h}{h0} \right) \right]}{\left[1 + b \left(\frac{g1}{g0} \right) + d \left(\frac{h}{h0} \right) + f \left(\frac{g1}{g0} \right)^2 + h \left(\frac{h}{h0} \right)^2 + j \left(\frac{g1}{g0} \right) \left(\frac{h}{h0} \right) \right]}$$

Hub Stress Correction Factor [f]:

= max(1; F1num / F1den)

= max(1; 1.2/1.86)

= 1.0000

Hub Stress Correction Factor [f2]:

= max(0.25; fn2) if h/ho < 0.35, else max (0.25; fn3)

= max(0.25; 0.79/2.03) if h/ho < 0.35, else max (0.25; 0.29/0.78)

= 0.3690

In this case, the hub ratio h/ho, 0.5836 was ≥ 0.35.

PV Elite iterates on the assembly bolt load stress, Sfmax, until it exceeds the limits provided by WRC 538.

Bolting and Gasket Calculations per ASME PCC-1 Appendix O:

Input Data:



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 29 of 204

Flg Calc [Int P]: New Flange

Flng: 5 9:40am

Sep 9,2026

Maximum permissible bolt stress	Sbmax	507.5 N./mm ²
Minimum permissible bolt stress	Sbmin	290.0 N./mm ²
Max. permissible bolt stress prior to flange damage	Sfmax	546.6 N./mm ²
Target assembly gasket stress	SgT	207.0 N./mm ²
Maximum permissible gasket stress	Sgmax	276.0 N./mm ²
Minimum gasket operating stress	Sgmin-O	97.0 N./mm ²
Minimum gasket seating stress	Sgmin-S	140.0 N./mm ²
Nut Factor	K	0.200
Fraction of Gasket Load remaining after relaxation	Phig	0.700
Root Area of a Single Bolt	Abs	3.5548 cm ²
Max. permissible single flange rotation for gasket	Thetagmax	1.000 deg

Calculated Results:

Flange Material Ambient Yield Stress	Sya	250.0 N./mm ²
Flange Material Operating Yield Stress	Syo	200.0 N./mm ²
Single flange rotation at Sfmax	Thetaamax	0.167 deg

Gasket Contact Area [Ag]:

$$= \pi/4 (GO.D.^2 - GI.D.^2)$$

$$= \pi/4 (247^2 - 221^2)$$

$$= 95.5 \text{ cm}^2$$

Target Bolt Stress [Sbsel]: (Eq. O-1)

$$= SgT \cdot Ag / (nb \cdot Abs)$$

$$= 207 \cdot 95.5 / (12 \cdot 3.55)$$

$$= 463.6 \text{ N./mm}^2$$

Upper Bolt Stress Limit [Sbsel]: (Eq. O-4)

$$= \min(Sbsel; Sbmax)$$

$$= \min(464; 508)$$

$$= 463.6 \text{ N./mm}^2$$

Lower Bolt Stress Limit [Sbsel]: (Eq. O-5)

$$= \max(Sbsel; Sbmin)$$

$$= \max(464; 290)$$

$$= 463.6 \text{ N./mm}^2$$

Upper Bolt Stress Limit including the Flange [Sbsel]: (Eq. O-6)

$$= \min(Sbsel; Sfmax)$$

$$= \min(464; 547)$$

$$= 463.6 \text{ N./mm}^2$$

Check if Gasket Assembly Seating Stress is achieved. (Eq. O-7)

$$\therefore Sbsel \geq Sgmin-S (Ag / (nb \cdot Abs))$$

$$\therefore 464 \geq 140 (95.5 / (12 \cdot 3.55))$$

$$\therefore 463.6 \geq 313.6 \text{ N./mm}^2 \text{ Check Passes}$$

Check if Gasket Operating Stress is maintained. (Eq. O-8)

$$\therefore Sbsel \geq (Sgmin-O \cdot Ag + \pi/4 \cdot Pmax \cdot GI.D.^2) / (\phi G \cdot Abs \cdot nb)$$

$$\therefore 464 \geq (97 \cdot 95.5 + \pi/4 \cdot 2402 \cdot 221^2) / (0.7 \cdot 3.55 \cdot 12)$$

$$\therefore 463.6 \geq 341.2 \text{ N./mm}^2 \text{ Check Passes}$$

Check if Gasket Maximum Stress is achieved. (Eq. O-9)

$$\therefore Sbsel \leq Sgmax (Ag / (nb \cdot Abs))$$

$$\therefore 464 \leq 276 (95.5 / (12 \cdot 3.55))$$

$$\therefore 463.6 \leq 618.2 \text{ N./mm}^2 \text{ Check Passes}$$

Check if Flange Rotation Limit is exceeded. (Eq. O-10)

$$\therefore Sbsel \leq Sfmax (thetagmax / thetaamax)$$

$$\therefore 464 \leq 547 (1/0.17)$$

$$\therefore 463.6 \leq 3281.2 \text{ N./mm}^2 \text{ Check Passes}$$

Assembly Bolt Torque [Tb]: (Eq. O-2)

$$= Sbsel \cdot K \cdot Abs \cdot \phi b$$



PV Elite 28 Licensee: SL User
 FileName : 161-C1-C2 _(Stack) Page 30 of 204
 Flg Calc [Int P]: New Flange Flng: 5 9:40am Sep 9,2026

$$= 464 \cdot 0.2 \cdot 3.55 \cdot 25.4$$

$$= 85.4 \text{ Kg-m.}$$

Bolt Allowable Stress for: SA-193 B8 Cl. 2 SbB8 138 N./mm²
 Bolt Allowable Stress for: SA-193 B7 Sb 171 N./mm²

Note: Since Sb >= SbB8, bolt allowable stress comparison check Passes (see Div 1 UG-44(b)).

Flange rigidity based on required thickness [ASME]:

Flange Rigidity Criterion, Seating per Table 4.16.10 [Jg]:

$$= 52.14 \cdot Ma / Bsc \cdot Cnvfac \cdot V / (\lambda \cdot Eamb \cdot go^2 \cdot ho \cdot Ki)$$

$$= 52.14 \cdot 2465 / 1 \cdot 9807 \cdot 0.26 / (2.6 \cdot 202713 \cdot 10.2^2 \cdot 44.5 \cdot 0.3)$$

$$= 0.446 \text{ (should be } \leq 1)$$

Flange Rigidity Criterion, Operating per Table 4.16.10 [Jo]:

$$= 52.14 \cdot Mo / Bsc \cdot Cnvfac \cdot V / (\lambda \cdot Eop \cdot goc^2 \cdot ho \cdot Ki)$$

$$= 52.14 \cdot 689 / 1 \cdot 9807 \cdot 0.26 / (2.6 \cdot 187243 \cdot 10.2^2 \cdot 44.5 \cdot 0.3)$$

$$= 0.135 \text{ (should be } \leq 1)$$

Flange rigidity based on given thickness [ASME]:

Flange Rigidity Criterion, Seating per Table 4.16.10 [Jg]:

$$= 52.14 \cdot Ma / Bsc \cdot Cnvfac \cdot V / (\lambda \cdot Eamb \cdot go^2 \cdot ho \cdot Ki)$$

$$= 52.14 \cdot 2465 / 1 \cdot 9807 \cdot 0.26 / (3.54 \cdot 202713 \cdot 10.2^2 \cdot 44.5 \cdot 0.3)$$

$$= 0.328 \text{ (should be } \leq 1)$$

Flange Rigidity Criterion, Operating per Table 4.16.10 [Jo]:

$$= 52.14 \cdot Mo / Bsc \cdot Cnvfac \cdot V / (\lambda \cdot Eop \cdot goc^2 \cdot ho \cdot Ki)$$

$$= 52.14 \cdot 689 / 1 \cdot 9807 \cdot 0.26 / (3.54 \cdot 187243 \cdot 10.2^2 \cdot 44.5 \cdot 0.3)$$

$$= 0.099 \text{ (should be } \leq 1)$$

Minimum Design Metal Temperature Results:

Thickness Ratio = 0.34, Temperature Reduction per Fig. UCS 66.1 = 78 °C

Min Metal Temp. w/o impact per UCS-66, Curve A 0 °C
 Min Metal Temp. at Required thickness (UCS 66.1) -104 °C

Note: UCS-66(b)(-c) was considered in the flange MDMT calculation.

Per ASME VIII-2, 4.16.2.3, Perform Calculations in the New Condition:

Flange Stress Analysis Results: N./mm²

	Operating		Gasket Seating	
	Actual	Allowed	Actual	Allowed
Longitudinal Hub	30.13	207.00	105.48	207.00
Radial Flange	8.69	138.00	30.42	138.00
Tangential Flange	21.74	138.00	76.14	138.00
Maximum Average	25.93	138.00	90.81	138.00
Bolting	40.20	172.00	76.37	172.00

Minimum Req'd Thickness, ambient, no Corrosion: 41.097 mm

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)

Page 31 of 204

Flg Calc [Int P]: New Flange


Flng: 6 9:40am Sep 9,2026

Flange Input Data Values

Description: New Flange :

RHS Ch Flg

Flange Type	Integral Weld Neck		
Design Pressure	P	2401.91	KPa.
Design Temperature		260	°C
Internal Corrosion Allowance	ci	3.0000	mm
External Corrosion Allowance	ce	0.0000	mm
Use Corrosion Allowance in Thickness Calcs.		Yes	
Flange Inside Diameter	B	202.717	mm
Flange Outside Diameter	A	360.000	mm
Flange Thickness	t	56.0000	mm
Thickness of Hub at Small End	go	7.1564	mm
Thickness of Hub at Large End	gl	12.0000	mm
Length of Hub	h	16.0000	mm
Flange Material		SA-105	
Flange Material UNS number		K03504	
Flange Allowable Stress At Temperature	Sfo	134.60	N./mm ²
Flange Allowable Stress At Ambient	Sfa	138.00	N./mm ²
Bolt Material		SA-193 B7	
Bolt Allowable Stress At Temperature	Sb	172.00	N./mm ²
Bolt Allowable Stress At Ambient	Sa	172.00	N./mm ²
Diameter of Bolt Circle	C	300.000	mm
Nominal Bolt Diameter	a	25.4000	mm
Type of Threads	UNC Thread Series		
Number of Bolts		12	
Flange Face Outside Diameter	Fod	271.717	mm
Flange Face Inside Diameter	Fid	202.717	mm
Flange Facing Sketch		Sketch 1a	
Gasket Outside Diameter	Go	260.717	mm
Gasket Inside Diameter	Gi	234.717	mm
Gasket Factor	m	3.0000	
Gasket Design Seating Stress	y	68.95	N./mm ²
Gasket Thickness	tg	3.1750	mm
Raised face depth	Fd	0.0000	mm





PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 32 of 204

Flg Calc [Int P]: New Flange

Flng: 6 9:40am

Sep 9, 2026

ASME Code, Section VIII Division 1, 2025

Hub Small End Required Thickness due to Internal Pressure:

$$= (P \cdot (D/2 + Ca)) / (S \cdot E - 0.6 \cdot P) \text{ per UG-27 (c)(1)}$$

$$= (2402 \cdot (203/2 + 3)) / (118 \cdot 1 - 0.6 \cdot 2402) + Ca$$

$$= 5.1507 \text{ mm}$$

Small End Hub MAWP:

$$= (S \cdot E \cdot t) / (R + 0.6 \cdot t) \text{ per UG-27 (c)(1)}$$

$$= (118 \cdot 1 \cdot 4.16) / (104 + 0.6 \cdot 4.16)$$

$$= 4589.732 \text{ KPa.}$$

Hub Small End Hub MAPnc:

$$= (Sa \cdot E \cdot t) / (R + 0.6 \cdot t) \text{ per UG-27 (c)(1)}$$

$$= (118 \cdot 1 \cdot 7.16) / (101 + 0.6 \cdot 7.16)$$

$$= 7992.219 \text{ KPa.}$$

Corroded Flange Thickness, $t_c = T - c_i$	53.000 mm
Corroded Flange ID, $B_{cor} = B + 2 \cdot c_i$	208.717 mm
Corroded Large Hub, $g1_{cor} = g1 - c_i$	9.000 mm
Corroded Small Hub, $g0_{cor} = g0 - c_i$	4.156 mm
Code R Dimension, $R = ((C - B_{cor})/2) - g1_{cor}$	36.641 mm

Gasket Contact Width, $N = (G_o - G_i)/2$	13.000 mm
Basic Gasket Width, $b_o = N/2$	6.500 mm
Effective Gasket Width, $b = C_b \cdot \sqrt{b_o}$	6.425 mm
Gasket Reaction Diameter, $G = G_o - 2 \cdot b$	247.868 mm

Basic Flange and Bolt Loads:

Hydrostatic End Load due to Pressure [H or Wo,1]:

$$= \pi/4 \cdot G^2 \cdot P$$

$$= \pi/4 \cdot 248^2 \cdot 2402$$

$$= 11819.086 \text{ Kgf}$$

Contact Load on Gasket Surfaces [Hp or Wo,2]:

$$= 2 \cdot b \cdot \pi \cdot G \cdot m \cdot P$$

$$= 2 \cdot 6.42 \cdot \pi \cdot 248 \cdot 3 \cdot 2402$$

$$= 7352.222 \text{ Kgf}$$

Hydrostatic End Load at Flange ID [Hd]:

$$= \pi/4 \cdot B_{cor}^2 \cdot P$$

$$= \pi/4 \cdot 209^2 \cdot 2402$$

$$= 8380.291 \text{ Kgf}$$

Pressure Force on Flange Face [Ht]:

$$= H - H_d$$

$$= 11819 - 8380$$

$$= 3438.796 \text{ Kgf}$$

Design Bolt Load for the Operating Condition [Wo]:

$$= \max(W_o,1 + W_o,2 + H'p, 0)$$

$$= \max(11819 + 7352 + 0, 0)$$

$$= 19171.309 \text{ Kgf}$$

Design Bolt Load for the Gasket Seating Condition [Wg]:

$$= y \cdot b \cdot \pi \cdot G + y_{Part} \cdot b_{Part} \cdot l_p$$

$$= 68.9 \cdot 6.42 \cdot \pi \cdot 248 + 0 \cdot 0 \cdot 0$$

$$= 35173.809 \text{ Kgf}$$

Required Bolt Area [Am]:

$$= \max((W_o + Fa + 4Me/G)/S_b, W_g/S_a)$$

$$= \max((19171 + 0 + 4 \cdot 0/248)/172, 35174/172)$$

$$= 20.055 \text{ cm}^2$$



PV Elite 28 Licensee: SL User
 FileName : 161-C1-C2 _(Stack) Page 33 of 204
 Flg Calc [Int P]: New Flange Flng: 6 9:40am Sep 9,2026

ASME Maximum Circumferential Spacing between Bolts, Table 4.16.11 [Bsmax]:

$$= 2a + 6t/(m + 0.5)$$

$$= 2 \cdot 25.4 + 6 \cdot 53/(3 + 0.5)$$

$$= 141.657 \text{ mm}$$

Actual Circumferential Bolt Spacing [Bs]:

$$= C \cdot \sin(\pi / n)$$

$$= 300 \cdot \sin(\pi / 12)$$

$$= 77.646 \text{ mm}$$

ASME Moment Multiplier for Bolt Spacing per Table 4.16.11 [Bsc]:

$$= \max(\sqrt{Bs/(2a + t)}, 1)$$

$$= \max(\sqrt{77.6/(2 \cdot 25.4 + 53)}, 1)$$

$$= 1.0000$$

Bolting Information for UNC Thread Series (Non Mandatory):

	Minimum	Actual	Maximum
Bolt Area:	20.055	42.658	
Radial Distance between Hub and Bolts:	34.925	36.642	
Radial Distance between Bolts and Edge:	26.987	30.000	
Circ. Spacing between the Bolts:	57.150	77.646	141.657

Min. Gasket Contact Width (Brownell Young) [Not an ASME Calc] [Nmin]:

$$= Ab \cdot Sa / (y \cdot \pi (Go + Gi))$$

$$= 42.7 \cdot 172 / (68.9 \cdot \pi (261 + 235))$$

$$= 6.837 \text{ mm}$$

Flange Design Bolt Load, Gasket Seating [W or Wgs]:

$$= Sa \cdot Ab$$

$$= 172 \cdot 42.7$$

$$= 74815.61 \text{ Kg}$$

Gasket Load for the Operating Condition [HG]:

$$= Wo - H$$

$$= 19171 - 11819$$

$$= 7352.22 \text{ Kg}$$

Moment Arm Calculations:

Distance to Gasket Load Reaction [hg]:

$$= (C - G) / 2$$

$$= (300 - 248) / 2$$

$$= 26.0661 \text{ mm}$$

Distance to Face Pressure Reaction [ht]:

$$= 0.5((C - B) / 2 + hg)$$

$$= 0.5((300 - 209) / 2 + 26.1)$$

$$= 35.8538 \text{ mm}$$

Distance to End Pressure Reaction [hd]:

$$= (C - B - g1) / 2$$

$$= (300 - 209 - 9) / 2$$

$$= 41.1415 \text{ mm}$$

Summary of Moments for Internal Pressure: (Kg-m.)

Loading	Force	Distance	Bolt Corr	Moment
End Pressure, Md	8380.	41.1415	1.0000	345.
Face Pressure, Mt	3439.	35.8538	1.0000	123.
Gasket Load, Mg	7352.	26.0661	1.0000	192.
Gasket Seating, Matm	74816.	26.0661	1.0000	1950.



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 34 of 204

Flg Calc [Int P]: New Flange

Flng: 6 9:40am Sep 9, 2026

Total Moment for Operation, Mo 660. Kg-m.
Total Moment for Gasket seating, Mg 1950. Kg-m.

Effective Hub Length, ho = sqrt(Bcor*goCor) 29.454 mm
Hub Ratio, h/h0 = HL / H0 0.543
Thickness Ratio, g1/g0 = (g1Cor/goCor) 2.165

Flange Factors for Integral Flange:

Factor F per 4.16.5 0.809
Factor V per 4.16.5 0.200
Factor f per 4.16.5 1.280

Stress factor from Table 4.16.4 [K]:

= A / B
= 360/209
= 1.725

Stress factor from Table 4.16.4 [Y]:

= (0.66845 + (5.7169(K² • log10(K))) / (K² - 1))/(K - 1)
= (0.66845 + (5.7169(1.72² • log10(1.72))) / (1.72² - 1))/(1.72 - 1)
= 3.735

Stress factor from Table 4.16.4 [T]:

= (K²(1 + 8.55246 • log10(K)) - 1) / ((1.0472 + 1.9448 • K²) • (K - 1))
= (1.72²(1 + 8.55246 • log10(1.72)) - 1) / ((1.0472 + 1.9448 • 1.72²) • (1.72 - 1))
= 1.615

Stress factor from Table 4.16.4 [U]:

= (K²(1 + 8.55246 • log10(K)) - 1) / (1.36136(K² - 1) • (K - 1))
= (1.72²(1 + 8.55246 • log10(1.72)) - 1) / (1.36136(1.72² - 1) • (1.72 - 1))
= 4.104

Stress factor from Table 4.16.4 [Z]:

= (K² + 1) / (K² - 1)
= (1.72² + 1) / (1.72² - 1)
= 2.013

Stress factor from Table 4.16.4 for integral flanges [d]:

= U • g0² • h0 / V
= 4.1 • 4.16² • 29.5 / 0.2
= 10445.670 mm³

Stress factor from Table 4.16.4 for integral flanges [e]:

= F / h0
= 0.81/29.5
= 0.027 1/mm

Stress factor from Table 4.16.4 [L]:

= (t • e + 1) / T + t³/d
= (53 • 0.027 + 1) / 1.62 + 53³/10446
= 15.773

Flange Stresses

Longitudinal Hub Stress, Operating [SHo]:

= (f • Mop / Bcor) / (L • g1²)
= (1.28•660/209)/(15.8•9²)
= 31.07 N./mm²

Longitudinal Hub Stress, Seating [SHa]:

= (f • Matm / Bcor) / (L • g1²)
= (1.28•1950/209)/(15.8•9²)
= 91.83 N./mm²



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 35 of 204

Flg Calc [Int P]: New Flange

Flng: 6 9:40am

Sep 9, 2026

Radial Flange Stress, Operating [SRo]:

$$= (\beta \cdot Mop / Bcor) / (L \cdot t^2)$$

$$= (2.94 \cdot 660 / 209) / (15.8 \cdot 53^2)$$

$$= 2.06 \text{ N./mm}^2$$

Radial Flange Stress, Seating [SRa]:

$$= (\beta \cdot Matm / Bcor) / (L \cdot t^2)$$

$$= (2.94 \cdot 1950 / 209) / (15.8 \cdot 53^2)$$

$$= 6.08 \text{ N./mm}^2$$

Tangential Flange Stress, Operating [STo]:

$$= (Y \cdot Mo / (t^2 \cdot Bcor)) - Z \cdot SRO$$

$$= (3.73 \cdot 660 / (53^2 \cdot 209)) - 2.01 \cdot 2.06$$

$$= 37.07 \text{ N./mm}^2$$

Tangential Flange Stress, Seating [STa]:

$$= (y \cdot Matm / (t^2 \cdot Bcor)) - Z \cdot SRA$$

$$= (3.73 \cdot 1950 / (53^2 \cdot 209)) - 2.01 \cdot 6.08$$

$$= 109.59 \text{ N./mm}^2$$

Average Flange Stress, Operating [SAo]:

$$= (SHo + \max(SRo, STo)) / 2$$

$$= (31.1 + \max(2.06, 37.1)) / 2$$

$$= 34.07 \text{ N./mm}^2$$

Average Flange Stress, Seating [SAa]:

$$= (SHa + \max(SRa, STa)) / 2$$

$$= (91.8 + \max(6.08, 110)) / 2$$

$$= 100.71 \text{ N./mm}^2$$

Bolt Stress, Operating [BSo]:

$$= Wm1 / Ab$$

$$= 19171 / 42.7$$

$$= 44.07 \text{ N./mm}^2$$

Bolt Stress, Seating [BSa]:

$$= (Wm2 / Ab)$$

$$= (35174 / 42.7)$$

$$= 80.86 \text{ N./mm}^2$$

Flange Stress Analysis Results: N./mm²

	Actual	Operating Allowed	Gasket Actual	Seating Allowed
Longitudinal Hub	31.07	201.90	91.83	207.00
Radial Flange	2.06	134.60	6.08	138.00
Tangential Flange	37.07	134.60	109.59	138.00
Maximum Average	34.07	134.60	100.71	138.00
Bolting	44.07	172.00	80.86	172.00

Minimum Required Flange Thickness 49.403 mm

Estimated M.A.W.P. (Operating) 4590 KPa.

Estimated Finished Weight of Flange at given Thk. 31.0 kg.

Estimated Unfinished Weight of Forging at given Thk 38.8 kg.

Flange Stress results per WRC-538 at computed Sfmax (N./mm²):

	Actual	Operating Allowed	stress ratio	Gasket Actual	Seating Allowed	stress ratio
Longitudinal Hub Sh	293.32	461.72	0.635	293.32	499.99	0.587



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)

Page 36 of 204

Flg Calc [Int P]: New Flange

Flng: 6 9:40am

Sep 9, 2026

Tangential Flange	St	346.29	346.29	1.000	346.29	374.99	0.923
Tangential Flange	Sto	132.11	230.86	0.572	132.11	250.00	0.528
Combined	Sh/f + St	572.90	692.57	0.827	572.90	749.99	0.764
Combined	Sr + St	365.51	692.57	0.528	365.51	749.99	0.487
Combined	Sh + Sto	425.44	692.57	0.614	425.44	749.99	0.567
Radial Flange	Sr	19.22	461.72	0.042	19.22	499.99	0.038
Maximum Stress Ratio				1.000			0.923

Coefficients for f and f2

	<i>f</i>	<i>f2</i>	<i>f3</i>
<i>a</i>	-0.71375912	-0.01447638	-0.06456312
<i>b</i>	-0.12846279	-0.27814745	-0.08232239
<i>c</i>	1.08037907	0.01035395	0.13691677
<i>d</i>	0.99766848	1.37984158	-0.77879888
<i>e</i>	1.21823466	-0.34346764	0.14909019
<i>f</i>	0.01024612	0.02536192	0.00660062
<i>g</i>	0.4262313	-0.0014508	0.0616252
<i>h</i>	1.4204976	2.25543162	0.74639834
<i>i</i>	-0.70278181	-0.60889597	-0.079595
<i>j</i>	-0.02483937	-0.15735462	0.09851673
<i>k</i>	-1.59460436	1.22516062	-0.1121436

$$f_n = \frac{\left[a + c \left(\frac{g1}{g0} \right) + e \left(\frac{h}{h0} \right) + g \left(\frac{g1}{g0} \right)^2 + i \left(\frac{h}{h0} \right)^2 + k \left(\frac{g1}{g0} \right) \left(\frac{h}{h0} \right) \right]}{\left[1 + b \left(\frac{g1}{g0} \right) + d \left(\frac{h}{h0} \right) + f \left(\frac{g1}{g0} \right)^2 + h \left(\frac{h}{h0} \right)^2 + j \left(\frac{g1}{g0} \right) \left(\frac{h}{h0} \right) \right]}$$

Hub Stress Correction Factor [f]:

= max(1; F1num / F1den)

= max(1; 2.2/1.7)

= 1.2944

Hub Stress Correction Factor [f2]:

= max(0.25; fn2) if h/ho < 0.35, else max (0.25; fn3)

= max(0.25; 1.08/1.75) if h/ho < 0.35, else max (0.25; 0.45/0.77)

= 0.5830

In this case, the hub ratio h/ho, 0.5432 was ≥ 0.35.

PV Elite iterates on the assembly bolt load stress, Sfmax, until it exceeds the limits provided by WRC 538.

Bolting and Gasket Calculations per ASME PCC-1 Appendix O:

Input Data:



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 37 of 204

Flg Calc [Int P]: New Flange

Flng: 6 9:40am

Sep 9,2026

Maximum permissible bolt stress	Sbmax	507.5 N./mm ²
Minimum permissible bolt stress	Sbmin	290.0 N./mm ²
Max. permissible bolt stress prior to flange damage	Sfmax	543.5 N./mm ²
Target assembly gasket stress	SgT	207.0 N./mm ²
Maximum permissible gasket stress	Sgmax	276.0 N./mm ²
Minimum gasket operating stress	Sgmin-O	97.0 N./mm ²
Minimum gasket seating stress	Sgmin-S	140.0 N./mm ²
Nut Factor	K	0.200
Fraction of Gasket Load remaining after relaxation	Phig	0.700
Root Area of a Single Bolt	Abs	3.5548 cm ²
Max. permissible single flange rotation for gasket	Thetagmax	1.000 deg

Calculated Results:

Flange Material Ambient Yield Stress	Sya	250.0 N./mm ²
Flange Material Operating Yield Stress	Syo	202.0 N./mm ²
Single flange rotation at Sfmax	Thetaamax	0.101 deg

Gasket Contact Area [Ag]:

$$= \pi/4 (GO.D.^2 - GI.D.^2)$$

$$= \pi/4 (261^2 - 235^2)$$

$$= 101.2 \text{ cm}^2$$

Target Bolt Stress [Sbsel]: (Eq. O-1)

$$= SgT \cdot Ag / (nb \cdot Ab)$$

$$= 207 \cdot 101 / (12 \cdot 3.55)$$

$$= 490.9 \text{ N./mm}^2$$

Upper Bolt Stress Limit [Sbsel]: (Eq. O-4)

$$= \min(Sbsel; Sbmax)$$

$$= \min(491; 508)$$

$$= 490.9 \text{ N./mm}^2$$

Lower Bolt Stress Limit [Sbsel]: (Eq. O-5)

$$= \max(Sbsel; Sbmin)$$

$$= \max(491; 290)$$

$$= 490.9 \text{ N./mm}^2$$

Upper Bolt Stress Limit including the Flange [Sbsel]: (Eq. O-6)

$$= \min(Sbsel; Sfmax)$$

$$= \min(491; 543)$$

$$= 490.9 \text{ N./mm}^2$$

Check if Gasket Assembly Seating Stress is achieved. (Eq. O-7)

$$:: Sbsel \geq Sgmin-S (Ag / (nb \cdot Abs))$$

$$:: 491 \geq 140 (101 / (12 \cdot 3.55))$$

$$:: 490.9 \geq 332.0 \text{ N./mm}^2 \text{ Check Passes}$$

Check if Gasket Operating Stress is maintained. (Eq. O-8)

$$:: Sbsel \geq (Sgmin-O \cdot Ag + \pi/4 \cdot Pmax \cdot GI.D.^2) / (\phi G \cdot Abs \cdot nb)$$

$$:: 491 \geq (97 \cdot 101 + \pi/4 \cdot 2402 \cdot 235^2) / (0.7 \cdot 3.55 \cdot 12)$$

$$:: 490.9 \geq 363.4 \text{ N./mm}^2 \text{ Check Passes}$$

Check if Gasket Maximum Stress is achieved. (Eq. O-9)

$$:: Sbsel \leq Sgmax (Ag / (nb \cdot Abs))$$

$$:: 491 \leq 276 (101 / (12 \cdot 3.55))$$

$$:: 490.9 \leq 654.6 \text{ N./mm}^2 \text{ Check Passes}$$

Check if Flange Rotation Limit is exceeded. (Eq. O-10)

$$:: Sbsel \leq Sfmax (thetagmax / thetaamax)$$

$$:: 491 \leq 543 (1/0.1)$$

$$:: 490.9 \leq 5380.9 \text{ N./mm}^2 \text{ Check Passes}$$

Assembly Bolt Torque [Tb]: (Eq. O-2)

$$= Sbsel \cdot K \cdot Abs \cdot \phi b$$



PV Elite 28 Licensee: SL User
 FileName : 161-C1-C2 _(Stack) Page 38 of 204
 Flg Calc [Int P]: New Flange Flng: 6 9:40am Sep 9,2026

$$= 491 \cdot 0.2 \cdot 3.55 \cdot 25.4$$

$$= 90.4 \text{ Kg-m.}$$

Bolt Allowable Stress for: SA-193 B8 Cl. 2 SbB8 138 N./mm²
 Bolt Allowable Stress for: SA-193 B7 Sb 171 N./mm²

Note: Since Sb >= SbB8, bolt allowable stress comparison check Passes (see Div 1 UG-44(b)).

Flange rigidity based on required thickness [ASME]:

Flange Rigidity Criterion, Seating per Table 4.16.10 [Jg]:

$$= 52.14 \cdot Ma / Bsc \cdot Cnvfac \cdot V / (\lambda \cdot Eamb \cdot go^2 \cdot ho \cdot Ki)$$

$$= 52.14 \cdot 1950 / 1 \cdot 9807 \cdot 0.2 / (11 \cdot 202713 \cdot 4.16^2 \cdot 29.5 \cdot 0.3)$$

$$= 0.587 \text{ (should be } \leq 1)$$

Flange Rigidity Criterion, Operating per Table 4.16.10 [Jo]:

$$= 52.14 \cdot Mo / Bsc \cdot Cnvfac \cdot V / (\lambda \cdot Eop \cdot goc^2 \cdot ho \cdot Ki)$$

$$= 52.14 \cdot 660 / 1 \cdot 9807 \cdot 0.2 / (11 \cdot 188235 \cdot 4.16^2 \cdot 29.5 \cdot 0.3)$$

$$= 0.214 \text{ (should be } \leq 1)$$

Flange rigidity based on given thickness [ASME]:

Flange Rigidity Criterion, Seating per Table 4.16.10 [Jg]:

$$= 52.14 \cdot Ma / Bsc \cdot Cnvfac \cdot V / (\lambda \cdot Eamb \cdot go^2 \cdot ho \cdot Ki)$$

$$= 52.14 \cdot 1950 / 1 \cdot 9807 \cdot 0.2 / (15.8 \cdot 202713 \cdot 4.16^2 \cdot 29.5 \cdot 0.3)$$

$$= 0.408 \text{ (should be } \leq 1)$$

Flange Rigidity Criterion, Operating per Table 4.16.10 [Jo]:

$$= 52.14 \cdot Mo / Bsc \cdot Cnvfac \cdot V / (\lambda \cdot Eop \cdot goc^2 \cdot ho \cdot Ki)$$

$$= 52.14 \cdot 660 / 1 \cdot 9807 \cdot 0.2 / (15.8 \cdot 188235 \cdot 4.16^2 \cdot 29.5 \cdot 0.3)$$

$$= 0.148 \text{ (should be } \leq 1)$$

Minimum Design Metal Temperature Results:

Thickness Ratio = 0.34, Temperature Reduction per Fig. UCS 66.1 = 78 °C

Min Metal Temp. w/o impact per UCS-66, Curve A -8 °C
 Min Metal Temp. at Required thickness (UCS 66.1) -104 °C
 Min Metal Temp. w/o impact per UG-20(f) -29 °C

Note: UCS-66(b)(-c) was considered in the flange MDMT calculation.

Per ASME VIII-2, 4.16.2.3, Perform Calculations in the New Condition:

Flange Stress Analysis Results: N./mm²

	Actual	Operating Allowed	Gasket Actual	Seating Allowed
Longitudinal Hub	28.86	207.00	83.39	207.00
Radial Flange	3.36	138.00	9.70	138.00
Tangential Flange	30.51	138.00	88.17	138.00
Maximum Average	29.69	138.00	85.78	138.00
Bolting	44.07	172.00	80.86	172.00

Minimum Req'd Thickness, ambient, no Corrosion: 44.069 mm

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)

Page 39 of 204

Internal Pressure Calculations: Step: 5 9:40am Sep 9,2026

Internal Pressure Results Summary:

Element Thickness, Pressure, Diameter and Allowable Stress :

From	To	Int. Press + Liq. Hd KPa.	Nominal Thickness mm	Total Corr Allowance mm	Element Diameter mm	Allowable Stress(SE) N./mm ²	Element#
LHS dish end		2401.8	15.062	3	188.95	137.2	1
LHS Ch Shell		2401.8	15.062	3	188.95	118	2
LHS Ch Flange		2401.9	68	3	188.95	133.2	3
Main Shell		2401.8	15.062	3	188.95	118	4
RHS Ch Flg		2401.9	64	3	202.72	134.6	5
RHS Ch Shell		2401.8	15.062	3	188.95	118	6
RHS Dish End		2401.8	10.312	3	188.95	137.2	7

Element Required Thickness and MAWP :

From	To	Design Pressure KPa.	M.A.W.P. Corroded KPa.	M.A.P. New & Cold KPa.	Minimum Thickness mm	Required Thickness mm	Element#
LHS dish end		2400	14749	18985	13.1794	4.64249	1
LHS Ch Shell		2400	11594	15189	13.1794	5.00876	2
LHS Ch Flange		2400	10275	10276	56	48.387	3
Main Shell		2400	11594	15189	13.1794	5.00876	4
RHS Ch Flg		2400	4588	7992	56	49.403	5
RHS Ch Shell		2400	11594	15189	13.1794	5.00876	6
RHS Dish End		2400	8765	13055	9.02335	4.64249	7

Warning: Shell Side MAWP governed by a standard Flange!

Summary of Heat Exchanger Maximum Allowable Working Pressures :

Note:

For Exchanger designs, the following values include MAWPs that consider the tubesheet, tubes, tube/tubesheet joint etc. These values were determined by iteration. Review the tubesheet analysis report for more information.

Shell Side MAWP = 5004 KPa.
 Shell Side MAPnc = 10200 KPa.
 Channel Side MAWP = 4588 KPa.
 Channel Side MAPnc = 7992 KPa.


Elements Suitable for Design Internal Pressure.

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



Internal Pressure Calculation Results:

ASME Code, Section VIII Division 1, 2025



Internal Pressure Results for: LHS dish end

Elliptical Head Design Information:					
Design Pressure	P	2401.843 KPa.	Int. Design Temperature		270 °C
Material		SA-516 70	Ext. Design Temperature		270 °C
Length		50.800 mm	External Pressure Chart		CS-2
			UNS Number		K02700
Int. Corr. All.	c	3.0000 mm	Allowable Stress (ope)	S	137.2 N./mm ²
Ext. Corr. All.	ce	0.0000 mm	Allowable Stress (amb)	Sa	138.0 N./mm ²
Inside Diameter	Di	188.951 mm	Actual Stress		22.3 N./mm ²
Spec. Min. Thk t,e, or sa		13.1794 mm	Spec. Nominal Thk.		15.062 mm
Surface Area		869.9 cm ²	SG of Contents		1.000
Element Volume		2307.9 cm ³	Weight of Contents		2.3 Kg
Empty Weight		9.6 Kg	Operating Weight		11.9 Kg
			Comp. All. Ope. Stress		123.6 N./mm ²
			Aspect Ratio		2.00

Radiography Information:					
User Defined			User Defined		
Circ. Joint Efficiency		100 %	Long. Joint Eff.	E or v	100 %

Tolerance for Formed Heads per UG-81(a):

Head inner surface maximum deviation outside the specified shape, 1.25% of D: 2.362 mm
 Head inner surface maximum deviation inside the specified shape, 0.625% of D: 1.181 mm

Required Thickness due to Internal Pressure [tr]:

$$= (P \cdot D \cdot K_{cor}) / (2 \cdot S \cdot E - 0.2 \cdot P) \text{ Appendix 1-4(c)}$$

$$= (2402 \cdot 195 \cdot 0.96) / (2 \cdot 137 \cdot 1 - 0.2 \cdot 2402)$$

$$= 1.6425 + 3.0000 = 4.6425 \text{ mm}$$

Max. Allowable Working Pressure at given Thickness, corroded [MAWP]:

Less Operating Hydrostatic Head Pressure of 1.843 KPa.

$$= (2 \cdot S \cdot E \cdot t) / (K_{cor} \cdot D + 0.2 \cdot t) \text{ per Appendix 1-4 (c)}$$

$$= (2 \cdot 137 \cdot 1 \cdot 10.2) / (0.96 \cdot 195 + 0.2 \cdot 10.2)$$

$$= 14751 - 1.84 = 14749 \text{ KPa.}$$

Maximum Allowable Pressure, New and Cold [MAPNC]:

$$= (2 \cdot S \cdot E \cdot t) / (K \cdot D + 0.2 \cdot t) \text{ per Appendix 1-4 (c)}$$

$$= (2 \cdot 138 \cdot 1 \cdot 13.2) / (1 \cdot 189 + 0.2 \cdot 13.2)$$

$$= 18985 \text{ KPa.}$$



PV Elite 28 Licensee: SL User
 FileName : 161-C1-C2 _(Stack) Page 41 of 204
 Element: LHS dish end Step: 6 9:40am Sep 9,2026

Actual stress at given pressure and thickness, corroded [Sact]:

$$= (P \cdot (K_{cor} \cdot D + 0.2 \cdot t)) / (2 \cdot E \cdot t)$$

$$= (2402 \cdot (0.96 \cdot 195 + 0.2 \cdot 10.2)) / (2 \cdot 1 \cdot 10.2)$$

$$= 22.339 \text{ N./mm}^2$$

Straight Flange Required Thickness:

$$= (P \cdot R) / (S \cdot E - 0.6 \cdot P) + c \text{ per UG-27 (c)(1)}$$

$$= (2402 \cdot 97.5) / (137 \cdot 1 - 0.6 \cdot 2402) + 3$$

$$= 4.725 \text{ mm}$$

Straight Flange Maximum Allowable Working Pressure:

[Less Operating Hydrostatic Head Pressure of 1.843 KPa.](#)

$$= (S \cdot E \cdot t) / (R + 0.6 \cdot t) \text{ per UG-27 (c)(1)}$$

$$= (137 \cdot 1 \cdot 12.1) / (97.5 + 0.6 \cdot 12.1)$$

$$= 15803 - 1.84 = 15802 \text{ KPa.}$$

Factor K, corroded condition [Kcor]:

$$= (2 + (\text{Inside Diameter} / (2 \cdot \text{Inside Head Depth})))^2 / 6$$

$$= (2 + (195 / (2 \cdot 50.2)))^2 / 6$$

$$= 0.960784$$

Percent Elong. per UCS-79, VIII-1-01-57 $(75 \cdot t_{nom} / R_f) \cdot (1 - R_f / R_o)$ 28.489 %

[Note: Please Check Requirements of UCS-79 as Elongation is > 5%.](#)

MDMT Calculations in the Knuckle Portion:

Govrn. thk, tg = 13.2, tr = 3.12, c = 3 mm, E* = 1
 Thickness Ratio = $tr \cdot E^* / (tg - c) = 0.31$, Temp. Reduction = 78 °C

Min Metal Temp. w/o impact per UCS-66, Curve B	-20 °C
Min Metal Temp. at Required thickness (UCS 66.1)	-104 °C
Min Metal Temp. w/o impact per UG-20(f)	-29 °C

MDMT Calculations in the Head Straight Flange:

Govrn. thk, tg = 15.1, tr = 3.31, c = 3 mm, E* = 1
 Thickness Ratio = $tr \cdot E^* / (tg - c) = 0.27$, Temp. Reduction = 78 °C

Min Metal Temp. w/o impact per UCS-66, Curve B	-16 °C
Min Metal Temp. at Required thickness (UCS 66.1)	-104 °C
Min Metal Temp. w/o impact per UG-20(f)	-29 °C

MDMT Design Information:			
MDMT Curve	B	Press. at MDMT	4587.820 KPa.
UCS-66(b) red.	Yes	Min. Des. Mtl. Temp.	-12 °C
Governing Thk.	13.179 mm	Basic MDMT	-20 °C
Stress/Thk. Ratio	0.307	Temperature Difference	84 °C
UCS-66(c) red.	No	Computed Min. Temp.	-104 °C
		MDMT per UG-20(f)	-29 °C
		Joint Efficiency E*	100 %

[Note: Temperature values displayed above are for the location with the highest basic MDMT](#)

Tolerance for Formed Heads per UG-81(a):

Head inner surface maximum deviation outside the specified shape, 1.25% of D: 2.362 mm
 Head inner surface maximum deviation inside the specified shape, 0.625% of D: 1.181 mm

EXTERNAL PRESSURE RESULTS for: LHS dish end

Elliptical Head From 10 to 20 Ext. Chart: CS-2 at 270 °C



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)

Page 42 of 204

Element: LHS dish end

Step: 6

9:40am

Sep 9,2026

Elastic Modulus from Chart: CS-2 at 270 °C: 184606480 KPa.

Results for Maximum Allowable Ext. Pressure				MAEP
Tca	Outer Dia	Do/t	Factor A	Factor B
10.179	215.31	21.15	0.0065664	94.80

$$MAEP = B/(K0*Do/t) = 94.8/(0.9 * 21.2) = 4980 \text{ KPa.}$$

Results for Required Thickness				Tca
Tca	Outer Dia	Do/t	Factor A	Factor B
0.580	215.31	371.11	0.0003742	34.55

$$MAEP = B/(K0*Do/t) = 34.5/(0.9 * 371) = 103 \text{ KPa.}$$

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)

Page 43 of 204

Element: LHS Ch Shell


Step: 7

9:40am

Sep 9, 2026

Internal Pressure Calculation Results:

ASME Code, Section VIII Division 1, 2025



Internal Pressure Results for: LHS Ch Shell

Cylindrical Shell Design Information:			
Design Pressure P	2401.843 KPa.	Int. Design Temperature	270 °C
Material	SA-106 B	Ext. Design Temperature	270 °C
Length	300.000 mm	External Pressure Chart	CS-2
		UNS Number	K03006
Int. Corr. All. c	3.0000 mm	Allowable Stress (ope) S	118.0 N./mm ²
Ext. Corr. All. ce	0.0000 mm	Allowable Stress (amb) Sa	118.0 N./mm ²
Inside Diameter Di	188.951 mm	Actual Stress	24.4 N./mm ²
Spec. Min. Thk t _e , or sa	13.1794 mm	Spec. Nominal Thk.	15.062 mm
Surface Area	2064.7 cm ²	SG of Contents	1.000
Element Volume	8413.7 cm ³	Weight of Contents	8.4 Kg
Empty Weight	22.4 Kg	Operating Weight	30.8 Kg
		Comp. All. Ope. Stress	123.6 N./mm ²

Radiography Information:			
User Defined		User Defined	
Circ. Joint Efficiency	100 %	Long. Joint Eff.	E or v 100 %

Required Thickness due to Internal Pressure [tr]:

$$\begin{aligned}
 &= (P \cdot R) / (S \cdot E - 0.6 \cdot P) \text{ per UG-27 (c)(1)} \\
 &= (2402 \cdot 97.5) / (118 \cdot 1 - 0.6 \cdot 2402) \\
 &= 2.0088 + 3.0000 = 5.0088 \text{ mm}
 \end{aligned}$$

Max. Allowable Working Pressure at given Thickness, corroded [MAWP]:

Less Operating Hydrostatic Head Pressure of 1.843 KPa.

$$\begin{aligned}
 &= (S \cdot E \cdot t) / (R + 0.6 \cdot t) \text{ per UG-27 (c)(1)} \\
 &= (118 \cdot 1 \cdot 10.2) / (97.5 + 0.6 \cdot 10.2) \\
 &= 11595 - 1.84 = 11594 \text{ KPa.}
 \end{aligned}$$

Maximum Allowable Pressure, New and Cold [MAPNC]:

$$\begin{aligned}
 &= (S \cdot E \cdot t) / (R + 0.6 \cdot t) \text{ per UG-27 (c)(1)} \\
 &= (118 \cdot 1 \cdot 13.2) / (94.5 + 0.6 \cdot 13.2) \\
 &= 15189 \text{ KPa.}
 \end{aligned}$$

Actual stress at given pressure and thickness, corroded [Sact]:

$$\begin{aligned}
 &= (P \cdot (R + 0.6 \cdot t)) / (E \cdot t) \\
 &= (2402 \cdot (97.5 + 0.6 \cdot 10.2)) / (1 \cdot 10.2) \\
 &= 24.442 \text{ N./mm}^2
 \end{aligned}$$



PV Elite 28 Licensee: SL User
 FileName : 161-C1-C2 _(Stack) Page 44 of 204
 Element: LHS Ch Shell Step: 7 9:40am Sep 9,2026

Minimum Design Metal Temperature Results:

Govrn. thk, tg = 13.2, tr = 1.88, c = 3 mm, E* = 1
 Thickness Ratio = tr * E*/(tg - c) = 0.18, Temp. Reduction = 78 °C

Min Metal Temp. w/o impact per UCS-66, Curve B -20 °C
 Min Metal Temp. at Required thickness (UCS 66.1) -104 °C
 Min Metal Temp. w/o impact per UG-20(f) -29 °C

MDMT Design Information:			
MDMT Curve	B	Press. at MDMT	4587.820 KPa.
UCS-66(b) red.	Yes	Min. Des. Mtl. Temp.	-12 °C
Governing Thk.	13.179 mm	Basic MDMT	-20 °C
Stress/Thk. Ratio	0.185	Temperature Difference	84 °C
UCS-66(c) red.	No	Computed Min. Temp.	-104 °C
		MDMT per UG-20(f)	-29 °C
		Joint Efficiency E*	100 %

EXTERNAL PRESSURE RESULTS for: LHS Ch Shell

Cylindrical Shell From 20 to 30 Ext. Chart: CS-2 at 270 °C

Elastic Modulus from Chart: CS-2 at 270 °C: 184606480 KPa.

Results for Maximum Allowable Ext. Pressure				MAEP		
Tca	Outer Dia	Slen	Do/t	L/D	Factor A	Factor B
10.179	215.31	366.55	21.15	1.7024	0.0079202	97.44

$$MAEP = (4*B)/(3*(Do/t)) = (4*97.4)/(3*21.2) = 6142 \text{ KPa.}$$

Results for Required Thickness				Tca		
Tca	Outer Dia	Slen	Do/t	L/D	Factor A	Factor B
0.889	215.31	366.55	242.09	1.7024	0.0002034	18.78

$$MAEP = (4*B)/(3*(Do/t)) = (4*18.8)/(3*242) = 103 \text{ KPa.}$$

Results for Maximum Stiffened Length				Slen		
Tca	Outer Dia	Slen	Do/t	L/D	Factor A	Factor B
10.179	215.31	19863.49	21.15	50.0000	0.0024904	80.91

$$MAEP = (4*B)/(3*(Do/t)) = (4*80.9)/(3*21.2) = 5100 \text{ KPa.}$$

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 45 of 204

Element: Main Shell


Step: 8

9:40am

Sep 9,2026

Internal Pressure Calculation Results:

ASME Code, Section VIII Division 1, 2025



Internal Pressure Results for: Main Shell

Cylindrical Shell Design Information:			
Design Pressure P	2401.843 KPa.	Int. Design Temperature	260 °C
Material	SA-106 B	Ext. Design Temperature	260 °C
Length	5785.000 mm	External Pressure Chart	CS-2
		UNS Number	K03006
Int. Corr. All. c	3.0000 mm	Allowable Stress (ope) S	118.0 N./mm ²
Ext. Corr. All. ce	0.0000 mm	Allowable Stress (amb) Sa	118.0 N./mm ²
Inside Diameter Di	188.951 mm	Actual Stress	24.4 N./mm ²
Spec. Min. Thk t,e, or sa	13.1794 mm	Spec. Nominal Thk.	15.062 mm
Surface Area	39814.9 cm ²	SG of Contents	1.000
Element Volume	102874.1 cm ³	Weight of Contents	102.8 Kg
Empty Weight	432.8 Kg	Operating Weight	535.7 Kg
		Comp. All. Ope. Stress	125.6 N./mm ²

Radiography Information:			
User Defined		User Defined	
Circ. Joint Efficiency	100 %	Long. Joint Eff.	E or v 100 %

Required Thickness due to Internal Pressure [tr]:

$$\begin{aligned}
 &= (P \cdot R) / (S \cdot E - 0.6 \cdot P) \text{ per UG-27 (c)(1)} \\
 &= (2402 \cdot 97.5) / (118 \cdot 1 - 0.6 \cdot 2402) \\
 &= 2.0088 + 3.0000 = 5.0088 \text{ mm}
 \end{aligned}$$

Max. Allowable Working Pressure at given Thickness, corroded [MAWP]:

Less Operating Hydrostatic Head Pressure of 1.843 KPa.

$$\begin{aligned}
 &= (S \cdot E \cdot t) / (R + 0.6 \cdot t) \text{ per UG-27 (c)(1)} \\
 &= (118 \cdot 1 \cdot 10.2) / (97.5 + 0.6 \cdot 10.2) \\
 &= 11595 - 1.84 = 11594 \text{ KPa.}
 \end{aligned}$$

Maximum Allowable Pressure, New and Cold [MAPNC]:

$$\begin{aligned}
 &= (S \cdot E \cdot t) / (R + 0.6 \cdot t) \text{ per UG-27 (c)(1)} \\
 &= (118 \cdot 1 \cdot 13.2) / (94.5 + 0.6 \cdot 13.2) \\
 &= 15189 \text{ KPa.}
 \end{aligned}$$

Actual stress at given pressure and thickness, corroded [Sact]:

$$\begin{aligned}
 &= (P \cdot (R + 0.6 \cdot t)) / (E \cdot t) \\
 &= (2402 \cdot (97.5 + 0.6 \cdot 10.2)) / (1 \cdot 10.2) \\
 &= 24.442 \text{ N./mm}^2
 \end{aligned}$$



PV Elite 28 Licensee: SL User
 FileName : 161-C1-C2 _(Stack) Page 46 of 204
 Element: Main Shell Step: 8 9:40am Sep 9,2026

Minimum Design Metal Temperature Results:

Govrn. thk, tg = 13.2, tr = 2.05, c = 3 mm, E* = 1
 Thickness Ratio = tr * E*/(tg - c) = 0.2, Temp. Reduction = 78 °C

Min Metal Temp. w/o impact per UCS-66, Curve B -20 °C
 Min Metal Temp. at Required thickness (UCS 66.1) -104 °C
 Min Metal Temp. w/o impact per UG-20(f) -29 °C

MDMT Design Information:			
MDMT Curve	B	Press. at MDMT	5003.981 KPa.
UCS-66(b) red.	Yes	Min. Des. Mtl. Temp.	-12 °C
Governing Thk.	13.179 mm	Basic MDMT	-20 °C
Stress/Thk. Ratio	0.201	Temperature Difference	84 °C
UCS-66(c) red.	No	Computed Min. Temp.	-104 °C
		MDMT per UG-20(f)	-29 °C
		Joint Efficiency E*	100 %

EXTERNAL PRESSURE RESULTS for: Main Shell

Cylindrical Shell From 40 to Ring R1 Fr40 Ext. Chart: CS-2 at 260 °C

Elastic Modulus from Chart: CS-2 at 260 °C: 186156960 KPa.

Results for Maximum Allowable Ext. Pressure				MAEP		
Tca	Outer Dia	Slen	Do/t	L/D	Factor A	Factor B
10.179	215.31	1200.00	21.15	5.5734	0.0027364	83.65

$$MAEP = (4*B)/(3*(Do/t)) = (4*83.7)/(3*21.2) = 5273 \text{ KPa.}$$

Results for Required Thickness				Tca		
Tca	Outer Dia	Slen	Do/t	L/D	Factor A	Factor B
1.472	215.31	1200.00	146.28	5.5734	0.0001219	11.35

$$MAEP = (4*B)/(3*(Do/t)) = (4*11.3)/(3*146) = 103 \text{ KPa.}$$

Results for Maximum Stiffened Length				Slen		
Tca	Outer Dia	Slen	Do/t	L/D	Factor A	Factor B
10.179	215.31	60676.85	21.15	50.0000	0.0024904	82.27

$$MAEP = (4*B)/(3*(Do/t)) = (4*82.3)/(3*21.2) = 5186 \text{ KPa.}$$

Cylindrical Shell From Ring R1 Fr40 to Ring R2 Fr40 Ext. Chart: CS-2 at 260 °C

Elastic Modulus from Chart: CS-2 at 260 °C: 186156960 KPa.

Results for Maximum Allowable Ext. Pressure				MAEP		
Tca	Outer Dia	Slen	Do/t	L/D	Factor A	Factor B
10.179	215.31	3450.00	21.15	16.0234	0.0025207	82.45

$$MAEP = (4*B)/(3*(Do/t)) = (4*82.4)/(3*21.2) = 5197 \text{ KPa.}$$



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 47 of 204

Element: Main Shell

Step: 8

9:40am

Sep 9,2026

Results for Required Thickness					Tca	
Tca	Outer Dia	Slen	Do/t	L/D	Factor A	Factor B
1.931	215.31	3450.00	111.52	16.0234	0.0000929	8.65

$$MAEP = (4*B)/(3*(Do/t)) = (4*8.65)/(3*112) = 103 \text{ KPa.}$$

Results for Maximum Stiffened Length					Slen	
Tca	Outer Dia	Slen	Do/t	L/D	Factor A	Factor B
10.179	215.31	173183.92	21.15	50.0000	0.0024904	82.27

$$MAEP = (4*B)/(3*(Do/t)) = (4*82.3)/(3*21.2) = 5186 \text{ KPa.}$$

Cylindrical Shell From Ring R2 Fr40 to 50 Ext. Chart: CS-2 at 260 °C

Elastic Modulus from Chart: CS-2 at 260 °C: 186156960 KPa.

Results for Maximum Allowable Ext. Pressure					MAEP	
Tca	Outer Dia	Slen	Do/t	L/D	Factor A	Factor B
10.179	215.31	1135.00	21.15	5.2715	0.0027734	83.85

$$MAEP = (4*B)/(3*(Do/t)) = (4*83.9)/(3*21.2) = 5285 \text{ KPa.}$$

Results for Required Thickness					Tca	
Tca	Outer Dia	Slen	Do/t	L/D	Factor A	Factor B
1.438	215.31	1135.00	149.71	5.2715	0.0001248	11.61

$$MAEP = (4*B)/(3*(Do/t)) = (4*11.6)/(3*150) = 103 \text{ KPa.}$$

Results for Maximum Stiffened Length					Slen	
Tca	Outer Dia	Slen	Do/t	L/D	Factor A	Factor B
10.179	215.31	57460.54	21.15	50.0000	0.0024904	82.27

$$MAEP = (4*B)/(3*(Do/t)) = (4*82.3)/(3*21.2) = 5186 \text{ KPa.}$$

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)

Page 48 of 204

Element: RHS Ch Shell


Step: 9

9:40am

Sep 9, 2026

Internal Pressure Calculation Results:

ASME Code, Section VIII Division 1, 2025



Internal Pressure Results for: RHS Ch Shell

Cylindrical Shell Design Information:			
Design Pressure P	2401.843 KPa.	Int. Design Temperature	270 °C
Material	SA-106 B	Ext. Design Temperature	270 °C
Length	300.000 mm	External Pressure Chart	CS-2
		UNS Number	K03006
Int. Corr. All. c	3.0000 mm	Allowable Stress (ope) S	118.0 N./mm ²
Ext. Corr. All. ce	0.0000 mm	Allowable Stress (amb) Sa	118.0 N./mm ²
Inside Diameter Di	188.951 mm	Actual Stress	24.4 N./mm ²
Spec. Min. Thk t _e , or s _a	13.1794 mm	Spec. Nominal Thk.	15.062 mm
Surface Area	2064.7 cm ²	SG of Contents	1.000
Element Volume	8413.7 cm ³	Weight of Contents	8.4 Kg
Empty Weight	22.4 Kg	Operating Weight	30.8 Kg
		Comp. All. Ope. Stress	125.6 N./mm ²

Radiography Information:			
User Defined		User Defined	
Circ. Joint Efficiency	100 %	Long. Joint Eff.	E or v 100 %

Required Thickness due to Internal Pressure [tr]:

$$\begin{aligned}
 &= (P \cdot R) / (S \cdot E - 0.6 \cdot P) \text{ per UG-27 (c)(1)} \\
 &= (2402 \cdot 97.5) / (118 \cdot 1 - 0.6 \cdot 2402) \\
 &= 2.0088 + 3.0000 = 5.0088 \text{ mm}
 \end{aligned}$$

Max. Allowable Working Pressure at given Thickness, corroded [MAWP]:

Less Operating Hydrostatic Head Pressure of 1.843 KPa.

$$\begin{aligned}
 &= (S \cdot E \cdot t) / (R + 0.6 \cdot t) \text{ per UG-27 (c)(1)} \\
 &= (118 \cdot 1 \cdot 10.2) / (97.5 + 0.6 \cdot 10.2) \\
 &= 11595 - 1.84 = 11594 \text{ KPa.}
 \end{aligned}$$

Maximum Allowable Pressure, New and Cold [MAPNC]:

$$\begin{aligned}
 &= (S \cdot E \cdot t) / (R + 0.6 \cdot t) \text{ per UG-27 (c)(1)} \\
 &= (118 \cdot 1 \cdot 13.2) / (94.5 + 0.6 \cdot 13.2) \\
 &= 15189 \text{ KPa.}
 \end{aligned}$$

Actual stress at given pressure and thickness, corroded [Sact]:

$$\begin{aligned}
 &= (P \cdot (R + 0.6 \cdot t)) / (E \cdot t) \\
 &= (2402 \cdot (97.5 + 0.6 \cdot 10.2)) / (1 \cdot 10.2) \\
 &= 24.442 \text{ N./mm}^2
 \end{aligned}$$



PV Elite 28 Licensee: SL User
 FileName : 161-C1-C2 _(Stack) Page 49 of 204
 Element: RHS Ch Shell Step: 9 9:40am Sep 9,2026

Minimum Design Metal Temperature Results:

Govrn. thk, tg = 13.2, tr = 1.88, c = 3 mm, E* = 1
 Thickness Ratio = tr * E*/(tg - c) = 0.18, Temp. Reduction = 78 °C

Min Metal Temp. w/o impact per UCS-66, Curve B -20 °C
 Min Metal Temp. at Required thickness (UCS 66.1) -104 °C
 Min Metal Temp. w/o impact per UG-20(f) -29 °C

MDMT Design Information:			
MDMT Curve	B	Press. at MDMT	4587.820 KPa.
UCS-66(b) red.	Yes	Min. Des. Mtl. Temp.	-12 °C
Governing Thk.	13.179 mm	Basic MDMT	-20 °C
Stress/Thk. Ratio	0.185	Temperature Difference	84 °C
UCS-66(c) red.	No	Computed Min. Temp.	-104 °C
		MDMT per UG-20(f)	-29 °C
		Joint Efficiency E*	100 %

EXTERNAL PRESSURE RESULTS for: RHS Ch Shell

Cylindrical Shell From 60 to 70 Ext. Chart: CS-2 at 270 °C

Elastic Modulus from Chart: CS-2 at 270 °C: 184606480 KPa.

Results for Maximum Allowable Ext. Pressure				MAEP		
Tca	Outer Dia	Slen	Do/t	L/D	Factor A	Factor B
10.179	215.31	366.55	21.15	1.7024	0.0079202	97.44

$$MAEP = (4*B)/(3*(Do/t)) = (4*97.4)/(3*21.2) = 6142 \text{ KPa.}$$

Results for Required Thickness				Tca		
Tca	Outer Dia	Slen	Do/t	L/D	Factor A	Factor B
0.889	215.31	366.55	242.09	1.7024	0.0002034	18.78

$$MAEP = (4*B)/(3*(Do/t)) = (4*18.8)/(3*242) = 103 \text{ KPa.}$$

Results for Maximum Stiffened Length				Slen		
Tca	Outer Dia	Slen	Do/t	L/D	Factor A	Factor B
10.179	215.31	19863.49	21.15	50.0000	0.0024904	80.91


$$MAEP = (4*B)/(3*(Do/t)) = (4*80.9)/(3*21.2) = 5100 \text{ KPa.}$$

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



Internal Pressure Calculation Results:

ASME Code, Section VIII Division 1, 2025



Internal Pressure Results for: RHS Dish End

Elliptical Head Design Information:					
Design Pressure	P	2401.843 KPa.	Int. Design Temperature		270 °C
Material		SA-516 70	Ext. Design Temperature		270 °C
Length		50.800 mm	External Pressure Chart		CS-2
			UNS Number		K02700
Int. Corr. All.	c	3.0000 mm	Allowable Stress (ope)	S	137.2 N./mm ²
Ext. Corr. All.	ce	0.0000 mm	Allowable Stress (amb)	Sa	138.0 N./mm ²
Inside Diameter	Di	188.951 mm	Actual Stress		37.6 N./mm ²
Spec. Min. Thk t,e, or sa		9.0233 mm	Spec. Nominal Thk.		10.312 mm
Surface Area		810.6 cm ²	SG of Contents		1.000
Element Volume		2307.9 cm ³	Weight of Contents		2.3 Kg
Empty Weight		6.3 Kg	Operating Weight		8.6 Kg
			Comp. All. Ope. Stress		123.6 N./mm ²
			Aspect Ratio		2.00
Radiography Information:					
User Defined			User Defined		
Circ. Joint Efficiency		100 %	Long. Joint Eff.	E or v	100 %

Tolerance for Formed Heads per UG-81(a):

Head inner surface maximum deviation outside the specified shape, 1.25% of D: 2.362 mm
 Head inner surface maximum deviation inside the specified shape, 0.625% of D: 1.181 mm

Required Thickness due to Internal Pressure [tr]:

$$= (P \cdot D \cdot K_{cor}) / (2 \cdot S \cdot E - 0.2 \cdot P) \text{ Appendix 1-4(c)}$$

$$= (2402 \cdot 195 \cdot 0.96) / (2 \cdot 137 \cdot 1 - 0.2 \cdot 2402)$$

$$= 1.6425 + 3.0000 = 4.6425 \text{ mm}$$

Max. Allowable Working Pressure at given Thickness, corroded [MAWP]:

Less Operating Hydrostatic Head Pressure of 1.843 KPa.

$$= (2 \cdot S \cdot E \cdot t) / (K_{cor} \cdot D + 0.2 \cdot t) \text{ per Appendix 1-4 (c)}$$

$$= (2 \cdot 137 \cdot 1 \cdot 6.02) / (0.96 \cdot 195 + 0.2 \cdot 6.02)$$

$$= 8767 - 1.84 = 8765 \text{ KPa.}$$

Maximum Allowable Pressure, New and Cold [MAPNC]:

$$= (2 \cdot S \cdot E \cdot t) / (K \cdot D + 0.2 \cdot t) \text{ per Appendix 1-4 (c)}$$

$$= (2 \cdot 138 \cdot 1 \cdot 9.02) / (1 \cdot 189 + 0.2 \cdot 9.02)$$

$$= 13055 \text{ KPa.}$$



PV Elite 28 Licensee: SL User
 FileName : 161-C1-C2 _(Stack) Page 51 of 204
 Element: RHS Dish End Step: 10 9:40am Sep 9,2026

Actual stress at given pressure and thickness, corroded [Sact]:

$$= (P \cdot (K_{cor} \cdot D + 0.2 \cdot t)) / (2 \cdot E \cdot t)$$

$$= (2402 \cdot (0.96 \cdot 195 + 0.2 \cdot 6.02)) / (2 \cdot 1 \cdot 6.02)$$

$$= 37.587 \text{ N./mm}^2$$

Straight Flange Required Thickness:

$$= (P \cdot R) / (S \cdot E - 0.6 \cdot P) + c \text{ per UG-27 (c)(1)}$$

$$= (2402 \cdot 97.5) / (137 \cdot 1 - 0.6 \cdot 2402) + 3$$

$$= 4.725 \text{ mm}$$

Straight Flange Maximum Allowable Working Pressure:

[Less Operating Hydrostatic Head Pressure of 1.843 KPa.](#)

$$= (S \cdot E \cdot t) / (R + 0.6 \cdot t) \text{ per UG-27 (c)(1)}$$

$$= (137 \cdot 1 \cdot 7.31) / (97.5 + 0.6 \cdot 7.31)$$

$$= 9848 - 1.84 = 9847 \text{ KPa.}$$

Factor K, corroded condition [Kcor]:

$$= (2 + (\text{Inside Diameter} / (2 \cdot \text{Inside Head Depth})))^2 / 6$$

$$= (2 + (195 / (2 \cdot 50.2)))^2 / 6$$

$$= 0.960784$$

Percent Elong. per UCS-79, VIII-1-01-57 $(75 \cdot t_{nom} / R_f) \cdot (1 - R_f / R_o)$ 20.748 %

[Note: Please Check Requirements of UCS-79 as Elongation is > 5%.](#)

MDMT Calculations in the Knuckle Portion:

Govrn. thk, tg = 9.02, tr = 3.12, c = 3 mm, E* = 1
 Thickness Ratio = $tr \cdot E* / (tg - c) = 0.52$, Temp. Reduction = 30 °C

Min Metal Temp. w/o impact per UCS-66, Curve B -29 °C
 Min Metal Temp. at Required thickness (UCS 66.1) -48 °C

MDMT Calculations in the Head Straight Flange:

Govrn. thk, tg = 10.3, tr = 3.31, c = 3 mm, E* = 1
 Thickness Ratio = $tr \cdot E* / (tg - c) = 0.45$, Temp. Reduction = 40 °C

Min Metal Temp. w/o impact per UCS-66, Curve B -28 °C
 Min Metal Temp. at Required thickness (UCS 66.1) -48 °C
 Min Metal Temp. w/o impact per UG-20(f) -29 °C

MDMT Design Information:			
MDMT Curve	B	Press. at MDMT	4587.820 KPa.
UCS-66(b) red.	Yes	Min. Des. Mtl. Temp.	-12 °C
Governing Thk.	9.023 mm	Basic MDMT	-29 °C
Stress/Thk. Ratio	0.519	Temperature Difference	19 °C
UCS-66(c) red.	No	Computed Min. Temp.	-48 °C
		MDMT per UG-20(f)	-29 °C
		Joint Efficiency E*	100 %

[Note: Temperature values displayed above are for the location with the highest basic MDMT](#)

Tolerance for Formed Heads per UG-81(a):

Head inner surface maximum deviation outside the specified shape, 1.25% of D: 2.362 mm
 Head inner surface maximum deviation inside the specified shape, 0.625% of D: 1.181 mm

EXTERNAL PRESSURE RESULTS for: RHS Dish End

Elliptical Head From 70 to 80 Ext. Chart: CS-2 at 270 °C

Elastic Modulus from Chart: CS-2 at 270 °C: 184606480 KPa.



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)

Page 52 of 204

Element: RHS Dish End

Step: 10

9:40am

Sep 9, 2026

Results for Maximum Allowable Ext. Pressure				MAEP
Tca	Outer Dia	Do/t	Factor A	Factor B
6.023	207.00	34.37	0.0040415	87.89

$$\text{MAEP} = B / (K_0 * \text{Do} / t) = 87.9 / (0.9 * 34.4) = 2842 \text{ KPa.}$$

Results for Required Thickness				Tca
Tca	Outer Dia	Do/t	Factor A	Factor B
0.558	207.00	371.11	0.0003743	34.55

$$\text{MAEP} = B / (K_0 * \text{Do} / t) = 34.5 / (0.9 * 371) = 103 \text{ KPa.}$$

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User
 FileName : 161-C1-C2 _(Stack) Page 53 of 204
 Shop Pressure Test Results: Step: 11 9:40am Sep 9,2026

Hydrostatic Test Pressure Results:

Exchanger Shell Side Hydrostatic Test Pressures:

UG99(b)	= 1.30 * M.A.W.P. * Sa/S	6505.176 KPa.
UG99b(b)(35)	= 1.30 * Design Pres * Sa/S	3120.000 KPa.
UG99(c)	= 1.30 * M.A.P. - Head(Hyd)	13260.004 KPa.
UG100	= 1.10 * M.A.W.P. * Sa/S	5504.380 KPa.
PED	= max(1.43*DP, 1.25*DP*ratio)	3432.000 KPa.
PED&UG99(b)(35)	= max(1.43*DP, 1.3*DP*ratio)	3432.000 KPa.
App 27-4	= M.A.W.P.	5003.981 KPa.

Exchanger Channel Side Hydrostatic Test Pressures:

UG99(b)	= 1.30 * M.A.W.P. * Sa/S	5964.167 KPa.
UG99b(b)(35)	= 1.30 * Design Pres * Sa/S	3120.000 KPa.
UG99(c)	= 1.30 * M.A.P. - Head(Hyd)	10387.897 KPa.
UG100	= 1.10 * M.A.W.P. * Sa/S	5046.603 KPa.
PED	= max(1.43*DP, 1.25*DP*ratio)	3432.000 KPa.
PED&UG99(b)(35)	= max(1.43*DP, 1.3*DP*ratio)	3432.000 KPa.
App 27-4	= M.A.W.P.	4587.820 KPa.

Horizontal Test performed per: UG-99c

Please note that Nozzle, Shell, Head, Flange, etc MAWPs are all considered when determining the hydrotest pressure for those test types that are based on the MAWP of the vessel.

Stresses on Elements due to Test Pressure (N./mm² & KPa.):

From To	Stress	Allowable	Ratio	Pressure
LHS dish end	96.6	234.0	0.413	10389.75
LHS Ch Shell	105.7	216.0	0.489	10389.75
Main Shell	135.0	216.0	0.625	13261.86
RHS Ch Shell	105.7	216.0	0.489	10389.75
RHS Dish End	162.6	234.0	0.695	10389.75

Stress ratios for Nozzle and Pad Materials (N./mm²):

Description	Pad/Nozzle	Ambient	Operating	Ratio
N1-Tube Inlet	Nozzle	118.00	118.00	1.000
N1-Tube Inlet	Pad	138.00	137.20	1.006
N3-Shell inlet	Nozzle	118.00	118.00	1.000
N3-Shell inlet	Pad	138.00	137.60	1.003
N4-Shell outlet	Nozzle	118.00	118.00	1.000
N4-Shell outlet	Pad	138.00	137.60	1.003
N2-Tube Outlet	Nozzle	118.00	118.00	1.000
N2-Tube Outlet	Pad	138.00	137.20	1.006

Minimum 1.000

Stress ratios for Stiffening Ring Materials (N./mm²):

Description	Ambient	Operating	Ratio
Ring R1 Fr40	138.00	137.60	1.003
Ring R2 Fr40	138.00	137.60	1.003

Minimum 1.003

Stress ratios for Pressurized Vessel Elements (N./mm²):



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 54 of 204

Shop Pressure Test Results:

Step: 11

9:40am

Sep 9, 2026

Description	Ambient	Operating	Ratio
LHS dish end	138.00	137.20	1.006
LHS Ch Shell	118.00	118.00	1.000
LHS Ch Flange	138.00	133.20	1.036
Main Shell	118.00	118.00	1.000
RHS Ch Flg	138.00	134.60	1.025
RHS Ch Shell	118.00	118.00	1.000
RHS Dish End	138.00	137.20	1.006

Minimum

1.000

Stress ratios for Exchanger Materials (N./mm²):

Description	Ambient	Operating	Ratio
Tube Material	92.40	92.30	1.001
Tubesheet Material	138.00	134.60	1.025

Minimum

1.001

Hoop Stress in Nozzle Wall during Pressure Test (N./mm²):

Description	Ambient	Operating	Ratio
N1-Tube Inlet	53.64	216.00	0.248
N3-Shell inlet	68.47	216.00	0.317
N4-Shell outlet	68.47	216.00	0.317
N2-Tube Outlet	53.64	216.00	0.248

Elements Suitable for Test Pressure.

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User
 FileName : 161-C1-C2 _(Stack) Page 55 of 204
 Field Pressure Test Results: Step: 12 9:40am Sep 9,2026

Hydrostatic Test Pressure Results:

Exchanger Shell Side Hydrostatic Test Pressures:

UG99(b)	= 1.30 * M.A.W.P. * Sa/S	6505.176 KPa.
UG99b(b)(35)	= 1.30 * Design Pres * Sa/S	3120.000 KPa.
UG99(c)	= 1.30 * M.A.P. - Head(Hyd)	13260.004 KPa.
UG100	= 1.10 * M.A.W.P. * Sa/S	5504.380 KPa.
PED	= max(1.43*DP, 1.25*DP*ratio)	3432.000 KPa.
PED&UG99(b)(35)	= max(1.43*DP, 1.3*DP*ratio)	3432.000 KPa.
App 27-4	= M.A.W.P.	5003.981 KPa.

Exchanger Channel Side Hydrostatic Test Pressures:

UG99(b)	= 1.30 * M.A.W.P. * Sa/S	5964.167 KPa.
UG99b(b)(35)	= 1.30 * Design Pres * Sa/S	3120.000 KPa.
UG99(c)	= 1.30 * M.A.P. - Head(Hyd)	10387.897 KPa.
UG100	= 1.10 * M.A.W.P. * Sa/S	5046.603 KPa.
PED	= max(1.43*DP, 1.25*DP*ratio)	3432.000 KPa.
PED&UG99(b)(35)	= max(1.43*DP, 1.3*DP*ratio)	3432.000 KPa.
App 27-4	= M.A.W.P.	4587.820 KPa.

UG-99(b)(35), Test Pressure Calculation [Shell Side]:

= Test Factor • Design Pressure • Stress Ratio
 = 1.3 • 2400 • 1
 = 3120.000 KPa.

UG-99(b) Note 35, Test Pressure Calculation [Channel Side]:

= Test Factor • Design Pressure • Stress Ratio
 = 1.3 • 2400 • 1
 = 3120.000 KPa.

Horizontal Test performed per: UG-99b (Note 35)

Please note that Nozzle, Shell, Head, Flange, etc MAWPs are all considered when determining the hydrotest pressure for those test types that are based on the MAWP of the vessel.

Stresses on Elements due to Test Pressure (N./mm² & KPa.):

From To	Stress	Allowable	Ratio	Pressure
LHS dish end	29.0	234.0	0.124	3121.85
LHS Ch Shell	31.8	216.0	0.147	3121.85
Main Shell	31.8	216.0	0.147	3121.85
RHS Ch Shell	31.8	216.0	0.147	3121.85
RHS Dish End	48.9	234.0	0.209	3121.85

Stress ratios for Nozzle and Pad Materials (N./mm²):

Description	Pad/Nozzle	Ambient	Operating	Ratio
N1-Tube Inlet	Nozzle	118.00	118.00	1.000
N1-Tube Inlet	Pad	138.00	137.20	1.006
N3-Shell inlet	Nozzle	118.00	118.00	1.000
N3-Shell inlet	Pad	138.00	137.60	1.003
N4-Shell outlet	Nozzle	118.00	118.00	1.000
N4-Shell outlet	Pad	138.00	137.60	1.003
N2-Tube Outlet	Nozzle	118.00	118.00	1.000
N2-Tube Outlet	Pad	138.00	137.20	1.006

Minimum

1.000



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 56 of 204

Field Pressure Test Results: Step: 12 9:40am Sep 9, 2026

Stress ratios for Stiffening Ring Materials (N./mm²):

Description	Ambient	Operating	Ratio
Ring R1 Fr40	138.00	137.60	1.003
Ring R2 Fr40	138.00	137.60	1.003

Minimum 1.003

Stress ratios for Pressurized Vessel Elements (N./mm²):

Description	Ambient	Operating	Ratio
LHS dish end	138.00	137.20	1.006
LHS Ch Shell	118.00	118.00	1.000
LHS Ch Flange	138.00	133.20	1.036
Main Shell	118.00	118.00	1.000
RHS Ch Flg	138.00	134.60	1.025
RHS Ch Shell	118.00	118.00	1.000
RHS Dish End	138.00	137.20	1.006

Minimum 1.000

Stress ratios for Exchanger Materials (N./mm²):

Description	Ambient	Operating	Ratio
Tube Material	92.40	92.30	1.001
Tubesheet Material	138.00	134.60	1.025

Minimum 1.001

Hoop Stress in Nozzle Wall during Pressure Test (N./mm²):

Description	Ambient	Operating	Ratio
N1-Tube Inlet	16.12	216.00	0.075
N3-Shell inlet	16.12	216.00	0.075
N4-Shell outlet	16.12	216.00	0.075
N2-Tube Outlet	16.12	216.00	0.075

Elements Suitable for Test Pressure.

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 57 of 204

ASME TS Calc: Pressure Test

Case: 1 9:40a Sep 9,2026

Input Echo, Tubesheet Number 1, Description: Fixed Tubesheet

Shell Data:

Main Shell Description: Main Shell

Shell Test Pressure		3120.00 KPa.
Shell Thickness	ts	15.0622 mm
Shell Internal Corrosion Allowance	cas	0.0000 mm
Shell External Corrosion Allowance	casext	0.0000 mm
Inside Diameter of Shell	Ds	188.951 mm
Shell Circumferential Joint Efficiency	Esw	1.000
Shell Temperature for Internal Pressure	Ts	21.11 °C
Shell Material		SA-106 B

See ASME VIII Div. 1, UG-23(e), for determination of the SPS allowable.

Shell Material UNS Number		K03006
Shell Allowable Stress at Temperature	Ss	118.00 N./mm ²
Shell Allowable Stress at Ambient		118.00 N./mm ²

Channel Data:

Channel Description: LHS Ch Shell

Channel Type:		Cylinder
Channel Test Pressure		3120.00 KPa.
Channel Thickness	tc	15.0622 mm
Channel Internal Corrosion Allowance	cac	0.0000 mm
Channel External Corrosion Allowance	cacext	0.0000 mm
Inside Diameter of Channel	Dc	188.951 mm
Channel Design Temperature	TEMPC	21.11 °C
Channel Flange Matl		SA-106 B

See ASME VIII Div. 1, UG-23(e), for determination of the SPS allowable.

Channel Material UNS Number		K03006
Channel Allowable Stress at Temperature	Sc	118.00 N./mm ²
Channel Allowable Stress at Ambient		118.00 N./mm ²

Tube Data:

Number of Tube Holes	Nt	81
Tube Wall Thickness	et	2.1100 mm
Tube Outside Diameter	D	12.7000 mm
Total Straight Tube Length	Lt	6000.00 mm
Straight Tube Length (bet. inner tubsht faces) L		5860.00 mm
Design Temperature of the Tubes		21.11 °C
Tube Material		SA-179
Tube Material UNS Number		K01200
Is this a Welded Tube		No
Tube Material Specification used		Smls. tube
Tube Allowable Stress at Temperature		92.40 N./mm ²
Tube Allowable Stress At Ambient		92.40 N./mm ²
Tube Yield Stress At design Temperature	Syt	180.00 N./mm ²
Tube Pitch (Center to Center Spacing)	P	15.8750 mm
Tube Layout Pattern		Triangular

Fillet Weld Leg	af	2.1100 mm
Groove Weld Leg	ag	2.1100 mm
Tube-Tubesheet Joint Weld Type		Full Strength
Method for Tube-Tubesheet Jt. Allowable		UW-20.3
Is the Tube Inset		No

Radius to Outermost Tube Hole Center	ro	80.203 mm
Largest Center-to-Center Tube Distance	Ul	0.0000 mm
Length of Expanded Portion of Tube	ltx	0.0000 mm
Tube-side pass partition groove depth	hg	0.0000 mm
Area of Tube Layout	Ap	163.7 cm ²



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 58 of 204

ASME TS Calc: Pressure Test

Case: 1 9:40a Sep 9, 2026

Perimeter of Tube Layout Cp 476.2 mm

Tubesheet Data:

Tubesheet TYPE: Fixed Tubesheet Exchanger, Conf B

Tubesheet Design Metal Temperature T 21.11 °C
Tubesheet Material SA-266 2

See ASME VIII Div. 1, UG-23(e), for determination of the SPS allowable.

Tubesheet Material UNS Number		K03506
Tubesheet Allowable Stress at Temperature	S	138.00 N./mm ²
Tubesheet Allowable Stress at Ambient	Tt	138.00 N./mm ²
Thickness of Tubesheet	h	70.0000 mm
Tubesheet Corr. Allowance (Shell side)	Cats	0.0000 mm
Tubesheet Corr. Allowance (Channel side)	Catc	0.0000 mm
Tubesheet Outside Diameter	A	360.000 mm

Additional Data for Stepped Tubesheets:

Is the Tubesheet Stepped?		Yes
Is the Tubesheet Flat on Tubeside?		No
Step 1 Diameter on the Tubeside	dt1	243.00 mm
Step 1 Depth on the Tubeside	ht1	9.00 mm
Step 2 Diameter on the Tubeside	dt2	192.00 mm
Step 2 Depth on the Tubeside	ht2	7.00 mm
Is the Tubesheet Flat on Shellside?		Yes
Calculated Tubesheet Diameter per Div 2, 4.18.4		243.00 mm

Note: Tubesheet diameter is now: 243.000 mm Div 2, 4.18.4.

Area of the Untubed Lanes AL 0.0 cm²

Additional Data for Fixed/Floating Tubesheet Exchangers:

Unsupported Tube Span under consideration	l	560.000 mm
Tube End condition corresponding to Span (l)	k	1.00
Ignore Radial Thermal Exp. effects (4.18.8/4.18.9)		Yes
Perform Differential Pressure Design		No
Run Multiple Load Cases		Yes
Shell Side Min. Design Pressure	Psd,min	-103.4190 KPa.
Channel Side Min. Design Pressure	Ptd,min	-103.4190 KPa.
Mean Shell Metal Temp. along Shell len.	Tsm	21.11 °C
Mean Tube Metal Temp. along Tube length	Ttm	21.11 °C
Junction Stress Reduction option		Perform Plastic Calculation

Additional Data for Gasketed Tubesheets:

Tubesheet Gasket on which Side		Channel
Flange Outside Diameter	A	360.000 mm
Flange Inside Diameter	B	188.951 mm
Flange Face Outside Diameter	Fod	257.951 mm
Flange Face Inside Diameter	Fid	188.951 mm
Gasket Outside Diameter	Go	246.951 mm
Gasket Inside Diameter	Gi	220.951 mm
Small end Hub thk.	g0	13.1794 mm
Large end Hub thk.	g1	20.0000 mm
Gasket Factor,	m	3.00
Gasket Design Seating Stress	y	68.95 N./mm ²
Flange Facing Sketch		Code Sketch 1a
Gasket Thickness	tg	3.1750 mm
Full face Gasket Flange Option		Program Selects

Bolting Information:

Diameter of Bolt Circle C 300.000 mm



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 59 of 204

ASME TS Calc: Pressure Test


Case: 1 9:40a Sep 9, 2026

Nominal Bolt Diameter	dB	25.4000 mm
Thread Series	UNC Thread Series	
Number of Bolts	n	12
Bolt Material	SA-193 B7	
Bolt Allowable Stress At Temperature	Sb	172.00 N./mm ²
Bolt Allowable Stress At Ambient	Sa	172.00 N./mm ²
Weld between Flange and Shell/Channel		0.0000 mm

Note: The full bolt load $Sa \cdot Ab$, was used for all load cases.

Tubesheet Integral with	Shell
Tubesheet Extended as Flange	Yes
Thickness of Extended Portion of Tubesheet	Tf 54.0000 mm
Is Bolt Load Transferred to the Tubesheet	Yes
Is Exchanger in Creep range (skip EP, Use 3S for Sps)	No

Tubesheet Integral w/Shell, Gasketed w/Channel, Extended as a Flange



Configuration b:

ASME TubeSheet Results per Part UHX/4.18, 2025

Elasticity/Expansion Material Properties:

Shell - TE-1 Carbon & Low Alloy Steels, Group 1
Shell - TM-1 Carbon Steels with C<= 0.3%

Th. Exp. Coeff. Metal Temp. along Len	21.1 °C	0.0000115191 /°C
Elastic Mod. at Design Temperature	21.1 °C	0.20270E+09 KPa.
Th. Exp. Coeff. Metal Temp. at Tubsht	21.1 °C	0.0000115191 /°C
Elastic Mod. at Metal Temp. along Len	21.1 °C	0.20270E+09 KPa.
Elastic Mod. at Ambient Temperature	21.1 °C	0.20270E+09 KPa.

Channel - TE-1 Carbon & Low Alloy Steels, Group 1
Channel - TM-1 Carbon Steels with C<= 0.3%

Th. Exp. Coeff. Metal Temp. at Tubsht	21.1 °C	0.0000115191 /°C
Elastic Mod. at Design Temperature	21.1 °C	0.20270E+09 KPa.
Elastic Mod. at Ambient Temperature	21.1 °C	0.20270E+09 KPa.



PV Elite 28 Licensee: SL User
 FileName : 161-C1-C2 _(Stack) Page 60 of 204
 ASME TS Calc: Pressure Test Case: 1 9:40a Sep 9,2026

Tubes - TE-1 Carbon & Low Alloy Steels, Group 1
 Tubes - TM-1 Carbon Steels with C<= 0.3%

Th. Exp. Coeff. Metal Temp. along Len	21.1 °C	0.0000115191 /°C
Elastic Mod. at Design Temperature	21.1 °C	0.20270E+09 KPa.
Elastic Mod. at Metal Temp. along Len	21.1 °C	0.20270E+09 KPa.
Elastic Mod. at Tubsht. Design Temp.	21.1 °C	0.20270E+09 KPa.
Elastic Mod. at Ambient Temperature	21.1 °C	0.20270E+09 KPa.

TubeSheet - TE-1 Carbon & Low Alloy Steels, Group 1
 TubeSheet - TM-1 Carbon Steels with C<= 0.3%

Elastic Mod. at Design Temperature	21.1 °C	0.20270E+09 KPa.
Elastic Mod. at Ambient Temperature	21.1 °C	0.20270E+09 KPa.

Note:
 The Elasticity and Alpha values are taken from Tables in ASME II D.
 Please insure these properties are consistent with the
 type of Material for the tubes, shell, channel etc.

Tube Required Thickness under Internal Pressure (Tubeside pressure):

Thickness Due to Internal Pressure:
 $= (P \cdot (D/2 - CAE)) / (S \cdot E + 0.4 \cdot P)$ per Appendix 1-1 (a)(1)
 $= (3223 \cdot (12.7/2 - 0)) / (92.4 \cdot 1 + 0.4 \cdot 3223)$
 $= 0.2185 + 0.0000 = 0.2185 \text{ mm}$

Tube Required Thickness under External Pressure (Shellside pressure) :

External Pressure Chart CS-1 at 21.11 °C
 Elastic Modulus for Material 199943392.00 KPa.

Results for Max. Allowable External Pressure (Emawp):

TCA	ODCA	SLEN	D/T	L/D	Factor A	B
2.1100	12.70	5860.00	6.02	50.0000	0.0303634	95.84

EMAWP = $(2.167 / (D/T) - 0.0833) \cdot B = 26520 \text{ KPa.}$

Results for Req'd Thickness for Ext. Pressure (Tca):

TCA	ODCA	SLEN	D/T	L/D	Factor A	B
0.3968	12.70	5860.00	32.00	50.0000	0.0010740	77.38

EMAWP = $(4 \cdot B) / (3 \cdot (D/T)) = (4 \cdot 77.4) / (3 \cdot 32) = 3224 \text{ KPa.}$

Summary of Tube Required Thickness Results:

Total Required Thickness including Corrosion all.	0.3968 mm
Allowable Internal Pressure at Corroded thickness	35406.68 KPa.
Required Internal Design Pressure	3223.42 KPa.
Allowable External Pressure at Corroded thickness	26520.32 KPa.
Required External Design Pressure	3223.42 KPa.
Required Thickness due to Shell Side pressure	0.3968 mm

Detailed Results for load Case D3 un-corr. (Psd,max + Ptd,max)

Intermediate Calculations For Tubesheets Extended As Flanges:

ASME Code, Section VIII Division 1, 2025

Gasket Contact Width,	$N = (Goc - Gic) / 2$	13.000 mm
Basic Gasket Width,	$b0 = N / 2$	6.500 mm
Effective Gasket Width,	$b = \text{sqrt}(b0) \cdot 2.5$	6.422 mm
Gasket Reaction Diameter,	$G = Go - 2.0 \cdot b$	234.107 mm

Results for ASME Fixed Tubesheet Calculations for Configuration b:



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 61 of 204

ASME TS Calc: Pressure Test

Case: 1 9:40a Sep 9, 2026

Results for Tubesheet Calculations Original Thickness:

ASME Section VIII-2 Part 4.18.8.4 Step 1:

Tube expansion depth ratio [ρ]:

= l_{tx} / h (modified for corrosion if present)

= 0/70

= 0.0000 (must be $0 \leq \rho \leq 1$)

Effective tube hole diameter [d^*]:

= $\max(dt - 2 \cdot tt(EtT/E) \cdot (StT/S) \cdot (\rho); dt - 2 \cdot tt)$

= $\max(12.7 - 2 \cdot 2.11 (202701232/202701232) \cdot$

$(92.4/138) \cdot (0); 12.7 - 2 \cdot 2.11)$

= 12.7000 mm

Equivalent outer tube limit circle diameter [Do]:

= $2 \cdot r_o + dt$

= $2 \cdot 80.2 + 12.7$

= 173.106 mm

Determine the basic ligament efficiency for shear [μ]:

= $(p - dt) / p$

= $(15.9 - 12.7) / 15.9$

= 0.200

Equivalent outer tube limit radius [ao]:

= $Do / 2$

= 173/2

= 86.5530 mm

Effective tube pitch [p^*]:

= $p / \sqrt{ 1 - 4 \cdot \min(AL \cdot CNVfactor; 4 \cdot Do \cdot p) / (\pi \cdot Do^2) }$

= $15.9 / \sqrt{ 1 - 4 \cdot \min(0 \cdot 100 ; 4 \cdot 173 \cdot 15.9) / (\pi \cdot 173^2) }$

= 15.8750 mm

Effective ligament efficiency for bending [μ^*]:

= $(p^* - d^*) / p^*$

= $(15.9 - 12.7) / 15.9$

= 0.2000

Ratio [ρ_s]:

= a_s / a_o

= 94.5/86.6

= 1.0915

Ratio [ρ_c]:

= a_c / a_o

= 117/86.6

= 1.3524

Compute parameter [xt]:

= $1 - Nt((dt - 2 \cdot tt) / (2 \cdot a_o))^2$

= $1 - 81 ((12.7 - 2 \cdot 2.11) / (2 \cdot 86.6))^2$

= 0.8056

Determine parameter [xs]:

= $1 - Nt(dt / (2 \cdot a_o))^2$

= $1 - 81 (12.7 / (2 \cdot 86.6))^2$

= 0.5640

Determine the value [$h'g$]:

= $\max((h_g - CATC); 0)$ (For pressure only cases)

= $\max((0 - 0); 0)$

= 0.000 mm



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)

Page 62 of 204

ASME TS Calc: Pressure Test

Case: 1 9:40a Sep 9, 2026

ASME Section VIII-2 Part 4.18.8.4 Step 2:

Axial Shell Stiffness [Ks]:

$$= \pi \cdot ts (Ds + ts) Es / L$$

$$= \pi \cdot 15.1 (189 + 15.1) 202701232 / 5860$$

$$= 34052.6562 \text{ Kg/mm}$$

Axial Tube Stiffness [Kt]:

$$= \pi \cdot tt (Dt - tt) Et / L$$

$$= \pi \cdot 2.11 (12.7 - 2.11) 202701232 / 5860$$

$$= 247.6188 \text{ Kg/mm}$$

Stiffness Factor [Ks,t]:

$$= Ks / (Nt \cdot Kt)$$

$$= 34053 / (81 \cdot 248)$$

$$= 1.69778$$

Rigidity Ratio [J]:

$$= 1 / (1 + Ks/Kj)$$

$$= 1 / (1 + 34053/0)$$

$$= 1.0000 (= 1 \text{ if No Exp. Jt.})$$

Shell coefficient [β_s]:

$$= ((12(1 - \nu_s^2))^{1/4}) / ((Ds + ts)ts)$$

$$= ((12(1 - 0.3^2))^{1/4}) / ((189 + 15.1)15.1)$$

$$= 0.0328 \text{ 1/mm}$$

Shell coefficient [ks]:

$$= \beta_s \cdot Es \cdot ts^3 / (6(1 - \nu_s^2))$$

$$= 0.033 \cdot 202701232 \cdot 15.1^3 / (6(1 - 0.3^2))$$

$$= 4160175104.0000 \text{ KPa} \cdot \text{mm}^2$$

Shell coefficient [λ_s]:

$$= 6(Ds + ts) \cdot ks / h^3 \cdot (1 + h \cdot \beta_s + (h \cdot \beta_s)^2 / 2)$$

$$= 6(189 + 15.1) \cdot 4.16E+09 / 70^3 \cdot (1 + 70 \cdot 0.033 + (70 \cdot 0.033)^2 / 2)$$

$$= 88043448.0000 \text{ KPa}$$

Shell coefficient [δ_s]:

$$= Ds^2 / (4 \cdot Es \cdot ts) \cdot (1 - Ds \cdot \nu_s / (2(Ds + ts)))$$

$$= 189^2 / (4 \cdot 202701232 \cdot 15.1) \cdot (1 - 189 \cdot 0.3 / (2(189 + 15.1)))$$

$$= 0.25171E-02 \text{ mm/N/mm}^2$$

Intermediate parameters for Tubesheet Gasketed on the Channel Side:

β_C , k_C , λ_C , δ_C are all = 0

ASME Section VIII-2 Part 4.18.8.4 Step 3:

$h/p = 4.409449$; $\mu^* = 0.200000$; $E^* = 31489462 \text{ KPa}$.

$E^*/E = 0.155349$; $\nu^* = 0.458572$

Note: As h/p (4.409) is > 2, data values for $h/p = 2$ were used.

Tube Bundle Stiffness Factor [X_a]:

$$= ((24(1 - \nu^*)Nt \cdot Et \cdot tt(dt - tt)ao^2) / (E^* \cdot L \cdot H^3))^{1/4}$$

$$= ((24(1 - 0.46^2)81 \cdot 202701232 \cdot 2.11$$

$$(12.7 - 2.11)86.6^2) / (31489462 \cdot 5860 \cdot 70^3))^{1/4}$$

$$= 0.9525$$

Values from Table 4.18.3

$Z_d = 2.482893$; $Z_v = 0.170039$; $Z_m = 0.681610$
 $Z_a = 0.350844E+00$; $Z_w = 0.170039$

ASME Section VIII-2 Part 4.18.8.4 Step 4:



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 63 of 204

ASME TS Calc: Pressure Test

Case: 1 9:40a Sep 9, 2026

Diameter ratio [K]:

$$= A / D_o$$

$$= 243/173$$

$$= 1.4038$$

Compute coefficient [F]:

$$= (1 - \nu^*) / E^* \cdot (\lambda s + \lambda c + E \cdot \ln(K))$$

$$= (1 - 0.46) / 31489462 \cdot (88043448 + 0 + 202701232 \cdot \ln(1.4))$$

$$= 2.6959$$

Compute parameter [\phi]:

$$= (1 + \nu^*)^F$$

$$= (1 + 0.46)^{2.7}$$

$$= 3.9321$$

Compute parameter [Q1]:

$$= (\rho s - 1 - \phi \cdot Z_v) / (1 + \phi \cdot Z_m)$$

$$= (1.09 - 1 - 3.93 \cdot 0.17) / (1 + 3.93 \cdot 0.68)$$

$$= -0.156808$$

Compute Parameter [Qz1]:

$$= (Z_d + Q1 \cdot Z_w) / 2 \cdot X_a^4$$

$$= (2.48 + -0.16 \cdot 0.17) / 2 \cdot 0.95^4$$

$$= 1.0108$$

Compute parameter [Qz2]:

$$= (Z_v + Q1 \cdot Z_m) / 2 \cdot X_a^4$$

$$= (0.17 + -0.16 \cdot 0.68) / 2 \cdot 0.95^4$$

$$= 0.0260$$

Compute parameter [U]:

$$= (Z_w + (\rho s - 1) Z_m) X_a^4 / (1 + \phi \cdot Z_m)$$

$$= (0.17 + (1.09 - 1) 0.68) 0.95^4 / (1 + 3.93 \cdot 0.68)$$

$$= 0.0520$$

ASME Section VIII-2 Part 4.18.8.4 Step 5:

Determine factor [\gamma_b]:

$$= (G_c - C) / D_o \text{ (config b)}$$

$$= (234 - 300) / 173 = -0.38$$

Compute Parameter [\gamma]:

$$= 0.000 \text{ mm (For Pressure only cases)}$$

Calculate parameter [\omega s]:

$$= \rho s \cdot k_s \cdot \beta s \cdot \delta S (1 + h \cdot \beta s)$$

$$= 1.09 \cdot 4.16E+09 \cdot 0.033 \cdot 0.00251714 (1 + 70 \cdot 0.033)$$

$$= 1235.3409 \text{ mm}^2$$

Calculate parameter [\omega*s]:

$$= a o^2 (\rho s^2 - 1) \cdot (\rho s - 1) / 4 - \omega s$$

$$= 86.6^2 (1.09^2 - 1) \cdot (1.09 - 1) / 4 - 1235$$

$$= -1202.5233 \text{ mm}^2$$

Parameter [\omega c]:

$$= \rho c \cdot k c [\delta C (C_m \Theta + \beta C + C_q \Delta \cdot h \cdot \beta C^2) - \zeta c (C_m \Theta + h \cdot C_q \Theta \cdot h \cdot \beta C / 2)]$$

$$= 1.35 \cdot 0 [0.000 (0 + 0 \cdot 0 \cdot 70) - 0.000 (0/70 + 0 \cdot 0/2)]$$

$$= 0.0000 \text{ mm}^2$$

Parameter [\omega*c]:

$$= a o^2 [(\rho c^2 + 1) \cdot (\rho c - 1) / 4 - (\rho s - 1) / 2] - \omega c$$

$$= 86.6^2 [(1.35^2 + 1) \cdot (1.35 - 1) / 4 - (1.09 - 1) / 2] - 0$$



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 64 of 204

ASME TS Calc: Pressure Test

Case: 1 9:40a Sep 9, 2026

$$= 1524.1832 \text{ mm}^2$$

Pressure [P*S]:

$$= 0 \text{ For Pressure only cases or Configurations d,e,f,A,B,C,D}$$

Pressure [P*C]:

$$= 0 \text{ For Pressure only cases or Configurations b,c,d,B,C,D}$$

ASME Section VIII-2 Part 4.18.8.4 Step 6:

Pressure [P's]:

$$\begin{aligned} &= P_s \{ x_s + 2(1 - x_s) v_t + [2/Kst \cdot (D_s/D_o)^2] v_s - \\ &\quad [(p_s^2 - 1)/(J \cdot Kst)] - [(1 - J)/(2J \cdot Kst)] [(D_j^2 - (D_s)^2)/D_o^2] \} \\ &= 3120 \{ 0.56 + 2(1 - 0.56) 0.3 + [2/1.7 \cdot \\ &\quad (189/173)^2] 0.3 - [(1.09^2 - 1)/(1 \cdot 1.7)] - \\ &\quad [(1 - 1)/(2 \cdot 1 \cdot 1.7)] [(0^2 - (189)^2)/173^2] \} \\ &= 3537.7852 \text{ KPa.} \end{aligned}$$

Pressure [P't]:

$$\begin{aligned} &= [x_t + 2(1 - x_t) v_t + 1/(J \cdot Kst)] P_t \\ &= [0.81 + 2(1 - 0.81) 0.3 + 1/(1 \cdot 1.7)] 3120 \\ &= 4715.1025 \text{ KPa.} \end{aligned}$$

Pressure [P_y]:

$$\begin{aligned} &= N_t \cdot K_t \cdot \gamma / (\pi \cdot a_o^2) \\ &= 81 \cdot 248 \cdot 0 / (3.14 \cdot 86.6^2) \\ &= 0.0000 \text{ KPa.} \end{aligned}$$

Pressure [P_w]:

$$\begin{aligned} &= -\gamma_b \cdot U \cdot W^* / (2 \cdot \pi \cdot a_o^2) \\ &= -0.38 \cdot 0.052 \cdot 74816 / (2 \cdot \pi \cdot 86.6^2) \\ &= 308.3961 \text{ KPa.} \end{aligned}$$

Calculate the pressure [Prim]:

$$\begin{aligned} &= -(U/a_o^2) \cdot (\omega^* s \cdot P_s - \omega^* c \cdot P_t) \\ &= -(0.052/86.6^2) \cdot (-1203 \cdot 3120 - 1524 \cdot 3120) \\ &= 59.0277 \text{ KPa.} \end{aligned}$$

Calculate the pressure [P_w]:

$$\begin{aligned} &= (U/a_o^2) \cdot (\omega^* s \cdot P^* s - \omega^* c \cdot P^* c) \\ &= (0.052/86.6^2) \cdot (1235 \cdot 0 - 0 \cdot 0) \\ &= 0.0000 \text{ KPa.} \end{aligned}$$

Determine the effective pressure [P_e]:

$$\begin{aligned} &= J \cdot Kst / (1 + J \cdot Kst (Qz1 + (p_s - 1) Qz2)) \cdot \\ &\quad (P^* s - P^* t + P_y + P_w + P_w + Prim) \\ &= 0.1000E+01 \cdot 1.7 / (1 + 1 \cdot 1.7 (1.01 + (1.09 - \\ &\quad 1) 0.026)) \cdot (3538 - 4715 + 0 + 0 + 308 + 59) \\ &= -505.5082 \text{ KPa.} \end{aligned}$$

ASME Section VIII-2 Part 4.18.8.4 Step 7:

Determine factor [Q2]:

$$\begin{aligned} &= [((\omega^* s \cdot P_s - \omega^* c \cdot P_t) - (\omega^* s \cdot P^* s - \omega^* c \cdot P^* c)) + \\ &\quad W^* \cdot \gamma_b / (2 \cdot \pi)] / (1 + \phi \cdot Z_m) \\ &= [((-1203 \cdot 3120 - 1524 \cdot 3120) - \\ &\quad (1235 \cdot 0 - 0 \cdot 0)) \cdot 0.0001 + \\ &\quad 74816 \cdot -0.38 / (2 \cdot \pi)] / (1 + 3.93 \cdot 0.68) \\ &= -1467.3518 \text{ Kg} \end{aligned}$$

Calculate factor [Q3]:

$$\begin{aligned} &= Q1 + 2 \cdot Q2 / (P_e \cdot a_o^2) \\ &= -0.16 + 2 \cdot -1467 / (-506 \cdot 86.6^2) \\ &= 7.44252 \end{aligned}$$



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 65 of 204

ASME TS Calc: Pressure Test

Case: 1 9:40a Sep 9, 2026

Fm Value from Table 4.18.3 = 3.881648

Tubesheet Bending Stress - original thickness [σ]:

$$= (1.5 \cdot F_m / \mu \cdot) \cdot (2 \cdot a_o / (H - h'g))^2 \cdot P_e$$

$$= (1.5 \cdot 3.88 / 0.2) \cdot (2 \cdot 86.6 / (70 - 0))^2 \cdot -506$$

$$= -90.0034 \text{ N./mm}^2$$

Allowable Tubesheet Bending Stress [σ allowed]:

$$= 1.5 \cdot \beta_T \cdot S_y = 1.5 \cdot 0.95 \cdot 250 = 356 \text{ N./mm}^2, 4.18.233$$

Tubesheet Bending Stress - final thickness [σ_f]:

$$= (1.5 \cdot F_m / \mu \cdot) \cdot (2 \cdot a_o / (h - h'g))^2 \cdot P_e$$

$$= (1.5 \cdot 0.31 / 0.2) \cdot (2 \cdot 86.6 / (11.9 - 0))^2 \cdot 734$$

$$= 356.2436 \text{ N./mm}^2$$

Reqd Tubesheet Thickness, for Bending Stress (including CA) [HReqB]:

$$= h + C_{ats} + C_{atc}$$

$$= 11.9 + 0 + 0$$

$$= 11.8925 \text{ mm}$$

ASME Section VIII-2 Part 4.18.8.4 Step 8:

Shear Stress check [τ limit]:

$$= (2 \cdot \mu \cdot h / a_o) \cdot (0.8 \cdot \beta_T \cdot S_y)$$

$$= (2 \cdot 0.2 \cdot 70 / 86.6) \cdot 190$$

$$= 61.4641 \text{ N./mm}^2$$

Shear Stress is not required to be computed; [P_e] <= τ limit

Tubesheet Shear Stress is probably low, use the following req. thk:

$$\text{Tubesheet thickness (Incl. Corr.)} = 3.8100 \text{ mm}$$

$$\text{Tubesheet Shear Stress} = 14.0613 \text{ N./mm}^2$$

Reqd Tubesheet Thickness for Given Loadings (including CA) [Hreqd] :

$$= \max(H_{reqB}; H_{reqS})$$

$$= \max(11.9; 3.81)$$

$$= 11.8925 \text{ mm}$$

ASME Section VIII-2 Part 4.18.8.4 Step 9:

The F_{tmin} and F_{tmax} Coefficients from Table 4.18.4:

$$F_{tmin} = 0.45, F_{tmax} = 1.54$$

First Extreme Tube Axial Stress from among all the tubes [σ_{t1}]:

$$= ((P_s \cdot x_s - P_t \cdot x_t) - P_e \cdot F_{tmin}) / (X_t - X_s)$$

$$= ((3120 \cdot 0.56 - 3120 \cdot 0.81) - (-506) \cdot 0.45) /$$

$$(0.81 - 0.56)$$

$$= -2.1683 \text{ N./mm}^2$$

Second Extreme value of Tube Axial Stress from among all the tubes [σ_{t2}]:

$$= ((P_s \cdot x_s - P_t \cdot x_t) - P_e \cdot F_{tmax}) / (X_t - X_s)$$

$$= ((3120 \cdot 0.56 - 3120 \cdot 0.81) - (-506) \cdot 1.54) /$$

$$(0.81 - 0.56)$$

$$= 0.1074 \text{ N./mm}^2$$

Maximum Tube Axial Stress [$\sigma_{t,max}$]:

$$= \max(|\sigma_{t,1}|; |\sigma_{t,2}|) = 2.17 \text{ N./mm}^2$$

Allowable Tube Stress [$\sigma_{t,A}$]:

$$= \beta_T \cdot S_{y,t} = 170.9969 \text{ N./mm}^2$$

Check for Buckling as some of the tubes are in compression.

Determine the Factor of Safety [Fs]:



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)

Page 66 of 204

ASME TS Calc: Pressure Test

Case: 1 9:40a Sep 9, 2026

$$= \max((3.25 - 0.25(Z_d + Q_3 \cdot Z_w)X_a^4); 1.25)$$

$$= \max((3.25 - 0.25(2.48 + 7.44 \cdot 0.17)0.95^4); 1.25)$$

$$= 2.0000 \text{ (Should be } \leq 2 \text{)}$$

Determine the factor [rt]:

$$= (\sqrt{ (dt^2 + (dt - 2 \cdot tt)^2) }) / 4$$

$$= (\sqrt{ (12.7^2 + (12.7 - 2 \cdot 2.11)^2) }) / 4$$

$$= 3.8177 \text{ mm}$$

Determine the factor [Ct]:

$$= \sqrt{ (2 \cdot \pi^2 \cdot Et / S_{yt}) }$$

$$= \sqrt{ (2 \cdot \pi^2 \cdot 202701232 / 180) }$$

$$= 159.3101$$

Determine the factor [Ft]:

$$= k \cdot L / r$$

$$= 1 \cdot 560 / 3.82$$

$$= 146.6842$$

Buckling Allowable Stress [Stb]:

$$= (S_{y,t} / F_s) \cdot (1 - F_t / (2 \cdot C_t))$$

$$= (180 / 2) \cdot (1 - 147 / (2 \cdot 159))$$

$$= 170.997 \text{ N./mm}^2 \text{ (Never greater than } S_{ot} \text{)}$$

Note: The Axial Compressive stress in tubes is within limits.

Largest tube-to-tubesheet Joint Load [Wt]:

$$= \sigma_{t,max} \cdot \text{Tube Area}$$

$$= 2.17 \cdot 0.7$$

$$= 15.52 \text{ Kg}$$

Tube Metal Area [At]:

$$= \pi (d_o - t) t$$

$$= \pi (12.7 - 2.11) 2.11$$

$$= 0.702 \text{ cm}^2$$

Tube Weld Size Results per UW-20.3:

Tube Strength [Ft]:

$$= \pi \cdot t (d_o - t) S$$

$$= \pi \cdot 2.11 (12.7 - 2.11) 171$$

$$= 1224.018 \text{ Kg}$$

Groove Weld Strength [Fg]:

$$= 0.85 \cdot \pi \cdot a_g (d_o + 0.67 \cdot a_g) S_w \text{ (but not } > F_t \text{)}$$

$$= 0.85 \cdot \pi \cdot 2.11 (12.7 + 0.67 \cdot 2.11) 171$$

$$= 1224.0182 \text{ Kg}$$

Weld Strength Factor [fw]:

$$= S / S_w \text{ where } S_w = \min(S \text{ and } S_t)$$

$$= 171 / 171$$

$$= 1.000$$

Design Strength Ratio [fd]:

$$= 1 \text{ for full strength welds}$$

Fillet Weld Strength [Ff]:

$$= 0.55 \cdot \pi \cdot a_f (d_o + 0.67 \cdot a_f) S_w \text{ (but not } > F_t \text{)}$$

$$= 0.55 \cdot \pi \cdot 2.11 (12.7 + 0.67 \cdot 2.11) 171$$

$$= 897.2130 \text{ Kg}$$

Minimum Length of Weld [ar]:

$$= 2 (\sqrt{ ((0.75 \cdot d_o)^2 + 1.07 \cdot t \cdot (d_o - t) f_w \cdot f_d) - 0.75 \cdot d_o })$$

$$= 2 (\sqrt{ ((0.75 \cdot 12.7)^2 + 1.07 \cdot 2.11 \cdot (12.7 - 2.11) 1 \cdot 1) - 0.75 \cdot 12.7 })$$



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 67 of 204

ASME TS Calc: Pressure Test

Case: 1 9:40a Sep 9, 2026

= 2.364 mm

Minimum Required Fillet Weld Leg [afr]: 1.2660 mm

Minimum Required Groove Weld Leg [agr]: 1.2660 mm

Tube-Tubesheet Jt allowable, 1224 is >= tube strength 1224 Kgf

Note: This tube-tubesheet joint is a Full Strength joint

ASME Section VIII-2 Part 4.18.8.4 Step 10:

Shell Axial Membrane Allowable Stress:

$$= \beta T \cdot S_{y,s} = 0.95 \cdot 240 = 342 \text{ N./mm}^2$$

Axial Membrane Stress in Shell [σ_s, m]:

$$= a o^2 / ((D_s + t_s) t_s) \cdot [P_e + (p_s^2 - 1)(P_s - P_t)] + a s^2 \cdot P_t / ((D_s + t_s) t_s)$$

$$= 86.6^2 / ((189 + 15.1) 15.1) \cdot [-506 + (1.09^2 - 1)(3120 - 3120)] + 94.5^2 \cdot 3120 / ((189 + 15.1) 15.1)$$

$$= 7.8305 \text{ N./mm}^2$$

ASME Section VIII-2 Part 4.18.8.4 Step 11:

Note:

For a given Shell thickness of 15.1 mm, the minimum Shell length adjacent to the tubesheet should be 96.026 mm

Computations completed for ASME tubesheet configuration: b

Stress/Force Summary for Loadcase D3 un-corr. (Psd,max + Ptd,max):

Stress Description	Actual	Allowable	Pass/Fail
Tubesheet Bend. Stress	90.0 <=	356.2 N./mm ²	Pass
Tubesheet Shear Stress	1.2 <=	190.0 N./mm ²	Pass
Maximum Tube Stress	2.2 <=	171.0 N./mm ²	Pass
Minimum Tube Stress (Buckling)	-2.2 <=	-171.0 N./mm ²	Pass
Maximum Force on any one Tube	15.5 <=	1224.0 Kgf	Pass
Axial Membrane Stress in Shell	7.8 <=	342.0 N./mm ²	Pass

Thickness Results for Loadcase D3 un-corr. (Psd,max + Ptd,max):

Thickness (mm)	Required	Actual	P/F
Tubesheet Thickness :	11.893	70.000	Ok
Tube-Tubesheet Fillet Weld Leg :	1.266	2.110	Ok
Tube-Tubesheet Groove Weld Leg :	1.266	2.110	Ok

Fixed Tubesheet results per ASME Div. 2 Part 4.18.8 2025

Results for 3 Load Cases:

Case#	--Reqd. Thk. + CA Tbsht Extnsn	----	Tubesheet Bend	Stresses Allwd	Shear	Case Type	Pass/ Fail
D1uc	3.810	28.742	98	356	7	Ps+Pt-Th	D1 Ok
D2uc	8.773	...	14	356	6	Ps+Pt-Th	D2 Ok
D3uc	11.893	...	90	356	1	Ps+Pt-Th	D3 Ok
Max:	11.8925	28.742 mm	0.275		0.036	(Str. Ratio)	

Load Case Definitions:

[Ps & Pt]:

Shell-side and Tube-side Design or Operating Pressures



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 68 of 204

ASME TS Calc: Pressure Test

Case: 1 9:40a Sep 9, 2026

derived from Psd,min Ptd,max, Psox,min, Ptox,max etc. per the Load Case Tables

[(+)-Th]:

With or Without Thermal Expansion, Tt,mx & Ts,mx

[c]:

With or Without Corrosion Allowance

[D1, D2, D3]:

Design Load Cases using the Maximum and Minimum Design Pressures

[D4]:

Design Load Case using the Minimum (Vacuum) Pressures (if specified)

[O1, O2, O3, O4]:

Operating Load Cases using the Maximum and Minimum Operating Pressures and Operating Temperatures

Shell Axial Membrane Stress Summary:

Case#	Shell Stresses				:	Shell Band Stress				:	Pass Fail
	Ten	Allwd	Cmp	Allwd		Ten	Allwd	Cmp	Allwd		
D1uc	1	341	...	...	:	...	...	...	...	:	Ok
D2uc	7	341	...	...	:	...	...	...	...	:	Ok
D3uc	8	341	...	...	:	...	...	...	...	:	Ok
Max RATIO	0.023				:	...				:	...

Tube, Shell and Channel Stress Summary:

Case#	Tube Stresses				Tube Loads		Shell Stress		Channel Stress		Pass Fail
	Ten	Allwd	Cmp	Allwd	Ld	Allwd	Stress	Allwd	Stress	Allwd	
D1uc	2	170	...	-170	15	1224	...	341	...	...	Ok
D2uc	2	170	-2	-170	14	1224	...	341	...	...	Ok
D3uc	2	170	-2	-170	16	1224	...	341	...	...	Ok
Max RATIO	0.013		0.013		0.013		...		...		...

Summary of Thickness Comparisons for 3 Load Cases:

Thickness (mm)	Required	Actual	P/F
Tubesheet thickness :	11.893	70.000	Ok
Tubesheet thickness flanged extension :	28.742	54.000	Ok
Tube thickness :	0.397	2.110	Ok
Tube-tubesheet fillet weld leg :	1.266	2.110	Ok
Tube-tubesheet groove weld leg :	1.266	2.110	Ok

Min Shell length of thk, (15.062) adj. to tubesheet: 96.026 mm

Note: This is a full strength Tube to Tubesheet Joint.

Summary of Axial Differential Expansion between Shell and Tubes :

Due to Thermal Expansion Shell Extends by : +.000 mm
 Due to Pressure Shell Compresses by : -0.081 mm
 Due to Pressure + Thermal Shell Compresses by : -0.081 mm

Summary of Exchanger Pressure and Thermal Displacements: (mm)

Load Case#	Due to Pressure		Due to Thermal Exp.		Computed Delta Ms	
	UnCorroded	Corroded	UnCorroded	Corroded	UnCorroded	Corroded



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

ASME TS Calc: Pressure Test

Case: 1 9:40a Sep 9, 2026

1	0.0074	...	...	...	...	...
2	-0.0815	...	...	...	...	...
3	-0.0767	...	...	...	...	...
4	...	...	...	...	...	...
5	...	...	...	...	...	...
6	...	...	...	...	...	...
7	...	...	...	...	...	...
8	...	...	...	...	...	...

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User
 FileName : 161-C1-C2_(Stack) Page 70 of 204
 External Pressure Calculations: Step: 13 9:40am Sep 9,2026

External Pressure Calculation Results Summary:

ASME Code, Section VIII Division 1, 2025


MDMT Calculations for: Ring R1 Fr40, Shell to Ring Junction, Curve: B

Govrn. thk, $t_g = 13.2$, $t_r = 4.24$, $c = 3$ mm, $E^* = 1$
 Thickness Ratio = $t_r * E^* / (t_g - c) = 0.42$, Temp. Reduction = 47 °C

Min Metal Temp. w/o impact per UCS-66, Curve B -20 °C
 Min Metal Temp. at Required thickness (UCS 66.1) -48 °C
 Min Metal Temp. w/o impact per UG-20(f) -29 °C

Stiffening Ring Calculations for: Ring R1 Fr40, SA-516 70 , Bar Ring: 21.5 x 20.0 mm

Material treatment options:



Effective Length of Shell: 51 mm

	Area (cm ²)	Distance (mm)	Area*Dist
Shell:	5.242	5.0897	26.681
Ring :	4.306	20.9449	90.193
Total:	9.548		116.874

Centroid of Ring plus Shell: 12 mm

	Inertia	Distance	A*Dist ²
Shell:	0.453	7.1505	268.031
Ring :	1.664	-8.7047	326.287
Total:	2.116		594.318

Available Moment of Inertia, Ring + Shell: 0.806E+01 cm⁴

Required Stress in Ring plus Shell Breq 1.61 N./mm²
 Required Strain in Ring plus Shell Areq 0.0000173

Required Moment of Inertia, Ring plus Shell:

$$= (D_o^2 \cdot L_s(t + A_s/L_s)A) / 10.9$$

$$= (215^2 \cdot 2325(10.2 + 4.31/2325)0.17311E-04) / 10.9$$

$$= 0 \text{ cm}^4$$



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)

Page 71 of 204

External Pressure Calculations: Step: 13 9:40am Sep 9, 2026

Results for Stiffening Ring Weld Calculations per UG-30:

Given Stiffening Ring Fillet Weld Size	Wleg	6.000	mm
Stiffening Ring Attachment Style		CONTINUOUS	
Location of Stiffening Ring		EXTERNAL	
Radial Pressure Load	Pext*Slen	24.52	Kgf/mm
The Radial Shear Load	V	52.79	Kgf
The First Moment of the Area (Ring + Shell)	Q	3748.41	mm ³
Weld Shear Flow due to Rad. Shear Load	VQ/I	2.46	Kgf/mm
The Weld Allowable Stress	0.55*S	64.90	N./mm ²
Minimum Weld Leg Size Min(6mm, t, tw)	Wldmin	6.00	mm
The Weld Allowable Load	2* WLeg*0.55*S	79.41	Kgf/mm
The Combined Weld Load	SRSS of VQ/I and Pext*Slen	24.64	Kgf/mm
MAEP of Stiffening Ring Weld	Weld MAEP	0.33	N./mm ²

MDMT Calculations for: Ring R2 Fr40, Shell to Ring Junction, Curve: B


Govern. thk, tg = 13.2, tr = 4.24, c = 3 mm, E* = 1

Thickness Ratio = $tr * E^* / (tg - c) = 0.42$, Temp. Reduction = 47 °C

Min Metal Temp. w/o impact per UCS-66, Curve B	-20 °C
Min Metal Temp. at Required thickness (UCS 66.1)	-48 °C
Min Metal Temp. w/o impact per UG-20(f)	-29 °C

Stiffening Ring Calculations for: Ring R2 Fr40, SA-516 70 , Bar Ring: 21.5 x 20.0 mm

Material treatment options:



Effective Length of Shell: 51 mm

	Area (cm ²)	Distance (mm)	Area*Dist
Shell:	5.242	5.0897	26.681
Ring :	4.306	20.9449	90.193
Total:	9.548		116.874

Centroid of Ring plus Shell: 12 mm

	Inertia	Distance	A*Dist ²
Shell:	0.453	7.1505	268.031
Ring :	1.664	-8.7047	326.287
Total:	2.116		594.318

Available Moment of Inertia, Ring + Shell: 0.806E+01 cm⁴



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 72 of 204

External Pressure Calculations: Step: 13 9:40am Sep 9,2026

Required Stress in Ring plus Shell Breq 1.61 N./mm²
Required Strain in Ring plus Shell Areq 0.0000173

Required Moment of Inertia, Ring plus Shell:

$$= (D_o^2 \cdot L_s(t + A_s/L_s)A) / 10.9$$

$$= (215^2 \cdot 2293(10.2 + 4.31/2293)0.17307E-04) / 10.9$$

$$= 0 \text{ cm}^4$$

Results for Stiffening Ring Weld Calculations per UG-30:

Given Stiffening Ring Fillet Weld Size Wleg 6.000 mm
Stiffening Ring Attachment Style CONTINUOUS
Location of Stiffening Ring EXTERNAL
Radial Pressure Load Pext*Slen 24.18 Kg/mm
The Radial Shear Load V 52.06 Kg
The First Moment of the Area (Ring + Shell) Q 3748.41 mm³
Weld Shear Flow due to Rad. Shear Load VQ/I 2.42 Kg/mm
The Weld Allowable Stress 0.55*S 64.90 N./mm²
Minimum Weld Leg Size Min(6mm, t, tw) Wldmin 6.00 mm
The Weld Allowable Load 2* WLeg*0.55*S 79.41 Kg/mm
The Combined Weld Load SRSS of VQ/I and Pext*Slen 24.30 Kg/mm
MAEP of Stiffening Ring Weld Weld MAEP 0.34 N./mm²

External Pressure Calculations:

From	To	Section Length mm	Outside Diameter mm	Corroded Thickness mm	Factor A	Factor B N./mm ²
10	20	No Calc	215.31	10.1794	0.0065664	94.8001
20	30	366.546	215.309	10.1794	0.0079202	97.442
30	40	No Calc	...	53	No Calc	No Calc
40	Ring	1200	215.309	10.1794	0.0027364	83.6538
Ring	Ring	3450	215.309	10.1794	0.0025207	82.4486
Ring	50	1135	215.309	10.1794	0.0027734	83.8506
50	60	No Calc	...	53	No Calc	No Calc
60	70	366.546	215.309	10.1794	0.0079202	97.442
70	80	No Calc	206.998	6.02335	0.0040415	87.8935

External Pressure Calculations:

From	To	External Actual T. mm	External Required T. mm	External Design Pressure KPa.	External M.A.W.P. KPa.
10	20	13.1794	3.58017	103.419	4980
20	30	13.1794	3.88937	103.419	6142
30	40	56	48.387	103.419	No Calc
40	Ring	13.1794	4.47193	103.419	5273
Ring	Ring	13.1794	4.93071	103.419	5197
Ring	50	13.1794	4.43819	103.419	5285
50	60	56	49.403	103.419	No Calc
60	70	13.1794	3.88937	103.419	6142
70	80	9.02335	3.55778	103.419	2842
Ring R1 Fr40					333
Ring R2 Fr40					338

Minimum

333

External Pressure Calculations:

From	To	Actual Length Bet. Stiffeners	Allowable Length Bet. Stiffeners	Ring Inertia Required	Ring Inertia Available
------	----	----------------------------------	-------------------------------------	--------------------------	---------------------------



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 73 of 204

External Pressure Calculations: Step: 13 9:40am Sep 9,2026

		mm	mm	cm^4	cm^4
10	20	No Calc	No Calc	No Calc	No Calc
20	30	366.546	19863.5	No Calc	No Calc
30	40	No Calc	No Calc	No Calc	No Calc
40	Ring	1200	60676.8	No Calc	No Calc
Ring	Ring	3450	173184	0.17742	8.05941
Ring	50	1135	57460.5	0.17494	8.05941
50	60	No Calc	No Calc	No Calc	No Calc
60	70	366.546	19863.5	No Calc	No Calc
70	80	No Calc	No Calc	No Calc	No Calc

Elements Suitable for External Pressure.

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)

Page 74 of 204

Element and Detail Weights:

Step: 14

9:40am

Sep 9,2026

Element and Detail Weights:

From	To	Element Metal Wgt. kg.	Element ID Volume cm ³	Corroded Metal Wgt. kg.	Corroded ID Volume cm ³	Extra due Misc % kg.
10	20	9.61628	2307.93	7.70096	2486.69	1.92326
20	30	22.4464	8413.67	18.24	8956.5	4.48928
30	40	41.0259	2759.34	39.7078	2806.38	8.20517
40	50	432.841	102874	351.728	113342	86.5683
50	60	35.2725	2706.59	34.0704	2737.62	7.05451
60	70	22.4464	8413.67	18.24	8956.5	4.48928
70	80	6.34	2307.93	4.49562	2486.69	1.268
Total		569	129783.25	474	141771.94	113



For elements specified as shell side elements, the volume(s) shown above for those elements, reflects the displacement of the tubes.

Weight of Details:

From	Type	Weight of Detail kg.	X Offset, Dtl. Cent. mm	Y Offset, Dtl. Cent. mm	Z Offset Dtl. Cent. mm	Description
10	Liqd	2.30354	-15.7459	1.9755	...	Liquid: 10
10	Insl	5.17533	25.4	...	...	Insulation
20	Liqd	8.36565	150	1.97531	...	Liquid: 20
20	Insl	10.4727	150	...	...	Insulation
20	Nozl	28.6208	150	138.975	...	N1-Tube Inlet
30	Liqd	2.75765	41	-3.02451	...	Liquid: 30
30	Insl	6.5431	41	...	...	Insulation
30	Forc	...	155.175	...	...	TOP HE FORCE
30	Forc	...	155.175	...	...	TOP HE FORCE
30	Forc	...	155.175	...	...	TOP HE FORCE
30	Forc	...	155.175	...	...	TOP HE FORCE
40	Sadl	104.429	1200	301.148	...	LH floating sad
40	Sadl	104.429	4650	301.148	...	RH fixed saddle
40	Liqd	102.811	2892.5	1.97531	...	Liquid: 50
40	Insl	201.774	2890	...	...	Insulation
40	Ring	2.97996	1200	...	...	Ring R1 Fr40
40	Ring	2.97996	4650	...	...	Ring R2 Fr40
40	Nozl	28.6208	600	138.975	...	N3-Shell inlet
40	Nozl	28.6208	5250	-138.975	...	N4-Shell outlet
40	Wght	1500	2944.76	1070	...	TOP HE EMPTY
40	Wght	400	2943.53	1070	...	TOP HE OPERATIN
40	Wght	300	2945.66	1070	...	TOP HE TEST
50	Liqd	2.67123	36	3.85849	...	Liquid: 60
50	Insl	5.50906	41.5	...	...	Insulation
60	Liqd	8.36565	150	1.97531	...	Liquid: 80
60	Insl	10.4727	150	...	...	Insulation
60	Nozl	28.6208	150	-138.975	...	N2-Tube Outlet
70	Liqd	2.30354	66.5459	1.9755	...	Liquid: 90
70	Insl	4.95415	25.4	...	...	Insulation
30	FTsh	59.5878	120.175	...	...	Fixed Tubesheet
30	Tube	317.304	3085.18	...	...	Tubes
30	RTsh	59.5878	6050.17	...	...	Tubesheet
40	Baf1	5.59703	560	...	...	Baffles
40	Baf1	5.59703	1120	...	...	Baffles
40	Baf1	5.59703	1680	...	...	Baffles
40	Baf1	5.59703	2240	...	...	Baffles
40	Baf1	5.59703	2800	...	...	Baffles



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 75 of 204

Element and Detail Weights:

Step: 14

9:40am

Sep 9, 2026

40 Baf1	5.59703	3360	...	...	Baffles
40 Baf1	5.59703	3920	...	...	Baffles
40 Baf1	5.59703	4480	...	...	Baffles
40 Baf1	5.59703	5040	...	...	Baffles
40 Baf1	5.66053	5600	...	...	Baffles

Total Weight of Each Detail Type:

Saddles	208.9
Liquid	129.6
Insulation	244.9
Stiffeners	6.0
Nozzles	114.5
Weights	2200.0
Exchanger Components	492.5
Liquid in Tubes	27.4

Sum of the Detail Weights 3423.7 kg.

Weight Summation Results: (kg.)

	Fabricated	Shop Test	Shipping	Erected	Empty	Operating
Main Elements	684.0	684.0	684.0	684.0	684.0	684.0
Saddles	208.9	208.9	208.9	208.9	208.9	208.9
Stif. Rings	6.0	6.0	6.0	6.0	6.0	6.0
Nozzles	114.5	114.5	114.5	114.5	114.5	114.5
Wld Weights	1500.0	1500.0	1500.0	1500.0	1500.0	1500.0
Exchanger	492.5	492.5	492.5	492.5	492.5	492.5
Insulation	...	...	...	...	244.9	244.9 *
Test Weights	...	300.0	...	...	...	...
Ope Weights	...	...	...	...	...	400.0
Ope. Liquid	...	...	...	...	...	129.6
Tube Ope Lqd	...	...	...	...	...	27.4
Test Liquid	...	129.7	...	...	...	...
Tube Tst Lqd	...	27.4	...	...	...	...
Totals	3005.8	3462.9	3005.8	3005.8	3250.7	3807.7

Field Installation Options:

* Insulation installed after lifting.

Miscellaneous Weight Percent: 20.0 %

Note that the above value for the miscellaneous weight percent has been applied to the shells/heads/flange/tubesheets/tubes etc. in the weight calculations for metallic components.

Weight Summary:

Fabricated Wt.	- Bare weight without removable internals	3005.8 kg.
Shop Test Wt.	- Fabricated weight + water (full)	3462.9 kg.
Shipping Wt.	- Fab. weight + removable intls.+ shipping app.	3005.8 kg.
Erected Wt.	- Fab. wt + or - loose items (trays,platforms etc.)	3005.8 kg.
Ope. Wt. no Liq	- Fab. weight + internals. + details + weights	3250.7 kg.
Operating Wt.	- Empty weight + operating liq. uncorroded	3807.7 kg.
Oper. Wt. + CA	- Corr wt. + operating liquid	3692.8 kg.
Field Test Wt.	- Empty weight + test medium (full)	3604.9 kg.

Exchanger Tube Data

Volume of Exchanger tubes :	27453.4 cm ³
Weight of Ope Liq in tubes :	27.4 kg.
Weight of Water in tubes :	27.4 kg.



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 76 of 204

Element and Detail Weights:

Step: 14

9:40am

Sep 9,2026

Field Test weight is computed in the corroded condition.

Surface Areas of Elements:

From	To	Outside Surface Area cm ²	Inside Surface Area cm ²
10	20	869.877	688.562
20	30	2064.73	1780.82
30	40	1693.54	557.991
40	50	39814.9	34340.1
50	60	1532.91	509.483
60	70	2064.73	1780.82
70	80	810.576	688.562

Total	48851.3	40346.3 cm ²
Total	52.6	43.4 ft ²

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 77 of 204

Nozzle Flange MAWP:

Step: 15 9:40am Sep 9,2026

Nozzle Flange MAWP Results: (KPa. & °C)

Nozzle Description	Flange Rating Ope.	Ambient	Des. Temp	Class	Grade/Group	Equiv. Press	- - - UG-44	Max Pressure 50%	DNV
N1-Tube Inlet	8226.1	10200.0	270	600	GR 1.1	7458.2	4881.0	8226.1	4881.0
N3-Shell inlet	8308.1	10200.0	260	600	GR 1.1	7458.2	5004.0	8308.1	5004.0
N4-Shell outlet	8308.1	10200.0	260	600	GR 1.1	7458.2	5004.0	8308.1	5004.0
N2-Tube Outlet	8226.1	10200.0	270	600	GR 1.1	7458.2	4881.0	8226.1	4881.0

Shellside Flange Rating

Lowest Flange Pressure Rating was (Ope)[ShellSide]: 5003.981 KPa.

Lowest Flange Pressure Rating was (Amb)[ShellSide]: 10200.003 KPa.

Channelside Flange Rating

Lowest Flange Pressure Rating was (Ope)[TubeSide]: 4880.982 KPa.

Lowest Flange Pressure Rating was (Amb)[TubeSide]: 10200.003 KPa.

Selected Method for Derating ASME B16.5 Flange MAWP: ASME UG-44(b)

The UG-44(b) Method is based on the paper PVP 2013-97814. PV Elite uses the maximum loads from each load category to determine ME and FE. In many cases, the computed maximum allowable pressure will be greater than the flange rating. In these cases, the minimum of the rating from the table and the UG-44(b) method will be used. SA-193 B8 Cl. 2 bolts or ones with higher allowable stresses at the specified bolt size shall be used.

The axial force FE must put the nozzle in tension (-P for 107/297; +Fr for PD 5500 AnnexG) to be considered.

Nozzle Description	Gasket Dimension G mm	Fm Value	Resolved Moment ME Kg-m.	Axial Force FE Kgf	MAWP PD KPa.	Maximum Pressure Pmax KPa.	Pass Fail
N1-Tube Inlet	111.125	0.50	185	734	4587.8	4881.0	Pass
N3-Shell inlet	111.125	0.50	185	734	5004.0	5004.0	Pass
N4-Shell outlet	111.125	0.50	185	734	5004.0	5004.0	Pass
N2-Tube Outlet	111.125	0.50	185	734	4587.8	4881.0	Pass

Evaluating Flange on Nozzle [N1-Tube Inlet]:

$$= 16 \cdot ME + 4 \cdot FE \cdot G \leq \pi \cdot G^3 [((PR - PD) + FM \cdot PR)]$$

$$= 16(185) + 4 \cdot \text{abs}(734) \cdot 111.125 \leq \pi \cdot 111.125^3 [(8226.086 - 4587.820) + .500 \cdot 8226.086]$$

$$= 0.32788E+04 \leq 0.34077E+04 \text{ Check Passes}$$

Maximum Pressure for Flange on Nozzle N1-Tube Inlet [Pmax]:

$$= \min(PR, FM \cdot PR + PR - (16 \cdot ME + 4 \cdot FE \cdot G) / (\pi \cdot G^3))$$

$$= \min(8226.086, 0.500 \cdot 8226.086 + 8226.086 - 3278.8 / (\pi \cdot 111.125^3))$$

$$= \min(8226.086, 4880.982)$$

$$= 4880.982 \text{ KPa.}$$

Evaluating Flange on Nozzle [N3-Shell inlet]:

$$= 16 \cdot ME + 4 \cdot FE \cdot G \leq \pi \cdot G^3 [((PR - PD) + FM \cdot PR)]$$

$$= 16(185) + 4 \cdot \text{abs}(734) \cdot 111.125 \leq \pi \cdot 111.125^3 [(8308.086 - 5003.981) + .500 \cdot 8308.086]$$

$$= 0.32788E+04 \leq 0.32788E+04 \text{ Check Passes}$$

Maximum Pressure for Flange on Nozzle N3-Shell inlet [Pmax]:

$$= \min(PR, FM \cdot PR + PR - (16 \cdot ME + 4 \cdot FE \cdot G) / (\pi \cdot G^3))$$

$$= \min(8308.086, 0.500 \cdot 8308.086 + 8308.086 - 3278.8 / (\pi \cdot 111.125^3))$$

$$= \min(8308.086, 5003.981)$$

$$= 5003.981 \text{ KPa.}$$

Evaluating Flange on Nozzle [N4-Shell outlet]:



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 78 of 204

Nozzle Flange MAWP:

Step: 15 9:40am Sep 9, 2026

$$\begin{aligned}
 &= 16 \cdot ME + 4 \cdot FE \cdot G \leq \pi \cdot G^3 [(PR - PD) + FM \cdot PR] \\
 &= 16(185) + 4 \cdot \text{abs}(734) 111.125 \leq \pi \cdot 111.125^3 [(8308.086 - 5003.981) + .500 \cdot 8308.086] \\
 &= 0.32788E+04 \leq 0.32788E+04 \text{ Check Passes}
 \end{aligned}$$

Maximum Pressure for Flange on Nozzle N4-Shell outlet [Pmax]:

$$\begin{aligned}
 &= \min(PR, FM \cdot PR + PR - (16 \cdot ME + 4 \cdot FE \cdot G) / (\pi \cdot G^3)) \\
 &= \min(8308.086, 0.500 \cdot 8308.086 + 8308.086 - 3278.8 / (\pi \cdot 111.125^3)) \\
 &= \min(8308.086, 5003.981) \\
 &= 5003.981 \text{ KPa.}
 \end{aligned}$$

Evaluating Flange on Nozzle [N2-Tube Outlet]:

$$\begin{aligned}
 &= 16 \cdot ME + 4 \cdot FE \cdot G \leq \pi \cdot G^3 [(PR - PD) + FM \cdot PR] \\
 &= 16(185) + 4 \cdot \text{abs}(734) 111.125 \leq \pi \cdot 111.125^3 [(8226.086 - 4587.820) + .500 \cdot 8226.086] \\
 &= 0.32788E+04 \leq 0.34077E+04 \text{ Check Passes}
 \end{aligned}$$

Maximum Pressure for Flange on Nozzle N2-Tube Outlet [Pmax]:

$$\begin{aligned}
 &= \min(PR, FM \cdot PR + PR - (16 \cdot ME + 4 \cdot FE \cdot G) / (\pi \cdot G^3)) \\
 &= \min(8226.086, 0.500 \cdot 8226.086 + 8226.086 - 3278.8 / (\pi \cdot 111.125^3)) \\
 &= \min(8226.086, 4880.982) \\
 &= 4880.982 \text{ KPa.}
 \end{aligned}$$

Flange Pressure Ratings are per ASME B16.5 2025 Metric Edition

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



Wind Load Calculation Results:

Input Values:

Wind Design Code	ASCE/SEI 7-16
Wind Load Reduction Scale Factor	1.100
Basic Wind Speed [V]	97.2 Km/hr
Surface Roughness Category	C: Open Terrain
Type of Surface	Moderately Smooth
Base Elevation	300 mm
Percent Wind for Hydrotest	50.0
Using User defined Wind Press. Vs Elev.	N
Height of Hill or Escarpment H or Hh	0 mm
Distance Upwind of Crest Lh	0 mm
Distance from Crest to the Vessel x	0 mm
Type of Terrain (Hill, Escarpment)	Flat
Damping Factor (Beta) for Wind (Ope)	0.0100
Damping Factor (Beta) for Wind (Empty)	0.0000
Damping Factor (Beta) for Wind (Filled)	0.0000
Site Elevation above Sea Level	0 mm

Wind Analysis Results

The importance factor is not used in the calculation of wind pressure vs. elevation for the selected wind code.

Static Gust-Effect Factor, Operating Case [G]:

$$\begin{aligned}
 &= \min(0.85, 0.925((1 + 1.7 \cdot gQ \cdot I_{zbar} \cdot Q)/(1 + 1.7 \cdot gV \cdot I_{zbar}))) \\
 &= \min(0.85, 0.925((1 + 1.7 \cdot 3.4 \cdot 0.23 \cdot 0.99)/(1 + 1.7 \cdot 3.4 \cdot 0.23))) \\
 &= \min(0.85, 0.92) \\
 &= 0.850
 \end{aligned}$$

Natural Frequency of Vessel (Operating)	33.000 Hz
Natural Frequency of Vessel (Empty)	33.000 Hz
Natural Frequency of Vessel (Test)	33.000 Hz

User Entered Importance Factor is	1.000
Force Coefficient [Cf]	0.657
Structure Height to Diameter ratio	17.197

This is classified as a rigid structure. Static analysis performed.

Sample Calculation for the First Element:

The ASCE code performs calculations in Imperial Units. The wind pressure is therefore computed in these units.

Value of [α] and [Zg]:

Exposure Category: C from Table 26.11-1
 $\alpha = 9.5 : Z_g = 274320 \text{ mm}$

Effective Height [z]:

$$\begin{aligned}
 &= \text{Centroid Height} + \text{Vessel Base Elevation} \\
 &= 535 + 300 = 835 \text{ mm} \\
 &= 2.74 \text{ ft. Imperial Units}
 \end{aligned}$$

Velocity Pressure coefficient evaluated at height z [Kz]:

$$\begin{aligned}
 &\text{Because } z (2.74 \text{ ft.}) < 15 \text{ ft.} \\
 &= 2.01(15 / Z_g)^{2/\alpha} \\
 &= 2.01(15/900)^{2/9.5} \\
 &= 0.85
 \end{aligned}$$

Type of Hill: No Hill



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)

Page 80 of 204

Wind Load Calculation:

Step: 16

9:40am

Sep 9, 2026

Wind Directionality Factor [Kd]:

= 1, per Table 26.6-1

As there is No Hill Present: [Kzt]:

K1 = 0, K2 = 0, K3 = 0

Topographical Factor [Kzt]:

= (1 + K1 • K2 • K3)²

= (1 + 0 • 0 • 0)²

= 1

Velocity Pressure evaluated at height z, Imperial Units [qz]:

= max(16, 0.00256 • Kz • Kzt • Kd • Ke • V(mph)²)

= max(16, 0.00256 • 0.85 • 1 • 1 • 1 • 60.4²)

= 16 psf [78.1] Kgs/m²

Force on the first element [F]:

= qz • G • Cf • WindArea

= 16 • 0.85 • 0.66 • 0.84

= 7.46 lbs. [3.39] Kgf

Element	Hgt (z) mm	K1	K2	K3	Kz	Kzt	qz Kgs/m ²
LHS dish end	835.0	0.000	0.000	0.000	0.849	1.000	78.120
LHS Ch Shell	835.0	0.000	0.000	0.000	0.849	1.000	78.120
LHS Ch Flange	835.0	0.000	0.000	0.000	0.849	1.000	78.120
Main Shell	835.0	0.000	0.000	0.000	0.849	1.000	78.120
RHS Ch Flg	835.0	0.000	0.000	0.000	0.849	1.000	78.120
RHS Ch Shell	835.0	0.000	0.000	0.000	0.849	1.000	78.120
RHS Dish End	835.0	0.000	0.000	0.000	0.849	1.000	78.120

Wind Loads on Masses/Equipment/Piping

ID	Wind Area cm ²	Elevation mm	Pressure Kgs/m ²	Force Kgf
TOP HE EMPTY	375.00	1905.00	78.12	2.93
TOP HE OPERAT	-1.01	1905.00	78.12	-0.01
TOP HE TEST	-1.01	1905.00	78.12	-0.01

Wind Load Calculation:

From	To	Wind Height mm	Wind Diameter mm	Wind Area cm ²	Wind Pressure Kgs/m ²	Element Wind Load Kgf
10	20	835	498.372	776.427	78.12	3.72398
20	30	835	498.371	1495.11	78.12	7.17103
30	40	835	466.741	382.728	78.12	1.83568
40	50	835	498.164	28818.8	78.12	141.429
50	60	835	483.26	347.948	78.12	1.66886
60	70	835	498.371	1495.11	78.12	7.17103
70	80	835	488.397	747.603	78.12	3.58573

The Wind Loads calculated and printed in the Wind Load calculation report have been factored by the input scalar/load reduction factor of: 1.100.

Be sure the wind speed is in accordance with the specified wind design code.

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User
 FileName : 161-C1-C2_(Stack) Page 81 of 204
 Earthquake Load Calculation: Step: 17 9:40am Sep 9,2026

Earthquake Load Calculation Results:

Earthquake Load Calculation:

Input Values:

Seismic Design Code	ASCE/SEI 7-16
Seismic Load Reduction Scale Factor	1.000
Importance Factor	1.250
Table Value Fa	1.600
Table Value Fv	2.400
Max. Mapped Res. Acceleration [Ss]	0.147
Max. Eff. Ground Acceleration [S]	0.065
Force Modification Factor R	3.000
Site Class	D
Component Elevation Ratio z/h	0.000
Amplification Factor Ap	1.000
Force Factor	0.000
Consider Vertical Acceleration	Yes
Minimum Acceleration Multiplier	0.000
User Value of Sds (used if > 0)	0.000
User Value of Sd1 (used if > 0)	0.000
Moment Reduction Factor Tau	1.000

Seismic Analysis Results:

$$\begin{aligned} SMS &= Fa * Ss = 1.6 * 0.15 = 0.24 \\ SM1 &= Fv * S1 = 2.4 * 0.065 = 0.16 \\ SDS &= 2/3 * Sms = 2/3 * 0.24 = 0.16 \\ SD1 &= 2/3 * Sm1 = 2/3 * 0.16 = 0.1 \end{aligned}$$

Check Approximate Fundamental Period from 12.8-7 [Ta]:
 = $C_t \cdot h_{nx}$ where $C_t = 0.020$, $x = 0.75$ and h_n = Structural Height (ft.)
 = $0.020(2.090.75)$
 = 0.035 seconds

The Coefficient C_u from Table 12.8-1 is : 1.700

Fundamental Period (1/Frequency) [T]:
 = (1/Natural Frequency) = (1/33)
 = 0.030

Check the Value of T which is the smaller of $C_u \cdot T_a$ and T:
 = Minimum Value of ($1.7 \cdot 0.035$, 0.03) per 12.8.2
 = 0.030
 As the time period is < 0.06 second, use section 15.4.2.

Base Shear per equation 15.4-5, [V]:
 = $0.3 \cdot Sds \cdot W \cdot I$
 = $0.3 \cdot 0.16 \cdot 3599 \cdot 1.25$
 = 211.613 Kgf

Vertical load per 12.4-4, [Ev]:
 = $0.2 \cdot Sds \cdot W$
 = $0.2 \cdot 0.16 \cdot 3599$
 = 112.9 Kgf

Earthquake Load Calculation:

From	To	Earthquake Height mm	Earthquake Weight Kgf	Element Ope Load Kgf
10	20	94.4755	399.873	23.3238



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)

Page 82 of 204

Earthquake Load Calculation:

Step: 17

9:40am

Sep 9, 2026

20	30	94.4753	399.873	23.3237
30	40	94.4755	399.873	23.3238
40	Sad1	94.4753	399.873	23.3237
Sad1	50	94.4753	399.873	23.3237
40	50	94.4753	399.873	23.3237
50	60	101.358	399.873	25.023
60	70	94.4753	399.873	23.3237
70	80	94.4755	399.873	23.3238

The Earthquake Weight does not include the weight of the saddles.

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)

Page 83 of 204

Center of Gravity Calculation: Step: 18 9:40am Sep 9,2026

Shop/Field Installation Options :

Insulation is installed in the Field after being lifted.

Note : The CG is computed from the first Element From Node

Center of Gravity of the Saddles	3430.975 mm
Center of Gravity of the Liquid	3395.611 mm
Center of Gravity of the Insulation	3380.140 mm
Center of Gravity of the Stiffening Rings	3430.975 mm
Center of Gravity of the Nozzles	3412.225 mm
Center of Gravity of the Added Weights (Operating)	3450.480 mm
Center of Gravity of the Added Weights (Empty)	3450.740 mm
Center of Gravity of the Tubesheet(s)	3435.975 mm
Center of Gravity of the Tubes	3435.975 mm
Center of Gravity of the Baffles	3588.831 mm
Center of Gravity of Bare Shell New and Cold	3347.848 mm
Center of Gravity of Bare Shell Corroded	3338.999 mm
Vessel CG in the Operating Condition	3424.668 mm
Vessel CG in the Fabricated (Shop/Empty) Condition	3424.877 mm
Vessel CG in the Test Condition	3423.802 mm

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 84 of 204

Saddle Calcs: Road Transport:

Step: 19

9:40am


Sep 9, 2026

ASME VIII Division 2 Horizontal Vessel Analysis, Left Saddle:

Horizontal Vessel Stress Calculations : Road Transport

Input and Calculated Values:

Vessel Mean Radius	Rm	101.07	mm
Shell Thickness used in this Case	t	13.179	mm
Stiffened Vessel Length per 4.15.6	L	5785.00	mm
Distance from Saddle to Vessel tangent	a1 or a	1200.00	mm
Saddle Width	b1 or b	275.00	mm
Saddle Bearing Angle	delta or theta	120.00	degrees
Wear Plate Width	b2 or b1	335.00	mm
Wear Plate Bearing Angle	delta2 or theta1	132.00	degrees
Wear Plate Thickness	e2 or tr	14.0	mm
Wear Plate Allowable Stress	fw or Sr	118.00	N./mm ²
Shell Allowable Stress used in Calculation		118.00	N./mm ²
Head Allowable Stress used in Calculation		133.20	N./mm ²
Circumferential Efficiency in Plane of Saddle		1.00	
Circumferential Efficiency at Mid-Span		1.00	
Distance from Saddle Base to Centerline	B	535.00	mm
Coefficient of Friction	mu	0.30	



Results for Horizontal Vessel Analysis:

Saddle Force Q for this Transportation Case		2026.23	Kgf
Shipping Longitudinal Acceleration	gx	0.10	g
Shipping Transverse Acceleration	gz	0.10	g
Shipping Vertical Acceleration	gy	0.05	g
Vertical Acceleration Acting with Transverse	gw	1.00	g
Internal Pressure during Transport		0.00	KPa.
Transportation Wind Load Scalar Factor	wlsf	1.00	
Transportation Wind Velocity	wv	97.2	Km/hr



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)


Page 85 of 204

Saddle Calcs: Road Transport:

Step: 19

9:40am

Sep 9, 2026



Horizontal Vessel Analysis Results:	Actual N./mm ²	Allowable N./mm ²
Long. Stress at Top of Midspan	-11.61	-216.00
Long. Stress at Top of Midspan	11.61	118.00
Long. Stress at Bottom of Midspan	11.61	118.00
Long. Stress at Top of Saddles	11.65	118.00
Long. Stress at Bottom of Saddles	-11.65	-216.00
Long. Stress at Bottom of Saddles	11.65	118.00
Tangential Shear in Shell	2.78	94.40
Circ. Compressive Stress in Shell	1.05	118.00
Stiffener Circ. Stress at Shell	5.52	118.00
Stiffener Circ. Stress at Tip	24.59	234.00

Intermediate Results: Saddle Reaction Q due to Road Transport Load:

Transverse Force due to Wind during Transport [F_{tw}]:

$$= \text{Transverse Area} \cdot 0.00256 \cdot wv^2 \cdot wlsf$$

$$= 36.7 \cdot 0.00256 \cdot 60.4^2 \cdot 1$$

$$= 342.4 \text{ lbf}$$

$$= 155.322 \text{ Kgf}$$

Longitudinal Force due to Wind during Transport [F_{lw}]:

$$= \pi \cdot D^2/4 \cdot 0.00256 \cdot wv^2 \cdot wlsf \cdot \text{Wind Dia. Mult}$$

$$= \pi \cdot 1.36^2/4 \cdot 0.00256 \cdot 60.4^2 \cdot 1 \cdot 1.2$$

$$= 16.3 \text{ lbf}$$

$$= 7.4 \text{ Kgf}$$

Transverse Force due to Lateral Acceleration [F_t]:

$$= g_z \cdot \text{Shipping Weight} \cdot g_w + F_{tw}$$

$$= 0.1 \cdot 2797 \cdot 1 + 155$$

$$= 435.0 \text{ Kgf}$$

Longitudinal Force due to Axial Acceleration [F_l]:

$$= g_x \cdot \text{Shipping Weight} \cdot g_w + F_{lw}$$

$$= 0.1 \cdot 2797 \cdot 1 + 7.41$$

$$= 287.1 \text{ Kgf}$$

Saddle Reaction Force due to Transverse Load [F_{wt}]:

$$= F_t / \text{Num of Saddles} \cdot B / E$$

$$= 435/2 \cdot 535/211$$

$$= 552.3 \text{ Kgf}$$

Saddle Reaction Force due to Longitudinal Load [F_{wl}]:

$$= F_l \cdot B / L_s$$

$$= 287 \cdot 535/3450$$

$$= 44.5 \text{ Kgf}$$

Saddle Reaction Force due to Vertical Transportation Acceleration [F_{rv}]:

$$= \text{Saddle Load} \cdot g_y$$



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 86 of 204

Saddle Calcs: Road Transport: Step: 19 9:40am Sep 9, 2026

$$= 1404 \cdot 0.05$$

$$= 70.189 \text{ Kgf}$$

Load Combination Results due to Transport Loading [Q]:

$$= \text{Saddle Load} + \text{Frv} + \max(\text{Fwl}, \text{Fwt})$$

$$= 1404 + 70.2 + \max(44.5, 552)$$

$$= 2026.2 \text{ Kgf}$$

Summary of Loads at the Base of this Saddle:

Vertical Load (including saddle weight)	2130.66	Kgf
Transverse Shear Load	217.51	Kgf
Longitudinal Shear Load	287.11	Kgf

Note: Wear Plate is Welded to the Shell, $k = 0.1$

Saddle Dimension [E]:

$$= \min(2(\text{ShellID}/2 + t + \text{WearPadThickness})\sin(\theta/2), 2 \cdot R_m)$$

$$= \min(2(189/2 + 13.2 + 14)\sin(120/2), 2 \cdot 101)$$

$$= 210.712 \text{ mm}$$

The Computed K values from Table 4.15.1:

K1 = 0.1066	K2 = 1.1707	K3 = 0.8799	K4 = 0.4011
K5 = 0.7603	K6 = 0.0529	K7 = 0.0529	K8 = 0.3405
K9 = 0.2711	K10 = 0.0581	K1* = 0.1923	K6p = 0.0434
K7p = 0.0434			

The suffix 'p' denotes the values for a wear plate if it exists.

Note: Dimension a is greater than or equal to $R_m/2$.

Moment per Equation 4.15.1 [M1]:

$$= -Q \cdot a [1 - (1 - a/L + (R_m^2 - h_m^2)/(2a \cdot L))/(1 + (4h_m)/3L)]$$

$$= -2026 \cdot 1200 [1 - (1 - 1200/5785 + (101^2 - 0^2)/$$

$$(2 \cdot 1200 \cdot 5785))/(1 + (4 \cdot 0)/(3 \cdot 5785))]$$

$$= -502.6 \text{ Kg-m.}$$

Moment per Equation 4.15.2 [M2]:

$$= Q \cdot L/4((1 + 2(R_m^2 - h_m^2)/(L^2))/(1 + (4h_m^2)/(3L)) - 4a/L)$$

$$= 2026 \cdot 5785/4((1 + 2(101^2 - 0^2)/(5785^2))/(1 + (4 \cdot 0)/$$

$$(3 \cdot 5785)) - 4 \cdot 1200/5785)$$

$$= 500.8 \text{ Kg-m.}$$

Longitudinal Stress at Top of Shell (4.15.4) [σ_1]:

$$= P \cdot R_m/(2t) - M2/(\pi \cdot R_m^2 t)$$

$$= 0 \cdot 101/(2 \cdot 13.2) - 501/(\pi \cdot 101^2 \cdot 13.2)$$

$$= -11.61 \text{ N./mm}^2$$

Longitudinal Stress at Bottom of Shell (4.15.5) [σ_2]:

$$= P \cdot R_m/(2t) + M2/(\pi \cdot R_m^2 \cdot t)$$

$$= 0 \cdot 101/(2 \cdot 13.2) + 501/(\pi \cdot 101^2 \cdot 13.2)$$

$$= 11.61 \text{ N./mm}^2$$

Longitudinal Stress at Top of Shell at Support (4.15.6) [σ_3]:

$$= P \cdot R_m/(2t) - M1/(\pi \cdot R_m^2 \cdot t)$$

$$= 0 \cdot 101/(2 \cdot 13.2) - 503/(\pi \cdot 101^2 \cdot 13.2)$$

$$= 11.65 \text{ N./mm}^2$$

Longitudinal Stress at bottom of Shell at Support (4.15.7) [σ_4]:

$$= P \cdot R_m/(2t) + M1/(\pi \cdot R_m^2 t)$$

$$= 0 \cdot 101/(2 \cdot 13.2) + 503/(\pi \cdot 101^2 \cdot 13.2)$$

$$= -11.65 \text{ N./mm}^2$$

Maximum Shear Force in the Saddle (4.15.3) [T]:

$$= Q(L - 2a)/(L + (4 \cdot h_m/3))$$

$$= 2026(5785 - 2 \cdot 1200)/(5785 + (4 \cdot 0/3))$$



PV Elite 28 Licensee: SL User
 FileName : 161-C1-C2 _(Stack) Page 87 of 204
 Saddle Calcs: Road Transport: Step: 19 9:40am Sep 9,2026

= 1185.6 Kgf

Shear Stress in the shell with a single ring (4.15.13) [T1]:

$$= T / (\pi \cdot R_m \cdot t)$$

$$= 1186 / (\pi \cdot 101 \cdot 13.2)$$

$$= 2.78 \text{ N./mm}^2$$

Decay Length (4.15.20) [x1,x2]:

$$= 0.78 \cdot \sqrt{(R_m \cdot t)}$$

$$= 0.78 \cdot \sqrt{(101 \cdot 13.2)}$$

$$= 28.467 \text{ mm}$$

Circ. Stress in shell w/ring in Plane of Saddle (4.15.32) [σ6*]:

$$= -K5 \cdot Q \cdot k/A$$

$$= -0.76 \cdot 2026 \cdot 0.1/14.4$$

$$= -1.05 \text{ N./mm}^2$$

Note: Single Ring in Plane of Saddle Outside the Shell.

Circ. + Bending Stress in shell w/ring in Plane of Saddle (4.15.35) [σ8*]:

$$= -K8 \cdot Q/A + K6 \cdot Q \cdot R_m \cdot c1/l$$

$$= -0.34 \cdot 2026 / 14.4 + 0.053 \cdot 2026 \cdot 101 \cdot 11.8 / 12.2$$

$$= 5.52 \text{ N./mm}^2$$

Circ. + Bending Stress in ring w/ring in Plane of Saddle (4.15.36) [σ9*]:

$$= -K8 \cdot Q/A - K6 \cdot Q \cdot R_m \cdot c2/l$$

$$= -0.34 \cdot 2026 / 14.4 - 0.053 \cdot 2026 \cdot 101 \cdot 22.9 / 12.2$$

$$= -24.59 \text{ N./mm}^2$$

Results for Vessel Ribs, Web and Base:

Baseplate Length	Bplen	600.0000	mm
Baseplate Thickness	Bpthk	20.0000	mm
Baseplate Width	Bpwid	300.0000	mm
Number of Ribs (inc. outside ribs)	Nribs	3	
Rib Thickness	Ribtk	14.0000	mm
Web Thickness	Webtk	14.0000	mm
Web Location	Webloc	Center	
Saddle Yield Stress	Sy	260.0	N./mm ²
Height of Web at Center	Hw,c	440.0	mm
Friction Coefficient	mu	0.300	

Moment of Inertia of Saddle - Transverse Direction (90 degrees to long axis)

Inertia of Shell [ShellInertia]:

$$= ((1.56 \cdot \sqrt{(R \cdot t)} + \text{WearPlateWidth})^3) / 12$$

$$= ((1.56 \cdot \sqrt{(94.5 \cdot 13.2)} + 335)^3) / 12$$

$$= 7.441 \text{ cm}^4$$

Resolved Inertia for the Shell [I,shell]:

$$= \text{ShellInertia} + A_{\text{Shell}} (C1 - Y)^2$$

$$= 7.44 + 51.4 (185 - 6.59)^2$$

$$= 16343.900 \text{ cm}^4$$

	B mm	D mm	Y mm	A cm ²	AY mm ³	I + AD ² cm ⁴
Shell	390.0	13.2	6.6	51.4	33875.0	0.163E+05
Wearplate	335.0	14.0	20.2	46.9	94641.5	0.127E+05
Web	14.0	393.3	223.9	55.1	1232716.1	0.794E+04
BasePlate	300.0	20.0	430.5	60.0	2583148.0	0.362E+05
Totals	...	...	...	213.4	3944380.8	0.732E+05

Distance to Centroid [C1]:

$$= AY / A$$

$$= 3944380 / 213$$



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 88 of 204

Saddle Calcs: Road Transport:

Step: 19 9:40am

Sep 9, 2026

$$= 184.857 \text{ mm}$$

Angle [β]:

$$= 180 - \text{Saddle Angle}/2$$

$$= 180 - 120/2$$

$$= 120.0$$

Saddle Splitting Coefficient [K1]:

$$= (1 + \cos(\beta) - 0.5 \cdot \sin(\beta)^2) / (\pi - \beta + \sin(\beta) \cos(\beta))$$

$$= (1 + \cos(120) - 0.5 \cdot \sin(120)^2) / (\pi - 2.09 + \sin(120) \cos(120))$$

$$= 0.2035$$

Saddle Splitting Force [Fh]:

$$= K1 \cdot Q$$

$$= 0.2 \cdot 2026$$

$$= 412.3816 \text{ Kgf}$$

$$\text{Tension Stress, } St = (Fh / As) = 0.2497 \text{ N./mm}^2$$

$$\text{Allowed Stress, } Sa = 0.6 \cdot \text{Yield Str} = 155.9972 \text{ N./mm}^2$$

Saddle Splitting Dimension [d]:

$$= B - R \cdot \sin(\theta/2) / (\theta/2 \text{ in radians})$$

$$= 535 - 94.5 \cdot \sin(120/2) / 1.05$$

$$= 456.870 \text{ mm}$$

$$\text{Bending Moment, } M = Fh \cdot d = 188.4083 \text{ Kg-m.}$$

$$\text{Bending Stress, } Sb = (M \cdot C1 / I) = 0.4664 \text{ N./mm}^2$$

$$\text{Allowed Stress, } Sa = 2/3 \cdot \text{Yield Str} = 173.3302 \text{ N./mm}^2$$

Minimum Thickness of Baseplate per Moss:

$$= \sqrt{(3(Q + \text{SaddleWt}) \cdot \text{BasePlateWidth}) / (4 \cdot \text{BasePlateLength} \cdot \text{AllStress})}$$

$$= \sqrt{(3(2026 + 104) \cdot 300) / (4 \cdot 600 \cdot 173)}$$

$$= 6.724 \text{ mm}$$

Calculation of Axial Load, Intermediate Values and Compressive Stress:

Web Length Dimension [Web Length]:

$$= 2 \cdot \cos(90 - \text{Saddle Angle}/2) (\text{Inside Radius} + \text{Shell Thk} + \text{Wear Plate Thk})$$

$$= 2 \cdot \cos(90 - 120/2) (94.5 + 13.2 + 14)$$

$$= 210.712 \text{ mm}$$

Distance between Ribs [e]:

$$= \text{Web Length} / (\text{Nr ribs} - 1)$$

$$= 211 / (3 - 1)$$

$$= 105.356 \text{ mm}$$

Baseplate Pressure Area [Ap]:

$$= e \cdot \text{Bpwid} / 2$$

$$= 105 \cdot 300 / 2$$

$$= 158.034 \text{ cm}^2$$

Bearing Pressure [Bp]:

$$= (Q + \text{SaddleWt}) / (\text{BasePlateLength} \cdot \text{BasePlateWidth})$$

$$= 2131 / (600 \cdot 300)$$

$$= 1.184 \text{ Kgf/cm}^2$$

Axial Load [P]:

$$= Ap \cdot Bp$$

$$= 158 \cdot 1.18$$

$$= 187.065 \text{ Kgf}$$

Area of the Rib and Web [Ar]:

$$= \text{Rib Area} + \text{Web Area}$$

$$= 36.5 + 7.37$$



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 89 of 204

Saddle Calcs: Road Transport:

Step: 19

9:40am

Sep 9, 2026

$$= 43.915 \text{ cm}^2$$

Compressive Stress [Sc]:

$$= P/A_r$$

$$= 187/43.9$$

$$= 0.418 \text{ N./mm}^2$$

Check of Outside Ribs:

Inertia of Saddle, Outer Ribs - Longitudinal Direction

	B	D	Y	A	AY	Io
Rib+Web	14.0	275.0	...	38.5	...	0.243E+04

Rib dimension [D]:

$$= \text{Saddle Width} - \text{Web Thickness}$$

$$= 275 - 14$$

$$= 261.000 \text{ mm}$$

Distance to Centroid from Datum [ytot]:

$$= AY / A$$

$$= 0/43.9$$

$$= 0.000 \text{ mm}$$

Distance to Centroid [C1]:

$$= \text{Saddle Width} / 2$$

$$= 275/2$$

$$= 137.500 \text{ mm}$$

Radius of Gyration [r]:

$$= \sqrt{(\text{Total Inertia} / \text{Total Area})}$$

$$= \sqrt{(2426/43.9)}$$

$$= 74.330 \text{ mm}$$

Length of Outer Rib [L]:

$$= \text{Saddle Height} - \cos(\theta/2) (\text{radius} + \text{shlthk} + \text{wpdthk}) - \text{bpthk}$$

$$= 535 - \cos(120/2) (94.5 + 13.2 + 14) - 20$$

$$= 454.173 \text{ mm}$$

Intermediate Term [Cc]:

$$= \sqrt{(2 \cdot \pi^2 \cdot \text{Elastic Modulus} / \text{Yield Stress})}$$

$$= \sqrt{(2 \cdot \pi^2 \cdot 199943008/260)}$$

$$= 123.211$$

Slenderness ratio [KL/r]:

$$= KL/r$$

$$= 1 \cdot 454/74.3$$

$$= 6.110$$

Bending Moment [Rm]:

$$= FI / (2 \cdot B_{plen}) \cdot e \cdot L / 2$$

$$= 287 / (2 \cdot 600) \cdot 105 \cdot 454/2$$

$$= 5.724 \text{ Kg-m.}$$

Compressive Allowable, $KL/r < C_c$ ($6.11 < 123$) per AISC E2-1 [Sca]:

$$= (1 - (KL/r)^2 / (2 \cdot C_c^2)) F_y / (5/3 + 3 \cdot (KL/r) / (8 \cdot C_c) - (KL/r)^3 / (8 \cdot C_c^3))$$

$$= (1 - (6.11)^2 / (2 \cdot 123^2)) 260 /$$

$$(5/3 + 3 \cdot (6.11) / (8 \cdot 123) - (6.11^3) / (8 \cdot 123^3))$$

$$= 154.1 \text{ N./mm}^2$$

AISC Unity Check of Outside Ribs (must be ≤ 1)

$$= Sc/Sca + (Rm \cdot C1 / I) / Sba$$

$$= 0.42/154 + (5.72 \cdot 138/24263022) / 173$$

$$= 0.005$$



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 90 of 204

Saddle Calcs: Road Transport:

Step: 19

9:40am

Sep 9, 2026

Check of Inside Ribs:

Inertia of Saddle, Inner Ribs - Axial Direction

	B	D	Y	A	AY	Io
Rib	14.0	261.0	0.0	36.5	0.0	0.243E+04
Web	105.4	14.0	0.0	14.7	0.0	2.41
Totals	...	...	...	51.3	...	0.243E+04

Distance to Centroid from Datum [ytot]:

$$= AY / A$$

$$= 0/51.3$$

$$= 0.000 \text{ mm}$$

Distance to Centroid [C1]:

$$= \text{Saddle Width} / 2$$

$$= 275/2$$

$$= 137.500 \text{ mm}$$

Length of Inner Rib [L]:

$$= \text{Saddle Height} - \text{Outside Radius} - \text{Bpthk}$$

$$= 535 - \cos(122/2)(20 + 0 + 0) - 0$$

$$= 393.345 \text{ mm}$$

Radius of Gyration [r]:

$$= \sqrt{(\text{Total Inertia} / \text{Total Area})}$$

$$= \sqrt{(2428/51.3)}$$

$$= 68.809 \text{ mm}$$

Slenderness ratio [KL/r]:

$$= KL/r$$

$$= 1 \cdot 393/68.8$$

$$= 5.717$$

Unit Force [Force,u]:

$$= FI / (2 \cdot \text{Baseplate Length})$$

$$= 287/(2 \cdot 600)$$

$$= 0.239 \text{ Kg/mm}$$

Moment at base of inner Rib [Mbase,c]:

$$= \text{Unit Force} \cdot e \cdot L$$

$$= 0.24 \cdot 105 \cdot 393$$

$$= 9.915 \text{ Kg-m.}$$

Bending Stress due to Transverse Force and Weight Load [σ_B ,base,c]:

$$= \text{Bending Moment} / \text{Section Modulus}$$

$$= 9.92/176610$$

$$= 0.551 \text{ N./mm}^2$$

Compressive Allowable, $KL/r < C_c$ ($5.72 < 123$) per AISC E2-1 [Sca]:

$$= (1 - (KL/r)^2 / (2 \cdot C_c^2)) F_y / (5/3 + 3 \cdot (KL/r) / (8 \cdot C_c) - (KL/r)^3 / (8 \cdot C_c^3))$$

$$= (1 - (5.72)^2 / (2 \cdot 123^2)) 260 /$$

$$(5/3 + 3 \cdot (5.72) / (8 \cdot 123) - (5.72^3) / (8 \cdot 123^3))$$

$$= 154.2 \text{ N./mm}^2$$

AISC Unity Check of Inside Ribs (must be ≤ 1)

$$= S_c / S_{ca} + (M_{base,c} \cdot C_{1/I}) / S_{ba}$$

$$= 0.72/154 + (9.92 \cdot 138/2428) / 173$$

$$= 0.008$$

ASME VIII Division 2 Horizontal Vessel Analysis, Right Saddle:

Input and Calculated Values:



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 91 of 204

Saddle Calcs: Road Transport: Step: 19 9:40am Sep 9,2026

Vessel Mean Radius	Rm	101.07	mm
Shell Thickness used in this Case	t	13.179	mm
Stiffened Vessel Length per 4.15.6	L	5785.00	mm
Distance from Saddle to Vessel tangent	a1 or a	1200.00	mm
Saddle Width	b1 or b	275.00	mm
Saddle Bearing Angle	delta or theta	120.00	degrees
Wear Plate Width	b2 or b1	335.00	mm
Wear Plate Bearing Angle	delta2 or theta1	132.00	degrees
Wear Plate Thickness	e2 or tr	14.0	mm
Wear Plate Allowable Stress	fw or Sr	118.00	N./mm ²
Shell Allowable Stress used in Calculation		118.00	N./mm ²
Head Allowable Stress used in Calculation		134.60	N./mm ²
Circumferential Efficiency in Plane of Saddle		1.00	
Circumferential Efficiency at Mid-Span		1.00	
Distance from Saddle Base to Centerline	B	535.00	mm
Coefficient of Friction	mu	0.00	

Results for Horizontal Vessel Analysis:

Saddle Force Q for this Transportation Case		2015.07	Kgf
Shipping Longitudinal Acceleration	gx	0.10	g
Shipping Transverse Acceleration	gz	0.10	g
Shipping Vertical Acceleration	gy	0.05	g
Vertical Acceleration Acting with Transverse	gw	1.00	g
Internal Pressure during Transport		0.00	KPa.
Transportation Wind Load Scalar Factor	wlsf	1.00	
Transportation Wind Velocity	wv	97.2	Km/hr

Horizontal Vessel Analysis Results:		Actual N./mm ²	Allowable N./mm ²
Long. Stress at Top of Midspan		-11.55	-216.00
Long. Stress at Top of Midspan		11.55	118.00
Long. Stress at Bottom of Midspan		11.55	118.00
Long. Stress at Top of Saddles		11.59	118.00
Long. Stress at Bottom of Saddles		-11.59	-216.00
Long. Stress at Bottom of Saddles		11.59	118.00
Tangential Shear in Shell		2.76	94.40
Circ. Compressive Stress in Shell		1.04	118.00
Stiffener Circ. Stress at Shell		5.49	118.00
Stiffener Circ. Stress at Tip		24.45	234.00

Intermediate Results: Saddle Reaction Q due to Road Transport Load:

Transverse Force due to Wind during Transport [Ftw]:

$$\begin{aligned}
 &= \text{Transverse Area} \cdot 0.00256 \cdot wv^2 \cdot wlsf \\
 &= 36.7 \cdot 0.00256 \cdot 60.4^2 \cdot 1 \\
 &= 342.4 \text{ lbf} \\
 &= 155.322 \text{ Kgf}
 \end{aligned}$$

Longitudinal Force due to Wind during Transport [Flw]:

$$\begin{aligned}
 &= \pi \cdot D^2/4 \cdot 0.00256 \cdot wv^2 \cdot wlsf \cdot \text{Wind Dia. Mult} \\
 &= \pi \cdot 1.36^2/4 \cdot 0.00256 \cdot 60.4^2 \cdot 1 \cdot 1.2 \\
 &= 16.3 \text{ lbf} \\
 &= 7.4 \text{ Kgf}
 \end{aligned}$$

Transverse Force due to Lateral Acceleration [Ft]:

$$\begin{aligned}
 &= gz \cdot \text{Shipping Weight} \cdot gw + Ftw \\
 &= 0.1 \cdot 2797 \cdot 1 + 155
 \end{aligned}$$



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 92 of 204

Saddle Calcs: Road Transport:

Step: 19

9:40am

Sep 9, 2026

= 435.0 Kgf

Longitudinal Force due to Axial Acceleration [FI]:

= $g_x \cdot \text{Shipping Weight} \cdot g_w + F_{lw}$

= $0.1 \cdot 2797 \cdot 1 + 7.41$

= 287.1 Kgf

Saddle Reaction Force due to Transverse Load [Fwt]:

= $F_t / \text{Num of Saddles} \cdot B / E$

= $435/2 \cdot 535/211$

= 552.3 Kgf

Saddle Reaction Force due to Longitudinal Load [Fwl]:

= $F_l \cdot B / L_s$

= $287 \cdot 535/3450$

= 44.5 Kgf

Saddle Reaction Force due to Vertical Transportation Acceleration [Frv]:

= Saddle Load $\cdot g_y$

= $1393 \cdot 0.05$

= 69.658 Kgf

Load Combination Results due to Transport Loading [Q]:

= Saddle Load + Frv + max(Fwl, Fwt)

= $1393 + 69.7 + \max(44.5, 552)$

= 2015.1 Kgf

Summary of Loads at the Base of this Saddle:

Vertical Load (including saddle weight)

2119.50 Kgf

Transverse Shear Load

217.51 Kgf

Longitudinal Shear Load

287.11 Kgf

Note: Wear Plate is Welded to the Shell, $k = 0.1$

Saddle Dimension [E]:

= $\min(2(\text{ShellID}/2 + t + \text{WearPadThickness}) \sin(\theta/2), 2 \cdot R_m)$

= $\min(2(189/2 + 13.2 + 14) \sin(120/2), 2 \cdot 101)$

= 210.712 mm

The Computed K values from Table 4.15.1:

K1 = 0.1066 K2 = 1.1707 K3 = 0.8799 K4 = 0.4011

K5 = 0.7603 K6 = 0.0529 K7 = 0.0529 K8 = 0.3405

K9 = 0.2711 K10 = 0.0581 K1* = 0.1923 K6p = 0.0434

K7p = 0.0434

The suffix 'p' denotes the values for a wear plate if it exists.

Note: Dimension a is greater than or equal to $R_m/2$.

Moment per Equation 4.15.1 [M1]:

= $-Q \cdot a [1 - (1 - a/L + (R_m^2 - h_m^2)/(2a \cdot L)) / (1 + (4h_m)/3L)]$

= $-2015 \cdot 1200 [1 - (1 - 1200/5785 + (101^2 - 0^2)/$

$(2 \cdot 1200 \cdot 5785)) / (1 + (4 \cdot 0)/(3 \cdot 5785))]$

= -499.8 Kg-m.

Moment per Equation 4.15.2 [M2]:

= $Q \cdot L/4 ((1 + 2(R_m^2 - h_m^2)/(L^2)) / (1 + (4h_m^2)/(3L)) - 4a/L)$

= $2015 \cdot 5785/4 ((1 + 2(101^2 - 0^2)/(5785^2)) / (1 + (4 \cdot 0)/$

$(3 \cdot 5785)) - 4 \cdot 1200/5785)$

= 498.0 Kg-m.

Longitudinal Stress at Top of Shell (4.15.4) [σ_1]:

= $P \cdot R_m / (2t) - M_2 / (\pi \cdot R_m^3 t)$

= $0 \cdot 101 / (2 \cdot 13.2) - 498 / (\pi \cdot 101^3 \cdot 13.2)$

= -11.55 N./mm²



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 93 of 204

Saddle Calcs: Road Transport:

Step: 19

9:40am

Sep 9, 2026

Longitudinal Stress at Bottom of Shell (4.15.5) [σ_2]:

$$= P \cdot R_m / (2t) + M_2 / (\pi \cdot R_m^2 \cdot t)$$

$$= 0 \cdot 101 / (2 \cdot 13.2) + 498 / (\pi \cdot 101^2 \cdot 13.2)$$

$$= 11.55 \text{ N./mm}^2$$

Longitudinal Stress at Top of Shell at Support (4.15.6) [σ_3]:

$$= P \cdot R_m / (2t) - M_1 / (\pi \cdot R_m^2 \cdot t)$$

$$= 0 \cdot 101 / (2 \cdot 13.2) - 500 / (\pi \cdot 101^2 \cdot 13.2)$$

$$= 11.59 \text{ N./mm}^2$$

Longitudinal Stress at bottom of Shell at Support (4.15.7) [σ_4]:

$$= P \cdot R_m / (2t) + M_1 / (\pi \cdot R_m^2 \cdot t)$$

$$= 0 \cdot 101 / (2 \cdot 13.2) + 500 / (\pi \cdot 101^2 \cdot 13.2)$$

$$= -11.59 \text{ N./mm}^2$$

Maximum Shear Force in the Saddle (4.15.3) [T]:

$$= Q(L - 2a) / (L + (4 \cdot h_m / 3))$$

$$= 2015 \cdot (5785 - 2 \cdot 1200) / (5785 + (4 \cdot 0 / 3))$$

$$= 1179.1 \text{ Kgf}$$

Shear Stress in the shell with a single ring (4.15.13) [τ_1]:

$$= T / (\pi \cdot R_m \cdot t)$$

$$= 1179 / (\pi \cdot 101 \cdot 13.2)$$

$$= 2.76 \text{ N./mm}^2$$

Decay Length (4.15.20) [x_1, x_2]:

$$= 0.78 \cdot \sqrt{(R_m \cdot t)}$$

$$= 0.78 \cdot \sqrt{(101 \cdot 13.2)}$$

$$= 28.467 \text{ mm}$$

Circ. Stress in shell w/ring in Plane of Saddle (4.15.32) [σ_6^*]:

$$= -K_5 \cdot Q \cdot k / A$$

$$= -0.76 \cdot 2015 \cdot 0.1 / 14.4$$

$$= -1.04 \text{ N./mm}^2$$

Note: Single Ring in Plane of Saddle Outside the Shell.

Circ. + Bending Stress in shell w/ring in Plane of Saddle (4.15.35) [σ_8^*]:

$$= -K_8 \cdot Q / A + K_6 \cdot Q \cdot R_m \cdot c_1 / I$$

$$= -0.34 \cdot 2015 / 14.4 + 0.053 \cdot 2015 \cdot 101 \cdot 11.8 / 12.2$$

$$= 5.49 \text{ N./mm}^2$$

Circ. + Bending Stress in ring w/ring in Plane of Saddle (4.15.36) [σ_9^*]:

$$= -K_8 \cdot Q / A - K_6 \cdot Q \cdot R_m \cdot c_2 / I$$

$$= -0.34 \cdot 2015 / 14.4 - 0.053 \cdot 2015 \cdot 101 \cdot 22.9 / 12.2$$

$$= -24.45 \text{ N./mm}^2$$

Results for Vessel Ribs, Web and Base:

Baseplate Length	Bplen	600.0000	mm
Baseplate Thickness	Bpthk	20.0000	mm
Baseplate Width	Bpwid	300.0000	mm
Number of Ribs (inc. outside ribs)	Nribs	3	
Rib Thickness	Ribtk	14.0000	mm
Web Thickness	Webtk	14.0000	mm
Web Location	Webloc	Center	
Saddle Yield Stress	Sy	260.0	N./mm ²
Height of Web at Center	Hw,c	440.0	mm
Friction Coefficient	mu	0.000	

Moment of Inertia of Saddle - Transverse Direction (90 degrees to long axis)

Inertia of Shell [ShellInertia]:

$$= ((1.56 \cdot \sqrt{(R \cdot t)} + \text{WearPlateWidth})^3) / 12$$



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 94 of 204

Saddle Calcs: Road Transport:

Step: 19

9:40am

Sep 9, 2026

$$= ((1.56 \cdot \sqrt{(94.5 \cdot 13.2)} + 335) / 12) / 12$$

$$= 7.441 \text{ cm}^4$$

Resolved Inertia for the Shell [I,shell]:

$$= \text{ShellInertia} + A_{\text{Shell}} (C1 - Y)^2$$

$$= 7.44 + 51.4 (185 - 6.59)^2$$

$$= 16343.900 \text{ cm}^4$$

	B mm	D mm	Y mm	A cm ²	AY mm ³	I + AD ² cm ⁴
Shell	390.0	13.2	6.6	51.4	33875.0	0.163E+05
Wearplate	335.0	14.0	20.2	46.9	94641.5	0.127E+05
Web	14.0	393.3	223.9	55.1	1232716.1	0.794E+04
BasePlate	300.0	20.0	430.5	60.0	2583148.0	0.362E+05
Totals	...	...	...	213.4	3944380.8	0.732E+05

Distance to Centroid [C1]:

$$= AY / A$$

$$= 3944380 / 213$$

$$= 184.857 \text{ mm}$$

Angle [β]:

$$= 180 - \text{Saddle Angle} / 2$$

$$= 180 - 120 / 2$$

$$= 120.0$$

Saddle Splitting Coefficient [K1]:

$$= (1 + \cos(\beta) - 0.5 \cdot \sin(\beta)^2) / (\pi - \beta + \sin(\beta) \cos(\beta))$$

$$= (1 + \cos(120) - 0.5 \cdot \sin(120)^2) / (\pi - 2.09 + \sin(120) \cos(120))$$

$$= 0.2035$$

Saddle Splitting Force [Fh]:

$$= K1 \cdot Q$$

$$= 0.2 \cdot 2015$$

$$= 410.1109 \text{ Kg}$$

$$\text{Tension Stress, } St = (Fh / As) = 0.2483 \text{ N./mm}^2$$

$$\text{Allowed Stress, } Sa = 0.6 \cdot \text{Yield Str} = 155.9972 \text{ N./mm}^2$$

Saddle Splitting Dimension [d]:

$$= B - R \cdot \sin(\theta/2) / (\theta/2 \text{ in radians})$$

$$= 535 - 94.5 \cdot \sin(120/2) / 1.05$$

$$= 456.870 \text{ mm}$$

$$\text{Bending Moment, } M = Fh \cdot d = 187.3709 \text{ Kg-m.}$$

$$\text{Bending Stress, } Sb = (M \cdot C1 / I) = 0.4638 \text{ N./mm}^2$$

$$\text{Allowed Stress, } Sa = 2/3 \cdot \text{Yield Str} = 173.3302 \text{ N./mm}^2$$

Minimum Thickness of Baseplate per Moss:

$$= \sqrt{(3(Q + \text{SaddleWt}) \cdot \text{BasePlateWidth}) / (4 \cdot \text{BasePlateLength} \cdot \text{AllStress})}$$

$$= \sqrt{(3(2015 + 104) \cdot 300) / (4 \cdot 600 \cdot 173)}$$

$$= 6.706 \text{ mm}$$

Calculation of Axial Load, Intermediate Values and Compressive Stress:

Web Length Dimension [Web Length]:

$$= 2 \cdot \cos(90 - \text{Saddle Angle} / 2) (\text{Inside Radius} + \text{Shell Thk} + \text{Wear Plate Thk})$$

$$= 2 \cdot \cos(90 - 120/2) (94.5 + 13.2 + 14)$$

$$= 210.712 \text{ mm}$$

Distance between Ribs [e]:

$$= \text{Web Length} / (N_{\text{ribs}} - 1)$$

$$= 211 / (3 - 1)$$



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 95 of 204

Saddle Calcs: Road Transport:

Step: 19

9:40am

Sep 9, 2026

= 105.356 mm

Baseplate Pressure Area [Ap]:

= e • Bpwid / 2

= 105 • 300/2

= 158.034 cm²

Bearing Pressure [Bp]:

= (Q + SaddleWt) / (BasePlateLength • BasePlateWidth)

= 2120/(600 • 300)

= 1.178 Kg/cm²

Axial Load [P]:

= Ap • Bp

= 158 • 1.18

= 186.085 Kg

Area of the Rib and Web [Ar]:

= Rib Area + Web Area

= 36.5 + 7.37

= 43.915 cm²

Compressive Stress [Sc]:

= P/Ar

= 186/43.9

= 0.416 N./mm²

Check of Outside Ribs:

Inertia of Saddle, Outer Ribs - Longitudinal Direction

	B	D	Y	A	AY	Io
Rib+Web	14.0	275.0	...	38.5	...	0.243E+04

Rib dimension [D]:

= Saddle Width - Web Thickness

= 275 - 14

= 261.000 mm

Distance to Centroid from Datum [ytot]:

= AY / A

= 0/43.9

= 0.000 mm

Distance to Centroid [C1]:

= Saddle Width / 2

= 275/2

= 137.500 mm

Radius of Gyration [r]:

= $\sqrt{\text{Total Inertia} / \text{Total Area}}$

= $\sqrt{2426/43.9}$

= 74.330 mm

Length of Outer Rib [L]:

= Saddle Height - cos(theta/2)(radius + shlthk + wpdthk) - bpthk

= 535 - cos(120/2)(94.5 + 13.2 + 14) - 20

= 454.173 mm

Intermediate Term [Cc]:

= $\sqrt{2 \cdot \pi^2 \cdot \text{Elastic Modulus} / \text{Yield Stress}}$

= $\sqrt{2 \cdot \pi^2 \cdot 199943008/260}$

= 123.211



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 96 of 204

Saddle Calcs: Road Transport:

Step: 19

9:40am

Sep 9, 2026

Slenderness ratio [KL/r]:

$$= KL/r$$

$$= 1 \cdot 454/74.3$$

$$= 6.110$$

Bending Moment [Rm]:

$$= Fl / (2 \cdot B_{pln}) \cdot e \cdot L / 2$$

$$= 287 / (2 \cdot 600) \cdot 105 \cdot 454 / 2$$

$$= 5.724 \text{ Kg-m.}$$

Compressive Allowable, $KL/r < C_c$ (6.11 < 123) per AISC E2-1 [Sca]:

$$= (1 - (KL/r)^2 / (2 \cdot C_c^2)) F_y / (5/3 + 3 \cdot (KL/r) / (8 \cdot C_c) - (KL/r)^3 / (8 \cdot C_c^3))$$

$$= (1 - (6.11)^2 / (2 \cdot 123^2)) 260 / (5/3 + 3 \cdot (6.11) / (8 \cdot 123) - (6.11)^3 / (8 \cdot 123^3))$$

$$= 154.1 \text{ N./mm}^2$$

AISC Unity Check of Outside Ribs (must be ≤ 1)

$$= S_c / S_{ca} + (R_m \cdot C_1 / I) / S_{ba}$$

$$= 0.42 / 154 + (5.72 \cdot 138 / 24263022) / 173$$

$$= 0.005$$

Check of Inside Ribs:

Inertia of Saddle, Inner Ribs - Axial Direction

	B	D	Y	A	AY	Io
Rib	14.0	261.0	0.0	36.5	0.0	0.243E+04
Web	105.4	14.0	0.0	14.7	0.0	2.41
Totals	...	...	...	51.3	...	0.243E+04

Distance to Centroid from Datum [ytot]:

$$= AY / A$$

$$= 0/51.3$$

$$= 0.000 \text{ mm}$$

Distance to Centroid [C1]:

$$= \text{Saddle Width} / 2$$

$$= 275/2$$

$$= 137.500 \text{ mm}$$

Length of Inner Rib [L]:

$$= \text{Saddle Height} - \text{Outside Radius} - B_{pthk}$$

$$= 535 - \cos(122/2) (20 + 0 + 0) - 0$$

$$= 393.345 \text{ mm}$$

Radius of Gyration [r]:

$$= \sqrt{ (\text{Total Inertia} / \text{Total Area}) }$$

$$= \sqrt{ (2428/51.3) }$$

$$= 68.809 \text{ mm}$$

Slenderness ratio [KL/r]:

$$= KL/r$$

$$= 1 \cdot 393/68.8$$

$$= 5.717$$

Unit Force [Force,u]:

$$= Fl / (2 \cdot \text{Baseplate Length})$$

$$= 287 / (2 \cdot 600)$$

$$= 0.239 \text{ Kg/mm}$$

Moment at base of inner Rib [Mbase,c]:

$$= \text{Unit Force} \cdot e \cdot L$$

$$= 0.24 \cdot 105 \cdot 393$$

$$= 9.915 \text{ Kg-m.}$$



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 97 of 204

Saddle Calcs: Road Transport:

Step: 19

9:40am

Sep 9, 2026

Bending Stress due to Transverse Force and Weight Load [σ_B ,base,c]:

= Bending Moment / Section Modulus

= 9.92/176610

= 0.551 N./mm²

Compressive Allowable, $KL/r < C_c$ (5.72 < 123) per AISC E2-1 [Sca]:

= (1-(KL/r)²/(2• C_c^2)) F_y /(5/3+3•(KL/r)/(8• C_c)-(KL/r)³)/(8• C_c^3)

= (1-(5.72)²/(2 • 123²))260/

(5/3+3•(5.72)/(8• 123)-(5.72³)/(8•123³)

= 154.2 N./mm²

AISC Unity Check of Inside Ribs (must be ≤ 1)

= $S_c/S_{ca} + (M_{base,c} \cdot C_{1/I})/S_{ba}$

= 0.71/154 + (9.92 • 138/2428)/173

= 0.008

Review notes about nozzle loadings and supports in the Warnings report.

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 98 of 204

Saddle Calcs: Operating Case:

Step: 20

9:40am


Sep 9, 2026

ASME VIII Division 2 Horizontal Vessel Analysis, Left Saddle:

Horizontal Vessel Stress Calculations : Operating Case

Input and Calculated Values:

Vessel Mean Radius	Rm	102.57	mm
Shell Thickness used in this Case	t	13.179	mm
Stiffened Vessel Length per 4.15.6	L	5785.00	mm
Distance from Saddle to Vessel tangent	a1 or a	1200.00	mm
Saddle Width	b1 or b	275.00	mm
Saddle Bearing Angle	delta or theta	120.00	degrees
Wear Plate Width	b2 or b1	335.00	mm
Wear Plate Bearing Angle	delta2 or theta1	132.00	degrees
Wear Plate Thickness	e2 or tr	14.0	mm
Wear Plate Allowable Stress	fw or Sr	118.00	N./mm ²
Shell Allowable Stress used in Calculation		118.00	N./mm ²
Head Allowable Stress used in Calculation		133.20	N./mm ²
Circumferential Efficiency in Plane of Saddle		1.00	
Circumferential Efficiency at Mid-Span		1.00	
Distance from Saddle Base to Centerline	B	535.00	mm
Coefficient of Friction	mu	0.30	



Results for Horizontal Vessel Analysis:

Saddle Force Q, Operating Case	10652.70	Kgf
Pressure used in Analysis	P	2400.887 KPa.

Horizontal Vessel Analysis Results:	Actual N./mm ²	Allowable N./mm ²
Long. Stress at Top of Midspan	-64.66	-176.76
Long. Stress at Top of Midspan	64.66	118.00
Long. Stress at Bottom of Midspan	88.85	118.00
Long. Stress at Top of Saddles	89.11	118.00
Long. Stress at Bottom of Saddles	-64.92	-176.76
Long. Stress at Bottom of Saddles	64.92	118.00
Tangential Shear in Shell	18.64	94.40



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 99 of 204

Saddle Calcs: Operating Case: Step: 20 9:40am Sep 9, 2026

Circ. Compressive Stress in Shell	6.92	118.00
Stiffener Circ. Stress at Shell	38.12	147.50
Stiffener Circ. Stress at Tip	160.42	172.00

Intermediate Results: Saddle Reaction Q due to Wind or Seismic:

Transverse Saddle Reaction Force [Fwt]:

$$= \text{Ftr}(\text{Ft/Num of Saddles} + \text{Z Force Load}) \cdot B / E$$

$$= 3 (167/2 + 1048) \cdot 535/211$$

$$= 8617.3 \text{ Kgf}$$

Longitudinal Saddle Reaction Force [Fwl]:

$$= \max(\text{Fl,wind}; \text{Sum of X Forces}) \cdot B / \text{Ls}$$

$$= \max(16.8, 300) \cdot 535/3450$$

$$= 7.8 \text{ Kgf}$$

Saddle Reaction Force due to Earthquake Fl [Fsl]:

$$= \max(\text{Fl,eq}; \text{Sum of X Forces}) \cdot B / \text{Ls}$$

$$= \max(212, 300) \cdot 535/3450$$

$$= 46.5 \text{ Kgf}$$

Saddle Reaction Force due to Earthquake Ft [Fst]:

$$= \text{Ftr}(\text{Ft/Num of Saddles} + \text{Z Force Load}) \cdot B / E$$

$$= 3 (212/2 + 1048) \cdot 535/211$$

$$= 8788.8 \text{ Kgf}$$

Load Combination Results for Q + Wind or Seismic [Q]:

$$= \text{Saddle Load} + \max(\text{Fwl}, \text{Fwt}, \text{Fsl}, \text{Fst})$$

$$= 1864 + \max(7.75, 8617, 46.5, 8789)$$

$$= 10652.7 \text{ Kgf}$$

Longitudinal Wind Force [Fl]:

$$= \text{WindScalar} \cdot \text{WindPress}(\text{Platform Area} + (\pi/4(\text{OD} \cdot \text{WindDiaMult})^2))$$

$$= 1.1 \cdot 766 (0 + \pi/4(0.42 \cdot 1.2)^2)$$

$$= 164.386 \text{ N}$$

Summary of Loads at the Base of this Saddle:

Vertical Load (including saddle weight)	10757.13	Kgf
Transverse Shear Load	1153.83	Kgf
Longitudinal Shear Load	300.00	Kgf

Note: Wear Plate is Welded to the Shell, k = 0.1

Saddle Dimension [E]:

$$= \min(2(\text{ShellID}/2 + t + \text{WearPadThickness}) \sin(\theta/2), 2 \cdot \text{Rm})$$

$$= \min(2(189/2 + 13.2 + 14) \sin(120/2), 2 \cdot 103)$$

$$= 210.712 \text{ mm}$$

The Computed K values from Table 4.15.1:

K1 = 0.1066	K2 = 1.1707	K3 = 0.8799	K4 = 0.4011
K5 = 0.7603	K6 = 0.0529	K7 = 0.0529	K8 = 0.3405
K9 = 0.2711	K10 = 0.0581	K1* = 0.1923	K6p = 0.0434
K7p = 0.0434			

The suffix 'p' denotes the values for a wear plate if it exists.

Note: Dimension a is greater than or equal to Rm/2.

Moment per Equation 4.15.1 [M1]:

$$= -Q \cdot a [1 - (1 - a/L + (Rm^2 - hm^2)/(2a \cdot L)) / (1 + (4hm)/3L)]$$

$$= -10653 \cdot 1200 [1 - (1 - 1200/5785 + (103^2 - 0^2) /$$

$$(2 \cdot 1200 \cdot 5785)) / (1 + (4 \cdot 0) / (3 \cdot 5785))]$$

$$= -2642.0 \text{ Kg-m.}$$



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 100 of 204

Saddle Calcs: Operating Case: Step: 20 9:40am Sep 9, 2026

Moment per Equation 4.15.2 [M2]:

$$= Q \cdot L / 4 \cdot ((1 + 2(Rm^2 - hm^2) / (L^2)) / (1 + (4hm^2) / (3L)) - 4a/L)$$

$$= 10653 \cdot 5785 / 4 \cdot ((1 + 2(103^2 - 0^2) / (5785^2)) / (1 + (4 \cdot 0) / (3 \cdot 5785)) - 4 \cdot 1200 / 5785)$$

$$= 2633.0 \text{ Kg-m.}$$

Longitudinal Stress at Top of Shell (4.15.4) [σ_1]:

$$= P \cdot Rm / (2t) - M2 / (\pi \cdot Rm^2 \cdot t)$$

$$= 2401 \cdot 103 / (2 \cdot 10.2) - 2633 / (\pi \cdot 103^2 \cdot 10.2)$$

$$= -64.66 \text{ N./mm}^2$$

Longitudinal Stress at Bottom of Shell (4.15.5) [σ_2]:

$$= P \cdot Rm / (2t) + M2 / (\pi \cdot Rm^2 \cdot t)$$

$$= 2401 \cdot 103 / (2 \cdot 10.2) + 2633 / (\pi \cdot 103^2 \cdot 10.2)$$

$$= 88.85 \text{ N./mm}^2$$

Longitudinal Stress at Top of Shell at Support (4.15.6) [σ_3]:

$$= P \cdot Rm / (2t) - M1 / (\pi \cdot Rm^2 \cdot t)$$

$$= 2401 \cdot 103 / (2 \cdot 10.2) - 2642 / (\pi \cdot 103^2 \cdot 10.2)$$

$$= 89.11 \text{ N./mm}^2$$

Longitudinal Stress at bottom of Shell at Support (4.15.7) [σ_4]:

$$= P \cdot Rm / (2t) + M1 / (\pi \cdot Rm^2 \cdot t)$$

$$= 2401 \cdot 103 / (2 \cdot 10.2) + 2642 / (\pi \cdot 103^2 \cdot 10.2)$$

$$= -64.92 \text{ N./mm}^2$$

Maximum Shear Force in the Saddle (4.15.3) [T]:

$$= Q(L - 2a) / (L + (4 \cdot hm / 3))$$

$$= 10653 \cdot (5785 - 2 \cdot 1200) / (5785 + (4 \cdot 0 / 3))$$

$$= 6233.3 \text{ Kg}$$

Shear Stress in the shell with a single ring (4.15.13) [τ_1]:

$$= T / (\pi \cdot Rm \cdot t)$$

$$= 6233 / (\pi \cdot 103 \cdot 10.2)$$

$$= 18.64 \text{ N./mm}^2$$

Decay Length (4.15.20) [x1,x2]:

$$= 0.78 \cdot \sqrt{(Rm \cdot t)}$$

$$= 0.78 \cdot \sqrt{(103 \cdot 10.2)}$$

$$= 25.203 \text{ mm}$$

Circ. Stress in shell w/ring in Plane of Saddle (4.15.32) [σ_6^*]:

$$= -K5 \cdot Q \cdot k/A$$

$$= -0.76 \cdot 10653 \cdot 0.1 / 11.5$$

$$= -6.92 \text{ N./mm}^2$$

Note: Single Ring in Plane of Saddle Outside the Shell.

Circ. + Bending Stress in shell w/ring in Plane of Saddle (4.15.35) [σ_8^*]:

$$= -K8 \cdot Q/A + K6 \cdot Q \cdot Rm \cdot c1/l$$

$$= -0.34 \cdot 10653 / 11.5 + 0.053 \cdot 10653 \cdot 103 \cdot 11 / 9.04$$

$$= 38.12 \text{ N./mm}^2$$

Circ. + Bending Stress in ring w/ring in Plane of Saddle (4.15.36) [σ_9^*]:

$$= -K8 \cdot Q/A - K6 \cdot Q \cdot Rm \cdot c2/l$$

$$= -0.34 \cdot 10653 / 11.5 - 0.053 \cdot 10653 \cdot 103 \cdot 20.7 / 9.04$$

$$= -160.42 \text{ N./mm}^2$$

Distance between Saddle Supports [Ls]:

$$= 3450.0 \text{ mm}$$

Free Un-Restrained Thermal Expansion between the Saddles [Exp]:

$$= \alpha \cdot Ls (\text{Design Temperature} - \text{Ambient Temperature})$$

$$= 0.13139 \text{E-04} \cdot 3450 (260 - 21.1)$$

$$= 10.828 \text{ mm}$$



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 101 of 204

Saddle Calcs: Operating Case:

Step: 20

9:40am

Sep 9, 2026

Results for Vessel Ribs, Web and Base:

Baseplate Length	Bplen	600.0000	mm
Baseplate Thickness	Bpthk	20.0000	mm
Baseplate Width	Bpwid	300.0000	mm
Number of Ribs (inc. outside ribs)	Nribs	3	
Rib Thickness	Ribtk	14.0000	mm
Web Thickness	Webtk	14.0000	mm
Web Location	Webloc	Center	
Saddle Design Temperature		21.1	°C
Saddle Yield Stress	Sy	213.6	N./mm ²
Height of Web at Center	Hw,c	440.0	mm
Friction Coefficient	mu	0.300	

Moment of Inertia of Saddle - Transverse Direction (90 degrees to long axis)

Inertia of Shell [ShellInertia]:

$$= ((1.56 \cdot \sqrt{(R \cdot t) + \text{WearPlateWidth}})^3) / 12$$

$$= ((1.56 \cdot \sqrt{(97.5 \cdot 10.2) + 335})^3) / 12$$

$$= 3.377 \text{ cm}^4$$

Resolved Inertia for the Shell [I,shell]:

$$= \text{ShellInertia} + A_{\text{shell}} (C1 - Y)^2$$

$$= 3.38 + 39.1 (193 - 5.09)^2$$

$$= 13819.127 \text{ cm}^4$$

	B mm	D mm	Y mm	A cm ²	AY mm ³	I + AD ² (2) cm ⁴
Shell	384.1	10.2	5.1	39.1	19902.4	0.138E+05
Wearplate	335.0	14.0	17.2	46.9	80571.5	0.145E+05
Web	14.0	393.3	220.9	55.1	1216195.6	0.753E+04
BasePlate	300.0	20.0	427.5	60.0	2565148.2	0.330E+05
Totals	...	...	...	201.1	3881817.8	0.689E+05

Distance to Centroid [C1]:

$$= AY / A$$

$$= 3881817 / 201$$

$$= 193.057 \text{ mm}$$

Angle [β]:

$$= 180 - \text{Saddle Angle} / 2$$

$$= 180 - 120 / 2$$

$$= 120.0$$

Saddle Splitting Coefficient [K1]:

$$= (1 + \cos(\beta) - 0.5 \cdot \sin(\beta)^2) / (\pi - \beta + \sin(\beta) \cos(\beta))$$

$$= (1 + \cos(120) - 0.5 \cdot \sin(120)^2) / (\pi - 2.09 + \sin(120) \cos(120))$$

$$= 0.2035$$

Saddle Splitting Force [Fh]:

$$= K1 \cdot Q$$

$$= 0.2 \cdot 10653$$

$$= 2168.0549 \text{ Kgf}$$

$$\text{Tension Stress, St} = (Fh / A_s) = 1.3127 \text{ N./mm}^2$$

$$\text{Allowed Stress, Sa} = 0.6 \cdot \text{Yield Str} = 128.1609 \text{ N./mm}^2$$

Saddle Splitting Dimension [d]:

$$= B - R \cdot \sin(\text{theta} / 2) / (\text{theta} / 2 \text{ in radians})$$

$$= 535 - 97.5 \cdot \sin(120 / 2) / 1.05$$

$$= 454.389 \text{ mm}$$

$$\text{Bending Moment, M} = Fh \cdot d = 985.1588 \text{ Kg-m.}$$



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 102 of 204

Saddle Calcs: Operating Case: Step: 20 9:40am Sep 9,2026

Bending Stress, $S_b = (M * C_1 / I) = 2.7084 \text{ N./mm}^2$
 Allowed Stress, $S_a = 2/3 * \text{Yield Str} = 142.4010 \text{ N./mm}^2$

Minimum Thickness of Baseplate per Moss:

$= \sqrt{ \frac{ 3(Q + \text{SaddleWt}) \text{BasePlateWidth} }{ 4 * \text{BasePlateLength} * \text{AllStress} } })$
 $= \sqrt{ \frac{ 3(10653 + 104)300 }{ 4 * 600 * 142 } })$
 $= 16.668 \text{ mm}$

Calculation of Axial Load, Intermediate Values and Compressive Stress:

Web Length Dimension [Web Length]:
 $= 2 * \cos(90 - \text{Saddle Angle}/2) (\text{Inside Radius} + \text{Shell Thk} + \text{Wear Plate Thk})$
 $= 2 * \cos(90 - 120/2) (94.5 + 13.2 + 14)$
 $= 210.712 \text{ mm}$

Distance between Ribs [e]:
 $= \text{Web Length} / (\text{Nr ribs} - 1)$
 $= 211 / (3 - 1)$
 $= 105.356 \text{ mm}$

Baseplate Pressure Area [Ap]:
 $= e * \text{Bpwid} / 2$
 $= 105 * 300 / 2$
 $= 158.034 \text{ cm}^2$

Bearing Pressure [Bp]:
 $= (Q + \text{SaddleWt}) / (\text{BasePlateLength} * \text{BasePlateWidth})$
 $= 10757 / (600 * 300)$
 $= 5.976 \text{ Kg/cm}^2$

Axial Load [P]:
 $= A_p * B_p$
 $= 158 * 5.98$
 $= 944.441 \text{ Kg}$

Area of the Rib and Web [Ar]:
 $= \text{Rib Area} + \text{Web Area}$
 $= 36.5 + 7.37$
 $= 43.915 \text{ cm}^2$

Compressive Stress [Sc]:
 $= P / A_r$
 $= 944 / 43.9$
 $= 2.109 \text{ N./mm}^2$

Check of Outside Ribs:

Inertia of Saddle, Outer Ribs - Longitudinal Direction

	B	D	Y	A	AY	Io
Rib+Web	14.0	275.0	...	38.5	...	0.243E+04

Rib dimension [D]:
 $= \text{Saddle Width} - \text{Web Thickness}$
 $= 275 - 14$
 $= 261.000 \text{ mm}$

Distance to Centroid from Datum [ytot]:
 $= A_Y / A$
 $= 0 / 43.9$
 $= 0.000 \text{ mm}$

Distance to Centroid [C1]:
 $= \text{Saddle Width} / 2$



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 103 of 204

Saddle Calcs: Operating Case: Step: 20 9:40am Sep 9,2026

$$= 275/2$$

$$= 137.500 \text{ mm}$$

Radius of Gyration [r]:

$$= \sqrt{\text{Total Inertia} / \text{Total Area}}$$

$$= \sqrt{2426/43.9}$$

$$= 74.330 \text{ mm}$$

Length of Outer Rib [L]:

$$= \text{Saddle Height} - \cos(\theta/2) (\text{radius} + \text{shlthk} + \text{wpdthk}) - \text{bpthk}$$

$$= 535 - \cos(120/2) (94.5 + 13.2 + 14) - 20$$

$$= 454.173 \text{ mm}$$

Intermediate Term [Cc]:

$$= \sqrt{2 \cdot \pi^2 \cdot \text{Elastic Modulus} / \text{Yield Stress}}$$

$$= \sqrt{2 \cdot \pi^2 \cdot 199943008/214}$$

$$= 135.934$$

Slenderness ratio [KL/r]:

$$= KL/r$$

$$= 1 \cdot 454/74.3$$

$$= 6.110$$

Bending Moment [Rm]:

$$= FI / (2 \cdot \text{Bplen}) \cdot e \cdot L / 2$$

$$= 300 / (2 \cdot 600) \cdot 105 \cdot 454/2$$

$$= 5.981 \text{ Kg-m.}$$

Compressive Allowable, $KL/r < Cc$ ($6.11 < 136$) per AISC E2-1 [Sca]:

$$= (1 - (KL/r)^2 / (2 \cdot Cc^2)) Fy / (5/3 + 3 \cdot (KL/r) / (8 \cdot Cc) - (KL/r)^3 / (8 \cdot Cc^3))$$

$$= (1 - (6.11)^2 / (2 \cdot 136^2)) 214 / (5/3 + 3 \cdot (6.11) / (8 \cdot 136) - (6.11)^3 / (8 \cdot 136^3))$$

$$= 126.8 \text{ N./mm}^2$$

AISC Unity Check of Outside Ribs (must be ≤ 1)

$$= Sc/Sca + (Rm \cdot C1 / I) / Sba$$

$$= 2.11/127 + (5.98 \cdot 138/24263022) / 142$$

$$= 0.019$$

Check of Inside Ribs:

Inertia of Saddle, Inner Ribs - Axial Direction

	B	D	Y	A	AY	Io
Rib	14.0	261.0	0.0	36.5	0.0	0.243E+04
Web	105.4	14.0	0.0	14.7	0.0	2.41
Totals	...	...	...	51.3	...	0.243E+04

Distance to Centroid from Datum [ytot]:

$$= AY / A$$

$$= 0/51.3$$

$$= 0.000 \text{ mm}$$

Distance to Centroid [C1]:

$$= \text{Saddle Width} / 2$$

$$= 275/2$$

$$= 137.500 \text{ mm}$$

Length of Inner Rib [L]:

$$= \text{Saddle Height} - \text{Outside Radius} - \text{Bpthk}$$

$$= 535 - \cos(122/2) (20 + 0 + 0) - 0$$

$$= 393.345 \text{ mm}$$

Radius of Gyration [r]:

$$= \sqrt{\text{Total Inertia} / \text{Total Area}}$$



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)

Page 104 of 204

Saddle Calcs: Operating Case: Step: 20 9:40am Sep 9, 2026

$$= \sqrt{(2428/51.3)}$$

$$= 68.809 \text{ mm}$$

Slenderness ratio [KL/r]:

$$= KL/r$$

$$= 1 \cdot 393/68.8$$

$$= 5.717$$

Unit Force [Force,u]:

$$= FI / (2 \cdot \text{Baseplate Length})$$

$$= 300 / (2 \cdot 600)$$

$$= 0.250 \text{ Kg/mm}$$

Moment at base of inner Rib [Mbase,c]:

$$= \text{Unit Force} \cdot e \cdot L$$

$$= 0.25 \cdot 105 \cdot 393$$

$$= 10.361 \text{ Kg-m.}$$

Bending Stress due to Transverse Force and Weight Load [σ_B ,base,c]:

$$= \text{Bending Moment} / \text{Section Modulus}$$

$$= 10.4/176610$$

$$= 0.575 \text{ N./mm}^2$$

Compressive Allowable, $KL/r < C_c$ ($5.72 < 136$) per AISC E2-1 [Sca]:

$$= (1 - (KL/r)^2 / (2 \cdot C_c^2)) F_y / (5/3 + 3 \cdot (KL/r) / (8 \cdot C_c) - (KL/r)^3 / (8 \cdot C_c^3))$$

$$= (1 - (5.72)^2 / (2 \cdot 136^2)) 214 /$$

$$(5/3 + 3 \cdot (5.72) / (8 \cdot 136) - (5.72)^3 / (8 \cdot 136^3))$$

$$= 126.8 \text{ N./mm}^2$$

AISC Unity Check of Inside Ribs (must be ≤ 1)

$$= S_c / S_{ca} + (M_{base,c} \cdot C1/I) / S_{ba}$$

$$= 3.62/127 + (10.4 \cdot 138/2428) / 142$$

$$= 0.033$$

Input Data for Base Plate Bolting Calculations:

Total Number of Bolts per BasePlate	Nbolts	4
Total Number of Bolts in Tension/Baseplate	Nbt	2
Bolt Design Temperature		21.1 °C
Bolt Material Specification		SA-307 A
Bolt Allowable Stress	Stba	138.00 N./mm ²
Bolt Corrosion Allowance	Bca	1.5 mm
Distance from Bolts to Edge	Edgedis	50.8 mm
User Defined Area in a Single Bolt	UserBoltArea	1.5500 cm ²
BasePlate Allowable Stress	S	137.60 N./mm ²
Area Available in a Single Bolt	BltArea	0.9592 cm ²
Saddle Load Q0 (Weight)	Q0	1968.4 Kg
Saddle Load QL (Wind/Seismic contribution)	QL	46.5 Kg
Maximum Transverse Force	Ft	1153.8 Kg
Maximum Longitudinal Force	F1	300.0 Kg
Saddle Bolted to Steel Foundation		No

Shear Stress in a Single Bolt, Longitudinal Direction [τ_b ,l]:

$$= FI / (\text{Bolt Area} \cdot \text{Number of Bolts})$$

$$= 300 / (0.96 \cdot 4)$$

$$= 7.7 \text{ N./mm}^2. \text{ Must be less than } 82.8 \text{ N./mm}^2.$$

Shear Stress in a Single Bolt, Transverse Direction [τ_b ,t]:

$$= Ft / (\text{Bolt Area} \cdot \text{Number of Bolts})$$

$$= 1154 / (0.96 \cdot 4)$$

$$= 29.5 \text{ N./mm}^2. \text{ Must be less than } 82.8 \text{ N./mm}^2.$$

Bolt Area Calculation per Dennis R. Moss

Bolt Area Requirement Due to Longitudinal Load [Bltarearl]:



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 105 of 204

Saddle Calcs: Operating Case: Step: 20 9:40am Sep 9, 2026

= 0.0 (QO > QL --> No Uplift in Longitudinal direction)

Bolt Area due to Shear Load [Bltarears]:

= $F_l / (\text{BoltShearAllowable} \cdot N_{\text{bolts}})$

= $300 / (82.8 \cdot 4)$

= 0.0888 cm²

Bolt Area due to Transverse Load:

Moment on Baseplate Due to Transverse Load [Rmom]:

= $B \cdot F_t + \text{Sum of X Moments}$

= $535 \cdot 1154 + 0$

= 617.31 Kg-m.

Eccentricity (e):

= R_{mom} / QO

= 617/1968

= 313.61 mm > Bplen/6 --> Uplift in Transverse direction

f = Bplen / 2 - Edgedis

= $600/2 - 50.8$

= 249.20 mm

Modular Ratio Of Steel/Concrete (n1):

= E_S / E_C

= $203402/21526$

= 9.45

K1 = 3 (e - 0.5 • Bplen)

= $3 (314 - 0.5 \cdot 600)$

= 40.84 mm

K2 = $6 \cdot n1 \cdot A_t / B_{\text{pwid}} \cdot (f + e)$

= $6 \cdot 9.45 \cdot 1.92/300 \cdot (249 + 314)$

= 20403.49 mm²

K3 = -K2 • (0.5 • Bplen + f)

= $-20403 \cdot (0.5 \cdot 600 + 249)$

= -11205597.22 mm³

Iteratively Solving for the Effective Bearing Length:

$Y^3 + K1 \cdot Y^2 + K2 \cdot Y + K3 = 0$

$Y^3 + 40.8 \cdot Y^2 + 20403 \cdot Y - 11205597 = 0$

Y = 182.82 mm

Num = (Bplen / 2 - Y / 3 - e)

= $(600/2 - 183/3 - 314)$

= -74.55

Denom = (Bplen / 2 - Y / 3 + f)

= $(600/2 - 183/3 + 249)$

= 488.26

Total Bolt Tension Force [Tforce]:

= $-QO \cdot \text{Num} / \text{Denom}$

= $-1968 \cdot -74.6/488$

= 300.55 Kg

Bolt Area Required due to Transverse Load [Bltareart]:

= $T_{\text{force}} / (Stba \cdot N_{\text{bt}})$

= $301 / (138 \cdot 2)$

= 0.1068 cm²

Required Area of a Single Bolt [Bltarear]:

= max[Bltarearl, Bltarears, Bltareart]



PV Elite 28 Licensee: SL User
 FileName : 161-C1-C2 _(Stack) Page 106 of 204
 Saddle Calcs: Operating Case: Step: 20 9:40am Sep 9, 2026

= max[0, 0.089, 0.11]
 = 0.1068 cm²

Baseplate Thickness Calculation per D. Moss:

Bearing Pressure (fc)
 = 2(QO + Tforce) / (Y • Bpwid)
 = 2(1968 + 301)/(183 • 300)
 = 811.34 KPa.

Distance from Baseplate Edge to the Web [ADIST]:
 = (Bplen - WebIngh) / 2
 = (600 - 549)/2
 = 25.4000 mm

Overturning Moment due To Bolt Tension [Mt]:
 = Tforce • Adist
 = 301 • 25.4
 = 7.63 Kg-m.

Equivalent Bearing Pressure (f1):
 = fc • (Y - Adist) / Y
 = 811 • (183 - 25.4)/183
 = 698.62 KPa.

Overturning Moment due to Bearing Pressure [Mc]:
 = (Adist² • Bpwid / 6) • (f1 + 2 • fc)
 = (25.4² • 300/6) • (699 + 2 • 811)
 = 7.64 Kg-m.

Baseplate Required Thickness [Treq]:

$$= \sqrt{(6 \cdot \max(Mt, Mc) / (Bpwid \cdot Sba))}$$

$$= \sqrt{(6 \cdot \max(7.63, 7.64) / (300 \cdot 206))}$$

 = 2.6938 mm

MDMT Calculations for: LH floating sad, Saddle to Wearplate Junction, Curve: B

Govrn. thk, tg = 13.2, tr = 4.24, c = 3 mm, E* = 1
 Thickness Ratio = tr • E*/(tg - c) = 0.42, Temp. Reduction = 47 °C

Min Metal Temp. w/o impact per UCS-66, Curve B	-20 °C
Min Metal Temp. at Required thickness (UCS 66.1)	-48 °C
Min Metal Temp. w/o impact per UG-20(f)	-29 °C

ASME VIII Division 2 Horizontal Vessel Analysis, Right Saddle:

Input and Calculated Values:

Vessel Mean Radius	Rm	102.57	mm
Shell Thickness used in this Case	t	13.179	mm
Stiffened Vessel Length per 4.15.6	L	5785.00	mm
Distance from Saddle to Vessel tangent	a1 or a	1200.00	mm
Saddle Width	b1 or b	275.00	mm
Saddle Bearing Angle	delta or theta	120.00	degrees
Wear Plate Width	b2 or b1	335.00	mm
Wear Plate Bearing Angle	delta2 or theta1	132.00	degrees
Wear Plate Thickness	e2 or tr	14.0	mm
Wear Plate Allowable Stress	fw or Sr	118.00	N./mm ²
Shell Allowable Stress used in Calculation		118.00	N./mm ²
Head Allowable Stress used in Calculation		134.60	N./mm ²



PV Elite 28 Licensee: SL User
 FileName : 161-C1-C2 _(Stack) Page 107 of 204
 Saddle Calcs: Operating Case: Step: 20 9:40am Sep 9,2026

Circumferential Efficiency in Plane of Saddle		1.00
Circumferential Efficiency at Mid-Span		1.00
Distance from Saddle Base to Centerline	B	535.00 mm
Coefficient of Friction	mu	0.00

Results for Horizontal Vessel Analysis:

Saddle Force Q, Operating Case		4619.12 Kgf
Pressure used in Analysis	P	2400.887 KPa.

Horizontal Vessel Analysis Results:	Actual N./mm ²	Allowable N./mm ²
Long. Stress at Top of Midspan	-21.18	-176.76
Long. Stress at Top of Midspan	21.18	118.00
Long. Stress at Bottom of Midspan	45.38	118.00
Long. Stress at Top of Saddles	45.49	118.00
Long. Stress at Bottom of Saddles	-21.30	-176.76
Long. Stress at Bottom of Saddles	21.30	118.00
Tangential Shear in Shell	8.08	94.40
Circ. Compressive Stress in Shell	3.00	118.00
Stiffener Circ. Stress at Shell	16.53	147.50
Stiffener Circ. Stress at Tip	69.56	172.00

Intermediate Results: Saddle Reaction Q due to Wind or Seismic:

Transverse Saddle Reaction Force [Fwt]:
 $= Ftr(Ft/Num \text{ of Saddles} + Z \text{ Force Load}) \cdot B / E$
 $= 3 (167/2 + 258) \cdot 535/211$
 $= 2599.8 \text{ Kgf}$

Longitudinal Saddle Reaction Force [Fwl]:
 $= \max(Fl,wind; \text{Sum of X Forces}) \cdot B / Ls$
 $= \max(16.8, 300) \cdot 535/3450$
 $= 7.8 \text{ Kgf}$

Saddle Reaction Force due to Earthquake Fl [Fsl]:
 $= \max(Fl,eq; \text{Sum of X Forces}) \cdot B / Ls$
 $= \max(212, 300) \cdot 535/3450$
 $= 46.5 \text{ Kgf}$

Saddle Reaction Force due to Earthquake Ft [Fst]:
 $= Ftr(Ft/Num \text{ of Saddles} + Z \text{ Force Load}) \cdot B / E$
 $= 3 (212/2 + 258) \cdot 535/211$
 $= 2771.3 \text{ Kgf}$

Load Combination Results for Q + Wind or Seismic [Q]:
 $= \text{Saddle Load} + \max(Fwl, Fwt, Fsl, Fst)$
 $= 1848 + \max(7.75, 2600, 46.5, 2771)$
 $= 4619.1 \text{ Kgf}$

Longitudinal Wind Force [Fl]:
 $= WindScalar \cdot WindPress(Platform \text{ Area} + (\pi/4(OD \cdot WindDiaMult)^2))$
 $= 1.1 \cdot 766 (0 + \pi/4(0.42 \cdot 1.2)^2)$
 $= 164.386 \text{ N}$

Summary of Loads at the Base of this Saddle:

Vertical Load (including saddle weight)	4723.55 Kgf
Transverse Shear Load	363.83 Kgf
Longitudinal Shear Load	300.00 Kgf

Note: Wear Plate is Welded to the Shell, k = 0.1



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 108 of 204

Saddle Calcs: Operating Case: Step: 20 9:40am Sep 9, 2026

Saddle Dimension [E]:

$$= \min(2(\text{ShellID}/2 + t + \text{WearPadThickness}) \sin(\theta/2), 2 \cdot R_m)$$

$$= \min(2(189/2 + 13.2 + 14) \sin(120/2), 2 \cdot 103)$$

$$= 210.712 \text{ mm}$$

The Computed K values from Table 4.15.1:

K1 = 0.1066	K2 = 1.1707	K3 = 0.8799	K4 = 0.4011
K5 = 0.7603	K6 = 0.0529	K7 = 0.0529	K8 = 0.3405
K9 = 0.2711	K10 = 0.0581	K1* = 0.1923	K6p = 0.0434
K7p = 0.0434			

The suffix 'p' denotes the values for a wear plate if it exists.

Note: Dimension a is greater than or equal to $R_m/2$.

Moment per Equation 4.15.1 [M1]:

$$= -Q \cdot a [1 - (1 - a/L + (R_m^2 - h_m^2)/(2a \cdot L)) / (1 + (4h_m)/3L)]$$

$$= -4619 \cdot 1200 [1 - (1 - 1200/5785 + (103^2 - 0^2)/(2 \cdot 1200 \cdot 5785)) / (1 + (4 \cdot 0)/(3 \cdot 5785))]$$

$$= -1145.6 \text{ Kg-m.}$$

Moment per Equation 4.15.2 [M2]:

$$= Q \cdot L/4 ((1 + 2(R_m^2 - h_m^2)/(L^2)) / (1 + (4h_m^2)/(3L)) - 4a/L)$$

$$= 4619 \cdot 5785/4 ((1 + 2(103^2 - 0^2)/(5785^2)) / (1 + (4 \cdot 0)/(3 \cdot 5785)) - 4 \cdot 1200/5785)$$

$$= 1141.7 \text{ Kg-m.}$$

Longitudinal Stress at Top of Shell (4.15.4) [σ_1]:

$$= P \cdot R_m/(2t) - M2/(\pi \cdot R_m^2 t)$$

$$= 2401 \cdot 103/(2 \cdot 10.2) - 1142/(\pi \cdot 103^2 \cdot 10.2)$$

$$= -21.18 \text{ N./mm}^2$$

Longitudinal Stress at Bottom of Shell (4.15.5) [σ_2]:

$$= P \cdot R_m/(2t) + M2/(\pi \cdot R_m^2 \cdot t)$$

$$= 2401 \cdot 103/(2 \cdot 10.2) + 1142/(\pi \cdot 103^2 \cdot 10.2)$$

$$= 45.38 \text{ N./mm}^2$$

Longitudinal Stress at Top of Shell at Support (4.15.6) [σ_3]:

$$= P \cdot R_m/(2t) - M1/(\pi \cdot R_m^2 \cdot t)$$

$$= 2401 \cdot 103/(2 \cdot 10.2) - 1146/(\pi \cdot 103^2 \cdot 10.2)$$

$$= 45.49 \text{ N./mm}^2$$

Longitudinal Stress at bottom of Shell at Support (4.15.7) [σ_4]:

$$= P \cdot R_m/(2t) + M1/(\pi \cdot R_m^2 t)$$

$$= 2401 \cdot 103/(2 \cdot 10.2) + 1146/(\pi \cdot 103^2 \cdot 10.2)$$

$$= -21.30 \text{ N./mm}^2$$

Maximum Shear Force in the Saddle (4.15.3) [T]:

$$= Q(L - 2a)/(L + (4 \cdot h_m/3))$$

$$= 4619 (5785 - 2 \cdot 1200)/(5785 + (4 \cdot 0/3))$$

$$= 2702.8 \text{ Kgf}$$

Shear Stress in the shell with a single ring (4.15.13) [τ_1]:

$$= T / (\pi \cdot R_m \cdot t)$$

$$= 2703/(\pi \cdot 103 \cdot 10.2)$$

$$= 8.08 \text{ N./mm}^2$$

Decay Length (4.15.20) [x1,x2]:

$$= 0.78 \cdot \sqrt{(R_m \cdot t)}$$

$$= 0.78 \cdot \sqrt{(103 \cdot 10.2)}$$

$$= 25.203 \text{ mm}$$

Circ. Stress in shell w/ring in Plane of Saddle (4.15.32) [σ_6]:

$$= -K5 \cdot Q \cdot k/A$$



PV Elite 28 Licensee: SL User
 FileName : 161-C1-C2 _(Stack) Page 109 of 204
 Saddle Calcs: Operating Case: Step: 20 9:40am Sep 9,2026

$$= -0.76 \cdot 4619 \cdot 0.1/11.5$$

$$= -3.00 \text{ N./mm}^2$$

Note: Single Ring in Plane of Saddle Outside the Shell.

Circ. + Bending Stress in shell w/ring in Plane of Saddle (4.15.35) [σ_8^*]:

$$= -K_8 \cdot Q/A + K_6 \cdot Q \cdot R_m \cdot c_1/l$$

$$= -0.34 \cdot 4619/11.5 + 0.053 \cdot 4619 \cdot 103 \cdot 11/9.04$$

$$= 16.53 \text{ N./mm}^2$$

Circ. + Bending Stress in ring w/ring in Plane of Saddle (4.15.36) [σ_9^*]:

$$= -K_8 \cdot Q/A - K_6 \cdot Q \cdot R_m \cdot c_2/l$$

$$= -0.34 \cdot 4619/11.5 - 0.053 \cdot 4619 \cdot 103 \cdot 20.7/9.04$$

$$= -69.56 \text{ N./mm}^2$$

Results for Vessel Ribs, Web and Base:

Baseplate Length	Bplen	600.0000	mm
Baseplate Thickness	Bpthk	20.0000	mm
Baseplate Width	Bpwid	300.0000	mm
Number of Ribs (inc. outside ribs)	Nribs	3	
Rib Thickness	Ribtk	14.0000	mm
Web Thickness	Webtk	14.0000	mm
Web Location	Webloc	Center	
Saddle Design Temperature		21.1	°C
Saddle Yield Stress	Sy	213.6	N./mm ²
Height of Web at Center	Hw,c	440.0	mm
Friction Coefficient	mu	0.000	

Moment of Inertia of Saddle - Transverse Direction (90 degrees to long axis)

Inertia of Shell [ShellInertia]:

$$= ((1.56 \cdot \sqrt{(R \cdot t)} + \text{WearPlateWidth})^3)/12$$

$$= ((1.56 \cdot \sqrt{(97.5 \cdot 10.2)} + 335)^3)/12$$

$$= 3.377 \text{ cm}^4$$

Resolved Inertia for the Shell [I,shell]:

$$= \text{ShellInertia} + A_{\text{Shell}}(C_1 - Y)^2$$

$$= 3.38 + 39.1(193 - 5.09)^2$$

$$= 13819.127 \text{ cm}^4$$

	B mm	D mm	Y mm	A cm ²	AY mm ³	I + AD ⁽²⁾ cm ⁴
Shell	384.1	10.2	5.1	39.1	19902.4	0.138E+05
Wearplate	335.0	14.0	17.2	46.9	80571.5	0.145E+05
Web	14.0	393.3	220.9	55.1	1216195.6	0.753E+04
BasePlate	300.0	20.0	427.5	60.0	2565148.2	0.330E+05
Totals	...	...	...	201.1	3881817.8	0.689E+05

Distance to Centroid [C1]:

$$= AY / A$$

$$= 3881817/201$$

$$= 193.057 \text{ mm}$$

Angle [β]:

$$= 180 - \text{Saddle Angle}/2$$

$$= 180 - 120/2$$

$$= 120.0$$

Saddle Splitting Coefficient [K1]:

$$= (1 + \cos(\beta) - 0.5 \cdot \sin(\beta)^2)/(\pi - \beta + \sin(\beta)\cos(\beta))$$

$$= (1 + \cos(120) - 0.5 \cdot \sin(120)^2)/(\pi - 2.09 + \sin(120)\cos(120))$$

$$= 0.2035$$



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 110 of 204

Saddle Calcs: Operating Case: Step: 20 9:40am Sep 9,2026

Saddle Splitting Force [Fh]:

$$= K1 \cdot Q$$

$$= 0.2 \cdot 4619$$

$$= 940.0922 \text{ Kgf}$$

$$\text{Tension Stress, } St = (Fh/As) = 0.5692 \text{ N./mm}^2$$

$$\text{Allowed Stress, } Sa = 0.6 \cdot \text{Yield Str} = 128.1609 \text{ N./mm}^2$$

Saddle Splitting Dimension [d]:

$$= B - R \cdot \sin(\theta/2) / (\theta/2 \text{ in radians})$$

$$= 535 - 97.5 \cdot \sin(120/2) / 1.05$$

$$= 454.389 \text{ mm}$$

$$\text{Bending Moment, } M = Fh \cdot d = 427.1755 \text{ Kg-m.}$$

$$\text{Bending Stress, } Sb = (M \cdot C1 / I) = 1.1744 \text{ N./mm}^2$$

$$\text{Allowed Stress, } Sa = 2/3 \cdot \text{Yield Str} = 142.4010 \text{ N./mm}^2$$

Minimum Thickness of Baseplate per Moss:

$$= \sqrt{\frac{3(Q + \text{SaddleWt}) \cdot \text{BasePlateWidth}}{4 \cdot \text{BasePlateLength} \cdot \text{AllStress}}}$$

$$= \sqrt{\frac{3(4619 + 104) \cdot 300}{4 \cdot 600 \cdot 142}}$$

$$= 11.045 \text{ mm}$$

Calculation of Axial Load, Intermediate Values and Compressive Stress:

Web Length Dimension [Web Length]:

$$= 2 \cdot \cos(90 - \text{Saddle Angle}/2) \cdot \text{Inside Radius} + \text{Shell Thk} + \text{Wear Plate Thk}$$

$$= 2 \cdot \cos(90 - 120/2) \cdot (94.5 + 13.2 + 14)$$

$$= 210.712 \text{ mm}$$

Distance between Ribs [e]:

$$= \text{Web Length} / (\text{Nr ribs} - 1)$$

$$= 211 / (3 - 1)$$

$$= 105.356 \text{ mm}$$

Baseplate Pressure Area [Ap]:

$$= e \cdot \text{Bpwid} / 2$$

$$= 105 \cdot 300 / 2$$

$$= 158.034 \text{ cm}^2$$

Bearing Pressure [Bp]:

$$= (Q + \text{SaddleWt}) / (\text{BasePlateLength} \cdot \text{BasePlateWidth})$$

$$= 4724 / (600 \cdot 300)$$

$$= 2.624 \text{ Kgf/cm}^2$$

Axial Load [P]:

$$= Ap \cdot Bp$$

$$= 158 \cdot 2.62$$

$$= 414.713 \text{ Kgf}$$

Area of the Rib and Web [Ar]:

$$= \text{Rib Area} + \text{Web Area}$$

$$= 36.5 + 7.37$$

$$= 43.915 \text{ cm}^2$$

Compressive Stress [Sc]:

$$= P / Ar$$

$$= 415 / 43.9$$

$$= 0.926 \text{ N./mm}^2$$

Check of Outside Ribs:

Inertia of Saddle, Outer Ribs - Longitudinal Direction

B	D	Y	A	AY	Io
---	---	---	---	----	----



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 111 of 204

Saddle Calcs: Operating Case: Step: 20 9:40am Sep 9, 2026

Rib+Web	14.0	275.0	...	38.5	...	0.243E+04
---------	------	-------	-----	------	-----	-----------

Rib dimension [D]:

= Saddle Width - Web Thickness

= 275 - 14

= 261.000 mm

Distance to Centroid from Datum [ytot]:

= AY / A

= 0/43.9

= 0.000 mm

Distance to Centroid [C1]:

= Saddle Width / 2

= 275/2

= 137.500 mm

Radius of Gyration [r]:

= $\sqrt{\text{Total Inertia} / \text{Total Area}}$

= $\sqrt{2426/43.9}$

= 74.330 mm

Length of Outer Rib [L]:

= Saddle Height - cos(theta/2)(radius + shlthk + wpdthk) - bpthk

= 535 - cos(120/2)(94.5 + 13.2 + 14) - 20

= 454.173 mm

Intermediate Term [Cc]:

= $\sqrt{2 \cdot \pi^2 \cdot \text{Elastic Modulus} / \text{Yield Stress}}$

= $\sqrt{2 \cdot \pi^2 \cdot 199943008/214}$

= 135.934

Slenderness ratio [KL/r]:

= KL/r

= 1 • 454/74.3

= 6.110

Bending Moment [Rm]:

= FI / (2 • Bplen) • e • L / 2

= 300 / (2 • 600) • 105 • 454/2

= 5.981 Kg-m.

Compressive Allowable, KL/r < Cc (6.11 < 136) per AISC E2-1 [Sca]:

= $(1 - (KL/r)^2 / (2 \cdot Cc^2)) Fy / (5/3 + 3 \cdot (KL/r) / (8 \cdot Cc) - (KL/r)^3 / (8 \cdot Cc^3))$

= $(1 - (6.11)^2 / (2 \cdot 136^2)) 214 /$

$(5/3 + 3 \cdot (6.11) / (8 \cdot 136) - (6.11^3) / (8 \cdot 136^3))$

= 126.8 N./mm²

AISC Unity Check of Outside Ribs (must be ≤ 1)

= Sc/Sca + (Rm • C1 / I) / Sba

= 0.93/127 + (5.98 • 138/24263022) / 142

= 0.010

Check of Inside Ribs:

Inertia of Saddle, Inner Ribs - Axial Direction

	B	D	Y	A	AY	Io
Rib	14.0	261.0	0.0	36.5	0.0	0.243E+04
Web	105.4	14.0	0.0	14.7	0.0	2.41
Totals	...	...	...	51.3	...	0.243E+04

Distance to Centroid from Datum [ytot]:

= AY / A



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 112 of 204

Saddle Calcs: Operating Case: Step: 20 9:40am Sep 9, 2026

= 0/51.3
= 0.000 mm

Distance to Centroid [C1]:

= Saddle Width / 2
= 275/2
= 137.500 mm

Length of Inner Rib [L]:

= Saddle Height - Outside Radius - Bpthk
= 535 - cos(122/2)(20 + 0 + 0) - 0
= 393.345 mm

Radius of Gyration [r]:

= $\sqrt{\text{Total Inertia} / \text{Total Area}}$
= $\sqrt{(2428/51.3)}$
= 68.809 mm

Slenderness ratio [KL/r]:

= KL/r
= 1 • 393/68.8
= 5.717

Unit Force [Force,u]:

= FI / (2 • Baseplate Length)
= 300/(2 • 600)
= 0.250 Kg/mm

Moment at base of inner Rib [Mbase,c]:

= Unit Force • e • L
= 0.25 • 105 • 393
= 10.361 Kg-m.

Bending Stress due to Transverse Force and Weight Load [σ_B ,base,c]:

= Bending Moment / Section Modulus
= 10.4/176610
= 0.575 N./mm²

Compressive Allowable, KL/r < Cc (5.72 < 136) per AISC E2-1 [Sca]:

= $(1 - (KL/r)^2 / (2 \cdot Cc^2)) F_y / (5/3 + 3 \cdot (KL/r) / (8 \cdot Cc) - (KL/r)^3 / (8 \cdot Cc^3))$
= $(1 - (5.72)^2 / (2 \cdot 136^2)) 214 /$
 $(5/3 + 3 \cdot (5.72) / (8 \cdot 136) - (5.72^3) / (8 \cdot 136^3))$
= 126.8 N./mm²

AISC Unity Check of Inside Ribs (must be ≤ 1)

= Sc/Sca + (Mbase,c • C1/I)/Sba
= 1.59/127 + (10.4 • 138/2428)/142
= 0.017

Input Data for Base Plate Bolting Calculations:

Total Number of Bolts per BasePlate	Nbolts	4
Total Number of Bolts in Tension/Baseplate	Nbt	2
Bolt Design Temperature		21.1 °C
Bolt Material Specification		SA-307 A
Bolt Allowable Stress	Stba	138.00 N./mm ²
Bolt Corrosion Allowance	Bca	1.5 mm
Distance from Bolts to Edge	Edgedis	50.8 mm
User Defined Area in a Single Bolt	UserBoltArea	1.5500 cm ²
BasePlate Allowable Stress	S	137.60 N./mm ²
Area Available in a Single Bolt	BltArea	0.9592 cm ²
Saddle Load Q0 (Weight)	Q0	1952.2 Kg
Saddle Load QL (Wind/Seismic contribution)	QL	46.5 Kg
Maximum Transverse Force	Ft	363.8 Kg
Maximum Longitudinal Force	F1	300.0 Kg



PV Elite 28 Licensee: SL User
 FileName : 161-C1-C2 _(Stack) Page 113 of 204
 Saddle Calcs: Operating Case: Step: 20 9:40am Sep 9,2026

Saddle Bolted to Steel Foundation No

Friction force due to thermal growth, [Ff]:
 = 590.5 Kg

Shear Stress in a Single Bolt, Longitudinal Direction [τb,l]:
 = $\max(F_f, F_l) / (\text{Bolt Area} \cdot \text{Number of Bolts})$
 = $591 / (0.96 \cdot 4)$
 = 15.1 N./mm². Must be less than 82.8 N./mm².

Shear Stress in a Single Bolt, Transverse Direction [τb,t]:
 = $F_t / (\text{Bolt Area} \cdot \text{Number of Bolts})$
 = $364 / (0.96 \cdot 4)$
 = 9.3 N./mm². Must be less than 82.8 N./mm².

Bolt Area Calculation per Dennis R. Moss

Bolt Area Requirement Due to Longitudinal Load [Bltarearl]:
 = 0.0 (QO > QL --> No Uplift in Longitudinal direction)

Bolt Area due to Shear Load [Bltarears]:
 = $F_l / (\text{BoltShearAllowable} \cdot \text{Nbols})$
 = $300 / (82.8 \cdot 4)$
 = 0.0888 cm²

Bolt Area due to Transverse Load:

Moment on Baseplate Due to Transverse Load [Rmom]:
 = $B \cdot F_t + \text{Sum of X Moments}$
 = $535 \cdot 364 + 0$
 = 194.65 Kg-m.

Eccentricity (e):
 = R_{mom} / QO
 = 195/1952
 = 99.71 mm < Bplen/6 --> No Uplift in Transverse direction

Bolt Area due to Transverse Load [Bltareart]:
 = 0 (No Uplift)

Required Area of a Single Bolt [Bltarear]:
 = $\max[Bltarearl, Bltarears, Bltareart]$
 = $\max[0, 0.089, 0]$
 = 0.0888 cm²

MDMT Calculations for: RH fixed saddle, Saddle to Wearplate Junction, Curve: B

Govrn. thk, tg = 13.2, tr = 4.24, c = 3 mm, E* = 1
 Thickness Ratio = $tr \cdot E^* / (tg - c) = 0.42$, Temp. Reduction = 47 °C

Min Metal Temp. w/o impact per UCS-66, Curve B	-20 °C
Min Metal Temp. at Required thickness (UCS 66.1)	-48 °C
Min Metal Temp. w/o impact per UG-20(f)	-29 °C

Review notes about nozzle loadings and supports in the Warnings report.

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 114 of 204

Saddle Calcs: Test Case:

Step: 21

9:40am


Sep 9, 2026

ASME VIII Division 2 Horizontal Vessel Analysis, Left Saddle:

Horizontal Vessel Stress Calculations : Test Case

Input and Calculated Values:

Vessel Mean Radius	Rm	102.57	mm
Shell Thickness used in this Case	t	13.179	mm
Stiffened Vessel Length per 4.15.6	L	5785.00	mm
Distance from Saddle to Vessel tangent	a1 or a	1200.00	mm
Saddle Width	b1 or b	275.00	mm
Saddle Bearing Angle	delta or theta	120.00	degrees
Wear Plate Width	b2 or b1	335.00	mm
Wear Plate Bearing Angle	delta2 or theta1	132.00	degrees
Wear Plate Thickness	e2 or tr	14.0	mm
Wear Plate Allowable Stress	fw or Sr	118.00	N./mm ²
Shell Allowable Stress used in Calculation		216.00	N./mm ²
Head Allowable Stress used in Calculation		216.00	N./mm ²
Circumferential Efficiency in Plane of Saddle		1.00	
Circumferential Efficiency at Mid-Span		1.00	
Distance from Saddle Base to Centerline	B	535.00	mm
Coefficient of Friction	mu	0.30	



Results for Horizontal Vessel Analysis:

Saddle Force Q, Test Case, no Ext. Forces		1949.04	Kgf
Pressure used in Analysis	P	3121.005	KPa.

Horizontal Vessel Analysis Results:	Actual N./mm ²	Allowable N./mm ²
Long. Stress at Top of Midspan	1.68	216.00
Long. Stress at Bottom of Midspan	29.77	216.00
Long. Stress at Top of Saddles	29.82	216.00
Long. Stress at Bottom of Saddles	1.63	216.00
Tangential Shear in Shell	3.41	127.92
Circ. Compressive Stress in Shell	1.27	216.00
Stiffener Circ. Stress at Shell	6.98	216.00



PV Elite 28 Licensee: SL User
 FileName : 161-C1-C2 _(Stack)
 Saddle Calcs: Test Case: Step: 21 9:40am Page 115 of 204
 Sep 9, 2026

Stiffener Circ. Stress at Tip	29.35	234.00
-------------------------------	-------	--------

Intermediate Results: Saddle Reaction Q due to Wind or Seismic:

Transverse Saddle Reaction Force [Fwt]:
 $= Ftr(Ft/Num\ of\ Saddles + Z\ Force\ Load) \cdot B / E$
 $= 3 (83.3/2 + 0) \cdot 535/211$
 $= 317.2\ Kg$

Longitudinal Saddle Reaction Force [Fwl]:
 $= \max(Fl,wind; Sum\ of\ X\ Forces) \cdot B / Ls$
 $= \max(8.38, 0) \cdot 535/3450$
 $= 1.3\ Kg$

Load Combination Results for Q + Wind or Seismic [Q]:
 $= Saddle\ Load + \max(Fwl, Fwt, Fsl, Fst)$
 $= 1632 + \max(1.3, 317, 0, 0)$
 $= 1949.0\ Kg$

Longitudinal Wind Force [Fl]:
 $= WindScalar \cdot WindPress(Platform\ Area + (\pi/4(OD \cdot WindDiaMult)^2))$
 $= 1.1 \cdot 766 (0 + \pi/4(0.42 \cdot 1.2)^2)$
 $= 164.386\ N$

Summary of Loads at the Base of this Saddle:

Vertical Load (including saddle weight)	2053.47	Kgf
Transverse Shear Load	41.65	Kgf
Longitudinal Shear Load	8.38	Kgf

Note: Wear Plate is Welded to the Shell, $k = 0.1$

Saddle Dimension [E]:
 $= \min(2(ShellID/2 + t + WearPadThickness)\sin(\theta/2), 2 \cdot Rm)$
 $= \min(2(189/2 + 13.2 + 14)\sin(120/2), 2 \cdot 103)$
 $= 210.712\ mm$

The Computed K values from Table 4.15.1:

K1 = 0.1066	K2 = 1.1707	K3 = 0.8799	K4 = 0.4011
K5 = 0.7603	K6 = 0.0529	K7 = 0.0529	K8 = 0.3405
K9 = 0.2711	K10 = 0.0581	K1* = 0.1923	K6p = 0.0434
K7p = 0.0434			

The suffix 'p' denotes the values for a wear plate if it exists.

Note: Dimension a is greater than or equal to $Rm/2$.

Moment per Equation 4.15.1 [M1]:
 $= -Q \cdot a [1 - (1 - a/L + (Rm^2 - hm^2)/(2a \cdot L)) / (1 + (4hm)/(3L))]$
 $= -1949 \cdot 1200 [1 - (1 - 1200/5785 + (103^2 - 0^2)/(2 \cdot 1200 \cdot 5785)) / (1 + (4 \cdot 0)/(3 \cdot 5785))]$
 $= -483.4\ Kg \cdot m$

Moment per Equation 4.15.2 [M2]:
 $= Q \cdot L / 4 ((1 + 2(Rm^2 - hm^2)/(L^2)) / (1 + (4hm)/(3L)) - 4a/L)$
 $= 1949 \cdot 5785 / 4 ((1 + 2(103^2 - 0^2)/(5785^2)) / (1 + (4 \cdot 0)/(3 \cdot 5785)) - 4 \cdot 1200/5785)$
 $= 481.7\ Kg \cdot m$

Longitudinal Stress at Top of Shell (4.15.4) [σ_1]:
 $= P \cdot Rm / (2t) - M2 / (\pi \cdot Rm^2 t)$
 $= 3121 \cdot 103 / (2 \cdot 10.2) - 482 / (\pi \cdot 103^2 \cdot 10.2)$
 $= 1.68\ N/mm^2$

Longitudinal Stress at Bottom of Shell (4.15.5) [σ_2]:



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 116 of 204

Saddle Calcs: Test Case:

Step: 21

9:40am

Sep 9, 2026

$$\begin{aligned}
 &= P \cdot R_m / (2t) + M2 / (\pi \cdot R_m^2 \cdot t) \\
 &= 3121 \cdot 103 / (2 \cdot 10.2) + 482 / (\pi \cdot 103^2 \cdot 10.2) \\
 &= 29.77 \text{ N./mm}^2
 \end{aligned}$$

Longitudinal Stress at Top of Shell at Support (4.15.6) [σ_3]:

$$\begin{aligned}
 &= P \cdot R_m / (2t) - M1 / (\pi \cdot R_m^2 \cdot t) \\
 &= 3121 \cdot 103 / (2 \cdot 10.2) - 483 / (\pi \cdot 103^2 \cdot 10.2) \\
 &= 29.82 \text{ N./mm}^2
 \end{aligned}$$

Longitudinal Stress at bottom of Shell at Support (4.15.7) [σ_4]:

$$\begin{aligned}
 &= P \cdot R_m / (2t) + M1 / (\pi \cdot R_m^2 \cdot t) \\
 &= 3121 \cdot 103 / (2 \cdot 10.2) + 483 / (\pi \cdot 103^2 \cdot 10.2) \\
 &= 1.63 \text{ N./mm}^2
 \end{aligned}$$

Maximum Shear Force in the Saddle (4.15.3) [T]:

$$\begin{aligned}
 &= Q(L-2a) / (L + (4 \cdot h_m / 3)) \\
 &= 1949 (5785 - 2 \cdot 1200) / (5785 + (4 \cdot 0 / 3)) \\
 &= 1140.5 \text{ Kg}
 \end{aligned}$$

Shear Stress in the shell with a single ring (4.15.13) [τ_1]:

$$\begin{aligned}
 &= T / (\pi \cdot R_m \cdot t) \\
 &= 1140 / (\pi \cdot 103 \cdot 10.2) \\
 &= 3.41 \text{ N./mm}^2
 \end{aligned}$$

Decay Length (4.15.20) [x_1, x_2]:

$$\begin{aligned}
 &= 0.78 \cdot \sqrt{(R_m \cdot t)} \\
 &= 0.78 \cdot \sqrt{(103 \cdot 10.2)} \\
 &= 25.203 \text{ mm}
 \end{aligned}$$

Circ. Stress in shell w/ring in Plane of Saddle (4.15.32) [σ_6^*]:

$$\begin{aligned}
 &= -K5 \cdot Q \cdot k / A \\
 &= -0.76 \cdot 1949 \cdot 0.1 / 11.5 \\
 &= -1.27 \text{ N./mm}^2
 \end{aligned}$$

Note: Single Ring in Plane of Saddle Outside the Shell.

Circ. + Bending Stress in shell w/ring in Plane of Saddle (4.15.35) [σ_8^*]:

$$\begin{aligned}
 &= -K8 \cdot Q / A + K6 \cdot Q \cdot R_m \cdot c1 / I \\
 &= -0.34 \cdot 1949 / 11.5 + 0.053 \cdot 1949 \cdot 103 \cdot 11 / 9.04 \\
 &= 6.98 \text{ N./mm}^2
 \end{aligned}$$

Circ. + Bending Stress in ring w/ring in Plane of Saddle (4.15.36) [σ_9^*]:

$$\begin{aligned}
 &= -K8 \cdot Q / A - K6 \cdot Q \cdot R_m \cdot c2 / I \\
 &= -0.34 \cdot 1949 / 11.5 - 0.053 \cdot 1949 \cdot 103 \cdot 20.7 / 9.04 \\
 &= -29.35 \text{ N./mm}^2
 \end{aligned}$$

Results for Vessel Ribs, Web and Base:

Baseplate Length	Bplen	600.0000	mm
Baseplate Thickness	Bpthk	20.0000	mm
Baseplate Width	Bpwid	300.0000	mm
Number of Ribs (inc. outside ribs)	Nribs	3	
Rib Thickness	Ribtk	14.0000	mm
Web Thickness	Webtk	14.0000	mm
Web Location	Webloc	Center	
Saddle Yield Stress	Sy	260.0	N./mm ²
Height of Web at Center	Hw,c	440.0	mm
Friction Coefficient	mu	0.300	

Moment of Inertia of Saddle - Transverse Direction (90 degrees to long axis)

Inertia of Shell [ShellInertia]:

$$\begin{aligned}
 &= ((1.56 \cdot \sqrt{(R \cdot t)} + \text{WearPlateWidth})^3) / 12 \\
 &= ((1.56 \cdot \sqrt{(97.5 \cdot 10.2)} + 335)^3) / 12 \\
 &= 3.377 \text{ cm}^4
 \end{aligned}$$



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 117 of 204

Saddle Calcs: Test Case:

Step: 21

9:40am

Sep 9, 2026

Resolved Inertia for the Shell [I,shell]:

$$= \text{ShellInertia} + A_{\text{Shell}} (C1 - Y)^2$$

$$= 3.38 + 39.1 (193 - 5.09)^2$$

$$= 13819.127 \text{ cm}^4$$

	B mm	D mm	Y mm	A cm ²	AY mm ³	I + AD ² (2) cm ⁴
Shell	384.1	10.2	5.1	39.1	19902.4	0.138E+05
Wearplate	335.0	14.0	17.2	46.9	80571.5	0.145E+05
Web	14.0	393.3	220.9	55.1	1216195.6	0.753E+04
BasePlate	300.0	20.0	427.5	60.0	2565148.2	0.330E+05
Totals	...	...	...	201.1	3881817.8	0.689E+05

Distance to Centroid [C1]:

$$= AY / A$$

$$= 3881817/201$$

$$= 193.057 \text{ mm}$$

Angle [β]:

$$= 180 - \text{Saddle Angle}/2$$

$$= 180 - 120/2$$

$$= 120.0$$

Saddle Splitting Coefficient [K1]:

$$= (1 + \cos(\beta) - 0.5 \cdot \sin(\beta)^2) / (\pi - \beta + \sin(\beta) \cos(\beta))$$

$$= (1 + \cos(120) - 0.5 \cdot \sin(120)^2) / (\pi - 2.09 + \sin(120) \cos(120))$$

$$= 0.2035$$

Saddle Splitting Force [Fh]:

$$= K1 \cdot Q$$

$$= 0.2 \cdot 1949$$

$$= 396.6722 \text{ Kgf}$$

$$\text{Tension Stress, } St = (Fh / As) = 0.2402 \text{ N./mm}^2$$

$$\text{Allowed Stress, } Sa = 0.6 \cdot \text{Yield Str} = 155.9972 \text{ N./mm}^2$$

Saddle Splitting Dimension [d]:

$$= B - R \cdot \sin(\theta/2) / (\theta/2 \text{ in radians})$$

$$= 535 - 97.5 \cdot \sin(120/2) / 1.05$$

$$= 454.389 \text{ mm}$$

$$\text{Bending Moment, } M = Fh \cdot d = 180.2469 \text{ Kg-m.}$$

$$\text{Bending Stress, } Sb = (M \cdot C1 / I) = 0.4955 \text{ N./mm}^2$$

$$\text{Allowed Stress, } Sa = 2/3 \cdot \text{Yield Str} = 173.3302 \text{ N./mm}^2$$

Minimum Thickness of Baseplate per Moss:

$$= \sqrt{(3(Q + \text{SaddleWt}) \text{BasePlateWidth}) / (4 \cdot \text{BasePlateLength} \cdot \text{AllStress})}$$

$$= \sqrt{(3(1949 + 104)300 / (4 \cdot 600 \cdot 173))}$$

$$= 6.601 \text{ mm}$$

Calculation of Axial Load, Intermediate Values and Compressive Stress:

Web Length Dimension [Web Length]:

$$= 2 \cdot \cos(90 - \text{Saddle Angle}/2) (\text{Inside Radius} + \text{Shell Thk} + \text{Wear Plate Thk})$$

$$= 2 \cdot \cos(90 - 120/2) (94.5 + 13.2 + 14)$$

$$= 210.712 \text{ mm}$$

Distance between Ribs [e]:

$$= \text{Web Length} / (N_{\text{ribs}} - 1)$$

$$= 211 / (3 - 1)$$

$$= 105.356 \text{ mm}$$

Baseplate Pressure Area [Ap]:



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 118 of 204

Saddle Calcs: Test Case:

Step: 21

9:40am

Sep 9, 2026

$$= e \cdot Bpwid / 2$$

$$= 105 \cdot 300 / 2$$

$$= 158.034 \text{ cm}^2$$

Bearing Pressure [Bp]:

$$= (Q + SaddleWt) / (BasePlateLength \cdot BasePlateWidth)$$

$$= 2053 / (600 \cdot 300)$$

$$= 1.141 \text{ Kg/cm}^2$$

Axial Load [P]:

$$= Ap \cdot Bp$$

$$= 158 \cdot 1.14$$

$$= 180.288 \text{ Kg}$$

Area of the Rib and Web [Ar]:

$$= Rib \text{ Area} + Web \text{ Area}$$

$$= 36.5 + 7.37$$

$$= 43.915 \text{ cm}^2$$

Compressive Stress [Sc]:

$$= P / Ar$$

$$= 180 / 43.9$$

$$= 0.403 \text{ N./mm}^2$$

Check of Outside Ribs:

Inertia of Saddle, Outer Ribs - Longitudinal Direction

	B	D	Y	A	AY	Io
Rib+Web	14.0	275.0	...	38.5	...	0.243E+04

Rib dimension [D]:

$$= Saddle \text{ Width} - Web \text{ Thickness}$$

$$= 275 - 14$$

$$= 261.000 \text{ mm}$$

Distance to Centroid from Datum [ytot]:

$$= AY / A$$

$$= 0 / 43.9$$

$$= 0.000 \text{ mm}$$

Distance to Centroid [C1]:

$$= Saddle \text{ Width} / 2$$

$$= 275 / 2$$

$$= 137.500 \text{ mm}$$

Radius of Gyration [r]:

$$= \sqrt{ (Total \text{ Inertia} / Total \text{ Area}) }$$

$$= \sqrt{ (2426 / 43.9) }$$

$$= 74.330 \text{ mm}$$

Length of Outer Rib [L]:

$$= Saddle \text{ Height} - \cos(\theta / 2) (radius + shlthk + wpdthk) - bpthk$$

$$= 535 - \cos(120 / 2) (94.5 + 13.2 + 14) - 20$$

$$= 454.173 \text{ mm}$$

Intermediate Term [Cc]:

$$= \sqrt{ (2 \cdot \pi^2 \cdot Elastic \text{ Modulus} / Yield \text{ Stress}) }$$

$$= \sqrt{ (2 \cdot \pi^2 \cdot 199943008 / 260) }$$

$$= 123.211$$

Slenderness ratio [KL/r]:

$$= KL / r$$

$$= 1 \cdot 454 / 74.3$$



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 119 of 204

Saddle Calcs: Test Case:

Step: 21

9:40am

Sep 9, 2026

= 6.110

Bending Moment [Rm]:

= $Fl / (2 \cdot B_{plen}) \cdot e \cdot L / 2$

= $8.38 / (2 \cdot 600) \cdot 105 \cdot 454 / 2$

= 0.167 Kg-m.

Compressive Allowable, $KL/r < C_c$ ($6.11 < 123$) per AISC E2-1 [Sca]:

= $(1 - (Klr)^2 / (2 \cdot Cc^2)) F_y / (5/3 + 3 \cdot (Klr) / (8 \cdot Cc) - (Klr)^3 / (8 \cdot Cc^3))$

= $(1 - (6.11)^2 / (2 \cdot 123^2)) 260 /$

$(5/3 + 3 \cdot (6.11) / (8 \cdot 123) - (6.11^3) / (8 \cdot 123^3))$

= 154.1 N./mm²

AISC Unity Check of Outside Ribs (must be ≤ 1)

= $Sc/Sca + (Rm \cdot C1 / I) / Sba$

= $0.4/154 + (0.17 \cdot 138/24263022) / 173$

= 0.003

Check of Inside Ribs:

Inertia of Saddle, Inner Ribs - Axial Direction

	B	D	Y	A	AY	Io
Rib	14.0	261.0	0.0	36.5	0.0	0.243E+04
Web	105.4	14.0	0.0	14.7	0.0	2.41
Totals	...	...	...	51.3	...	0.243E+04

Distance to Centroid from Datum [ytot]:

= AY / A

= $0/51.3$

= 0.000 mm

Distance to Centroid [C1]:

= Saddle Width / 2

= $275/2$

= 137.500 mm

Length of Inner Rib [L]:

= Saddle Height - Outside Radius - Bpthk

= $535 - \cos(122/2) (20 + 0 + 0) - 0$

= 393.345 mm

Radius of Gyration [r]:

= $\sqrt{(\text{Total Inertia} / \text{Total Area})}$

= $\sqrt{(2428/51.3)}$

= 68.809 mm

Slenderness ratio [KL/r]:

= KL/r

= $1 \cdot 393/68.8$

= 5.717

Unit Force [Force,u]:

= $Fl / (2 \cdot \text{Baseplate Length})$

= $8.38 / (2 \cdot 600)$

= 0.007 Kg/mm

Moment at base of inner Rib [Mbase,c]:

= Unit Force $\cdot e \cdot L$

= $0.007 \cdot 105 \cdot 393$

= 0.289 Kg-m.

Bending Stress due to Transverse Force and Weight Load [$\sigma_{B,base,c}$]:

= Bending Moment / Section Modulus

= 0.29/176610



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 120 of 204

Saddle Calcs: Test Case:

Step: 21

9:40am

Sep 9, 2026

$$= 0.016 \text{ N./mm}^2$$

Compressive Allowable, $KL/r < C_c$ ($5.72 < 123$) per AISC E2-1 [Sca]:

$$= (1 - (KL/r)^2 / (2 \cdot C_c^2)) F_y / (5/3 + 3 \cdot (KL/r) / (8 \cdot C_c) - (KL/r)^3 / (8 \cdot C_c^3))$$

$$= (1 - (5.72)^2 / (2 \cdot 123^2)) 260 /$$

$$(5/3 + 3 \cdot (5.72) / (8 \cdot 123) - (5.72^3) / (8 \cdot 123^3))$$

$$= 154.2 \text{ N./mm}^2$$

AISC Unity Check of Inside Ribs (must be ≤ 1)

$$= S_c / S_{ca} + (M_{base,c} \cdot C_{1/I}) / S_{ba}$$

$$= 0.69 / 154 + (0.29 \cdot 138 / 2428) / 173$$

$$= 0.005$$

Input Data for Base Plate Bolting Calculations:

Total Number of Bolts per BasePlate	Nbolts	4
Total Number of Bolts in Tension/Baseplate	Nbt	2
Bolt Material Specification		SA-307 A
Bolt Allowable Stress	Stba	48.30 N./mm ²
Bolt Corrosion Allowance	Bca	1.5 mm
Distance from Bolts to Edge	Edgedis	50.8 mm
User Defined Area in a Single Bolt	UserBoltArea	1.5500 cm ²
BasePlate Allowable Stress	S	138.00 N./mm ²
Area Available in a Single Bolt	BltArea	0.9592 cm ²
Saddle Load Q0 (Weight)	Q0	1736.3 Kgf
Saddle Load QL (Wind/Seismic contribution)	QL	1.3 Kgf
Maximum Transverse Force	Ft	41.6 Kgf
Maximum Longitudinal Force	Fl	8.4 Kgf
Saddle Bolted to Steel Foundation		No

Shear Stress in a Single Bolt, Longitudinal Direction [rb,l]:

$$= Fl / (\text{Bolt Area} \cdot \text{Number of Bolts})$$

$$= 8.38 / (0.96 \cdot 4)$$

$$= 0.2 \text{ N./mm}^2. \text{ Must be less than } 29.0 \text{ N./mm}^2.$$

Shear Stress in a Single Bolt, Transverse Direction [rb,t]:

$$= Ft / (\text{Bolt Area} \cdot \text{Number of Bolts})$$

$$= 41.6 / (0.96 \cdot 4)$$

$$= 1.1 \text{ N./mm}^2. \text{ Must be less than } 29.0 \text{ N./mm}^2.$$

Bolt Area Calculation per Dennis R. Moss

Bolt Area Requirement Due to Longitudinal Load [Bltarearl]:

$$= 0.0 \text{ (} Q_0 > Q_L \text{ --> No Uplift in Longitudinal direction)}$$

Bolt Area due to Shear Load [Bltarears]:

$$= Fl / (\text{BoltShearAllowable} \cdot \text{Nbolts})$$

$$= 8.38 / (29 \cdot 4)$$

$$= 0.0071 \text{ cm}^2$$

Bolt Area due to Transverse Load:

Moment on Baseplate Due to Transverse Load [Rmom]:

$$= B \cdot Ft + \text{Sum of X Moments}$$

$$= 535 \cdot 41.6 + 0$$

$$= 22.28 \text{ Kg-m.}$$

Eccentricity (e):

$$= R_{mom} / Q_0$$

$$= 22.3 / 1736$$

$$= 12.83 \text{ mm} < B_{plen} / 6 \text{ --> No Uplift in Transverse direction}$$

Bolt Area due to Transverse Load [Bltareart]:

$$= 0 \text{ (No Uplift)}$$



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 121 of 204

Saddle Calcs: Test Case:

Step: 21

9:40am

Sep 9, 2026

Required Area of a Single Bolt [Bltarear]:

= max[Bltarearl, Bltarears, Bltareart]

= max[0, 0.0071, 0]

= 0.0071 cm²

ASME VIII Division 2 Horizontal Vessel Analysis, Right Saddle:

Input and Calculated Values:

Vessel Mean Radius	Rm	102.57	mm
Shell Thickness used in this Case	t	13.179	mm
Stiffened Vessel Length per 4.15.6	L	5785.00	mm
Distance from Saddle to Vessel tangent	a1 or a	1200.00	mm
Saddle Width	b1 or b	275.00	mm
Saddle Bearing Angle	delta or theta	120.00	degrees
Wear Plate Width	b2 or b1	335.00	mm
Wear Plate Bearing Angle	delta2 or theta1	132.00	degrees
Wear Plate Thickness	e2 or tr	14.0	mm
Wear Plate Allowable Stress	fw or Sr	118.00	N./mm ²
Shell Allowable Stress used in Calculation		216.00	N./mm ²
Head Allowable Stress used in Calculation		216.00	N./mm ²
Circumferential Efficiency in Plane of Saddle		1.00	
Circumferential Efficiency at Mid-Span		1.00	
Distance from Saddle Base to Centerline	B	535.00	mm
Coefficient of Friction	mu	0.00	

Results for Horizontal Vessel Analysis:

Saddle Force Q, Test Case, no Ext. Forces		1939.48	Kgf
Pressure used in Analysis	P	3121.005	KPa.

Horizontal Vessel Analysis Results:	Actual N./mm ²	Allowable N./mm ²
Long. Stress at Top of Midspan	1.75	216.00
Long. Stress at Bottom of Midspan	29.70	216.00
Long. Stress at Top of Saddles	29.75	216.00
Long. Stress at Bottom of Saddles	1.70	216.00
Tangential Shear in Shell	3.39	127.92
Circ. Compressive Stress in Shell	1.26	216.00
Stiffener Circ. Stress at Shell	6.94	216.00
Stiffener Circ. Stress at Tip	29.21	234.00

Intermediate Results: Saddle Reaction Q due to Wind or Seismic:

Transverse Saddle Reaction Force [Fwt]:

= Ftr(Ft/Num of Saddles + Z Force Load) • B / E

= 3 (83.3/2 + 0) • 535/211

= 317.2 Kgf

Longitudinal Saddle Reaction Force [Fwl]:

= max(Fl,wind; Sum of X Forces) • B / Ls

= max(8.38, 0) • 535/3450

= 1.3 Kgf

Load Combination Results for Q + Wind or Seismic [Q]:

= Saddle Load + max(Fwl, Fwt, Fsl, Fst)

= 1622 + max(1.3, 317, 0, 0)



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 122 of 204

Saddle Calcs: Test Case:

Step: 21

9:40am

Sep 9, 2026

= 1939.5 Kgf

Longitudinal Wind Force [FI]:

= WindScalar • WindPress (Platform Area + ($\pi/4$ (OD • WindDiaMult)²))

= 1.1 • 766 (0 + $\pi/4$ (0.42 • 1.2)²)

= 164.386 N

Summary of Loads at the Base of this Saddle:

Vertical Load (including saddle weight) 2043.91 Kgf

Transverse Shear Load 41.65 Kgf

Longitudinal Shear Load 8.38 Kgf

Note: Wear Plate is Welded to the Shell, k = 0.1

Saddle Dimension [E]:

= min(2(ShellID/2 + t + WearPadThickness)sin($\theta/2$), 2•Rm)

= min(2(189/2 + 13.2 + 14)sin(120/2), 2•103)

= 210.712 mm

The Computed K values from Table 4.15.1:

K1 = 0.1066 K2 = 1.1707 K3 = 0.8799 K4 = 0.4011

K5 = 0.7603 K6 = 0.0529 K7 = 0.0529 K8 = 0.3405

K9 = 0.2711 K10 = 0.0581 K1* = 0.1923 K6p = 0.0434

K7p = 0.0434

The suffix 'p' denotes the values for a wear plate if it exists.

Note: Dimension a is greater than or equal to Rm/2.

Moment per Equation 4.15.1 [M1]:

= -Q•a [1 - (1 - a/L + (Rm²-hm²)/(2a•L))/(1+(4hm)/3L)]

= -1939•1200[1-(1-1200/5785+(103²-0²)/

(2•1200•5785))/(1+(4•0)/(3•5785))]

= -481.0 Kg-m.

Moment per Equation 4.15.2 [M2]:

= Q•L/4((1+2(Rm²-hm²)/(L²))/(1+(4hm²)/(3L))-4a/L)

= 1939•5785/4((1+2(103²-0²)/(5785²))/(1+(4•0)/

(3•5785))-4•1200/5785)

= 479.4 Kg-m.

Longitudinal Stress at Top of Shell (4.15.4) [σ_1]:

= P • Rm/(2t) - M2/(π •Rm²t)

= 3121 • 103/(2•10.2) - 479/(π •103²•10.2)

= 1.75 N./mm²

Longitudinal Stress at Bottom of Shell (4.15.5) [σ_2]:

= P • Rm/(2t) + M2/(π • Rm² • t)

= 3121 • 103/(2 • 10.2) + 479/(π • 103² • 10.2)

= 29.70 N./mm²

Longitudinal Stress at Top of Shell at Support (4.15.6) [σ_3]:

= P • Rm/(2t) - M1/(π • Rm² • t)

= 3121 • 103/(2 • 10.2) - -481/(π • 103² • 10.2)

= 29.75 N./mm²

Longitudinal Stress at bottom of Shell at Support (4.15.7) [σ_4]:

= P • Rm/(2t) + M1/(π •Rm²t)

= 3121 • 103/(2•10.2) + -481/(π •103²•10.2)

= 1.70 N./mm²

Maximum Shear Force in the Saddle (4.15.3) [T]:

= Q(L-2a)/(L+(4•hm/3))

= 1939 (5785 - 2 • 1200)/(5785 + (4 • 0/3))

= 1134.9 Kgf



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 123 of 204

Saddle Calcs: Test Case:

Step: 21

9:40am

Sep 9, 2026

Shear Stress in the shell with a single ring (4.15.13) $[\tau_1]$:

$$= T / (\pi \cdot R_m \cdot t)$$

$$= 1135 / (\pi \cdot 103 \cdot 10.2)$$

$$= 3.39 \text{ N./mm}^2$$

Decay Length (4.15.20) $[x_1, x_2]$:

$$= 0.78 \cdot \sqrt{(R_m \cdot t)}$$

$$= 0.78 \cdot \sqrt{(103 \cdot 10.2)}$$

$$= 25.203 \text{ mm}$$

Circ. Stress in shell w/ring in Plane of Saddle (4.15.32) $[\sigma_6^*]$:

$$= -K_5 \cdot Q \cdot k/A$$

$$= -0.76 \cdot 1939 \cdot 0.1/11.5$$

$$= -1.26 \text{ N./mm}^2$$

Note: Single Ring in Plane of Saddle Outside the Shell.

Circ. + Bending Stress in shell w/ring in Plane of Saddle (4.15.35) $[\sigma_8^*]$:

$$= -K_8 \cdot Q/A + K_6 \cdot Q \cdot R_m \cdot c_1/I$$

$$= -0.34 \cdot 1939/11.5 + 0.053 \cdot 1939 \cdot 103 \cdot 11/9.04$$

$$= 6.94 \text{ N./mm}^2$$

Circ. + Bending Stress in ring w/ring in Plane of Saddle (4.15.36) $[\sigma_9^*]$:

$$= -K_8 \cdot Q/A - K_6 \cdot Q \cdot R_m \cdot c_2/I$$

$$= -0.34 \cdot 1939/11.5 - 0.053 \cdot 1939 \cdot 103 \cdot 20.7/9.04$$

$$= -29.21 \text{ N./mm}^2$$

Results for Vessel Ribs, Web and Base:

Baseplate Length	Bplen	600.0000	mm
Baseplate Thickness	Bpthk	20.0000	mm
Baseplate Width	Bpwid	300.0000	mm
Number of Ribs (inc. outside ribs)	Nribs	3	
Rib Thickness	Ribtk	14.0000	mm
Web Thickness	Webtk	14.0000	mm
Web Location	Webloc	Center	
Saddle Yield Stress	Sy	260.0	N./mm ²
Height of Web at Center	Hw,c	440.0	mm
Friction Coefficient	mu	0.000	

Moment of Inertia of Saddle - Transverse Direction (90 degrees to long axis)

Inertia of Shell $[ShellInertia]$:

$$= ((1.56 \cdot \sqrt{(R \cdot t)} + WearPlateWidth)^3)/12$$

$$= ((1.56 \cdot \sqrt{(97.5 \cdot 10.2)} + 335)^3)/12$$

$$= 3.377 \text{ cm}^4$$

Resolved Inertia for the Shell $[I, shell]$:

$$= ShellInertia + A_{Shell} (C_1 - Y)^2$$

$$= 3.38 + 39.1 (193 - 5.09)^2$$

$$= 13819.127 \text{ cm}^4$$

	B mm	D mm	Y mm	A cm ²	AY mm ³	I + AD ² cm ⁴
Shell	384.1	10.2	5.1	39.1	19902.4	0.138E+05
Wearplate	335.0	14.0	17.2	46.9	80571.5	0.145E+05
Web	14.0	393.3	220.9	55.1	1216195.6	0.753E+04
BasePlate	300.0	20.0	427.5	60.0	2565148.2	0.330E+05
Totals	...	...	...	201.1	3881817.8	0.689E+05

Distance to Centroid $[C_1]$:

$$= AY / A$$

$$= 3881817/201$$



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 124 of 204

Saddle Calcs: Test Case:

Step: 21

9:40am

Sep 9, 2026

$$= 193.057 \text{ mm}$$

Angle [β]:

$$= 180 - \text{Saddle Angle}/2$$

$$= 180 - 120/2$$

$$= 120.0$$

Saddle Splitting Coefficient [K1]:

$$= (1 + \cos(\beta) - 0.5 \cdot \sin(\beta)^2) / (\pi - \beta + \sin(\beta) \cos(\beta))$$

$$= (1 + \cos(120) - 0.5 \cdot \sin(120)^2) / (\pi - 2.09 + \sin(120) \cos(120))$$

$$= 0.2035$$

Saddle Splitting Force [Fh]:

$$= K1 \cdot Q$$

$$= 0.2 \cdot 1939$$

$$= 394.7271 \text{ Kg}$$

$$\text{Tension Stress, } St = (Fh / As) = 0.2390 \text{ N./mm}^2$$

$$\text{Allowed Stress, } Sa = 0.6 \cdot \text{Yield Str} = 155.9972 \text{ N./mm}^2$$

Saddle Splitting Dimension [d]:

$$= B - R \cdot \sin(\theta/2) / (\theta/2 \text{ in radians})$$

$$= 535 - 97.5 \cdot \sin(120/2) / 1.05$$

$$= 454.389 \text{ mm}$$

$$\text{Bending Moment, } M = Fh \cdot d = 179.3630 \text{ Kg-m.}$$

$$\text{Bending Stress, } Sb = (M \cdot C1 / I) = 0.4931 \text{ N./mm}^2$$

$$\text{Allowed Stress, } Sa = 2/3 \cdot \text{Yield Str} = 173.3302 \text{ N./mm}^2$$

Minimum Thickness of Baseplate per Moss:

$$= \sqrt{(3(Q + \text{SaddleWt}) \cdot \text{BasePlateWidth}) / (4 \cdot \text{BasePlateLength} \cdot \text{AllStress})}$$

$$= \sqrt{(3(1939 + 104) \cdot 300) / (4 \cdot 600 \cdot 173)}$$

$$= 6.585 \text{ mm}$$

Calculation of Axial Load, Intermediate Values and Compressive Stress:

Web Length Dimension [Web Length]:

$$= 2 \cdot \cos(90 - \text{Saddle Angle}/2) (\text{Inside Radius} + \text{Shell Thk} + \text{Wear Plate Thk})$$

$$= 2 \cdot \cos(90 - 120/2) (94.5 + 13.2 + 14)$$

$$= 210.712 \text{ mm}$$

Distance between Ribs [e]:

$$= \text{Web Length} / (\text{Nr ribs} - 1)$$

$$= 211 / (3 - 1)$$

$$= 105.356 \text{ mm}$$

Baseplate Pressure Area [Ap]:

$$= e \cdot \text{Bpwid} / 2$$

$$= 105 \cdot 300 / 2$$

$$= 158.034 \text{ cm}^2$$

Bearing Pressure [Bp]:

$$= (Q + \text{SaddleWt}) / (\text{BasePlateLength} \cdot \text{BasePlateWidth})$$

$$= 2044 / (600 \cdot 300)$$

$$= 1.136 \text{ Kg/cm}^2$$

Axial Load [P]:

$$= Ap \cdot Bp$$

$$= 158 \cdot 1.14$$

$$= 179.449 \text{ Kg}$$

Area of the Rib and Web [Ar]:

$$= \text{Rib Area} + \text{Web Area}$$

$$= 36.5 + 7.37$$



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 125 of 204

Saddle Calcs: Test Case:

Step: 21

9:40am

Sep 9, 2026

$$= 43.915 \text{ cm}^2$$

Compressive Stress [Sc]:

$$= P/A_r$$

$$= 179/43.9$$

$$= 0.401 \text{ N./mm}^2$$

Check of Outside Ribs:

Inertia of Saddle, Outer Ribs - Longitudinal Direction

	B	D	Y	A	AY	Io
Rib+Web	14.0	275.0	...	38.5	...	0.243E+04

Rib dimension [D]:

$$= \text{Saddle Width} - \text{Web Thickness}$$

$$= 275 - 14$$

$$= 261.000 \text{ mm}$$

Distance to Centroid from Datum [ytot]:

$$= AY / A$$

$$= 0/43.9$$

$$= 0.000 \text{ mm}$$

Distance to Centroid [C1]:

$$= \text{Saddle Width} / 2$$

$$= 275/2$$

$$= 137.500 \text{ mm}$$

Radius of Gyration [r]:

$$= \sqrt{(\text{Total Inertia} / \text{Total Area})}$$

$$= \sqrt{(2426/43.9)}$$

$$= 74.330 \text{ mm}$$

Length of Outer Rib [L]:

$$= \text{Saddle Height} - \cos(\theta/2) (\text{radius} + \text{shlthk} + \text{wpdthk}) - \text{bpthk}$$

$$= 535 - \cos(120/2) (94.5 + 13.2 + 14) - 20$$

$$= 454.173 \text{ mm}$$

Intermediate Term [Cc]:

$$= \sqrt{(2 \cdot \pi^2 \cdot \text{Elastic Modulus} / \text{Yield Stress})}$$

$$= \sqrt{(2 \cdot \pi^2 \cdot 199943008/260)}$$

$$= 123.211$$

Slenderness ratio [KL/r]:

$$= KL/r$$

$$= 1 \cdot 454/74.3$$

$$= 6.110$$

Bending Moment [Rm]:

$$= FI / (2 \cdot B_{plen}) \cdot e \cdot L / 2$$

$$= 8.38 / (2 \cdot 600) \cdot 105 \cdot 454/2$$

$$= 0.167 \text{ Kg-m.}$$

Compressive Allowable, $KL/r < C_c$ ($6.11 < 123$) per AISC E2-1 [Sca]:

$$= (1 - (KL/r)^2 / (2 \cdot C_c^2)) F_y / (5/3 + 3 \cdot (KL/r) / (8 \cdot C_c) - (KL/r)^3 / (8 \cdot C_c^3))$$

$$= (1 - (6.11)^2 / (2 \cdot 123^2)) 260 /$$

$$(5/3 + 3 \cdot (6.11) / (8 \cdot 123) - (6.11^3) / (8 \cdot 123^3))$$

$$= 154.1 \text{ N./mm}^2$$

AISC Unity Check of Outside Ribs (must be ≤ 1)

$$= Sc/Sca + (Rm \cdot C1 / I) / Sba$$

$$= 0.4/154 + (0.17 \cdot 138/24263022) / 173$$

$$= 0.003$$



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 126 of 204

Saddle Calcs: Test Case:

Step: 21

9:40am

Sep 9, 2026

Check of Inside Ribs:

Inertia of Saddle, Inner Ribs - Axial Direction

	B	D	Y	A	AY	Io
Rib	14.0	261.0	0.0	36.5	0.0	0.243E+04
Web	105.4	14.0	0.0	14.7	0.0	2.41
Totals	...	...	...	51.3	...	0.243E+04

Distance to Centroid from Datum [ytot]:

$$= AY / A$$

$$= 0/51.3$$

$$= 0.000 \text{ mm}$$

Distance to Centroid [C1]:

$$= \text{Saddle Width} / 2$$

$$= 275/2$$

$$= 137.500 \text{ mm}$$

Length of Inner Rib [L]:

$$= \text{Saddle Height} - \text{Outside Radius} - \text{Bpthk}$$

$$= 535 - \cos(122/2)(20 + 0 + 0) - 0$$

$$= 393.345 \text{ mm}$$

Radius of Gyration [r]:

$$= \sqrt{(\text{Total Inertia} / \text{Total Area})}$$

$$= \sqrt{(2428/51.3)}$$

$$= 68.809 \text{ mm}$$

Slenderness ratio [KL/r]:

$$= KL/r$$

$$= 1 \cdot 393/68.8$$

$$= 5.717$$

Unit Force [Force,u]:

$$= FI / (2 \cdot \text{Baseplate Length})$$

$$= 8.38/(2 \cdot 600)$$

$$= 0.007 \text{ Kg/mm}$$

Moment at base of inner Rib [Mbase,c]:

$$= \text{Unit Force} \cdot e \cdot L$$

$$= 0.007 \cdot 105 \cdot 393$$

$$= 0.289 \text{ Kg-m.}$$

Bending Stress due to Transverse Force and Weight Load [σ_B ,base,c]:

$$= \text{Bending Moment} / \text{Section Modulus}$$

$$= 0.29/176610$$

$$= 0.016 \text{ N./mm}^2$$

Compressive Allowable, $KL/r < C_c$ ($5.72 < 123$) per AISC E2-1 [Sca]:

$$= (1 - (KL/r)^2 / (2 \cdot C_c^2)) F_y / (5/3 + 3 \cdot (KL/r) / (8 \cdot C_c) - (KL/r)^3 / (8 \cdot C_c^3))$$

$$= (1 - (5.72)^2 / (2 \cdot 123^2)) 260 /$$

$$(5/3 + 3 \cdot (5.72) / (8 \cdot 123) - (5.72^3) / (8 \cdot 123^3))$$

$$= 154.2 \text{ N./mm}^2$$

AISC Unity Check of Inside Ribs (must be ≤ 1)

$$= S_c / S_{ca} + (M_{base,c} \cdot C1/I) / S_{ba}$$

$$= 0.69/154 + (0.29 \cdot 138/2428) / 173$$

$$= 0.005$$

Input Data for Base Plate Bolting Calculations:

Total Number of Bolts per BasePlate

Nbolts

4

Total Number of Bolts in Tension/Baseplate

Nbt

2



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 127 of 204

Saddle Calcs: Test Case:

Step: 21 9:40am

Sep 9, 2026

Bolt Material Specification		SA-307 A
Bolt Allowable Stress	Stba	48.30 N./mm ²
Bolt Corrosion Allowance	Bca	1.5 mm
Distance from Bolts to Edge	Edgedis	50.8 mm
User Defined Area in a Single Bolt	UserBoltArea	1.5500 cm ²
BasePlate Allowable Stress	S	138.00 N./mm ²
Area Available in a Single Bolt	BltArea	0.9592 cm ²
Saddle Load QO (Weight)	QO	1726.7 Kgf
Saddle Load QL (Wind/Seismic contribution)	QL	1.3 Kgf
Maximum Transverse Force	Ft	41.6 Kgf
Maximum Longitudinal Force	Fl	8.4 Kgf
Saddle Bolted to Steel Foundation		No

Shear Stress in a Single Bolt, Longitudinal Direction [tb,l]:

$$= Fl / (\text{Bolt Area} \cdot \text{Number of Bolts})$$

$$= 8.38 / (0.96 \cdot 4)$$

$$= 0.2 \text{ N./mm}^2. \text{ Must be less than } 29.0 \text{ N./mm}^2.$$

Shear Stress in a Single Bolt, Transverse Direction [tb,t]:

$$= Ft / (\text{Bolt Area} \cdot \text{Number of Bolts})$$

$$= 41.6 / (0.96 \cdot 4)$$

$$= 1.1 \text{ N./mm}^2. \text{ Must be less than } 29.0 \text{ N./mm}^2.$$

Bolt Area Calculation per Dennis R. Moss

Bolt Area Requirement Due to Longitudinal Load [Bltarearl]:

$$= 0.0 \text{ (} QO > QL \text{ --> No Uplift in Longitudinal direction)}$$

Bolt Area due to Shear Load [Bltarears]:

$$= Fl / (\text{BoltShearAllowable} \cdot \text{Nbols})$$

$$= 8.38 / (29 \cdot 4)$$

$$= 0.0071 \text{ cm}^2$$

Bolt Area due to Transverse Load:

Moment on Baseplate Due to Transverse Load [Rmom]:

$$= B \cdot Ft + \text{Sum of X Moments}$$

$$= 535 \cdot 41.6 + 0$$

$$= 22.28 \text{ Kg-m.}$$

Eccentricity (e):

$$= Rmom / QO$$

$$= 22.3 / 1727$$

$$= 12.90 \text{ mm} < Bplen/6 \text{ --> No Uplift in Transverse direction}$$

Bolt Area due to Transverse Load [Bltareart]:

$$= 0 \text{ (No Uplift)}$$

Required Area of a Single Bolt [Bltarear]:

$$= \max[Bltarearl, Bltarears, Bltareart]$$

$$= \max[0, 0.0071, 0]$$

$$= 0.0071 \text{ cm}^2$$

Review notes about nozzle loadings and supports in the Warnings report.

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.




PV Elite 28 Licensee: SL User
 FileName : 161-C1-C2 _(Stack) Page 128 of 204
 Saddle Calcs: Ext. Pressure: Step: 22 9:40am Sep 9,2026

ASME VIII Division 2 Horizontal Vessel Analysis, Left Saddle:

Horizontal Vessel Stress Calculations : External Pressure

Input and Calculated Values:

Vessel Mean Radius	Rm	102.57	mm
Shell Thickness used in this Case	t	13.179	mm
Stiffened Vessel Length per 4.15.6	L	5785.00	mm
Distance from Saddle to Vessel tangent	a1 or a	1200.00	mm
Saddle Width	b1 or b	275.00	mm
Saddle Bearing Angle	delta or theta	120.00	degrees
Wear Plate Width	b2 or b1	335.00	mm
Wear Plate Bearing Angle	delta2 or theta1	132.00	degrees
Wear Plate Thickness	e2 or tr	14.0	mm
Wear Plate Allowable Stress	fw or Sr	118.00	N./mm ²
Shell Allowable Stress used in Calculation		118.00	N./mm ²
Head Allowable Stress used in Calculation		133.20	N./mm ²
Circumferential Efficiency in Plane of Saddle		1.00	
Circumferential Efficiency at Mid-Span		1.00	
Distance from Saddle Base to Centerline	B	535.00	mm
Coefficient of Friction	mu	0.30	



Results for Horizontal Vessel Analysis:

Saddle Force Q, External Pressure Case	10652.70	Kgf
Pressure used in Analysis	P	-103.419 KPa.

Horizontal Vessel Analysis Results:	Actual N./mm ²	Allowable N./mm ²
Long. Stress at Top of Midspan	-77.27	-176.76
Long. Stress at Top of Midspan	77.27	118.00
Long. Stress at Bottom of Midspan	76.23	118.00
Long. Stress at Top of Saddles	76.50	118.00
Long. Stress at Bottom of Saddles	-77.54	-176.76
Long. Stress at Bottom of Saddles	77.54	118.00
Tangential Shear in Shell	18.64	94.40



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 129 of 204

Saddle Calcs: Ext. Pressure: Step: 22 9:40am Sep 9, 2026

Circ. Compressive Stress in Shell	6.92	118.00
Stiffener Circ. Stress at Shell	38.12	147.50
Stiffener Circ. Stress at Tip	160.42	292.49

Intermediate Results: Saddle Reaction Q due to Wind or Seismic:

Transverse Saddle Reaction Force [Fwt]:

$$= \text{Ftr}(\text{Ft/Num of Saddles} + \text{Z Force Load}) \cdot B / E$$

$$= 3 (167/2 + 1048) \cdot 535/211$$

$$= 8617.3 \text{ Kgf}$$

Longitudinal Saddle Reaction Force [Fwl]:

$$= \max(\text{Fl,wind}; \text{Sum of X Forces}) \cdot B / \text{Ls}$$

$$= \max(16.8, 300) \cdot 535/3450$$

$$= 7.8 \text{ Kgf}$$

Saddle Reaction Force due to Earthquake Fl [Fsl]:

$$= \max(\text{Fl,eq}; \text{Sum of X Forces}) \cdot B / \text{Ls}$$

$$= \max(212, 300) \cdot 535/3450$$

$$= 46.5 \text{ Kgf}$$

Saddle Reaction Force due to Earthquake Ft [Fst]:

$$= \text{Ftr}(\text{Ft/Num of Saddles} + \text{Z Force Load}) \cdot B / E$$

$$= 3 (212/2 + 1048) \cdot 535/211$$

$$= 8788.8 \text{ Kgf}$$

Load Combination Results for Q + Wind or Seismic [Q]:

$$= \text{Saddle Load} + \max(\text{Fwl}, \text{Fwt}, \text{Fsl}, \text{Fst})$$

$$= 1864 + \max(7.75, 8617, 46.5, 8789)$$

$$= 10652.7 \text{ Kgf}$$

Longitudinal Wind Force [Fl]:

$$= \text{WindScalar} \cdot \text{WindPress}(\text{Platform Area} + (\pi/4(\text{OD} \cdot \text{WindDiaMult})^2))$$

$$= 1.1 \cdot 766 (0 + \pi/4(0.42 \cdot 1.2)^2)$$

$$= 164.386 \text{ N}$$

Summary of Loads at the Base of this Saddle:

Vertical Load (including saddle weight)	10757.13	Kgf
Transverse Shear Load	1153.83	Kgf
Longitudinal Shear Load	300.00	Kgf

Note: Wear Plate is Welded to the Shell, k = 0.1

Saddle Dimension [E]:

$$= \min(2(\text{ShellID}/2 + t + \text{WearPadThickness}) \sin(\theta/2), 2 \cdot \text{Rm})$$

$$= \min(2(189/2 + 13.2 + 14) \sin(120/2), 2 \cdot 103)$$

$$= 210.712 \text{ mm}$$

The Computed K values from Table 4.15.1:

K1 = 0.1066	K2 = 1.1707	K3 = 0.8799	K4 = 0.4011
K5 = 0.7603	K6 = 0.0529	K7 = 0.0529	K8 = 0.3405
K9 = 0.2711	K10 = 0.0581	K1* = 0.1923	K6p = 0.0434
K7p = 0.0434			

The suffix 'p' denotes the values for a wear plate if it exists.

Note: Dimension a is greater than or equal to Rm/2.

Moment per Equation 4.15.1 [M1]:

$$= -Q \cdot a [1 - (1 - a/L + (Rm^2 - hm^2)/(2a \cdot L)) / (1 + (4hm)/3L)]$$

$$= -10653 \cdot 1200 [1 - (1 - 1200/5785 + (103^2 - 0^2) /$$

$$(2 \cdot 1200 \cdot 5785)) / (1 + (4 \cdot 0) / (3 \cdot 5785))]$$

$$= -2642.0 \text{ Kg-m.}$$



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 130 of 204

Saddle Calcs: Ext. Pressure: Step: 22 9:40am Sep 9, 2026

Moment per Equation 4.15.2 [M2]:

$$= Q \cdot L / 4 \cdot ((1 + 2(Rm^2 - hm^2) / (L^2)) / (1 + (4hm^2) / (3L)) - 4a / L)$$

$$= 10653 \cdot 5785 / 4 \cdot ((1 + 2(103^2 - 0^2) / (5785^2)) / (1 + (4 \cdot 0) / (3 \cdot 5785)) - 4 \cdot 1200 / 5785)$$

$$= 2633.0 \text{ Kg-m.}$$

Longitudinal Stress at Top of Shell (4.15.4) [σ_1]:

$$= P \cdot Rm / (2t) - M2 / (\pi \cdot Rm^2 \cdot t)$$

$$= -103 \cdot 103 / (2 \cdot 10.2) - 2633 / (\pi \cdot 103^2 \cdot 10.2)$$

$$= -77.27 \text{ N./mm}^2$$

Longitudinal Stress at Bottom of Shell (4.15.5) [σ_2]:

$$= P \cdot Rm / (2t) + M2 / (\pi \cdot Rm^2 \cdot t)$$

$$= -103 \cdot 103 / (2 \cdot 10.2) + 2633 / (\pi \cdot 103^2 \cdot 10.2)$$

$$= 76.23 \text{ N./mm}^2$$

Longitudinal Stress at Top of Shell at Support (4.15.6) [σ_3]:

$$= P \cdot Rm / (2t) - M1 / (\pi \cdot Rm^2 \cdot t)$$

$$= -103 \cdot 103 / (2 \cdot 10.2) - 2642 / (\pi \cdot 103^2 \cdot 10.2)$$

$$= 76.50 \text{ N./mm}^2$$

Longitudinal Stress at bottom of Shell at Support (4.15.7) [σ_4]:

$$= P \cdot Rm / (2t) + M1 / (\pi \cdot Rm^2 \cdot t)$$

$$= -103 \cdot 103 / (2 \cdot 10.2) + 2642 / (\pi \cdot 103^2 \cdot 10.2)$$

$$= -77.54 \text{ N./mm}^2$$

Maximum Shear Force in the Saddle (4.15.3) [T]:

$$= Q(L - 2a) / (L + (4 \cdot hm / 3))$$

$$= 10653 \cdot (5785 - 2 \cdot 1200) / (5785 + (4 \cdot 0 / 3))$$

$$= 6233.3 \text{ Kg}$$

Shear Stress in the shell with a single ring (4.15.13) [τ_1]:

$$= T / (\pi \cdot Rm \cdot t)$$

$$= 6233 / (\pi \cdot 103 \cdot 10.2)$$

$$= 18.64 \text{ N./mm}^2$$

Decay Length (4.15.20) [x_1, x_2]:

$$= 0.78 \cdot \sqrt{(Rm \cdot t)}$$

$$= 0.78 \cdot \sqrt{(103 \cdot 10.2)}$$

$$= 25.203 \text{ mm}$$

Circ. Stress in shell w/ring in Plane of Saddle (4.15.32) [σ_6^*]:

$$= -K5 \cdot Q \cdot k / A$$

$$= -0.76 \cdot 10653 \cdot 0.1 / 11.5$$

$$= -6.92 \text{ N./mm}^2$$

Note: Single Ring in Plane of Saddle Outside the Shell.

Circ. + Bending Stress in shell w/ring in Plane of Saddle (4.15.35) [σ_8^*]:

$$= -K8 \cdot Q / A + K6 \cdot Q \cdot Rm \cdot c1 / I$$

$$= -0.34 \cdot 10653 / 11.5 + 0.053 \cdot 10653 \cdot 103 \cdot 11 / 9.04$$

$$= 38.12 \text{ N./mm}^2$$

Circ. + Bending Stress in ring w/ring in Plane of Saddle (4.15.36) [σ_9^*]:

$$= -K8 \cdot Q / A - K6 \cdot Q \cdot Rm \cdot c2 / I$$

$$= -0.34 \cdot 10653 / 11.5 - 0.053 \cdot 10653 \cdot 103 \cdot 20.7 / 9.04$$

$$= -160.42 \text{ N./mm}^2$$

Results for Vessel Ribs, Web and Base:

Baseplate Length	Bplen	600.0000	mm
Baseplate Thickness	Bpthk	20.0000	mm
Baseplate Width	Bpwid	300.0000	mm
Number of Ribs (inc. outside ribs)	Nribs	3	
Rib Thickness	Ribtk	14.0000	mm
Web Thickness	Webtk	14.0000	mm



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 131 of 204

Saddle Calcs: Ext. Pressure:

Step: 22

9:40am

Sep 9, 2026

Web Location	Webloc	Center	
Saddle Design Temperature		21.1	°C
Saddle Yield Stress	Sy	213.6	N./mm ²
Height of Web at Center	Hw,c	440.0	mm
Friction Coefficient	mu	0.300	

Moment of Inertia of Saddle - Transverse Direction (90 degrees to long axis)

Inertia of Shell [ShellInertia]:

$$= ((1.56 \cdot \sqrt{(R \cdot t) + \text{WearPlateWidth}})^3) / 12$$

$$= ((1.56 \cdot \sqrt{(97.5 \cdot 10.2) + 335})^3) / 12$$

$$= 3.377 \text{ cm}^4$$

Resolved Inertia for the Shell [I,shell]:

$$= \text{ShellInertia} + A_{\text{Shell}} (C1 - Y)^2$$

$$= 3.38 + 39.1 (193 - 5.09)^2$$

$$= 13819.127 \text{ cm}^4$$

	B mm	D mm	Y mm	A cm ²	AY mm ³	I + AD ² cm ⁴
Shell	384.1	10.2	5.1	39.1	19902.4	0.138E+05
Wearplate	335.0	14.0	17.2	46.9	80571.5	0.145E+05
Web	14.0	393.3	220.9	55.1	1216195.6	0.753E+04
BasePlate	300.0	20.0	427.5	60.0	2565148.2	0.330E+05
Totals	...	...	...	201.1	3881817.8	0.689E+05

Distance to Centroid [C1]:

$$= AY / A$$

$$= 3881817 / 201$$

$$= 193.057 \text{ mm}$$

Angle [β]:

$$= 180 - \text{Saddle Angle} / 2$$

$$= 180 - 120 / 2$$

$$= 120.0$$

Saddle Splitting Coefficient [K1]:

$$= (1 + \cos(\beta) - 0.5 \cdot \sin(\beta)^2) / (\pi - \beta + \sin(\beta) \cos(\beta))$$

$$= (1 + \cos(120) - 0.5 \cdot \sin(120)^2) / (\pi - 2.09 + \sin(120) \cos(120))$$

$$= 0.2035$$

Saddle Splitting Force [Fh]:

$$= K1 \cdot Q$$

$$= 0.2 \cdot 10653$$

$$= 2168.0549 \text{ Kg}$$

$$\text{Tension Stress, } St = (Fh / As) = 1.3127 \text{ N./mm}^2$$

$$\text{Allowed Stress, } Sa = 0.6 \cdot \text{Yield Str} = 128.1609 \text{ N./mm}^2$$

Saddle Splitting Dimension [d]:

$$= B - R \cdot \sin(\text{theta} / 2) / (\text{theta} / 2 \text{ in radians})$$

$$= 535 - 97.5 \cdot \sin(120 / 2) / 1.05$$

$$= 454.389 \text{ mm}$$

$$\text{Bending Moment, } M = Fh \cdot d = 985.1588 \text{ Kg-m.}$$

$$\text{Bending Stress, } Sb = (M \cdot C1 / I) = 2.7084 \text{ N./mm}^2$$

$$\text{Allowed Stress, } Sa = 2/3 \cdot \text{Yield Str} = 142.4010 \text{ N./mm}^2$$

Minimum Thickness of Baseplate per Moss:

$$= \sqrt[3]{(3(Q + \text{SaddleWt}) \text{BasePlateWidth}) / (4 \cdot \text{BasePlateLength} \cdot \text{AllStress})}$$

$$= \sqrt[3]{(3(10653 + 104)300) / (4 \cdot 600 \cdot 142)}$$

$$= 16.668 \text{ mm}$$



PV Elite 28 Licensee: SL User
 FileName : 161-C1-C2 _(Stack) Page 132 of 204
 Saddle Calcs: Ext. Pressure: Step: 22 9:40am Sep 9,2026

Calculation of Axial Load, Intermediate Values and Compressive Stress:

Web Length Dimension [Web Length]:
 $= 2 \cdot \cos(90 - \text{Saddle Angle}/2) (\text{Inside Radius} + \text{Shell Thk} + \text{Wear Plate Thk})$
 $= 2 \cdot \cos(90 - 120/2) (94.5 + 13.2 + 14)$
 $= 210.712 \text{ mm}$

Distance between Ribs [e]:
 $= \text{Web Length} / (\text{Nr ribs} - 1)$
 $= 211 / (3 - 1)$
 $= 105.356 \text{ mm}$

Baseplate Pressure Area [Ap]:
 $= e \cdot \text{Bpwid} / 2$
 $= 105 \cdot 300 / 2$
 $= 158.034 \text{ cm}^2$

Bearing Pressure [Bp]:
 $= (Q + \text{SaddleWt}) / (\text{BasePlateLength} \cdot \text{BasePlateWidth})$
 $= 10757 / (600 \cdot 300)$
 $= 5.976 \text{ Kg/cm}^2$

Axial Load [P]:
 $= \text{Ap} \cdot \text{Bp}$
 $= 158 \cdot 5.98$
 $= 944.441 \text{ Kg}$

Area of the Rib and Web [Ar]:
 $= \text{Rib Area} + \text{Web Area}$
 $= 36.5 + 7.37$
 $= 43.915 \text{ cm}^2$

Compressive Stress [Sc]:
 $= P / \text{Ar}$
 $= 944 / 43.9$
 $= 2.109 \text{ N/mm}^2$

Check of Outside Ribs:

Inertia of Saddle, Outer Ribs - Longitudinal Direction

	B	D	Y	A	AY	Io
Rib+Web	14.0	275.0	...	38.5	...	0.243E+04

Rib dimension [D]:
 $= \text{Saddle Width} - \text{Web Thickness}$
 $= 275 - 14$
 $= 261.000 \text{ mm}$

Distance to Centroid from Datum [ytot]:
 $= \text{AY} / \text{A}$
 $= 0 / 43.9$
 $= 0.000 \text{ mm}$

Distance to Centroid [C1]:
 $= \text{Saddle Width} / 2$
 $= 275 / 2$
 $= 137.500 \text{ mm}$

Radius of Gyration [r]:
 $= \sqrt{(\text{Total Inertia} / \text{Total Area})}$
 $= \sqrt{(2426 / 43.9)}$
 $= 74.330 \text{ mm}$



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 133 of 204

Saddle Calcs: Ext. Pressure: Step: 22 9:40am Sep 9, 2026

Length of Outer Rib [L]:

$$= \text{Saddle Height} - \cos(\theta/2) (\text{radius} + \text{shlthk} + \text{wpdthk}) - \text{bpthk}$$

$$= 535 - \cos(120/2) (94.5 + 13.2 + 14) - 20$$

$$= 454.173 \text{ mm}$$

Intermediate Term [Cc]:

$$= \sqrt{(2 \cdot \pi^2 \cdot \text{Elastic Modulus} / \text{Yield Stress})}$$

$$= \sqrt{(2 \cdot \pi^2 \cdot 199943008 / 214)}$$

$$= 135.934$$

Slenderness ratio [KL/r]:

$$= KL/r$$

$$= 1 \cdot 454 / 74.3$$

$$= 6.110$$

Bending Moment [Rm]:

$$= FI / (2 \cdot \text{Bplen}) \cdot e \cdot L / 2$$

$$= 300 / (2 \cdot 600) \cdot 105 \cdot 454 / 2$$

$$= 5.981 \text{ Kg-m.}$$

Compressive Allowable, $KL/r < Cc$ ($6.11 < 136$) per AISC E2-1 [Sca]:

$$= (1 - (KL/r)^2 / (2 \cdot Cc^2)) F_y / (5/3 + 3 \cdot (KL/r) / (8 \cdot Cc) - (KL/r)^3 / (8 \cdot Cc^3))$$

$$= (1 - (6.11)^2 / (2 \cdot 136^2)) 214 /$$

$$(5/3 + 3 \cdot (6.11) / (8 \cdot 136) - (6.11^3) / (8 \cdot 136^3))$$

$$= 126.8 \text{ N./mm}^2$$

AISC Unity Check of Outside Ribs (must be ≤ 1)

$$= S_c / S_{ca} + (R_m \cdot C_1 / I) / S_{ba}$$

$$= 2.11 / 127 + (5.98 \cdot 138 / 24263022) / 142$$

$$= 0.019$$

Check of Inside Ribs:

Inertia of Saddle, Inner Ribs - Axial Direction

	B	D	Y	A	AY	Io
Rib	14.0	261.0	0.0	36.5	0.0	0.243E+04
Web	105.4	14.0	0.0	14.7	0.0	2.41
Totals	...	...	...	51.3	...	0.243E+04

Distance to Centroid from Datum [ytot]:

$$= AY / A$$

$$= 0 / 51.3$$

$$= 0.000 \text{ mm}$$

Distance to Centroid [C1]:

$$= \text{Saddle Width} / 2$$

$$= 275 / 2$$

$$= 137.500 \text{ mm}$$

Length of Inner Rib [L]:

$$= \text{Saddle Height} - \text{Outside Radius} - \text{Bpthk}$$

$$= 535 - \cos(122/2) (20 + 0 + 0) - 0$$

$$= 393.345 \text{ mm}$$

Radius of Gyration [r]:

$$= \sqrt{(\text{Total Inertia} / \text{Total Area})}$$

$$= \sqrt{(2428 / 51.3)}$$

$$= 68.809 \text{ mm}$$

Slenderness ratio [KL/r]:

$$= KL/r$$

$$= 1 \cdot 393 / 68.8$$

$$= 5.717$$



PV Elite 28 Licensee: SL User
 FileName : 161-C1-C2 _(Stack) Page 134 of 204
 Saddle Calcs: Ext. Pressure: Step: 22 9:40am Sep 9,2026

Unit Force [Force,u]:
 = $F_l / (2 \cdot \text{Baseplate Length})$
 = $300 / (2 \cdot 600)$
 = 0.250 Kg/mm

Moment at base of inner Rib [Mbase,c]:
 = Unit Force $\cdot e \cdot L$
 = $0.25 \cdot 105 \cdot 393$
 = 10.361 Kg-m.

Bending Stress due to Transverse Force and Weight Load [σ_B ,base,c]:
 = Bending Moment / Section Modulus
 = $10.4 / 176610$
 = 0.575 N./mm²

Compressive Allowable, $KL/r < C_c$ ($5.72 < 136$) per AISC E2-1 [Sca]:
 = $(1 - (Kl/r)^2 / (2 \cdot C_c^2)) F_y / (5/3 + 3 \cdot (Kl/r) / (8 \cdot C_c) - (Kl/r)^3 / (8 \cdot C_c^3))$
 = $(1 - (5.72)^2 / (2 \cdot 136^2)) 214 / (5/3 + 3 \cdot (5.72) / (8 \cdot 136) - (5.72^3) / (8 \cdot 136^3))$
 = 126.8 N./mm²

AISC Unity Check of Inside Ribs (must be ≤ 1)
 = $S_c / S_{ca} + (M_{base,c} \cdot C_1 / I) / S_{ba}$
 = $3.62 / 127 + (10.4 \cdot 138 / 2428) / 142$
 = 0.033

ASME VIII Division 2 Horizontal Vessel Analysis, Right Saddle:

Input and Calculated Values:

Vessel Mean Radius	Rm	102.57	mm
Shell Thickness used in this Case	t	13.179	mm
Stiffened Vessel Length per 4.15.6	L	5785.00	mm
Distance from Saddle to Vessel tangent	a1 or a	1200.00	mm
Saddle Width	b1 or b	275.00	mm
Saddle Bearing Angle	delta or theta	120.00	degrees
Wear Plate Width	b2 or b1	335.00	mm
Wear Plate Bearing Angle	delta2 or theta1	132.00	degrees
Wear Plate Thickness	e2 or tr	14.0	mm
Wear Plate Allowable Stress	fw or Sr	118.00	N./mm ²
Shell Allowable Stress used in Calculation		118.00	N./mm ²
Head Allowable Stress used in Calculation		134.60	N./mm ²
Circumferential Efficiency in Plane of Saddle		1.00	
Circumferential Efficiency at Mid-Span		1.00	
Distance from Saddle Base to Centerline	B	535.00	mm
Coefficient of Friction	mu	0.00	

Results for Horizontal Vessel Analysis:

Saddle Force Q, External Pressure Case 4619.12 Kg
 Pressure used in Analysis P -103.419 KPa.

Horizontal Vessel Analysis Results:		Actual N./mm ²	Allowable N./mm ²
Long. Stress at Top of Midspan		-33.80	-176.76
Long. Stress at Top of Midspan		33.80	118.00
Long. Stress at Bottom of Midspan		32.76	118.00
Long. Stress at Top of Saddles		32.87	118.00
Long. Stress at Bottom of Saddles		-33.92	-176.76
Long. Stress at Bottom of Saddles		33.92	118.00



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 135 of 204

Saddle Calcs: Ext. Pressure: Step: 22 9:40am Sep 9, 2026

Tangential Shear in Shell	8.08	94.40
Circ. Compressive Stress in Shell	3.00	118.00
Stiffener Circ. Stress at Shell	16.53	147.50
Stiffener Circ. Stress at Tip	69.56	292.49

Intermediate Results: Saddle Reaction Q due to Wind or Seismic:

Transverse Saddle Reaction Force [Fwt]:

$$= Ftr(Ft/Num of Saddles + Z Force Load) \cdot B / E$$

$$= 3 (167/2 + 258) \cdot 535/211$$

$$= 2599.8 \text{ Kgf}$$

Longitudinal Saddle Reaction Force [Fwl]:

$$= \max(Fl,wind; \text{Sum of X Forces}) \cdot B / Ls$$

$$= \max(16.8, 300) \cdot 535/3450$$

$$= 7.8 \text{ Kgf}$$

Saddle Reaction Force due to Earthquake Fl [Fsl]:

$$= \max(Fl,eq; \text{Sum of X Forces}) \cdot B / Ls$$

$$= \max(212, 300) \cdot 535/3450$$

$$= 46.5 \text{ Kgf}$$

Saddle Reaction Force due to Earthquake Ft [Fst]:

$$= Ftr(Ft/Num of Saddles + Z Force Load) \cdot B / E$$

$$= 3 (212/2 + 258) \cdot 535/211$$

$$= 2771.3 \text{ Kgf}$$

Load Combination Results for Q + Wind or Seismic [Q]:

$$= \text{Saddle Load} + \max(Fwl, Fwt, Fsl, Fst)$$

$$= 1848 + \max(7.75, 2600, 46.5, 2771)$$

$$= 4619.1 \text{ Kgf}$$

Longitudinal Wind Force [Fl]:

$$= \text{WindScalar} \cdot \text{WindPress}(\text{Platform Area} + (\pi/4(OD \cdot \text{WindDiaMult})^2))$$

$$= 1.1 \cdot 766 (0 + \pi/4(0.42 \cdot 1.2)^2)$$

$$= 164.386 \text{ N}$$

Summary of Loads at the Base of this Saddle:

Vertical Load (including saddle weight)	4723.55	Kgf
Transverse Shear Load	363.83	Kgf
Longitudinal Shear Load	300.00	Kgf

Note: Wear Plate is Welded to the Shell, k = 0.1

Saddle Dimension [E]:

$$= \min(2(\text{ShellID}/2 + t + \text{WearPadThickness}) \sin(\theta/2), 2 \cdot Rm)$$

$$= \min(2(189/2 + 13.2 + 14) \sin(120/2), 2 \cdot 103)$$

$$= 210.712 \text{ mm}$$

The Computed K values from Table 4.15.1:

K1 = 0.1066	K2 = 1.1707	K3 = 0.8799	K4 = 0.4011
K5 = 0.7603	K6 = 0.0529	K7 = 0.0529	K8 = 0.3405
K9 = 0.2711	K10 = 0.0581	K1* = 0.1923	K6p = 0.0434
K7p = 0.0434			

The suffix 'p' denotes the values for a wear plate if it exists.

Note: Dimension a is greater than or equal to Rm/2.

Moment per Equation 4.15.1 [M1]:

$$= -Q \cdot a [1 - (1 - a/L + (Rm^2 - hm^2)/(2a \cdot L)) / (1 + (4hm)/3L)]$$

$$= -4619 \cdot 1200 [1 - (1 - 1200/5785 + (103^2 - 0^2) /$$

$$(2 \cdot 1200 \cdot 5785) / (1 + (4 \cdot 0) / (3 \cdot 5785))]$$



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 136 of 204

Saddle Calcs: Ext. Pressure:

Step: 22

9:40am

Sep 9, 2026

= -1145.6 Kg-m.

Moment per Equation 4.15.2 [M2]:

$$= Q \cdot L / 4 \left((1 + 2(Rm^2 - hm^2) / (L^2)) / (1 + (4hm^2) / (3L)) - 4a/L \right)$$

$$= 4619 \cdot 5785 / 4 \left((1 + 2(103^2 - 0^2) / (5785^2)) / (1 + (4 \cdot 0) / (3 \cdot 5785)) - 4 \cdot 1200 / 5785 \right)$$

$$= 1141.7 \text{ Kg-m.}$$

Longitudinal Stress at Top of Shell (4.15.4) [σ_1]:

$$= P \cdot Rm / (2t) - M2 / (\pi \cdot Rm^2 \cdot t)$$

$$= -103 \cdot 103 / (2 \cdot 10.2) - 1142 / (\pi \cdot 103^2 \cdot 10.2)$$

$$= -33.80 \text{ N./mm}^2$$

Longitudinal Stress at Bottom of Shell (4.15.5) [σ_2]:

$$= P \cdot Rm / (2t) + M2 / (\pi \cdot Rm^2 \cdot t)$$

$$= -103 \cdot 103 / (2 \cdot 10.2) + 1142 / (\pi \cdot 103^2 \cdot 10.2)$$

$$= 32.76 \text{ N./mm}^2$$

Longitudinal Stress at Top of Shell at Support (4.15.6) [σ_3]:

$$= P \cdot Rm / (2t) - M1 / (\pi \cdot Rm^2 \cdot t)$$

$$= -103 \cdot 103 / (2 \cdot 10.2) - 1146 / (\pi \cdot 103^2 \cdot 10.2)$$

$$= 32.87 \text{ N./mm}^2$$

Longitudinal Stress at bottom of Shell at Support (4.15.7) [σ_4]:

$$= P \cdot Rm / (2t) + M1 / (\pi \cdot Rm^2 \cdot t)$$

$$= -103 \cdot 103 / (2 \cdot 10.2) + 1146 / (\pi \cdot 103^2 \cdot 10.2)$$

$$= -33.92 \text{ N./mm}^2$$

Maximum Shear Force in the Saddle (4.15.3) [T]:

$$= Q(L - 2a) / (L + (4 \cdot hm / 3))$$

$$= 4619 (5785 - 2 \cdot 1200) / (5785 + (4 \cdot 0 / 3))$$

$$= 2702.8 \text{ Kgf}$$

Shear Stress in the shell with a single ring (4.15.13) [τ_1]:

$$= T / (\pi \cdot Rm \cdot t)$$

$$= 2703 / (\pi \cdot 103 \cdot 10.2)$$

$$= 8.08 \text{ N./mm}^2$$

Decay Length (4.15.20) [x1,x2]:

$$= 0.78 \cdot \sqrt{(Rm \cdot t)}$$

$$= 0.78 \cdot \sqrt{(103 \cdot 10.2)}$$

$$= 25.203 \text{ mm}$$

Circ. Stress in shell w/ring in Plane of Saddle (4.15.32) [σ_6^*]:

$$= -K5 \cdot Q \cdot k/A$$

$$= -0.76 \cdot 4619 \cdot 0.1 / 11.5$$

$$= -3.00 \text{ N./mm}^2$$

Note: Single Ring in Plane of Saddle Outside the Shell.

Circ. + Bending Stress in shell w/ring in Plane of Saddle (4.15.35) [σ_8^*]:

$$= -K8 \cdot Q/A + K6 \cdot Q \cdot Rm \cdot c1/l$$

$$= -0.34 \cdot 4619 / 11.5 + 0.053 \cdot 4619 \cdot 103 \cdot 11 / 9.04$$

$$= 16.53 \text{ N./mm}^2$$

Circ. + Bending Stress in ring w/ring in Plane of Saddle (4.15.36) [σ_9^*]:

$$= -K8 \cdot Q/A - K6 \cdot Q \cdot Rm \cdot c2/l$$

$$= -0.34 \cdot 4619 / 11.5 - 0.053 \cdot 4619 \cdot 103 \cdot 20.7 / 9.04$$

$$= -69.56 \text{ N./mm}^2$$

Results for Vessel Ribs, Web and Base:

Baseplate Length	Bplen	600.0000	mm
Baseplate Thickness	Bpthk	20.0000	mm
Baseplate Width	Bpwid	300.0000	mm



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 137 of 204

Saddle Calcs: Ext. Pressure:

Step: 22

9:40am

Sep 9, 2026

Number of Ribs (inc. outside ribs)	Nribs	3	
Rib Thickness	Ribtk	14.0000	mm
Web Thickness	Webtk	14.0000	mm
Web Location	Webloc	Center	
Saddle Design Temperature		21.1	°C
Saddle Yield Stress	Sy	213.6	N./mm ²
Height of Web at Center	Hw,c	440.0	mm
Friction Coefficient	mu	0.000	

Moment of Inertia of Saddle - Transverse Direction (90 degrees to long axis)

Inertia of Shell [ShellInertia]:

$$= ((1.56 \cdot \sqrt{(R \cdot t)} + \text{WearPlateWidth})t^3)/12$$

$$= ((1.56 \cdot \sqrt{(97.5 \cdot 10.2)} + 335)10.2^3)/12$$

$$= 3.377 \text{ cm}^4$$

Resolved Inertia for the Shell [I,shell]:

$$= \text{ShellInertia} + A_{\text{Shell}}(C1 - Y)^2$$

$$= 3.38 + 39.1(193 - 5.09)^2$$

$$= 13819.127 \text{ cm}^4$$

	B mm	D mm	Y mm	A cm ²	AY mm ³	I + AD ² cm ⁴
Shell	384.1	10.2	5.1	39.1	19902.4	0.138E+05
Wearplate	335.0	14.0	17.2	46.9	80571.5	0.145E+05
Web	14.0	393.3	220.9	55.1	1216195.6	0.753E+04
BasePlate	300.0	20.0	427.5	60.0	2565148.2	0.330E+05
Totals	...	...	...	201.1	3881817.8	0.689E+05

Distance to Centroid [C1]:

$$= AY / A$$

$$= 3881817/201$$

$$= 193.057 \text{ mm}$$

Angle [β]:

$$= 180 - \text{Saddle Angle}/2$$

$$= 180 - 120/2$$

$$= 120.0$$

Saddle Splitting Coefficient [K1]:

$$= (1 + \cos(\beta) - 0.5 \cdot \sin(\beta)^2) / (\pi - \beta + \sin(\beta)\cos(\beta))$$

$$= (1 + \cos(120) - 0.5 \cdot \sin(120)^2) / (\pi - 2.09 + \sin(120)\cos(120))$$

$$= 0.2035$$

Saddle Splitting Force [Fh]:

$$= K1 \cdot Q$$

$$= 0.2 \cdot 4619$$

$$= 940.0922 \text{ Kgf}$$

$$\text{Tension Stress, } St = (Fh/As) = 0.5692 \text{ N./mm}^2$$

$$\text{Allowed Stress, } Sa = 0.6 \cdot \text{Yield Str} = 128.1609 \text{ N./mm}^2$$

Saddle Splitting Dimension [d]:

$$= B - R \cdot \sin(\text{theta}/2) / (\text{theta}/2 \text{ in radians})$$

$$= 535 - 97.5 \cdot \sin(120/2) / 1.05$$

$$= 454.389 \text{ mm}$$

$$\text{Bending Moment, } M = Fh \cdot d = 427.1755 \text{ Kg-m.}$$

$$\text{Bending Stress, } Sb = (M \cdot C1 / I) = 1.1744 \text{ N./mm}^2$$

$$\text{Allowed Stress, } Sa = 2/3 \cdot \text{Yield Str} = 142.4010 \text{ N./mm}^2$$

Minimum Thickness of Baseplate per Moss:

$$= \sqrt{3(Q + \text{SaddleWt})\text{BasePlateWidth} / (4 \cdot \text{BasePlateLength} \cdot \text{AllStress})}$$



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 138 of 204

Saddle Calcs: Ext. Pressure: Step: 22 9:40am Sep 9,2026

$$= \sqrt{3(4619 + 104)300 / (4 \cdot 600 \cdot 142)}$$

$$= 11.045 \text{ mm}$$

Calculation of Axial Load, Intermediate Values and Compressive Stress:

Web Length Dimension [Web Length]:

$$= 2 \cdot \cos(90 - \text{Saddle Angle}/2) (\text{Inside Radius} + \text{Shell Thk} + \text{Wear Plate Thk})$$

$$= 2 \cdot \cos(90 - 120/2) (94.5 + 13.2 + 14)$$

$$= 210.712 \text{ mm}$$

Distance between Ribs [e]:

$$= \text{Web Length} / (\text{Nr ribs} - 1)$$

$$= 211 / (3 - 1)$$

$$= 105.356 \text{ mm}$$

Baseplate Pressure Area [Ap]:

$$= e \cdot \text{Bpwid} / 2$$

$$= 105 \cdot 300 / 2$$

$$= 158.034 \text{ cm}^2$$

Bearing Pressure [Bp]:

$$= (Q + \text{SaddleWt}) / (\text{BasePlateLength} \cdot \text{BasePlateWidth})$$

$$= 4724 / (600 \cdot 300)$$

$$= 2.624 \text{ Kg/cm}^2$$

Axial Load [P]:

$$= \text{Ap} \cdot \text{Bp}$$

$$= 158 \cdot 2.62$$

$$= 414.713 \text{ Kg}$$

Area of the Rib and Web [Ar]:

$$= \text{Rib Area} + \text{Web Area}$$

$$= 36.5 + 7.37$$

$$= 43.915 \text{ cm}^2$$

Compressive Stress [Sc]:

$$= P / \text{Ar}$$

$$= 415 / 43.9$$

$$= 0.926 \text{ N./mm}^2$$

Check of Outside Ribs:

Inertia of Saddle, Outer Ribs - Longitudinal Direction

	B	D	Y	A	AY	Io
Rib+Web	14.0	275.0	...	38.5	...	0.243E+04

Rib dimension [D]:

$$= \text{Saddle Width} - \text{Web Thickness}$$

$$= 275 - 14$$

$$= 261.000 \text{ mm}$$

Distance to Centroid from Datum [ytot]:

$$= \text{AY} / \text{A}$$

$$= 0 / 43.9$$

$$= 0.000 \text{ mm}$$

Distance to Centroid [C1]:

$$= \text{Saddle Width} / 2$$

$$= 275 / 2$$

$$= 137.500 \text{ mm}$$

Radius of Gyration [r]:

$$= \sqrt{(\text{Total Inertia} / \text{Total Area})}$$



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 139 of 204

Saddle Calcs: Ext. Pressure:

Step: 22

9:40am

Sep 9, 2026

$$= \sqrt{2426/43.9}$$

$$= 74.330 \text{ mm}$$

Length of Outer Rib [L]:

$$= \text{Saddle Height} - \cos(\theta/2) (\text{radius} + \text{shlthk} + \text{wpdthk}) - \text{bpthk}$$

$$= 535 - \cos(120/2) (94.5 + 13.2 + 14) - 20$$

$$= 454.173 \text{ mm}$$

Intermediate Term [Cc]:

$$= \sqrt{2 \cdot \pi^2 \cdot \text{Elastic Modulus} / \text{Yield Stress}}$$

$$= \sqrt{2 \cdot \pi^2 \cdot 199943008 / 214}$$

$$= 135.934$$

Slenderness ratio [KL/r]:

$$= KL/r$$

$$= 1 \cdot 454 / 74.3$$

$$= 6.110$$

Bending Moment [Rm]:

$$= FI / (2 \cdot B_{plen}) \cdot e \cdot L / 2$$

$$= 300 / (2 \cdot 600) \cdot 105 \cdot 454 / 2$$

$$= 5.981 \text{ Kg-m.}$$

Compressive Allowable, $KL/r < C_c$ ($6.11 < 136$) per AISC E2-1 [Sca]:

$$= (1 - (KL/r)^2 / (2 \cdot C_c^2)) F_y / (5/3 + 3 \cdot (KL/r) / (8 \cdot C_c) - (KL/r)^3 / (8 \cdot C_c^3))$$

$$= (1 - (6.11)^2 / (2 \cdot 136^2)) 214 / (5/3 + 3 \cdot (6.11) / (8 \cdot 136) - (6.11)^3 / (8 \cdot 136^3))$$

$$= 126.8 \text{ N/mm}^2$$

AISC Unity Check of Outside Ribs (must be ≤ 1)

$$= S_c / S_{ca} + (R_m \cdot C_1 / I) / S_{ba}$$

$$= 0.93 / 127 + (5.98 \cdot 138 / 24263022) / 142$$

$$= 0.010$$

Check of Inside Ribs:

Inertia of Saddle, Inner Ribs - Axial Direction

	B	D	Y	A	AY	Io
Rib	14.0	261.0	0.0	36.5	0.0	0.243E+04
Web	105.4	14.0	0.0	14.7	0.0	2.41
Totals	...	...	...	51.3	...	0.243E+04

Distance to Centroid from Datum [ytot]:

$$= AY / A$$

$$= 0 / 51.3$$

$$= 0.000 \text{ mm}$$

Distance to Centroid [C1]:

$$= \text{Saddle Width} / 2$$

$$= 275 / 2$$

$$= 137.500 \text{ mm}$$

Length of Inner Rib [L]:

$$= \text{Saddle Height} - \text{Outside Radius} - \text{Bpthk}$$

$$= 535 - \cos(122/2) (20 + 0 + 0) - 0$$

$$= 393.345 \text{ mm}$$

Radius of Gyration [r]:

$$= \sqrt{\text{Total Inertia} / \text{Total Area}}$$

$$= \sqrt{2428 / 51.3}$$

$$= 68.809 \text{ mm}$$

Slenderness ratio [KL/r]:

$$= KL/r$$



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 140 of 204

Saddle Calcs: Ext. Pressure:

Step: 22

9:40am

Sep 9, 2026

$$= 1 \cdot 393/68.8$$

$$= 5.717$$

Unit Force [Force,u]:

$$= F / (2 \cdot \text{Baseplate Length})$$

$$= 300 / (2 \cdot 600)$$

$$= 0.250 \text{ Kg/mm}$$

Moment at base of inner Rib [Mbase,c]:

$$= \text{Unit Force} \cdot e \cdot L$$

$$= 0.25 \cdot 105 \cdot 393$$

$$= 10.361 \text{ Kg-m.}$$

Bending Stress due to Transverse Force and Weight Load [σ_B ,base,c]:

$$= \text{Bending Moment} / \text{Section Modulus}$$

$$= 10.4/176610$$

$$= 0.575 \text{ N./mm}^2$$

Compressive Allowable, $KL/r < C_c$ ($5.72 < 136$) per AISC E2-1 [Sca]:

$$= (1 - (KL/r)^2 / (2 \cdot C_c^2)) F_y / (5/3 + 3 \cdot (KL/r) / (8 \cdot C_c) - (KL/r)^3 / (8 \cdot C_c^3))$$

$$= (1 - (5.72)^2 / (2 \cdot 136^2)) 214 / (5/3 + 3 \cdot (5.72) / (8 \cdot 136) - (5.72^3) / (8 \cdot 136^3))$$

$$= 126.8 \text{ N./mm}^2$$

AISC Unity Check of Inside Ribs (must be ≤ 1)

$$= S_c / S_{ca} + (M_{base,c} \cdot C_{1/I}) / S_{ba}$$

$$= 1.59/127 + (10.4 \cdot 138/2428) / 142$$

$$= 0.017$$

Review notes about nozzle loadings and supports in the Warnings report.

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 141 of 204

Nozzle Calcs.: N1-Tube Inlet

Nozl: 9 9:40am Sep 9,2026

Input, Nozzle Desc: N1-Tube Inlet

From: 20

Pressure for Reinforcement Calculations	P	2400.000	KPa.
Temperature for Internal Pressure	Temp	270	°C
Design External Pressure	Pext	103.42	KPa.
Temperature for External Pressure	Tempex	270	°C
Parent Material		SA-106 B	
Parent Allowable Stress at Temperature	Sv	118.00	N./mm ²
Parent Allowable Stress At Ambient	Sva	118.00	N./mm ²
Inside Diameter of Cylindrical Shell	D	188.95	mm
Design Length of Section	L	366.5459	mm
Shell Finished (Minimum) Thickness	t	13.1794	mm
Shell Internal Corrosion Allowance	c	3.0000	mm
Shell External Corrosion Allowance	co	0.0000	mm
Distance from Bottom/Left Tangent		200.80	mm
User Entered Minimum Design Metal Temperature		-12.00	°C

Type of Element Connected to the Parent : Nozzle

Material		SA-106 B	
Material UNS Number		K03006	
Material Specification/Type		Smls. pipe	
Allowable Stress at Temperature	Sn	118.00	N./mm ²
Allowable Stress At Ambient	Sna	118.00	N./mm ²
Diameter Basis (for tr calc only)		Outside	
Layout Angle		90.00	deg
Diameter		89.0000	mm
Size and Thickness Basis		Actual	
Actual Thickness	tn	11.0000	mm
Flange Material		SA-105	
Flange Type		Weld Neck Flange	
Corrosion Allowance	can	3.0000	mm
Joint Efficiency of Shell Seam at Nozzle	E1	1.00	
Joint Efficiency of Nozzle Neck	En	1.00	
Outside Projection	ho	200.0000	mm
Weld leg size between Nozzle and Pad/Shell	Wo	12.0000	mm
Groove weld depth between Nozzle and Vessel	Wgnv	10.0000	mm
Inside Projection	h	0.0000	mm
Weld leg size, Inside Element to Shell	Wi	0.0000	mm
Pad Material		SA-516 70	
Pad Allowable Stress at Temperature	Sp	137.20	N./mm ²
Pad Allowable Stress At Ambient	Spa	138.00	N./mm ²
Diameter of Pad along vessel surface	Dp	129.0000	mm
Thickness of Pad	te	14.0000	mm
Weld leg size between Pad and Shell	Wp	10.0000	mm
Groove weld depth between Pad and Nozzle	Wgpn	14.0000	mm
Reinforcing Pad Width		20.0000	mm
Flange Class		600	
Flange Grade		GR 1.1	

The Pressure Design option was Design Pressure + static head.



PV Elite 28 Licensee: SL User


FileName : 161-C1-C2_(Stack)

Page 142 of 204

Nozzle Calcs.: N1-Tube Inlet

Nozl: 9 9:40am

Sep 9,2026



Reinforcement CALCULATION, Description: N1-Tube Inlet

ASME Code, Section VIII, Div. 1, UG-37 to UG-45

Actual Outside Diameter Used in Calculation	89.000 mm.
Actual Thickness Used in Calculation	11.000 mm

Nozzle input data check completed without errors.

Reqd thk per UG-37(a) of Cylindrical Shell, tr [Int. Press]
 $= P \cdot R / (S_v \cdot E - 0.6 \cdot P)$ per UG-27 (c)(1)
 $= 2400 \cdot 97.5 / (118 \cdot 1 - 0.6 \cdot 2400)$
 $= 2.0072 \text{ mm}$

Reqd thk per UG-37(a) of Nozzle Wall, trn [Int. Press]
 $= P \cdot R_o / (S_n \cdot E + 0.4 \cdot P)$ per Appendix 1-1 (a)(1)
 $= 2400 \cdot 44.5 / (118 \cdot 1 + 0.4 \cdot 2400)$
 $= 0.8978 \text{ mm}$

Required Nozzle thickness under External Pressure per UG-28 : 0.4125 mm

UG-40, Limits of Reinforcement: [Internal Pressure]

Parallel to Vessel Wall (Diameter Limit)	D1	146.0000 mm
Parallel to Vessel Wall, opening length	d	73.0000 mm
Normal to Vessel Wall (Thickness Limit), pad side Tlwp		25.4486 mm

*Taking a UG-36(c)(3)(a) exemption for nozzle: N1-Tube Inlet.
 This calculation is valid for nozzles that meet all the requirements of paragraph UG-36. Please check the Code carefully, especially for nozzles that are not isolated or do not meet Code spacing requirements. To force the computation of areas for small nozzles go to Tools->Configuration and check the box to force the UG-37 small nozzle area calculation.*

UG-45 Minimum Nozzle Neck Thickness Requirement: [Int. Press.]

Wall Thickness for Internal/External pressures	ta = 3.8978 mm
Wall Thickness per UG16(b),	tr16b = 4.5000 mm
Wall Thickness, shell/head, internal pressure	trb1 = 5.0072 mm
Wall Thickness	tb1 = max(trb1, tr16b) = 5.0072 mm
Wall Thickness	tb2 = max(trb2, tr16b) = 4.5000 mm
Wall Thickness per table UG-45	tb3 = 8.0200 mm

Determine Nozzle Thickness candidate [tb]:
 $= \min[tb3, \max(tb1, tb2)]$
 $= \min[8.02, \max(5.01, 4.5)]$
 $= 5.0072 \text{ mm}$

Minimum Wall Thickness of Nozzle Necks [tUG-45]:
 $= \max(ta, tb)$
 $= \max(3.9, 5.01)$
 $= 5.0072 \text{ mm}$

Available Nozzle Neck Thickness = 11.0000 mm -> OK



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)

Page 143 of 204

Nozzle Calcs.: N1-Tube Inlet

Nozl: 9

9:40am

Sep 9, 2026

Stresses on Nozzle due to External and Pressure Loads per the ASME B31.3 Piping Code, (see 319.4.4 and 302.3.5):

Sustained	:	49.2,	Allowable	:	118.0 N./mm ²	Passed
Expansion	:	0.0,	Allowable	:	245.8 N./mm ²	Passed
Occasional	:	4.9,	Allowable	:	156.9 N./mm ²	Passed
Shear	:	30.0,	Allowable	:	82.6 N./mm ²	Passed

The number of cycles on this nozzle was assumed to be 7000 or less for the determination of the expansion stress allowable.

Nozzle Junction Minimum Design Metal Temperature (MDMT) Calculations:

Nozzle Neck to Flange Weld, min(Curve:B, Curve:A)

Govrn. thk, tg = 11, tr = 0.9, c = 3 mm, E* = 1

Thickness Ratio = $tr * E^* / (tg - c) = 0.11$, Temp. Reduction = 78 °C

Min Metal Temp. w/o impact per UCS-66, Curve A	-5 °C
Min Metal Temp. at Required thickness (UCS 66.1)	-104 °C
Min Metal Temp. w/o impact per UG-20(f)	-29 °C

Nozzle Neck to Pad Weld for the Nozzle, Curve: B

Govrn. thk, tg = 11, tr = 0.9, c = 3 mm, E* = 1

Thickness Ratio = $tr * E^* / (tg - c) = 0.11$, Temp. Reduction = 78 °C

Min Metal Temp. w/o impact per UCS-66, Curve B	-26 °C
Min Metal Temp. at Required thickness (UCS 66.1)	-104 °C
Min Metal Temp. w/o impact per UG-20(f)	-29 °C

Nozzle Neck to Pad Weld for Reinforcement pad, Curve: B

Govrn. thk, tg = 11, tr = 0.9, c = 3 mm, E* = 1

Thickness Ratio = $tr * E^* / (tg - c) = 0.11$, Temp. Reduction = 78 °C

Min Metal Temp. w/o impact per UCS-66, Curve B	-26 °C
Min Metal Temp. at Required thickness (UCS 66.1)	-104 °C
Min Metal Temp. w/o impact per UG-20(f)	-29 °C

Shell to Pad Weld Junction at Pad OD, Curve: B

Govrn. thk, tg = 13.2, tr = 2.01, c = 3 mm, E* = 1

Thickness Ratio = $tr * E^* / (tg - c) = 0.2$, Temp. Reduction = 78 °C

Min Metal Temp. w/o impact per UCS-66, Curve B	-20 °C
Min Metal Temp. at Required thickness (UCS 66.1)	-104 °C
Min Metal Temp. w/o impact per UG-20(f)	-29 °C

Nozzle-Shell/Head Weld (UCS-66(a)1(b)), Curve: B

Govrn. thk, tg = 11, tr = 0.9, c = 3 mm, E* = 1

Thickness Ratio = $tr * E^* / (tg - c) = 0.11$, Temp. Reduction = 78 °C

Min Metal Temp. w/o impact per UCS-66, Curve B	-26 °C
Min Metal Temp. at Required thickness (UCS 66.1)	-104 °C
Min Metal Temp. w/o impact per UG-20(f)	-29 °C

Gov. MDMT of the Nozzle	: -104 °C
Gov. MDMT of the Reinforcement Pad	: -104 °C
Gov. MDMT of the nozzle to shell joint welded assembly	: -104 °C

Flange MDMT including Temperature reduction per UCS-66.1:

Unadjusted MDMT of ASME B16.5/47 flanges per UCS-66(c)	-18 °C
--	--------



PV Elite 28 Licensee: SL User
 FileName : 161-C1-C2 _(Stack) Page 144 of 204
 Nozzle Calcs.: N1-Tube Inlet Nozl: 9 9:40am Sep 9,2026

Flange MDMT with Temp reduction per UCS-66(b)(1)(-b) -104 °C

Where the Stress Reduction Ratio per UCS-66(b)(1)(-b) is :
 Design Pressure/Ambient Rating = 2400.00/10200.00 = 0.235

Weld Size Calculations, Description: N1-Tube Inlet

Intermediate Calc. for nozzle/shell Welds Tmin 8.0000 mm
 Intermediate Calc. for pad/shell Welds TminPad 12.0622 mm

Results Per UW-16.1:

	Required Thickness	Actual Thickness
Nozzle Weld	5.6000 = 0.7 * tmin.	8.4840 = 0.7 * Wo mm
Pad Weld	6.0311 = 0.5*TminPad	7.0700 = 0.7 * Wp mm

Skipping the nozzle attachment weld strength calculations. Per UW-15(b)(2) the nozzles exempted by UG-36(c)(3)(a) (small nozzles) do not require a weld strength check.

Maximum Allowable Pressure for this Nozzle at this Location:

Converged Maximum Allowable Pressure in the Operating case: 11594 KPa.

Note: The MAWP of this junction was limited by the parent Shell/Head.

The Drop for this Nozzle is : 11.1366 mm
 The Cut Length for this Nozzle is, Drop + Ho + H + T : 224.3161 mm

Input Echo, WRC297 Item 1, Description: N1-Tube Inlet :

Diameter Basis for Cylindrical Shell	ID	
Shell Internal Corrosion Allowance	3.0000	mm
Shell External Corrosion Allowance	0.0000	mm
Shell Diameter	188.951	mm
Shell Thickness	13.1794	mm
Shell Stress Concentration Factor	1.000	
Vessel Material	SA-106 B	
Vessel Cold S.I. Allowable	Smc	118.00 N./mm ²
Vessel Hot S.I. Allowable	Smh	118.00 N./mm ²

See ASME VIII Div. 2, 4.1.6.3, for determination of the SPS allowable.

Diameter Basis for Nozzle	OD	
Nozzle Corrosion Allowance	3.0000	mm
Nozzle Diameter	89.000	mm
Nozzle Thickness	11.0000	mm
Nozzle Stress Concentration Factor	1.000	
Nozzle Material	SA-106 B	
Nozzle Cold S.I. Allowable	SNmc	118.00 N./mm ²
Nozzle Hot S.I. Allowable	SNmh	118.00 N./mm ²

See ASME VIII Div. 2, 4.1.6.3, for determination of the SPS allowable.

Diameter of Reinforcing Pad	129.000	mm
Thickness of Reinforcing Pad	14.0000	mm

Note:
 External Forces and Moments in WRC 107/537 Convention:
 These loads are assumed to be SUSained loads.

Design Internal Pressure	Dp	2400.00	KPa.
Radial Load	P	-734.25	Kgf
Circumferential Shear	Vc	530.29	Kgf
Longitudinal Shear	Vl	530.29	Kgf
Circumferential Moment	Mc	130.48	Kg-m.



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 145 of 204

Nozzle Calcs.: N1-Tube Inlet

Nozl: 9 9:40am Sep 9, 2026

Longitudinal Moment	Ml	130.48	Kg-m.
Torsional Moment	Mt	150.05	Kg-m.

Include Axial Pressure Thrust	No
Include Pressure Stress Indices per Div. 2	No
Local Loads applied at end of Nozzle/Attachment	No

*Warning - The ratio, D_v/T_v (16.337) is < 20
check the limitations of WRC bulletin 297.*

*Warning - The ratio, D_n/T_n (8.091) is < 10
check the limitations of WRC bulletin 297.*

Stress Computations at the Edge of the Nozzle:

Stress Attenuation Diameter (for Insert Plates) per WRC 297:

$$= \text{NozzleOD} + 2 \cdot 1.65 \cdot \sqrt{R_{\text{mean}}(t - c_a)}$$

$$= 89.0 + 2 \cdot 1.65 \cdot \sqrt{109.565(13.179 - 3.0)}$$

$$= 199.208 \text{ mm}$$

WRC 297 Curve Access Parameters:

Vessel Mean Diameter	(D) =	219.130 mm
Nozzle Outside Diameter	(d) =	89.000 mm
Vessel Thickness used	(T) =	24.179 mm
Nozzle Thickness used	(t) =	8.000 mm
T / t	=	3.022
d / t	=	11.125

$$\lambda = [(d/D) \cdot \sqrt{(D/T)}] = 1.223$$

Nr/P	=	0.148
Mr/P	=	0.117
M0/P	=	0.131
N0/P	=	0.194
MrD/Mc	=	0.176
NrDL/Mc	=	0.175
M0d/Mc	=	0.199
N0DL/Mc	=	0.052
MrD/Ml	=	0.143
NrDL/Ml	=	0.147
M0D/Ml	=	0.173
N0DL/Ml	=	0.173

Vessel Stresses (N/mm²):

LONGITUDINAL PLANE (Stresses Normal to longitudinal plane)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Outplane Membrane (P)	2	2	2	2
Outplane Bending (P)	9	-9	9	-9
Outplane Membrane (Mc)	0	0	0	0
Outplane Bending (Mc)	0	0	0	0
Outplane Membrane (ML)	-4	-4	4	4
Outplane Bending (ML)	-25	25	25	-25
Normal Pressure Stress	8	11	8	11
Outplane Stress Summary	-9	24	50	-17

Vessel Stresses (N/mm²):

LONGITUDINAL PLANE (Stresses parallel to longitudinal plane)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Inplane Membrane (P)	1	1	1	1
Inplane Bending (P)	8	-8	8	-8



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 146 of 204

Nozzle Calcs.: N1-Tube Inlet

Nozl: 9 9:40am

Sep 9, 2026

Inplane Membrane (Mc)	0	0	0	0
Inplane Bending (Mc)	0	0	0	0
Inplane Membrane (ML)	-3	-3	3	3
Inplane Bending (ML)	-21	21	21	-21
Inplane Pressure Stress	4	4	4	4

Inplane Stress Summary	-10	15	39	-20
------------------------	-----	----	----	-----

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE	Au	Al	Bu	Bl
(Shear stress normal to longitudinal plane)	Top Outside	Top Inside	Bottom Outside	Bottom Inside

Outplane Shear (Vc)	1	1	-1	-1
Outplane Shear (Vl)	0	0	0	0
Outplane Shear (Mt)	4	4	4	4

Shear Stress Summary	6	6	3	3
----------------------	---	---	---	---

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE	Au	Al	Bu	Bl
(Stress Intensities)	Top Outside	Top Inside	Bottom Outside	Bottom Inside

Two * Max Shear Stress	15	28	51	22
------------------------	----	----	----	----

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE	Cu	Cl	Du	Dl
(Stresses Normal to circumferential plane)	Left Outside	Left Inside	Right Outside	Right Inside

Outplane Membrane (P)	2	2	2	2
Outplane Bending (P)	9	-9	9	-9
Outplane Membrane (Mc)	-1	-1	1	1
Outplane Bending (Mc)	-29	29	29	-29
Outplane Membrane (ML)	0	0	0	0
Outplane Bending (ML)	0	0	0	0
Normal Pressure Stress	4	4	4	4

Outplane Stress Summary	-14	25	47	-31
-------------------------	-----	----	----	-----

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE	Cu	Cl	Du	Dl
(Stresses parallel to circumferential plane)	Left Outside	Left Inside	Right Outside	Right Inside

Inplane Membrane (P)	1	1	1	1
Inplane Bending (P)	8	-8	8	-8
Inplane Membrane (Mc)	-4	-4	4	4
Inplane Bending (Mc)	-25	25	25	-25
Inplane Membrane (ML)	0	0	0	0
Inplane Bending (ML)	0	0	0	0
Inplane Pressure Stress	8	11	8	11

Inplane Stress Summary	-11	25	49	-17
------------------------	-----	----	----	-----

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE	Cu	Cl	Du	Dl
(Shear stress normal to circumferential plane)	Left Outside	Left Inside	Right Outside	Right Inside

Outplane Shear (Vc)	0	0	0	0
Outplane Shear (Vl)	-1	-1	1	1
Torsional Shear (Mt)	4	4	4	4



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)

Page 147 of 204

Nozzle Calcs.: N1-Tube Inlet

Nozl: 9 9:40am

Sep 9,2026

Shear Stress Summary	3	3	6	6
----------------------	---	---	---	---

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Stress Intensities)	Cu Left Outside	Cl Left Inside	Du Right Outside	Dl Right Inside
Two * Max Shear Stress	16	28	54	33

Nozzle Stresses (N./mm²):

LONGITUDINAL PLANE (Stresses in the hoop direction)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Hoop Membrane (P)	2	2	2	2
Hoop Bending (P)	0	0	0	0
Hoop Membrane (Mc)	0	0	0	0
Hoop Bending (Mc)	0	0	0	0
Hoop Membrane (ML)	-4	-4	4	4
Hoop Bending (ML)	0	0	0	0
Hoop Pressure Stress	11	14	11	14
Hoop Stress Summary	9	12	18	21

Nozzle Stresses (N./mm²):

LONGITUDINAL PLANE (Stresses Normal to pipe cross-section)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Axial Membrane (P)	3	3	3	3
Axial Bending (P)	28	-28	28	-28
Axial Membrane (Mc)	0	0	0	0
Axial Bending (Mc)	0	0	0	0
Axial Membrane (ML)	-33	-33	33	33
Axial Bending (ML)	-93	93	93	-93
Axial Pressure Stress	5	5	5	5
Axial Stress Summary	-89	40	166	-79

Nozzle Stresses (N./mm²):

LONGITUDINAL PLANE (Shear stress)	Au Outside	Al Inside	Bu Outside	Bl Inside
Shear due to (Vc)	4	4	-4	-4
Shear due to (Vl)	0	0	0	0
Shear due to Torsion	14	14	14	14
Shear Stress Summary	19	19	10	10

Nozzle Stresses (N./mm²):

LONGITUDINAL PLANE (Stress Intensities)	Au Outside	Al Inside	Bu Outside	Bl Inside
Two * Max Shear Stress	106	50	166	103

Nozzle Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Stresses in the hoop direction)	Cu Left Outside	Cl Left Inside	Du Right Outside	Dl Right Inside
Hoop Membrane (P)	2	2	2	2
Hoop Bending (P)	0	0	0	0
Hoop Membrane (Mc)	-1	-1	1	1
Hoop Bending (Mc)	0	0	0	0
Hoop Membrane (ML)	0	0	0	0



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)

Page 148 of 204

Nozzle Calcs.: N1-Tube Inlet

Nozl: 9 9:40am

Sep 9, 2026

Hoop Bending (ML)	0	0	0	0
Hoop Pressure Stress	11	14	11	14
Hoop Stress Summary	12	15	15	18

Nozzle Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Stresses Normal to pipe cross-section)	Cu Left Outside	Cl Left Inside	Du Right Outside	Dl Right Inside
Axial Membrane (P)	3	3	3	3
Axial Bending (P)	28	-28	28	-28
Axial Membrane (Mc)	-33	-33	33	33
Axial Bending (Mc)	-119	119	119	-119
Axial Membrane (ML)	0	0	0	0
Axial Bending (ML)	0	0	0	0
Axial Pressure Stress	5	5	5	5
Axial Stress Summary	-114	66	191	-105

Nozzle Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Shear stress)	Cu Outside	Cl Inside	Du Outside	Dl Inside
Shear due to (Vc)	0	0	0	0
Shear due to (Vl)	-4	-4	4	4
Shear due to Torsion	14	14	14	14
Shear Stress Summary	10	10	19	19

Nozzle Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Stress Intensities)	Cu Outside	Cl Inside	Du Outside	Dl Inside
Two * Max Shear Stress	129	68	193	129

Stress Computations at the Edge of the Reinforcing Pad:

Stress Attenuation Diameter (for Insert Plates) per WRC 297:

$$= \text{NozzleOD} + 2 \cdot 1.65 \cdot \sqrt{R_{\text{mean}}(t - ca)}$$

$$= 89.0 + 2 \cdot 1.65 \cdot \sqrt{102.565(13.179 - 3.0)}$$

$$= 195.629 \text{ mm}$$

WRC 297 Curve Access Parameters:

Vessel Mean Diameter	(D) =	205.130 mm
Nozzle Outside Diameter	(d) =	129.000 mm
Vessel Thickness used	(T) =	10.179 mm
Nozzle Thickness used	(t) =	28.000 mm
T / t	=	0.364
d / t	=	10.000

$$\lambda = [(d/D) \cdot \sqrt{(D/T)}] = 2.823$$

Note: Re-pad thickness is added to nozzle thickness to simulate the Re-pad.

Nr/P	=	0.061
Mr/P	=	0.110
M0/P	=	0.034
N0/P	=	0.077
MrD/Mc	=	0.268
NrDL/Mc	=	0.096
M0d/Mc	=	0.081
N0DL/Mc	=	0.085



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)

Page 149 of 204

Nozzle Calcs.: N1-Tube Inlet

Nozl: 9 9:40am

Sep 9, 2026

MrD/M1 = 0.092
NrDL/M1 = 0.058
MØD/M1 = 0.026
NØDL/M1 = 0.090

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Stresses Normal to longitudinal plane)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Outplane Membrane (P)	5	5	5	5
Outplane Bending (P)	14	-14	14	-14
Outplane Membrane (Mc)	0	0	0	0
Outplane Bending (Mc)	0	0	0	0
Outplane Membrane (ML)	-8	-8	8	8
Outplane Bending (ML)	-14	14	14	-14
Normal Pressure Stress	21	24	21	24
Outplane Stress Summary	18	21	64	8

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Stresses parallel to longitudinal plane)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Inplane Membrane (P)	4	4	4	4
Inplane Bending (P)	45	-45	45	-45
Inplane Membrane (Mc)	0	0	0	0
Inplane Bending (Mc)	0	0	0	0
Inplane Membrane (ML)	-5	-5	5	5
Inplane Bending (ML)	-53	53	53	-53
Inplane Pressure Stress	10	10	10	10
Inplane Stress Summary	2	16	119	-78

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Shear stress normal to longitudinal plane)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Outplane Shear (Vc)	2	2	-2	-2
Outplane Shear (Vl)	0	0	0	0
Outplane Shear (Mt)	5	5	5	5
Shear Stress Summary	8	8	3	3

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Stress Intensities)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Two * Max Shear Stress	22	27	119	87

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Stresses Normal to circumferential plane)	Cu Left Outside	Cl Left Inside	Du Right Outside	Dl Right Inside
Outplane Membrane (P)	5	5	5	5
Outplane Bending (P)	14	-14	14	-14
Outplane Membrane (Mc)	-8	-8	8	8
Outplane Bending (Mc)	-46	46	46	-46
Outplane Membrane (ML)	0	0	0	0
Outplane Bending (ML)	0	0	0	0
Normal Pressure Stress	10	10	10	10



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 150 of 204

Nozzle Calcs.: N1-Tube Inlet

Nozl: 9 9:40am

Sep 9, 2026

Outplane Stress Summary	-23	40	85	-36
-------------------------	-----	----	----	-----

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Stresses parallel to circumferential plane)	Cu Left Outside	Cl Left Inside	Du Right Outside	Dl Right Inside
--	-----------------------	----------------------	------------------------	-----------------------

Inplane Membrane (P)	4	4	4	4
Inplane Bending (P)	45	-45	45	-45
Inplane Membrane (Mc)	-9	-9	9	9
Inplane Bending (Mc)	-153	153	153	-153
Inplane Membrane (ML)	0	0	0	0
Inplane Bending (ML)	0	0	0	0
Inplane Pressure Stress	21	24	21	24

Inplane Stress Summary	-91	127	234	-162
------------------------	-----	-----	-----	------

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Shear stress normal to circumferential plane)	Cu Left Outside	Cl Left Inside	Du Right Outside	Dl Right Inside
--	-----------------------	----------------------	------------------------	-----------------------

Outplane Shear (Vc)	0	0	0	0
Outplane Shear (Vl)	-2	-2	2	2
Torsional Shear (Mt)	5	5	5	5

Shear Stress Summary	3	3	8	8
----------------------	---	---	---	---

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Stress Intensities)	Cu Left Outside	Cl Left Inside	Du Right Outside	Dl Right Inside
---	-----------------------	----------------------	------------------------	-----------------------

Two * Max Shear Stress	91	127	235	162
------------------------	----	-----	-----	-----

WRC 297 Stress Summations per ASME Sec. VIII Div. 2:

Vessel Stress Summation at Vessel-Nozzle Junction (N./mm²):

Type of Stress Int. Location	Stress Values at							
	Au	Al	Bu	Bl	Cu	Cl	Du	Dl
Circ. Pm (SUS)	8	11	8	11	8	11	8	11
Circ. Pl (SUS)	-2	-2	6	6	-3	-3	5	5
Circ. Q (SUS)	-16	16	34	-34	-17	17	33	-33
Long. Pm (SUS)	4	4	4	4	4	4	4	4
Long. Pl (SUS)	-2	-2	4	4	1	1	3	3
Long. Q (SUS)	-13	13	29	-29	-20	20	38	-38
Shear Pm (SUS)	0	0	0	0	0	0	0	0
Shear Pl (SUS)	1	1	-1	-1	-1	-1	1	1
Shear Q (SUS)	4	4	4	4	4	4	4	4
Pm (SUS)	8.0	11.0	8.0	11.0	8.0	11.0	8.0	11.0
Pm+Pl (SUS)	6.2	9.1	14.2	17.1	6.0	8.3	13.2	16.1
Pm+Pl+Q (Total)	15.5	27.1	48.8	22.6	16.9	28.0	50.5	32.6

Vessel Stress Summation Comparison (N./mm²):



PV Elite 28 Licensee: SL User
 FileName : 161-C1-C2_(Stack) Page 151 of 204
 Nozzle Calcs.: N1-Tube Inlet Nozl: 9 9:40am Sep 9,2026

Type of Stress Int.	Max. S.I.	S.I. Allowable	Result
Pm (SUS)	11.00	118.00	Passed
Pm+Pl (SUS)	17.11	177.00	Passed
Pm+Pl+Q (TOTAL)	50.52	353.99	Passed

Because only sustained loads were specified, the Pm+Pl+Q allowable was 3 * Smh.

WRC 297 Stress Summations per ASME Sec. VIII Div. 2:

Vessel Stress Summation at Reinforcing Pad Edge (N./mm²):

Type of Stress Int. Location	Stress Values at							
	Au	Al	Bu	Bl	Cu	Cl	Du	Dl
Circ. Pm (SUS)	21	24	21	24	21	24	21	24
Circ. Pl (SUS)	-3	-3	13	13	-5	-5	13	13
Circ. Q (SUS)	0	0	28	-28	-108	108	198	-198
Long. Pm (SUS)	10	10	10	10	10	10	10	10
Long. Pl (SUS)	-1	-1	9	9	-3	-3	13	13
Long. Q (SUS)	-8	8	98	-98	-32	32	60	-60
Shear Pm (SUS)	0	0	0	0	0	0	0	0
Shear Pl (SUS)	2	2	-2	-2	-2	-2	2	2
Shear Q (SUS)	5	5	5	5	5	5	5	5
Pm (SUS)	21.0	24.0	21.0	24.0	21.0	24.0	21.0	24.0
Pm+Pl (SUS)	18.4	21.3	34.3	37.2	16.4	19.3	34.4	37.3
Pm+Pl+Q (Total)	22.0	26.3	117.2	88.2	92.1	127.1	232.3	161.4

Vessel Stress Summation Comparison (N./mm²):

Type of Stress Int.	Max. S.I.	S.I. Allowable	Result
Pm (SUS)	24.00	118.00	Passed
Pm+Pl (SUS)	37.28	177.00	Passed
Pm+Pl+Q (TOTAL)	232.33	353.99	Passed

Because only sustained loads were specified, the Pm+Pl+Q allowable was 3 * Smh.

WRC 297 Stress Summations per ASME Sec. VIII Div. 2:

Nozzle Stress Summation at Vessel-Nozzle Junction (N./mm²):

Type of Stress Int. Location	Stress Values at							
	Au	Al	Bu	Bl	Cu	Cl	Du	Dl
Circ. Pm (SUS)	11	14	11	14	11	14	11	14
Circ. Pl (SUS)	-2	-2	6	6	1	1	3	3
Circ. Q (SUS)	0	0	0	0	0	0	0	0
Long. Pm (SUS)	5	5	5	5	5	5	5	5
Long. Pl (SUS)	-30	-30	36	36	-30	-30	36	36
Long. Q (SUS)	-65	65	121	-121	-91	91	147	-147
Shear Pm (SUS)	0	0	0	0	0	0	0	0
Shear Pl (SUS)	4	4	-4	-4	-4	-4	4	4



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 152 of 204

Nozzle Calcs.: N1-Tube Inlet

Nozl: 9 9:40am

Sep 9, 2026

Shear Q (SUS)	14	14	14	14	14	14	14	14
Pm (SUS)	11.0	14.0	11.0	14.0	11.0	14.0	11.0	14.0
Pm+Pl (SUS)	34.9	37.9	41.6	41.7	37.9	40.8	41.6	41.6
Pm+Pl+Q (Total)	105.3	48.8	162.7	102.0	129.6	67.9	189.8	128.2

Nozzle Stress Summation Comparison (N./mm²):

Type of Stress Int.	Max. S.I.	S.I. Allowable	Result
Pm (SUS)	14.00	118.00	Passed
Pm+Pl (SUS)	41.74	177.00	Passed
Pm+Pl+Q (TOTAL)	189.84	353.99	Passed

*Because only sustained loads were specified, the Pm+Pl+Q allowable was 3 * Smh.*

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)

Page 153 of 204

Nozzle Calcs.: N3-Shell inlet

Nozl: 10

9:40am

Sep 9,2026

Input, Nozzle Desc: N3-Shell inlet

From: 40

Pressure for Reinforcement Calculations	P	2400.000	KPa.
Temperature for Internal Pressure	Temp	260	°C
Design External Pressure	Pext	103.42	KPa.
Temperature for External Pressure	Tempex	260	°C
Parent Material		SA-106 B	
Parent Allowable Stress at Temperature	Sv	118.00	N./mm ²
Parent Allowable Stress At Ambient	Sva	118.00	N./mm ²
Inside Diameter of Cylindrical Shell	D	188.95	mm
Design Length of Section	L	1200.0001	mm
Shell Finished (Minimum) Thickness	t	13.1794	mm
Shell Internal Corrosion Allowance	c	3.0000	mm
Shell External Corrosion Allowance	co	0.0000	mm
Distance from Bottom/Left Tangent		1105.97	mm
User Entered Minimum Design Metal Temperature		-12.00	°C

Type of Element Connected to the Parent : Nozzle

Material		SA-106 B	
Material UNS Number		K03006	
Material Specification/Type		Smls. pipe	
Allowable Stress at Temperature	Sn	118.00	N./mm ²
Allowable Stress At Ambient	Sna	118.00	N./mm ²
Diameter Basis (for tr calc only)		Outside	
Layout Angle		90.00	deg
Diameter		89.0000	mm
Size and Thickness Basis		Actual	
Actual Thickness	tn	11.0000	mm
Flange Material		SA-105	
Flange Type		Weld Neck Flange	
Corrosion Allowance	can	3.0000	mm
Joint Efficiency of Shell Seam at Nozzle	E1	1.00	
Joint Efficiency of Nozzle Neck	En	1.00	
Outside Projection	ho	200.0000	mm
Weld leg size between Nozzle and Pad/Shell	Wo	10.0000	mm
Groove weld depth between Nozzle and Vessel	Wgnv	11.0000	mm
Inside Projection	h	0.0000	mm
Weld leg size, Inside Element to Shell	Wi	0.0000	mm
Pad Material		SA-516 70	
Pad Allowable Stress at Temperature	Sp	137.60	N./mm ²
Pad Allowable Stress At Ambient	Spa	138.00	N./mm ²
Diameter of Pad along vessel surface	Dp	129.0000	mm
Thickness of Pad	te	12.0000	mm
Weld leg size between Pad and Shell	Wp	10.0000	mm
Groove weld depth between Pad and Nozzle	Wgpn	12.0000	mm
Reinforcing Pad Width		20.0000	mm
Flange Class		600	
Flange Grade		GR 1.1	

The Pressure Design option was Design Pressure + static head.



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)


Page 154 of 204

Nozzle Calcs.: N3-Shell inlet

Nozl: 10

9:40am

Sep 9, 2026



Reinforcement CALCULATION, Description: N3-Shell inlet

ASME Code, Section VIII, Div. 1, UG-37 to UG-45

Actual Outside Diameter Used in Calculation	89.000 mm.
Actual Thickness Used in Calculation	11.000 mm

Nozzle input data check completed without errors.

Reqd thk per UG-37(a) of Cylindrical Shell, tr [Int. Press]
 $= P \cdot R / (S_v \cdot E - 0.6 \cdot P)$ per UG-27 (c)(1)
 $= 2400 \cdot 97.5 / (118 \cdot 1 - 0.6 \cdot 2400)$
 $= 2.0072 \text{ mm}$

Reqd thk per UG-37(a) of Nozzle Wall, trn [Int. Press]
 $= P \cdot R_o / (S_n \cdot E + 0.4 \cdot P)$ per Appendix 1-1 (a)(1)
 $= 2400 \cdot 44.5 / (118 \cdot 1 + 0.4 \cdot 2400)$
 $= 0.8978 \text{ mm}$

Required Nozzle thickness under External Pressure per UG-28 : 0.4111 mm

UG-40, Limits of Reinforcement: [Internal Pressure]

Parallel to Vessel Wall (Diameter Limit)	D1	146.0000 mm
Parallel to Vessel Wall, opening length	d	73.0000 mm
Normal to Vessel Wall (Thickness Limit), pad side Tlwp		25.4486 mm

*Taking a UG-36(c)(3)(a) exemption for nozzle: N3-Shell inlet.
 This calculation is valid for nozzles that meet all the requirements of paragraph UG-36. Please check the Code carefully, especially for nozzles that are not isolated or do not meet Code spacing requirements. To force the computation of areas for small nozzles go to Tools->Configuration and check the box to force the UG-37 small nozzle area calculation.*

UG-45 Minimum Nozzle Neck Thickness Requirement: [Int. Press.]

Wall Thickness for Internal/External pressures	ta = 3.8978 mm
Wall Thickness per UG16(b),	tr16b = 4.5000 mm
Wall Thickness, shell/head, internal pressure	trb1 = 5.0072 mm
Wall Thickness	tb1 = max(trb1, tr16b) = 5.0072 mm
Wall Thickness	tb2 = max(trb2, tr16b) = 4.5000 mm
Wall Thickness per table UG-45	tb3 = 8.0200 mm

Determine Nozzle Thickness candidate [tb]:
 $= \min[tb3, \max(tb1, tb2)]$
 $= \min[8.02, \max(5.01, 4.5)]$
 $= 5.0072 \text{ mm}$

Minimum Wall Thickness of Nozzle Necks [tUG-45]:
 $= \max(ta, tb)$
 $= \max(3.9, 5.01)$
 $= 5.0072 \text{ mm}$

Available Nozzle Neck Thickness = 11.0000 mm -> OK



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)

Page 155 of 204

Nozzle Calcs.: N3-Shell inlet

Nozl: 10

9:40am

Sep 9, 2026

Stresses on Nozzle due to External and Pressure Loads per the ASME B31.3 Piping Code, (see 319.4.4 and 302.3.5):

Sustained :	49.2,	Allowable :	118.0 N./mm ²	Passed
Expansion :	0.0,	Allowable :	245.8 N./mm ²	Passed
Occasional :	4.9,	Allowable :	156.9 N./mm ²	Passed
Shear :	30.0,	Allowable :	82.6 N./mm ²	Passed

The number of cycles on this nozzle was assumed to be 7000 or less for the determination of the expansion stress allowable.

Nozzle Junction Minimum Design Metal Temperature (MDMT) Calculations:

Nozzle Neck to Flange Weld, min(Curve:B, Curve:A)

Govrn. thk, tg = 11, tr = 0.9, c = 3 mm, E* = 1

Thickness Ratio = $tr * E* / (tg - c) = 0.11$, Temp. Reduction = 78 °C

Min Metal Temp. w/o impact per UCS-66, Curve A	-5 °C
Min Metal Temp. at Required thickness (UCS 66.1)	-104 °C
Min Metal Temp. w/o impact per UG-20(f)	-29 °C

Nozzle Neck to Pad Weld for the Nozzle, Curve: B

Govrn. thk, tg = 11, tr = 0.9, c = 3 mm, E* = 1

Thickness Ratio = $tr * E* / (tg - c) = 0.11$, Temp. Reduction = 78 °C

Min Metal Temp. w/o impact per UCS-66, Curve B	-26 °C
Min Metal Temp. at Required thickness (UCS 66.1)	-104 °C
Min Metal Temp. w/o impact per UG-20(f)	-29 °C

Nozzle Neck to Pad Weld for Reinforcement pad, Curve: B

Govrn. thk, tg = 11, tr = 0.9, c = 3 mm, E* = 1

Thickness Ratio = $tr * E* / (tg - c) = 0.11$, Temp. Reduction = 78 °C

Min Metal Temp. w/o impact per UCS-66, Curve B	-26 °C
Min Metal Temp. at Required thickness (UCS 66.1)	-104 °C
Min Metal Temp. w/o impact per UG-20(f)	-29 °C

Shell to Pad Weld Junction at Pad OD, Curve: B

Govrn. thk, tg = 12, c = 3 mm, E* = 1

Thickness Ratio = $tr * E* / (tg - c) = 0.2$, Temp. Reduction = 78 °C

Attachment governing, Attachment stress = Shell stress per Code

Min Metal Temp. w/o impact per UCS-66, Curve B	-23 °C
Min Metal Temp. at Required thickness (UCS 66.1)	-104 °C
Min Metal Temp. w/o impact per UG-20(f)	-29 °C

Nozzle-Shell/Head Weld (UCS-66(a)1(b)), Curve: B

Govrn. thk, tg = 11, tr = 0.9, c = 3 mm, E* = 1

Thickness Ratio = $tr * E* / (tg - c) = 0.11$, Temp. Reduction = 78 °C

Min Metal Temp. w/o impact per UCS-66, Curve B	-26 °C
Min Metal Temp. at Required thickness (UCS 66.1)	-104 °C
Min Metal Temp. w/o impact per UG-20(f)	-29 °C

Gov. MDMT of the Nozzle	: -104 °C
Gov. MDMT of the Reinforcement Pad	: -104 °C
Gov. MDMT of the nozzle to shell joint welded assembly	: -104 °C

Flange MDMT including Temperature reduction per UCS-66.1:



PV Elite 28 Licensee: SL User
 FileName : 161-C1-C2 _(Stack) Page 156 of 204
 Nozzle Calcs.: N3-Shell inlet Nozl: 10 9:40am Sep 9,2026

Unadjusted MDMT of ASME B16.5/47 flanges per UCS-66(c) -18 °C
 Flange MDMT with Temp reduction per UCS-66(b)(1)(-b) -104 °C

Where the Stress Reduction Ratio per UCS-66(b)(1)(-b) is :
 Design Pressure/Ambient Rating = 2400.00/10200.00 = 0.235

Weld Size Calculations, Description: N3-Shell inlet

Intermediate Calc. for nozzle/shell Welds Tmin 8.0000 mm
 Intermediate Calc. for pad/shell Welds TminPad 12.0000 mm

Results Per UW-16.1:

	Required Thickness	Actual Thickness
Nozzle Weld	5.6000 = 0.7 * tmin.	7.0700 = 0.7 * Wo mm
Pad Weld	6.0000 = 0.5*TminPad	7.0700 = 0.7 * Wp mm

Skipping the nozzle attachment weld strength calculations. Per UW-15(b)(2) the nozzles exempted by UG-36(c)(3)(a) (small nozzles) do not require a weld strength check.

Maximum Allowable Pressure for this Nozzle at this Location:

Converged Maximum Allowable Pressure in the Operating case: 11594 KPa.

Note: The MAWP of this junction was limited by the parent Shell/Head.

The Drop for this Nozzle is : 11.1366 mm
 The Cut Length for this Nozzle is, Drop + Ho + H + T : 224.3161 mm

Input Echo, WRC297 Item 1, Description: N3-Shell inlet:

Diameter Basis for Cylindrical Shell	ID	
Shell Internal Corrosion Allowance	3.0000	mm
Shell External Corrosion Allowance	0.0000	mm
Shell Diameter	188.951	mm
Shell Thickness	13.1794	mm
Shell Stress Concentration Factor	1.000	
Vessel Material	SA-106 B	
Vessel Cold S.I. Allowable	Smc	118.00 N./mm ²
Vessel Hot S.I. Allowable	Smh	118.00 N./mm ²

See ASME VIII Div. 2, 4.1.6.3, for determination of the SPS allowable.

Diameter Basis for Nozzle	OD	
Nozzle Corrosion Allowance	3.0000	mm
Nozzle Diameter	89.000	mm
Nozzle Thickness	11.0000	mm
Nozzle Stress Concentration Factor	1.000	
Nozzle Material	SA-106 B	
Nozzle Cold S.I. Allowable	SNmc	118.00 N./mm ²
Nozzle Hot S.I. Allowable	SNmh	118.00 N./mm ²

See ASME VIII Div. 2, 4.1.6.3, for determination of the SPS allowable.

Diameter of Reinforcing Pad	129.000	mm
Thickness of Reinforcing Pad	12.0000	mm

Note:
 External Forces and Moments in WRC 107/537 Convention:
 These loads are assumed to be SUSained loads.

Design Internal Pressure	Dp	2400.00	KPa.
Radial Load	P	-734.25	Kgf
Circumferential Shear	Vc	530.29	Kgf
Longitudinal Shear	Vl	530.29	Kgf



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 157 of 204

Nozzle Calcs.: N3-Shell inlet

Nozl: 10

9:40am

Sep 9, 2026

Circumferential Moment	Mc	130.48	Kg-m.
Longitudinal Moment	Ml	130.48	Kg-m.
Torsional Moment	Mt	150.05	Kg-m.

Include Axial Pressure Thrust	No
Include Pressure Stress Indices per Div. 2	No
Local Loads applied at end of Nozzle/Attachment	No

*Warning - The ratio, Dv/Tv (16.337) is < 20
check the limitations of WRC bulletin 297.*

*Warning - The ratio, Dn/Tn (8.091) is < 10
check the limitations of WRC bulletin 297.*

Stress Computations at the Edge of the Nozzle:

Stress Attenuation Diameter (for Insert Plates) per WRC 297:

$$= \text{NozzleOD} + 2 \cdot 1.65 \cdot \sqrt{R_{\text{mean}}(t - c_a)}$$

$$= 89.0 + 2 \cdot 1.65 \cdot \sqrt{108.565(13.179 - 3.0)}$$

$$= 198.703 \text{ mm}$$

WRC 297 Curve Access Parameters:

Vessel Mean Diameter	(D) =	217.130 mm
Nozzle Outside Diameter	(d) =	89.000 mm
Vessel Thickness used	(T) =	22.179 mm
Nozzle Thickness used	(t) =	8.000 mm
T / t	=	2.772
d / t	=	11.125

$$\lambda = [(d/D) \cdot \sqrt{(D/T)}] = 1.282$$

Nr/P	=	0.144
Mr/P	=	0.118
M0/P	=	0.115
N0/P	=	0.184
MrD/Mc	=	0.184
NrDL/Mc	=	0.178
M0d/Mc	=	0.187
N0DL/Mc	=	0.055
MrD/Ml	=	0.147
NrDL/Ml	=	0.146
M0D/Ml	=	0.158
N0DL/Ml	=	0.173

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Stresses Normal to longitudinal plane)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Outplane Membrane (P)	2	2	2	2
Outplane Bending (P)	10	-10	10	-10
Outplane Membrane (Mc)	0	0	0	0
Outplane Bending (Mc)	0	0	0	0
Outplane Membrane (ML)	-5	-5	5	5
Outplane Bending (ML)	-27	27	27	-27
Normal Pressure Stress	9	11	9	11
Outplane Stress Summary	-10	27	54	-18

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Stresses parallel to longitudinal plane)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Inplane Membrane (P)	2	2	2	2



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)

Page 158 of 204

Nozzle Calcs.: N3-Shell inlet

Nozl: 10

9:40am

Sep 9, 2026

Inplane Bending (P)	10	-10	10	-10
Inplane Membrane (Mc)	0	0	0	0
Inplane Bending (Mc)	0	0	0	0
Inplane Membrane (ML)	-4	-4	4	4
Inplane Bending (ML)	-25	25	25	-25
Inplane Pressure Stress	4	4	4	4
Inplane Stress Summary	-12	18	47	-25

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE		Au	Al	Bu	Bl
(Shear stress normal to longitudinal plane)		Top Outside	Top Inside	Bottom Outside	Bottom Inside
Outplane Shear (Vc)	1	1	-1	-1	
Outplane Shear (Vl)	0	0	0	0	
Outplane Shear (Mt)	5	5	5	5	
Shear Stress Summary	7	7	3	3	

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE		Au	Al	Bu	Bl
(Stress Intensities)		Top Outside	Top Inside	Bottom Outside	Bottom Inside
Two * Max Shear Stress	18	30	56	26	

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE		Cu	Cl	Du	Dl
(Stresses Normal to circumferential plane)		Left Outside	Left Inside	Right Outside	Right Inside
Outplane Membrane (P)	2	2	2	2	
Outplane Bending (P)	10	-10	10	-10	
Outplane Membrane (Mc)	-1	-1	1	1	
Outplane Bending (Mc)	-32	32	32	-32	
Outplane Membrane (ML)	0	0	0	0	
Outplane Bending (ML)	0	0	0	0	
Normal Pressure Stress	4	4	4	4	
Outplane Stress Summary	-16	28	51	-33	

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE		Cu	Cl	Du	Dl
(Stresses parallel to circumferential plane)		Left Outside	Left Inside	Right Outside	Right Inside
Inplane Membrane (P)	2	2	2	2	
Inplane Bending (P)	10	-10	10	-10	
Inplane Membrane (Mc)	-5	-5	5	5	
Inplane Bending (Mc)	-32	32	32	-32	
Inplane Membrane (ML)	0	0	0	0	
Inplane Bending (ML)	0	0	0	0	
Inplane Pressure Stress	9	11	9	11	
Inplane Stress Summary	-15	30	59	-23	

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE		Cu	Cl	Du	Dl
(Shear stress normal to circumferential plane)		Left Outside	Left Inside	Right Outside	Right Inside
Outplane Shear (Vc)	0	0	0	0	
Outplane Shear (Vl)	-1	-1	1	1	
Torsional Shear (Mt)	5	5	5	5	



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)

Page 159 of 204

Nozzle Calcs.: N3-Shell inlet

Nozl: 10

9:40am

Sep 9, 2026

Shear Stress Summary	3	3	7	7
----------------------	---	---	---	---

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Stress Intensities)	Cu	C1	Du	D1
	Left	Left	Right	Right
	Outside	Inside	Outside	Inside
Two * Max Shear Stress	19	33	63	37

Nozzle Stresses (N./mm²):

LONGITUDINAL PLANE (Stresses in the hoop direction)	Au	A1	Bu	B1
	Top	Top	Bottom	Bottom
	Outside	Inside	Outside	Inside
Hoop Membrane (P)	2	2	2	2
Hoop Bending (P)	0	0	0	0
Hoop Membrane (Mc)	0	0	0	0
Hoop Bending (Mc)	0	0	0	0
Hoop Membrane (ML)	-5	-5	5	5
Hoop Bending (ML)	0	0	0	0
Hoop Pressure Stress	11	14	11	14
Hoop Stress Summary	9	12	19	22

Nozzle Stresses (N./mm²):

LONGITUDINAL PLANE (Stresses Normal to pipe cross-section)	Au	A1	Bu	B1
	Top	Top	Bottom	Bottom
	Outside	Inside	Outside	Inside
Axial Membrane (P)	3	3	3	3
Axial Bending (P)	30	-30	30	-30
Axial Membrane (Mc)	0	0	0	0
Axial Bending (Mc)	0	0	0	0
Axial Membrane (ML)	-33	-33	33	33
Axial Bending (ML)	-100	100	100	-100
Axial Pressure Stress	5	5	5	5
Axial Stress Summary	-93	45	174	-87

Nozzle Stresses (N./mm²):

LONGITUDINAL PLANE (Shear stress)	Au	A1	Bu	B1
	Outside	Inside	Outside	Inside
	Outside	Inside	Outside	Inside
Shear due to (Vc)	4	4	-4	-4
Shear due to (Vl)	0	0	0	0
Shear due to Torsion	14	14	14	14
Shear Stress Summary	19	19	10	10

Nozzle Stresses (N./mm²):

LONGITUDINAL PLANE (Stress Intensities)	Au	A1	Bu	B1
	Outside	Inside	Outside	Inside
	Outside	Inside	Outside	Inside
Two * Max Shear Stress	110	54	174	111

Nozzle Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Stresses in the hoop direction)	Cu	C1	Du	D1
	Left	Left	Right	Right
	Outside	Inside	Outside	Inside
Hoop Membrane (P)	2	2	2	2
Hoop Bending (P)	0	0	0	0
Hoop Membrane (Mc)	-1	-1	1	1
Hoop Bending (Mc)	0	0	0	0



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)

Page 160 of 204

Nozzle Calcs.: N3-Shell inlet

Nozl: 10

9:40am

Sep 9, 2026

Hoop Membrane (ML)	0	0	0	0
Hoop Bending (ML)	0	0	0	0
Hoop Pressure Stress	11	14	11	14

Hoop Stress Summary	12	15	16	19
---------------------	----	----	----	----

Nozzle Stresses (N./mm²):

CIRCUMFERENTIAL PLANE	Cu	Cl	Du	Dl
(Stresses Normal to	Left	Left	Right	Right
pipe cross-section)	Outside	Inside	Outside	Inside

Axial Membrane (P)	3	3	3	3
Axial Bending (P)	30	-30	30	-30
Axial Membrane (Mc)	-33	-33	33	33
Axial Bending (Mc)	-128	128	128	-128
Axial Membrane (ML)	0	0	0	0
Axial Bending (ML)	0	0	0	0
Axial Pressure Stress	5	5	5	5

Axial Stress Summary	-122	73	202	-116
----------------------	------	----	-----	------

Nozzle Stresses (N./mm²):

CIRCUMFERENTIAL PLANE	Cu	Cl	Du	Dl
(Shear stress)	Outside	Inside	Outside	Inside

Shear due to (Vc)	0	0	0	0
Shear due to (Vl)	-4	-4	4	4
Shear due to Torsion	14	14	14	14

Shear Stress Summary	10	10	19	19
----------------------	----	----	----	----

Nozzle Stresses (N./mm²):

CIRCUMFERENTIAL PLANE	Cu	Cl	Du	Dl
(Stress Intensities	Outside	Inside	Outside	Inside

Two * Max Shear Stress	136	75	204	140
------------------------	-----	----	-----	-----

Stress Computations at the Edge of the Reinforcing Pad:

Stress Attenuation Diameter (for Insert Plates) per WRC 297:

$$= \text{NozzleOD} + 2 \cdot 1.65 \cdot \sqrt{R_{\text{mean}}(t - ca)}$$

$$= 89.0 + 2 \cdot 1.65 \cdot \sqrt{102.565(13.179 - 3.0)}$$

$$= 195.629 \text{ mm}$$

WRC 297 Curve Access Parameters:

Vessel Mean Diameter	(D) =	205.130 mm
Nozzle Outside Diameter	(d) =	129.000 mm
Vessel Thickness used	(T) =	10.179 mm
Nozzle Thickness used	(t) =	28.000 mm
T / t	=	0.364
d / T	=	10.000

$$\lambda = [(d/D) \cdot \sqrt{(D/T)}] = 2.823$$

Note: Re-pad thickness is added to nozzle thickness to simulate the Re-pad.

Nr/P	=	0.061
Mr/P	=	0.110
M0/P	=	0.034
N0/P	=	0.077
MrD/Mc	=	0.268
NrDL/Mc	=	0.096
M0d/Mc	=	0.081



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)

Page 161 of 204

Nozzle Calcs.: N3-Shell inlet

Nozl: 10

9:40am

Sep 9, 2026

NØDL/Mc = 0.085
MrD/Ml = 0.092
NrDL/Ml = 0.058
MØD/Ml = 0.026
NØDL/Ml = 0.090

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Stresses Normal to longitudinal plane)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Outplane Membrane (P)	5	5	5	5
Outplane Bending (P)	14	-14	14	-14
Outplane Membrane (Mc)	0	0	0	0
Outplane Bending (Mc)	0	0	0	0
Outplane Membrane (ML)	-8	-8	8	8
Outplane Bending (ML)	-14	14	14	-14
Normal Pressure Stress	21	24	21	24
Outplane Stress Summary	18	21	64	8

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Stresses parallel to longitudinal plane)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Inplane Membrane (P)	4	4	4	4
Inplane Bending (P)	45	-45	45	-45
Inplane Membrane (Mc)	0	0	0	0
Inplane Bending (Mc)	0	0	0	0
Inplane Membrane (ML)	-5	-5	5	5
Inplane Bending (ML)	-53	53	53	-53
Inplane Pressure Stress	10	10	10	10
Inplane Stress Summary	2	16	119	-78

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Shear stress normal to longitudinal plane)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Outplane Shear (Vc)	2	2	-2	-2
Outplane Shear (Vl)	0	0	0	0
Outplane Shear (Mt)	5	5	5	5
Shear Stress Summary	8	8	3	3

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Stress Intensities)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Two * Max Shear Stress	22	27	119	87

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Stresses Normal to circumferential plane)	Cu Left Outside	Cl Left Inside	Du Right Outside	Dl Right Inside
Outplane Membrane (P)	5	5	5	5
Outplane Bending (P)	14	-14	14	-14
Outplane Membrane (Mc)	-8	-8	8	8
Outplane Bending (Mc)	-46	46	46	-46
Outplane Membrane (ML)	0	0	0	0
Outplane Bending (ML)	0	0	0	0



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)

Page 162 of 204

Nozzle Calcs.: N3-Shell inlet

Nozl: 10

9:40am

Sep 9,2026

Normal Pressure Stress	10	10	10	10
------------------------	----	----	----	----

Outplane Stress Summary	-23	40	85	-36
-------------------------	-----	----	----	-----

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Stresses parallel to circumferential plane)	Cu	Cl	Du	Dl
	Left Outside	Left Inside	Right Outside	Right Inside

Inplane Membrane (P)	4	4	4	4
Inplane Bending (P)	45	-45	45	-45
Inplane Membrane (Mc)	-9	-9	9	9
Inplane Bending (Mc)	-153	153	153	-153
Inplane Membrane (ML)	0	0	0	0
Inplane Bending (ML)	0	0	0	0
Inplane Pressure Stress	21	24	21	24

Inplane Stress Summary	-91	127	234	-162
------------------------	-----	-----	-----	------

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Shear stress normal to circumferential plane)	Cu	Cl	Du	Dl
	Left Outside	Left Inside	Right Outside	Right Inside

Outplane Shear (Vc)	0	0	0	0
Outplane Shear (Vl)	-2	-2	2	2
Torsional Shear (Mt)	5	5	5	5

Shear Stress Summary	3	3	8	8
----------------------	---	---	---	---

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Stress Intensities	Cu	Cl	Du	Dl
	Left Outside	Left Inside	Right Outside	Right Inside

Two * Max Shear Stress	91	127	235	162
------------------------	----	-----	-----	-----

WRC 297 Stress Summations per ASME Sec. VIII Div. 2:

Vessel Stress Summation at Vessel-Nozzle Junction (N./mm²):

Type of Stress Int. Location	Stress Values at							
	Au	Al	Bu	Bl	Cu	Cl	Du	Dl
Circ. Pm (SUS)	9	11	9	11	9	11	9	11
Circ. Pl (SUS)	-3	-3	7	7	-3	-3	7	7
Circ. Q (SUS)	-17	17	37	-37	-22	22	42	-42
Long. Pm (SUS)	4	4	4	4	4	4	4	4
Long. Pl (SUS)	-2	-2	6	6	1	1	3	3
Long. Q (SUS)	-15	15	35	-35	-22	22	42	-42
Shear Pm (SUS)	0	0	0	0	0	0	0	0
Shear Pl (SUS)	1	1	-1	-1	-1	-1	1	1
Shear Q (SUS)	5	5	5	5	5	5	5	5
Pm (SUS)	9.0	11.0	9.0	11.0	9.0	11.0	9.0	11.0
Pm+Pl (SUS)	6.2	8.2	16.2	18.1	6.6	8.3	16.1	18.1
Pm+Pl+Q (Total)	18.1	28.2	54.7	27.0	20.5	32.8	61.0	37.6

Vessel Stress Summation Comparison (N./mm²):



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)

Page 163 of 204

Nozzle Calcs.: N3-Shell inlet

Nozl: 10

9:40am

Sep 9, 2026

Type of Stress Int.	Max. S.I.	S.I. Allowable	Result
Pm (SUS)	11.00	118.00	Passed
Pm+Pl (SUS)	18.12	177.00	Passed
Pm+Pl+Q (TOTAL)	61.00	353.99	Passed

Because only sustained loads were specified, the Pm+Pl+Q allowable was 3 * Smh.

WRC 297 Stress Summations per ASME Sec. VIII Div. 2:

Vessel Stress Summation at Reinforcing Pad Edge (N./mm²):

Type of Stress Int. Location	Stress Values at							
	Au	Al	Bu	Bl	Cu	Cl	Du	Dl
Circ. Pm (SUS)	21	24	21	24	21	24	21	24
Circ. Pl (SUS)	-3	-3	13	13	-5	-5	13	13
Circ. Q (SUS)	0	0	28	-28	-108	108	198	-198
Long. Pm (SUS)	10	10	10	10	10	10	10	10
Long. Pl (SUS)	-1	-1	9	9	-3	-3	13	13
Long. Q (SUS)	-8	8	98	-98	-32	32	60	-60
Shear Pm (SUS)	0	0	0	0	0	0	0	0
Shear Pl (SUS)	2	2	-2	-2	-2	-2	2	2
Shear Q (SUS)	5	5	5	5	5	5	5	5
Pm (SUS)	21.0	24.0	21.0	24.0	21.0	24.0	21.0	24.0
Pm+Pl (SUS)	18.4	21.3	34.3	37.2	16.4	19.3	34.4	37.3
Pm+Pl+Q (Total)	22.0	26.3	117.2	88.2	92.1	127.1	232.3	161.4

Vessel Stress Summation Comparison (N./mm²):

Type of Stress Int.	Max. S.I.	S.I. Allowable	Result
Pm (SUS)	24.00	118.00	Passed
Pm+Pl (SUS)	37.28	177.00	Passed
Pm+Pl+Q (TOTAL)	232.33	353.99	Passed

Because only sustained loads were specified, the Pm+Pl+Q allowable was 3 * Smh.

WRC 297 Stress Summations per ASME Sec. VIII Div. 2:

Nozzle Stress Summation at Vessel-Nozzle Junction (N./mm²):

Type of Stress Int. Location	Stress Values at							
	Au	Al	Bu	Bl	Cu	Cl	Du	Dl
Circ. Pm (SUS)	11	14	11	14	11	14	11	14
Circ. Pl (SUS)	-3	-3	7	7	1	1	3	3
Circ. Q (SUS)	0	0	0	0	0	0	0	0
Long. Pm (SUS)	5	5	5	5	5	5	5	5
Long. Pl (SUS)	-30	-30	36	36	-30	-30	36	36
Long. Q (SUS)	-70	70	130	-130	-98	98	158	-158
Shear Pm (SUS)	0	0	0	0	0	0	0	0



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)

Page 164 of 204

Nozzle Calcs.: N3-Shell inlet

Nozl: 10

9:40am

Sep 9, 2026

Shear P1 (SUS)	4	4	-4	-4	-4	-4	4	4
Shear Q (SUS)	14	14	14	14	14	14	14	14
Pm (SUS)	11.0	14.0	11.0	14.0	11.0	14.0	11.0	14.0
Pm+P1 (SUS)	34.0	36.9	41.7	41.8	37.9	40.8	41.6	41.6
Pm+P1+Q (Total)	109.1	52.8	171.7	111.8	136.5	74.7	200.7	138.8

Nozzle Stress Summation Comparison (N./mm²):

Type of Stress Int.	Max. S.I.	S.I. Allowable	Result
Pm (SUS)	14.00	118.00	Passed
Pm+P1 (SUS)	41.77	177.00	Passed
Pm+P1+Q (TOTAL)	200.74	353.99	Passed

Because only sustained loads were specified, the Pm+P1+Q allowable was 3 * Smh.

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)

Page 165 of 204

Nozzle Calcs.: N4-Shell outlet

Nozl: 11

9:40am

Sep 9, 2026

Input, Nozzle Desc: N4-Shell outlet

From: 40

Pressure for Reinforcement Calculations	P	2401.813	KPa.
Temperature for Internal Pressure	Temp	260	°C
Design External Pressure	Pext	103.42	KPa.
Temperature for External Pressure	Tempex	260	°C
Parent Material		SA-106 B	
Parent Allowable Stress at Temperature	Sv	118.00	N./mm ²
Parent Allowable Stress At Ambient	Sva	118.00	N./mm ²
Inside Diameter of Cylindrical Shell	D	188.95	mm
Design Length of Section	L	1135.0001	mm
Shell Finished (Minimum) Thickness	t	13.1794	mm
Shell Internal Corrosion Allowance	c	3.0000	mm
Shell External Corrosion Allowance	co	0.0000	mm
Distance from Bottom/Left Tangent		5755.98	mm
User Entered Minimum Design Metal Temperature		-12.00	°C

Type of Element Connected to the Parent : Nozzle

Material		SA-106 B	
Material UNS Number		K03006	
Material Specification/Type		Smls. pipe	
Allowable Stress at Temperature	Sn	118.00	N./mm ²
Allowable Stress At Ambient	Sna	118.00	N./mm ²
Diameter Basis (for tr calc only)		Outside	
Layout Angle		270.00	deg
Diameter		89.0000	mm
Size and Thickness Basis		Actual	
Actual Thickness	tn	11.0000	mm
Flange Material		SA-105	
Flange Type		Weld Neck Flange	
Corrosion Allowance	can	3.0000	mm
Joint Efficiency of Shell Seam at Nozzle	E1	1.00	
Joint Efficiency of Nozzle Neck	En	1.00	
Outside Projection	ho	200.0000	mm
Weld leg size between Nozzle and Pad/Shell	Wo	10.0000	mm
Groove weld depth between Nozzle and Vessel	Wgnv	11.0000	mm
Inside Projection	h	0.0000	mm
Weld leg size, Inside Element to Shell	Wi	0.0000	mm
Pad Material		SA-516 70	
Pad Allowable Stress at Temperature	Sp	137.60	N./mm ²
Pad Allowable Stress At Ambient	Spa	138.00	N./mm ²
Diameter of Pad along vessel surface	Dp	129.0000	mm
Thickness of Pad	te	12.0000	mm
Weld leg size between Pad and Shell	Wp	10.0000	mm
Groove weld depth between Pad and Nozzle	Wgpn	12.0000	mm
Reinforcing Pad Width		20.0000	mm
Flange Class		600	
Flange Grade		GR 1.1	

The Pressure Design option was Design Pressure + static head.



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)


Page 166 of 204

Nozzle Calcs.: N4-Shell outlet

Nozl: 11

9:40am

Sep 9,2026



Reinforcement CALCULATION, Description: N4-Shell outlet

ASME Code, Section VIII, Div. 1, UG-37 to UG-45

Actual Outside Diameter Used in Calculation	89.000 mm.
Actual Thickness Used in Calculation	11.000 mm

Nozzle input data check completed without errors.

Reqd thk per UG-37(a) of Cylindrical Shell, tr [Int. Press]
 $= P \cdot R / (S_v \cdot E - 0.6 \cdot P)$ per UG-27 (c)(1)
 $= 2402 \cdot 97.5 / (118 \cdot 1 - 0.6 \cdot 2402)$
 $= 2.0087 \text{ mm}$

Reqd thk per UG-37(a) of Nozzle Wall, trn [Int. Press]
 $= P \cdot R_o / (S_n \cdot E + 0.4 \cdot P)$ per Appendix 1-1 (a)(1)
 $= 2402 \cdot 44.5 / (118 \cdot 1 + 0.4 \cdot 2402)$
 $= 0.8985 \text{ mm}$

Required Nozzle thickness under External Pressure per UG-28 : 0.4111 mm

UG-40, Limits of Reinforcement: [Internal Pressure]

Parallel to Vessel Wall (Diameter Limit)	D1	146.0000 mm
Parallel to Vessel Wall, opening length	d	73.0000 mm
Normal to Vessel Wall (Thickness Limit), pad side Tlwp		25.4486 mm

*Taking a UG-36(c)(3)(a) exemption for nozzle: N4-Shell outlet.
 This calculation is valid for nozzles that meet all the requirements of paragraph UG-36. Please check the Code carefully, especially for nozzles that are not isolated or do not meet Code spacing requirements. To force the computation of areas for small nozzles go to Tools->Configuration and check the box to force the UG-37 small nozzle area calculation.*

UG-45 Minimum Nozzle Neck Thickness Requirement: [Int. Press.]

Wall Thickness for Internal/External pressures	ta = 3.8985 mm
Wall Thickness per UG16(b),	tr16b = 4.5000 mm
Wall Thickness, shell/head, internal pressure	trb1 = 5.0087 mm
Wall Thickness	tb1 = max(trb1, tr16b) = 5.0087 mm
Wall Thickness	tb2 = max(trb2, tr16b) = 4.5000 mm
Wall Thickness per table UG-45	tb3 = 8.0200 mm

Determine Nozzle Thickness candidate [tb]:
 $= \min[tb3, \max(tb1, tb2)]$
 $= \min[8.02, \max(5.01, 4.5)]$
 $= 5.0087 \text{ mm}$

Minimum Wall Thickness of Nozzle Necks [tUG-45]:
 $= \max(ta, tb)$
 $= \max(3.9, 5.01)$
 $= 5.0087 \text{ mm}$

Available Nozzle Neck Thickness = 11.0000 mm -> OK



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)

Page 167 of 204

Nozzle Calcs.: N4-Shell outlet

Nozl: 11

9:40am

Sep 9, 2026

Stresses on Nozzle due to External and Pressure Loads per the ASME B31.3 Piping Code, (see 319.4.4 and 302.3.5):

Sustained	:	49.2,	Allowable	:	118.0 N./mm ²	Passed
Expansion	:	0.0,	Allowable	:	245.8 N./mm ²	Passed
Occasional	:	4.9,	Allowable	:	156.9 N./mm ²	Passed
Shear	:	30.0,	Allowable	:	82.6 N./mm ²	Passed

The number of cycles on this nozzle was assumed to be 7000 or less for the determination of the expansion stress allowable.

Nozzle Junction Minimum Design Metal Temperature (MDMT) Calculations:

Nozzle Neck to Flange Weld, min(Curve:B, Curve:A)

Govrn. thk, tg = 11, tr = 0.9, c = 3 mm, E* = 1

Thickness Ratio = $tr * E^* / (tg - c) = 0.11$, Temp. Reduction = 78 °C

Min Metal Temp. w/o impact per UCS-66, Curve A	-5 °C
Min Metal Temp. at Required thickness (UCS 66.1)	-104 °C
Min Metal Temp. w/o impact per UG-20(f)	-29 °C

Nozzle Neck to Pad Weld for the Nozzle, Curve: B

Govrn. thk, tg = 11, tr = 0.9, c = 3 mm, E* = 1

Thickness Ratio = $tr * E^* / (tg - c) = 0.11$, Temp. Reduction = 78 °C

Min Metal Temp. w/o impact per UCS-66, Curve B	-26 °C
Min Metal Temp. at Required thickness (UCS 66.1)	-104 °C
Min Metal Temp. w/o impact per UG-20(f)	-29 °C

Nozzle Neck to Pad Weld for Reinforcement pad, Curve: B

Govrn. thk, tg = 11, tr = 0.9, c = 3 mm, E* = 1

Thickness Ratio = $tr * E^* / (tg - c) = 0.11$, Temp. Reduction = 78 °C

Min Metal Temp. w/o impact per UCS-66, Curve B	-26 °C
Min Metal Temp. at Required thickness (UCS 66.1)	-104 °C
Min Metal Temp. w/o impact per UG-20(f)	-29 °C

Shell to Pad Weld Junction at Pad OD, Curve: B

Govrn. thk, tg = 12, c = 3 mm, E* = 1

Thickness Ratio = $tr * E^* / (tg - c) = 0.2$, Temp. Reduction = 78 °C

Attachment governing, Attachment stress = Shell stress per Code

Min Metal Temp. w/o impact per UCS-66, Curve B	-23 °C
Min Metal Temp. at Required thickness (UCS 66.1)	-104 °C
Min Metal Temp. w/o impact per UG-20(f)	-29 °C

Nozzle-Shell/Head Weld (UCS-66(a)1(b)), Curve: B

Govrn. thk, tg = 11, tr = 0.9, c = 3 mm, E* = 1

Thickness Ratio = $tr * E^* / (tg - c) = 0.11$, Temp. Reduction = 78 °C

Min Metal Temp. w/o impact per UCS-66, Curve B	-26 °C
Min Metal Temp. at Required thickness (UCS 66.1)	-104 °C
Min Metal Temp. w/o impact per UG-20(f)	-29 °C

Gov. MDMT of the Nozzle	: -104 °C
Gov. MDMT of the Reinforcement Pad	: -104 °C
Gov. MDMT of the nozzle to shell joint welded assembly	: -104 °C

Flange MDMT including Temperature reduction per UCS-66.1:



PV Elite 28 Licensee: SL User
 FileName : 161-C1-C2_(Stack) Page 168 of 204
 Nozzle Calcs.: N4-Shell outlet Nozl: 11 9:40am Sep 9,2026

Unadjusted MDMT of ASME B16.5/47 flanges per UCS-66(c) -18 °C
 Flange MDMT with Temp reduction per UCS-66(b)(1)(-b) -104 °C

Where the Stress Reduction Ratio per UCS-66(b)(1)(-b) is :
 Design Pressure/Ambient Rating = $2401.81/10200.00 = 0.235$

Weld Size Calculations, Description: N4-Shell outlet

Intermediate Calc. for nozzle/shell Welds Tmin 8.0000 mm
 Intermediate Calc. for pad/shell Welds TminPad 12.0000 mm

Results Per UW-16.1:

	Required Thickness	Actual Thickness
Nozzle Weld	$5.6000 = 0.7 * t_{min}$	$7.0700 = 0.7 * W_o$ mm
Pad Weld	$6.0000 = 0.5 * T_{minPad}$	$7.0700 = 0.7 * W_p$ mm

Skipping the nozzle attachment weld strength calculations. Per UW-15(b)(2) the nozzles exempted by UG-36(c)(3)(a) (small nozzles) do not require a weld strength check.

Maximum Allowable Pressure for this Nozzle at this Location:

Converged Maximum Allowable Pressure in the Operating case: 11594 KPa.

Note: The MAWP of this junction was limited by the parent Shell/Head.

The Drop for this Nozzle is : 11.1366 mm
 The Cut Length for this Nozzle is, Drop + Ho + H + T : 224.3161 mm

Input Echo, WRC297 Item 1, Description: N4-Shell outle:

Diameter Basis for Cylindrical Shell	ID	
Shell Internal Corrosion Allowance	3.0000	mm
Shell External Corrosion Allowance	0.0000	mm
Shell Diameter	188.951	mm
Shell Thickness	13.1794	mm
Shell Stress Concentration Factor	1.000	
Vessel Material	SA-106 B	
Vessel Cold S.I. Allowable	Smc	118.00 N./mm ²
Vessel Hot S.I. Allowable	Smh	118.00 N./mm ²

See ASME VIII Div. 2, 4.1.6.3, for determination of the SPS allowable.

Diameter Basis for Nozzle	OD	
Nozzle Corrosion Allowance	3.0000	mm
Nozzle Diameter	89.000	mm
Nozzle Thickness	11.0000	mm
Nozzle Stress Concentration Factor	1.000	
Nozzle Material	SA-106 B	
Nozzle Cold S.I. Allowable	SNmc	118.00 N./mm ²
Nozzle Hot S.I. Allowable	SNmh	118.00 N./mm ²

See ASME VIII Div. 2, 4.1.6.3, for determination of the SPS allowable.

Diameter of Reinforcing Pad	129.000	mm
Thickness of Reinforcing Pad	12.0000	mm

Note:
 External Forces and Moments in WRC 107/537 Convention:
 These loads are assumed to be SUSTAINED loads.

Design Internal Pressure	Dp	2401.81	KPa.
Radial Load	P	-734.25	Kgf
Circumferential Shear	Vc	530.29	Kgf
Longitudinal Shear	Vl	530.29	Kgf



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 169 of 204

Nozzle Calcs.: N4-Shell outlet

Nozl: 11 9:40am Sep 9, 2026

Circumferential Moment	Mc	130.48	Kg-m.
Longitudinal Moment	Ml	130.48	Kg-m.
Torsional Moment	Mt	150.05	Kg-m.

Include Axial Pressure Thrust	No
Include Pressure Stress Indices per Div. 2	No
Local Loads applied at end of Nozzle/Attachment	No

*Warning - The ratio, Dv/Tv (16.337) is < 20
check the limitations of WRC bulletin 297.*

*Warning - The ratio, Dn/Tn (8.091) is < 10
check the limitations of WRC bulletin 297.*

Stress Computations at the Edge of the Nozzle:

Stress Attenuation Diameter (for Insert Plates) per WRC 297:

$$= \text{NozzleOD} + 2 \cdot 1.65 \cdot \sqrt{R_{\text{mean}}(t - ca)}$$

$$= 89.0 + 2 \cdot 1.65 \cdot \sqrt{108.565(13.179 - 3.0)}$$

$$= 198.703 \text{ mm}$$

WRC 297 Curve Access Parameters:

Vessel Mean Diameter	(D) =	217.130 mm
Nozzle Outside Diameter	(d) =	89.000 mm
Vessel Thickness used	(T) =	22.179 mm
Nozzle Thickness used	(t) =	8.000 mm
T / t	=	2.772
d / t	=	11.125

$$\lambda = [(d/D) \cdot \sqrt{(D/T)}] = 1.282$$

Nr/P	=	0.144
Mr/P	=	0.118
M0/P	=	0.115
N0/P	=	0.184
MrD/Mc	=	0.184
NrDL/Mc	=	0.178
M0d/Mc	=	0.187
N0DL/Mc	=	0.055
MrD/Ml	=	0.147
NrDL/Ml	=	0.146
M0D/Ml	=	0.158
N0DL/Ml	=	0.173

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Stresses Normal to longitudinal plane)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Outplane Membrane (P)	2	2	2	2
Outplane Bending (P)	10	-10	10	-10
Outplane Membrane (Mc)	0	0	0	0
Outplane Bending (Mc)	0	0	0	0
Outplane Membrane (Ml)	-5	-5	5	5
Outplane Bending (Ml)	-27	27	27	-27
Normal Pressure Stress	9	11	9	11
Outplane Stress Summary	-10	27	54	-18

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Stresses parallel to longitudinal plane)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Inplane Membrane (P)	2	2	2	2



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)

Page 170 of 204

Nozzle Calcs.: N4-Shell outlet

Nozl: 11 9:40am

Sep 9, 2026

Inplane Bending (P)	10	-10	10	-10
Inplane Membrane (Mc)	0	0	0	0
Inplane Bending (Mc)	0	0	0	0
Inplane Membrane (ML)	-4	-4	4	4
Inplane Bending (ML)	-25	25	25	-25
Inplane Pressure Stress	4	4	4	4
Inplane Stress Summary	-12	18	47	-25

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE		Au	Al	Bu	Bl
(Shear stress normal to longitudinal plane)		Top Outside	Top Inside	Bottom Outside	Bottom Inside
Outplane Shear (Vc)	1	1	-1	-1	
Outplane Shear (Vl)	0	0	0	0	
Outplane Shear (Mt)	5	5	5	5	
Shear Stress Summary	7	7	3	3	

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE		Au	Al	Bu	Bl
(Stress Intensities)		Top Outside	Top Inside	Bottom Outside	Bottom Inside
Two * Max Shear Stress	18	30	56	26	

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE		Cu	Cl	Du	Dl
(Stresses Normal to circumferential plane)		Left Outside	Left Inside	Right Outside	Right Inside
Outplane Membrane (P)	2	2	2	2	
Outplane Bending (P)	10	-10	10	-10	
Outplane Membrane (Mc)	-1	-1	1	1	
Outplane Bending (Mc)	-32	32	32	-32	
Outplane Membrane (ML)	0	0	0	0	
Outplane Bending (ML)	0	0	0	0	
Normal Pressure Stress	4	4	4	4	
Outplane Stress Summary	-16	28	51	-33	

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE		Cu	Cl	Du	Dl
(Stresses parallel to circumferential plane)		Left Outside	Left Inside	Right Outside	Right Inside
Inplane Membrane (P)	2	2	2	2	
Inplane Bending (P)	10	-10	10	-10	
Inplane Membrane (Mc)	-5	-5	5	5	
Inplane Bending (Mc)	-32	32	32	-32	
Inplane Membrane (ML)	0	0	0	0	
Inplane Bending (ML)	0	0	0	0	
Inplane Pressure Stress	9	11	9	11	
Inplane Stress Summary	-15	30	59	-23	

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE		Cu	Cl	Du	Dl
(Shear stress normal to circumferential plane)		Left Outside	Left Inside	Right Outside	Right Inside
Outplane Shear (Vc)	0	0	0	0	
Outplane Shear (Vl)	-1	-1	1	1	
Torsional Shear (Mt)	5	5	5	5	



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)

Page 171 of 204

Nozzle Calcs.: N4-Shell outlet

Nozl: 11 9:40am

Sep 9,2026

Shear Stress Summary	3	3	7	7
----------------------	---	---	---	---

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Stress Intensities)	Cu	C1	Du	D1
	Left	Left	Right	Right
	Outside	Inside	Outside	Inside
Two * Max Shear Stress	19	33	63	37

Nozzle Stresses (N./mm²):

LONGITUDINAL PLANE (Stresses in the hoop direction)	Au	A1	Bu	B1
	Top	Top	Bottom	Bottom
	Outside	Inside	Outside	Inside
Hoop Membrane (P)	2	2	2	2
Hoop Bending (P)	0	0	0	0
Hoop Membrane (Mc)	0	0	0	0
Hoop Bending (Mc)	0	0	0	0
Hoop Membrane (ML)	-5	-5	5	5
Hoop Bending (ML)	0	0	0	0
Hoop Pressure Stress	11	14	11	14
Hoop Stress Summary	9	12	19	22

Nozzle Stresses (N./mm²):

LONGITUDINAL PLANE (Stresses Normal to pipe cross-section)	Au	A1	Bu	B1
	Top	Top	Bottom	Bottom
	Outside	Inside	Outside	Inside
Axial Membrane (P)	3	3	3	3
Axial Bending (P)	30	-30	30	-30
Axial Membrane (Mc)	0	0	0	0
Axial Bending (Mc)	0	0	0	0
Axial Membrane (ML)	-33	-33	33	33
Axial Bending (ML)	-100	100	100	-100
Axial Pressure Stress	5	5	5	5
Axial Stress Summary	-93	45	174	-87

Nozzle Stresses (N./mm²):

LONGITUDINAL PLANE (Shear stress)	Au	A1	Bu	B1
	Outside	Inside	Outside	Inside
Shear due to (Vc)	4	4	-4	-4
Shear due to (Vl)	0	0	0	0
Shear due to Torsion	14	14	14	14
Shear Stress Summary	19	19	10	10

Nozzle Stresses (N./mm²):

LONGITUDINAL PLANE (Stress Intensities)	Au	A1	Bu	B1
	Outside	Inside	Outside	Inside
Two * Max Shear Stress	110	54	174	111

Nozzle Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Stresses in the hoop direction)	Cu	C1	Du	D1
	Left	Left	Right	Right
	Outside	Inside	Outside	Inside
Hoop Membrane (P)	2	2	2	2
Hoop Bending (P)	0	0	0	0
Hoop Membrane (Mc)	-1	-1	1	1
Hoop Bending (Mc)	0	0	0	0



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)

Page 172 of 204

Nozzle Calcs.: N4-Shell outlet

Nozl: 11 9:40am

Sep 9, 2026

Hoop Membrane (ML)	0	0	0	0
Hoop Bending (ML)	0	0	0	0
Hoop Pressure Stress	11	14	11	14

Hoop Stress Summary	12	15	16	19
---------------------	----	----	----	----

Nozzle Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Stresses Normal to pipe cross-section)	Cu Left Outside	Cl Left Inside	Du Right Outside	Dl Right Inside
---	-----------------------	----------------------	------------------------	-----------------------

Axial Membrane (P)	3	3	3	3
Axial Bending (P)	30	-30	30	-30
Axial Membrane (Mc)	-33	-33	33	33
Axial Bending (Mc)	-128	128	128	-128
Axial Membrane (ML)	0	0	0	0
Axial Bending (ML)	0	0	0	0
Axial Pressure Stress	5	5	5	5

Axial Stress Summary	-122	73	202	-116
----------------------	------	----	-----	------

Nozzle Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Shear stress)	Cu Outside	Cl Inside	Du Outside	Dl Inside
---	---------------	--------------	---------------	--------------

Shear due to (Vc)	0	0	0	0
Shear due to (Vl)	-4	-4	4	4
Shear due to Torsion	14	14	14	14

Shear Stress Summary	10	10	19	19
----------------------	----	----	----	----

Nozzle Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Stress Intensities)	Cu Outside	Cl Inside	Du Outside	Dl Inside
---	---------------	--------------	---------------	--------------

Two * Max Shear Stress	136	75	204	140
------------------------	-----	----	-----	-----

Stress Computations at the Edge of the Reinforcing Pad:

Stress Attenuation Diameter (for Insert Plates) per WRC 297:

$$= \text{NozzleOD} + 2 \cdot 1.65 \cdot \sqrt{\text{Rmean}(t - ca)}$$

$$= 89.0 + 2 \cdot 1.65 \cdot \sqrt{102.565(13.179 - 3.0)}$$

$$= 195.629 \text{ mm}$$

WRC 297 Curve Access Parameters:

Vessel Mean Diameter	(D) =	205.130 mm
Nozzle Outside Diameter	(d) =	129.000 mm
Vessel Thickness used	(T) =	10.179 mm
Nozzle Thickness used	(t) =	28.000 mm
T / t	=	0.364
d / T	=	10.000

$$\lambda = [(d/D) \cdot \sqrt{(D/T)}] = 2.823$$

Note: Re-pad thickness is added to nozzle thickness to simulate the Re-pad.

Nr/P	=	0.061
Mr/P	=	0.110
M0/P	=	0.034
N0/P	=	0.077
MrD/Mc	=	0.268
NrDL/Mc	=	0.096
M0d/Mc	=	0.081



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)

Page 173 of 204

Nozzle Calcs.: N4-Shell outlet

Nozl: 11

9:40am

Sep 9, 2026

NØDL/Mc = 0.085
MrD/Ml = 0.092
NrDL/Ml = 0.058
MØD/Ml = 0.026
NØDL/Ml = 0.090

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Stresses Normal to longitudinal plane)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Outplane Membrane (P)	5	5	5	5
Outplane Bending (P)	14	-14	14	-14
Outplane Membrane (Mc)	0	0	0	0
Outplane Bending (Mc)	0	0	0	0
Outplane Membrane (ML)	-8	-8	8	8
Outplane Bending (ML)	-14	14	14	-14
Normal Pressure Stress	21	24	21	24
Outplane Stress Summary	18	21	64	8

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Stresses parallel to longitudinal plane)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Inplane Membrane (P)	4	4	4	4
Inplane Bending (P)	45	-45	45	-45
Inplane Membrane (Mc)	0	0	0	0
Inplane Bending (Mc)	0	0	0	0
Inplane Membrane (ML)	-5	-5	5	5
Inplane Bending (ML)	-53	53	53	-53
Inplane Pressure Stress	10	10	10	10
Inplane Stress Summary	2	16	119	-78

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Shear stress normal to longitudinal plane)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Outplane Shear (Vc)	2	2	-2	-2
Outplane Shear (Vl)	0	0	0	0
Outplane Shear (Mt)	5	5	5	5
Shear Stress Summary	8	8	3	3

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Stress Intensities)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Two * Max Shear Stress	22	27	119	87

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Stresses Normal to circumferential plane)	Cu Left Outside	Cl Left Inside	Du Right Outside	Dl Right Inside
Outplane Membrane (P)	5	5	5	5
Outplane Bending (P)	14	-14	14	-14
Outplane Membrane (Mc)	-8	-8	8	8
Outplane Bending (Mc)	-46	46	46	-46
Outplane Membrane (ML)	0	0	0	0
Outplane Bending (ML)	0	0	0	0



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)

Page 174 of 204

Nozzle Calcs.: N4-Shell outlet

Nozl: 11 9:40am

Sep 9,2026

Normal Pressure Stress	10	10	10	10
------------------------	----	----	----	----

Outplane Stress Summary	-23	40	85	-36
-------------------------	-----	----	----	-----

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Stresses parallel to circumferential plane)	Cu	Cl	Du	Dl
	Left Outside	Left Inside	Right Outside	Right Inside

Inplane Membrane (P)	4	4	4	4
Inplane Bending (P)	45	-45	45	-45
Inplane Membrane (Mc)	-9	-9	9	9
Inplane Bending (Mc)	-153	153	153	-153
Inplane Membrane (ML)	0	0	0	0
Inplane Bending (ML)	0	0	0	0
Inplane Pressure Stress	21	24	21	24

Inplane Stress Summary	-91	127	234	-161
------------------------	-----	-----	-----	------

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Shear stress normal to circumferential plane)	Cu	Cl	Du	Dl
	Left Outside	Left Inside	Right Outside	Right Inside

Outplane Shear (Vc)	0	0	0	0
Outplane Shear (Vl)	-2	-2	2	2
Torsional Shear (Mt)	5	5	5	5

Shear Stress Summary	3	3	8	8
----------------------	---	---	---	---

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Stress Intensities	Cu	Cl	Du	Dl
	Left Outside	Left Inside	Right Outside	Right Inside

Two * Max Shear Stress	91	127	235	162
------------------------	----	-----	-----	-----

WRC 297 Stress Summations per ASME Sec. VIII Div. 2:

Vessel Stress Summation at Vessel-Nozzle Junction (N./mm²):

Type of Stress Int. Location	Stress Values at							
	Au	Al	Bu	Bl	Cu	Cl	Du	Dl
Circ. Pm (SUS)	9	11	9	11	9	11	9	11
Circ. Pl (SUS)	-3	-3	7	7	-3	-3	7	7
Circ. Q (SUS)	-17	17	37	-37	-22	22	42	-42
Long. Pm (SUS)	4	4	4	4	4	4	4	4
Long. Pl (SUS)	-2	-2	6	6	1	1	3	3
Long. Q (SUS)	-15	15	35	-35	-22	22	42	-42
Shear Pm (SUS)	0	0	0	0	0	0	0	0
Shear Pl (SUS)	1	1	-1	-1	-1	-1	1	1
Shear Q (SUS)	5	5	5	5	5	5	5	5
Pm (SUS)	9.0	11.0	9.0	11.0	9.0	11.0	9.0	11.0
Pm+Pl (SUS)	6.2	8.2	16.2	18.1	6.6	8.3	16.1	18.1
Pm+Pl+Q (Total)	18.1	28.2	54.7	27.0	20.5	32.8	61.0	37.6

Vessel Stress Summation Comparison (N./mm²):



PV Elite 28 Licensee: SL User
 FileName : 161-C1-C2_(Stack) Page 175 of 204
 Nozzle Calcs.: N4-Shell outlet Nozl: 11 9:40am Sep 9,2026

Type of Stress Int.	Max. S.I.	S.I. Allowable	Result
Pm (SUS)	11.00	118.00	Passed
Pm+Pl (SUS)	18.12	177.00	Passed
Pm+Pl+Q (TOTAL)	61.00	353.99	Passed

Because only sustained loads were specified, the Pm+Pl+Q allowable was 3 * Smh.

WRC 297 Stress Summations per ASME Sec. VIII Div. 2:

Vessel Stress Summation at Reinforcing Pad Edge (N./mm²):

Type of Stress Int. Location	Stress Values at							
	Au	Al	Bu	Bl	Cu	Cl	Du	Dl
Circ. Pm (SUS)	21	24	21	24	21	24	21	24
Circ. Pl (SUS)	-3	-3	13	13	-5	-5	13	13
Circ. Q (SUS)	0	0	28	-28	-108	108	198	-198
Long. Pm (SUS)	10	10	10	10	10	10	10	10
Long. Pl (SUS)	-1	-1	9	9	-3	-3	13	13
Long. Q (SUS)	-8	8	98	-98	-32	32	60	-60
Shear Pm (SUS)	0	0	0	0	0	0	0	0
Shear Pl (SUS)	2	2	-2	-2	-2	-2	2	2
Shear Q (SUS)	5	5	5	5	5	5	5	5
Pm (SUS)	21.0	24.0	21.0	24.0	21.0	24.0	21.0	24.0
Pm+Pl (SUS)	18.4	21.3	34.3	37.2	16.4	19.3	34.4	37.3
Pm+Pl+Q (Total)	22.0	26.3	117.2	88.2	92.1	127.1	232.3	161.4

Vessel Stress Summation Comparison (N./mm²):

Type of Stress Int.	Max. S.I.	S.I. Allowable	Result
Pm (SUS)	24.00	118.00	Passed
Pm+Pl (SUS)	37.28	177.00	Passed
Pm+Pl+Q (TOTAL)	232.33	353.99	Passed

Because only sustained loads were specified, the Pm+Pl+Q allowable was 3 * Smh.

WRC 297 Stress Summations per ASME Sec. VIII Div. 2:

Nozzle Stress Summation at Vessel-Nozzle Junction (N./mm²):

Type of Stress Int. Location	Stress Values at							
	Au	Al	Bu	Bl	Cu	Cl	Du	Dl
Circ. Pm (SUS)	11	14	11	14	11	14	11	14
Circ. Pl (SUS)	-3	-3	7	7	1	1	3	3
Circ. Q (SUS)	0	0	0	0	0	0	0	0
Long. Pm (SUS)	5	5	5	5	5	5	5	5
Long. Pl (SUS)	-30	-30	36	36	-30	-30	36	36
Long. Q (SUS)	-70	70	130	-130	-98	98	158	-158
Shear Pm (SUS)	0	0	0	0	0	0	0	0



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)

Page 176 of 204

Nozzle Calcs.: N4-Shell outlet

Nozl: 11

9:40am

Sep 9, 2026

Shear P1 (SUS)	4	4	-4	-4	-4	-4	4	4
Shear Q (SUS)	14	14	14	14	14	14	14	14
Pm (SUS)	11.0	14.0	11.0	14.0	11.0	14.0	11.0	14.0
Pm+P1 (SUS)	34.0	36.9	41.7	41.8	37.9	40.8	41.6	41.6
Pm+P1+Q (Total)	109.1	52.8	171.7	111.8	136.5	74.7	200.7	138.8

Nozzle Stress Summation Comparison (N./mm²):

Type of Stress Int.	Max. S.I.	S.I. Allowable	Result
Pm (SUS)	14.00	118.00	Passed
Pm+P1 (SUS)	41.77	177.00	Passed
Pm+P1+Q (TOTAL)	200.74	353.99	Passed

Because only sustained loads were specified, the Pm+P1+Q allowable was 3 * Smh.

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)

Page 177 of 204

Nozzle Calcs.: N2-Tube Outlet

Nozl: 12

9:40am

Sep 9, 2026

Input, Nozzle Desc: N2-Tube Outlet

From: 60

Pressure for Reinforcement Calculations	P	2401.813	KPa.
Temperature for Internal Pressure	Temp	270	°C
Design External Pressure	Pext	103.42	KPa.
Temperature for External Pressure	Tempex	270	°C
Parent Material		SA-106 B	
Parent Allowable Stress at Temperature	Sv	118.00	N./mm ²
Parent Allowable Stress At Ambient	Sva	118.00	N./mm ²
Inside Diameter of Cylindrical Shell	D	188.95	mm
Design Length of Section	L	366.5459	mm
Shell Finished (Minimum) Thickness	t	13.1794	mm
Shell Internal Corrosion Allowance	c	3.0000	mm
Shell External Corrosion Allowance	co	0.0000	mm
Distance from Bottom/Left Tangent		6586.15	mm
User Entered Minimum Design Metal Temperature		-12.00	°C

Type of Element Connected to the Parent : Nozzle

Material		SA-106 B	
Material UNS Number		K03006	
Material Specification/Type		Smls. pipe	
Allowable Stress at Temperature	Sn	118.00	N./mm ²
Allowable Stress At Ambient	Sna	118.00	N./mm ²
Diameter Basis (for tr calc only)		Outside	
Layout Angle		270.00	deg
Diameter		89.0000	mm
Size and Thickness Basis		Actual	
Actual Thickness	tn	11.0000	mm
Flange Material		SA-105	
Flange Type		Weld Neck Flange	
Corrosion Allowance	can	3.0000	mm
Joint Efficiency of Shell Seam at Nozzle	E1	1.00	
Joint Efficiency of Nozzle Neck	En	1.00	
Outside Projection	ho	200.0000	mm
Weld leg size between Nozzle and Pad/Shell	Wo	10.0000	mm
Groove weld depth between Nozzle and Vessel	Wgnv	11.0000	mm
Inside Projection	h	0.0000	mm
Weld leg size, Inside Element to Shell	Wi	0.0000	mm
Pad Material		SA-516 70	
Pad Allowable Stress at Temperature	Sp	137.20	N./mm ²
Pad Allowable Stress At Ambient	Spa	138.00	N./mm ²
Diameter of Pad along vessel surface	Dp	129.0000	mm
Thickness of Pad	te	12.0000	mm
Weld leg size between Pad and Shell	Wp	10.0000	mm
Groove weld depth between Pad and Nozzle	Wgpn	12.0000	mm
Reinforcing Pad Width		20.0000	mm
Flange Class		600	
Flange Grade		GR 1.1	

The Pressure Design option was Design Pressure + static head.



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)


Page 178 of 204

Nozzle Calcs.: N2-Tube Outlet

Nozl: 12

9:40am

Sep 9, 2026



Reinforcement CALCULATION, Description: N2-Tube Outlet

ASME Code, Section VIII, Div. 1, UG-37 to UG-45

Actual Outside Diameter Used in Calculation	89.000 mm.
Actual Thickness Used in Calculation	11.000 mm

Nozzle input data check completed without errors.

Reqd thk per UG-37(a) of Cylindrical Shell, tr [Int. Press]
 $= P \cdot R / (S_v \cdot E - 0.6 \cdot P)$ per UG-27 (c)(1)
 $= 2402 \cdot 97.5 / (118 \cdot 1 - 0.6 \cdot 2402)$
 $= 2.0087 \text{ mm}$

Reqd thk per UG-37(a) of Nozzle Wall, trn [Int. Press]
 $= P \cdot R_o / (S_n \cdot E + 0.4 \cdot P)$ per Appendix 1-1 (a)(1)
 $= 2402 \cdot 44.5 / (118 \cdot 1 + 0.4 \cdot 2402)$
 $= 0.8985 \text{ mm}$

Required Nozzle thickness under External Pressure per UG-28 : 0.4125 mm

UG-40, Limits of Reinforcement: [Internal Pressure]

Parallel to Vessel Wall (Diameter Limit)	D1	146.0000 mm
Parallel to Vessel Wall, opening length	d	73.0000 mm
Normal to Vessel Wall (Thickness Limit), pad side Tlwp		25.4486 mm

*Taking a UG-36(c)(3)(a) exemption for nozzle: N2-Tube Outlet.
 This calculation is valid for nozzles that meet all the requirements of paragraph UG-36. Please check the Code carefully, especially for nozzles that are not isolated or do not meet Code spacing requirements. To force the computation of areas for small nozzles go to Tools->Configuration and check the box to force the UG-37 small nozzle area calculation.*

UG-45 Minimum Nozzle Neck Thickness Requirement: [Int. Press.]

Wall Thickness for Internal/External pressures	ta = 3.8985 mm
Wall Thickness per UG16(b),	tr16b = 4.5000 mm
Wall Thickness, shell/head, internal pressure	trb1 = 5.0087 mm
Wall Thickness	tb1 = max(trb1, tr16b) = 5.0087 mm
Wall Thickness	tb2 = max(trb2, tr16b) = 4.5000 mm
Wall Thickness per table UG-45	tb3 = 8.0200 mm

Determine Nozzle Thickness candidate [tb]:
 $= \min[tb3, \max(tb1, tb2)]$
 $= \min[8.02, \max(5.01, 4.5)]$
 $= 5.0087 \text{ mm}$

Minimum Wall Thickness of Nozzle Necks [tUG-45]:
 $= \max(ta, tb)$
 $= \max(3.9, 5.01)$
 $= 5.0087 \text{ mm}$

Available Nozzle Neck Thickness = 11.0000 mm -> OK



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 179 of 204

Nozzle Calcs.: N2-Tube Outlet

Nozl: 12

9:40am

Sep 9, 2026

Stresses on Nozzle due to External and Pressure Loads per the ASME B31.3 Piping Code, (see 319.4.4 and 302.3.5):

Sustained :	49.2,	Allowable :	118.0 N./mm ²	Passed
Expansion :	0.0,	Allowable :	245.8 N./mm ²	Passed
Occasional :	4.9,	Allowable :	156.9 N./mm ²	Passed
Shear :	30.0,	Allowable :	82.6 N./mm ²	Passed

The number of cycles on this nozzle was assumed to be 7000 or less for the determination of the expansion stress allowable.

Nozzle Junction Minimum Design Metal Temperature (MDMT) Calculations:

Nozzle Neck to Flange Weld, min(Curve:B, Curve:A)

Govrn. thk, tg = 11, tr = 0.9, c = 3 mm, E* = 1

Thickness Ratio = $tr * E^* / (tg - c) = 0.11$, Temp. Reduction = 78 °C

Min Metal Temp. w/o impact per UCS-66, Curve A	-5 °C
Min Metal Temp. at Required thickness (UCS 66.1)	-104 °C
Min Metal Temp. w/o impact per UG-20(f)	-29 °C

Nozzle Neck to Pad Weld for the Nozzle, Curve: B

Govrn. thk, tg = 11, tr = 0.9, c = 3 mm, E* = 1

Thickness Ratio = $tr * E^* / (tg - c) = 0.11$, Temp. Reduction = 78 °C

Min Metal Temp. w/o impact per UCS-66, Curve B	-26 °C
Min Metal Temp. at Required thickness (UCS 66.1)	-104 °C
Min Metal Temp. w/o impact per UG-20(f)	-29 °C

Nozzle Neck to Pad Weld for Reinforcement pad, Curve: B

Govrn. thk, tg = 11, tr = 0.9, c = 3 mm, E* = 1

Thickness Ratio = $tr * E^* / (tg - c) = 0.11$, Temp. Reduction = 78 °C

Min Metal Temp. w/o impact per UCS-66, Curve B	-26 °C
Min Metal Temp. at Required thickness (UCS 66.1)	-104 °C
Min Metal Temp. w/o impact per UG-20(f)	-29 °C

Shell to Pad Weld Junction at Pad OD, Curve: B

Govrn. thk, tg = 12, c = 3 mm, E* = 1

Thickness Ratio = $tr * E^* / (tg - c) = 0.2$, Temp. Reduction = 78 °C

Attachment governing, Attachment stress = Shell stress per Code

Min Metal Temp. w/o impact per UCS-66, Curve B	-23 °C
Min Metal Temp. at Required thickness (UCS 66.1)	-104 °C
Min Metal Temp. w/o impact per UG-20(f)	-29 °C

Nozzle-Shell/Head Weld (UCS-66(a)1(b)), Curve: B

Govrn. thk, tg = 11, tr = 0.9, c = 3 mm, E* = 1

Thickness Ratio = $tr * E^* / (tg - c) = 0.11$, Temp. Reduction = 78 °C

Min Metal Temp. w/o impact per UCS-66, Curve B	-26 °C
Min Metal Temp. at Required thickness (UCS 66.1)	-104 °C
Min Metal Temp. w/o impact per UG-20(f)	-29 °C

Gov. MDMT of the Nozzle	: -104 °C
Gov. MDMT of the Reinforcement Pad	: -104 °C
Gov. MDMT of the nozzle to shell joint welded assembly	: -104 °C

Flange MDMT including Temperature reduction per UCS-66.1:



PV Elite 28 Licensee: SL User
 FileName : 161-C1-C2 _(Stack) Page 180 of 204
 Nozzle Calcs.: N2-Tube Outlet Nozl: 12 9:40am Sep 9,2026

Unadjusted MDMT of ASME B16.5/47 flanges per UCS-66(c) -18 °C
 Flange MDMT with Temp reduction per UCS-66(b)(1)(-b) -104 °C

Where the Stress Reduction Ratio per UCS-66(b)(1)(-b) is :
 Design Pressure/Ambient Rating = 2401.81/10200.00 = 0.235

Weld Size Calculations, Description: N2-Tube Outlet

Intermediate Calc. for nozzle/shell Welds Tmin 8.0000 mm
 Intermediate Calc. for pad/shell Welds TminPad 12.0000 mm

Results Per UW-16.1:

	Required Thickness	Actual Thickness
Nozzle Weld	5.6000 = 0.7 * tmin.	7.0700 = 0.7 * Wo mm
Pad Weld	6.0000 = 0.5*TminPad	7.0700 = 0.7 * Wp mm

Skipping the nozzle attachment weld strength calculations. Per UW-15(b)(2) the nozzles exempted by UG-36(c)(3)(a) (small nozzles) do not require a weld strength check.

Maximum Allowable Pressure for this Nozzle at this Location:

Converged Maximum Allowable Pressure in the Operating case: 11594 KPa.

Note: The MAWP of this junction was limited by the parent Shell/Head.

The Drop for this Nozzle is : 11.1366 mm
 The Cut Length for this Nozzle is, Drop + Ho + H + T : 224.3161 mm

Input Echo, WRC297 Item 1, Description: N2-Tube Outlet:

Diameter Basis for Cylindrical Shell	ID	
Shell Internal Corrosion Allowance	3.0000	mm
Shell External Corrosion Allowance	0.0000	mm
Shell Diameter	188.951	mm
Shell Thickness	13.1794	mm
Shell Stress Concentration Factor	1.000	
Vessel Material	SA-106 B	
Vessel Cold S.I. Allowable	Smc	118.00 N./mm ²
Vessel Hot S.I. Allowable	Smh	118.00 N./mm ²

See ASME VIII Div. 2, 4.1.6.3, for determination of the SPS allowable.

Diameter Basis for Nozzle	OD	
Nozzle Corrosion Allowance	3.0000	mm
Nozzle Diameter	89.000	mm
Nozzle Thickness	11.0000	mm
Nozzle Stress Concentration Factor	1.000	
Nozzle Material	SA-106 B	
Nozzle Cold S.I. Allowable	SNmc	118.00 N./mm ²
Nozzle Hot S.I. Allowable	SNmh	118.00 N./mm ²

See ASME VIII Div. 2, 4.1.6.3, for determination of the SPS allowable.

Diameter of Reinforcing Pad	129.000	mm
Thickness of Reinforcing Pad	12.0000	mm

Note:
 External Forces and Moments in WRC 107/537 Convention:
 These loads are assumed to be SUSained loads.

Design Internal Pressure	Dp	2401.81	KPa.
Radial Load	P	-734.25	Kgf
Circumferential Shear	Vc	530.29	Kgf
Longitudinal Shear	Vl	530.29	Kgf



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 181 of 204

Nozzle Calcs.: N2-Tube Outlet

Nozl: 12

9:40am

Sep 9, 2026

Circumferential Moment	Mc	130.48	Kg-m.
Longitudinal Moment	Ml	130.48	Kg-m.
Torsional Moment	Mt	150.05	Kg-m.

Include Axial Pressure Thrust	No
Include Pressure Stress Indices per Div. 2	No
Local Loads applied at end of Nozzle/Attachment	No

*Warning - The ratio, D_v/T_v (16.337) is < 20
check the limitations of WRC bulletin 297.*

*Warning - The ratio, D_n/T_n (8.091) is < 10
check the limitations of WRC bulletin 297.*

Stress Computations at the Edge of the Nozzle:

Stress Attenuation Diameter (for Insert Plates) per WRC 297:

$$= \text{NozzleOD} + 2 \cdot 1.65 \cdot \sqrt{R_{\text{mean}}(t - c_a)}$$

$$= 89.0 + 2 \cdot 1.65 \cdot \sqrt{108.565(13.179 - 3.0)}$$

$$= 198.703 \text{ mm}$$

WRC 297 Curve Access Parameters:

Vessel Mean Diameter	(D) =	217.130 mm
Nozzle Outside Diameter	(d) =	89.000 mm
Vessel Thickness used	(T) =	22.179 mm
Nozzle Thickness used	(t) =	8.000 mm
T / t	=	2.772
d / t	=	11.125

$$\lambda = [(d/D) \cdot \sqrt{(D/T)}] = 1.282$$

Nr/P	=	0.144
Mr/P	=	0.118
M0/P	=	0.115
N0/P	=	0.184
MrD/Mc	=	0.184
NrDL/Mc	=	0.178
M0d/Mc	=	0.187
N0DL/Mc	=	0.055
MrD/Ml	=	0.147
NrDL/Ml	=	0.146
M0D/Ml	=	0.158
N0DL/Ml	=	0.173

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Stresses Normal to longitudinal plane)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Outplane Membrane (P)	2	2	2	2
Outplane Bending (P)	10	-10	10	-10
Outplane Membrane (Mc)	0	0	0	0
Outplane Bending (Mc)	0	0	0	0
Outplane Membrane (Ml)	-5	-5	5	5
Outplane Bending (Ml)	-27	27	27	-27
Normal Pressure Stress	9	11	9	11
Outplane Stress Summary	-10	27	54	-18

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Stresses parallel to longitudinal plane)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Inplane Membrane (P)	2	2	2	2



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 182 of 204

Nozzle Calcs.: N2-Tube Outlet

Nozl: 12 9:40am

Sep 9, 2026

Inplane Bending (P)	10	-10	10	-10
Inplane Membrane (Mc)	0	0	0	0
Inplane Bending (Mc)	0	0	0	0
Inplane Membrane (ML)	-4	-4	4	4
Inplane Bending (ML)	-25	25	25	-25
Inplane Pressure Stress	4	4	4	4
Inplane Stress Summary	-12	18	47	-25

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Shear stress normal to longitudinal plane)			Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Outplane	Shear	(Vc)	1	1	-1	-1
Outplane	Shear	(Vl)	0	0	0	0
Outplane	Shear	(Mt)	5	5	5	5
Shear Stress Summary			7	7	3	3

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Stress Intensities	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Two * Max Shear Stress	18	30	56	26

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Stresses Normal to circumferential plane)	Cu Left Outside	Cl Left Inside	Du Right Outside	Dl Right Inside
Outplane Membrane (P)	2	2	2	2
Outplane Bending (P)	10	-10	10	-10
Outplane Membrane (Mc)	-1	-1	1	1
Outplane Bending (Mc)	-32	32	32	-32
Outplane Membrane (ML)	0	0	0	0
Outplane Bending (ML)	0	0	0	0
Normal Pressure Stress	4	4	4	4
Outplane Stress Summary	-16	28	51	-33

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Stresses parallel to circumferential plane)		Cu Left Outside	Cl Left Inside	Du Right Outside	Dl Right Inside
Inplane Membrane (P)		2	2	2	2
Inplane Bending (P)		10	-10	10	-10
Inplane Membrane (Mc)		-5	-5	5	5
Inplane Bending (Mc)		-32	32	32	-32
Inplane Membrane (ML)		0	0	0	0
Inplane Bending (ML)		0	0	0	0
Inplane Pressure Stress		9	11	9	11
Inplane Stress Summary		-15	30	59	-23

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Shear stress normal to circumferential plane)			Cu Left Outside	Cl Left Inside	Du Right Outside	Dl Right Inside
Outplane Shear (Vc)			0	0	0	0
Outplane Shear (Vl)			-1	-1	1	1
Torsional Shear (Mt)			5	5	5	5



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)

Page 183 of 204

Nozzle Calcs.: N2-Tube Outlet

Nozl: 12 9:40am

Sep 9,2026

Shear Stress Summary	3	3	7	7
----------------------	---	---	---	---

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Stress Intensities)	Cu Left Outside	Cl Left Inside	Du Right Outside	Dl Right Inside
Two * Max Shear Stress	19	33	63	37

Nozzle Stresses (N./mm²):

LONGITUDINAL PLANE (Stresses in the hoop direction)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Hoop Membrane (P)	2	2	2	2
Hoop Bending (P)	0	0	0	0
Hoop Membrane (Mc)	0	0	0	0
Hoop Bending (Mc)	0	0	0	0
Hoop Membrane (ML)	-5	-5	5	5
Hoop Bending (ML)	0	0	0	0
Hoop Pressure Stress	11	14	11	14
Hoop Stress Summary	9	12	19	22

Nozzle Stresses (N./mm²):

LONGITUDINAL PLANE (Stresses Normal to pipe cross-section)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Axial Membrane (P)	3	3	3	3
Axial Bending (P)	30	-30	30	-30
Axial Membrane (Mc)	0	0	0	0
Axial Bending (Mc)	0	0	0	0
Axial Membrane (ML)	-33	-33	33	33
Axial Bending (ML)	-100	100	100	-100
Axial Pressure Stress	5	5	5	5
Axial Stress Summary	-93	45	174	-87

Nozzle Stresses (N./mm²):

LONGITUDINAL PLANE (Shear stress)	Au Outside	Al Inside	Bu Outside	Bl Inside
Shear due to (Vc)	4	4	-4	-4
Shear due to (Vl)	0	0	0	0
Shear due to Torsion	14	14	14	14
Shear Stress Summary	19	19	10	10

Nozzle Stresses (N./mm²):

LONGITUDINAL PLANE (Stress Intensities)	Au Outside	Al Inside	Bu Outside	Bl Inside
Two * Max Shear Stress	110	54	174	111

Nozzle Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Stresses in the hoop direction)	Cu Left Outside	Cl Left Inside	Du Right Outside	Dl Right Inside
Hoop Membrane (P)	2	2	2	2
Hoop Bending (P)	0	0	0	0
Hoop Membrane (Mc)	-1	-1	1	1
Hoop Bending (Mc)	0	0	0	0



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)

Page 184 of 204

Nozzle Calcs.: N2-Tube Outlet

Nozl: 12 9:40am

Sep 9, 2026

Hoop Membrane (ML)	0	0	0	0
Hoop Bending (ML)	0	0	0	0
Hoop Pressure Stress	11	14	11	14

Hoop Stress Summary	12	15	16	19
---------------------	----	----	----	----

Nozzle Stresses (N./mm²):

CIRCUMFERENTIAL PLANE	Cu	Cl	Du	Dl
(Stresses Normal to	Left	Left	Right	Right
pipe cross-section)	Outside	Inside	Outside	Inside

Axial Membrane (P)	3	3	3	3
Axial Bending (P)	30	-30	30	-30
Axial Membrane (Mc)	-33	-33	33	33
Axial Bending (Mc)	-128	128	128	-128
Axial Membrane (ML)	0	0	0	0
Axial Bending (ML)	0	0	0	0
Axial Pressure Stress	5	5	5	5

Axial Stress Summary	-122	73	202	-116
----------------------	------	----	-----	------

Nozzle Stresses (N./mm²):

CIRCUMFERENTIAL PLANE	Cu	Cl	Du	Dl
(Shear stress)	Outside	Inside	Outside	Inside

Shear due to (Vc)	0	0	0	0
Shear due to (Vl)	-4	-4	4	4
Shear due to Torsion	14	14	14	14

Shear Stress Summary	10	10	19	19
----------------------	----	----	----	----

Nozzle Stresses (N./mm²):

CIRCUMFERENTIAL PLANE	Cu	Cl	Du	Dl
(Stress Intensities	Outside	Inside	Outside	Inside

Two * Max Shear Stress	136	75	204	140
------------------------	-----	----	-----	-----

Stress Computations at the Edge of the Reinforcing Pad:

Stress Attenuation Diameter (for Insert Plates) per WRC 297:

$$= \text{NozzleOD} + 2 \cdot 1.65 \cdot \sqrt{R_{\text{mean}}(t - ca)}$$

$$= 89.0 + 2 \cdot 1.65 \cdot \sqrt{102.565(13.179 - 3.0)}$$

$$= 195.629 \text{ mm}$$

WRC 297 Curve Access Parameters:

Vessel Mean Diameter	(D) =	205.130 mm
Nozzle Outside Diameter	(d) =	129.000 mm
Vessel Thickness used	(T) =	10.179 mm
Nozzle Thickness used	(t) =	28.000 mm
T / t	=	0.364
d / T	=	10.000

$$\lambda = [(d/D) \cdot \sqrt{(D/T)}] = 2.823$$

Note: Re-pad thickness is added to nozzle thickness to simulate the Re-pad.

Nr/P	=	0.061
Mr/P	=	0.110
M0/P	=	0.034
N0/P	=	0.077
MrD/Mc	=	0.268
NrDL/Mc	=	0.096
M0d/Mc	=	0.081



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 185 of 204

Nozzle Calcs.: N2-Tube Outlet

Nozl: 12 9:40am

Sep 9, 2026

NØDL/Mc = 0.085
MrD/Ml = 0.092
NrDL/Ml = 0.058
MØD/Ml = 0.026
NØDL/Ml = 0.090

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Stresses Normal to longitudinal plane)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Outplane Membrane (P)	5	5	5	5
Outplane Bending (P)	14	-14	14	-14
Outplane Membrane (Mc)	0	0	0	0
Outplane Bending (Mc)	0	0	0	0
Outplane Membrane (ML)	-8	-8	8	8
Outplane Bending (ML)	-14	14	14	-14
Normal Pressure Stress	21	24	21	24
Outplane Stress Summary	18	21	64	8

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Stresses parallel to longitudinal plane)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Inplane Membrane (P)	4	4	4	4
Inplane Bending (P)	45	-45	45	-45
Inplane Membrane (Mc)	0	0	0	0
Inplane Bending (Mc)	0	0	0	0
Inplane Membrane (ML)	-5	-5	5	5
Inplane Bending (ML)	-53	53	53	-53
Inplane Pressure Stress	10	10	10	10
Inplane Stress Summary	2	16	119	-78

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Shear stress normal to longitudinal plane)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Outplane Shear (Vc)	2	2	-2	-2
Outplane Shear (Vl)	0	0	0	0
Outplane Shear (Mt)	5	5	5	5
Shear Stress Summary	8	8	3	3

Vessel Stresses (N./mm²):

LONGITUDINAL PLANE (Stress Intensities)	Au Top Outside	Al Top Inside	Bu Bottom Outside	Bl Bottom Inside
Two * Max Shear Stress	22	27	119	87

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Stresses Normal to circumferential plane)	Cu Left Outside	Cl Left Inside	Du Right Outside	Dl Right Inside
Outplane Membrane (P)	5	5	5	5
Outplane Bending (P)	14	-14	14	-14
Outplane Membrane (Mc)	-8	-8	8	8
Outplane Bending (Mc)	-46	46	46	-46
Outplane Membrane (ML)	0	0	0	0
Outplane Bending (ML)	0	0	0	0



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 186 of 204

Nozzle Calcs.: N2-Tube Outlet

Nozl: 12 9:40am

Sep 9,2026

Normal Pressure Stress	10	10	10	10
------------------------	----	----	----	----

Outplane Stress Summary	-23	40	85	-36
-------------------------	-----	----	----	-----

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Stresses parallel to circumferential plane)	Cu	Cl	Du	Dl
	Left Outside	Left Inside	Right Outside	Right Inside

Inplane Membrane (P)	4	4	4	4
Inplane Bending (P)	45	-45	45	-45
Inplane Membrane (Mc)	-9	-9	9	9
Inplane Bending (Mc)	-153	153	153	-153
Inplane Membrane (ML)	0	0	0	0
Inplane Bending (ML)	0	0	0	0
Inplane Pressure Stress	21	24	21	24

Inplane Stress Summary	-91	127	234	-161
------------------------	-----	-----	-----	------

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Shear stress normal to circumferential plane)	Cu	Cl	Du	Dl
	Left Outside	Left Inside	Right Outside	Right Inside

Outplane Shear (Vc)	0	0	0	0
Outplane Shear (Vl)	-2	-2	2	2
Torsional Shear (Mt)	5	5	5	5

Shear Stress Summary	3	3	8	8
----------------------	---	---	---	---

Vessel Stresses (N./mm²):

CIRCUMFERENTIAL PLANE (Stress Intensities	Cu	Cl	Du	Dl
	Left Outside	Left Inside	Right Outside	Right Inside

Two * Max Shear Stress	91	127	235	162
------------------------	----	-----	-----	-----

WRC 297 Stress Summations per ASME Sec. VIII Div. 2:

Vessel Stress Summation at Vessel-Nozzle Junction (N./mm²):

Type of Stress Int. Location	Stress Values at							
	Au	Al	Bu	Bl	Cu	Cl	Du	Dl
Circ. Pm (SUS)	9	11	9	11	9	11	9	11
Circ. Pl (SUS)	-3	-3	7	7	-3	-3	7	7
Circ. Q (SUS)	-17	17	37	-37	-22	22	42	-42
Long. Pm (SUS)	4	4	4	4	4	4	4	4
Long. Pl (SUS)	-2	-2	6	6	1	1	3	3
Long. Q (SUS)	-15	15	35	-35	-22	22	42	-42
Shear Pm (SUS)	0	0	0	0	0	0	0	0
Shear Pl (SUS)	1	1	-1	-1	-1	-1	1	1
Shear Q (SUS)	5	5	5	5	5	5	5	5
Pm (SUS)	9.0	11.0	9.0	11.0	9.0	11.0	9.0	11.0
Pm+Pl (SUS)	6.2	8.2	16.2	18.1	6.6	8.3	16.1	18.1
Pm+Pl+Q (Total)	18.1	28.2	54.7	27.0	20.5	32.8	61.0	37.6

Vessel Stress Summation Comparison (N./mm²):



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)

Page 187 of 204

Nozzle Calcs.: N2-Tube Outlet

Nozl: 12

9:40am

Sep 9, 2026

Type of Stress Int.	Max. S.I.	S.I. Allowable	Result
Pm (SUS)	11.00	118.00	Passed
Pm+Pl (SUS)	18.12	177.00	Passed
Pm+Pl+Q (TOTAL)	61.00	353.99	Passed

Because only sustained loads were specified, the Pm+Pl+Q allowable was 3 * Smh.

WRC 297 Stress Summations per ASME Sec. VIII Div. 2:

Vessel Stress Summation at Reinforcing Pad Edge (N./mm²):

Type of Stress Int. Location	Stress Values at							
	Au	Al	Bu	Bl	Cu	Cl	Du	Dl
Circ. Pm (SUS)	21	24	21	24	21	24	21	24
Circ. Pl (SUS)	-3	-3	13	13	-5	-5	13	13
Circ. Q (SUS)	0	0	28	-28	-108	108	198	-198
Long. Pm (SUS)	10	10	10	10	10	10	10	10
Long. Pl (SUS)	-1	-1	9	9	-3	-3	13	13
Long. Q (SUS)	-8	8	98	-98	-32	32	60	-60
Shear Pm (SUS)	0	0	0	0	0	0	0	0
Shear Pl (SUS)	2	2	-2	-2	-2	-2	2	2
Shear Q (SUS)	5	5	5	5	5	5	5	5
Pm (SUS)	21.0	24.0	21.0	24.0	21.0	24.0	21.0	24.0
Pm+Pl (SUS)	18.4	21.3	34.3	37.2	16.4	19.3	34.4	37.3
Pm+Pl+Q (Total)	22.0	26.3	117.2	88.2	92.1	127.1	232.3	161.4

Vessel Stress Summation Comparison (N./mm²):

Type of Stress Int.	Max. S.I.	S.I. Allowable	Result
Pm (SUS)	24.00	118.00	Passed
Pm+Pl (SUS)	37.28	177.00	Passed
Pm+Pl+Q (TOTAL)	232.33	353.99	Passed

Because only sustained loads were specified, the Pm+Pl+Q allowable was 3 * Smh.

WRC 297 Stress Summations per ASME Sec. VIII Div. 2:

Nozzle Stress Summation at Vessel-Nozzle Junction (N./mm²):

Type of Stress Int. Location	Stress Values at							
	Au	Al	Bu	Bl	Cu	Cl	Du	Dl
Circ. Pm (SUS)	11	14	11	14	11	14	11	14
Circ. Pl (SUS)	-3	-3	7	7	1	1	3	3
Circ. Q (SUS)	0	0	0	0	0	0	0	0
Long. Pm (SUS)	5	5	5	5	5	5	5	5
Long. Pl (SUS)	-30	-30	36	36	-30	-30	36	36
Long. Q (SUS)	-70	70	130	-130	-98	98	158	-158
Shear Pm (SUS)	0	0	0	0	0	0	0	0



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2_(Stack)

Page 188 of 204

Nozzle Calcs.: N2-Tube Outlet

Nozl: 12

9:40am

Sep 9, 2026

Shear P1 (SUS)	4	4	-4	-4	-4	-4	4	4
Shear Q (SUS)	14	14	14	14	14	14	14	14
Pm (SUS)	11.0	14.0	11.0	14.0	11.0	14.0	11.0	14.0
Pm+P1 (SUS)	34.0	36.9	41.7	41.8	37.9	40.8	41.6	41.6
Pm+P1+Q (Total)	109.1	52.8	171.7	111.8	136.5	74.7	200.7	138.8

Nozzle Stress Summation Comparison (N./mm²):

Type of Stress Int.	Max. S.I.	S.I. Allowable	Result
Pm (SUS)	14.00	118.00	Passed
Pm+P1 (SUS)	41.77	177.00	Passed
Pm+P1+Q (TOTAL)	200.74	353.99	Passed

Because only sustained loads were specified, the Pm+P1+Q allowable was 3 * Smh.

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 189 of 204

ASME TS Calc:

Case: 1 9:40a Sep 9,2026

Input Echo, Tubesheet Number 1, Description: Fixed Tubesheet

Shell Data:

Main Shell Description: Main Shell

Shell Maximum Design Pressure	Psd,max	2400.00 KPa.
Shell Maximum Operating Pressure	Psox,max	2400.00 KPa.
Shell Minimum Operating Pressure	Psox,min	15.00 KPa.
Shell Thickness	ts	15.0622 mm
Shell Internal Corrosion Allowance	cas	3.0000 mm
Shell External Corrosion Allowance	casext	0.0000 mm
Inside Diameter of Shell	Ds	188.951 mm
Shell Circumferential Joint Efficiency	Esw	1.000
Shell Temperature for Internal Pressure	Ts	270.00 °C
Shell Material		SA-106 B

See ASME VIII Div. 1, UG-23(e), for determination of the SPS allowable.

Shell Material UNS Number		K03006
Shell Allowable Stress at Temperature	Ss	118.00 N./mm ²
Shell Allowable Stress at Ambient		118.00 N./mm ²

Channel Data:

Channel Description: LHS Ch Shell

Channel Type:		Cylinder
Channel Maximum Design Pressure	Ptd,max	2400.00 KPa.
Channel Maximum Operating Pressure	Ptox,max	2400.00 KPa.
Channel Minimum Operating Pressure	Ptox,min	0.00 KPa.
Channel Thickness	tc	15.0622 mm
Channel Internal Corrosion Allowance	cac	3.0000 mm
Channel External Corrosion Allowance	cacext	0.0000 mm
Inside Diameter of Channel	Dc	188.951 mm
Channel Design Temperature	TEMPC	260.00 °C
Channel Flange Matl		SA-106 B

See ASME VIII Div. 1, UG-23(e), for determination of the SPS allowable.

Channel Material UNS Number		K03006
Channel Allowable Stress at Temperature	Sc	118.00 N./mm ²
Channel Allowable Stress at Ambient		118.00 N./mm ²

Tube Data:

Number of Tube Holes	Nt	81
Tube Wall Thickness	et	2.1100 mm
Tube Outside Diameter	D	12.7000 mm
Total Straight Tube Length	Lt	6000.00 mm
Straight Tube Length (bet. inner tubsht faces) L		5860.00 mm
Design Temperature of the Tubes		260.00 °C
Tube Material		SA-179
Tube Material UNS Number		K01200
Is this a Welded Tube		No
Tube Material Specification used	Smls. tube	
Tube Allowable Stress at Temperature		92.30 N./mm ²
Tube Allowable Stress At Ambient		92.40 N./mm ²
Tube Yield Stress At design Temperature	Syt	146.40 N./mm ²
Tube Pitch (Center to Center Spacing)	P	15.8750 mm
Tube Layout Pattern		Triangular
Fillet Weld Leg	af	2.1100 mm
Groove Weld Leg	ag	2.1100 mm
Tube-Tubesheet Joint Weld Type		Full Strength
Method for Tube-Tubesheet Jt. Allowable		UW-20.3
Is the Tube Inset		No
Radius to Outermost Tube Hole Center	ro	80.203 mm



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 190 of 204

ASME TS Calc:

Case: 1 9:40a Sep 9,2026

Largest Center-to-Center Tube Distance	U1	0.0000 mm
Length of Expanded Portion of Tube	ltx	0.0000 mm
Tube-side pass partition groove depth	hg	0.0000 mm
Area of Tube Layout	Ap	163.7 cm ²
Perimeter of Tube Layout	Cp	476.2 mm

Tubesheet Data:

Tubesheet TYPE: Fixed Tubesheet Exchanger, Conf B

Tubesheet Design Metal Temperature	T	260.00 °C
Tubesheet Material		SA-266 2

See ASME VIII Div. 1, UG-23(e), for determination of the SPS allowable.

Tubesheet Material UNS Number		K03506
Tubesheet Allowable Stress at Temperature	S	134.60 N./mm ²
Tubesheet Allowable Stress at Ambient	Tt	138.00 N./mm ²
Thickness of Tubesheet	h	70.0000 mm
Tubesheet Corr. Allowance (Shell side)	Cats	3.0000 mm
Tubesheet Corr. Allowance (Channel side)	Catc	3.0000 mm
Tubesheet Outside Diameter	A	360.000 mm

Additional Data for Stepped Tubesheets:

Is the Tubesheet Stepped?		Yes
Is the Tubesheet Flat on Tubeside?		No
Step 1 Diameter on the Tubeside	dt1	243.00 mm
Step 1 Depth on the Tubeside	ht1	9.00 mm
Step 2 Diameter on the Tubeside	dt2	192.00 mm
Step 2 Depth on the Tubeside	ht2	7.00 mm
Is the Tubesheet Flat on Shellside?		Yes
Calculated Tubesheet Diameter per Div 2, 4.18.4		243.00 mm

Note: Tubesheet diameter is now: 243.000 mm Div 2, 4.18.4.

Area of the Untubed Lanes	AL	0.0 cm ²
---------------------------	----	---------------------

Additional Data for Fixed/Floating Tubesheet Exchangers:

Unsupported Tube Span under consideration	l	560.000 mm
Tube End condition corresponding to Span (l)	k	1.00
Ignore Radial Thermal Exp. effects (4.18.8/4.18.9)		Yes
Perform Differential Pressure Design		No
Run Multiple Load Cases		Yes
Shell Side Min. Design Pressure	Psd,min	-103.4190 KPa.
Channel Side Min. Design Pressure	Ptd,min	-103.4190 KPa.
Mean Shell Metal Temp. along Shell len.	Tsm	0.00 °C
Mean Tube Metal Temp. along Tube length	Ttm	0.00 °C
Junction Stress Reduction option		Perform Plastic Calculation

Additional Data for Gasketed Tubesheets:

Tubesheet Gasket on which Side		Channel
Flange Outside Diameter	A	360.000 mm
Flange Inside Diameter	B	188.951 mm
Flange Face Outside Diameter	Fod	257.951 mm
Flange Face Inside Diameter	Fid	188.951 mm
Gasket Outside Diameter	Go	246.951 mm
Gasket Inside Diameter	Gi	220.951 mm
Small end Hub thk.	g0	13.1794 mm
Large end Hub thk.	g1	20.0000 mm
Gasket Factor,	m	3.00
Gasket Design Seating Stress	y	68.95 N./mm ²
Flange Facing Sketch	Code	Sketch 1a
Gasket Thickness	tg	3.1750 mm



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 191 of 204

ASME TS Calc:

Case: 1 9:40a Sep 9, 2026

Full face Gasket Flange Option

Program Selects


Bolting Information:

Diameter of Bolt Circle	C	300.000 mm
Nominal Bolt Diameter	dB	25.4000 mm
Thread Series	UNC Thread Series	
Number of Bolts	n	12
Bolt Material	SA-193 B7	
Bolt Allowable Stress At Temperature	Sb	172.00 N./mm ²
Bolt Allowable Stress At Ambient	Sa	172.00 N./mm ²
Weld between Flange and Shell/Channel		0.0000 mm

Note: The full bolt load $Sa \cdot Ab$, was used for all load cases.

Tubesheet Integral with	Shell
Tubesheet Extended as Flange	Yes
Thickness of Extended Portion of Tubesheet	Tf 54.0000 mm
Is Bolt Load Transferred to the Tubesheet	Yes
Is Exchanger in Creep range (skip EP, Use 3S for Sps)	No

Tubesheet Integral w/Shell, Gasketed w/Channel, Extended as a Flange



Configuration b:

ASME TubeSheet Results per Part UHX/4.18, 2025

Elasticity/Expansion Material Properties:

Shell - TE-1 Carbon & Low Alloy Steels, Group 1
 Shell - TM-1 Carbon Steels with C<= 0.3%

Th. Exp. Coeff. Metal Temp. along Len	0.0 °C	0.0000112153 /°C
Elastic Mod. at Design Temperature	270.0 °C	0.18723E+09 KPa.
Th. Exp. Coeff. Metal Temp. at Tubsht	21.1 °C	0.0000115190 /°C
Elastic Mod. at Metal Temp. along Len	0.0 °C	0.20409E+09 KPa.
Elastic Mod. at Ambient Temperature	21.1 °C	0.20270E+09 KPa.

Channel - TE-1 Carbon & Low Alloy Steels, Group 1
 Channel - TM-1 Carbon Steels with C<= 0.3%



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 192 of 204

ASME TS Calc: Case: 1 9:40a Sep 9, 2026

Th. Exp. Coeff. Metal Temp. at Tubsht	21.1 °C	0.0000115190 /°C
Elastic Mod. at Design Temperature	260.0 °C	0.18822E+09 KPa.
Elastic Mod. at Ambient Temperature	21.1 °C	0.20270E+09 KPa.

Tubes - TE-1 Carbon & Low Alloy Steels, Group 1
Tubes - TM-1 Carbon Steels with C<= 0.3%

Th. Exp. Coeff. Metal Temp. along Len	0.0 °C	0.0000112153 /°C
Elastic Mod. at Design Temperature	260.0 °C	0.18822E+09 KPa.
Elastic Mod. at Metal Temp. along Len	0.0 °C	0.20409E+09 KPa.
Elastic Mod. at Tubsht. Design Temp.	260.0 °C	0.18822E+09 KPa.
Elastic Mod. at Ambient Temperature	21.1 °C	0.20270E+09 KPa.

TubeSheet - TE-1 Carbon & Low Alloy Steels, Group 1
TubeSheet - TM-1 Carbon Steels with C<= 0.3%

Elastic Mod. at Design Temperature	260.0 °C	0.18822E+09 KPa.
Elastic Mod. at Ambient Temperature	21.1 °C	0.20270E+09 KPa.

Note:

The Elasticity and Alpha values are taken from Tables in ASME II D.
Please insure these properties are consistent with the
type of Material for the tubes, shell, channel etc.

Tube Required Thickness under Internal Pressure (Tubeside pressure):

Thickness Due to Internal Pressure:

$$= (P \cdot (D/2 - CAE)) / (S \cdot E + 0.4 \cdot P) \text{ per Appendix 1-1 (a)(1)}$$

$$= (2503 \cdot (12.7/2 - 0)) / (92.3 \cdot 1 + 0.4 \cdot 2503)$$

$$= 0.1704 + 0.0000 = 0.1704 \text{ mm}$$

Tube Required Thickness under External Pressure (Shellside pressure) :

External Pressure Chart CS-1 at 260.00 °C
Elastic Modulus for Material 186156960.00 KPa.

Results for Max. Allowable External Pressure (Emawp):

TCA	ODCA	SLEN	D/T	L/D	Factor A	B
2.1100	12.70	5860.00	6.02	50.0000	0.0303634	90.33

EMAWP = (2.167 / (D/T) - 0.0833) * B = 24994 KPa.

Results for Req'd Thickness for Ext. Pressure (Tca):

TCA	ODCA	SLEN	D/T	L/D	Factor A	B
0.3994	12.70	5860.00	31.80	50.0000	0.0010880	59.71

EMAWP = (4 * B) / (3 * (D/T)) = (4 * 59.7) / (3 * 31.8) = 2504 KPa.

Summary of Tube Required Thickness Results:

Total Required Thickness including Corrosion all.	0.3994 mm
Allowable Internal Pressure at Corroded thickness	35368.44 KPa.
Required Internal Design Pressure	2503.42 KPa.
Allowable External Pressure at Corroded thickness	24994.28 KPa.
Required External Design Pressure	2503.42 KPa.
Required Thickness due to Shell Side pressure	0.3994 mm

Detailed Results for load Case D3 un-corr. (Psd,max + Ptd,max)

Intermediate Calculations For Tubesheets Extended As Flanges:

ASME Code, Section VIII Division 1, 2025

Gasket Contact Width,	N = (Goc - Gic) / 2	13.000 mm
Basic Gasket Width,	b0 = N / 2	6.500 mm
Effective Gasket Width,	b = sqrt(b0) * 2.5	6.422 mm



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 193 of 204

ASME TS Calc:

Case: 1 9:40a Sep 9, 2026

Gasket Reaction Diameter, $G = Go - 2.0 \cdot b$

234.107 mm

Results for ASME Fixed Tubesheet Calculations for Configuration b:

Results for Tubesheet Calculations Original Thickness:

ASME Section VIII-2 Part 4.18.8.4 Step 1:

Tube expansion depth ratio $[\rho]$:

$= l_{tx} / h$ (modified for corrosion if present)

$= 0/70$

$= 0.0000$ (must be $0 \leq \rho \leq 1$)

Effective tube hole diameter $[d^*]$:

$= \max(dt - 2 \cdot tt(Et/E) \cdot (StT/S) \cdot (\rho); dt - 2 \cdot tt)$

$= \max(12.7 - 2 \cdot 2.11 (188224240/188224240) \cdot$

$(92.3/135) \cdot (0); 12.7 - 2 \cdot 2.11)$

$= 12.7000$ mm

Equivalent outer tube limit circle diameter $[Do]$:

$= 2 \cdot ro + dt$

$= 2 \cdot 80.2 + 12.7$

$= 173.106$ mm

Determine the basic ligament efficiency for shear $[\mu]$:

$= (p - dt) / p$

$= (15.9 - 12.7) / 15.9$

$= 0.200$

Equivalent outer tube limit radius $[ao]$:

$= Do / 2$

$= 173/2$

$= 86.5530$ mm

Effective tube pitch $[p^*]$:

$= p / \sqrt{ (1 - 4 \cdot \min(AL \cdot CNVfactor; 4 \cdot Do \cdot p) / (\pi \cdot Do^2)) }$

$= 15.9 / \sqrt{ (1 - 4 \cdot \min(0 \cdot 100 ; 4 \cdot 173 \cdot 15.9) / (\pi \cdot 173^2)) }$

$= 15.8750$ mm

Effective ligament efficiency for bending $[\mu^*]$:

$= (p^* - d^*) / p^*$

$= (15.9 - 12.7) / 15.9$

$= 0.2000$

Ratio $[ps]$:

$= as / ao$

$= 94.5/86.6$

$= 1.0915$

Ratio $[pc]$:

$= ac / ao$

$= 117/86.6$

$= 1.3524$

Compute parameter $[xt]$:

$= 1 - Nt((dt - 2 \cdot tt) / (2 \cdot ao))^2$

$= 1 - 81 ((12.7 - 2 \cdot 2.11) / (2 \cdot 86.6))^2$

$= 0.8056$

Determine parameter $[xs]$:

$= 1 - Nt(dt / (2 \cdot ao))^2$

$= 1 - 81 (12.7 / (2 \cdot 86.6))^2$

$= 0.5640$



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 194 of 204

ASME TS Calc:

Case: 1 9:40a Sep 9, 2026

Determine the value [h'g]:

$$= \max((h_g - CATC); 0) \text{ (For pressure only cases)}$$

$$= \max((0 - 0); 0)$$

$$= 0.000 \text{ mm}$$

ASME Section VIII-2 Part 4.18.8.4 Step 2:

Axial Shell Stiffness [Ks]:

$$= \pi \cdot ts(D_s + ts)E_s/L$$

$$= \pi \cdot 15.1 (189 + 15.1)187232032/5860$$

$$= 31453.9180 \text{ Kg/mm}$$

Axial Tube Stiffness [Kt]:

$$= \pi \cdot tt(D_t - tt)E_t/L$$

$$= \pi \cdot 2.11 (12.7 - 2.11)188224240/5860$$

$$= 229.9337 \text{ Kg/mm}$$

Stiffness Factor [Ks,t]:

$$= K_s / (N_t \cdot K_t)$$

$$= 31454 / (81 \cdot 230)$$

$$= 1.68883$$

Rigidity Ratio [J]:

$$= 1 / (1 + K_s/K_t)$$

$$= 1 / (1 + 31454/0)$$

$$= 1.0000 (= 1 \text{ if No Exp. Jt.})$$

Shell coefficient [β_s]:

$$= ((12(1 - \nu_s^2))^{1/4}) / ((D_s + ts) ts)$$

$$= ((12(1 - 0.3^2))^{1/4}) / ((189 + 15.1) 15.1)$$

$$= 0.0328 \text{ 1/mm}$$

Shell coefficient [ks]:

$$= \beta_s \cdot E_s \cdot ts^3 / (6(1 - \nu_s^2))$$

$$= 0.033 \cdot 187232032 \cdot 15.1^3 / (6(1 - 0.3^2))$$

$$= 3842690048.0000 \text{ KPa} \cdot \text{mm}^2$$

Shell coefficient [λ_s]:

$$= 6(D_s + ts) \cdot ks/h^3 \cdot (1 + h \cdot \beta_s + (h \cdot \beta_s)^2/2)$$

$$= 6(189 + 15.1) \cdot 3.84E+09/70^3 \cdot (1 + 70 \cdot 0.033 + (70 \cdot 0.033)^2/2)$$

$$= 81324392.0000 \text{ KPa}$$

Shell coefficient [δ_s]:

$$= D_s^2 / (4 \cdot E_s \cdot ts) \cdot (1 - D_s \cdot \nu_s / (2(D_s + ts)))$$

$$= 189^2 / (4 \cdot 187232032 \cdot 15.1) \cdot (1 - 189 \cdot 0.3 / (2(189 + 15.1)))$$

$$= 0.27251E-02 \text{ mm/N./mm}^2$$

Intermediate parameters for Tubesheet Gasketed on the Channel Side:

β_C , k_C , λ_C , δ_C are all = 0

ASME Section VIII-2 Part 4.18.8.4 Step 3:

$h/p = 4.409449$; $\mu^* = 0.200000$; $E^* = 29240470 \text{ KPa}$.

$E^*/E = 0.155349$; $\nu^* = 0.458572$

Note: As h/p (4.409) is > 2, data values for $h/p = 2$ were used.

Tube Bundle Stiffness Factor [X_a]:

$$= ((24(1 - \nu^{*2})N_t \cdot E_t \cdot tt(d_t - tt)a_o^2) / (E^* \cdot L \cdot H^3))^{1/4}$$

$$= ((24(1 - 0.46^2)81 \cdot 188224240 \cdot 2.11$$

$$(12.7 - 2.11)86.6^2) / (29240470 \cdot 5860 \cdot 70^3))^{1/4}$$

$$= 0.9525$$

Values from Table 4.18.3

$Z_d = 2.482893$; $Z_v = 0.170039$; $Z_m = 0.681610$



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 195 of 204

ASME TS Calc:

Case:

1

9:40a

Sep 9, 2026

$$Z_a = 0.350844E+00 ; Z_w = 0.170039$$

ASME Section VIII-2 Part 4.18.8.4 Step 4:

Diameter ratio [K]:

$$\begin{aligned} &= A / D_o \\ &= 243/173 \\ &= 1.4038 \end{aligned}$$

Compute coefficient [F]:

$$\begin{aligned} &= (1 - \nu^*) / E^* \cdot (\lambda_s + \lambda_c + E \cdot \ln(K)) \\ &= (1 - 0.46) / 29240470 \cdot (81324392 + 0 + 188224240 \cdot \ln(1.4)) \\ &= 2.6879 \end{aligned}$$

Compute parameter [ϕ]:

$$\begin{aligned} &= (1 + \nu^*) F \\ &= (1 + 0.46) 2.69 \\ &= 3.9205 \end{aligned}$$

Compute parameter [Q1]:

$$\begin{aligned} &= (\psi_s - 1 - \phi \cdot Z_v) / (1 + \phi \cdot Z_m) \\ &= (1.09 - 1 - 3.92 \cdot 0.17) / (1 + 3.92 \cdot 0.68) \\ &= -0.156608 \end{aligned}$$

Compute Parameter [Qz1]:

$$\begin{aligned} &= (Z_d + Q1 \cdot Z_w) / 2 \cdot X_a^4 \\ &= (2.48 + -0.16 \cdot 0.17) / 2 \cdot 0.95^4 \\ &= 1.0108 \end{aligned}$$

Compute parameter [Qz2]:

$$\begin{aligned} &= (Z_v + Q1 \cdot Z_m) / 2 \cdot X_a^4 \\ &= (0.17 + -0.16 \cdot 0.68) / 2 \cdot 0.95^4 \\ &= 0.0260 \end{aligned}$$

Compute parameter [U]:

$$\begin{aligned} &= (Z_w + (\psi_s - 1) Z_m) X_a^4 / (1 + \phi \cdot Z_m) \\ &= (0.17 + (1.09 - 1) 0.68) 0.95^4 / (1 + 3.92 \cdot 0.68) \\ &= 0.0521 \end{aligned}$$

ASME Section VIII-2 Part 4.18.8.4 Step 5:

Determine factor [γ_b]:

$$\begin{aligned} &= (G_c - C) / D_o \text{ (config b)} \\ &= (234 - 300) / 173 = -0.38 \end{aligned}$$

Compute Parameter [γ]:

$$= 0.000 \text{ mm (For Pressure only cases)}$$

Calculate parameter [ω_s]:

$$\begin{aligned} &= \psi_s \cdot k_s \cdot \beta_s \cdot \delta_s (1 + h \cdot \beta_s) \\ &= 1.09 \cdot 3.84E+09 \cdot 0.033 \cdot 0.002725107 (1 + 70 \cdot 0.033) \\ &= 1235.3409 \text{ mm}^2 \end{aligned}$$

Calculate parameter [ω^*s]:

$$\begin{aligned} &= a o^2 (\psi_s^2 - 1) \cdot (\psi_s - 1) / 4 - \omega_s \\ &= 86.6^2 (1.09^2 - 1) \cdot (1.09 - 1) / 4 - 1235 \\ &= -1202.5232 \text{ mm}^2 \end{aligned}$$

Parameter [ω_c]:

$$\begin{aligned} &= \psi_c \cdot k_c [\delta_c (C_m \theta \cdot \beta_c + C_q \Delta \cdot h \cdot \beta_c^2) - \zeta_c (C_m \theta + h \cdot C_q \theta \cdot h \cdot \beta_c / 2)] \\ &= 1.35 \cdot 0 [0.000 (0 + 0 \cdot 0 \cdot 70) - 0.000 (0/70 + 0 \cdot 0/2)] \\ &= 0.0000 \text{ mm}^2 \end{aligned}$$



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 196 of 204

ASME TS Calc:

Case: 1 9:40a Sep 9, 2026

Parameter [$\omega \cdot c$]:

$$= ao^2 [(\rho c^2 + 1) \cdot (\rho c - 1) / 4 - (\rho s - 1) / 2] - \omega c$$

$$= 86.6^2 [(1.35^2 + 1) \cdot (1.35 - 1) / 4 - (1.09 - 1) / 2] - 0$$

$$= 1524.1832 \text{ mm}^2$$

Pressure [$P \cdot S$]:

= 0 For Pressure only cases or Configurations d,e,f,A,B,C,D

Pressure [$P \cdot C$]:

= 0 For Pressure only cases or Configurations b,c,d,B,C,D

ASME Section VIII-2 Part 4.18.8.4 Step 6:

Pressure [$P's$]:

$$= Ps \{ xs + 2(1 - xs) vt + [2 / Kst \cdot (Ds / Do)^2] vs - [(\rho s^2 - 1) / (J \cdot Kst)] - [(1 - J) / (2 J \cdot Kst)] [(Dj^2 - (Ds)^2) / Do^2] \}$$

$$= 2400 \{ 0.56 + 2(1 - 0.56) 0.3 + [2 / 1.69 \cdot (189 / 173)^2] 0.3 - [(1.09^2 - 1) / (1 \cdot 1.69)] - [(1 - 1) / (2 \cdot 1 \cdot 1.69)] [(0^2 - (189)^2) / 173^2] \}$$

$$= 2725.2944 \text{ KPa.}$$

Pressure [$P't$]:

$$= [xt + 2(1 - xt) vt + 1 / (J \cdot Kst)] Pt$$

$$= [0.81 + 2(1 - 0.81) 0.3 + 1 / (1 \cdot 1.69)] 2400$$

$$= 3634.4932 \text{ KPa.}$$

Pressure [P_Y]:

$$= Nt \cdot Kt \cdot \gamma / (\pi \cdot ao^2)$$

$$= 81 \cdot 230 \cdot 0 / (3.14 \cdot 86.6^2)$$

$$= 0.0000 \text{ KPa.}$$

Pressure [P_W]:

$$= -\gamma b \cdot U \cdot W \cdot / (2 \cdot \pi \cdot ao^2)$$

$$= -0.38 \cdot 0.052 \cdot 74816 / (2 \cdot \pi \cdot 86.6^2)$$

$$= 309.0623 \text{ KPa.}$$

Calculate the pressure [$Prim$]:

$$= - (U / ao^2) \cdot (\omega \cdot s \cdot Ps - \omega \cdot c \cdot Pt)$$

$$= - (0.052 / 86.6^2) \cdot (-1203 \cdot 2400 - 1524 \cdot 2400)$$

$$= 45.5040 \text{ KPa.}$$

Calculate the pressure [$P\omega$]:

$$= (U / ao^2) \cdot (\omega s \cdot P's - \omega c \cdot P \cdot c)$$

$$= (0.052 / 86.6^2) \cdot (1235 \cdot 0 - 0 \cdot 0)$$

$$= 0.0000 \text{ KPa.}$$

Determine the effective pressure [Pe]:

$$= J \cdot Kst / (1 + J \cdot Kst (Qz1 + (\rho s - 1) Qz2)) \cdot (P's - P't + P_Y + P\omega + P_W + Prim)$$

$$= 0.1000E+01 \cdot 1.69 / (1 + 1 \cdot 1.69 (1.01 + (1.09 - 1) 0.026)) \cdot (2725 - 3634 + 0 + 0 + 309 + 45.5)$$

$$= -345.5055 \text{ KPa.}$$

ASME Section VIII-2 Part 4.18.8.4 Step 7:

Determine factor [$Q2$]:

$$= [((\omega \cdot s \cdot Ps - \omega \cdot c \cdot Pt) - (\omega s \cdot P's - \omega c \cdot P \cdot c)) + W \cdot \gamma b / (2 \cdot \pi)] / (1 + \phi \cdot Zm)$$

$$= [((-1203 \cdot 2400 - 1524 \cdot 2400) - (1235 \cdot 0 - 0 \cdot 0)) \cdot 0.0001 + 74816 \cdot -0.38 / (2 \cdot \pi)] / (1 + 3.92 \cdot 0.68)$$

$$= -1416.0040 \text{ Kg}$$

Calculate factor [$Q3$]:



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 197 of 204

ASME TS Calc:

Case: 1 9:40a Sep 9, 2026

$$\begin{aligned}
 &= Q1 + 2 \cdot Q2 / (Pe \cdot ao^2) \\
 &= -0.16 + 2 \cdot -1416 / (-346 \cdot 86.6^2) \\
 &= 10.57287
 \end{aligned}$$

Fm Value from Table 4.18.3 = 5.424430

Tubesheet Bending Stress - original thickness [σ]:

$$\begin{aligned}
 &= (1.5 \cdot Fm / \mu \cdot) \cdot (2 \cdot ao / (h - h'g))^2 \cdot Pe \\
 &= (1.5 \cdot 5.42 / 0.2) \cdot (2 \cdot 86.6 / (70 - 0))^2 \cdot -346 \\
 &= -85.9654 \text{ N./mm}^2
 \end{aligned}$$

Allowable Tubesheet Bending Stress [σ allowed]:

$$= 1.5 \cdot S = 1.5 \cdot 135 = 202 \text{ N./mm}^2$$

Tubesheet Bending Stress - final thickness [σ_f]:

$$\begin{aligned}
 &= (1.5 \cdot Fm / \mu \cdot) \cdot (2 \cdot ao / (h - h'g))^2 \cdot Pe \\
 &= (1.5 \cdot 1.36 / 0.2) \cdot (2 \cdot 86.6 / (27 - 0))^2 \cdot 482 \\
 &= 201.8940 \text{ N./mm}^2
 \end{aligned}$$

Reqd Tubesheet Thickness, for Bending Stress (including CA) [HReqB]:

$$\begin{aligned}
 &= h + Cats + Catc \\
 &= 27 + 0 + 0 \\
 &= 27.0014 \text{ mm}
 \end{aligned}$$

ASME Section VIII-2 Part 4.18.8.4 Step 8:

Shear Stress check [τ limit]:

$$\begin{aligned}
 &= (2 \cdot \mu \cdot h / ao) \cdot \min(0.8S; 0.533Sy) \\
 &= (2 \cdot 0.2 \cdot 70 / 86.6) \cdot 108 \\
 &= 34.8302 \text{ N./mm}^2
 \end{aligned}$$

Shear Stress is not required to be computed; [Pe] <= τ limit

Tubesheet Shear Stress is probably low, use the following req. thk:

$$\begin{aligned}
 \text{Tubesheet thickness (Incl. Corr.)} &= 3.8100 \text{ mm} \\
 \text{Tubesheet Shear Stress} &= 16.7185 \text{ N./mm}^2
 \end{aligned}$$

Reqd Tubesheet Thickness for Given Loadings (including CA) [Hreqd]:

$$\begin{aligned}
 &= \max(HreqB; HreqS) \\
 &= \max(27; 3.81) \\
 &= 27.0014 \text{ mm}
 \end{aligned}$$

ASME Section VIII-2 Part 4.18.8.4 Step 9:

The F_{tmin} and F_{tmax} Coefficients from Table 4.18.4:

$$F_{tmin} = 0.24, F_{tmax} = 1.76$$

First Extreme Tube Axial Stress from among all the tubes [σ_{t1}]:

$$\begin{aligned}
 &= ((Ps \cdot xs - Pt \cdot xt) - Pe \cdot F_{tmin}) / (Xt - Xs) \\
 &= ((2400 \cdot 0.56 - 2400 \cdot 0.81) - (-346) \cdot 0.24) / \\
 &\quad (0.81 - 0.56) \\
 &= -2.0619 \text{ N./mm}^2
 \end{aligned}$$

Second Extreme value of Tube Axial Stress from among all the tubes [σ_{t2}]:

$$\begin{aligned}
 &= ((Ps \cdot xs - Pt \cdot xt) - Pe \cdot F_{tmax}) / (Xt - Xs) \\
 &= ((2400 \cdot 0.56 - 2400 \cdot 0.81) - (-346) \cdot 1.76) / \\
 &\quad (0.81 - 0.56) \\
 &= 0.1191 \text{ N./mm}^2
 \end{aligned}$$

Maximum Tube Axial Stress [$\sigma_{t,max}$]:

$$= \max(|\sigma_{t,1}|; |\sigma_{t,2}|) = 2.06 \text{ N./mm}^2$$

Allowable Tube Stress [$\sigma_{t,A}$]:

$$= S_{ot} = 92.2986 \text{ N./mm}^2$$



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 198 of 204

ASME TS Calc:

Case: 1 9:40a Sep 9, 2026

Check for Buckling as some of the tubes are in compression.

Determine the Factor of Safety [Fs]:

$$= \max((3.25 - 0.25(Z_d + Q_3 \cdot Z_w) X_{a^4}); 1.25)$$

$$= \max((3.25 - 0.25(2.48 + 10.6 \cdot 0.17) 0.95^4); 1.25)$$

$$= 2.0000 \text{ (Should be } \leq 2 \text{)}$$

Determine the factor [rt]:

$$= (\sqrt{ (\frac{d_t^2}{4} + (\frac{d_t}{2} - t_t)^2) }) / 4$$

$$= (\sqrt{ (\frac{12.7^2}{4} + (\frac{12.7}{2} - 2.11)^2) }) / 4$$

$$= 3.8177 \text{ mm}$$

Determine the factor [Ct]:

$$= \sqrt{ (2 \cdot \pi^2 \cdot E_t / S_{yt})}$$

$$= \sqrt{ (2 \cdot \pi^2 \cdot 188224240 / 146)}$$

$$= 159.3101$$

Determine the factor [Ft]:

$$= k \cdot L / r$$

$$= 1 \cdot 560 / 3.82$$

$$= 146.6842$$

Buckling Allowable Stress [Stb]:

$$= (S_{y,t} / F_s) \cdot (1 - F_t / (2 \cdot C_t))$$

$$= (146 / 2) \cdot (1 - 147 / (2 \cdot 159))$$

$$= 39.501 \text{ N./mm}^2 \text{ (Never greater than } S_{ot} \text{)}$$

Note: The Axial Compressive stress in tubes is within limits.

Largest tube-to-tubesheet Joint Load [Wt]:

$$= \sigma_{t,max} \cdot \text{Tube Area}$$

$$= 2.06 \cdot 0.7$$

$$= 14.76 \text{ Kg}$$

Tube Metal Area [At]:

$$= \pi (d_o - t) t$$

$$= \pi (12.7 - 2.11) 2.11$$

$$= 0.702 \text{ cm}^2$$

Tube Weld Size Results per UW-20.3:

Tube Strength [Ft]:

$$= \pi \cdot t (d_o - t) S$$

$$= \pi \cdot 2.11 (12.7 - 2.11) 92.3$$

$$= 660.685 \text{ Kg}$$

Groove Weld Strength [Fg]:

$$= 0.85 \cdot \pi \cdot a_g (d_o + 0.67 \cdot a_g) S_w \text{ (but not } > F_t \text{)}$$

$$= 0.85 \cdot \pi \cdot 2.11 (12.7 + 0.67 \cdot 2.11) 92.3$$

$$= 660.6851 \text{ Kg}$$

Weld Strength Factor [fw]:

$$= S / S_w \text{ where } S_w = \min(S \text{ and } S_t)$$

$$= 92.3 / 92.3$$

$$= 1.000$$

Design Strength Ratio [fd]:

$$= 1 \text{ for full strength welds}$$

Fillet Weld Strength [Ff]:

$$= 0.55 \cdot \pi \cdot a_f (d_o + 0.67 \cdot a_f) S_w \text{ (but not } > F_t \text{)}$$

$$= 0.55 \cdot \pi \cdot 2.11 (12.7 + 0.67 \cdot 2.11) 92.3$$

$$= 484.2863 \text{ Kg}$$



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 199 of 204

ASME TS Calc:

Case: 1 9:40a Sep 9, 2026

Minimum Length of Weld [ar]:

$$= 2 \left(\sqrt{(0.75 \cdot do)^2 + 1.07 \cdot t \cdot (do - t) \cdot fw \cdot fd} - 0.75 \cdot do \right)$$

$$= 2 \left(\sqrt{(0.75 \cdot 12.7)^2 + 1.07 \cdot 2.11 \cdot (12.7 - 2.11) \cdot 1 \cdot 1} - 0.75 \cdot 12.7 \right)$$

$$= 2.364 \text{ mm}$$

Minimum Required Fillet Weld Leg [afr]: 1.2660 mm

Minimum Required Groove Weld Leg [agr]: 1.2660 mm

Tube-Tubesheet Jt allowable, 661 is >= tube strength 661 Kgf

Note: This tube-tubesheet joint is a Full Strength joint

ASME Section VIII-2 Part 4.18.8.4 Step 10:

Shell Axial Membrane Allowable Stress:

$$= Ss \cdot Esw = 118 \cdot 1 = 118 \text{ N./mm}^2$$

Axial Membrane Stress in Shell [σs,m]:

$$= ao^2 / ((Ds + ts) \cdot ts) \cdot [Pe + (ps^2 - 1)(Ps - Pt)] + as^2 \cdot Pt / ((Ds + ts) \cdot ts)$$

$$= 86.6^2 / ((189 + 15.1) \cdot 15.1) \cdot [-346 + (1.09^2 - 1)(2400 - 2400)] + 94.5^2 \cdot 2400 / ((189 + 15.1) \cdot 15.1)$$

$$= 6.1292 \text{ N./mm}^2$$

ASME Section VIII-2 Part 4.18.8.4 Step 11:

Note:

For a given Shell thickness of 15.1 mm, the minimum Shell length adjacent to the tubesheet should be 96.026 mm

Shell Membrane Stress due to Joint Interaction [σs,m]:

$$= ao^2 / ((Ds + ts) \cdot ts) \cdot [Pe + (ps^2 - 1)(Ps - Pt)] + as^2 \cdot Pt / ((Ds + ts) \cdot ts)$$

$$= 86.6^2 / ((189 + 15.1) \cdot 15.1) \cdot [-346 + (1.09^2 - 1)(2400 - 2400)] + 94.5^2 \cdot 2400 / ((189 + 15.1) \cdot 15.1)$$

$$= 6.1292 \text{ N./mm}^2$$

Shell Bending Stress due to Joint Interaction [σs,b]:

$$= 6 \cdot ks / ts^2 \cdot \{ \beta s [\delta s \cdot Ps + as^2 \cdot P \cdot s / (Es \cdot ts)] + 6(1 - \nu^2) / (E \cdot h) \cdot (ao/h)^3 \cdot (1 + h \cdot \beta s / 2) \cdot [Pe (Zv + Zm \cdot Q1) + 2 \cdot ao^2 \cdot Zm \cdot Q2] \}$$

$$= 6 \cdot 3.84E+09 / 15.1^2 \cdot \{ 0.033 [0.002725107 \cdot 2400 + 94.5^2 \cdot 0 / (2.82E+09)] + 6(1 - 0.46^2) / (29240470) \cdot (86.6/70)^3 \cdot (1 + 70 \cdot 0.033/2) \cdot [-346 (0.17 + 0.68 \cdot -0.16) + 2/86.6^2 \cdot 0.68 \cdot -1416] \}$$

$$= -148.6209 \text{ N./mm}^2$$

Shell Stress Summation vs. Allowable

$$\therefore |\sigma_{s,m}| + |\sigma_{s,b}| \leq 1.5 \cdot Ss$$

$$\therefore |6.13| + |-149| \leq 177 \text{ N./mm}^2$$

$$\therefore 155, \text{ must be } \leq 177 \text{ N./mm}^2$$

Computations completed for ASME tubesheet configuration: b

Stress/Force Summary for Loadcase D3 un-corr. (Psd,max + Ptd,max):

Stress Description	Actual	Allowable	Pass/Fail
Tubesheet Bend. Stress	86.0 <=	201.9 N./mm ²	Pass
Tubesheet Shear Stress	0.8 <=	107.7 N./mm ²	Pass
Maximum Tube Stress	2.1 <=	92.3 N./mm ²	Pass
Minimum Tube Stress (Buckling)	-2.1 <=	-39.5 N./mm ²	Pass
Maximum Force on any one Tube	14.8 <=	660.7 Kgf	Pass
Axial Membrane Stress in Shell	6.1 <=	118.0 N./mm ²	Pass
Shell Stress (jt. inter.)	154.8 <=	177.0 N./mm ²	Pass



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 200 of 204

ASME TS Calc:

Case: 1 9:40a Sep 9,2026

Thickness Results for Loadcase D3 un-corr. (Psd,max + Ptd,max):

Thickness (mm)	Required	Actual	P/F
Tubesheet Thickness :	27.001	70.000	Ok
Tube-Tubesheet Fillet Weld Leg :	1.266	2.110	Ok
Tube-Tubesheet Groove Weld Leg :	1.266	2.110	Ok

Fixed Tubesheet results per ASME Div. 2 Part 4.18.8 2025

Results for 16 Load Cases:

Case#	--Reqd. Thk. + CA Tbsht Extnsn	----	Tubesheet Bend Allwd	Stresses Shear Allwd	Case Type	Pass/ Fail
D1uc	9.286 37.706	92	202	5 108	Ps+Pt-Th	D1 Ok
D2uc	12.291 ...	11	202	4 108	Ps+Pt-Th	D2 Ok
D3uc	27.001 ...	86	202	1 108	Ps+Pt-Th	D3 Ok
D4uc	3.810 ...	1	202	... 108	Ps+Pt-Th	D4 Ok
O1uc	9.956 ...	92	404	5 108	Ps+Pt+Th	O1 Ok
O2uc	17.766 ...	86	404	5 108	Ps+Pt+Th	O2 Ok
O3uc	9.519 ...	86	404	1 108	Ps+Pt+Th	O3 Ok
O4uc	11.011 ...	75	404	... 108	Ps+Pt+Th	O4 Ok
D1c	46.033 37.706	121	202	5 108	Ps+Pt-Th-c	D1 Ok
D2c	17.660 ...	12	202	5 108	Ps+Pt-Th-c	D2 Ok
D3c	44.664 ...	111	202	1 108	Ps+Pt-Th-c	D3 Ok
D4c	9.810 ...	1	202	... 108	Ps+Pt-Th-c	D4 Ok
O1c	19.099 ...	119	404	5 108	Ps+Pt+Th-c	O1 Ok
O2c	28.959 ...	110	404	5 108	Ps+Pt+Th-c	O2 Ok
O3c	25.349 ...	111	404	1 108	Ps+Pt+Th-c	O3 Ok
O4c	25.054 ...	99	404	1 108	Ps+Pt+Th-c	O4 Ok
Max:	46.0334 37.706 mm	0.600	0.051	(Str. Ratio)		

Load Case Definitions:

[Ps & Pt]:

Shell-side and Tube-side Design or Operating Pressures derived from Psd,min Ptd,max, Psox,min, Ptox,max etc. per the Load Case Tables

[(+/-)Th]:

With or Without Thermal Expansion, Tt,mx & Ts,mx

[c]:

With or Without Corrosion Allowance

[D1, D2, D3]:

Design Load Cases using the Maximum and Minimum Design Pressures

[D4]:

Design Load Case using the Minimum (Vacuum) Pressures (if specified)

[O1, O2, O3, O4]:

Operating Load Cases using the Maximum and Minimum Operating Pressures and Operating Temperatures

Shell Axial Membrane Stress Summary:

Case#	----	Shell Stresses	----	:	----	Shell Band Stress	----	:	Pass
Ten	Allwd	Cmp	Allwd	:	Ten	Allwd	Cmp	Allwd	: Fail



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 201 of 204

ASME TS Calc:

Case: 1 9:40a Sep 9,2026

D1uc	1	117	...	...	...	...	...	...	Ok
D2uc	5	117	...	...	...	...	...	...	Ok
D3uc	6	117	...	...	...	...	...	...	Ok
D4uc	...	117	...	-108	...	...	...	...	Ok
O1uc	1	389	...	...	...	...	...	...	Ok
O2uc	6	389	...	...	...	...	...	...	Ok
O3uc	6	389	...	...	...	...	...	...	Ok
O4uc	...	389	...	...	...	...	...	...	Ok
D1c	1	117	...	...	...	...	...	...	Ok
D2c	7	117	...	...	...	...	...	...	Ok
D3c	8	117	...	...	...	...	...	...	Ok
D4c	...	117	...	-105	...	...	...	...	Ok
O1c	1	389	...	...	...	...	...	...	Ok
O2c	8	389	...	...	...	...	...	...	Ok
O3c	8	389	...	...	...	...	...	...	Ok
O4c	1	389	...	...	...	...	...	...	Ok

Max RATIO 0.069 0.003 ...

Tube, Shell and Channel Stress Summary:

		---- Tube Stresses		Tube Loads		Shell Stress		Channel	Stress Pass		
Case#	Ten	Allwd	Cmp	Allwd	Ld	Allwd	Stress	Allwd	Stress	Allwd	Fail
D1uc	2	92	-1	-39	12	660	170	176	...	...	Ok
D2uc	2	92	-2	-39	11	660	26	176	...	...	Ok
D3uc	2	92	-2	-39	15	660	155	176	...	...	Ok
D4uc	...	92	...	...	...	660	...	176	...	...	Ok
O1uc	2	184	-1	-39	12	1321	169	389	...	...	Ok
O2uc	3	184	-3	-39	23	1321	133	389	...	...	Ok
O3uc	2	184	-2	-39	15	1321	155	389	...	...	Ok
O4uc	2	184	-2	-39	12	1321	147	389	...	...	Ok
D1c	2	92	-1	-39	13	660	219	389	...	...	Ok
D2c	1	92	-1	-39	9	660	36	176	...	...	Ok
D3c	3	92	-3	-39	19	660	197	389	...	...	Ok
D4c	...	92	...	-39	...	660	...	176	...	...	Ok
O1c	2	184	-1	-39	12	1321	218	389	...	...	Ok
O2c	4	184	-4	-39	26	1321	168	389	...	...	Ok
O3c	3	184	-3	-39	19	1321	197	389	...	...	Ok
O4c	2	184	-2	-39	18	1321	189	389	...	...	Ok

Max RATIO 0.028 0.091 0.028 0.958 ...

Summary of Thickness Comparisons for 16 Load Cases:

Thickness (mm)	Required	Actual	P/F
Tubesheet thickness :			
	46.033	70.000	Ok
Tubesheet thickness flanged extension :			
	37.706	54.000	Ok
Tube thickness :			
	0.399	2.110	Ok
Tube-tubesheet fillet weld leg :			
	1.266	2.110	Ok
Tube-tubesheet groove weld leg :			
	1.266	2.110	Ok

Min Shell length of thk, (15.062) adj. to tubesheet: 96.026 mm

Note: This is a full strength Tube to Tubesheet Joint.

Summary of Axial Differential Expansion between Shell and Tubes :

Due to Thermal Expansion Shell Extends by : +.000 mm
 Due to Pressure Shell Compresses by : -0.068 mm
 Due to Pressure + Thermal Shell Compresses by : -0.068 mm

Tubesheet MAWP used to Compute Hydrotest Pressure:

Stress / Force	Tubeside	0 shellside	Shellside	0 tubeside
----------------	----------	-------------	-----------	------------



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 202 of 204

ASME TS Calc:

Case: 1 9:40a Sep 9, 2026

Condition	MAWP	Stress Rat.	MAWP	Stress Rat.
Tubesheet Bending Stress	9740.23	1.000	42122.71	1.000
Tubesheet Shear Stress	43194.61	1.000	58257.62	1.000
Tube Tensile Stress	141007.59	1.000	148292.67	1.000
Tube Compressive Stress	No Calc	No Calc	62592.63	1.000
Tube-Tubesheet Joint load	141007.59	1.000	148289.88	1.000
Shell Stress (Axial, Junction)	9740.23	1.000	24994.27	0.930
Tube Pressure Stress	35368.43	1.000	24994.27	1.000
Tubesheet Extension Stress	10277.60	...	No Calc	No Calc
Minimum MAWP	9740.23		24994.27	

Tubesheet MAPnc used to Compute Hydrotest Pressure:

Stress / Force Condition	Tubeside MAPnc	Ø shellside Stress Rat.	Shellside MAPnc	Ø tubeside Stress Rat.
Tubesheet Bending Stress	13055.24	1.000	44887.56	1.000
Tubesheet Shear Stress	48985.20	1.000	63069.34	1.000
Tube Tensile Stress	146968.98	1.000	148085.11	1.000
Tube Compressive Stress	No Calc	No Calc	73287.18	1.000
Tube-Tubesheet Joint load	146968.98	1.000	148085.14	1.000
Shell Stress (Axial, Junction)	13055.24	1.000	26520.31	0.570
Tube Pressure Stress	35406.67	1.000	26520.31	1.000
Tubesheet Extension Stress	10277.60	...	No Calc	No Calc
Minimum MAPnc	10277.60		26520.31	

(*) Only the design load cases were analyzed to compute the MAWP for determining the test pressure.

Summary of Exchanger Pressure and Thermal Displacements: (mm)

Load Case#	Due to Pressure		Due to Thermal Exp.		Computed Delta Ms	
	UnCorroded	Corroded	UnCorroded	Corroded	UnCorroded	Corroded
1	0.0068	0.0068	...	...	...	...
2	-0.0675	-0.0676	...	...	...	...
3	-0.0635	-0.0636	...	...	...	...
4	0.0027	0.0027	...	...	...	...
5	0.0039	0.0039	...	...	...	...
6	-0.0674	-0.0674	...	...	...	...
7	-0.0635	-0.0636	...	...	...	...
8	...	...	...	...	...	...

Tubesheet MDMT Calculations:

Shell Side MDMT calculation:

Governing thickness on the shell side per figure UCS-66.3 (e):

= max(tubesheet thk/4, min(tubesheet thk, shell thickness))

= max(70/4, min(70, 15.1))

= 17.500 mm

Thickness Ratio = 0.23, Temperature Reduction per Fig. UCS 66.1 = 78 °C

Min Metal Temp. w/o impact per UCS-66, Curve B -11 °C

Min Metal Temp. at Required thickness (UCS 66.1) -104 °C

Min Metal Temp. w/o impact per UG-20(f) -29 °C

Channel Side MDMT calculation:

Governing thickness for the channel side:

= tubesheet thickness/4

= 70/4



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 203 of 204

ASME TS Calc:

Case: 1 9:40a Sep 9, 2026

= 17.500 mm

Thickness Ratio = 0.23, Temperature Reduction per Fig. UCS 66.1 = 78 °C

Min Metal Temp. w/o impact per UCS-66, Curve B -11 °C

Min Metal Temp. at Required thickness (UCS 66.1) -104 °C

Min Metal Temp. w/o impact per UG-20(f) -29 °C

where the MDMT reduction ratio per UCS 66 (b)(1)(b) is:

= max(pt/Tubeside MAPnc, ps/Shellside MAPnc), must be ≤ 1

= max(2400/10278, 2400/26520)

= 0.234

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite 28 Licensee: SL User

FileName : 161-C1-C2 _(Stack)

Page 204 of 204

Problems/Failures Summary:

Step: 32

9:40am

Sep 9, 2026

Noted issues for the current model:

Listed below are the known problem areas for the current design. If one or more of the design flags are turned on, please re-run the analysis. Some of these issues may be resolved when using updated input values.

**** Warning: A standard flange seems to be governing the Shellside MAWP!**

Please review all reports carefully!

PV Elite is a trademark of Hexagon AB, 2026, All rights reserved.



PV Elite[®] Pressure Vessel Design Notes

Project Information	
Project Number	
Client	
Date	
Designer	
Design Code	
Additional Standards	

Design Conditions		
Internal Design Pressure:		
External Design Pressure:		
Design Int. Temperature:		
Design Ext. Temperature:		
Corrosion Allowance:		

Vessel Geometry		
Vessel Type		
Diameter		
Tangent-to-Tangent Length		
Head Type		
Number of Segments		

Material Specifications	
Shell:	
Head:	
Nozzle:	

Nozzle/Opening Details	ID/OD	Size	Rating	Matl.	Reinf.

Miscellaneous		
Support Type		
Number of Supports		
Support Material		
Seismic Code		
Wind Code		
Insulation		
Pressure Test		
Radiography		
Fatigue Analysis		

Analysis Notes: