

C++

Information

Tutorials

Reference

Articles

Forum

Reference

C library:

Containers:

Input/Output:

Multi-threading:

Other:

<algorithm>

<bitset>

<chrono>

<codecvt>

<complex>

<exception>

<functional>

<initializer_list>

<iterator>

<limits>

<locale>

<memory>

<new>

<numeric>

<random>

<ratio>

<regex>

<stdexcept>

<string>

<system_error>

<tuple>

<typeindex>

<typeinfo>

<type_traits>

<utility>

<valarray>

<random>

distributions:

bernoulli_distribution

binomial_distribution

cauchy_distribution

chi_squared_distribution

discrete_distribution

exponential_distribution

extreme_value_distribution

fisher_f_distribution

gamma_distribution

geometric_distribution

lognormal_distribution

negative_binomial_distribution

normal_distribution

piecewise_constant_distribution

piecewise_linear_distribution

poisson_distribution

student_t_distribution

uniform_int_distribution

uniform_real_distribution

weibull_distribution

generators:

default_random_engine

discard_block_engine

independent_bits_engine

knuth_b

linear_congruential_engine

mersenne_twister_engine

minstd_rand

minstd_rand0

mt19937

mt19937_64

random_device

ranlux24

ranlux24_base

ranlux48

ranlux48_base

shuffle_order_engine

subtract_with_carry_engine

other:

generate_canonical

seed_seq

uniform_real_distribution

uniform_real_distribution::(constructor)

member functions:

uniform_real_distribution::a

uniform_real_distribution::b

uniform_real_distribution::max



class template

std::uniform_real_distribution

<random>

template <class RealType = double> class uniform_real_distribution;

Uniform real distribution

Random number distribution that produces floating-point values according to a *uniform distribution*, which is described by the following *probability density function*:

$$p(x|a,b) = \frac{1}{b-a} \quad , \quad a \leq x < b$$

This distribution (also know as rectangular distribution) produces random numbers in a range [a, b) where all intervals of the same length within it are equally probable.

The distribution parameters, a and b, are set on *construction*.

To produce a random value following this distribution, call its member function *operator()*.

Template parameters

RealType

A floating-point type. Aliased as member type *result_type*.

By default, this is *double*.

Member types

The following aliases are member types of *uniform_real_distribution*:

member type	definition	notes
result_type	The first template parameter (RealType)	The type of the numbers generated (defaults to double)
param_type	not specified	The type returned by member <i>param</i> .

Member functions

(constructor)	Construct uniform real distribution (public member function)
operator()	Generate random number (public member function)
reset	Reset distribution (public member function)
param	Distribution parameters (public member function)
min	Minimum value (public member function)
max	Upper bound of range (public member function)

Distribution parameters:

a	Lower bound of range (public member function)
b	Upper bound of range (public member function)

Non-member functions

operator<<	Insert into output stream (function template)
operator>>	Extract from input stream (function template)
relational operators	Relational operators (function template)

Example

```
1 // uniform_real_distribution
2 #include <iostream>
3 #include <random>
4
5 int main()
6 {
7     const int nrolls=10000; // number of experiments
8     const int nstars=95;    // maximum number of stars to distribute
9     const int nintervals=10; // number of intervals
10
11     std::default_random_engine generator;
12     std::uniform_real_distribution<double> distribution(0.0,1.0);
13
14     int p[nintervals]={};
15
16     for (int i=0; i<nrolls; ++i) {
17         double number = distribution(generator);
18         ++p[int(nintervals*number)];
19     }
20
21     std::cout << "uniform_real_distribution (0.0,1.0):" << std::endl;
22     std::cout << std::fixed; std::cout.precision(1);
23
24     for (int i=0; i<nintervals; ++i) {
25         std::cout << float(i)/nintervals << "-" << float(i+1)/nintervals << ": ";
26         std::cout << std::string(p[i]*nstars/nrolls, '*') << std::endl;
27     }
28 }
```

uniform_real_distribution::min
uniform_real_distribution::operator()
uniform_real_distribution::param
uniform_real_distribution::reset
non-member functions:
operator<<
operator>>
relational operators

Ultra Tune Car Servicing

Contact us for your servicing, tyre, vehicle maintenance and repair needs. Go to ultratune.com.au

```
29 | return 0;  
30 | }
```

Possible output:

```
uniform_real_distribution (0.0,1.0):  
0.0-0.1: *****  
0.1-0.2: *****  
0.2-0.3: *****  
0.3-0.4: *****  
0.4-0.5: *****  
0.5-0.6: *****  
0.6-0.7: *****  
0.7-0.8: *****  
0.8-0.9: *****  
0.9-1.0: *****
```

See also

uniform_int_distribution	Uniform discrete distribution (class template)
generate_canonical	Generate canonical numbers (function template)

[Home page](#) | [Privacy policy](#)

© cplusplus.com, 2000-2017 - All rights reserved - v3.1
[Spotted an error? contact us](#)