

[Home](#)[C++](#)[STL](#)[C++11](#)[Multithreading](#)[Python](#)[Design Patterns](#)[Datastructure](#)[About Us](#)[Privacy Policy](#)

# thispointer.com

[C++11 Tutorials](#)[STL](#)[Python](#)[C++ Tutorials](#)[Multithreading](#)[Boost Library ▾](#)[Design Patterns](#)[java](#)[GDB](#)[Datastructure ▾](#)[Subscribe](#)[Home](#) » [insert](#) » [std::map](#) » [STL](#) » You are reading »

## C++ Map Insert Example

👤 Varun ⌚ September 21, 2016 📄 insert, std::map, STL 💬 1 Comment

In this article we will discuss how to insert a key value pair in std::map.

Map internally store elements in a pair of key value i.e.

```
1 | std::pair<key Type, Value Type>
```

So, to add an element in map we can use one of its member function insert() i.e.

```
1 | pair<iterator, bool> insert (const value_type& element);
```

It accepts an object of key value pair and returns an pair of map iterator and bool.

In the returned pair i.e.

```
1 | pair<iterator, bool>
```

**bool** represents the result of insertion and iterator represents the position of newly added element in map.

*If insertion in map is successful then,*

bool —> true

Iterator —> Points to Position of newly added element.

[Vector](#)[List](#)[Deque](#)[Set](#)[Map](#)[MultiMap](#)[STL Algorithms](#)

1.) What's std::vector and why to use it?

2.) Different ways to initialize a vector

3.) How does std::vector works internally

4.) User Defined Objects & std::vector

5.) How to use vector efficiently in C++?

6.) std::vector and Iterator Invalidation

7.) Remove repeated elements from a vector

8.) Fill a vector with random numbers

9.) Hidden cost of std::vector

10.) Adding elements in Vector

### Advertisements

**If insertion in map failed then,**

bool —> false

Iterator —> Pointing to the passed pair

Let's see an example,

Suppose we have a map of string & int as key value pair i.e.

```
1 std::map<std::string, int> mapOfWordCount;
```

To insert an element in it we will create a pair of string & int i.e.

```
1 std::pair<std::string, int>("first", 1)
```

insert() function will return a pair of map iterator & bool i.e.

```
1 std::pair<std::map<std::string, int>::iterator, bool> result;
2 result = mapOfWordCount.insert(std::pair<std::string, int>("first", 1));
```

Now, to check if insertion we will first check the bool in result pair i.e.

```
1 if(result.second == false)
2 {
3     std::cout<<"Failed to add . duplicate key :: " << result.first->first << std::endl;
4 }
5 else
6 {
7     std::cout<<"Successful in Adding , key :: " << result.first->first << std::endl;
8 }
```

Complete example is as follows,

```
1 #include <iostream>
2 #include <map>
3 #include <string>
4 #include <iterator>
5 #include <algorithm>
6
7 void testResult(
8     std::pair<std::map<std::string, int>::iterator, bool> & result) {
9     // Check if Insertion was successful
10    if (result.second == false) {
11        // Insertion Failed
12        std::cout << "Failed to add . duplicate key :: " << result.first->first << std::endl;
13    } else {
14        // Insertion was successful
15        std::cout << "Successful in Adding , key :: " << result.first->first << std::endl;
16    }
17 }
18
19 int main() {
20
21 }
```

**Advertisements**


Microsoft

Get our most popular products free for 1 year

Microsoft Azure

TRY AZURE FREE →

Microsoft Azure

The advertisement features a blue background with the Microsoft logo at the top. Below the logo, the text 'Get our most popular products free for 1 year' is displayed in white. A central image shows a laptop displaying the Azure portal dashboard, which includes various charts and data points. At the bottom, a green button with the text 'TRY AZURE FREE' and a right-pointing arrow is visible, followed by the 'Microsoft Azure' logo.

```

22
23 // Map of string and int
24 std::map<std::string, int> mapOfWordCount;
25
26 // Pair of Map Iterator and bool
27 std::pair<std::map<std::string, int>::iterator, bool> result
28
29 // Insert Element in map
30 result = mapOfWordCount.insert(std::pair<std::string, int>("
31 // Test its result
32 testResult(result);
33
34 // Insert Element in map
35 result = mapOfWordCount.insert(std::pair<std::string, int>("
36 // Test its result
37 testResult(result);
38
39 // Insert Element in map
40 result = mapOfWordCount.insert(std::pair<std::string, int>("
41 // Test its result
42 testResult(result);
43
44 // Try to add duplicate element
45 result = mapOfWordCount.insert(std::pair<std::string, int>("
46 // Test its result
47 testResult(result);
48
49 // Create a map iterator and point to beginning of map
50 std::map<std::string, int>::iterator it = mapOfWordCount.beg
51
52 std::cout << "*****" << std::endl;
53 // Iterate over a map using std::for_each and Lambda function
54 std::for_each(mapOfWordCount.begin(), mapOfWordCount.end(),
55               [](std::pair<std::string, int> element) {
56                   // Accessing KEY from element
57                   std::string word = element.first;
58                   // Accessing VALUE from element.
59                   int count = element.second;
60                   std::cout<<word<<" :: "<<count<<std::endl;
61               });
62
63 return 0;
64 }

```

### Output:

```

1 Successful in Adding , key :: first
2 Successful in Adding , key :: second
3 Successful in Adding , key :: third
4 Failed to add . duplicate key :: third
5 *****
6 first :: 1
7 second :: 2
8 third :: 3

```

To compile the above example in linux use following command,

**g++ -std=c++11 example.cpp**

## Subscribe For latest Tutorials

\* indicates required

Email Address \*

Subscribe

### Advertisements

**SET YOURSELF  
UP FOR  
SUCCESS.**

### Advertisements



## [Click Here to Subscribe for more Articles / Tutorials like this.](#)

Like 466

Share

Search

Search ...

Search

### Related Posts:

- [How to Iterate over a map in C++](#)
- [How to Insert elements in an unordered\\_set in C++11](#)
- [Different ways to insert elements in an unordered\\_map](#)
- [C++ : Different ways to insert elements in Set](#)
- [How to Access Element by index in a Set | C++](#)
- [How to Sort a Map by Value in C++](#)
- [C++ : How to find an element in vector and get its index ?](#)
- [Finding all values for a key in multimap using...](#)
- [C++ : How to find duplicates in a vector ?](#)
- [multimap Example and Tutorial in C++](#)
- [How to iterate a map in reverse order - C++](#)
- [Unordered\\_map Usage Tutorial and Example](#)
- [How to iterate over an unordered\\_map in C++11](#)
- [C++11 'auto' Tutorial and Examples](#)
- [C++ List - Find | Contains : How to search an...](#)
- [How to copy all Values from a Map to a Vector in C++](#)
- [How to search by value in a Map | C++](#)
- [How to Erase / Remove an element from an unordered\\_map](#)
- [Python : How to add / append key value pairs in...](#)
- [Different Ways to initialize an unordered\\_map](#)
- [C++ map : Erase element by key or Iterator or Range](#)
- [C++11 - std::all\\_of\(\) - Algorithm...](#)
- [C++11 : std::any\\_of\(\) Examples and Tutorial](#)
- [How to find an element in unordered\\_map](#)
- [C++ : How to insert element in vector at specific...](#)

## 1 Comment Already



**Aniket Bhardwaj** - December 3rd, 2017 at 7:07 pm

Great Article. As part of code optimization can be skip these additional steps as below:

```
// Pair of Map Iterator and bool  
std::pair<std::map::iterator, bool> result;
```

```
// Insert Element in map  
result = mapOfWordCount.insert(std::pair("first", 1));  
// Test its result  
testResult(result);
```

and replace it with one line code:

```
testResult(mapOfWordCount.insert(std::pair("first", 1)));
```

Please let me know if i am missing something.

[Reply](#)

## Leave a Reply

Your email address will not be published. Required fields are marked \*

This  
site

**Name \***

**Email \***

**Website**

☐ Save my name, email, and website in this browser for the next time I comment.

Post Comment

uses Akismet to reduce spam. [Learn how your comment data is processed.](#)

« [How to Iterate over a map in C++](#)

[How to iterate a map in reverse order](#)

– C++ »

## Python : List

Check if an item exists in List

Check if a list contains all the elements of other list

Create a List and initialize with values

How to Iterate over a List

Insert an element at specific index in List

Sort a list of tuples by 2nd Item

Sort a list of strings

Add an element in list | append() vs extend()

Check if all elements in a List are same

Merge / Join two or more lists

Remove Duplicates from a List

Convert a list to string

Remove element from a list by value or Index

Remove multiple elements from list

## Python : Dictionary

Creating Dictionaries in Python

Iterating over Dictionaries in Python

Check if a key exists in Dictionary

## C++11 - Utilities

std::bind

auto specifier

Variadic Templates

## C++11 - Unordered Set

1.) unordered\_set Basic Example

2.) Initializing an unordered\_set

3.) Inserting elements in an unordered\_set

4.) Searching an element in unordered\_set

5.) unordered\_set - Custom Hasher & Comparator

6.) Unordered\_set & User defined classes

## C++11 - UnorderedMap

Basic Usage Detail and Example

Initializing an unordered\_map

Searching in unordered\_map

Insert elements in unordered\_map

Erasing an element

Erase elements while iterating

## Advertisement

PSD to HTML SERVICE YOU  
Get started

## Design Patterns

Behavioral Design Patterns

Observer Design Pattern  
State Design Pattern  
Strategy Design Pattern

Structural Design Patterns

Composite Design Pattern  
Flyweight Design Pattern

Creational Design Patterns

Factory Method Design Pattern

## Pointers

Pointer vs Reference

Allocating 2D Array Dynamically

## Callbacks in C++

Function Pointers

## STL - Vector

1.) What's std::vector and why to use it?

2.) Different ways to initialize a vector

3.) How does std::vector works internally

4.) User Defined Objects & std::vector

5.) How to use vector efficiently in C++?

6.) std::vector and Iterator Invalidation

7.) Remove repeated elements from a vector

8.) Fill a vector with random numbers

9.) Hidden cost of std::vector

10.) Adding elements in Vector

## STL - Deque

1.) What is std::deque and how deque works internally.

2.) deque vs vector : What to choose ?

## STL - List

1.) std::list Internals & Usage Details

2.) List vs Vector

3.) Different ways to Initialize a list

Get list of all the keys in Dictionary

Get list of all the Values in a Dictionary

Remove multiple keys in Dictionary while Iterating

Remove a key from Dictionary

Add key/value pairs in Dictionary

Find keys by value in Dictionary

Sort a Dictionary by key or Value

Copy a dictionary | Shallow vs Deep Copy

## Python Strings

Access characters in string by index in Python

Iterate over the characters in string

How to Replace characters in a string ?

## Java - Hashmap

What is Hashing and Hash Table?

Associating Multiple values with same Key

Remove elements while Iterating

Update the value of an existing key

Get all keys by a value in HashMap

## Java - HashSet

What is Hashing and Hash Table?

Create and add elements in a HashSet

Iterate over a HashSet

Search for an element in HashSet

std::map vs std::unordered\_map

## C++11 Smart Pointers

shared\_ptr<> Tutorial and Examples

shared\_ptr and Custom Deletor

shared\_ptr vs raw pointer

Create shared\_ptr objects carefully

weak\_ptr Tutorial | shared\_ptr and Cyclic References

unique\_ptr<> Tutorial and Examples

## C++11 Multithreading

Part 1: Three Ways to Create Threads

Part 2: Joining and Detaching Threads

Part 3: Passing Arguments to Threads

Part 4 : Sharing Data & Race Conditions

Part 5 : Fixing Race Conditions using mutex

Part 6 : Need of Event Handling

Part 7: Condition Variables

Part 8: std::future and std::promise

Part 9: std::async Tutorial & Example

Part 10: std::packaged\_task<> Tutorial

## C++11 Rvalue References

lvalue vs rvalue

Is rvalue immutable in C++?

What is rvalue reference in C++11

Function Objects & Functors

## C++ Strings

Find and Replace all occurrences of a string

Find all occurrences of a sub string

Case Insensitive string::find

Convert First Letter of each word to Upper Case

Converting a String to Upper & Lower Case

Trim strings in C++

C++ : How to split a string using String and character as Delimiter?

startsWith() Implementation

endsWith() Implementation

Remove Sub Strings from String

## C++ Memory Management

Memory Leaks

new and delete operator

delete vs []delete

Out Of Memory Errors

Overload new & delete

Restrict Dynamic Deletion

Placement new operator

Delete 'this' pointer

## Polymorphism

Virtual Functions

vTable and vPointer

4.) Erase elements using iterators

5.) Remove elements while Iterating

6.) Remove elements based on External Criterion

7.) Get element by index in List

8.) Searching an element in std::list

9.) Different Ways to iterate over a List

10.) Sorting a List & custom Comparator

## STL - Set

1.) C++ Set basic example and Tutorial

2.) Using std::set with user defined classes

3.) std::set and external Sorting criteria | Comparator

4.) Access Element by index in Set

5.) How to insert elements in Set

6.) How to iterate over a Set

7.) Removing an element from Set

8.) Erase elements while Iterating & Generic erase\_if()

## STL - Map

1.) std::map Usage Detail with examples

2.) std::map and Comparator

3.) std::map & User defined class objects as keys

4.) Set vs Map

5.) How to Iterate over a map in C++

6.) Map Insert Example

7.) Iterate a map in reverse order

Merge two HashSets

Move Constructor

Initializing HashSet  
from an Array

Convert a HashSet into  
an Array

Merge an Array in a  
HashSet

## Java Interview Questions

---

Method Overriding  
Tutorial

Overriding with  
Different Return Type

Calling Base class's  
overridden method

Preventing Method  
Overriding

Need of preventing  
Method Overriding

8.) Check if a key exists  
in a Map

9.) Search by value in a  
Map

10.) Erase by Key |  
Iterators

11.) C++ Map : Operator  
[]

12.) Erase by Value or  
callback

13.) copy all Values  
from a Map to vector

## STL Multimap

---

MultiMap Example and  
Tutorial

multimap::equals\_range  
- Tutorial

## STL Algorithms

---

std::sort Tutorial &  
Example

std::unique Tutorial &  
Example

1.) Using std::find &  
std::find\_if with User  
Defined Classes

2.) Iterating over a  
range of User Defined  
objects and calling  
member function using  
std::for\_each

## Terms and Conditions

---

Terms and Conditions  
Policy