

Search:

Go

Not logged in

Reference <string> string compare

register

log in



C++

Information

Tutorials

Reference

Articles

Forum

Reference

C library:

Containers:

Input/Output:

Multi-threading:

Other:

<algorithm>

<bitset>

<chrono>

<codecvt>

<complex>

<exception>

<functional>

<initializer_list>

<iterator>

<limits>

<locale>

<memory>

<new>

<numeric>

<random>

<ratio>

<regex>

<stdexcept>

<string>

<system_error>

<tuple>

<typeindex>

<typeinfo>

<type_traits>

<utility>

<valarray>

<string>

class templates:

basic_string

char_traits

classes:

string

u16string

u32string

wstring

functions:

stod

stof

stoi

stol

stold

stoll

stoul

stoull

to_string

to_wstring

string

string::string

string::~string

member functions:

string::append

string::assign

string::at

string::back

string::begin

string::capacity

string::cbegin

string::cend

string::clear

string::compare

string::copy

string::cbegin

string::crend

string::c_str

string::data

string::empty

string::end

string::erase

string::find

string::find_first_not_of

public member function

std::string::compare

<string>

C++98	C++11	C++14
<div>string (1)int compare (const string& str) const noexcept;</div> <div>substrings (2)int compare (size_t pos, size_t len, const string& str, size_t subpos, size_t sublen) const;</div> <div>c-string (3)int compare (const char* s) const;</div> <div>buffer (4)int compare (size_t pos, size_t len, const char* s, size_t n) const;</div>		

Compare strings

Compares the value of the [string](#) object (or a substring) to the sequence of characters specified by its arguments.

The *compared string* is the value of the [string](#) object or -if the signature used has a *pos* and a *len* parameters- the substring that begins at its character in position *pos* and spans *len* characters.

This string is compared to a *comparing string*, which is determined by the other arguments passed to the function.

Parameters

- str

Another [string](#) object, used entirely (or partially) as the *comparing string*.
- pos

Position of the first character in the *compared string*.
If this is greater than the [string](#) length, it throws [out_of_range](#).
Note: The first character is denoted by a value of 0 (not 1).
- len

Length of *compared string* (if the string is shorter, as many characters as possible).
A value of [string::npos](#) indicates all characters until the end of the string.
- subpos, sublen

Same as *pos* and *len* above, but for the *comparing string*.
- s

Pointer to an array of characters.
If argument *n* is specified (4), the first *n* characters in the array are used as the *comparing string*.
Otherwise (3), a null-terminated sequence is expected: the length of the sequence with the characters to use as *comparing string* is determined by the first occurrence of a null character.
- n

Number of characters to compare.

[size_t](#) is an unsigned integral type (the same as member type [string::size_type](#)).

Return Value

Returns a signed integral indicating the relation between the strings:

value	relation between <i>compared string</i> and <i>comparing string</i>
0	They compare equal
<0	Either the value of the first character that does not match is lower in the <i>compared string</i> , or all compared characters match but the <i>compared string</i> is shorter.
>0	Either the value of the first character that does not match is greater in the <i>compared string</i> , or all compared characters match but the <i>compared string</i> is longer.

Example

```
1 // comparing apples with apples
2 #include <iostream>
3 #include <string>
4
5 int main ()
6 {
7     std::string str1 ("green apple");
8     std::string str2 ("red apple");
9
10    if (str1.compare(str2) != 0)
11        std::cout << str1 << " is not " << str2 << '\n';
12
13    if (str1.compare(6,5,"apple") == 0)
14        std::cout << "still, " << str1 << " is an apple\n";
15
16    if (str2.compare(str2.size()-5,5,"apple") == 0)
17        std::cout << "and " << str2 << " is also an apple\n";
18
19    if (str1.compare(6,5,str2,4,5) == 0)
20        std::cout << "therefore, both are apples\n";
21
22    return 0;
23 }
```

string::find_first_of
string::find_last_not_of
string::find_last_of
string::front
string::get_allocator
string::insert
string::length
string::max_size
string::operator+=
string::operator=
string::operator[]
string::pop_back
string::push_back
string::rbegin
string::rend
string::replace
string::reserve
string::resize
string::rfind
string::shrink_to_fit
string::size
string::substr
string::swap
member constants:
string::npos
non-member overloads:
getline (string)
operator+ (string)
operator<< (string)
operator>> (string)
relational operators (string)
swap (string)

Yoga Retreats in Bali

Radiantly Alive Retreats in Bali - Yoga, Surf & Wellness Go to radiantlyalive.com

Output:

green apple is not red apple
still, green apple is an apple
and red apple is also an apple
therefore, both are apples

Complexity

Unspecified, but generally up to linear in both the *compared* and *comparing string's lengths*.

Iterator validity

No changes.

Data races

The object is accessed.

Exception safety

Strong guarantee: if an exception is thrown, there are no changes in the *string* (except (1), which is guaranteed to not throw).

If *s* does not point to an array long enough, it causes *undefined behavior*.

If *pos* is greater than the *string* *length*, or if *subpos* is greater than *str's length*, an *out_of_range* exception is thrown.

See also

string::find	Find content in string (public member function)
string::replace	Replace portion of string (public member function)
string::substr	Generate substring (public member function)
relational operators (string)	Relational operators for string (function)