

Search:

Go

C++
Information
Tutorials
Reference
Articles
Forum

Reference
C library:
<cassert> (assert.h)
<cctype> (ctype.h)
<cerrno> (errno.h)
<cfenv> (fenv.h)
<cfloat> (float.h)
< cinttypes> (inttypes.h)
<ciso646> (iso646.h)
<climits> (limits.h)
<locale> (locale.h)
<cmath> (math.h)
< csetjmp> (setjmp.h)
<csignal> (signal.h)
< cstdarg> (stdarg.h)
< cstdbool> (stdbool.h)
< cstddef> (stddef.h)
< cstdint> (stdint.h)
< cstdio> (stdio.h)
< cstdlib> (stdlib.h)
< cstring> (string.h)
< ctmath> (tmath.h)
<ctime> (time.h)
<uchar> (uchar.h)
<wchar> (wchar.h)
<wctype> (wctype.h)
Containers:
Input/Output:
Multi-threading:
Other:

<cstdlib> (stdlib.h)
functions:
abort
abs
atexit
atof
atoi
atol
atoll
at_quick_exit
bsearch
calloc
div
exit
free
getenv
labs
ldiv
llabs
lldiv
malloc
mblen
mbstowcs
mbtowc
qsort
quick_exit
rand
realloc
srand
strtod
strtof
strtol
strtold
strtoll
strtoul
strtoull
system
wcstombs
wctomb
_Exit
functions (non-standard):
itoa
types:
div_t
ldiv_t
lldiv_t
size_t

function **rand** <cstdlib>

Generate random number
Returns a pseudo-random integral number in the range between 0 and **RAND_MAX**.

This number is generated by an algorithm that returns a sequence of apparently non-related numbers each time it is called. This algorithm uses a seed to generate the series, which should be initialized to some distinctive value using function **srand**.

RAND_MAX is a constant defined in **<cstdlib>**.

A typical way to generate trivial pseudo-random numbers in a determined range using **rand** is to use the modulo of the returned value by the range span and add the initial value of the range:

```
1 v1 = rand() % 100;           // v1 in the range 0 to 99
2 v2 = rand() % 100 + 1;       // v2 in the range 1 to 100
3 v3 = rand() % 30 + 1985;      // v3 in the range 1985-2014
```

Notice though that this modulo operation does not generate uniformly distributed random numbers in the span (since in most cases this operation makes lower numbers slightly more likely).

C++ supports a wide range of powerful tools to generate random and pseudo-random numbers (see **<random>** for more info).

Parameters
(none)

Return Value
An integer value between 0 and **RAND_MAX**.

Example

```
1 /* rand example: guess the number */
2 #include <stdio.h>           /* printf, scanf, puts, NULL */
3 #include <stdlib.h>          /* srand, rand */
4 #include <time.h>            /* time */
5
6 int main ()
7 {
8     int iSecret, iGuess;
9
10    /* initialize random seed: */
11    srand (time(NULL));
12
13    /* generate secret number between 1 and 10: */
14    iSecret = rand() % 10 + 1;
15
16    do {
17        printf ("Guess the number (1 to 10): ");
18        scanf ("%d",&iGuess);
19        if (iSecret<iGuess) puts ("The secret number is lower");
20        else if (iSecret>iGuess) puts ("The secret number is higher");
21    } while (iSecret!=iGuess);
22
23    puts ("Congratulations!");
24    return 0;
25 }
```

In this example, the random seed is initialized to a value representing the current time (calling **time**) to generate a different value every time the program is run.

Possible output:


```
Guess the number (1 to 10): 5
The secret number is higher
Guess the number (1 to 10): 8
The secret number is lower
Guess the number (1 to 10): 7
Congratulations!
```

Compatibility
In C, the generation algorithm used by **rand** is guaranteed to only be advanced by calls to this function. In C++, this constraint is relaxed, and a library implementation is allowed to advance the generator on other circumstances (such as calls to elements of **<random>**).

Data races
The function accesses and modifies internal state objects, which may cause data races with concurrent calls to **rand** or **srand**.
Some libraries provide an alternative function that explicitly avoids this kind of data race: **rand_r** (non-portable).

macro constants:

- [EXIT_FAILURE](#)
- [EXIT_SUCCESS](#)
- [MB_CUR_MAX](#)
- [NULL](#)
- [RAND_MAX](#)



Microsoft's
74-409
Server
Virtualization
with Windo...

C++ library implementations are allowed to guarantee no *data races* for calling this function.

Exceptions (C++)

No-throw guarantee: this function never throws exceptions.

See also

srand	Initialize random number generator (function)
-----------------------	---