

Search:

Go

Reference <random> uniform_int_distribution

register

Not logged in
log in

C++
Information
Tutorials
Reference
Articles
Forum

Reference
C library:
Containers:
Input/Output:
Multi-threading:
Other:
<algorithm>
<bitset>
<chrono>
<codecvt>
<complex>
<exception>
<functional>
<initializer_list>
<iterator>
<limits>
<locale>
<memory>
<new>
<numeric>
<random>
<ratio>
<regex>
<stdexcept>
<string>
<system_error>
<tuple>
<typeindex>
<typeinfo>
<type_traits>
<utility>
<valarray>

<random>
distributions:
bernoulli_distribution
binomial_distribution
cauchy_distribution
chi_squared_distribution
discrete_distribution
exponential_distribution
extreme_value_distribution
fisher_f_distribution
gamma_distribution
geometric_distribution
lognormal_distribution
negative_binomial_distribution
normal_distribution
piecewise_constant_distribution
piecewise_linear_distribution
poisson_distribution
student_t_distribution
uniform_int_distribution
uniform_real_distribution
weibull_distribution
generators:
default_random_engine
discard_block_engine
independent_bits_engine
knuth_b
linear_congruential_engine
mersenne_twister_engine
minstd_rand
minstd_rand0
mt19937
mt19937_64
random_device
ranlux24
ranlux24_base
ranlux48
ranlux48_base
shuffle_order_engine
subtract_with_carry_engine
other:
generate_canonical
_seed_seq

uniform_int_distribution
uniform_int_distribution::(constructor)
member functions:
uniform_int_distribution::a
uniform_int_distribution::b
uniform_int_distribution::max
uniform_int_distribution::min



TASTE THE FEELING™

DISCOVER NOW



class template

std::uniform_int_distribution

<random>

```
template <class IntType = int> class uniform_int_distribution;
```

Uniform discrete distribution

Random number distribution that produces integer values according to a *uniform discrete distribution*, which is described by the following *probability mass function*:

$$P(i|a,b) = \frac{1}{b-a+1} \quad , \quad a \leq i \leq b$$

This distribution produces random integers in a range [a, b] where each possible value has an equal likelihood of being produced. This is the distribution function that appears on many trivial random processes (like the result of rolling a die).

The distribution parameters, **a** and **b**, are set on [construction](#).

To produce a random value following this distribution, call its member function [operator\(\)](#).

For a discrete distribution that can have different probabilities for each possible value, see [discrete_distribution](#).

Template parameters

IntType
An integer type. Aliased as member type `result_type`.
By default, this is `int`.

Member types

The following aliases are member types of `uniform_int_distribution`:

member type	definition	notes
<code>result_type</code>	The first template parameter (<code>IntType</code>)	The type of the numbers generated (defaults to <code>int</code>)
<code>param_type</code>	<i>not specified</i>	The type returned by member <code>param</code> .

Member functions

(constructor)	Construct uniform discrete distribution (public member function)
operator()	Generate random number (public member function)
reset	Reset distribution (public member function)
param	Distribution parameters (public member function)
min	Minimum value (public member function)
max	Maximum value (public member function)

Distribution parameters:

a	Lower bound of range (public member function)
b	Upper bound of range (public member function)

Non-member functions

operator<<	Insert into output stream (function template)
operator>>	Extract from input stream (function template)
relational operators	Relational operators (function template)


Example

```
1 // uniform_int_distribution
2 #include <iostream>
3 #include <random>
4
5 int main()
6 {
7     const int nrolls = 10000; // number of experiments
8     const int nstars = 95;    // maximum number of stars to distribute
9
10    std::default_random_engine generator;
11    std::uniform_int_distribution<int> distribution(0,9);
12
13    int p[10]={};
14
15    for (int i=0; i<nrolls; ++i) {
16        int number = distribution(generator);
17        ++p[number];
18    }
19
20    std::cout << "uniform_int_distribution (0,9):" << std::endl;
21    for (int i=0; i<10; ++i)
22        std::cout << i << ": " << std::string(p[i]*nstars/nrolls, '*') << std::endl;
23
24    return 0;
25 }
```


Possible output:

`uniform_int_distribution::operator()
uniform_int_distribution::param`

non-member functions:
`operator<<
operator>>
relational operators`



**Easily
manage
files**



```
uniform_int_distribution (0,9):  
0: *****  
1: *****  
2: *****  
3: *****  
4: *****  
5: *****  
6: *****  
7: *****  
8: *****  
9: *****
```

See also

uniform_real_distribution	Uniform real distribution (class template)
bernoulli_distribution	Bernoulli distribution (class)