



two dimensional vector c++ example



All

Videos

News

Images

Shopping

More

Settings

Tools

About 2,160,000 results (0.70 seconds)

multidimensional vector, how to - C++ Forum - Cplusplus.com

www.cplusplus.com › Forum › General C++ Programming ▼

Mar 18, 2008 - 12 posts - 3 authors

Im trying to make use of a **vector** container to hold my matrix. But I dont know how to configure the **vector** container to be **multidimensional**.

[push back in 2D vectors ?](#) 3 posts 31 Jul 2013

[two dimensional arrays!](#) 17 posts 1 May 2011

[Initialising 2D vectors](#) 8 posts 6 Jul 2009

[Multi-Dimensional Arrays](#) 10 posts 3 Feb 2009

[More results from www.cplusplus.com](#)

c++ - Multi-dimensional vector - Stack Overflow

stackoverflow.com/questions/823562/multi-dimensional-vector ▼

May 5, 2009 - Multi-dimensional **vector** ... How to create a 2D **vector** where in like 2D array ... grow twice in the first dimension `a.push_back(vector<int>());` `a.push_back(vector<int>());` `a[0].push_back(5);` `// a[0].size() == 1, ...` Here is a link to a short **example**. changing all adjacent elements in a **two dimensional vector**.

c++ - Initializing a two dimensional std::vector - Stack Overflow

stackoverflow.com/questions/17663186/initializing-a-two-dimensional-stdvector ▼

Jul 15, 2013 - Use the `std::vector::vector(count, value)` constructor that accepts an initial size and a ...

If a value other zero, say 4 for **example**, was required to be the default then:

```
std::vector<std::vector<int>> fog( A_NUMBER, ...
```

c++ - Two Dimensional Vector push_back - Stack Overflow

stackoverflow.com/questions/16312682/two-dimensional-vector-push-back ▼

May 1, 2013 - What you have is correct except that indexes start at 0 , so it should be ... Here is an

example of your code that works fine. – Jesse Good May 1 ...

[\[PDF\] Introduction to Programming \(in C++\) Multi-dimensional vectors](#)

https://www.cs.upc.edu/~jordicf/Teaching/programming/pdf/IP10_Matrices.pdf ▼

A matrix can be considered a **two-dimensional vector**, i.e. a ... `typedef vector<Row> Matrix; // Matrix:`
a **vector** of rows **Example:** let us find 10 in the matrix.

[\[Solved\] How to use Multidimensional vector in C++ - CodeProject](#)

<https://www.codeproject.com> › General Programming › Uncategorized Quick Answers ▼

Rating: 1 - 2 votes

Sep 10, 2012 - I want to know the process to create and return the 2dimensional and 3dimensional **vector** values where size will be changed dynamically.

[C++ Made Easy HD Tutorial 59 - Multidimensional Vectors - YouTube](#)



https://www.youtube.com/watch?v=InqjNYd_hho ▼

Dec 14, 2012 - Uploaded by CodingMadeEasy

In this tutorial we will be learning about a concept that a lot of people dread and that is **multidimensional** ...

[Creating a Two Dimensional Vector - C/C++ Tutorials - Codecall](#)

forum.codecall.net › Tutorial Forums › C/C++ Tutorials ▼

Mar 31, 2010 - 2 posts - 2 authors

Creating a **Two Dimensional Vector** - posted in C/C++ Tutorials: This ... for **example**, a map class for a game, which would have a **vector** as an ...

[Two dimensional vector in C++ - Ars Technica OpenForum](#)

<https://arstechnica.com/civis/viewtopic.php?t=549105> ▼

Apr 6, 2004 - 10 posts - 7 authors

Is it possible to create a **two dimensional vector** in **C++** and how would you do ... Their **example** of RAI is a 2 dimensional matrix class which is ...

[How to create a 2D vector array using std::vector<> - Quora](#)

<https://www.quora.com/How-do-I-create-a-2D-vector-array-using-std-vector> ▼

You can create a 2D array by doing `int a[5][7]`, but `vector<int> a(5,7)` won't create a 2D **vector** ... For more knowledge on **vectors**, visit **C++ vector** memory and 2D **vectors**. 14.7k Views ... The **two vectors** are **two 1-D** arrays of a class. How do I ...

Searches related to two dimensional vector c++ example

two dimensional vector c++ **initialization**

two dimensional vector **definition**

3 dimensional vector c++

vector vector **int** c++ example

push_back 2d vector c++

vector vector **int** **initialize**

multidimensional vector

vector **of vectors** c++ example

[1](#) [2](#) [3](#) [4](#) [5](#) [6](#) [7](#) [8](#) [9](#) [10](#)

[Next](#)

Winston Hills, New South Wales - From your Internet address - Use precise location - [Learn more](#)

[Help](#)

[Send feedback](#)

[Privacy](#)

[Terms](#)