

Game-theoretic Foundations of Multi-agent Systems

Lecture 9: Learning in Games

Seyed Majid Zahedi

UNIVERSITY OF
WATERLOO



Outline

1. Introduction
2. Fictitious Play
3. Best-response Dynamics
4. No-regret Learning
5. Background: Single-agent Reinforcement Learning
6. Multi-agent Reinforcement Learning



Single-agent vs Multi-agent Learning

- In artificial intelligence (AI), learning is usually performed by **single agent**
- Learning agent learns to function successfully in **unknown environment**
- In multi-agent setting, environment contains other agents
- Agents' learning changes the environment
- These changes **depend** in part on actions of learning agents
- Learning of each agent is **impacted** by learning performed by others
- Different learning rules lead to different **dynamical system**
- Simple learning rules can lead to complex global behaviors of system



Learning and Teaching

- In multi-agent systems, learning and teaching are inseparable
- Agents must consider what they have **learned** from others' past behavior
- They also must consider how they wish to **influence** others' future behavior
- In such setting, learning as **accumulating knowledge** is not always beneficial
- Accumulating knowledge should never hurt, one can always ignore what is learned
- But when one pre-commits to particular strategy for acting on accumulated knowledge, sometimes less is more
- E.g., in game of Chicken, if your opponent is learning your strategy to play best response, then optimal strategy is to always dare



Is Agent Learning in Optimal Way?

- In (repeated or stochastic) zero-sum games, this question is meaningful to ask
- In general, answer depends not only on learning procedure but also on others' behavior
- When all agents adopt same strategy, the setting is called **self-play**
 - E.g., all agents adopt TfT, or all adopt reinforcement learning (RL)
- One way to evaluate learning procedures is based on their performance in self-play
- But learning agents can also be judged by how they do in context of other agent types
 - TfT agent may perform well against TfT agents, but less well against RL agents
- Note that in GT, **optimal strategy** is replaced by **best response** (and equilibrium)



Properties of Learning Rules

- **Safety**: Guarantee agents at least their maxmin value
- **Rationality**: Settle on best response to opponent's strategy whenever opponent settles on stationary strategy
 - Opponent adopts same mixed strategy each time, regardless of the past
- **No regret**: Yield payoff that is no less than payoff agent could have obtained by playing any pure strategy against any set of opponents (details later!)



Outline

1. Introduction
2. Fictitious Play
3. Best-response Dynamics
4. No-regret Learning
5. Background: Single-agent Reinforcement Learning
6. Multi-agent Reinforcement Learning



Fictitious Play: Introduction

- What are agents learning about?
- Arguably, most plausible answer is strategies of others
- **Fictitious** play (FP), one of earliest learning rules, takes this approach
- FP was first introduced by G. W. Brown in 1951¹
- Brown imagined that agents would “**simulate**” the game in their mind and update their future play based on this simulation; hence name fictitious play
- In its current use, FP is misnomer, since each play of the game actually occurs

¹Brown, G. W. “Iterative solution of games by fictitious play.” 1951



Fictitious Play

- Two agents repeatedly play stage game G
- $\eta_i^t(a_{-i})$ denotes number of times agent i has observed a_{-i} before time t
- η_i^1 represents **fictitious past** and cannot be zero for all a_{-i}
- Agents assume that their opponent is using **stationary mixed strategy**
- Agents **update their beliefs** about this strategy at each step according to:

$$\mu_i^t(a_{-i}) = \frac{\eta_i^t(a_{-i})}{\sum_{a'_{-i}} \eta_i^t(a'_{-i})}$$

- μ_i^t is **empirical distribution** of past actions and is treated as mixed strategy
- Agents best-respond to their beliefs about opponent's strategy

$$a_i^{t+1} = \operatorname{argmax}_{a_i} u_i(a_i, \mu_i^t)$$



Fictitious Play: Example

- Consider the following coordination game

| | | |
|---|------|------|
| | L | R |
| U | 3, 3 | 0, 0 |
| D | 4, 0 | 1, 1 |

- Note that this game is dominant solvable with unique NE of (D, R)
- Suppose that $\eta_1^1 = (3, 0)$ and $\eta_2^1 = (1, 2.5)$
- FP proceeds as follows:

| Round | 1's η | 2's η | 1's action | 2's action |
|-------|------------|------------|------------|------------|
| 1 | (3, 0) | (1, 2.5) | D | L |
| 2 | (4, 0) | (1, 3.5) | D | R |
| 3 | (4, 1) | (1, 4.5) | D | R |
| 4 | (4, 2) | (1, 5.5) | D | R |



Fictitious Play: Discussion

- In FP, agents **do not** need to know anything about their opponent's utilities
- FP is somewhat paradoxical as agents assume stationary strategy for their opponent, yet no agent plays stationary strategy except when FP converges
- Even though FP is **belief based** it is also **myopic**
- I.e., agents maximize current utility without considering their future ones
- Agents do not learn **true model** that generates empirical frequencies
- In other words, they do not learn how their opponent is actually playing the game



Convergence of Fictitious Play to Pure Strategies

- Let $\{a^t\}$ be sequence of action profiles generated by FP for G
- Sequence **converges** to a^* if there exists T s.t. $a^t = a^*$ for all $t \geq T$
- a^* is called **steady state** or **absorbing state** of FP
- (I) If sequence converges to a^* , then a^* is pure-strategy NE of G
- (II) If for some t , $a^t = a^*$, where a^* is strict NE of G , then $a^\tau = a^*$ for all $\tau > t$



Proof

- (I) is straightforward, for (II), let $a^t = a^*$, we want to show that $a^{t+1} = a^*$
- First, note that we can write μ as:

$$\mu_i^{t+1} = (1 - \alpha)\mu_i^t + \alpha a_{-i}^t = (1 - \alpha)\mu_i^t + \alpha a_{-i}^*$$

here, abusing notation, a_{-i}^t denotes degenerate probability distribution and:

$$\alpha = \frac{1}{\sum_{a'_{-i}} \eta_i^t(a'_{-i}) + 1}$$

- By linearity of expected utility, we have for all a_i :

$$u_i(a_i, \mu_i^{t+1}) = (1 - \alpha)u_i(a_i, \mu_i^t) + \alpha u_i(a_i, a_{-i}^*)$$

- Since a_i^* maximizes both terms, it follows that it is played at $t + 1$



Convergence of Fictitious Play to Mixed Strategies

- Of course, one cannot guarantee that fictitious play always converges to NE
- In FP, agents only play pure strategies and pure-strategy NE may not exist
- While FP sequence may not converge, its empirical distribution may
- Sequence $\{a^t\}$ converges to s^* in time-average sense if for all i and a_i :

$$\lim_{T \rightarrow \infty} \frac{\sum_{t=1}^T \mathbb{1}(a_i^t = a_i)}{T} = s_i^*(a_i)$$

$\mathbb{1}(\cdot)$ denotes the indicator function

- If FP sequence converges to s^* in the time-average sense, then s^* is NE



Proof

- Suppose $\{a^t\}$ converges to s^* in time-average sense, but s^* is not NE
- There is some i , a'_i , and a_i with $s_i^*(a_i) > 0$ s.t. $u_i(a'_i, s_{-i}^*) > u_i(a_i, s_{-i}^*)$
- Choose ϵ s.t. $\epsilon < (u_i(a'_i, s_{-i}^*) - u_i(a_i, s_{-i}^*)) / 2$
- Choose T s.t. for all $t \geq T$, $|\mu_i^t(a_{-i}) - s_{-i}^*(a_{-i})| < \epsilon / \max_{a'} u_i(a')$ for all a_{-i}
- This is possible because $\mu_i^t(a_{-i}) \rightarrow s_{-i}^*(a_{-i})$ by assumption



Proof (cont.)

- Then, for any $t \geq T$, we have:

$$\begin{aligned} u_i(a_i, \mu_i^t) &= \sum_{a_{-i}} u_i(a_i, a_{-i}) \mu_i^t(a_{-i}) \\ &\leq \sum_{a_{-i}} u_i(a_i, a_{-i}) s_{-i}^*(a_{-i}) + \epsilon \\ &\leq \sum_{a_{-i}} u_i(a'_i, a_{-i}) s_{-i}^*(a_{-i}) - \epsilon \\ &\leq \sum_{a_{-i}} u_i(a'_i, a_{-i}) \mu_i^t(a_{-i}) = u_i(a'_i, \mu_i^t) \end{aligned}$$

- So after sufficiently large t , a_i is never played
- This implies that as $t \rightarrow \infty$, $\mu_i^t(a_i) \rightarrow 0$, which contradicts with $s_i^*(a_i) > 0$



Example: Matching Pennies

- Consider the matching-pennies game

| | | |
|---|-------|-------|
| | H | T |
| H | 1, -1 | -1, 1 |
| T | -1, 1 | 1, -1 |

| Round | 1's η | 2's η | 1's action | 2's action |
|-------|------------|------------|------------|------------|
| 1 | (1.5, 2) | (2, 1.5) | T | T |
| 2 | (1.5, 3) | (2, 2.5) | T | H |
| 3 | (2.5, 3) | (2, 3.5) | T | H |
| 4 | (3.5, 3) | (2, 4.5) | H | H |
| 5 | (4.5, 3) | (3, 4.5) | H | H |
| 6 | (5.5, 3) | (4, 4.5) | H | H |
| 7 | (6.5, 3) | (5, 4.5) | H | T |

- FP continues as deterministic cycle, time average converges to unique NE



Example: (Anti-)Coordination Game

- Note that if empirical distribution of actions converges to NE, there is no guarantee on distribution of played outcomes
- Consider the following coordination game

| | | |
|---|------|------|
| | A | B |
| A | 1, 1 | 0, 0 |
| B | 0, 0 | 1, 1 |

- Note that this game is unique NE of $((0.5, 0.5), (0.5, 0.5))$

| Round | 1's η | 2's η | 1's action | 2's action |
|-------|------------|------------|------------|------------|
| 1 | (0.5, 0) | (0, 0.5) | A | B |
| 2 | (0.5, 1) | (1, 0.5) | B | A |
| 3 | (1.5, 1) | (1, 1.5) | A | B |
| 4 | (1.5, 2) | (2, 1.5) | B | A |



General Fictitious Play Convergence

- Fictitious play converges in time-average sense for game G if:
 - G is zero-sum game
 - G is two-player game where each agent has at most two actions (2x2 games)
 - G is solvable by iterated strict dominance
 - G is **identical-interest game**, i.e., all agents have same payoff function
 - G is **potential game** (more on this later!)



Non-convergence of Fictitious Play

- Convergence of fictitious play **can not** be guaranteed in general
- Shapley showed that in modified rock-scissors-paper game, FP does not converge

| | Rock | Paper | Scissors |
|----------|------|-------|----------|
| Rock | 0, 0 | 0, 1 | 1, 0 |
| Paper | 1, 0 | 0, 0 | 0, 1 |
| Scissors | 0, 1 | 1, 0 | 0, 0 |

- This game has unique NE: each agent mixes uniformly
- Suppose $\eta_1^1 = (1, 0, 0)$ and $\eta_2^1 = (0, 1, 0)$
- Shapley showed that play cycles among 6 (off-diagonal) profiles with periods of ever-increasing length, thus non-convergence



Smooth Fictitious Play (SFP)

- Instead of best-responding to beliefs, agents respond randomly, but somewhat proportional to their expected utility

$$s_i^t(a_i | \mu_i^t) = \frac{\exp(u_i(a_i, \mu_i^t)/\gamma)}{\sum_{a'_i} \exp(u_i(a'_i, \mu_i^t)/\gamma)}$$

- γ is called the **smoothing** parameter
- This is called **soft-max** policy
- Soft-max policy respects best replies, but leaves room for **exploration**
- If all agents use SFP with sufficiently small γ_i , empirical play converges to ϵ -CCE



Outline

1. Introduction
2. Fictitious Play
- 3. Best-response Dynamics**
4. No-regret Learning
5. Background: Single-agent Reinforcement Learning
6. Multi-agent Reinforcement Learning



Best-response Dynamics (BRD): Introduction

- Agents start playing **arbitrary** actions
- In arbitrary order, agents take turns updating their action
- Agent update their action only if doing so can improve their utility
- This is repeated until no agents wants to update their action

Initialize $a = (a_1, \dots, a_n)$ to be arbitrary action profile;
while *there exists i such that $a_i \notin \operatorname{argmax}_{a \in A_i} u_i(a, a_{-i})$* **do**
 | Let a'_i be such that $u_i(a'_i, a_{-i}) > u(a)$;
 | Set $a_i \leftarrow a'_i$;
return a



Best-response Dynamics: Discussion

- If BRD halts, it returns pure strategy Nash equilibrium
 - Every agent must be playing best response
- Does BRD always halt?
 - No: Consider matching pennies/Rock Paper Scissors



Example: Congestion Games

- N is set of n agents
- M is set of m resources
- A_i is set of actions available to agent i
 - a_i represents subset of resources that agent i chooses (i.e., $a_i \subseteq M$)
- ℓ_j is congestion cost function for resources $j \in M$
 - $\ell_j(k)$ represents cost of congestion on resource j when k agents choose j
- $n_j(a)$ is number of agents who choose resource j (i.e., $n_j(a) = |\{i \mid j \in a_i\}|$)
- $c_i(a) = \sum_{j \in a_i} \ell_j(n_j(a))$ is total cost of agent
- Agents minimize their total cost (instead of maximizing their total utility)



BRD in Congestion Games

- Consider **potential function** $\phi : A \rightarrow \mathbb{R}$:

$$\phi(a) = \sum_{j=1}^m \sum_{k=1}^{n_j(a)} \ell_j(k)$$

(Note: **not** social welfare)

- How does ϕ change in one round of BRD? Say i switches from a_i to $b_i \in A_i$
- Well... We know it must have decreased agent i 's cost:

$$\begin{aligned} \Delta c_i &\equiv c_i(b_i, a_{-i}) - c_i(a_i, a_{-i}) \\ &= \sum_{j \in b_i \setminus a_i} \ell_j(n_j(a) + 1) - \sum_{j \in a_i \setminus b_i} \ell_j(n_j(a)) < 0 \end{aligned}$$



BRD in Congestion Games (cont.)

$$\phi(a) = \sum_{j=1}^m \sum_{k=1}^{n_j(a)} \ell_j(k)$$

- Change in potential is:

$$\begin{aligned}\Delta\phi &\equiv \phi(b_i, a_{-i}) - \phi(a_i, a_{-i}) \\ &= \sum_{j \in b_i \setminus a_i} \ell_j(n_j(a) + 1) - \sum_{j \in a_i \setminus b_i} \ell_j(n_j(a)) \\ &= \Delta c_i\end{aligned}$$

- Since ϕ can take on only finitely many values, this cannot go on forever
- And hence BRD halts in congestion games ...
- Which proves the **existence** of pure strategy Nash equilibria!



Example: Load Balancing Games on Identical Servers

- n clients $i \in N$ schedule jobs of size $w_i > 0$ on m identical servers M
- Action space $A_i = M$ for each client
- For each server $j \in M$, load $\ell_j(a) = \sum_{i: a_i=j} w_i$
- Cost of client i is load of server that i chooses : $c_i(a) = \ell_{a_i}(a)$



Load Balancing Games on Identical Servers: Discussion

- *Almost* congestion game — but server costs depend on **which** clients choose them
- BRD converges in load balancing games on identical servers
- Load balancing games on identical servers have pure strategy NE



BRD in Load Balancing Games on Identical Servers

- Consider **potential function** ϕ as:

$$\phi(a) = \frac{1}{2} \sum_{j=1}^m \ell_j(a)^2$$

- Suppose i switches from server j to server j' :

$$\begin{aligned} \Delta c_i(a) &\equiv c_i(j', a_{-i}) - c_i(j, a_{-i}) \\ &= \ell_{j'}(a) + w_i - \ell_j(a) \\ &< 0 \end{aligned}$$



BRD in Load Balancing Games on Identical Servers (cont.)

$$\begin{aligned}\Delta\phi(a) &\equiv \phi(j', a_{-i}) - \phi(j, a_{-i}) \\&= \frac{1}{2} ((\ell_{j'}(a) + w_i)^2 + (\ell_j(a) - w_i)^2 - \ell_{j'}(a)^2 - \ell_j(a)^2) \\&= \frac{1}{2} (2w_i\ell_{j'}(a) + w_i^2 - 2w_i\ell_j(a) + w_i^2) \\&= w_i (\ell_{j'}(a) + w_i - \ell_j(a)) \\&= w_i \cdot \Delta c_i(a) \\&< 0\end{aligned}$$

Note: $\Delta c_i \neq \Delta\phi$



Potential Games

- $\phi : A \rightarrow \mathbb{R}_{\geq 0}$ is **exact potential function** for game G if for all a , i , a_i , and b_i :

$$\phi(b_i, a_{-i}) - \phi(a_i, a_{-i}) = c_i(b_i, a_{-i}) - c_i(a_i, a_{-i})$$

- $\phi : A \rightarrow \mathbb{R}_{\geq 0}$ is **ordinal potential function** for game G if for all a , i , a_i , and b_i :

$$(c_i(b_i, a_{-i}) - c_i(a_i, a_{-i}) < 0) \Rightarrow (\phi(b_i, a_{-i}) - \phi(a_i, a_{-i}) < 0)$$

(i.e. the change in utility is always equal **in sign** to the change in potential)

- BRD is **guaranteed** to converge in game G **iff** G has ordinal potential function



BRD and Potential Games

- We've already seen ordinal potential function \Rightarrow BRD converges
- Lets prove other direction
- Consider graph $G = (V, E)$
- Let each $a \in A$ be a vertex in G (i.e., $V = A$)
- Add directed edge (a, b) if it is possible to go from b to a by best-response move
 - I.e., if there is i such that $b = (b_i, a_{-i})$, and $c_i(b_i, a_{-i}) < c_i(a)$
- BRD can be viewed as traversing this graph
 - Start at arbitrary vertex a , and then traverse arbitrary outgoing edges



BRD and Potential Games (cont.)

- Nash Equilibria are the sinks in this graph
- Suppose BRD converges \Rightarrow there are no cycles in this graph
- So, from every vertex a there is some sink s that is reachable (why?)
- We construct potential function $\phi(a)$ for each vertex a
- $\phi(a)$ is length of **longest** finite path from a to any sink s
- We need: for any edge $a \rightarrow b$, $\phi(b) < \phi(a)$.
- Its true! $\phi(a) \geq \phi(b) + 1$. (why?)



Outline

1. Introduction
2. Fictitious Play
3. Best-response Dynamics
- 4. No-regret Learning**
5. Background: Single-agent Reinforcement Learning
6. Multi-agent Reinforcement Learning



Sequential Prediction: Stock-prediction Example

- Every day GME goes **up** or **down**
- Goal is to predict direction each day before market opens (to buy or short)
- Market can behave arbitrarily/adversarially
- So there is no way we can promise to do **well**
- However, we get **advice**



Expert Advice

- There are N **experts** who make predictions in T rounds
- At each round t , each expert i makes prediction $p_i^t \in \{U, D\}$
- Expertise is self proclaimed — no promise experts know what they're talking about
- We (algorithm) want to aggregate predictions, to make our own prediction p_A^t
- We learn true outcome o^t at the end of each round
- If we predicted incorrectly (i.e. $p_A^t \neq o^t$), then we **made a mistake**



Expert Advice (cont.)

- Goal is to after a while do (almost) as well as **best** expert in hindsight
- To make things easy, we assume for now that there is one **perfect** expert
- Perfect expert never makes mistakes (but we don't know who the expert is)
- Can we find strategy that is guaranteed to make at most $\log(N)$ mistakes?



The Halving Algorithm

Let $S^1 \leftarrow \{1, \dots, N\}$ be set of all experts;

for $t = 1$ *to* T **do**

 Predict with majority vote;

 Observe the true outcome o^t ;

 Eliminate all experts that made a mistake: $S^{t+1} = \{i \in S^t \mid p_i^t = o^t\}$;



The Halving Algorithm: Analysis

- Algorithm predicts with majority vote
- Every time it makes a mistake, at least half of remaining experts are eliminated
- Hence $|S^{t+1}| \leq |S^t|/2$
- On the other hand, perfect expert is never eliminated
- Hence $|S^t| \geq 1$ for all t
- Since $|S^1| = N$, this means there can be at most $\log N$ mistakes
- But what if no expert is perfect? Say the best expert makes OPT mistakes
- Can we find a way to make not too many more than OPT mistakes?



The Iterated Halving Algorithm

Let $S^1 \leftarrow \{1, \dots, N\}$ be the set of all experts;

for $t = 1$ *to* T **do**

if $|S^t| = 0$ **then**

 Reset: Set $S^t \leftarrow \{1, \dots, N\}$

 Predict with majority vote;

 Eliminate all experts that made a mistake: $S^{t+1} = \{i \in S^t \mid p_i^t = o^t\};$



The Iterated Halving Algorithm: Analysis

- Whenever algorithm makes mistake, we eliminate half of experts
- So algorithm can make at most $\log N$ mistakes between any two resets
- But if we reset, it is because since last reset, **every** expert has made mistake
- In particular, between any two resets, **best** expert has made at least 1 mistake
- Algorithm makes at most $\log(N)(\text{OPT} + 1)$ mistakes
- Algorithm is wasteful in that every time we reset, we forget what we have learned!
- How about just **downweight** experts who make mistakes?



The Weighted Majority Algorithm

Set weights $w_i^1 \leftarrow 1$ for all experts i ;

for $t = 1$ *to* T **do**

 Predict with weighted majority vote;

 Down-weight experts who made mistakes: (i.e., if $p_i^t \neq o^t$, set $w_i^{t+1} \leftarrow w_i^t/2$)



The Weighted Majority Algorithm: Analysis

- Let M be total number of mistakes that algorithm makes
- Let $W^t = \sum_i w_i^t$ be total weight at step t
- When algorithm makes mistake, at least half of total weight is cut in half
- So: $W^{t+1} \leq (3/4)W^t$
- If algorithm makes M mistakes, $W^T \leq N \cdot (3/4)^M$
- Let i^* be the best expert, $W^T > w_{i^*}^T = (1/2)^{\text{OPT}}$, which gives:

$$(1/2)^{\text{OPT}} \leq W \leq N(3/4)^M \Rightarrow (4/3)^M \leq N \cdot 2^{\text{OPT}} \Rightarrow M \leq 2.4(\text{OPT} + \log(N))$$

- Algorithm makes at most $2.4(\text{OPT} + \log(N))$ mistakes
- $\log(N)$ is constant, so ratio of mistakes to OPT is 2.4 in limit – not great, but not bad



What Do We Want in an Algorithm?

- Make only $1\times$ as many mistakes as OPT in limit, rather than $2.4\times$
- Handle arbitrary costs in $[0, 1]$ per expert per round, not just right and wrong



New Model/Algorithm

- In rounds $1, \dots, T$, algorithm chooses some expert i^t
- Each expert i experiences loss: $\ell_i^t \in [0, 1]$
- Algorithm experiences the loss of the expert it chooses: $\ell_A^t = \ell_{i^t}^t$
- Total loss of expert i is $L_i^T = \sum_{t=1}^T \ell_i^t$
- Total loss of algorithm is $L_A^T = \sum_{t=1}^T \ell_A^t$
- Goal is to obtain loss “not much worse” than that of the best expert: $\min_i L_i^T$



Multiplicative Weights (MW) Algorithm (a.w.a. Hedge Algorithm)

Set weights $w_i^1 \leftarrow 1$ for all experts i ;

for $t = 1$ **to** T **do**

 Let $W^t = \sum_{i=1}^N w_i^t$;

 Choose expert i with probability w_i^t / W^t ;

 For each i , set $w_i^{t+1} \leftarrow w_i^t \cdot \exp(-\epsilon \ell_i^t)$;

- Can be viewed as “smoothed” version of weighted majority algorithm
- Has parameter ϵ which controls how quickly it down-weights experts
- Is *randomized* — chooses experts w.p. proportional to their weights
- Can be used with alternative update: $w_i^{t+1} \leftarrow w_i^t \cdot (1 - \epsilon \ell_i^t)$



Multiplicative Weights Algorithm: Discussion

- For any sequence of losses, and any expert k :

$$\frac{1}{T} \mathbb{E}[L_{MW}^T] \leq \frac{1}{T} L_k^T + \epsilon + \frac{\ln(N)}{\epsilon \cdot T}$$

- In particular, setting $\epsilon = \sqrt{\ln(N)/T}$:

$$\frac{1}{T} \mathbb{E}[L_{MW}^T] \leq \frac{1}{T} \min_k L_k^T + 2\sqrt{\frac{\ln(N)}{T}}$$

- Average loss quickly approaches that of best expert **exactly**, at rate of $1/\sqrt{T}$
- This works for **arbitrary** sequence of losses (e.g., chosen adaptively by adversary)
- So we could use it to play games (**experts** \leftrightarrow **actions** and **losses** \leftrightarrow **costs**)



Recall: Minimax Theorem (John von Neumann, 1928)

In any finite, two-player, zero-sum game, in any NE, each agent receives a payoff that is equal to both their maxmin value and their minmax value

$$\max_{s_i} \min_{s_{-i}} u_i(s_i, s_{-i}) = \min_{s_{-i}} \max_{s_i} u_i(s_i, s_{-i})$$



Simple Proof for Minimax Theorem

- Scale utilities such that u_1 is in $[0, 1]$
- Write $v_1 = \min_{s_2} \max_{s_1} u_1(s_1, s_2)$ and $v_2 = \max_{s_1} \min_{s_2} u_1(s_1, s_2)$
- Suppose theorem were false: $v_1 = v_2 + \epsilon$ for some constant $\epsilon > 0$
- Suppose A1 and A2 repeatedly play against each other as follows
 - A2 uses MW algorithm: at round t , $s_2^t(a_2) = w_{a_2}^t / W^t$
 - A1 plays best response to A2's strategy: $s_1^t = \operatorname{argmax}_{s_1} u_1(s_1, s_2^t)$



Simple Proof for Minimax Theorem (cont.)

- For A2's MW algorithm, we have:

$$\frac{1}{T} \sum_{t=1}^T \mathbb{E}[u_1(a_1^t, a_2^t)] \leq \frac{1}{T} \min_{a_2} \sum_{t=1}^T u_1(a_1^t, a_2) + 2\sqrt{\frac{\log n}{T}}$$

- Let \bar{s}_1 be mixed strategy that puts weight $1/T$ on each action a_1^t , we have:

$$\frac{1}{T} \min_{a_2} \sum_{t=1}^T u_1(a_1^t, a_2) = \min_{a_2} \sum_{t=1}^T \frac{1}{T} u_1(a_1^t, a_2) = \min_{a_2} u_1(\bar{s}_1, a_2)$$

- By definition, we have: $\min_{a_2} u_1(\bar{s}_1, a_2) \leq \max_{s_1} \min_{a_2} u_1(s_1, a_2) = v_2$, and so:

$$\frac{1}{T} \sum_{t=1}^T \mathbb{E}[u_1(a_1^t, a_2^t)] \leq v_2 + 2\sqrt{\frac{\log n}{T}}$$



Simple Proof for Minimax Theorem (cont.)

- On the other hand, A1 best responds to A2's mixed strategy:

$$\begin{aligned}\frac{1}{T} \sum_{t=1}^T \mathbb{E}[u_1(a_1^t, a_2^t)] &= \frac{1}{T} \sum_{t=1}^T \max_{a_1} u_1(a_1, s_2^t) \\ &\geq \frac{1}{T} \sum_{t=1}^T \min_{s_2} \max_{a_1} u_1(a_1, s_2) = \frac{1}{T} \sum_{t=1}^T v_1 = v_1\end{aligned}$$

- Combining these inequalities, we get: $v_1 \leq v_2 + 2\sqrt{\log n/T}$
- Since $v_1 = v_2 + \epsilon$, we have: $\epsilon \leq 2\sqrt{\log n/T}$
- Taking T large enough leads to contradiction



Incomplete Feedback

- The MW algorithm is simple, elegant, and offers strong regret guarantees
- However, it relies on **restrictive** assumption
- The algorithm has to observe loss of **all** experts at every round
- Unfortunately, this assumption does not hold in many setting
- More realistic assumption is that **only** the loss of **selected expert** is observed



Exp3 Algorithm

Set $u \leftarrow (1/N, \dots, 1/N)$;

Set weights $w_i^1 \leftarrow 1$ for all experts i ;

for $t = 1$ **to** T **do**

 Let $W^t = \sum_{i=1}^N w_i^t$;

 Calculate $p_i^t \leftarrow w_i^t / W^t$ for all i ;

 Calculate probabilities: $q^t = (1 - \gamma)p^t + \gamma u$;

 Choose expert i_t randomly according to q^t ;

 Observe expert i_t 's loss $\ell_{i_t}^t$;


 Set other experts losses: $\ell_i^t \leftarrow 0$ for all $i \neq i_t$;

 Calculate scaled losses: $\hat{\ell}_i^t \leftarrow \ell_i^t / q_i^t$ for all i ;

 Update weights: $w_i^{t+1} \leftarrow w_i^t \cdot \exp(-\epsilon \hat{\ell}_i^t)$ for all i ;



Exp3 Algorithm



Analysis of Exp3

- $\mathbb{E}[\hat{\ell}_i^t] = \ell_i^t / q_i^t \cdot q_i^t + 0 \cdot (1 - q_i^t) = \ell_i^t$
- True loss is in $[0, 1]$, but MW sees losses in $[0, N/\gamma]$
- From analysis of MW, we have:

$$\frac{1}{T} \mathbb{E}_p[\hat{L}_{MW}^T] \leq \frac{1}{T} \hat{L}_k^T + \frac{N}{\gamma} \left(\epsilon + \frac{\ln(N)}{\epsilon \cdot T} \right)$$

- Taking expectation over both sides, we have:

$$\frac{1}{T} \mathbb{E}_p[L_{MW}^T] \leq \frac{1}{T} L_k^T + \frac{N}{\gamma} \left(\epsilon + \frac{\ln(N)}{\epsilon \cdot T} \right)$$



Analysis of Exp3 (cont.)

- We make decisions based on q not p :

$$\begin{aligned}\frac{1}{T} \mathbb{E}_q[L_{MW}^T] &= \frac{(1-\gamma)}{T} \mathbb{E}_p[L_{MW}^T] + \frac{\gamma}{TN} \sum_i L_i^T \\ &\leq \frac{1}{T} L_k^T + \frac{N}{\gamma} \left(\epsilon + \frac{\ln(N)}{\epsilon \cdot T} \right) + \gamma\end{aligned}$$

- Setting $\epsilon = \sqrt{\ln(N)/T}$ and $\gamma = \sqrt{N} (\ln(N)/T)^{1/4}$ gives regret of $\approx N^{1/4} T^{3/4}$



External Regret

- Sequence a^1, \dots, a^T has **external regret** of $\Delta(T)$ if for every agent i and action a'_i :

$$\frac{1}{T} \sum_{t=1}^T u_i(a^t) \geq \frac{1}{T} \sum_{t=1}^T u_i(a'_i, a_{-i}) - \Delta(T)$$

- If $\Delta(T) = o_T(1)$, we say that sequence of action profiles has *no* external regret
- External regret measures regret to the best **fixed** action in hindsight
- If a^1, \dots, a^T has ϵ external regret, then distribution π that puts weight $1/T$ on each a^t (i.e., empirical distribution of actions) forms **ϵ -approximate CCE**

$$\mathbb{E}_{a \sim \pi}[u_i(a)] = \frac{1}{T} \sum_{t=1}^T u_i(a^t) \geq \frac{1}{T} \sum_{t=1}^T u_i(a'_i, a_{-i}) - \epsilon = \mathbb{E}_{a \sim \pi}[u_i(a'_i, a_{-i})] - \epsilon$$



No-(external-)regret Dynamics

- Suppose that all agents use MW algorithm to choose between k actions
- After T steps, sequence of outcomes has external regret of $\Delta(T) = 2\sqrt{\log k/T}$
- Empirical distribution of outcomes forms $\Delta(T)$ -approximate CCE
- For $T = 4 \log(k)/\epsilon^2$, distribution of outcomes converges to ϵ -approximate CCE



Swap Regret

- Sequence a^1, \dots, a^T has **swap regret** of $\Delta(T)$ if for every agent i and every **switching function** $F_i : A_i \rightarrow A_i$:

$$\frac{1}{T} \sum_{t=1}^T u_i(a^t) \geq \frac{1}{T} \sum_{t=1}^T u_i(F_i(a_i), a_{-i}) - \Delta(T)$$

- If $\Delta(T) = o_T(1)$, we say that sequence of action profiles has no swap regret
- This measures regret to counterfactual case where every action of particular type is swapped with different action in hindsight, separately for each action
- E.g., “Every time i bought Microsoft, i should have bought Apple, and every time i bought Google, i should have bought Comcast.”
- If a^1, \dots, a^T has ϵ swap regret, then distribution π that picks among a^1, \dots, a^T uniformly at random is ϵ -approximate correlated equilibrium



Generalization

- For any agent i , F_i , and $a \in A$, define **regret** as:

$$\text{Regret}_i(a, F_i) = u_i(F_i(a_i), a_{-i}) - u_i(a)$$

- F_i is **constant** switching function if $F_i(a_i) = F_i(a'_i)$ for all $a_i, a'_i \in A_i$
- π is CCE if for every agent i and every constant switching function F_i :

$$\mathbb{E}_{a \sim \pi}[\text{Regret}_i(a, F_i)] \leq 0$$

- π is CE if for every agent i and every switching function F_i :

$$\mathbb{E}_{a \sim \pi}[\text{Regret}_i(a, F_i)] \leq 0$$



How to Achieve No Swap Regret

- Define set of time steps that expert j is selected:

$$S_j = \{t : a_t = j\}$$

- Observation: To achieve no swap regret it would be sufficient that for every j :

$$\frac{1}{|S_j|} \sum_{t \in S_j} \ell_{a_t}^t \leq \frac{1}{|S_j|} \min_i \sum_{t \in S_j} \ell_i^t + \Delta(T)$$

- No **swap** regret = no **external** regret separately on each sequence of actions S_j
- Best switching function in hindsight = swapping each action j for best fixed action in hindsight over S_j
- Idea: Run k copies of PW, one responsible for each S_j




Algorithm Sketch for No Swap Regret

- Initialize k copies of MW algorithm one for each of k actions
- Let $q(i)_1^t, \dots, q(i)_k^t$ be distribution over experts for copy i at time t
- Combine these into single distribution over experts: p_1^t, \dots, p_k^t (details later!)
- Let $\ell_1^t, \dots, \ell_k^t$ be losses for experts at time t
- For copy i of MW algorithm, we **report** losses $p_i^t \ell_1^t, \dots, p_i^t \ell_k^t$
- I.e., to copy i , we report the true losses scaled by p_i^t



No-swap-regret Algorithm



No-swap-regret Algorithm: Analysis

- Expected cost of the master algorithm:

$$\frac{1}{T} \sum_{t=1}^T \sum_{i=1}^k p_i^t \cdot \ell_i^t \quad (1)$$

- Expected cost under switching function F

$$\frac{1}{T} \sum_{t=1}^T \sum_{i=1}^k p_i^t \cdot \ell_{F(i)}^t \quad (2)$$

- Goal: prove that (1) is at most (2) plus $\Delta(T) = o_T(1)$



No-swap-regret Algorithm: Analysis (cont.)

- Expected cost of M_j :

$$\frac{1}{T} \sum_{t=1}^T \sum_{i=1}^k q(j)_i^t (p_j^t \cdot \ell_i^t) \quad (3)$$

- M_j is no-regret algorithm, so its cost is at most:

$$\frac{1}{T} \sum_{t=1}^T p_j^t \cdot \ell_{F(j)}^t + \Delta(T) \quad (4)$$

for any arbitrary F



No-swap-regret Algorithm: Analysis (cont.)

- Summing inequality between (3) and (4) over all copies:

$$\frac{1}{T} \sum_{t=1}^T \sum_{i=1}^k \sum_{j=1}^k q(j)_i^t (p_j^t \cdot \ell_i^t) \leq \frac{1}{T} \sum_{t=1}^T \sum_{j=1}^k p_j^t \cdot \ell_{F(j)}^t + k \cdot \Delta(T) \quad (5)$$

- Right-hand side is equal to (2)
- For left-hand side to be equal to (1), we need:

$$p_i^t = \sum_{j=1}^k p_j^t \cdot q(j)_i^t$$



Combining Distributions

$$p_i^t = \sum_{j=1}^k p_j^t \cdot q(j)_i^t$$

- These might be familiar as those defining **stationary distribution** of **Markov chain**
 - There are k states, probability of going to state i from j is $q(j)_i^t$
 - Stationary distribution over states is $(p_1^t \dots p_k^t)$
- These equations **always** have solution as probability distribution
- Crucial property: two ways of viewing the distribution over experts:
 - Each expert i is chosen with probability p_i^t or
 - W.p. p_j^t we select copy j and then select expert i w.p. $q(j)_i^t$



Regret Matching

- α^t : Average per-step reward received by agent up until time t
- $\alpha^t(a)$: Average per-period reward that would have been received up until time t had pure strategy a was played by agent, assuming others played the same
- **Regret** at time t for not having played a : $R^t(a) = \alpha^t(a) - \alpha^t$
- **Regret matching**: At time t , choose action a w.p. proportional to its regret:

$$s^t(a) = \frac{R^t(a)^+}{\sum_{a'} R^t(a')^+}$$




Outline

1. Introduction
2. Fictitious Play
3. Best-response Dynamics
4. No-regret Learning
5. Background: Single-agent Reinforcement Learning
6. Multi-agent Reinforcement Learning




Reinforcement Learning

- Still assume MDP
 - Set of states $s \in S$
 - Set of actions $a \in A$
 - Model $p(s, a, s')$
 - Reward $r(s, a, s')$
- Still looking for policy $\pi(s)$
- New twist: we do not know p or r
- I.e. we do not know which states are good or what actions do
- Must actually try actions and states out to learn



Offline (MDPs) vs. Online (RL)



Offline solution



Online solution

Why Not Use Policy Evaluation?

- Simplified **Bellman updates** calculate V and Q for a fixed policy

$$V_t^\pi(s) \leftarrow \sum_{s'} p(s, \pi(s), s') (r(s, \pi(s), s') + \delta V_{t-1}^\pi(s'))$$

- This approach fully exploited connections between the states
- Unfortunately, we need p and r to do it!



Temporal Difference (TD) Learning

- Main idea: learn from every experience!
 - Update $V(s)$ each time we experience a transition (s, a, s', r)
 - Likely outcomes s' will contribute updates more often
- Temporal difference learning of values
 - Policy still fixed, still doing evaluation!
 - Move values toward value of whatever successor occurs: running average

Sample of $V(s)$: $r(s, a, s') + \delta V^\pi(s')$

Update of $V(s)$: $V^\pi(s) \leftarrow (1 - \alpha)V^\pi(s) + \alpha(r(s, a, s') + \delta V^\pi(s'))$

Same update : $V^\pi(s) \leftarrow V^\pi(s) + \alpha(r(s, a, s') + \delta V^\pi(s') - V^\pi(s))$



Problems with TD Value Learning


- TD value learning is model-free way to do policy evaluation
- It mimics Bellman updates with running sample averages
- However, if we want to turn values into (new) policy, we need p and r !

$$\begin{aligned}\pi(s) &= \operatorname{argmax}_a Q(s, a) \\ Q^\pi(s, a) &= \sum_{s'} p(s, a, s') (r(s, a, s') + \delta V(s'))\end{aligned}$$

- To solve this, we can learn Q-values instead of values
- This makes action selection model-free too!



Active Reinforcement Learning



Q-learning

- Q-Learning is sample-based Q-value iteration

$$Q_t(s, a) \leftarrow \sum_{s'} p(s, a, s') \left(r(s, a, s') + \delta \max_{a' \in A} Q_{t-1}(s', a') \right)$$

- We learn $Q(s, a)$ values as we go

$$\text{Sample : } r(s, a, s') + \delta \max_{a' \in A} Q(s', a')$$

$$\text{Update : } Q(s, a) \leftarrow (1 - \alpha_t) Q(s, a) + \alpha_t \left(r(s, a, s') + \delta \max_{a' \in A} Q(s', a') \right)$$



Q-learning Algorithm

repeat *until convergence*

 observe current state s ;

 select action a and take it (e.g., via ϵ -greedy policy);

 observe next state s' and reward $r(s, a, s')$;

$Q_{t+1}(s, a) \leftarrow (1 - \alpha_t)Q_t(s, a) + \alpha_t (r(s, a, s') + \delta V_t(s'))$;

$V_{t+1}(s) \leftarrow \max_a Q_t(s, a)$;

- ϵ -greedy: W.p. ϵ , act randomly, w.p. $(1 - \epsilon)$ act according to Q_t



Q-learning Properties

- Q-learning converges to optimal policy – even if agent acts sub-optimally!
- This is called **off-policy learning**
- There are some caveats
 - We have to explore enough
 - We have to eventually make the learning rate small enough
 - But we should not decrease it too quickly
 - Q-learning converges if $\sum_0^\infty \alpha_t = \infty$ and $\sum_0^\infty \alpha_t^2 < \infty$
 - Basically, in the limit, it does not matter how you select actions (!)



Outline

1. Introduction
2. Fictitious Play
3. Best-response Dynamics
4. No-regret Learning
5. Background: Single-agent Reinforcement Learning
- 6. Multi-agent Reinforcement Learning**



Independent Single-agent RL

- Setting: Two-player zero-sum games
- Naive idea: Agents **ignore** the existence of their opponent
- $Q_i^\pi(s, a_i)$: Value for i if both agents follow π starting from s and i plays a_i
- Learning dynamics: Agents deploy **independent Q-learning**
- **Good news**: **No-regret** property if opponent plays stationary policy
- **Bad news**: No convergence guarantee if both agents are learning (e.g., **self play**)!



Minimax-Q

- Littman² extended Q-learning algorithm to zero-sum stochastic games
- Main idea is to modify Q -function to consider actions of opponent

$$Q_{i,t+1}(s_t, a_t) = (1 - \alpha_t)Q_{i,t}(s_t, a_t) + \alpha_t (r_i(s_t, a_t) + \delta V_{i,t}(s_{t+1}))$$

- Since game is zero sum, we can have

$$V_{i,t}(s) = \max_{\pi_i} \min_{a_{-i}} Q_{i,t}(s, \pi_i, a_{-i})$$

²Littman, M. L. "Markov games as a framework for multi-agent reinforcement learning." 1994



Minimax-Q Algorithm

repeat *until convergence*

observe current state s ;

select action a_i and take it (e.g., via ϵ -greedy policy);

observe action profile a ;

observe next state s' and reward $r(s, a, s')$;

$Q_{i,t+1}(s, a) \leftarrow (1 - \alpha_t)Q_{i,t}(s, a) + \alpha_t (r(s, a) + \delta V_{i,t}(s'))$;

$\pi_i(s, \cdot) \leftarrow \operatorname{argmax}_{\pi'} \min_{a_{-i}} \sum_{a_i} \pi'(s, a_i) Q_{i,t}(s, a_i, a_{-i})$;

$V_{t+1}(s) \leftarrow \min_{a_{-i}} \sum_{a_i} \pi(s, a_i) Q_{i,t}(s, a_i, a_{-i})$;



Minimax-Q Algorithm: Discussion

- It guarantees agents payoff at least equal to that of their maxmin strategy
- In zero-sum games, minimax-Q converges to the value of the game in self play
- It no longer satisfies no-regret property
- If opponent plays sub-optimally, minimax-Q does not exploit it in most games



Nash-Q

- Hu and Wellman³ extended minimax-Q to general-sum games
- Algorithm is structurally identical to minimax-Q
- Extension requires that each agent maintains values for all other agents
- LP to find maxmin value is replaced with quadratic programming to find NE
- Nash-Q makes number of very limiting assumptions (e.g., uniqueness of NE)

³Hu, J, and Wellman, M. P. "Multiagent reinforcement learning: theoretical framework and an algorithm." 1998



Recall: Stochastic Games Model

- Focus on **stationary Markov strategies** (a mixed strategy per state)
- $\pi_i : S \mapsto \Delta(A_i)$ denotes (mixed) strategy of agent i at state s
- $\pi = (\pi_1, \dots, \pi_n)$ denotes strategy profile of all agents
- **Expected utility (value) function** of agent i is

$$v_i(s, \pi) := \mathbb{E}_{a_k \sim \pi(s_k)} \left[\sum_{k=0}^{\infty} \delta^k r_i(s_k, a_k) \mid s_0 = s \right]$$



Equilibrium Characterization

- Equilibrium **value function** is defined using **one-stage deviation** principle (**multi-agent** extension of **Bellman's equation**) as

$$v_i(s, \pi^*) = \max_{\pi_i} \mathbb{E}_{a \sim (\pi_i, \pi_{-i}^*(s))} \left[r_i(s, a) + \delta \sum_{s' \in S} p(s, a, s') v_i(s', \pi^*) \right]$$

- **Q-function** is defined as

$$Q_i(s, a, \pi^*) = r_i(s, a) + \delta \sum_{s' \in S} p(s, a, s') v_i(s', \pi^*)$$

- Recursion is then defined as

$$v_i(s, \pi^*) = \max_{\pi_i} \mathbb{E}_{a \sim (\pi_i, \pi_{-i}^*(s))} [Q_i(s, a, \pi^*)]$$



FP for Model-based Learning

- Consider learning dynamic that combines FP with value-function (or Q-function) iteration
- Agents form beliefs on opponent strategies (using empirical frequencies and assuming opponent uses stationary strategy)
- Agents also form beliefs about **equilibrium** value function, or Q-function
- Agents then choose best response action in **auxiliary game** given their beliefs (where payoffs are given by Q-function estimates)
- Key challenge is that payoffs or value functions in these auxiliary games are **non-stationary** (unlike repeated play of stage games)



FP for Model-based Learning: Model

- At time t , i 's belief on $-i$'s strategy is μ_i^t and on own Q-function is

$$Q_i^t := \mathbb{E}_{a_{-i} \sim \mu_i^t(s)} [Q_i^t(s, a_i, a_{-i})]$$

- Agent i selects best response $a_i^t(s) \in \operatorname{argmax}_{a_i} Q_i^t(s, a_i, \mu_i^t(s))$
- Agent i updates μ_i as

$$\mu_i^{t+1}(s) = (1 - \alpha_t) \mu_i^t(s) + \alpha_t a_{-i}^t(s)$$

- Agent i updates Q_i as

$$Q_i^{t+1}(s, a) = (1 - \beta_t) Q_i^t(s, a) + \beta_t \left(r_i(s, a) + \delta \sum_{s' \in S} p(s, a, s') v_i^t(s') \right)$$

where $v_i^t(s') = \max_{a_i} Q_i^t(s', a_i, \mu_i^t(s))$



Two-timescale Learning Framework

- Beliefs on Q-functions are updated at slower rate than beliefs on opponent strategies
- This postulate agents' choices to be more dynamic than changes in their preferences
- Q-functions in auxiliary games can be viewed as slowly evolving agent preferences
- This enables weakening the dependence between evolving strategies and Q-functions



Convergence of Two-timescale Learning Framework

- If each state is visited **infinitely** many times
- And, if $\lim_{k \rightarrow \infty} \alpha_k = \lim_{k \rightarrow \infty} \beta_k = 0$ and $\sum_k \alpha_k = \sum_k \beta_k = \infty$
- And, if $\lim_{k \rightarrow \infty} \beta_k / \alpha_k = 0$ (two-timescale learning: $\beta_k \rightarrow 0$ faster than $\alpha_k \rightarrow 0$)
- Then Q and μ converge to NE value and strategy in zero-sum stochastic games
- They also converge to NE value for single-controller stochastic games



Acknowledgment

- This lecture is a slightly modified version of ones prepared by
 - Asu Ozdaglar [MIT 6.254]
 - Vincent Conitzer [Duke CPS 590.4]
 - Aaron Roth [UPenn NETS 412]
 - Dan Klein and Pieter Abbeel [UC Berkeley CS 188]

