

AAE340 HW8 PROBLEM 4

```
clear all
close all
clc
```

<4b>

```
% Solving the differential equation using ode45
% Drag coefficient = 0.01
C_d1 = 0.01; % Drag coefficient
tspan1 = 0:0.0001:60; % Time interval
IC1 = [0, 0]; % Initial conditions
options = odeset('RelTol',1e-12, 'AbsTol',1e-12); % ode45 options
[t1, x1] = ode45(@(t,x) dfq(t, x, C_d1), tspan1, IC1, options);
x1_pos = x1(:,1); % The position vector
x1_vel = x1(:,2); % The velocity vector
temp = x1_pos; % Holding the vector of the positions
x1_pos(temp<0) = []; % Removing the position values smaller than 0 and reshaping the vector
x1_vel(temp<0) = []; % Same as above
t1(temp<0) = []; % Same as above
[maxAlt1, maxIdx1] = max(x1_pos); % Obtaining the maximum altitude and corresponding index
maxT1 = t1(maxIdx1); % Corresponding time of above


% Drag coefficient = 0.1
C_d2 = 0.1; % Drag coefficient
tspan2 = 0:0.0001:60; % Time interval
IC2 = [0, 0]; % Initial conditions
options = odeset('RelTol',1e-12, 'AbsTol',1e-12); % ode45 options
[t2, x2] = ode45(@(t,x) dfq(t, x, C_d2), tspan2, IC2, options);
x2_pos = x2(:,1); % The position vector
x2_vel = x2(:,2); % The velocity vector
temp = x2_pos; % Holding the vector of the positions
x2_pos(temp<0) = []; % Removing the position values smaller than 0 and reshaping the vector
x2_vel(temp<0) = []; % Same as above
t2(temp<0) = []; % Same as above
[maxAlt2, maxIdx2] = max(x2_pos); % Obtaining the maximum altitude and corresponding index
maxT2 = t2(maxIdx2); % Corresponding time of above

% Drag coefficient = 1
C_d3 = 1.0; % Drag coefficient
tspan3 = 0:0.0001:60; % Time interval
IC3 = [0, 0]; % Initial conditions
options = odeset('RelTol',1e-12, 'AbsTol',1e-12); % ode45 options
[t3, x3] = ode45(@(t,x) dfq(t,x,C_d3), tspan3, IC3, options);
x3_pos = x3(:,1); % The position vector
x3_vel = x3(:,2); % The velocity vector
temp = x3_pos; % Holding the vector of positions
x3_pos(temp<0) = []; % Removing the position values smaller than 0 and reshaping the vector
x3_vel(temp<0) = []; % Same as above
t3(temp<0) = []; % Same as above
[maxAlt3, maxIdx3] = max(x3_pos); % Obtaining the maximum altitude and corresponding index
maxT3 = t3(maxIdx3); % Corresponding time of above
```

```


% Plotting
figure('Renderer', 'painters', 'Position', [10 10 900 600])
plot(t1, x1_pos, '-b')
xlabel('time, t [s]')
ylabel('altitude, y [m]')
title({'Altitude of ONYX Rocket with Different Drag Coefficients', ['-'] ...
    ' By: Tomoki Koike'}})
hold on
plot(t2, x2_pos, '-r')
plot(t3, x3_pos, '-g')
plot(maxT1, maxAlt1, '.b', 'MarkerSize',18)
plot(maxT2, maxAlt2, '.r', 'MarkerSize',18)
plot(maxT3, maxAlt3, '.g', 'MarkerSize',18)
hold off
grid on
grid minor
box on
legend('C_d = 0.01', 'C_d = 0.1', 'C_d = 1')
txtFormat = 'Peak = %.2f m';
txt1 = sprintf(txtFormat, maxAlt1);
text(maxT1,maxAlt1+90,txt1,'HorizontalAlignment','left')
txt2 = sprintf(txtFormat, maxAlt2);
text(maxT2,maxAlt2+90,txt2,'HorizontalAlignment','left')
txt3 = sprintf(txtFormat, maxAlt3);
text(maxT3,maxAlt3+90,txt3,'HorizontalAlignment','left')

```




<4c>

```
% Plotting
figure('Renderer', 'painters', 'Position', [10 10 900 600])
plot(t1, x1_vel, '-b')
xlabel('time, t [s]')
ylabel('velocity, v [m/s]')
title({'Velocity of ONYX Rocket with Different Drag Coefficients', ['- ' ...
    ' By: Tomoki Koike']})
hold on
plot(t2, x2_vel, '-r')
plot(t3, x3_vel, '-g')
hold off
grid on
grid minor
box on
legend('C_d = 0.01', 'C_d = 0.1', 'C_d = 1')
```



<4d>

```
% Find the drag coefficient that gives us the advertised max altitude
figure('Renderer', 'painters', 'Position', [10 10 900 600])
[x,fval,exitflag,output,lambda,grad,hessian] = optC_d(0.5,0.3,1.26);
```



```
Cd_find = vpa(x,10);
```

```
tspan4 = 0:0.0001:25; % Time interval
IC4 = [0, 0]; % Initial conditions
options = odeset('RelTol',1e-12, 'AbsTol',1e-12); % ode45 options
[t4, x4] = ode45(@(t,x) dfq(t,x,Cd_find), tspan3, IC4, options);
x4_pos = x4(:,1); % The position vector
x4_vel = x4(:,2); % The velocity vector
temp = x4_pos; % Holding the vector of positions
x4_pos(temp<0) = []; % Removing the position values smaller than 0 and reshaping the vector
x4_vel(temp<0) = []; % Same as above
t4(temp<0) = []; % Same as above
[maxAlt4, maxIdx4] = max(x4_pos); % Obtaining the maximum altitude and corresponding index
maxT4 = t4(maxIdx4); % Corresponding time of above

fprintf(['The drag coefficient corresponding to the advertised altitude of %.2f m' ...
        ': %.7f'], maxAlt4, Cd_find);
```


The drag coefficient corresponding to the advertised altitude of 548.64 m: 0.5128061

```
% Plotting
figure('Renderer', 'painters', 'Position', [10 10 900 600])
plot(t4, x4_pos, '-b')
xlabel('time, t [s]')
ylabel('altitude, y [m]')
```

```

title({'Altitude of ONYX Rocket with Advertised Altitude', ['- ' ...
    ' By: Tomoki Koike']})
hold on
plot(maxT4, maxAlt4, '.g', 'MarkerSize',18)
hold off
grid on
grid minor
box on
txt4 = sprintf(txtFormat, maxAlt4);
text(maxT4,maxAlt4+20,txt4,'HorizontalAlignment','left')

```



FUNCTION

```

function dxdt = dfq(t, x, C_d)
    % Defining constants
    m_e = 0.368544; % Empty mass of the rocket [kg]
    m_motor = 0.125; % Mass of the motor [kg]
    m0 = m_e + m_motor; % Overall mass [kg]
    t_b = 3.0; % Burn time [s]
    T = 40.0; % Thrust [N]
    m_prop = 0.0625; % Mass of the propellant [kg]
    m_prop_dot = m_prop / t_b; % Mass flow rate of the propellant [kg/s]
    rho = 1.225; % Density of air [kg/m^3]
    D = 0.07874; % Diameter of the rocket [m]
    A = pi * (D/2)^2; % Cross-sectional area of the rocket [m^2]

```

```

drag = 0.5 * rho * A * C_d; % Drag term without the velocity squared timed to it yet
g = 9.80665; % Gravitational acceleration [m/s^2]

dxdt = zeros(2, 1); % Preallocating the derivative terms vector
dxdt(1) = x(2); % State variable of y_dot
if t <= t_b
    % State variable of y_double_dot when thruster is on
    m_t = m0 - m_prop_dot*t;
else
    % State variable of y_double_dot when thruster is not on
    m_t = m0 - m_prop;
    T = 0;
end
dxdt(2) = T/m_t - drag*(x(2))^2*sign(x(2)) / (m_t) - g;
end

% Optimization Objective function
function obj = myObj(C_d)
    tspan = 0:0.0001:25; % Time interval
    options = odeset('RelTol',1e-12, 'AbsTol',1e-12); % ode45 options
    [time, xs] = ode45(@(t,x) dfq(t, x, C_d), tspan, [0,0], options);
    obj = abs(max(xs(:,1))-548.64);
end

% Optimization fmincon function
function [x,fval,exitflag,output,lambda,grad,hessian] = optC_d(x0,lb,ub)
    %% Start with the default options
    options = optimoptions('fmincon');
    %% Modify options setting
    options = optimoptions(options,'Display', 'off');
    options = optimoptions(options,'PlotFcns', { @optimplotx @optimplotfunccount @optimplotfval});
    [x,fval,exitflag,output,lambda,grad,hessian] = ...
    fmincon(@myObj,x0,[],[],[],[],[],lb,ub,[],options);
end

```