

---

## Table of Contents

.....	1
.....	1
INITIALIZATION .....	1
.....	2
SUBPLOT FIGURE(S) .....	2
.....	3
LINEARIZATION .....	3
.....	5
MODEL .....	5
.....	8
ANALYSIS .....	8
-- Q1 .....	8
.....	8
ACADEMIC INTEGRITY STATEMENT .....	8

```
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% ENGR 132
% Program Description
% This program delves into the ignition delay of a turbine engine
% which
% is the time interval between the fuel enter the compressor and the
% fuel to actually combust. Mainly, the relation between the
% temperature and the ignition delay is modelled graphically for two
% different types of fuels.
% Assignment Information
%   Assignment:      PS 05, Problem 2
%   Author:          Tomoki Koike, koike@purdue.edu
%   Team ID:         002-08
%   Contributor:     no contributor
%   My contributor(s) helped me:
%       [ ] understand the assignment expectations without
%           telling me how they will approach it.
%       [ ] understand different ways to think about a solution
%           without helping me plan my solution.
%       [ ] think through the meaning of a specific error or
%           bug present in my code without looking at my code.
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
```

---

## INITIALIZATION

```
% Importing the data
dieselData = csvread("Data_diesel_ignition_delay.csv",1,0);
% the data for the diesel #2 fuel
jetData = csvread("Data_jetA_ignition_delay.csv",1,0);
```

---

```

% the data for the jet-A fuel

% setting variables for the columns in the data
% the diesel data
dieselTemp = dieselData(:,1); % the temperature factor 1000/T (K-1)
dieselDel = dieselData(:,2); % the ignition delay (msec)
% the jet fuel data
jetTemp = jetData(:,1); % the temperature factor 1000/t (K-1)
jetDel = jetData(:,2); % the ignition delay (msec)

```

---

## SUBPLOT FIGURE(S)

```

% plotting the two data sets together in the form of linear, semilogX,
% semilogY, and loglog
figure
% the subplot for the linear graph
subplot(2,2,1)
plot(dieselTemp,dieselDel,"or")
title('linear')
xlabel('1000/T (K-1)')
ylabel('Ignition Delay (msec)')
grid on
grid minor
hold on
plot(jetTemp,jetDel,"xb")
hold off
legend('diesel data','jetA data','location','northwest')

% the subplot for the semilogx
subplot(2,2,2)
semilogx(dieselTemp,dieselDel,"or")
title('Semilog X')
xlabel('1000/T (K-1)')
ylabel('Ignition Delay (msec)')
grid on
grid minor
hold on
semilogx(jetTemp,jetDel,"xb")
hold off
legend('diesel data','jetA data','location','northwest')

% the subplot for the semilogy
subplot(2,2,3)
semilogy(dieselTemp,dieselDel,"or")
title('Semilog Y')
xlabel('1000/T (K-1)')
ylabel('Ignition Delay (msec)')
grid on
grid minor
hold on

```

---


---

```

semilogy(jetTemp,jetDel,"xb")
hold off
legend('diesel data','jetA data','location','northwest')

% the subplot for the loglog
subplot(2,2,4)
loglog(dieselTemp,dieselDel,"or")
title('Loglog')
xlabel('1000/T (K^{-1})')
ylabel('Ignition Delay (msec)')
grid on
grid minor
hold on
loglog(jetTemp,jetDel,"xb")
hold off
legend('diesel data','jetA data','location','northwest')

```




---

## LINEARIZATION

```

% transforming the y-values to log(y)
% diesel
dieselLogDel = log10(dieselDel);
% jetA

```

---

```

jetLogDel = log10(jetDel);

% manipulating the linear regression
% diesel
pfitDiesel = polyfit(dieselTemp,dieselLogDel,1);
    % finding the slope and the y-intercept for the
    % regression line
dieselSlope = pfitDiesel(1,1);
    % the slope value
dieselY_incpt = pfitDiesel(1,2);
    % the y-intercept value
pvalDiesel = polyval(pfitDiesel,dieselTemp);
    % the y-values corresponding to the x-values on the
    % modeled regression line

% jetA
pfitJet = polyfit(jetTemp,jetLogDel,1);
    % finding the slope and the y-intercept for the
    % regression line
jetSlope = pfitJet(1,1);
    % the slope value
jetY_incpt = pfitJet(1,2);
    % the y-intercept value
pvalJet = polyval(pfitJet,jetTemp);
    % the y-values corresponding to the x-values on the
    % modeled regression line


% printing the predicted regression model equation
fprintf("The linear regression line for the diesel data set is y =
    %.3fx + %.3f .\n", dieselSlope, dieselY_incpt);
fprintf("The linear regression line for the jetA data set is y = %.3fx
    + %.3f .\n", jetSlope, jetY_incpt);

% plotting the linearized data and the trend line for the two data
sets
figure
plot(dieselTemp,pvalDiesel,"-or")
title('The Linearized Model of the Diesel and JetA Data Set')
xlabel('1000/T (K^{-1})')
ylabel('Ignition Delay (msec)')
grid on
grid minor
hold on
plot(jetTemp,pvalJet,"-xb")
hold off
legend('diesel data','jetA data','location','northwest')

The linear regression line for the diesel data set is y = 9.109x +
-11.012 .
The linear regression line for the jetA data set is y = 8.732x +
-10.707 .

```

---




---

## MODEL

```
% Because the linear regression model is
% log10(y) = a*x + b    //a and b are calculated by polyfit
% by manipulating this formula we can get
% y = 10^(ax+b)

% printing and plotting the general equation (best fit curve) for
% each data set
% diesel
dieselGenFormX = dieselTemp;
    % the x-values for the general form
dieselGenFormY = 10.^(dieselSlope*dieselGenFormX + dieselY_incpt);
    % the y-values for the general form
fprintf("\nThe general form of the best fit equation is y = 10^(%.3dx+
%.3d) .",dieselSlope, dieselY_incpt);
    % printing the equation on the command window
% jet
jetGenFormX = jetTemp;
    % the x-values for the general form
jetGenFormY = 10.^(jetSlope*jetGenFormX + jetY_incpt);
    % the y-values for the general form
```

---

```

fprintf("\nThe general form of the best fit equation is y = 10^(%.3dx+
%.3d) .\n",jetSlope, jetY_incpt);
    % printing the equation on the command window

% plotting
% diesel
figure
plot(dieselGenFormX,dieselGenFormY,"-or")
title('The Best Fit Curve of the Diesel Data Set')
xlabel('1000/T (K^{-1})')
ylabel('Ignition Delay (msec)')
grid on
grid minor



% jetA
figure
plot(jetGenFormX,jetGenFormY,"-xb")
title('The Best Fir Curve of the JetA Data Set')
xlabel('1000/T (K^{-1})')
ylabel('Ignition Delay (msec)')
grid on
grid minor

```

```

The general form of the best fit equation is y = 10^(9.109e+00x
+-1.101e+01) .
The general form of the best fit equation is y = 10^(8.732e+00x
+-1.071e+01) .

```



---

## ANALYSIS

### -- Q1

The model of the semilog y is possibly the best data representing model because the scattered data points line up linearly the best and also the x axis scaling does not have much difference by transforming the x-values to  $\log(x)$ . Namely, the normal x axis spans x-values from approximately 1.12 to 1.84, whereas the  $\log(x)$  x axis spans x-values from approximately 0 to 1.82. This means that transforming the x to  $\log(x)$  is unnecessary.

---

## ACADEMIC INTEGRITY STATEMENT

I have not used source code obtained from any other unauthorized source, either modified or unmodified. Neither have I provided access to my code to another. The script I am submitting is my own original work.

*Published with MATLAB® R2018a*