

绿色化工新材料 让生活更加幸福



**GREEN CHEMICAL INNOVATIONS
ENHANCING LIFE'S HAPPINESS**

KEYUAN HOLDING GROUP CO., LTD.

Framework Diagram

KEYUAN
PETROCHEMICALS

KEYUAN
PETROCHEMICALS

科元控股集团

Keyuan Holding Group Co.Ltd.



002377.SZ

湖北国创高新

Hubei Guochuang
High-Tech Material Inc.



605008.SH

宁波长鸿高科

Ningbo Changhong
Polymer Scientific and
Technical Inc.



广西长科

Guangxi Changke New
Materials Co.,Ltd



宁波科元精化

Ningbo Keyuan Fine
Chemical Co., Ltd.



广东艾凯茵

Guangdong Changhong
Aikaiyin Technology
Co., Ltd.



浙江长鸿生物

Zhejiang Changhong
Biological Material Co.,Ltd.



浙江鑫科化工

Zhejiang Xinke Chemical
Co., Ltd.



广西长鸿生物

Guangxi Changhong
Biological Material Co.,Ltd.

KEYUAN INTRODUCTION

科元介绍



Keyuan Holding Group Co., Ltd. was founded in April 2007 with its headquarters in Ningbo, Zhejiang Province. It is a large-scale modern chemical group integrating R&D, production and sales. The group focuses on four core industries: fine chemicals, thermoplastic elastomers, biodegradable plastics and engineering plastics.

Material Category	Application Industries / Specific Uses
Thermoplastic Elastomers (SBS/SEBS/SEPS/LCBR/SBR)	Asphalt modification, Automotive seals, adhesives/sealants, shoe materials, soft handles, etc.
Transparent Resin (MABS/AS/MS/PS)	Transparent components for electronics/home appliances/medical parts, instrument panels, consumer product housings
Engineering Plastics (PBT)	Electrical and electronic connectors, automotive parts, mechanical structural parts
Biodegradable Materials (PBAT, etc.)	Environmentally friendly packaging, disposable products, agricultural films
Black Masterbatch / Calcium Carbonate Masterbatch	Masterbatch: electrical conductivity, flame retardancy, UV resistance, weather resistance, etc.
High-Boiling Aromatic Solvent	Solvent for coatings/rubber/adhesive systems, cleaning agents.
Mesitylene	Organic synthesis intermediates (e.g., key intermediates for photoresist)
PMDA (Pyromellitic Dianhydride)	High-performance polyimide, battery separator, aerospace substrate, high-temperature insulating material
Trimellitic Anhydride (TMA)	Mainly used as a chemical intermediate in the manufacture of industrial compounds such as: plasticizers (PVC, etc.), paints/coatings, dyes, additives, etc.
Benzoic Acid	Food/medicine preservation, auxiliaries in textile and paper processing, laboratory organic synthesis reagents, etc.
Sodium Benzoate	Food preservatives, pharmaceutical/chemical preservation, feed additives, laboratory chemical reagents, etc.
High-Purity Sulfuric Acid	Chemical battery electrolyte, semiconductor/electronic-grade cleaning and etching, control, etc.

CHANGHONG POLYMER

长鸿高科 (STOCK CODE: 605008)



Ningbo Changhong Polymer Scientific and Technical Inc. was founded in 2012. It was listed on the Shanghai Stock Market in 2020. As a national high-tech enterprise, the company specializes in the field of thermoplastic elastomers (TPES) with 5 production lines and 250K tons capacity.

Core Products



SBS

waterproof membranes, road asphalt modification, high-end shoe materials, toys, hot melt adhesives



SEBS

automotive parts, electric wires and cables, high-end carpets, plastic modification



SEPS

cosmetics, medical supplies, food packaging, optical materials



SSBR

plastic modification, high-end shoe materials, high-performance tires, electric vehicles, adhesives and other fields

Product Series	Properties and Core Applications
SIS	Pressure-sensitive adhesives, adhesives, hygiene product adhesives
LCBR	Special resin modification, tires, adhesive tapes, rubber hoses, electric wires and cables, negative electrode binders for lithium-ion batteries, etc.
ES	High-end shoe materials, insoles, photovoltaic adhesive films, etc.

Changhong Polymer SBS & SEBS Technical Data Sheet

	SBS						SEBS			
Specification	CH301	CH302	CH332	CH412	CH401	CH406	CH510	CH520	CH540	CH506
Styrene (wt%)	29.5~31.5	29.5~30.5	30.0~31.0	39.5~40.5	39.0~41.0	39.0~41.0	29.5~31.0	33.0~35.0	34.5~35.5	30.0~31.0
Oil content (%)	-	-	-	8~15	-	-	-	-	-	-
Volatile matter (wt%)	≤1.00	≤1.00	≤1.00	≤1.00	≤0.70	≤0.50	≤0.60	≤0.60	≤0.60	≤0.60
Yellow Index	≤10	≤10	≤10	≤10	≤6	≤6	≤6	≤6	≤6	≤6
Ash Content (wt%)	≤0.20	≤0.20	≤0.20	≤0.20	≤0.20	≤0.20	≤0.20	≤0.20	≤0.20	≤0.20
300% Tensile Stress (Mpa)	≥2.0	≥1.8	≥1.8	≥2.0	≥3.0	≥2.5	≥3.0	≥3.0	≥3.0	≥3.0
Tensile Strength (Mpa)	≥14	≥10	≥10	≥16	≥20	≥16	≥16.0	≥18.0	≥18.0	≥20.0
Elongation (%)	≥600	≥550	≥570	≥700	≥680	≥580	≥450	≥400	≥400	≥430
Hardness, Shore A	≥68	≥80	≥80	≥83	≥85	≥85	≥68	≥70	≥80	≥82
Tensile Set (%)	≤40	≤30	≤30	≤40	≤40	≤38	≤40	≤40	≤48	≤50
10% TSV (Mpa.s)	-	-	-	-	-	-	200~800	1500~3000	200~800	50~150
Hydrogenation Degree (%)	-	-	-	-	-	-	≥97.0	≥97.0	≥97.0	≥97.0
Molecular Weight (10K)	11.2~12.2	22~25	26~29	20.0~22.0	7~9	6.0~6.5	8.0~12.0	19.0~22.0	22.0~26.0	5.9~6.5
MFR (200℃, 5kg, g/10min)	0.01~0.30	-	-	0.01~0.40	0.20~4.00	4.0~6.5 (190℃, 5kg)	-	-	-	-

Changhong Polymer SIS Technical Data Sheet

Specification	CH601	CH602	CH606	CH608
Styrene (wt%)	15.0~16.0	28.5~29.5	15.0~16.0	15.0~17.0
Molecular Weight (10K)	11.0~12.0	6.8~7.3	11.5~12.5	13.0~13.9
Volatile matter (wt%)	≤0.70	≤1.00	≤1.00	≤1.00
Yellow Index	≤10	≤10	≤10	≤10
Ash Content (wt%)	≤0.20	≤0.20	≤0.20	≤0.20
Tensile Strength (Mpa)	≥12	-	-	≥2.20
Elongation (%)	≥1000	-	-	≥1100
MFR (200℃, 5kg, g/10min)	8.00~12.0	8.00~14.0	8.00~14.0	8.00~14.0
Hardness, Shore A	35~50	≥60	≥33	≥23
25% TSV (Mpa.s)	≤2000	280~550	≤2000	800~1400
SI Content (%)	-	-	-	-

Changhong Polymer SSBR & LCBR Technical Data Sheet

	SSBR			LCBR	
Specification	CH265	CH268	CH1028	CH105L	CH100L
Styrene (wt%)	24.5~25.5	29.8~30.5	45.5~46.5	-	-
Molecular Weight (10K)	6.8~7.3	14.0~15.0	-	-	4.7~5.4
Volatile matter (wt%)	≤0.75	≤0.75	≤1.00	≤0.75	≤0.50
Yellow Index	≤10	≤10	-	-	-
5% TSV (Mpa.s)	10~17	21~29	-	130~200	22~32
Gel Content (ppm)	≤500	≤500	-	≤500	≤500
Mooney Viscosity (ML100℃, 1+4)	44.0~58.0	-	50.0~65.0	47.0~55.0	35.0~50.0

CHANGHONG BIOLOGICAL

长鸿生物



Zhejiang Changhong Biological Material Co., Ltd. was founded in 2020, located in Shengzhou, Zhejiang Province. The company focuses on the "dual-carbon" green materials sector, with business scope covering the manufacturing of PBT resin, production of high-performance carbon black, processing of terminal environmental protection products, etc. It specializes in the R&D, production and sales of fully biodegradable materials and derivative products, serving industries including rubber products, packaging and printing, modern agriculture, etc.

Core Products

Product System	Representative Products	Features and Applications
Biodegradable Resin	 PBTPBATPBS	It is used in packaging, agricultural mulch film, disposable tableware, electronic and electrical appliance housings, etc.
Modified PBT	PBT-GF30, NPFR-PBT/GF30, GRS-PBT, PBT/TPEE Impact Modified	Connectors, Auto'parts, Electrical and electronic components
High-performance Carbon Black	N326/N330/N550/N660	Environmentally friendly production process with zero detection of heavy metals. Used in tires, rubber products and plastic modification.
Derived Materials	THF	By-products are recycled and utilized as chemical intermediates or asphalt modifiers

Changhong Biological PBT Resin Technical Data Sheet

Specification	CH875	CH883	CH890	CH810	CH811	CH812
Intrinsic Viscosity (dl/g)	0.750±0.02	0.83±0.02	0.90±0.02	1.00±0.02	1.100±0.02	1.2±0.02
Carboxyl End Group (mol/t)	≤18	≤25	≤25	≤25	≤28	≤28
Melting Point (°C)	223±3	225±2	225±2	225±2	224±3	224±3
Density (g/cm³)	—	1.3	1.31	1.30-1.32	—	—
Tensile Strength (MPa)	≥50	50-60	50-60	50-60	≥50	≥50
Flexural Strength (MPa)	≥60	59	85±5	59	≥60	≥60
Flexural Modulus (MPa)	≥2000	—	—	—	≥2000	≥2000
Notched Izod Impact Strength (kJ/m²)	≥4.0	9.8	9.8	9.8	≥4.0	≥4.0
Melt Flow Index (250°C/2.16kg)	100-120	60-70	40-46	24-30	—	9.5-12.5
Color L	≥90.0	≥85	≥85	≥85	≥88.0	≥88.0
Color B	3.0±2.0	4.0±1.0	3.5±1.0	5.0±1.0	4.0±2.0	4.0±2.0
Packaging	25kg/bag, 1000kg/bag					

Changhong Biological Modified PBT Resin Technical Data Sheet

Specification	PBT/GF30	NPFR-PBT/GF30	PBT/TPEE Impact Mmodified	GRS-PBT
Density (g/cm³)	1.52	1.55	1.26	1.3-1.32
Glass Fiber Content (%)	30	30	-	-
Water Absorption in Water (+23°C/50% r.h 24hrs)	0.06	0.06	0.2	0.2
Molding Shrinkage Longitudinal (%)	0.3	0.3	1.6	-
Molding Shrinkage Transverse (%)	0.8	0.9	1.6	-
Tensile Modulus	10000	9500	2250	-
Tensile Strength (MPa)	135	105	42	40
Tensile Elongation (%)	2.8	2.2	20	5
Flexural Strength (MPa)	210	170	70	50
Flexural modulus	8500	8800	1950	1800
Charpy notched Impact Strength (kJ/m²)	10	8	18	-
Rockwell Hardness	120	120	-	-
Melt Temperature (°C)	224	224	224	-
HDT/1.8MPa (°C)	200	200	55	-
Flammability UL94 thickness 1.6mm	HB	V0	HB	-

GUANGXI CHANGKE

广西长科



SPECIALTY RESIN INDUSTRY CHAIN SERVICES



Guangxi Changke New Material Co., Ltd. was founded in 2012 with a registered capital of 887 million yuan. Located in Fangchenggang, the company integrates R&D, production and logistics, and is a benchmark enterprise in the new material industry in Southwest China. Nowadays Changke company has totally 7 production lines with 600K tons capacity.

Core Products

Grade	Product Features	Application Fields
SAN CN900	High heat resistance, high chemical resistance	Disposable lighter shell, ASA modified
SAN CN2800	High transparency, high strength	AS + glass fiber, ASA modified, stationery injection molding
SAN CN4800	High transparency, high fluidity	Color masterbatch, PC/ABS modified, large part injection molding
ABS CB817	Medium and low melt index, matte finish, high whiteness, heat resistance, excellent high purity, low VOC, low odor	Sheet, PC/ABS modified, heat-resistant ABS modified, automotive interior parts
ABS CB2716	High fluidity, high gloss, high whiteness, high purity, low VOC, low odor	PC/ABS modified, heat-resistant ABS modified, flame-retardant ABS modified, automotive interior parts
MABS CT2010	High strength, high transparency	Washing machine cover, air conditioner panel, toys
HIPS CH310	High gloss, high whiteness, high strength	Air conditioner housing, flame-retardant modification
MS CS1025	High transparency, weather resistance, low moisture absorption rate	Light guide plate, optical applications, daily necessities

Guangxi Changke Resin Products Technical Data Sheet

Product Type	MABS	SAN			ABS		HIPS	
Grade	CT2010	CN-900	CN-2800	CN-4800	CB817	CB2716	CH310	CH612
Density (g/cm³)	1.06	1.06	1.05	1.05	1.04	1.05	1.04	1.04
Melt Flow Index (g/10min)	26 (220°C/10kg)	11 (220°C/10kg)	34 (220°C/10kg)	48 (220°C/10kg)	8 (220°C/10kg)	25 (220°C/10kg)	4.2 (200°C/5kg)	6 (200°C/5kg)
Tensile Yield Strength (MPa)	50	80	70	69	39	42	32	25
Flexural Strength (MPa)	70	130	120	120	54	64	48	40
Flexural Modulus (MPa)	2063	3500	3300	3800	1800	2000	1870	1800
Notched Izod Impact Strength (kJ/m²)	10	4	3	3	16	16	10.4	12
Vicat Softening Temperature (°C)	93.7	99	96	94	99	92	93	90
Glossiness	91	—	—	—	60	94	93	70
Transmittance (%)	—	90	90	90	—	—	—	—
Flammability Rating (1.5mm)	HB	HB	HB	HB	HB	HB	HB	HB
Mold Shrinkage (%)	0.4~0.7	0.2~0.6	0.2~0.6	0.2~0.6	0.4~0.6	0.4~0.7	0.4~0.7	0.4~0.7
Packaging	25kg/bag							

科元炭黑

Production Bases	Location	Capacity	Grade
NINGBO CHANGHONG POLYMER SCIENTIFIC AND TECHNICAL INC.	Zhejiang Ningbo	80,000 MT	N326、N330
ZHEJIANG CHANGHONG BIOLOGICAL MATERIAL CO., LTD.	Zhejiang Shengzhou	120,000 MT	N326、N330
GUANGXI CHANGKE NEW MATERIALS CO., LTD.	Guangxi Fangchenggang	150,000 MT	N330、N550、N660、N220、N326
Total Capacity: 350,000 MT			

Carbon Black Technical Data Sheet							
Analysis Item	Unit	N330	N326	N220	N550	N660	Testing Methods
Iodine Adsorption Value	g/kg	82±6	82±6	121±6	39-47	32-40	GB/T 3780.1-2015
Oil Absorption Value	10 ⁻⁵ m³/kg	102±6	72±6	114±6	116-126	85-95	GB/T 3780.2-2017
Absorption Value for Compressed Sample	10 ⁻⁵ m³/kg	88±6	68±6	98±6	80-90	69-79	GB/T 3780.4-2017
Tinctorial Strength	%	104±8	111±8	116±8	/	/	GB/T 3780.6-2016
Bulk, 125°C, 1hr	%	≤0.8	≤0.8	≤0.8	≤0.8	≤0.8	GB/T 3780.8-2019
Ash Content	%	≤0.7	≤0.7	≤0.7	≤0.5	≤0.5	GB/T 3780.10-2017
45µm Sieve Residue by Water Washing	ppm	≤500	≤500	≤500	≤500	≤500	GB/T 3780.21-2016
Finess Content	%	≤7.0	≤7.0	≤7.0	≤10.0	≤7.0	GB/T 14853.2-2016
Pallet Hardness	cN	30±10	30±10	30±10	/	/	GB/T 14853.6-2013
STSA	10³m²/kg	78±5	76±5	106±5	34±5	34±5	GB/T 10722-2014
PH Value	/	5.0-9.0	5.0-9.0	5.0-9.0	5.0-9.0	6.0-10.0	GB/T 3780.7-2016
Pour Density	kg/m³	380±40	455±40	355±40	320-400	400-480	GB/T 14853.1-2013
Package: 25kg/bag, 500kg/bag, 1000kg/bag							

KEYUAN FINE CHEMICALS

科元精化



Ningbo Keyuan Fine Chemicals Co.,Ltd. is a unicorn enterprise in Zhejiang Province. Founded in 2007, This company has built a complete integrated industrial chain layout of "fuel oil – low-carbon olefins – high-end chemicals". It is equipped with more than 10 sets of modern petrochemical plants ranging from heavy oil cracking to aromatic hydrocarbon extraction and styrene production, together with a 5,000-ton self-provided chemical terminal. It ranks first in the domestic market share of aromatic hydrocarbon solvents and industrial cleaning agents.

Core Products



Industrial Hexane



Petroleum Ether



Light White Oil



High-Boiling Aromatic Solvent

Product	Product Features	Main Applications
Industrial Hexane	This product is water-white in appearance and residue-free in odor, characterized by extremely low benzene content and high purity.	It is mainly used as a raw material for the preparation of binders, coatings, inks and chemical synthesis processes, as well as a solvent for various extraction processes including vegetable oils.
Petroleum Ether	This product is a colorless and transparent liquid, mainly a mixture of pentane, hexane and heptane. It is insoluble in water, but soluble in most organic solvents.	Main applications include solvents, dye intermediates, pharmaceutical intermediates, additives, etc.
Light White Oil	Light White Oil is an environmentally friendly solvent that is colorless, odorless and chemically inert. It has a saturated hydrocarbon content of over 99%, and features low sulfur, low aromaticity, low toxicity and high safety, with no special fire prevention measures required. It has strong solvency and good volatility, making it an ideal substitute for chlorinated solvents.	It is mainly used for lubrication in chemical fiber, aluminum material processing, rubber and textile machinery. It is also applied in daily cosmetic products such as hair removal cream, hair oil, lipstick and skin cream.
High-Boiling Aromatic Solvent	High boiling point, slow evaporation, not prone to violent reactions, environmentally friendly solvent.	Widely used in coatings, inks, pesticides, pharmaceuticals and other fields.

GUOCHUANG GAOXIN

国创新高新 (STOCK CODE: 002377)



Hubei Guochuang High-tech Material Co., Ltd. was founded in 2002 and listed on the Shenzhen Stock Exchange in 2010. It is a “leading enterprise” in China’s transportation industry in the field of asphalt materials for highways. It took the lead in breaking foreign technological monopolies and achieved fully independent intellectual property rights for modified asphalt production equipment and core materials. In 2024, Guochuang High-tech was officially acquired by Keyuan Group. In August 2025, Guopei Petroleum – an enterprise integrating asphalt storage, road asphalt production and modified asphalt production – was merged into Guochuang High-tech and became its wholly-owned subsidiary.

Core Products

Product Series	Key Features
SBS Modified Asphalt	Improves high and low temperature performance, suitable for heavy-duty pavements such as expressways and airport runways.
High-Viscosity Modified Asphalt	Suitable for special projects such as drainage and noise-reducing pavement (OGFC), waterproof bonding layer of bridge deck, etc.
Rubber Asphalt	Environmentally friendly and energy-saving, with strong resistance to reflective cracking; suitable for stress-absorbing layers and high-grade pavements.
Colored Asphalt	Long-lasting color, beautifies urban roads, and is widely used in greenways, scenic areas, and bus-only lanes.
Emulsified Asphalt	Cold mixing enables convenient construction, suitable for prime coat, tack coat, microsurfacing and other preventive maintenance.
Special Materials	Including CA mortar, high-modulus additives, flame retardants, etc., serving special scenarios such as high-speed railways and tunnels.

GUANGXI CHANGHONG

广西长鸿



Guangxi Changhong Biological Materials Co., Ltd. was established in January 2023 with a registered capital of 600 million yuan. As the lead enterprise of Guangxi's key biodegradable masterbatch industrial park, the company leverages its marble mine resources with reserves exceeding 100 million tons to create a closed-loop full-process independent supply system covering "color-sorted ore – calcium carbonate powder – biodegradable masterbatch." This establishes a complete industrial chain layout spanning from mining to the production of biodegradable products.

Core Products

Product System	Representative Products	Characteristics & Uses
Calcium Carbonate Powder Series	 ◦ Vertical Mill Modified Powder (800-3000 mesh) ◦ Raymond Mill Powder (200-400 mesh) ◦ Ring Roller Mill Powder (400-1500 mesh)	High whiteness, high purity, uniform particle size. Suitable for filling and modification in plastics, rubber, coatings, etc.
Degradable Masterbatch Series	 ◦ PBAT Degradable Masterbatch ◦ PLA Degradable Masterbatch	Meets environmental standards. Used for film bags, agricultural mulch film, disposable products.
Shoe Material & Specialty Masterbatch	 ◦ Shoe Material Masterbatch ◦ PP Lunch Box Masterbatch ◦ PE Blown Film Masterbatch	Uniform color, good dispersion. Meets food-grade and industrial-grade application requirements.

GUANGDONG CHANGHONG

广东长鸿



BUILDING A CORE BASE FOR THE HIGH-END ACRYLIC ACID INDUSTRY CHAIN IN SOUTH CHINA

Guangdong Changhong Aikaiyin Technology Co., Ltd. was established in May 2024 with a registered capital of 160 million yuan. Located in the Green Chemical and Hydrogen Energy Industrial Park of Maoming Binhai New Area, the facility covers an area of 1,200 mu. As a vital component of Keyuan Holding Group's strategic layout, the company focuses on its independently developed one-step propane-to-acrylic acid production system, leading the global transformation of the acrylic acid industry.

Core Products

Product Series	Characteristics & Uses	Main Application Areas
 Butyl Acrylate	Key chemical raw material, high reactivity	Coatings, textiles, adhesives, plastic modification
 2-Ethylhexyl Acrylate	Polymer monomer, excellent adhesion and film-forming properties	Paper strengthening agents, industrial coatings, pressure-sensitive adhesives
 Super Absorbent Polymer (SAP)	Soft monomer, good flexibility	Pressure-sensitive adhesives, fabric finishing agents, leather auxiliaries
Acrylic Acid	Water absorption rate of several hundred times, strong water retention	Sanitary products, agricultural water retention, medical materials

ZHEJIANG XINKE

浙江鑫科



Zhejiang Xinke Chemical Co., Ltd. was established in March 2024 with a registered capital of 3 billion yuan. It represents a strategic initiative by Keyuan Holding Group to advance its goal of achieving a hundred-billion-yuan output value and to deeply improve and complete its green chemical full industry chain. Adhering to the development philosophy of "technology leadership, green and low-carbon practices, and high productivity and intensification," the company is committed to establishing a world-class production base for chemicals and new materials.

Core Products

The project will establish a diversified product portfolio covering 1,2,4-Trimethylbenzene (Pseudocumene), 1,3,5-Trimethylbenzene (Mesitylene), and 1,2,4,5-Tetramethylbenzene (Durene), with main products including:

		
1,2,4-Trimethylbenzene (Pseudocumene)	1,3,5-Trimethylbenzene (Mesitylene)	1,2,4,5-Tetramethylbenzene (Durene)
Product	Product Characteristics	Main Uses
1,2,4-Trimethylbenzene (Pseudocumene)	Almost insoluble in water, but soluble in ethanol, acetaldehyde, and benzene. It is flammable and has a strong odor. Primarily extracted from the C9 aromatic fraction of petroleum distillation, it is an important fine chemical raw material with a wide range of applications and high added value.	Waterborne coatings, inks, and adhesives; also used as a chemical intermediate in the production of plasticizers.
1,3,5-Trimethylbenzene (Mesitylene)	High chemical stability, good solubility, and a low freezing point give it outstanding advantages in low-temperature solvent and fine chemical applications.	Main applications include use as a solvent, dye intermediate, pharmaceutical intermediate, and additive.
1,2,4,5-Tetramethylbenzene (Durene)	Insoluble in water, soluble in organic solvents such as ethanol, ether, and benzene.	Used in markets such as polyimide, curing agents, matting agents, plasticizers, pharmaceuticals, pesticides, and dyes.

The total annual production capacity reaches 2.8434 million tons, providing a stable and high-quality raw material guarantee for downstream industries.



科元控股集团有限公司
KEYUAN HOLDING GROUP CO., LTD.

Add: No.102, Xinhui Road, Gaoxin Zone, Ningbo, Zhejiang Province

Tel: 0574-56804976

Email: maoxx@kygroup.ltd

