GEM5 Simulator: Hello World Program Execution Report

Course: Computer Architecture Design
Assignment: Using GEM5 Simulator
Student Name: Sai Mohan Manukonda
Student ID: 005046992
Instructor: Professor Gary Perry
Institution: University of the Cumberlands
Date: March 12, 2026

Abstract

This report documents the installation, configuration, and execution of the GEM5 computer architecture simulator. The primary objective was to execute a simple “Hello World” C program within the GEM5 simulated X86 environment to understand the fundamentals of processor simulation. The assignment was completed using Docker containers on macOS to create a compatible Linux environment. Key challenges included cross-platform compatibility issues and architecture mismatches between the host ARM64 system and the simulated X86 target. The simulation successfully executed the program, completing in 11,491,500 ticks with 10,220 instructions. This exercise provided valuable insights into cycle-accurate simulation, memory hierarchy, and performance metrics analysis in computer architecture research.

Keywords: GEM5, computer architecture, simulation, X86, syscall emulation, Docker

---

Table of Contents

1. Introduction
2. Environment Setup
3. GEM5 Installation
4. Hello World Program
5. Simulation Script
6. Running the Simulation
7. Output Analysis
8. Challenges Encountered
9. Lessons Learned
10. Conclusion
11. References

---

1. Introduction

GEM5 is a modular platform for computer-system architecture research, encompassing system-level architecture as well as processor microarchitecture. This assignment demonstrates the execution of a simple "Hello World" program using the GEM5 simulator to understand the basics of computer architecture simulation.

Objectives:

- Install and configure GEM5 simulator
- Write and compile a simple C program
- Create a simulation configuration script
- Execute the program in GEM5's Syscall Emulation (SE) mode
- Analyze the simulation output

---

2. Environment Setup

System Requirements:

- **Operating System:** Ubuntu 22.04 LTS (running in Docker container)
- **Host System:** macOS with Apple Silicon (ARM64)
- **RAM:** Minimum 8GB (16GB recommended for faster compilation)
- **Disk Space:** At least 10GB free space

Step 2.1: Docker Container Setup

Since GEM5 requires Linux, we used Docker to create an Ubuntu environment:

```
docker run -it -v
        ~/cumberlands/ComputerArchitectureDesign/Using_GEM5:/workspace
        ubuntu:22.04 /bin/bash
```

Step 2.2: System Update and Dependency Installation

Inside the Docker container, update the system packages and install required dependencies:

```
apt-get update
apt-get install -y python3 scons gcc g++ git build-essential m4 zlib1g
        zlib1g-dev \
    libprotobuf-dev protobuf-compiler libprotoc-dev libgoogle-
        perftools-dev \
    python3-dev python3-six python-is-python3 libboost-all-dev pkg-
        config \
    gcc-x86-64-linux-gnu
```



Figure 1: Terminal output showing successful installation of required dependencies

---

3. GEM5 Installation

Step 3.1: Clone GEM5 Repository

Clone the official GEM5 repository from Google Source:

```
git clone https://gem5.googlesource.com/public/gem5
cd gem5
```

```
root@590f72e57b21:/workspace# ./gem5/build/X86/gem5.opt ./gem5/configs/deprecated/example/se.py -c ./hello
gem5 Simulator System.  https://www.gem5.org
gem5 is copyrighted software; use the --copyright option for details.

gem5 version 23.0.0.1
gem5 compiled Mar 11 2026 15:53:27
gem5 started Mar 12 2026 01:28:55
gem5 executing on 590f72e57b21, pid 24299
command line: ./gem5/build/X86/gem5.opt ./gem5/configs/deprecated/example/se.py -c ./hello

warn: The `get_runtime_isa` function is deprecated. Please migrate away from using this function.
warn: The se.py script is deprecated. It will be removed in future releases of  gem5.
warn: The `get_runtime_isa` function is deprecated. Please migrate away from using this function.
Global frequency set at 1000000000000 ticks per second
warn: No dot file generated. Please install pydot to generate the dot file and pdf.
src/mem/dram_interface.cc:690: warn: DRAM device capacity (8192 Mbytes) does not match the address range assigned (512 Mbyte
s)
src/base/statistics.hh:279: warn: One of the stats is a legacy stat. Legacy stat is a stat that does not belong to any stati
stics::Group. Legacy stat is deprecated.
system.remote_gdb: Listening for connections on port 7000
**** REAL SIMULATION ****
src/sim/simulate.cc:194: info: Entering event queue @ 0.  Starting simulation...
src/sim/syscall_emul.cc:74: warn: ignoring syscall set_robust_list(...)
src/sim/syscall_emul.cc:74: warn: ignoring syscall rseq(...)
src/sim/mem_state.cc:443: info: Increasing stack size by one page.
src/sim/syscall_emul.cc:74: warn: ignoring syscall mprotect(...)
Hello, World!
Exiting @ tick 11491500 because exiting with last active thread context
root@590f72e57b21:/workspace# ls -la gem5/ | head -20 && echo "" && echo "gem5 repository successfully cloned from https://g
em5.googlesource.com/public/gem5"
total 224
drwxr-xr-x 33 root root  1056 Mar 11 14:59 .
drwxr-xr-x 12 root root   384 Mar 12 01:27 ..
drwxr-xr-x 14 root root   448 Mar 11 14:31 .git
-rw-r--r--  1 root root  1229 Mar 11 14:31 .git-blame-ignore-revs
drwxr-xr-x  3 root root    96 Mar 11 14:31 .github
-rw-r--r--  1 root root   653 Mar 11 14:31 .gitignore
-rw-r--r--  1 root root 23598 Mar 11 14:31 .mailmap
-rw-r--r--  1 root root  3340 Mar 11 14:31 .pre-commit-config.yaml
-rw-r--r--  1 root root  5595 Mar 11 14:31 CODE-OF-CONDUCT.md
-rw-r--r--  1 root root 27383 Mar 11 14:31 CONTRIBUTING.md
-rw-r--r--  1 root root  2332 Mar 11 14:31 COPYING
-rw-r--r--  1 root root  5681 Mar 11 14:31 KCONFIG.md
-rw-r--r--  1 root root  1478 Mar 11 14:31 LICENSE
-rw-r--r--  1 root root  7790 Mar 11 14:31 MAINTAINERS.yaml
-rw-r--r--  1 root root  2133 Mar 11 14:31 README
-rw-r--r--  1 root root 58665 Mar 11 14:31 RELEASE-NOTES.md
-rw-r--r--  1 root root  2655 Mar 11 14:31 SConsopts
-rwxr-xr-x  1 root root 34387 Mar 11 14:31 SConstruct
-rw-r--r--  1 root root  9064 Mar 11 14:31 TESTING.md

gem5 repository successfully cloned from https://gem5.googlesource.com/public/gem5
root@590f72e57b21:/workspace#
```

Figure 2: Cloning the GEM5 repository from Google Source

Step 3.2: Build GEM5 for X86 Architecture

Build the simulator optimized for X86 architecture:

```
scons build/X86/gem5.opt -j$(nproc)
```

Note: The `-j$(nproc)` flag enables parallel compilation using all available CPU cores. This process takes approximately 30-60 minutes depending on system specifications.



Figure 3: Successful completion of GEM5 build for X86 architecture

Build Output:

Upon successful compilation, you should see:

`scons: done building targets.`

---

4. Hello World Program

Step 4.1: Create the Source File

Create a simple C program named `hello.c`:

```c
#include <stdio.h>

int main() {
    printf("Hello, World!\n");
    return 0;
}
```

```
root@590f72e57b21:/workspace# cat hello.c
#include <stdio.h>

int main() {
    printf("Hello, World!\n");
    return 0;
}
root@590f72e57b21:/workspace#
```

Figure 4: The hello.c source code displayed in terminal

Step 4.2: Compile the Program

Since we're running on ARM64 Docker but simulating X86, we need to cross-compile:

```
x86_64-linux-gnu-gcc -static hello.c -o hello
```

Note: Static linking is required for GEM5 SE mode as it includes all library dependencies in the executable. Cross-compilation is necessary when the host architecture differs from the simulated architecture.

```
root@590f72e57b21:/workspace# x86_64-linux-gnu-gcc -static hello.c -o hello
root@590f72e57b21:/workspace# file hello
hello: ELF 64-bit LSB executable, x86-64, version 1 (GNU/Linux), statically linked, BuildID[sha1]=cc2aa326925cba382745bb09aa
353d0912947525, for GNU/Linux 3.2.0, not stripped
root@590f72e57b21:/workspace#
```

Figure 5: Cross-compilation of hello.c for X86 architecture and verification

Verification:

Verify the executable was created correctly:

```
file hello
```

Expected output:

```
hello: ELF 64-bit LSB executable, x86-64, version 1 (GNU/Linux),
statically linked...
```

---

5. Simulation Script

Step 5.1: Understanding the Configuration Script

The simulation script (`run_hello.py`) configures the simulated system:

```
import m5
from m5.objects import *
```

```
# Create the system
system = System()
system.clk_domain = SrcClockDomain()
system.clk_domain.clock = "1GHz"
system.clk_domain.voltage_domain = VoltageDomain()

# Memory configuration
system.mem_mode = "timing"
system.mem_ranges = [AddrRange("512MB")]
system.mem_ctrl = DDR3_1600_8x8()
system.mem_ctrl.range = system.mem_ranges[0]

# CPU configuration
system.cpu = TimingSimpleCPU()
system.cpu.icache = L1_ICache(size="32kB")
system.cpu.dcache = L1_DCache(size="32kB")

# Connecting CPU and Memory
system.membus = SystemXBar()
system.cpu.icache_port = system.membus.slave
system.cpu.dcache_port = system.membus.slave
system.cpu.createInterruptController()

# Setting up workload
system.workload = SEWorkload.init_compatible("hello")
system.cpu.workload = system.workload
system.cpu.createThreads()

# Simulation Configuration
root = Root(full_system=False, system=system)
m5.instantiate()

print("Beginning simulation!")
exit_event = m5.simulate()
print("Exiting @ tick {} because {}".format(
    m5.curTick(), exit_event.getCause()))
```

Configuration Components:

Component	Configuration	Description
Clock	1GHz	System clock frequency
Memory	512MB DDR3-1600	Main memory configuration
CPU	TimingSimpleCPU	Simple timing-accurate CPU model
L1 I-Cache	32KB	Instruction cache size
L1 D-Cache	32KB	Data cache size

---

6. Running the Simulation

Step 6.1: Execute with Built-in SE Script

Run the simulation using GEM5's built-in SE configuration:

```
./gem5/build/X86/gem5.opt ./gem5/configs/deprecated/example/se.py -c
        ./hello
```



Figure 6: GEM5 simulation output showing successful "Hello, World!" execution

Actual Simulation Output:

```
gem5 Simulator System.  https://www.gem5.org
gem5 version 23.0.0.1
gem5 compiled Mar 11 2026 15:53:27
gem5 started Mar 12 2026 01:05:17
gem5 executing on 590f72e57b21, pid 24277
command line: ./gem5/build/X86/gem5.opt
./gem5/configs/deprecated/example/se.py -c ./hello

warn: The `get_runtime_isa` function is deprecated. Please migrate
away from using this function.
warn: The se.py script is deprecated. It will be removed in future
releases of gem5.
Global frequency set at 1000000000000 ticks per second
warn: No dot file generated. Please install pydot to generate the dot
file and pdf.
src/mem/dram_interface.cc:690: warn: DRAM device capacity (8192
Mbytes) does not match the address range assigned (512 Mbytes)
system.remote_gdb: Listening for connections on port 7000
**** REAL SIMULATION ****
```

```
src/sim/simulate.cc:194: info: Entering event queue @ 0.  Starting
simulation...
Hello, World!
Exiting @ tick 11491500 because exiting with last active thread
context
```

---

7. Output Analysis

7.1 Simulation Results Summary

The simulation completed successfully with the following key metrics:

Metric	Value	Description
Exit Tick	11,491,500	Total simulation ticks
Simulated Time	0.000011 seconds (~11.5 μs)	Virtual time elapsed
Host Time	0.03 seconds	Real wall-clock time
Instructions Simulated	10,220	Total instructions executed
CPU Cycles	23,016	Total CPU cycles
CPI	2.25	Cycles per instruction
IPC	0.44	Instructions per cycle

7.2 Detailed Statistics from `m5out/stats.txt`:

```
---------- Begin Simulation Statistics ----------
simSeconds                                   0.000011
simTicks                                     11491500
simFreq                                   1000000000000
hostSeconds                                       0.03
hostTickRate                                 386384173
simInsts                                         10220
simOps                                           19633
system.cpu.numCycles                             23016
system.cpu.cpi                                 2.247656
system.cpu.ipc                                 0.444908
system.cpu.commitStats0.numInsts                 10240
system.cpu.commitStats0.numLoadInsts              1965
system.cpu.commitStats0.numStoreInsts             1986
system.cpu.commitStats0.numIntInsts              18767
system.cpu.commitStats0.numFpInsts                1405
```

```
Global frequency set at 1000000000000 ticks per second
warn: No dot file generated. Please install pydot to generate the dot file and pdf.
src/mem/dram_interface.cc:690: warn: DRAM device capacity (8192 Mbytes) does not match the address range assigned (512 Mbytes)
src/base/statistics.hh:279: warn: One of the stats is a legacy stat. Legacy stat is a stat that does not belong to any statistics::Group. Legacy stat is deprecated.
system.remote_gdb: Listening for connections on port 7000
**** REAL SIMULATION ****
src/sim/simulate.cc:194: info: Entering event queue @ 0.  Starting simulation...
src/sim/syscall_emul.cc:74: warn: ignoring syscall set_robust_list(...)
src/sim/syscall_emul.cc:74: warn: ignoring syscall rseq(...)
src/sim/mem_state.cc:443: info: Increasing stack size by one page.
src/sim/syscall_emul.cc:74: warn: ignoring syscall mprotect(...)
Hello, World!
Exiting @ tick 11491500 because exiting with last active thread context
root@590f72e57b21:/workspace# head -100 m5out/stats.txt

---------- Begin Simulation Statistics ----------
simSeconds                                   0.000011                       # Number of seconds simulated (Second)
simTicks                                     11491500                       # Number of ticks simulated (Tick)
finalTick                                    11491500                       # Number of ticks from beginning of simulation (restored from checkpoints and never reset) (Tick)
simFreq                                   1000000000000                      # The number of ticks per simulated second ((Tick/Second))
hostSeconds                                       0.03                       # Real time elapsed on the host (Second)
hostTickRate                                386384173                        # The number of ticks simulated per host second (ticks/s) ((Tick/Second))
hostMemory                                     645608                        # Number of bytes of host memory used (Byte)
simInsts                                        10220                        # Number of instructions simulated (Count)
simOps                                          19633                        # Number of ops (including micro ops) simulated (Count)
hostInstRate                                   337709                        # Simulator instruction rate (inst/s) ((Count/Second))
hostOpRate                                     646114                        # Simulator op (including micro ops) rate (op/s) ((Count/Second))
system.clk_domain.clock                         1000                         # Clock period in ticks (Tick)
system.cpu.numCycles                            23016                        # Number of cpu cycles simulated (Cycle)
system.cpu.cpi                                2.247656                       # CPI: cycles per instruction (core level) ((Cycle/Count))
system.cpu.ipc                                0.444908                       # IPC: instructions per cycle (core level) ((Count/Cycle))
system.cpu.numWorkItemsStarted                       0                       # Number of work items this cpu started (Count)
system.cpu.numWorkItemsCompleted                     0                       # Number of work items this cpu completed (Count)
system.cpu.commitStats0.numInsts                10240                        # Number of instructions committed (thread level) (Count)
system.cpu.commitStats0.numOps                  19654                        # Number of ops (including micro ops) committed (thread level) (Count)
system.cpu.commitStats0.numInstsNotNOP               0                       # Number of instructions committed excluding NOPs or prefetches (Count)
system.cpu.commitStats0.numOpsNotNOP                 0                       # Number of Ops (including micro ops) Simulated (Count)
system.cpu.commitStats0.cpi                   2.247656                       # CPI: cycles per instruction (thread level) ((Cycle/Count))
system.cpu.commitStats0.ipc                   0.444908                       # IPC: instructions per cycle (thread level) ((Count/Cycle))
system.cpu.commitStats0.numMemRefs                   0                       # Number of memory references committed (Count)
system.cpu.commitStats0.numFpInsts               1405                        # Number of float instructions (Count)
system.cpu.commitStats0.numIntInsts             18767                        # Number of integer instructions (Count)
system.cpu.commitStats0.numLoadInsts             1965                        # Number of load instructions (Count)
system.cpu.commitStats0.numStoreInsts            1986                        # Number of store instructions (Count)
system.cpu.commitStats0.numVecInsts                  0                       # Number of vector instructions (Count)
system.cpu.commitStats0.committedInstType::No_OpClass          217      1.10%      1.10% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::IntAlu        14884     75.73%     76.83% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::IntMult            4      0.02%     76.85% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::IntDiv           28      0.14%     77.00% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::FloatAdd         181      0.92%     77.92% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::FloatCmp           0      0.00%     77.92% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::FloatCvt           0      0.00%     77.92% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::FloatMult           0      0.00%     77.92% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::FloatMultAcc           0      0.00%     77.92% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::FloatDiv           0      0.00%     77.92% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::FloatMisc           0      0.00%     77.92% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::FloatSqrt           0      0.00%     77.92% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::SimdAdd           8      0.04%     77.96% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::SimdAddAcc           0      0.00%     77.96% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::SimdAlu          98      0.50%     78.46% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::SimdCmp           0      0.00%     78.46% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::SimdCvt          48      0.24%     78.70% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::SimdMisc         235      1.20%     79.90% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::SimdMult           0      0.00%     79.90% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::SimdMultAcc           0      0.00%     79.90% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::SimdMatMultAcc           0      0.00%     79.90% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::SimdShift           0      0.00%     79.90% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::SimdShiftAcc           0      0.00%     79.90% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::SimdDiv           0      0.00%     79.90% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::SimdSqrt           0      0.00%     79.90% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::SimdFloatAdd           0      0.00%     79.90% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::SimdFloatAlu           0      0.00%     79.90% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::SimdFloatCmp           0      0.00%     79.90% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::SimdFloatCvt           0      0.00%     79.90% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::SimdFloatDiv           0      0.00%     79.90% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::SimdFloatMisc           0      0.00%     79.90% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::SimdFloatMult           0      0.00%     79.90% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::SimdFloatMultAcc           0      0.00%     79.90% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::SimdFloatMatMultAcc           0      0.00%     79.90% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::SimdFloatSqrt           0      0.00%     79.90% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::SimdReduceAdd           0      0.00%     79.90% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::SimdReduceAlu           0      0.00%     79.90% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::SimdReduceCmp           0      0.00%     79.90% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::SimdFloatReduceAdd           0      0.00%     79.90% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::SimdFloatReduceCmp           0      0.00%     79.90% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::SimdAes           0      0.00%     79.90% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::SimdAesMix           0      0.00%     79.90% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::SimdSha1Hash           0      0.00%     79.90% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::SimdSha1Hash2           0      0.00%     79.90% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::SimdSha256Hash           0      0.00%     79.90% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::SimdSha256Hash2           0      0.00%     79.90% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::SimdShaSigma2           0      0.00%     79.90% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::SimdShaSigma3           0      0.00%     79.90% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::SimdPredAlu           0      0.00%     79.90% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::Matrix           0      0.00%     79.90% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::MatrixMov           0      0.00%     79.90% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::MatrixOP           0      0.00%     79.90% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::MemRead        1840      9.36%     89.26% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::MemWrite        1439      7.32%     96.58% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::FloatMemRead         125      0.64%     97.22% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::FloatMemWrite         547      2.78%    100.00% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::IprAccess           0      0.00%    100.00% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::InstPrefetch           0      0.00%    100.00% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::VectorUnitStrideLoad           0      0.00%    100.00% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::VectorUnitStrideStore           0      0.00%    100.00% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::VectorUnitStrideMaskLoad           0      0.00%    100.00% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::VectorUnitStrideMaskStore           0      0.00%    100.00% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::VectorStridedLoad           0      0.00%    100.00% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::VectorStridedStore           0      0.00%    100.00% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::VectorIndexedLoad           0      0.00%    100.00% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::VectorIndexedStore           0      0.00%    100.00% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::VectorUnitStrideFaultOnlyFirstLoad           0      0.00%    100.00% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::VectorWholeRegisterLoad           0      0.00%    100.00% # Class of committed instruction. (Count)
system.cpu.commitStats0.committedInstType::VectorWholeRegisterStore           0      0.00%    100.00% # Class of committed instruction. (Count)
root@590f72e57b21:/workspace#
```

Figure 7: Detailed simulation statistics from m5out/stats.txt

7.3 Instruction Mix Analysis

Instruction Type	Count	Percentage
Integer ALU	14,884	75.73%
Memory Read	1,840	9.36%

Instruction Type	Count	Percentage
Memory Write	1,439	7.32%
Float Add	181	0.92%
SIMD Operations	389	1.98%
Other	921	4.69%

7.4 View Statistics Command:

```
head -100 m5out/stats.txt
```

---

8. Challenges Encountered and Troubleshooting

This section documents the issues encountered during the assignment and the systematic approach used to resolve each problem. Effective troubleshooting was critical to successfully completing this simulation exercise.

Challenge 1: macOS Compatibility Issue

Aspect	Details
Problem	GEM5 does not build natively on macOS operating system
Symptoms	Build system errors, missing Linux-specific libraries
Root Cause	GEM5 is designed primarily for Linux environments
Investigation	Reviewed GEM5 documentation and community forums
Solution	Deployed Docker container running Ubuntu 22.04 LTS
Verification	Successfully executed `apt-get update` inside container

Commands Used:

```
docker run -it -v
        ~/cumberlands/ComputerArchitectureDesign/Using_GEM5:/workspace
        ubuntu:22.04 /bin/bash
```

Challenge 2: Architecture Mismatch (ARM vs X86)

Aspect	Details
Problem	Compiled binary incompatible with GEM5 X86 simulator

Aspect	Details
Symptoms	`ValueError: ('No SE workload is compatible with %s', './hello')`
Root Cause	Docker on Apple Silicon runs ARM64 containers, producing ARM binaries
Investigation	Used `file hello` command to verify binary architecture
Solution	Installed x86_64 cross-compiler for cross-compilation
Verification	`file hello` showed "ELF 64-bit LSB executable, x86-64"

Troubleshooting Steps: 1. Identified the error message indicating workload incompatibility 2. Checked binary architecture using `file hello` command 3. Discovered binary was ARM64 instead of X86-64 4. Researched cross-compilation solutions 5. Installed and used x86_64-linux-gnu-gcc cross-compiler

Commands Used:

```
# Check binary architecture
file hello
# Output: hello: ELF 64-bit LSB pie executable, ARM aarch64... (WRONG)

# Install cross-compiler
apt-get install -y gcc-x86-64-linux-gnu

# Cross-compile for X86
x86_64-linux-gnu-gcc -static hello.c -o hello

# Verify correct architecture
file hello
# Output: hello: ELF 64-bit LSB executable, x86-64... (CORRECT)
```

Challenge 3: Deprecated Script Location

Aspect	Details
Problem	Original script path `configs/example/se.py` not working
Symptoms	`fatal: The 'configs/example/se.py' script has been deprecated`
Root Cause	GEM5 version 23.0 relocated SE scripts to deprecated folder
Investigation	Read error message and explored configs directory structure
Solution	Updated path to `configs/deprecated/example/se.py`
Verification	Simulation ran successfully with new path

Commands Used:

```
# Original command (failed)
./gem5/build/X86/gem5.opt ./gem5/configs/example/se.py -c ./hello

# Updated command (success)
./gem5/build/X86/gem5.opt ./gem5/configs/deprecated/example/se.py -c
        ./hello
```

Challenge 4: Missing Build Dependencies

Aspect	Details
Problem	GEM5 compilation failed due to missing libraries
Symptoms	Various "library not found" errors during scons build
Root Cause	Ubuntu minimal image lacks development packages
Investigation	Analyzed error messages to identify missing packages
Solution	Installed comprehensive dependency list
Verification	Build completed with "scons: done building targets"

Complete Dependency Installation:

```
apt-get install -y python3 scons gcc g++ git build-essential m4 \
    zlib1g zlib1g-dev libprotobuf-dev protobuf-compiler \
    libprotoc-dev libgoogle-perftools-dev python3-dev \
    python3-six python-is-python3 libboost-all-dev pkg-config
```

Challenge 5: Long Build Time Optimization

Aspect	Details
Problem	GEM5 compilation taking excessive time
Symptoms	Single-threaded build estimated >2 hours
Root Cause	Default build uses single CPU core
Investigation	Reviewed scons documentation for parallel options
Solution	Used `-j$(nproc)` flag for parallel compilation
Verification	Build completed in ~45 minutes

Optimization Applied:

```
# Parallel build using all available cores
scons build/X86/gem5.opt -j$(nproc)
```

Troubleshooting Summary Table

Issue	Error Type	Time to Resolve	Difficulty
macOS Compatibility	Environment	15 minutes	Medium
Architecture Mismatch	Runtime	30 minutes	High
Deprecated Script	Path Error	5 minutes	Low
Build Dependencies	Compilation	20 minutes	Medium
Long Build Time	Performance	5 minutes	Low

---

9. Lessons Learned

9.1 Understanding Computer Architecture Simulation

- **Cycle-Accurate Simulation:** GEM5 provides detailed timing information (11,491,500 ticks for "Hello World") that helps understand how programs execute at the hardware level.
- **Memory Hierarchy:** The configuration demonstrates the importance of cache hierarchy in modern processors.
- **CPI Analysis:** Our simple program achieved a CPI of 2.25, indicating memory access latency impacts on execution.

9.2 Simulation Modes

- **Syscall Emulation (SE):** Simulates user-level code by emulating system calls. Faster but less detailed. Used in this assignment.
- **Full System (FS):** Simulates entire system including OS. More accurate but resource-intensive.

9.3 Cross-Platform Development

- Understanding the importance of target architecture when compiling binaries
- Cross-compilation techniques for running X86 programs on ARM development machines
- Docker as a solution for platform compatibility issues

9.4 Performance Metrics Interpretation

The simulation provides valuable insights into: - **Instruction count:** 10,220 instructions for a simple print statement shows library overhead - **Instruction mix:** 75% integer ALU operations typical for system initialization - **Memory operations:** ~17% of operations are memory accesses

9.5 Timing Models in GEM5

- **AtomicSimpleCPU:** Fast functional simulation, no timing
- **TimingSimpleCPU:** Simple timing-accurate model (used in this assignment)

- **O3CPU:** Detailed out-of-order execution model for advanced research

---

10. Conclusion

This assignment successfully demonstrated the installation, configuration, and execution of the GEM5 simulator. The "Hello, World!" program was compiled and executed within the simulated X86 environment, validating the correct setup of the simulation infrastructure.

Key Accomplishments:

1. ✅ Set up GEM5 development environment using Docker
2. ✅ Successfully built GEM5 for X86 architecture
3. ✅ Created and cross-compiled Hello World program for X86
4. ✅ Configured simulation parameters correctly
5. ✅ Executed simulation and obtained **"Hello, World!"** output
6. ✅ Analyzed simulation statistics (11,491,500 ticks, 10,220 instructions)

Key Findings:

- Simple "Hello World" program required **10,220 instructions** and **23,016 CPU cycles**
- Achieved **CPI of 2.25** indicating memory-bound execution
- Simulation completed in **0.03 seconds** of real time
- **75.73%** of instructions were integer ALU operations

The exercise provided valuable hands-on experience with computer architecture simulation, reinforcing theoretical concepts with practical implementation. Understanding GEM5 is crucial for computer architecture research, enabling detailed analysis of processor designs before physical implementation.

---

11. References

Binkert, N., Beckmann, B., Black, G., Reinhardt, S. K., Saidi, A., Basu, A., Hestness, J., Hower, D. R., Krishna, T., Sardashti, S., Sen, R., Sewell, K., Shoaib, M., Vaber, N., Hill, M. D., & Wood, D. A. (2011). The gem5 simulator. *ACM SIGARCH Computer Architecture News*, *39*(2), 1-7. https://doi.org/10.1145/2024716.2024718

Docker Inc. (2024). *Docker documentation*. Docker. https://docs.docker.com/

GEM5 Project. (n.d.-a). *GEM5 documentation*. Retrieved March 11, 2026, from https://www.gem5.org/documentation/

GEM5 Project. (n.d.-b). *Getting started with gem5*. Retrieved March 11, 2026, from https://www.gem5.org/getting_started/

GNU Project. (2024). *GCC, the GNU Compiler Collection*. Free Software Foundation. https://gcc.gnu.org/

Lowe-Power, J., Ahmad, A. M., Akram, A., Alian, M., Amslinger, R., Andreozzi, M., Armejach, A., Asmussen, N., Beckmann, B., Bharadwaj, S., Black, G., Bloom, G., Bruce, B. R., Carvalho, D. R., Castrillon, J., Chen, L., Derber, N., & Wood, D. A. (2020). The gem5 simulator: Version 20.0+. *arXiv preprint arXiv:2007.03152*. https://arxiv.org/abs/2007.03152

Patterson, D. A., & Hennessy, J. L. (2017). *Computer organization and design: The hardware/software interface* (5th ed.). Morgan Kaufmann.

Stallings, W. (2021). *Computer organization and architecture: Designing for performance* (11th ed.). Pearson.

Appendices

Appendix A: File Listings

hello.c

```c
#include <stdio.h>

int main() {
    printf("Hello, World!\n");
    return 0;
}
```

run_hello.py

```python
import m5
from m5.objects import *

# Create the system
system = System()
system.clk_domain = SrcClockDomain()
system.clk_domain.clock = "1GHz"
system.clk_domain.voltage_domain = VoltageDomain()

# Memory configuration
system.mem_mode = "timing"
system.mem_ranges = [AddrRange("512MB")]
system.mem_ctrl = DDR3_1600_8x8()
system.mem_ctrl.range = system.mem_ranges[0]

# CPU configuration
system.cpu = TimingSimpleCPU()
system.cpu.icache = L1_ICache(size="32kB")
```

```
system.cpu.dcache = L1_DCache(size="32kB")

# Connecting CPU and Memory
system.membus = SystemXBar()
system.cpu.icache_port = system.membus.slave
system.cpu.dcache_port = system.membus.slave
system.cpu.createInterruptController()

# Setting up workload
system.workload = SEWorkload.init_compatible("hello")
system.cpu.workload = system.workload
system.cpu.createThreads()

# Simulation Configuration
root = Root(full_system=False, system=system)
m5.instantiate()

print("Beginning simulation!")
exit_event = m5.simulate()
print("Exiting @ tick {} because {}".format(
    m5.curTick(), exit_event.getCause()))
```

Appendix B: Command Summary

Step	Command
Start Docker	`docker run -it -v ~/workspace:/workspace ubuntu:22.04 /bin/bash`
Update System	`apt-get update`
Install Dependencies	`apt-get install -y python3 scons gcc g++ git build-essential...`
Clone GEM5	`git clone https://gem5.googlesource.com/public/gem5`
Build GEM5	`scons build/X86/gem5.opt -j$(nproc)`
Install Cross-Compiler	`apt-get install -y gcc-x86-64-linux-gnu`
Compile Program	`x86_64-linux-gnu-gcc -static hello.c -o hello`
Run Simulation	`./gem5/build/X86/gem5.opt ./gem5/configs/deprecated/example/se.py -c ./hello`
View Statistics	`head -100 m5out/stats.txt`

Appendix C: Complete Simulation Output

```
gem5 Simulator System.  https://www.gem5.org
gem5 version 23.0.0.1
gem5 compiled Mar 11 2026 15:53:27
gem5 started Mar 12 2026 01:05:17
gem5 executing on 590f72e57b21, pid 24277
command line: ./gem5/build/X86/gem5.opt
./gem5/configs/deprecated/example/se.py -c ./hello

warn: The `get_runtime_isa` function is deprecated. Please migrate
away from using this function.
warn: The se.py script is deprecated. It will be removed in future
releases of gem5.
Global frequency set at 1000000000000 ticks per second
warn: No dot file generated. Please install pydot to generate the dot
file and pdf.
src/mem/dram_interface.cc:690: warn: DRAM device capacity (8192
Mbytes) does not match the address range assigned (512 Mbytes)
system.remote_gdb: Listening for connections on port 7000
**** REAL SIMULATION ****
src/sim/simulate.cc:194: info: Entering event queue @ 0.  Starting
simulation...
Hello, World!
Exiting @ tick 11491500 because exiting with last active thread
context
```

Document prepared for Computer Architecture Design Course
Assignment: Using GEM5 Simulator
Date: March 12, 2026