

Algorithm For Monitoring And Preventing Coffee Rust



Simón Marín Giraldo

Miguel Fernando Ramos García

Medellín, October 29, 2019.

Designed Data Structure

Inserten sus gráficas vectorizadas que explican su Estructura de Datos




Gráfico 1: Lista simplemente encadenada de personas. Una persona es una clase que contiene nombre, cédula y foto.

Escriban sus propias palabras para describir sus gráficas

Data Structure Operations




Gráfico 2: Operación de borrado de una estructura de datos

Operation	Complexity
leerArchivo(String data)	$O(n^2)$
seleccionarDataset()	$O(n)$
llenarMatriz(double [][] matriz)	$O(n^2)$
llenarImpureza(double [][] matriz)	$O(n^2)$
menores(double [][] matriz)	$O(n)$
addChild(Node childNode, int position)	$O(1)$
addNewNode(Node u, Object info, int i)	$O(1)$
numberOfNodesInTree(Node rootNode)	$O(n)$

Table 1: Table to report complexity analysis

Design Criteria of the Data Structure

- AVL decision trees are good for sorting, searching and storing big volumes of data with a low Big-O complexity.
- CART (Classification And Regression Tree) algorithm is a good decision tree implementation which can be easily managed recursively. It provides a clear and simple comprehension of the structures that are being created which filter and classify the data.

Time and Memory Consumption

Operation	Execution time
leerArchivo(String data)	0.0ms
seleccionarDataset()	0.0ms
llenarMatriz(double [][] matriz)	0.0ms
llenarImpureza(double [][] matriz)	0.0ms
menores(double [][] matriz)	0.0ms
addChild(Node childNode, int position)	0.0ms
addNewNode(Node u, Object info, int i)	0.0ms
numberOfNodesInTree(Node rootNode)	0.0ms

Table 2: Execution time of the operations of the data structure for each data set..

Data set	Memory used
data_set.csv	7.84 MB
data_set_balanced.csv	7.0 MB
data_set_train.csv	6.84 MB
data_set_test.csv	6.56 MB

Table 3: Memory used for each operation of the data structure and for each data set.