

Specification

Sandro Speth

Markus Zilch

Dominik Wagner

Wintersemester 18/19

1 Introduction

The traditional power grid is changing more and more over time. Due to increasing sensitization for the use of renewable and reliable sources of energy instead of nuclear power sources, there is an increasing accommodation of renewable energy. To fulfill our daily energy need only with such energy sources is quite difficult and needs a lot of planning and simulation. In this work we build a smart energy system to simulate a smart grid.

A smart grid is an energy efficient system with information and communication technology, automation and awareness of energy consumption. There are many different actors and technologies which are connected to each other and interoperate to optimize the grid.

A smart energy system creates the bridge between a power grid and a resilient and reliable smart grid. Users can simulate reliable energy sources, as well as different kinds of energy consumers, e.g. homes or offices. Simulation of distributed energy sources and automation of processes build an energy management system. Through this microgrids we can possibly rely completely on renewable energy sources in the future. This can be checked with our smart energy system.

The report is structured as follows. In section ?? we present our system design. First, we give some basic foundations which are relevant for our smart energy system, such as the difference between kWh and kW . Afterwards we present our functional requirements for the smart energy systems as user stories. From these functional requirements we created our architecture which will be described in this section as well.

2 System Design

2.1 Difference between kW and kWh

W is a measuring scale for energy applied per timeinstance. There are different possibilities to describe W in common terms. A pretty graphic one is the movement of mass. $1W$ equals $1kg$ of mass moved by 1 meter in one second: $1\frac{kg*m}{s}$. Or in electrical terms: $1W$ equals 1 Ampere of electrical power with a voltage of 1 Volt. Both of those formulas are equal to a much simpler Term for Watt: $1W = 1J/s$. In simple terms, 1 Watt is the same as one Joule of energy applied

over 1 second. For completeness, $1kW = 1000W$.

Wh are the common term for measuring energyconsumption/-production. $1Wh$ is $1W$ applied continuously over 1 hour. $1Wh = 1W * 1h = 1J/s * 3600s = 3600J$. For a scientific context the Wh therefore is simply not used, instead the common SI standard J is used.

In comparison, Wh is the total amount of energy used. W is how much energy is used in a specified timeslot (mostly 1 second).

Sources:

Robert A. Nelson: The International System of Units. Applied Technology Institute

https://www.atcourses.com/international_system_units.htm

G rard Borvon: History of the electrical units. S-eau-S, 10. September 2012

<http://seaus.free.fr/spip.php?article964>

Das Internationale Einheitensystem (SI). Deutsche  bersetzung der BIPM-Brosch re „Le Syst me international d’unit s/The International System of Units (8e  dition, 2006)“. In: PTB-Mitteilungen. Band 117, Nr. 2, 2007

<https://www.ptb.de/cms/fileadmin/internet/Themenrundgaenge/ImWeltweitenNetzDerMetrologiesi.pdf>

aufgrund der EU-Richtlinie 80/181/EWG in den Staaten der EU bzw. dem Bundesgesetz  ber das Messwesen in der Schweiz

<https://www.admin.ch/opc/de/classified-compilation/20101915/>

2.2 Difference between consumption and demand

2.3 Userstories

1. As a user, I need to create one or more wind turbines in the simulation so that I can calculate the potential energy output.
2. As a user, I need to create one or more photovoltaic panels in the simulation so that I can calculate the potential energy output.
3. As a user, I need to create one or more batteries in the simulation so to save unused energy of in my simulation.
4. As a user, I need to get the charge state of my batteries to know the impact of the energy storage on the grid.
5. As a user, I need to create one or more homes on the demand side in the simulation so that I can simulate some energy consumer.
6. As a user, I need to create one or more commercial buildings on the demand side in the simulation so to simulate some high energy consumer.
7. As a user, I need to get dynamic energy prices calculated from the simulation to determine if I want to sell my produced energy or store it for later use.

8. As a user, I need to use weather data in the simulation to simulate the smart energy system more precise and realistic.
9. As a user, I need to use already saved weather data in the simulation to not be dependent on the availability of the weather service.
10. As a user, I need to generate a forecast for energy generation and demand using the simulation in order to make informed decisions.
11. As a developer, I want to add more supplier modules than wind turbines and photovoltaic panels to the simulation to improve the smart energy system in the future with further technology.
12. As a developer, I want to add more consumer modules to the simulation to be able to add more consumer than homes and commercial buildings.
13. As a user, I want to be able to create a smart energy system which is independent to an power grid to simulate a reliable smart grid.
14. As a user, I want to get a visual notification if the supply of energy is smaller than the demand of energy to know when more energy supplier are needed.
15. As a demand module, I need to get energy from the (charged) batteries if the provided supply is too small for my demand so that I still have enough money.
16. As a user, I want to model a chargeable battery so I can store the energy for later usage, if the supply is greater than the demand.
17. As a user, I need the battery to be able to discharge energy if the supply is lower than the demand in order to make my stored energy usable and keep the demand satisfied.
18. As a user, I need the smart grid to be able to manage peaks in the demand in order to smooth the impact on the grid and reduce the likelihood of power outages.
19. As a user, I need that the demand side consumers feature different load scenarios like home users and commercial users (constant load, occasionally peak loads) in order to make the simulation accurate for real life applications.
20. As a user, I want to be able to use the system with my webbrowser so that I can use different platforms to view it and have easy access to the simulated data.
21. As a user, I want to be able to see the energy supply of each individual supply component in order to be able to assess the efficiency of the supplier.
22. As a user, I want to be able to see the energy demand of individual components for efficiency assessment and informed decision making.
23. As a user, I want to see a summary of energy supply and demand for all components in order to easily assess the current situation.
24. As a user, I want to adjust the demand by postponing the use of devices during peak hours in order to prevent a complete outage of the grid or to react to one-time-only scenarios.

25. As a user, I want the simulation to adapt the demand based on the price per kWh in order to minimize costs of my energy demands and maximize profits of my energy supply.

Todo:

1. Replace ... with content
2. check spelling and grammar
3. price per min and price of the next day
4. user stories for visualization

2.4 Architecture

System architecture Diagram

A5

add weather component

A6

reliable and responsive system

A7

three-tier system architecture