



REFERENCES

For all other details See:

WBNM_History.pdf
WBNM_Validation.pdf
WBNM_Runfile.pdf
WBNM_Theory.pdf
WBNM_Tutorial.pdf
WBNM_UserGuide.pdf

A list of papers referred to in WBNM_Theory

- Adams, A. (1991). Application and comparison of RORB, WBNM and RAFTS runoff routing models. Instn. Engrs. Australia, 20th Hydrology and Water Resources Symposium, NCP 91/22, Vol. 2, pp. 485-491.
- Aitken, A.P.(1975) Hydrologic Investigation and Design of Urban Stormwater Drainage Systems. Australian Water Resources Council, Technical Paper No. 10. ISBN 0 642 501 343
- ANCOLD Australian Committee on Large Dams (1986) Guidelines on Design Floods for Dams.
- Askew, A.J.(1968) Lag Time of Natural catchments. University of NSW Water Research Laboratory Report No.107
- Askew, A.J.(1970) Derivation of formulae for variable lag time. Journal of Hydrology, Vol.10, pp.225-242.
- Bates, B.C. and Pilgrim, D.H. (1986) Simple models for nonlinear runoff routing. Instn. Engineers Australia, Civil Engineering Transactions, Vol.CE28, pp.284-291.
- Boyd, M.J. (1975) Hydrograph synthesis using mathematical models. Instn. Engineers Australia, Hydrology Symposium, National Conference Publication 75/3, pp.117-121.
- Boyd, M.J. (1978) A storage routing model relating drainage basin hydrology and geomorphology. Water Resources Research, Vol.14, No. 5, pp.921-928.
- Boyd, M.J., Pilgrim, D.H. and Cordery, I. (1979) A storage routing model based on catchment geomorphology. Journal of Hydrology, Vol.42, pp.209-230
- Boyd, M.J., Pilgrim, D.H. and Cordery, I. (1979) An improved runoff routing model based on geomorphological relations. Instn. Engineers Australia, Hydrology and Water Resources Symposium, National Conference Publication 79/10, pp.229-233.
- Boyd, M.J. (1980) Evaluation of simplified methods for design of retarding basins. Instn. Engineers Australia, Hydrology and Water Resources Symposium, National Conference Publication 80/9, pp.182-183.
- Boyd, M.J. (1985) Effect of catchment sub-division on runoff routing models. Instn. Engineers Australia, Civil Engineering Transactions, Vol.CE27, No.4, pp.403-410.
- Boyd, M.J., Bates, B.C., Pilgrim, D.H. and Cordery, I. (1987) WBNM A General Runoff Routing Model-Computer Programs and User Guide. University of NSW Water Research Laboratory Report No. 170 ISBN 0/85824/379/2
- Boyd, M.J., Bates, B.C., Pilgrim, D.H. and Cordery, I. (1987) WBNM A general runoff routing model. Instn. Engineers Australia, Fourth National Conference on Local Government Engineering, National Conference Publication 87/9, pp.137-141.
- Boyd, M.J.(1987) Generalised head-discharge equations for culverts. Instn. Engineers Australia, Fourth National Conference on Local Government Engineering, National Conference Publication 87/9, pp.161-165.
- Boyd, M.J.(1987) Head-discharge relations for culverts. Proceedings 21st Congress, International Association for Hydraulic Research, Melbourne, Vol.6, Keynote Addresses, pp.118-122. ISBN 085825 280 5.
- Boyd, M.J. and Cordery, I. (1989) A study of design parameters for flood hydrograph models. Instn. Engineers Australia, Hydrology and Water Resources Symposium, National Conference Publication 89/19, pp.119-123.

- Boyd, M.J., Bufill, M.C. and Knee, R.M.(1993) Pervious and impervious runoff in urban catchments. *Hydrological sciences Journal*, Vol. 38, No. 6, pp. 200-220.
- Boyd, M.J., Rigby, E.H., Sharpin, M.G. and VanDrie, R. (1994) Enhanced runoff routing model WBNM. *Instn. Engineers Australia, Water Down Under Conference, National Conference Publication 94/15*, pp.445-448.
- Boyd, M.J. and Milevski, P. (1996) Modelling runoff from pervious and impervious surfaces in urban catchments. *7th International Conference on Urban Storm Drainage, Hannover Germany*, pp.1055-1060.
- Boyd, M.J. Rigby, E.H. and VanDrie, R. (1996) WBNM - a comprehensive flood model for natural and urban catchments. *7th International Conference on Urban Storm Drainage, Hannover Germany*, pp.329-334.
- Boyd, M.J. Rigby, E.H. and VanDrie, R. (1999) Modelling urban catchments with WBNM. *Instn. Engineers Australia, Water 99 Joint Congress. 25th Hydrology and Water Resources Symposium and 2nd International Conference on Water Resources and Environmental Research, National Conference Publication, ISBN 185 825 7165, Vol.2*, pp.831-835.
- Boyd, M.J. (2003). Accurate modelling of high early discharge onsite detention storages. *Institution of Engineers Australia, Australian Journal of Water Resources*, vol. 6, no.2, pp. 105-114.
- Boyd, M.J. and Bodhinayake, N.D. (2006). WBNM runoff routing parameters for South and Eastern Australia. *Institution of Engineers Australia, Australian Journal of Water Resources*, vol. 10, no. 1, pp. 35-48.
- Bufill, M.C. and Boyd, M.J. (1992) A simple flood hydrograph model for urban catchments. *Proceedings International Symposium on Urban Stormwater Management, Instn. Engineers Australia, National Conference Publication 92/1*, pp.98-103.
- Bureau of Meteorology, Australia (1984) *The Estimation of Probable Maximum Precipitation in Australia for Short Durations and Small Areas. Bulletin 51. ISBN 0 644 00598 X.*
- Bureau of Meteorology, Australia (1994) *The Estimation of Probable Maximum Precipitation in Australia: Generalised Short Duration Method. Bulletin 53. ISBN 0 644 33419 3.*
- Concrete Pipe Association of Australia. *Hydraulics of Precast Concrete Conduits. Hydraulic Design Manual.*
- Cordery, I, and Webb, S.N.(1974). Flood estimation in eastern New South Wales - A design method. *Instn. Engineers Australia, Civil Engineering Transactions*, Vol. CE16, No.1, pp.87-93.
- Goyen, A.G. and O'Loughlin, G.G. (2000). Examining the basic building blocks of urban runoff. *8th Intl. Confce. on Urban Storm Drainage, Sydney, Australia*, pp. 1382-1390.
- Green, J., Smith, G. and Varley, I. (2005) A guide to rainfall-runoff-routing model selection. *Instn. Engrs. Australia, 29th Hydrology and Water Resources Symposium, CD ROM of Proceedings*, 9 pp.
- Institution of Engineers Australia (1987). *Australian Rainfall and Runoff. A Guide to Flood Estimation. ISBN 085825 434 4 Volume 1 Text, Volume 2, Maps.*
- Institution of Engineers Australia (1998). *Australian Rainfall and Runoff. A Guide to Flood Estimation. Volume 1.*
- Jenkins, G (1997). Estimating the WBNM lag parameter for ungauged catchments in Queensland. *Research Monograph 97-6. Physical Infrastructure Centre. School of Civil Engineering, Queensland University of Technology.*

- Kemp, D.J. and Daniell, T.M. (1995) Towards simple and rational urban hydrology models - a new approach, Institution of Engineers Australia, 2nd International Symposium on Urban Stormwater Management , pp.195-200.
- MacDonald, TC and Langridge-Monopolis, J. (1984). Breaching characteristics of dam failures. ASCE Journal of Hydraulic Engineering, Vol. 110, No. 5, pp.567-586.
- Leopold, L.B., Wolman, M.G. and Miller, J.P. (1964). Fluvial Processes in Geomorphology. Freeman Publishing, San Francisco.
- Natural Environment Research Council UK(1975) Flood Studies Report, Vol. I Hydrological Studies.
- Pilgrim, D.H. (1977). Isochrones of travel time and distribution of flood storage from a tracer study on a small watershed. Water Resources Research, vol. 13, pp. 587-596.
- Pilgrim, D.H. (1982). Characteristics of nonlinearity and spatial variations of flood runoff from two tracing studies. Civil Engineering Transactions Institution of Engineers Australia, vol. CE24, pp. 121-126.
- Rao, A.R., Delleur, J.W. and Sarma, P.B.S. (1972) Conceptual hydrologic models for urbanising basins. Proceedings American Society of Civil Engineers, Vol. 98, No.HY7, pp.1215-1222.
- Rigby, E.H. and Bannigan, D.J.(1996) The embedded design storm concept - a critical review. Instn. Engineers Australia, Hydrology and Water Resources Symposium, National Conference Publication, pp.453-459.
- Rigby, E.H., Boyd, M.J. and VanDrie, R. (1999) Experiences in developing the hydrology model WBNM. 8th International Conference on Urban Storm Drainage, Sydney Australia, isbn 0 85825 718 1, Vol.3, pp. 1374-1381.
- Rigby, E.H. and Silveri, P. (2001). The impact of blockages on flood behaviour in the Wollongong storm of August 1998, Institution of Engineers Australia, Conference on Hydraulics in Civil Engineering, Tasmania, Dec. 2001, ISBN 085825 7858, pp. 107-116.
- Rigby, E.H., Boyd, M.J., Roso, S, Silveri, P and Davis, A. (2002). Causes and effects of culvert blockage during large storms. CD ROM of Proceedings, 9th International Conference on Urban Drainage, Portland, USA, ISBN 0-7844-0644-8, 16 pp.
- Rigby, E.H., Boyd, M.J., Roso, S. and VanDrie, R. (2005). Storms, storm bursts and flood estimation: a need for review of the AR&R procedures. Aust. Journal of Water Resources, 8(2):213-220.
- Rigby, E.H & Silveri, P. (2006) Experiences in Developing an Upgraded OSD Policy for the City of Wollongong, 30th Hydrology & water Resources Symposium, Launceston, December 2006
- Rigby, E.H. (2009) Quantifying Calibration Uncertainty in Coupled Hydrologic/Hydraulic Modelling, H2009 - 32nd Hydrology and Water Resources Symposium, Newcastle NSW, November 2009
- Rigby, E.H. and Barthelmess, A.J. (2010), Culvert Blockage Mechanisms and their Impact on Flood Behaviour, 34th World Congress of the International Association for Hydro-Environment Engineering and Research (IAHR) Brisbane 26 June – 1 July, 2011.
- Roso, S., Boyd, M.J. and Chisholm, L. A. (2006). Assessment of spatial analysis techniques for estimating impervious cover. Institution of Engineers Australia, 30th Hydrology & Water Resources Symposium, Launceston.
- Ryan, C.J. and Boyd, M.J. (2002). Automation of WBNM hydrologic modelling using GIS aided topographic parameterisation. Institution of Engineers Australia, 27th Hydrology and Water resources Symposium, Melbourne. CD-ROM of Proceedings, 8 pp.

Ryan, C.J. and Boyd, M.J. (2002). Automated catchment parameterisation for runoff routing models utilising 3D GIS contour information. 5th International Conference on Hydroinformatics, Cardiff UK. ISBN 1 84339 021 3, Volume 2, pp. 1043-1048.

Sharpin, M.G.(1993) The prediction of retarding basin requirements by runoff routing models. Instn. Engineers Australia, Watercomp 93 Conference, National Conference Publication 93/2, pp.195-200.

Sobinoff, P., Pola, J.P. and O'Loughlin, G.G. (1983) Runoff routing parameters for the Newcastle-Sydney-Wollongong region. Instn. Engineers Australia, Hydrology and Water Resources Symposium, National Conference Publication 83/13, pp.28-32.

US Department of Transport, Federal Highway Administration, *Hydraulic Charts for the Selection of Highway Culverts*, Hydraulic Engineering Circular 5.

VanDrie, R, Boyd, M.J. and Rigby, E.H. Modelling of hydraulic flows using WBNM2001, Institution of Engineers Australia, Conference on Hydraulics in Civil Engineering, Tasmania, Dec. 2001, ISBN 085825 7858, pp. 523-532.

Vermeyen, T. and Mares, D. (1992). Alternatives for enhancing spillway capacity currently being pursued by the United States Bureau of Reclamation. US Dept. of the Interior, Bureau of Reclamation Report.

Webb, S.N. and O'Loughlin, G.G. (1981) An evaluation of methods used for design flood estimation in NSW. Instn. Engineers Australia, First National Conference on Local Government Engineering, National Conference Publication 81/7, pp.118-123.

Wong, T.H.F. and Laurenson, E.M. (1983) Wave speed-discharge relations in natural channels. Water Resources Research, Vol.19, pp.701-706.