

## Features

- Siphon jet.
- ¾" (19 mm) top spud.
- 0.5 or 1.0 gpf (1.9 or 3.8 lpf) based on valve selected.
- Siphon jet.
- Includes inlet and outlet spuds and hangers.
- Includes anti-backsplash wall.
- 14-1/2" (368 mm) extended rim.
- 0.5 or 1.0 gpf (1.9 or 3.8 lpf).

## Material

- Vitreous china.

## Recommended Products/Accessories

K-23726 Drain treatment  
K-23725 Cast iron cleaner  
K-7526 Touchless hybrid 0.5 gpf urinal flushometer  
K-7537 Exposed hybrid 0.5 gpf washdown urinal flushometer  
K-7537-RF Exposed hybrid 0.5 gpf urinal flushometer retrofit  
K-13519 Manual 0.5 GPF Urinal Flushometer  
K-13519-RF Manual 0.5 GPF Urinal Flushometer  
K-76318 Manual 0.5 GPF Urinal Flushometer  
K-7527 Touchless hybrid 1.0 gpf washdown urinal flushometer  
K-7542 Exposed hybrid 1.0 gpf urinal flushometer  
K-76319 Manual 1.0 GPF Urinal Flushometer

## Included Components

Additional Components:

2" outlet spud  
¾" inlet spud  
Hanger(s)



**ADA**

## Codes/Standards





ASME A112.19.2/CSA B45.1  
DOE - Energy Policy Act 1992  
EPA WaterSense®  
ADA  
ICC/ANSI A117.1

## KOHLER® One-Year Limited Warranty

See website for detailed warranty information.

## Available Colors/Finishes

*Color tiles intended for reference only.*

Color	Code	Description
	0	White
	96	Biscuit
	47	Almond
	7	Black Black™

