# Datasheet

# HD-YM30D55



## General

- Indoor
- Spotlight
- Pre-embedded
- Version: round
- Housing: white
- Reflector: white/black/chrome
- System Output: 420lm
- IP 20

## LED

- 2700K/3000K/3500K/4000K/5000K
- CRI>90
- 50000h@L80B10
- SDCM: 3

## Optics

- Beam angle: 15°/24°/36°
- UGR <13
- Honeycomb mesh

## Electric

- LED Driver: none
- LED Power: 7W
- 36V
- 150mA


## Dimensions

- Measurement: Ø80mm
- Cutout: Ø55mm
- Height: 80mm
- Pivot: max. 30°
- Rotation: 355°

## Description

- Round adjustable Pre-embedded Spotlight (55 Series) made of die-cast aluminum with white powder-coating finish (RAL 9016) and white/black/chrome reflector;
- Work with DALI/0-10V/TRIAC dimming driver;
- LED 7W;
- Measurement Ø80mm; ceiling cutout of Ø55mm with a narrow mounting trim;
- High color rendering at an index of CRI90;
- After a lifetime of 50000h min. 80% of the luminous flux with energy efficient Luminus LED Chips;
- 5 years warranty;
- Beam characteristic with 15°/24°/36° beam angles;
- Lighting perfectly suitable for reading, writing as well as computer and control work according to DIN EN 12464-1(UGR<13);
- Degree of housing protection according to DIN EN 60529 (IP20).


## Light distribution




7W15°277lm

Lux


| h(m) | d(m) | Em | Emax |
|---|---|---|---|
| 1 | 0.29 | 1592 | 2571 |
| 2 | 0.59 | 398 | 642.8 |
| 3 | 0.89 | 176.9 | 285.7 |
| 4 | 1.19 | 99.51 | 160.7 |
| 5 | 1.49 | 102.8 | 102.8 |




7W24°359lm

Lux

| h(m) | d(m) | Em | Emax |
|---|---|---|---|
| 1 | 0.38 | 1414 | 2105 |
| 2 | 0.79 | 353.4 | 526.3 |
| 3 | 1.19 | 157.1 | 233.9 |
| 4 | 1.59 | 88.35 | 131.6 |
| 5 | 1.99 | 56.54 | 84.21 |





7W36°367lm

Lux

| h(m) | d(m) | Em | Emax |
|---|---|---|---|
| 1 | 0.56 | 848.1 | 1226 |
| 2 | 1.12 | 212 | 306.5 |
| 3 | 1.69 | 94.23 | 136.2 |
| 4 | 2.25 | 53.01 | 76.63 |
| 5 | 2.81 | 33.92 | 49.05 |




## Technical drawing




The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors.