# Datasheet

# HD-DZ9006



## General

- Indoor
- Accent Light
- Suspended
- Profile Inset
- Version: rectangle
- Housing: white/black
- Reflector: black
- System Output: 1080lm
- IP 20

## LED

- 2800K-6000K
- CRI>90
- 50000h@L80B10
- SDCM: 3

## Optics

- Beam angle: 15°/25°/30°
- UGR <15

## Electric

- LED Driver: none
- LED Power: 18W
- 36V
- 450mA


## Dimensions


- Measurement:598mm x 34mm
- Height: 65mm


## Description

- 0.6M Suspended Wire Grid Light with white/black painted finish (RAL 9016/RAL 9005) and black reflector;
- Work with DALI dimming driver;
- LED 18W;
- Measurement 598mm x 34mm; height of the profile inset 65mm;
- High color rendering at an index of CRI90;
- After a lifetime of 50000h min. 80% of the luminous flux with energy efficient OSRAM LED Chips;
- 5 years warranty;
- Precise beam characteristic with 15°/25°/30° beam angles;
- Lighting perfectly suitable for reading, writing as well as computer and control work according to DIN EN 12464-1 (UGR<15);
- Degree of housing protection according to DIN EN 60529 (IP20).

## Light distribution




18W 15°

Lux

| h(m) | d(m) | Em | Emax |
|---|---|---|---|
| 1 | 0.23 | 3769 | 5491 |
| 2 | 0.46 | 942.3 | 1373 |
| 3 | 0.69 | 418.8 | 610.1 |

18W 25°

Lux


| h(m) | d(m) | Em | Emax |
|---|---|---|---|
| 1 | 0.51 | 1492 | 2236 |
| 2 | 1.02 | 372.9 | 559.1 |
| 3 | 1.53 | 165.8 | 248.5 |

18W 30°

Lux

| h(m) | d(m) | Em | Emax |
|---|---|---|---|
| 1 | 0.68 | 1954 | 2859 |
| 2 | 1.36 | 488.5 | 714.8 |
| 3 | 2.04 | 217.1 | 317.7 |

## Technical drawing




The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors.