# Datasheet

# HD-YM3075



## General

- Indoor
- Spotlight
- Pre-embedded
- Version: round
- Housing: white
- Reflector: white/black/chrome
- System Output: 720lm
- IP 20

## LED

- 2800K-6000K
- CRI>90
- 50000h@L80B10
- SDCM: 3

## Optics

- Beam angle: 24°/36°
- UGR <13
- Honeycomb mesh

## Electric

- LED Driver: none
- LED Power: 12W
- 36V
- 300mA


## Dimensions

- Measurement: Ø103mm
- Cutout: Ø75mm
- Height: 91.5mm
- Pivot: max. 30°
- Rotation: 355°

## Description

- Round adjustable Pre-embedded Spotlight (75 Series) made of die-cast aluminum with white powder-coating finish (RAL 9016) and white/black/chrome reflector;
- Work with DALI dimming driver;
- LED 12W;
- Measurement Ø103mm; ceiling cutout of Ø75mm with a narrow mounting trim;
- High color rendering at an index of CRI90;
- After a lifetime of 50000h min. 80% of the luminous flux;
- 5 years warranty;
- Beam characteristic with 24°/36° beam angles;
- Lighting perfectly suitable for reading, writing as well as computer and control work according to DIN EN 12464-1(UGR<13);
- Degree of housing protection according to DIN EN 60529 (IP20).


## Light distribution




12W24°785lm

Lux

| h(m) | d(m) | Em | Emax |
|---|---|---|---|
| 1 | 0.39 | 3120 | 4716 |
| 2 | 0.78 | 780 | 1179 |
| 3 | 1.17 | 346.7 | 523.9 |
| 4 | 1.56 | 195 | 294.7 |
| 5 | 1.96 | 124.8 | 188.6 |





12W36°771lm

Lux

| h(m) | d(m) | Em | Emax |
|---|---|---|---|
| 1 | 0.59 | 1675 | 2451 |
| 2 | 1.18 | 418.8 | 612.7 |
| 3 | 1.77 | 186.1 | 272.3 |
| 4 | 2.36 | 104.7 | 153.2 |
| 5 | 2.95 | 67 | 98.04 |




## Technical drawing




The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors.

HDL®