## **APEX TRIGGERS MODULE:**

# GET STARTED WITH APEX TRIGGERS ASSESSMENT

AccountAddressTrigger.apxt

```
trigger AccountAddressTrigger on Account (before insert, before update) {
    for(Account account:Trigger.New){
        if(account.Match_Billing_Address__c == True) {
            account.ShippingPostalCode = account.BillingPostalCode;
        }
    }
}
```

#### **BULK APEX TRIGGERS ASSESSMENT**

ClosedOpportunityTrigger.apxt

}

```
trigger ClosedOpportunityTrigger on Opportunity (before insert, after update) {
   List<Task> tasklist = new List<Task>();
   for(Opportunity opp: Trigger.New){
```

```
if(opp.StageName == 'Closed Won'){
     tasklist.add(new Task(Subject = 'Follow Up Test Task', WhatId = opp.Id));
    }
  }
  if(tasklist.size()>0){
    insert tasklist;
  }
}
APEX TESTING:
GET STARTED WITH APEX UNIT TESTS
ASSESSMENT
VerifyDate.apxt
public class VerifyDate {
  //method to handle potential checks against two dates
      public static Date CheckDates(Date date1, Date date2) {
            //if date2 is within the next 30 days of date1, use date2. Otherwise
use the end of the month
            if(DateWithin30Days(date1,date2)) {
                  return date2;
            } else {
```

```
return SetEndOfMonthDate(date1);
             }
      }
      //method to check if date2 is within the next 30 days of date1
      @TestVisible private static Boolean DateWithin30Days(Date date1, Date
date2) {
             //check for date2 being in the past
      if( date2 < date1) { return false; }
      //check that date2 is within (>=) 30 days of date1
      Date date30Days = date1.addDays(30); //create a date 30 days away from
date1
             if( date2 >= date30Days ) { return false; }
             else { return true; }
      }
      //method to return the end of the month of a given date
      @TestVisible private static Date SetEndOfMonthDate(Date date1) {
             Integer totalDays = Date.daysInMonth(date1.year(), date1.month());
             Date lastDay = Date.newInstance(date1.year(), date1.month(),
totalDays);
             return lastDay;
      }
```

```
}
TestVerifyDate.apxc
@isTest
private class TestVerifyDate {
  @isTest static void Test_CheckDates_case1(){
    Date D = VerifyDate.CheckDates(date.parse('01/01/2020'),
date.parse('01/05/2020'));
    System.assertEquals(date.parse('01/05/2020'), D);
  }
  @isTest static void Test_CheckDates_case2(){
    Date D = VerifyDate.CheckDates(date.parse('01/01/2020'),
date.parse('05/05/2020'));
    System.assertEquals(date.parse('01/31/2020'), D);
  }
  @isTest static void Test_DateWithin30Days_case1(){
    Boolean flag = VerifyDate.DateWithin30Days(date.parse('01/01/2020'),
date.parse('12/30/2019'));
    System.assertEquals(false, flag);
  }
  @isTest static void Test_DateWithin30Days_case2(){
    Boolean flag = VerifyDate.DateWithin30Days(date.parse('01/01/2020'),
```

```
date.parse('02/02/2020'));
    System.assertEquals(false, flag);
  }
  @isTest static void Test DateWithin30Days case3(){
    Boolean flag = VerifyDate.DateWithin30Days(date.parse('01/01/2020'),
date.parse('01/15/2020'));
    System.assertEquals(true, flag);
  }
  @isTest static void Test_SetEndOfMonthDate(){
    Date returndate = VerifyDate.SetEndOfMonthDate(date.parse('01/01/2020'));
  }
TEST APEX TRIGGERS ASSESSMENT
RestrictContactByName.apxt
trigger RestrictContactByName on Contact (before insert, before update) {
      //check contacts prior to insert or update for invalid data
      For (Contact c : Trigger.New) {
            if(c.LastName == 'INVALIDNAME') { //invalidname is invalid
                  c.AddError('The Last Name "'+c.LastName+'" is not allowed
for DML'):
```

}

```
}
}
TestRestrictContactByName.apxc
@isTest
public class TestRestrictContactByName {
  @isTest static void Test_insertupdateContact(){
    Contact cnt = new Contact();
    cnt.LastName = 'INVALIDNAME';
    Test.startTest();
    Database.SaveResult result = Database.insert(cnt, false);
    Test.stopTest();
    System.assert(!result.isSuccess());
    System.assert(result.getErrors().size() > 0);
    System.assertEquals('The last Name "INVALIDNAME" is not allowed for
DML',result.getErrors()[0].getMessage());
  }
}
```

### CREATE TEST DATA FOR APEX TEST

#### **ASSESSMENT**

#### RandomContactFactory.apxc

```
public class RandomContactFactory {

public static List<Contact> generateRandomContacts(Integer numcnt, string lastname){
    List<Contact> contacts = new List<Contact>();
    for(Integer i=0;i<numcnt;i++){
        Contact cnt = new Contact(FirstName = 'Test' +i, LastName = lastname);
        contacts.add(cnt);
    }
    return contacts;
}</pre>
```

## **ASYNCHRONOUS APEX MODULE:**

#### **USE FUTURE METHODS ASSESSMENT**

#### AccountProcessor.apxc

```
public class AccountProcessor {
    @future
    public static void countContacts(List<Id> accountIds){
        List<Account> accountsToUpdate = new List<Account>();
```

```
List<Account> accounts = [Select Id, Name, (Select Id from Contacts) from Account Where Id in :accountIds];
```

```
For(Account acc:accounts){
      List<Contact> contactList = acc.Contacts;
      acc.Number_Of_Contacts__c = contactList.size();
      accountsToUpdate.add(acc);
    }
    update accountsToUpdate;
  }
AccountProcessorTest.apxc
@IsTest
private class AccountProcessorTest {
  @IsTest
  private static void testCountContacts(){
    Account newAccount = new Account(Name='Test Account');
    insert newAccount;
    Contact newContact1 = new
Contact(FirstName='John',LastName='Doe',AccountId = newAccount.Id);
    insert newContact1;
```

```
Contact newContact2 = new
Contact(FirstName='Jane',LastName='Doe',AccountId = newAccount.Id);
    insert newContact2;
    List<Id> accountIds = new List<Id>();
    accountIds.add(newAccount.Id);
   Test.startTest();
   AccountProcessor.countContacts(accountIds);
   Test.stopTest();
  }
}
USE BATCH APEX ASSESSMENT
LeadProcessor.apxc
global class LeadProcessor implements Database.Batchable<sObject> {
  global Integer count = 0;
  global Database.QueryLocator start(Database.BatchableContext bc){
   return Database.getQueryLocator('SELECT ID, LeadSource FROM Lead');
  }
```

```
global void execute (Database.BatchableContext bc, List<Lead> L_list){
    List<lead> L_list_new = new List<lead>();
    for(lead L:L_list){
      L.leadsource = 'Dreamforce';
      L_list_new.add(L);
      count += 1;
    }
    update L_list_new;
  }
  global void finish(Database.BatchableContext bc){
    system.debug('count = ' + count);
  }
}
```

#### LeadProcessorTest.apxc

```
@isTest
public class LeadProcessorTest {
    @isTest
    public static void testit(){
```

```
List<lead> L_list = new List<lead>();
  for(Integer i=0; i<200; i++){
    Lead L = new lead();
    L.LastName = 'name' + i;
    L.Company = 'Company';
    L.Status = 'Random Status';
    L_list.add(L);
  }
  insert L_list;
  Test.startTest();
  LeadProcessor lp = new LeadProcessor();
  Id batchId = Database.executeBatch(lp);
  Test.stopTest();
}
```

# CONTROL PROCESSES WITH QUEUEABLE APEX ASSESSMENT

## AddPrimaryContact.apxc

public class AddPrimaryContact implements Queueable{

```
private Contact con;
```

```
private String state;
  public AddPrimaryContact(Contact con, String state){
    this.con = con;
    this.state = state;
  }
  public void execute(QueueableContext context){
    List<Account> accounts = [Select Id, Name, (Select FirstName, LastName, Id
from contacts)
                            from Account where BillingState = :state Limit 200];
    List<Contact> primaryContacts = new List<Contact>();
    for(Account acc:accounts){
      Contact c = con.clone();
      c.AccountId = acc.Id;
      primaryContacts.add(c);
    }
    if(primaryContacts.size() > 0){
      insert primaryContacts;
    }
  }
```

```
}
AddPrimaryContactTest.apxc
@isTest
public class AddPrimaryContactTest {
  static testmethod void testQueueable(){
    List<Account> TestAccounts = new List<Account>();
    for(Integer i=0;i<50;i++){
      testAccounts.add(new Account(name = 'Account '+i,BillingState='CA'));
    }
    for(Integer j=0;j<50;j++){
      testAccounts.add(new Account(name = 'Account '+j,BillingState='NY'));
  }
  insert testAccounts;
  Contact testContact = new Contact(FirstName = 'John', LastName = 'Doe');
  insert testContact;
  AddPrimaryContact addit = new addPrimaryContact(testContact, 'CA');
  Test.startTest();
```

system.enqueueJob(addit);

```
Test.stopTest();
 System.assertEquals(50,[Select count() from Contact where accountId in (Select
Id from Account where BillingState='CA')]);
 }
SCHEDULE JOBS USING APEX SCHEDULER
ASSESSMENT
DailyLeadProcessor.apxc
public class DailyLeadProcessor implements Schedulable {
 Public void execute(SchedulableContext SC){
   List<Lead> LeadObj=[SELECT Id from Lead where LeadSource=null limit 200];
   for(Lead I:LeadObj){
     I.LeadSource='Dreamforce';
     update I;
   }
 }
}
DailyLeadProcessorTest.apxc
@isTest
```

# APEX INTEGRATION SERVICES MODULE: APEX REST CALLOUTS ASSESSMENT

#### AnimalLocator.apxc

```
public class AnimalLocator{
  public static String getAnimalNameById(Integer x){
    Http http = new Http();
    HttpRequest req = new HttpRequest();
    req.setEndpoint('https://th-apex-http-callout.herokuapp.com/animals/' + x);
```

```
req.setMethod('GET');
    Map<String, Object> animal= new Map<String, Object>();
    HttpResponse res = http.send(req);
      if (res.getStatusCode() == 200) {
    Map<String, Object> results = (Map<String,
Object>)JSON.deserializeUntyped(res.getBody());
   animal = (Map<String, Object>) results.get('animal');
    }
return (String)animal.get('name');
}
AnimalLocatorTest.apxc
@isTest
private class AnimalLocatorTest{
  @isTest static void AnimalLocatorMock1() {
    Test.setMock(HttpCalloutMock.class, new AnimalLocatorMock());
    string result = AnimalLocator.getAnimalNameById(3);
    String expectedResult = 'chicken';
    System.assertEquals(result,expectedResult);
  }
AnimalLocatorMock.apxc
@isTest
```

```
global class AnimalLocatorMock implements HttpCalloutMock {
    // Implement this interface method
    global HTTPResponse respond(HTTPRequest request) {
        // Create a fake response
        HttpResponse response = new HttpResponse();
        response.setHeader('Content-Type', 'application/json');
        response.setBody('{"animals": ["majestic badger", "fluffy bunny", "scary bear", "chicken", "mighty moose"]}');
        response.setStatusCode(200);
        return response;
    }
}
```

#### APEX SOAP CALLOUTS ASSESSMENT

#### ParkLocator.apxc

```
public class ParkLocator {
   public static string[] country(string theCountry) {
      ParkService.ParksImplPort parkSvc = new ParkService.ParksImplPort(); //
   remove space
      return parkSvc.byCountry(theCountry);
   }
}
```

#### ParkLocatorTest.apxc

@isTest

```
private class ParkLocatorTest {
  @isTest static void testCallout() {
    Test.setMock(WebServiceMock.class, new ParkServiceMock ());
    String country = 'United States';
    List<String> result = ParkLocator.country(country);
    List<String> parks = new List<String>{'Yellowstone', 'Mackinac National Park',
'Yosemite'};
    System.assertEquals(parks, result);
  }
}
ParkServiceMock.apxc
@isTest
global class ParkServiceMock implements WebServiceMock {
 global void doInvoke(
      Object stub,
      Object request,
      Map<String, Object> response,
      String endpoint,
      String soapAction,
      String requestName,
      String responseNS,
      String responseName,
      String responseType) {
    // start - specify the response you want to send
```

```
ParkService.byCountryResponse response_x = new
ParkService.byCountryResponse();
    response_x.return_x = new List<String>{'Yellowstone', 'Mackinac National
Park', 'Yosemite'};
    // end
    response.put('response_x', response_x);
}
```

#### **APEX WEB SERVICES ASSESSMENT**

#### AccountManagerTest.apxc

```
@isTest
private class AccountManagerTest {

   private static testMethod void getAccountTest1() {
      Id recordId = createTestRecord();
      // Set up a test request
      RestRequest request = new RestRequest();
      request.requestUri =
'https://na1.salesforce.com/services/apexrest/Accounts/'+
recordId +'/contacts';
    request.httpMethod = 'GET';
    RestContext.request = request;
    // Call the method to test
    Account thisAccount = AccountManager.getAccount();
```

```
// Verify results
    System.assert(thisAccount != null);
    System.assertEquals('Test record', thisAccount.Name);
  }
  // Helper method
    static Id createTestRecord() {
    // Create test record
    Account TestAcc = new Account(
     Name='Test record');
    insert TestAcc;
    Contact TestCon= new Contact(
    LastName='Test',
    AccountId = TestAcc.id);
    return TestAcc.Id
  }
AccountManager.apxc
@RestResource(urlMapping='/Accounts/*/contacts')
global class AccountManager {
  @HttpGet
```

#### MaintainenceRequestHelper.apxc

```
}
      }
    }
    if (!validIds.isEmpty()){
      List<Case> newCases = new List<Case>();
      Map<Id,Case> closedCasesM = new Map<Id,Case>([SELECT Id, Vehicle__c,
Equipment__c, Equipment__r.Maintenance_Cycle__c,(SELECT
Id,Equipment__c,Quantity__c FROM Equipment_Maintenance_Items__r)
                              FROM Case WHERE Id IN :validIds]);
      Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
      AggregateResult[] results = [SELECT Maintenance Request c,
MIN(Equipment__r.Maintenance_Cycle__c)cycle FROM
Equipment_Maintenance_Item__c WHERE Maintenance_Request__c IN: ValidIds
GROUP BY Maintenance_Request__c];
    for (AggregateResult ar : results){
      maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal)
ar.get('cycle'));
    }
      for(Case cc : closedCasesM.values()){
        Case nc = new Case (
          ParentId = cc.Id,
        Status = 'New',
          Subject = 'Routine Maintenance',
```

```
Type = 'Routine Maintenance',
          Vehicle__c = cc.Vehicle__c,
          Equipment__c =cc.Equipment__c,
          Origin = 'Web',
          Date_Reported__c = Date.Today()
        );
        If (maintenanceCycles.containskey(cc.Id)){
          nc.Date_Due__c = Date.today().addDays((Integer)
maintenanceCycles.get(cc.Id));
        }
        newCases.add(nc);
      }
     insert newCases;
     List<Equipment_Maintenance_Item__c> clonedWPs = new
List<Equipment_Maintenance_Item__c>();
     for (Case nc : newCases){
        for (Equipment_Maintenance_Item__c wp :
closedCasesM.get(nc.ParentId).Equipment_Maintenance_Items__r){
          Equipment_Maintenance_Item__c wpClone = wp.clone();
          wpClone.Maintenance Request c = nc.ld;
```

```
ClonedWPs.add(wpClone);
       }
     }
     insert ClonedWPs;
   }
 }
MaintenenceRequest.apxt
trigger MaintenanceRequest on Case (before update, after update) {
 if(Trigger.isUpdate && Trigger.isAfter){
   MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);
 }
SYNCHRONIZE SALESFORCE DATA WITH
EXTERNAL SYSTEM ASSESSMENT
WarehouseCalloutService.apxc
public with sharing class WarehouseCalloutService {
  private static final String WAREHOUSE_URL = 'https://th-superbadge-
apex.herokuapp.com/equipment';
 //@future(callout=true)
```

```
public static void runWarehouseEquipmentSync(){
    Http http = new Http();
    HttpRequest request = new HttpRequest();
    request.setEndpoint(WAREHOUSE_URL);
    request.setMethod('GET');
    HttpResponse response = http.send(request);
    List<Product2> warehouseEq = new List<Product2>();
    if (response.getStatusCode() == 200){
      List<Object> jsonResponse =
(List<Object>)JSON.deserializeUntyped(response.getBody());
      System.debug(response.getBody());
      for (Object eq : jsonResponse){
        Map<String,Object> mapJson = (Map<String,Object>)eq;
        Product2 myEq = new Product2();
        myEq.Replacement_Part__c = (Boolean) mapJson.get('replacement');
        myEq.Name = (String) mapJson.get('name');
        myEq.Maintenance Cycle c = (Integer)
mapJson.get('maintenanceperiod');
```

```
myEq.Lifespan_Months__c = (Integer) mapJson.get('lifespan');
        myEq.Cost c = (Decimal) mapJson.get('lifespan');
        myEq.Warehouse_SKU__c = (String) mapJson.get('sku');
        myEq.Current_Inventory__c = (Double) mapJson.get('quantity');
        warehouseEq.add(myEq);
      }
      if (warehouseEq.size() > 0){
        upsert warehouseEq;
        System.debug('Your equipment was synced with the warehouse one');
        System.debug(warehouseEq);
    }
  }
}
CTRI+E and run this method
```

System.enqueueJob(new WarehouseCalloutService());

# SCHEDULE SYNCHRONIZATION USING APEX CODE ASSESSMENT

#### WarehouseSyncSchedule.apxc

```
global class WarehouseSyncSchedule implements Schedulable {
    global void execute(SchedulableContext ctx) {
```

```
WarehouseCalloutService.runWarehouseEquipmentSync();
}
```

#### **TEST AUTOMATION LOGIC ASSESSMENT**

#### MaintenenceRequest.apxt

```
trigger MaintenanceRequest on Case (before update, after update) {
   if(Trigger.isUpdate && Trigger.isAfter){
      MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);
   }
}
```

#### MaintenanceRequestHelper.apxc

```
public with sharing class MaintenanceRequestHelper {
   public static void updateworkOrders(List<Case> updWorkOrders, Map<Id,Case> nonUpdCaseMap) {
      Set<Id> validIds = new Set<Id>();
```

```
For (Case c : updWorkOrders){
   if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
     if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
        validIds.add(c.Id);
   }
```

```
}
      }
    if (!validIds.isEmpty()){
      List<Case> newCases = new List<Case>();
      Map<Id,Case> closedCasesM = new Map<Id,Case>([SELECT Id, Vehicle__c,
Equipment__c, Equipment__r.Maintenance_Cycle__c,(SELECT
Id,Equipment__c,Quantity__c FROM Equipment_Maintenance_Items__r)
                             FROM Case WHERE Id IN :validIds]);
      Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
      AggregateResult[] results = [SELECT Maintenance_Request_ c,
MIN(Equipment__r.Maintenance_Cycle__c)cycle FROM
Equipment_Maintenance_Item__c WHERE Maintenance_Request__c IN :ValidIds
GROUP BY Maintenance_Request__c];
    for (AggregateResult ar : results){
      maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal)
ar.get('cycle'));
    }
      for(Case cc : closedCasesM.values()){
        Case nc = new Case (
          ParentId = cc.Id,
        Status = 'New',
```

```
Subject = 'Routine Maintenance',
          Type = 'Routine Maintenance',
          Vehicle__c = cc.Vehicle__c,
          Equipment__c =cc.Equipment__c,
          Origin = 'Web',
          Date_Reported__c = Date.Today()
        );
        If (maintenanceCycles.containskey(cc.Id)){
          nc.Date Due c = Date.today().addDays((Integer)
maintenanceCycles.get(cc.Id));
        }
        newCases.add(nc);
      }
     insert newCases;
     List<Equipment_Maintenance_Item__c> clonedWPs = new
List<Equipment_Maintenance_Item__c>();
     for (Case nc : newCases){
        for (Equipment_Maintenance_Item__c wp:
closedCasesM.get(nc.ParentId).Equipment_Maintenance_Items__r){
          Equipment Maintenance Item c wpClone = wp.clone();
```

```
wpClone.Maintenance_Request__c = nc.ld;
ClonedWPs.add(wpClone);

}
insert ClonedWPs;
}
}
```

#### MaintenanceRequestHelperTest.apxc

```
@istest

public with sharing class MaintenanceRequestHelperTest {

private static final string STATUS_NEW = 'New';

private static final string WORKING = 'Working';

private static final string CLOSED = 'Closed';

private static final string REPAIR = 'Repair';

private static final string REQUEST_ORIGIN = 'Web';

private static final string REQUEST_TYPE = 'Routine Maintenance';

private static final string REQUEST_SUBJECT = 'Testing subject';

PRIVATE STATIC Vehicle__c createVehicle(){
```

```
Vehicle__c Vehicle = new Vehicle__C(name = 'SuperTruck');
    return Vehicle;
  }
  PRIVATE STATIC Product2 createEq(){
    product2 equipment = new product2(name = 'SuperEquipment',
                     lifespan_months__C = 10,
                     maintenance_cycle__C = 10,
                     replacement_part__c = true);
    return equipment;
  }
  PRIVATE STATIC Case createMaintenanceRequest(id vehicleId, id equipmentId){
    case cs = new case(Type=REPAIR,
             Status=STATUS_NEW,
             Origin=REQUEST_ORIGIN,
             Subject=REQUEST_SUBJECT,
             Equipment__c=equipmentId,
             Vehicle c=vehicleId);
    return cs;
  }
  PRIVATE STATIC Equipment_Maintenance_Item__c createWorkPart(id
equipmentId,id requestId){
```

```
Equipment_Maintenance_Item__c wp = new
Equipment_Maintenance_Item__c(Equipment__c = equipmentId,
                                       Maintenance_Request__c = requestId);
    return wp;
  }
  @istest
  private static void testMaintenanceRequestPositive(){
    Vehicle__c vehicle = createVehicle();
    insert vehicle;
    id vehicleId = vehicle.Id;
    Product2 equipment = createEq();
    insert equipment;
    id equipmentId = equipment.Id;
    case somethingToUpdate =
createMaintenanceRequest(vehicleId,equipmentId);
    insert somethingToUpdate;
    Equipment_Maintenance_Item__c workP =
createWorkPart(equipmentId,somethingToUpdate.id);
    insert workP;
```

```
test.startTest();
    somethingToUpdate.status = CLOSED;
    update somethingToUpdate;
    test.stopTest();
    Case newReq = [Select id, subject, type, Equipment__c, Date_Reported__c,
Vehicle__c, Date_Due__c
           from case
           where status =: STATUS NEW];
    Equipment_Maintenance_Item__c workPart = [select id
                         from Equipment_Maintenance_Item__c
                         where Maintenance_Request__c =:newReq.Id];
    system.assert(workPart != null);
    system.assert(newReq.Subject != null);
    system.assertEquals(newReg.Type, REQUEST TYPE);
    SYSTEM.assertEquals(newReq.Equipment__c, equipmentId);
    SYSTEM.assertEquals(newReq.Vehicle__c, vehicleId);
    SYSTEM.assertEquals(newReq.Date_Reported__c, system.today());
  }
  @istest
  private static void testMaintenanceRequestNegative(){
```

```
Vehicle__C vehicle = createVehicle();
    insert vehicle;
    id vehicleId = vehicle.Id;
    product2 equipment = createEq();
    insert equipment;
    id equipmentId = equipment.Id;
    case emptyReq = createMaintenanceRequest(vehicleId,equipmentId);
    insert emptyReq;
    Equipment_Maintenance_Item__c workP = createWorkPart(equipmentId,
emptyReq.Id);
    insert workP;
    test.startTest();
    emptyReq.Status = WORKING;
    update emptyReq;
    test.stopTest();
    list<case> allRequest = [select id
                 from case];
    Equipment_Maintenance_Item__c workPart = [select id
```

```
where Maintenance_Request__c = :emptyReq.Id];
    system.assert(workPart != null);
    system.assert(allRequest.size() == 1);
  }
  @istest
  private static void testMaintenanceRequestBulk(){
    list<Vehicle__C> vehicleList = new list<Vehicle__C>();
    list<Product2> equipmentList = new list<Product2>();
    list<Equipment_Maintenance_Item__c> workPartList = new
list<Equipment_Maintenance_Item__c>();
    list<case> requestList = new list<case>();
    list<id> oldRequestIds = new list<id>();
    for(integer i = 0; i < 300; i++){
      vehicleList.add(createVehicle());
      equipmentList.add(createEq());
    }
    insert vehicleList;
    insert equipmentList;
    for(integer i = 0; i < 300; i++){
```

from Equipment\_Maintenance\_Item\_\_c

```
requestList.add(createMaintenanceRequest(vehicleList.get(i).id,
equipmentList.get(i).id));
    }
    insert requestList;
    for(integer i = 0; i < 300; i++){
      workPartList.add(createWorkPart(equipmentList.get(i).id,
requestList.get(i).id));
    }
    insert workPartList;
    test.startTest();
    for(case req : requestList){
      req.Status = CLOSED;
      oldRequestIds.add(req.Id);
    }
    update requestList;
    test.stopTest();
    list<case> allRequests = [select id
                  from case
                  where status =: STATUS_NEW];
    list<Equipment_Maintenance_Item__c> workParts = [select id
```

```
from Equipment_Maintenance_Item__c
                           where Maintenance_Request__c in:
oldRequestIds];
   system.assert(allRequests.size() == 300);
 }
}
TEST CALLOUT LOGIC ASSESSMENT
WarehouseCalloutService.apxc
public with sharing class WarehouseCalloutService {
  private static final String WAREHOUSE_URL = 'https://th-superbadge-
apex.herokuapp.com/equipment';
 //@future(callout=true)
  public static void runWarehouseEquipmentSync(){
    Http http = new Http();
    HttpRequest request = new HttpRequest();
    request.setEndpoint(WAREHOUSE_URL);
    request.setMethod('GET');
    HttpResponse response = http.send(request);
```

```
List<Product2> warehouseEq = new List<Product2>();
    if (response.getStatusCode() == 200){
      List<Object> isonResponse =
(List<Object>)JSON.deserializeUntyped(response.getBody());
      System.debug(response.getBody());
      for (Object eq: jsonResponse){
        Map<String,Object> mapJson = (Map<String,Object>)eq;
        Product2 myEq = new Product2();
        myEq.Replacement_Part__c = (Boolean) mapJson.get('replacement');
        myEq.Name = (String) mapJson.get('name');
        myEq.Maintenance_Cycle__c = (Integer)
mapJson.get('maintenanceperiod');
        myEq.Lifespan_Months__c = (Integer) mapJson.get('lifespan');
        myEq.Cost__c = (Decimal) mapJson.get('lifespan');
        myEq.Warehouse SKU c = (String) mapJson.get('sku');
        myEq.Current_Inventory__c = (Double) mapJson.get('quantity');
        warehouseEq.add(myEq);
      }
      if (warehouseEq.size() > 0){
        upsert warehouseEq;
```

```
System.debug('Your equipment was synced with the warehouse one');
        System.debug(warehouseEq);
      }
    }
  }
}
WarehouseCalloutServiceTest.apxc
@isTest
private class WarehouseCalloutServiceTest {
  @isTest
  static void testWareHouseCallout(){
    Test.startTest();
   // implement mock callout test here
   Test.setMock(HTTPCalloutMock.class, new WarehouseCalloutServiceMock());
   WarehouseCalloutService.runWarehouseEquipmentSync();
    Test.stopTest();
   System.assertEquals(1, [SELECT count() FROM Product2]);
  }
WarehouseCalloutServiceMock.apxc
```

@isTest

```
global class WarehouseCalloutServiceMock implements HttpCalloutMock {
  // implement http mock callout
  global static HttpResponse respond(HttpReguest reguest){
    System.assertEquals('https://th-superbadge-
apex.herokuapp.com/equipment', request.getEndpoint());
    System.assertEquals('GET', request.getMethod());
    // Create a fake response
    HttpResponse response = new HttpResponse();
    response.setHeader('Content-Type', 'application/json');
response.setBody('[{" id":"55d66226726b611100aaf741","replacement":false,"q
uantity":5,"name":"Generator 1000
kW","maintenanceperiod":365,"lifespan":120,"cost":5000,"sku":"100003"}]');
    response.setStatusCode(200);
    return response;
  }
}
```

#### TEST SCHEDULING LOGIC ASSESSMENT

#### WarehouseSyncSchedule.apxc

```
global class WarehouseSyncSchedule implements Schedulable {
   global void execute(SchedulableContext ctx) {
```

```
WarehouseCalloutService.runWarehouseEquipmentSync();
  }
}
WarehouseSyncScheduleTest.apxc
@isTest
public class WarehouseSyncScheduleTest {
  @isTest static void WarehousescheduleTest(){
    String scheduleTime = '00 00 01 * * ?';
    Test.startTest();
    Test.setMock(HttpCalloutMock.class, new WarehouseCalloutServiceMock());
    String jobID=System.schedule('Warehouse Time To Schedule to Test',
scheduleTime, new WarehouseSyncSchedule());
    Test.stopTest();
    //Contains schedule information for a scheduled job. CronTrigger is similar to
a cron job on UNIX systems.
    // This object is available in API version 17.0 and later.
    CronTrigger a=[SELECT Id FROM CronTrigger where NextFireTime > today];
    System.assertEquals(jobID, a.Id,'Schedule ');
  }
}
```