

APEX TRIGGERS

GET STARTED WITH APEX TRIGGERS:

1.AccountAddressTrigger.apxt:

```
trigger AccountAddressTrigger on Account (before insert,before update) {
    for(Account a:Trigger.New) {
        if(a.Match_Billing_Address__c==True)
        {
            a.ShippingPostalCode=a.BillingPostalCode;
        }
    }
}
```

BULK APEX TRIGGERS:

1.ClosedOpportunityTrigger.apxt:

```
trigger ClosedOpportunityTrigger on Opportunity (after insert,after update) {
    List<Task> taskList=new List<Task>();
    for(Opportunity opp:Trigger.New){
        if(opp.StageName=='Closed Won'){
            taskList.add(new Task(Subject='Follow Up Test Task',
                                WhatId=opp.Id));
        }
    }
    if(taskList.size()>0){
        insert taskList;
    }
}
```

APEX TESTING

GET STARTED WITH APEX UNIT TEST:

1.VerifyDate.apxc:

```
public class VerifyDate {
    public static Date CheckDates(Date date1, Date date2) {
        //if date2 is within the next 30 days of date1, use date2. Otherwise use
the end of the month
        if(DateWithin30Days(date1,date2)) {
            return date2;
        } else {
            return SetEndOfMonthDate(date1);
        }
    }
    //method to check if date2 is within the next 30 days of date1
    private static Boolean DateWithin30Days(Date date1, Date date2) {
        //check for date2 being in the past
        if( date2 < date1) { return false; }
        //check that date2 is within (>=) 30 days of date1
    }
}
```

```

        Date date30Days = date1.addDays(30); //create a date 30 days away from
date1
        if( date2 >= date30Days ) { return false; }
        else { return true; }
    }
    //method to return the end of the month of a given date
    private static Date SetEndOfMonthDate(Date date1) {
        Integer totalDays = Date.daysInMonth(date1.year(), date1.month());
        Date lastDay = Date.newInstance(date1.year(), date1.month(),
totalDays);
        return lastDay;
    }
}

```

2.TestVerifyDate.apxc:

```

@isTest
private class TestVerifyDate {
    static testMethod void testMethod1()
    {
        Date d=VerifyDate.CheckDates(System.today(),System.today()+1);
        Date d1=VerifyDate.CheckDates(System.today(),System.today()+60);
    }
}

```

TEST APEX TRIGGERS:

1.RestrictContactByName.apxt:

```

trigger RestrictContactByName on Contact (before insert, before update) {
    //check contacts prior to insert or update for invalid data
    For (Contact c : Trigger.New) {
        if(c.LastName == 'INVALIDNAME') { //invalidname is invalid
            c.AddError('The Last Name "'+c.LastName+'" is not allowed for
DML');
        }
    }
}

```

CREATE TEST DATA FOR APEX TESTS:

1.RandomContactFactory.apxc:

```

public class RandomContactFactory {

    public static List<Contact> generateRandomContacts(Integer numcnt,string
lastname){
        List<Contact> contacts =new List<Contact>();
        for(Integer i=0;i<numcnt;i++)
        {
            Contact cnt=new Contact(FirstName='Test'+i,LastName=lastname);
            contacts.add(cnt);
        }
    }
}

```

```

    }
    return contacts;
}
}

```

ASYNCHRONOUS APEX

USE FUTURE METHODS:

1.AccountProcessor.apxc:

```

public class AccountProcessor {
    @future
    public static void countContacts(List<Id> accountIds){
        List<Account> accounts = [Select Id, Name from Account Where Id IN:
accountIds];
        List<Account> updatedAccounts = new List<Account>();
        for(Account account: accounts){
            account.Number_of_Contacts__c = [Select count() from Contact Where
AccountId =: account.Id];
            System.debug('No Of Contacts = ' + account.Number_of_Contacts__c);
            updatedAccounts.add(account);
        }
        update updatedAccounts;
    }
}

```

2.AccountProcessorTest.apxc:

```

@isTest
public class AccountProcessorTest {
    @isTest
    public static void testNoOfContacts(){
        Account a = new Account();
        a.Name = 'Test Account';
        Insert a;

        Contact c= new Contact();
        c.FirstName= 'Bob';
        c.LastName='Willie';
        c.AccountId = a.Id;

        Contact c2= new Contact();
        c2.FirstName = 'Tom';
        c2.LastName= 'Cruise';
        c2.AccountId = a.Id;

        List<Id> acctIds = new List<Id>();
        acctIds.add(a.Id);

        Test.startTest();
    }
}

```

```

        AccountProcessor.countContacts (acctIds);
        Test.stopTest();
    }
}

```

USE BATCH APEX:

1.LeadProcessor.apxc:

```

public class LeadProcessor implements Database.Batchable<sObject>
{
    public Database.QueryLocator start(Database.BatchableContext bh)
    {
        return Database.getQueryLocator([Select LeadSource From Lead ]);
    }
    public void execute(Database.BatchableContext bh,List<Lead> leads)
    {
        for(Lead Lead:leads)
        {
            lead.LeadSource='Dreamforce';
        }
        update leads;
    }
    public void finish(Database.BatchableContext bh)
    {
    }
}

```

2.LeadProcessorTest.apxc:

```

@isTest
public class LeadProcessorTest
{
    @testSetup

    static void setup()
    {
        List<Lead> leads = new List<Lead>();

        for (Integer i=0;i<200;i++)
        {
            leads.add(new Lead(LastName='Lead '+i,Company='Lead',Status='Open-Not
Connected'));
        }
        insert leads;
    }
    static testmethod void test()
    {
        Test.startTest();
        LeadProcessor bh = new LeadProcessor();
    }
}

```

```

        Id batchId=Database.executeBatch(bh,200);
        Test.stopTest();

        System.assertEquals(200, [select count() from lead where
LeadSource='Dreamforce']);
    }
}

```

CONTROL PROCESSES WITH QUEUEABLE APEX:

1.AddPrimaryContact.apxc:

```

public class AddPrimaryContact implements Queueable
{
    private Contact c;
    private String state;
    public AddPrimaryContact(Contact c, String state)
    {
        this.c = c;
        this.state = state;
    }
    public void execute(QueueableContext context)
    {
        List<Account> ListAccount = [SELECT ID, Name ,(Select id,FirstName,LastName
from contacts ) FROM ACCOUNT WHERE BillingState = :state LIMIT 200];
        List<Contact> lstContact = new List<Contact>();
        for (Account acc:ListAccount)
        {
            Contact cont = c.clone(false,false,false,false);
            cont.AccountId = acc.id;
            lstContact.add( cont );
        }
        if(lstContact.size() >0 )
        {
            insert lstContact;
        }
    }
}

```

2.AddPrimaryContactTest.apxc:

```

@isTest
public class AddPrimaryContactTest
{
    @isTest static void TestList()
    {
        List<Account> Teste = new List <Account>();
        for(Integer i=0;i<50;i++)
        {
            Teste.add(new Account(BillingState = 'CA', name = 'Test'+i));
        }
    }
}

```

```

    for(Integer j=0;j<50;j++)
    {
        Teste.add(new Account(BillingState = 'NY', name = 'Test'+j));
    }
    insert Teste;

    Contact co = new Contact();
    co.FirstName='demo';
    co.LastName = 'demo';
    insert co;
    String state = 'CA';

    AddPrimaryContact apc = new AddPrimaryContact(co, state);
    Test.startTest();
    System.enqueueJob(apc);
    Test.stopTest();
}
}

```

SCHEDULE JOBS USING APEX SCHEDULER:

1.DailyLeadProcessor.apxc:

```

public class DailyLeadProcessor implements Schedulable {
    Public void execute(SchedulableContext SC){
        List<Lead> LeadObj=[SELECT Id from Lead where LeadSource=null limit 200];
        for(Lead l:LeadObj){
            l.LeadSource='Dreamforce';
            update l;
        }
    }
}

```

2.DailyLeadProcessorTest.apxc:

```

@isTest
private class DailyLeadProcessorTest {
    static testMethod void testDailyLeadProcessor() {
        String CRON_EXP = '0 0 1 * * ?';
        List<Lead> lList = new List<Lead>();
        for (Integer i = 0; i < 200; i++) {
            lList.add(new Lead(LastName='Dreamforce'+i, Company='Test1
Inc.', Status='Open - Not Contacted'));
        }
        insert lList;

        Test.startTest();
        String jobId = System.schedule('DailyLeadProcessor', CRON_EXP, new
DailyLeadProcessor());
    }
}

```

APEX INTEGRATION SERVICES

APEX REST CALLOUTS:

1. AnimalLocator.apxc:

```
public class AnimalLocator{
    public static String getAnimalNameById(Integer x){
        Http http = new Http();
        HttpRequest req = new HttpRequest();
        req.setEndpoint('https://th-apex-http-callout.herokuapp.com/animals/' + x);
        req.setMethod('GET');
        Map<String, Object> animal= new Map<String, Object>();
        HttpResponse res = http.send(req);
        if (res.getStatusCode() == 200) {
            Map<String, Object> results = (Map<String,
Object>)JSON.deserializeUntyped(res.getBody());
            animal = (Map<String, Object>) results.get('animal');
        }
        return (String)animal.get('name');
    }
}
```

2. AnimalLocatorMock.apxc:

```
@isTest
global class AnimalLocatorMock implements HttpCalloutMock {
    // Implement this interface method
    global HTTPResponse respond(HTTPRequest request) {
        // Create a fake response
        HttpResponse response = new HttpResponse();
        response.setHeader('Content-Type', 'application/json');
        response.setBody("{\"animals\": [\"majestic badger\", \"fluffy bunny\", \"scary bear\",
\"chicken\", \"mighty moose\"]}");
        response.getStatusCode(200);
        return response;
    }
}
```

3. AnimalLocatorTest.apxc:

```
@isTest
private class AnimalLocatorTest{
    @isTest static void AnimalLocatorMock1() {
        Test.setMock(HttpCalloutMock.class, new AnimalLocatorMock());
        string result = AnimalLocator.getAnimalNameById(3);
        String expectedResult = 'chicken';
        System.assertEquals(result,expectedResult );
    }
}
```

APEX SOAP CALLOUTS:

1.ParkService.apxc:

//Generated by wsdl2apex

```
public class ParkService {
    public class byCountryResponse {
        public String[] return_x;
        private String[] return_x_type_info = new
String[]{'return','http://parks.services/',null,'0','-1','false'};
        private String[] apex_schema_type_info = new
String[]{'http://parks.services/','false','false'};
        private String[] field_order_type_info = new String[]{'return_x'};
    }
    public class byCountry {
        public String arg0;
        private String[] arg0_type_info = new
String[]{'arg0','http://parks.services/',null,'0','1','false'};
        private String[] apex_schema_type_info = new
String[]{'http://parks.services/','false','false'};
        private String[] field_order_type_info = new String[]{'arg0'};
    }
    public class ParksImplPort {
        public String endpoint_x = 'https://th-apex-soap-
service.herokuapp.com/service/parks';
        public Map<String,String> inputHttpHeaders_x;
        public Map<String,String> outputHttpHeaders_x;
        public String clientCertName_x;
        public String clientCert_x;
        public String clientCertPasswd_x;
        public Integer timeout_x;
        private String[] ns_map_type_info = new String[]{'http://parks.services/',
'ParkService'};
        public String[] byCountry(String arg0) {
            ParkService.byCountry request_x = new ParkService.byCountry();
            request_x.arg0 = arg0;
            ParkService.byCountryResponse response_x;
            Map<String, ParkService.byCountryResponse> response_map_x = new
Map<String, ParkService.byCountryResponse>();
            response_map_x.put('response_x', response_x);
            WebServiceCallout.invoke(
                this,
                request_x,
                response_map_x,
                new String[]{endpoint_x,
                ",
                'http://parks.services/',
                'byCountry',
```



```

        'http://parks.services/',
        'byCountryResponse',
        'ParkService.byCountryResponse'}
    );
    response_x = response_map_x.get('response_x');
    return response_x.return_x;
}
}
}

```

2.ParkServiceMock.apxc:

```

@isTest
global class ParkServiceMock implements WebServiceMock {
    global void doInvoke(
        Object stub,
        Object request,
        Map<String, Object> response,
        String endpoint,
        String soapAction,
        String requestName,
        String responseNS,
        String responseName,
        String responseType) {
        // start - specify the response you want to send
        ParkService.byCountryResponse response_x = new
        ParkService.byCountryResponse();
        response_x.return_x = new List<String>{'Yellowstone', 'Mackinac National Park',
        'Yosemite'};
        // end
        response.put('response_x', response_x);
    }
}

```

3.ParkLocator.apxc:

```

public class ParkLocator {
    public static string[] country(string theCountry) {
        ParkService.ParksImplPort parkSvc = new ParkService.ParksImplPort(); //
remove space
        return parkSvc.byCountry(theCountry);
    }
}

```

4.ParkLocatorTest.apxc:

```

@isTest
private class ParkLocatorTest {
    @isTest static void testCallout() {
        Test.setMock(WebServiceMock.class, new ParkServiceMock ());
        String country = 'United States';
        List<String> result = ParkLocator.country(country);
    }
}

```

```

        List<String> parks = new List<String>{'Yellowstone', 'Mackinac National Park',
'Yosemite'};
        System.assertEquals(parks, result);
    }
}

```

APEX WEB SERVICES:

1.AccountManager.apxc:

```

@RestResource(urlMapping='/Accounts/*/contacts')
global class AccountManager {
    @HttpGet
    global static Account getAccount() {
        RestRequest req = RestContext.request;
        String accId = req.requestURI.substringBetween('Accounts/', '/contacts');
        Account acc = [SELECT Id, Name, (SELECT Id, Name FROM Contacts)
                        FROM Account WHERE Id = :accId];
        return acc;
    }
}

```

2.AccountManagerTest.apxc:

```

@isTest
private class AccountManagerTest {

    private static testMethod void getAccountTest1() {
        Id recordId = createTestRecord();
        // Set up a test request
        RestRequest request = new RestRequest();
        request.requestUri =
'https://na1.salesforce.com/services/apexrest/Accounts/'+ recordId +'/contacts' ;
        request.httpMethod = 'GET';
        RestContext.request = request;
        // Call the method to test
        Account thisAccount = AccountManager.getAccount();
        // Verify results
        System.assert(thisAccount != null);
        System.assertEquals('Test record', thisAccount.Name);
    }

    // Helper method
    static Id createTestRecord() {
        // Create test record
        Account TestAcc = new Account(
            Name='Test record');
        insert TestAcc;
        Contact TestCon= new Contact(
            LastName='Test',
            AccountId = TestAcc.id);
    }
}

```

```

    return TestAcc.Id;
}
}

```

APEX SPECIALIST SUPERBADGE

AUTOMATE RECORD CREATION:

1)MaintenanceRequest.apxt:

```

trigger MaintenanceRequest on Case (before update, after update) {
    if(Trigger.isUpdate && Trigger.isAfter){
        MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);
    }
}

```

2)MaintenanceRequestHelper.apxc:

```

public with sharing class MaintenanceRequestHelper {
    public static void updateworkOrders(List<Case> updWorkOrders, Map<Id,Case>
nonUpdCaseMap) {
        Set<Id> validIds = new Set<Id>();

```

```

        For (Case c : updWorkOrders){
            if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
                if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
                    validIds.add(c.Id);

```

```

                }
            }
        }

```

```

        if (!validIds.isEmpty()){
            List<Case> newCases = new List<Case>();
            Map<Id,Case> closedCasesM = new Map<Id,Case>([SELECT Id, Vehicle__c,
Equipment__c, Equipment__r.Maintenance_Cycle__c,(SELECT
Id,Equipment__c,Quantity__c FROM Equipment_Maintenance_Items__r)
FROM Case WHERE Id IN :validIds]);
            Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
            AggregateResult[] results = [SELECT Maintenance_Request__c,
MIN(Equipment__r.Maintenance_Cycle__c)cycle FROM
Equipment_Maintenance_Item__c WHERE Maintenance_Request__c IN :ValidIds
GROUP BY Maintenance_Request__c];

```

```

            for (AggregateResult ar : results){
                maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal)
ar.get('cycle'));
            }

```

```

            for(Case cc : closedCasesM.values()){

```

```

        Case nc = new Case (
            ParentId = cc.Id,
            Status = 'New',
            Subject = 'Routine Maintenance',
            Type = 'Routine Maintenance',
            Vehicle__c = cc.Vehicle__c,
            Equipment__c = cc.Equipment__c,
            Origin = 'Web',
            Date_Reported__c = Date.Today()

        );

        If (maintenanceCycles.containsKey(cc.Id)){
            nc.Date_Due__c = Date.today().addDays((Integer)
maintenanceCycles.get(cc.Id));
        }

        newCases.add(nc);
    }

    insert newCases;

    List<Equipment_Maintenance_Item__c> clonedWPs = new
List<Equipment_Maintenance_Item__c>();
    for (Case nc : newCases){
        for (Equipment_Maintenance_Item__c wp :
closedCasesM.get(nc.ParentId).Equipment_Maintenance_Items__r){
            Equipment_Maintenance_Item__c wpClone = wp.clone();
            wpClone.Maintenance_Request__c = nc.Id;
            ClonedWPs.add(wpClone);
        }
    }
    insert ClonedWPs;
}
}
}
}

```

SYNCHRONIZATION SALESFORCE DATA WITH AN EXTERNAL SYSTEM:

1)WarehouseCalloutService.apxc:

```
public with sharing class WarehouseCalloutService {
```

```
    private static final String WAREHOUSE_URL = 'https://th-superbadge-
apex.herokuapp.com/equipment';
```

```
    //@future(callout=true)
```

```
    public static void runWarehouseEquipmentSync(){
```

```

Http http = new Http();
HttpRequest request = new HttpRequest();

request.setEndpoint(WAREHOUSE_URL);
request.setMethod('GET');
HttpResponse response = http.send(request);

List<Product2> warehouseEq = new List<Product2>();

if (response.getStatusCode() == 200){
    List<Object> jsonResponse =
(List<Object>)JSON.deserializeUntyped(response.getBody());
    System.debug(response.getBody());

    for (Object eq : jsonResponse){
        Map<String,Object> mapJson = (Map<String,Object>)eq;
        Product2 myEq = new Product2();
        myEq.Replacement_Part__c = (Boolean) mapJson.get('replacement');
        myEq.Name = (String) mapJson.get('name');
        myEq.Maintenance_Cycle__c = (Integer) mapJson.get('maintenanceperiod');
        myEq.Lifespan_Months__c = (Integer) mapJson.get('lifespan');
        myEq.Cost__c = (Decimal) mapJson.get('lifespan');
        myEq.Warehouse_SKU__c = (String) mapJson.get('sku');
        myEq.Current_Inventory__c = (Double) mapJson.get('quantity');
        warehouseEq.add(myEq);
    }

    if (warehouseEq.size() > 0){
        upsert warehouseEq;
        System.debug('Your equipment was synced with the warehouse one');
        System.debug(warehouseEq);
    }
}
}
}

```

After saving the code open execute anonymous window (CTRL+E) and run this method , System.enqueueJob(new WarehouseCalloutService());

SCHEDULE SYNCHRONIZATION USING APEX CODE:

1)WarehouseSyncSchedule.apxc:

```

global class WarehouseSyncSchedule implements Schedulable {
    global void execute(SchedulableContext ctx) {
        WarehouseCalloutService.runWarehouseEquipmentSync();
    }
}

```

TEST AUTOMATION LOGIC:

1)MaintenanceRequestHelperTest.apxc:

@istest

public with sharing class MaintenanceRequestHelperTest {

```
private static final string STATUS_NEW = 'New';
private static final string WORKING = 'Working';
private static final string CLOSED = 'Closed';
private static final string REPAIR = 'Repair';
private static final string REQUEST_ORIGIN = 'Web';
private static final string REQUEST_TYPE = 'Routine Maintenance';
private static final string REQUEST_SUBJECT = 'Testing subject';
```

```
PRIVATE STATIC Vehicle__c createVehicle(){
    Vehicle__c Vehicle = new Vehicle__C(name = 'SuperTruck');
    return Vehicle;
}
```

```
PRIVATE STATIC Product2 createEq(){
    product2 equipment = new product2(name = 'SuperEquipment',
        lifespan_months__C = 10,
        maintenance_cycle__C = 10,
        replacement_part__c = true);
    return equipment;
}
```

```
PRIVATE STATIC Case createMaintenanceRequest(id vehicleId, id equipmentId){
    case cs = new case(Type=REPAIR,
        Status=STATUS_NEW,
        Origin=REQUEST_ORIGIN,
        Subject=REQUEST_SUBJECT,
        Equipment__c=equipmentId,
        Vehicle__c=vehicleId);
    return cs;
}
```

```
PRIVATE STATIC Equipment_Maintenance_Item__c createWorkPart(id
equipmentId,id requestId){
    Equipment_Maintenance_Item__c wp = new
Equipment_Maintenance_Item__c(Equipment__c = equipmentId,
        Maintenance_Request__c = requestId);
    return wp;
}
```

@istest

```
private static void testMaintenanceRequestPositive(){
    Vehicle__c vehicle = createVehicle();
    insert vehicle;
```

```

id vehicleId = vehicle.Id;

Product2 equipment = createEq();
insert equipment;
id equipmentId = equipment.Id;

case somethingToUpdate = createMaintenanceRequest(vehicleId,equipmentId);
insert somethingToUpdate;

Equipment_Maintenance_Item__c workP =
createWorkPart(equipmentId,somethingToUpdate.id);
insert workP;

test.startTest();
somethingToUpdate.status = CLOSED;
update somethingToUpdate;
test.stopTest();

Case newReq = [Select id, subject, type, Equipment__c, Date_Reported__c,
Vehicle__c, Date_Due__c
               from case
               where status =:STATUS_NEW];

Equipment_Maintenance_Item__c workPart = [select id
                                           from Equipment_Maintenance_Item__c
                                           where Maintenance_Request__c =:newReq.Id];

system.assert(workPart != null);
system.assert(newReq.Subject != null);
system.assertEquals(newReq.Type, REQUEST_TYPE);
SYSTEM.assertEquals(newReq.Equipment__c, equipmentId);
SYSTEM.assertEquals(newReq.Vehicle__c, vehicleId);
SYSTEM.assertEquals(newReq.Date_Reported__c, system.today());
}

@istest
private static void testMaintenanceRequestNegative(){
    Vehicle__C vehicle = createVehicle();
    insert vehicle;
    id vehicleId = vehicle.Id;

    product2 equipment = createEq();
    insert equipment;
    id equipmentId = equipment.Id;

    case emptyReq = createMaintenanceRequest(vehicleId,equipmentId);
    insert emptyReq;

```

```
Equipment_Maintenance_Item__c workP = createWorkPart(equipmentId,  
emptyReq.Id);  
insert workP;
```

```
test.startTest();  
emptyReq.Status = WORKING;  
update emptyReq;  
test.stopTest();
```

```
list<case> allRequest = [select id  
                        from case];
```

```
Equipment_Maintenance_Item__c workPart = [select id  
                                           from Equipment_Maintenance_Item__c  
                                           where Maintenance_Request__c = :emptyReq.Id];
```

```
system.assert(workPart != null);  
system.assert(allRequest.size() == 1);  
}
```

```
@istest  
private static void testMaintenanceRequestBulk(){  
    list<Vehicle__C> vehicleList = new list<Vehicle__C>();  
    list<Product2> equipmentList = new list<Product2>();  
    list<Equipment_Maintenance_Item__c> workPartList = new  
list<Equipment_Maintenance_Item__c>();  
    list<case> requestList = new list<case>();  
    list<id> oldRequestIds = new list<id>();  
  
    for(integer i = 0; i < 300; i++){  
        vehicleList.add(createVehicle());  
        equipmentList.add(createEq());  
    }  
    insert vehicleList;  
    insert equipmentList;  
  
    for(integer i = 0; i < 300; i++){  
        requestList.add(createMaintenanceRequest(vehicleList.get(i).id,  
equipmentList.get(i).id));  
    }  
    insert requestList;  
  
    for(integer i = 0; i < 300; i++){  
        workPartList.add(createWorkPart(equipmentList.get(i).id,  
requestList.get(i).id));  
    }  
    insert workPartList;
```



```

test.startTest();
for(case req : requestList){
    req.Status = CLOSED;
    oldRequestIds.add(req.Id);
}
update requestList;
test.stopTest();

list<case> allRequests = [select id
                        from case
                        where status =: STATUS_NEW];

list<Equipment_Maintenance_Item__c> workParts = [select id
                                                from Equipment_Maintenance_Item__c
                                                where Maintenance_Request__c in: oldRequestIds];

system.assert(allRequests.size() == 300);
}
}

```

2)MaintenanceRequestHelper.apxc:

```

public with sharing class MaintenanceRequestHelper {
    public static void updateworkOrders(List<Case> updWorkOrders, Map<Id,Case>
nonUpdCaseMap) {
        Set<Id> validIds = new Set<Id>();

```

```

        For (Case c : updWorkOrders){
            if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
                if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
                    validIds.add(c.Id);
                }
            }
        }
    }
}

```

```

        if (!validIds.isEmpty()){
            List<Case> newCases = new List<Case>();
            Map<Id,Case> closedCasesM = new Map<Id,Case>([SELECT Id, Vehicle__c,
Equipment__c, Equipment__r.Maintenance_Cycle__c,(SELECT
Id,Equipment__c,Quantity__c FROM Equipment_Maintenance_Items__r)
FROM Case WHERE Id IN :validIds]);
            Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
            AggregateResult[] results = [SELECT Maintenance_Request__c,
MIN(Equipment__r.Maintenance_Cycle__c)cycle FROM
Equipment_Maintenance_Item__c WHERE Maintenance_Request__c IN :ValidIds
GROUP BY Maintenance_Request__c];

```

```

        for (AggregateResult ar : results){
            maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal)
ar.get('cycle'));
        }

        for(Case cc : closedCasesM.values()){
            Case nc = new Case (
                ParentId = cc.Id,
                Status = 'New',
                Subject = 'Routine Maintenance',
                Type = 'Routine Maintenance',
                Vehicle__c = cc.Vehicle__c,
                Equipment__c =cc.Equipment__c,
                Origin = 'Web',
                Date_Reported__c = Date.Today()

            );

            If (maintenanceCycles.containsKey(cc.Id)){
                nc.Date_Due__c = Date.today().addDays((Integer)
maintenanceCycles.get(cc.Id));
            }

            newCases.add(nc);
        }

        insert newCases;

        List<Equipment_Maintenance_Item__c> clonedWPs = new
List<Equipment_Maintenance_Item__c>();
        for (Case nc : newCases){
            for (Equipment_Maintenance_Item__c wp :
closedCasesM.get(nc.ParentId).Equipment_Maintenance_Items__r){
                Equipment_Maintenance_Item__c wpClone = wp.clone();
                wpClone.Maintenance_Request__c = nc.Id;
                ClonedWPs.add(wpClone);
            }
        }
        insert ClonedWPs;
    }
}

```

3)MaintenanceRequest.apxt:

```

trigger MaintenanceRequest on Case (before update, after update) {
    if(Trigger.isUpdate && Trigger.isAfter){

```

```

        MaintenanceRequestHelper.updateWorkOrders(Triple.New, Triple.OldMap);
    }
}

```

TEST CALLOUT LOGIC:

1) WarehouseCalloutService.apxc:

```

public with sharing class WarehouseCalloutService {

    private static final String WAREHOUSE_URL = 'https://th-superbadge-
apex.herokuapp.com/equipment';

    // @future(callout=true)
    public static void runWarehouseEquipmentSync(){

        Http http = new Http();
        HttpRequest request = new HttpRequest();

        request.setEndpoint(WAREHOUSE_URL);
        request.setMethod('GET');
        HttpResponse response = http.send(request);

        List<Product2> warehouseEq = new List<Product2>();

        if (response.getStatusCode() == 200){
            List<Object> jsonResponse =
(List<Object>)JSON.deserializeUntyped(response.getBody());
            System.debug(response.getBody());

            for (Object eq : jsonResponse){
                Map<String, Object> mapJson = (Map<String, Object>)eq;
                Product2 myEq = new Product2();
                myEq.Replacement_Part__c = (Boolean) mapJson.get('replacement');
                myEq.Name = (String) mapJson.get('name');
                myEq.Maintenance_Cycle__c = (Integer) mapJson.get('maintenanceperiod');
                myEq.Lifespan_Months__c = (Integer) mapJson.get('lifespan');
                myEq.Cost__c = (Decimal) mapJson.get('lifespan');
                myEq.Warehouse_SKU__c = (String) mapJson.get('sku');
                myEq.Current_Inventory__c = (Double) mapJson.get('quantity');
                warehouseEq.add(myEq);
            }

            if (warehouseEq.size() > 0){
                upsert warehouseEq;
                System.debug('Your equipment was synced with the warehouse one');
                System.debug(warehouseEq);
            }
        }
    }
}

```

```

    }
  }
}

```

2)WarehouseCalloutServiceTest.apxc:

@isTest

```

private class WarehouseCalloutServiceTest {
    @isTest
    static void testWareHouseCallout(){
        Test.startTest();
        // implement mock callout test here
        Test.setMock(HTTPCalloutMock.class, new WarehouseCalloutServiceMock());
        WarehouseCalloutService.runWarehouseEquipmentSync();
        Test.stopTest();
        System.assertEquals(1, [SELECT count() FROM Product2]);
    }
}

```

3)WarehouseCalloutServiceMock.apxc:

@isTest

```

global class WarehouseCalloutServiceMock implements HttpCalloutMock {
    // implement http mock callout
    global static HttpResponse respond(HttpRequest request){

        System.assertEquals('https://th-superbadge-apex.herokuapp.com/equipment',
request.getEndpoint());
        System.assertEquals('GET', request.getMethod());

        // Create a fake response
        HttpResponse response = new HttpResponse();
        response.setHeader('Content-Type', 'application/json');
        response.setBody('{"_id":"55d66226726b611100aaf741","replacement":false,"qu
antity":5,"name":"Generator 1000
kW","maintenanceperiod":365,"lifespan":120,"cost":5000,"sku":"100003"}');
        response.setStatusCode(200);
        return response;
    }
}

```

TEST SCHEDULING LOGIC:

1)WarehouseSyncSchedule.apxc:

```

global class WarehouseSyncSchedule implements Schedulable {
    global void execute(SchedulableContext ctx) {
        WarehouseCalloutService.runWarehouseEquipmentSync();
    }
}

```

2)WarehouseSyncScheduleTest.apxc:

```

@isTest
public class WarehouseSyncScheduleTest {

    @isTest static void WarehousescheduleTest(){
        String scheduleTime = '00 00 01 * * ?';
        Test.startTest();
        Test.setMock(HttpCalloutMock.class, new WarehouseCalloutServiceMock());
        String jobId=System.schedule('Warehouse Time To Schedule to Test',
scheduleTime, new WarehouseSyncSchedule());
        Test.stopTest();
        //Contains schedule information for a scheduled job. CronTrigger is similar to a
cron job on UNIX systems.
        // This object is available in API version 17.0 and later.
        CronTrigger a=[SELECT Id FROM CronTrigger where NextFireTime > today];
        System.assertEquals(jobID, a.Id,'Schedule ');

    }
}

```