

MaintenanceRequestHelper.apxc :-

```
public with sharing class MaintenanceRequestHelper {
    public static void updateWorkOrders(List<Case> updWorkOrders, Map<Id,Case>
nonUpdCaseMap) {
    Set<Id> validIds = new Set<Id>();

    For (Case c : updWorkOrders){
        if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
            if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
                validIds.add(c.Id);
            }
        }
    }

    if (!validIds.isEmpty()){
        List<Case> newCases = new List<Case>();
        Map<Id,Case> closedCasesM = new Map<Id,Case>([SELECT Id, Vehicle__c,
Equipment__c, Equipment__r.Maintenance_Cycle__c,(SELECT Id,Equipment__c,Quantity__c
FROM Equipment_Maintenance_Items__r)
FROM Case WHERE Id IN :validIds]);
        Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
        AggregateResult[] results = [SELECT Maintenance_Request__c,
MIN(Equipment__r.Maintenance_Cycle__c)cycle FROM Equipment_Maintenance_Item__c
WHERE Maintenance_Request__c IN :ValidIds GROUP BY Maintenance_Request__c];

        for (AggregateResult ar : results){
            maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal) ar.get('cycle'));
        }

        for(Case cc : closedCasesM.values()){
            Case nc = new Case (
                ParentId = cc.Id,
                Status = 'New',
                Subject = 'Routine Maintenance',
                Type = 'Routine Maintenance',
                Vehicle__c = cc.Vehicle__c,
```

```

        Equipment__c = cc.Equipment__c,
        Origin = 'Web',
        Date_Reported__c = Date.Today()
    );
}

    If (maintenanceCycles.containsKey(cc.Id)){
        nc.Date_Due__c = Date.today().addDays((Integer) maintenanceCycles.get(cc.Id));
    } else {
        nc.Date_Due__c = Date.today().addDays((Integer)
cc.Equipment__r.maintenance_Cycle__c);
    }

    newCases.add(nc);
}

insert newCases;

    List<Equipment_Maintenance_Item__c> clonedWPs = new
List<Equipment_Maintenance_Item__c>();
    for (Case nc : newCases){
        for (Equipment_Maintenance_Item__c wp :
closedCasesM.get(nc.ParentId).Equipment_Maintenance_Items__r){
            Equipment_Maintenance_Item__c wpClone = wp.clone();
            wpClone.Maintenance_Request__c = nc.Id;
            ClonedWPs.add(wpClone);
        }
    }
    insert ClonedWPs;
}
}
}

```

MaintenanceRequest.apxt :-

trigger MaintenanceRequest on Case (before update, after update) {

```

    if (Trigger.isUpdate && Trigger.isAfter) {

        MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);

    }

}

```

WarehouseCalloutService.apxc :-

```

public with sharing class WarehouseCalloutService implements Queueable {
    private static final String WAREHOUSE_URL = 'https://th-superbadge-
apex.herokuapp.com/equipment';

    //class that makes a REST callout to an external warehouse system to get a list of
equipment that needs to be updated.
    //The callout's JSON response returns the equipment records that you upsert in
Salesforce.

    @future(callout=true)
    public static void runWarehouseEquipmentSync(){
        Http http = new Http();
        HttpRequest request = new HttpRequest();

        request.setEndpoint(WAREHOUSE_URL);
        request.setMethod('GET');
        HttpResponse response = http.send(request);

        List<Product2> warehouseEq = new List<Product2>();

        if (response.getStatusCode() == 200){
            List<Object> jsonResponse =
(List<Object>)JSON.deserializeUntyped(response.getBody());
            System.debug(response.getBody());

            //class maps the following fields: replacement part (always true), cost, current
inventory, lifespan, maintenance cycle, and warehouse SKU
            //warehouse SKU will be external ID for identifying which equipment records to

```

update within Salesforce

```
    for (Object eq : jsonResponse){
        Map<String,Object> mapJson = (Map<String,Object>)eq;
        Product2 myEq = new Product2();
        myEq.Replacement_Part__c = (Boolean) mapJson.get('replacement');
        myEq.Name = (String) mapJson.get('name');
        myEq.Maintenance_Cycle__c = (Integer) mapJson.get('maintenanceperiod');
        myEq.Lifespan_Months__c = (Integer) mapJson.get('lifespan');
        myEq.Cost__c = (Integer) mapJson.get('cost');
        myEq.Warehouse_SKU__c = (String) mapJson.get('sku');
        myEq.Current_Inventory__c = (Double) mapJson.get('quantity');
        myEq.ProductCode = (String) mapJson.get('_id');
        warehouseEq.add(myEq);
    }

    if (warehouseEq.size() > 0){
        upsert warehouseEq;
        System.debug('Your equipment was synced with the warehouse one');
    }
}

public static void execute (QueueableContext context){
    runWarehouseEquipmentSync();
}

}
```

WarehouseSyncShedule.apxc :-

```
global with sharing class WarehouseSyncSchedule implements Schedulable{
    global void execute(SchedulableContext ctx){
        System.enqueueJob(new WarehouseCalloutService());
    }
}
```

MaintenanceRequestHelperTest.apxc :-

```

@istest
public with sharing class MaintenanceRequestHelperTest {

    private static final string STATUS_NEW = 'New';
    private static final string WORKING = 'Working';
    private static final string CLOSED = 'Closed';
    private static final string REPAIR = 'Repair';
    private static final string REQUEST_ORIGIN = 'Web';
    private static final string REQUEST_TYPE = 'Routine Maintenance';
    private static final string REQUEST_SUBJECT = 'Testing subject';

    PRIVATE STATIC Vehicle__c createVehicle(){
        Vehicle__c Vehicle = new Vehicle__C(name = 'SuperTruck');
        return Vehicle;
    }

    PRIVATE STATIC Product2 createEq(){
        product2 equipment = new product2(name = 'SuperEquipment',
                                           lifespan_months__C = 10,
                                           maintenance_cycle__C = 10,
                                           replacement_part__c = true);
        return equipment;
    }

    PRIVATE STATIC Case createMaintenanceRequest(id vehicleId, id equipmentId){
        case cs = new case(Type=REPAIR,
                           Status=STATUS_NEW,
                           Origin=REQUEST_ORIGIN,
                           Subject=REQUEST_SUBJECT,
                           Equipment__c=equipmentId,
                           Vehicle__c=vehicleId);
        return cs;
    }

    PRIVATE STATIC Equipment_Maintenance_Item__c createWorkPart(id equipmentId,id
requestId){
        Equipment_Maintenance_Item__c wp = new

```

```

Equipment_Maintenance_Item__c(Equipment__c = equipmentId,
                                Maintenance_Request__c = requestId);
    return wp;
}

@istest
private static void testMaintenanceRequestPositive(){
    Vehicle__c vehicle = createVehicle();
    insert vehicle;
    id vehicleId = vehicle.Id;

    Product2 equipment = createEq();
    insert equipment;
    id equipmentId = equipment.Id;

    case somethingToUpdate = createMaintenanceRequest(vehicleId,equipmentId);
    insert somethingToUpdate;

    Equipment_Maintenance_Item__c workP =
createWorkPart(equipmentId,somethingToUpdate.id);
    insert workP;

    test.startTest();
    somethingToUpdate.status = CLOSED;
    update somethingToUpdate;
    test.stopTest();

    Case newReq = [Select id, subject, type, Equipment__c, Date_Reported__c,
Vehicle__c, Date_Due__c
                  from case
                  where status =:STATUS_NEW];

    Equipment_Maintenance_Item__c workPart = [select id
                                              from Equipment_Maintenance_Item__c
                                              where Maintenance_Request__c =:newReq.Id];

    system.assert(workPart != null);
    system.assert(newReq.Subject != null);

```

```

    system.assertEquals(newReq.Type, REQUEST_TYPE);
    SYSTEM.assertEquals(newReq.Equipment__c, equipmentId);
    SYSTEM.assertEquals(newReq.Vehicle__c, vehicleId);
    SYSTEM.assertEquals(newReq.Date_Reported__c, system.today());
}

@istest
private static void testMaintenanceRequestNegative(){
    Vehicle__C vehicle = createVehicle();
    insert vehicle;
    id vehicleId = vehicle.Id;

    product2 equipment = createEq();
    insert equipment;
    id equipmentId = equipment.Id;

    case emptyReq = createMaintenanceRequest(vehicleId,equipmentId);
    insert emptyReq;

    Equipment_Maintenance_Item__c workP = createWorkPart(equipmentId,
emptyReq.Id);
    insert workP;

    test.startTest();
    emptyReq.Status = WORKING;
    update emptyReq;
    test.stopTest();

    list<case> allRequest = [select id
                            from case];

    Equipment_Maintenance_Item__c workPart = [select id
                                                from Equipment_Maintenance_Item__c
                                                where Maintenance_Request__c = :emptyReq.Id];

    system.assert(workPart != null);
    system.assert(allRequest.size() == 1);
}

```



```

list<Equipment_Maintenance_Item__c> workParts = [select id
                                                    from Equipment_Maintenance_Item__c
                                                    where Maintenance_Request__c in: oldRequestIds];

system.assert(allRequests.size() == 300);
}
}

```

MaintenanceRequestHelper.apxc :-

```

public with sharing class MaintenanceRequestHelper {
    public static void updateworkOrders(List<Case> updWorkOrders, Map<Id,Case>
nonUpdCaseMap) {
        Set<Id> validIds = new Set<Id>();

        For (Case c : updWorkOrders){
            if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
                if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
                    validIds.add(c.Id);
                }
            }
        }

        if (!validIds.isEmpty()){
            List<Case> newCases = new List<Case>();
            Map<Id,Case> closedCasesM = new Map<Id,Case>([SELECT Id, Vehicle__c,
Equipment__c, Equipment__r.Maintenance_Cycle__c,(SELECT
Id,Equipment__c,Quantity__c FROM Equipment_Maintenance_Items__r)
FROM Case WHERE Id IN :validIds]);
            Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
            AggregateResult[] results = [SELECT Maintenance_Request__c,
MIN(Equipment__r.Maintenance_Cycle__c)cycle FROM Equipment_Maintenance_Item__c

```

```
WHERE Maintenance_Request__c IN :ValidIds GROUP BY Maintenance_Request__c];
```

```
    for (AggregateResult ar : results){  
        maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal)  
ar.get('cycle'));  
    }
```

```
    for(Case cc : closedCasesM.values()){  
        Case nc = new Case (  
            ParentId = cc.Id,  
            Status = 'New',  
            Subject = 'Routine Maintenance',  
            Type = 'Routine Maintenance',  
            Vehicle__c = cc.Vehicle__c,  
            Equipment__c = cc.Equipment__c,  
            Origin = 'Web',  
            Date_Reported__c = Date.Today()
```

```
    );
```

```
    If (maintenanceCycles.containsKey(cc.Id)){  
        nc.Date_Due__c = Date.today().addDays((Integer) maintenanceCycles.get(cc.Id));  
    }
```

```
        newCases.add(nc);  
    }
```

```
insert newCases;
```

```
    List<Equipment_Maintenance_Item__c> clonedWPs = new  
List<Equipment_Maintenance_Item__c>();  
    for (Case nc : newCases){  
        for (Equipment_Maintenance_Item__c wp :  
closedCasesM.get(nc.ParentId).Equipment_Maintenance_Items__r){  
            Equipment_Maintenance_Item__c wpClone = wp.clone();  
            wpClone.Maintenance_Request__c = nc.Id;  
            ClonedWPs.add(wpClone);  
        }  
    }
```

```

    }
    insert ClonedWPs;
  }
}

```

MaintenanceRequest.apxt :-

```

trigger MaintenanceRequest on Case (before update, after update) {
  if (Trigger.isUpdate && Trigger.isAfter) {
    MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);
  }
}

```

WarehouseCalloutService.apxc :-

```

public with sharing class WarehouseCalloutService {
  private static final String WAREHOUSE_URL = 'https://th-superbadge-
apex.herokuapp.com/equipment';

```

```

  // @future(callout=true)
  public static void runWarehouseEquipmentSync() {

```

```

    Http http = new Http();
    HttpRequest request = new HttpRequest();

    request.setEndpoint(WAREHOUSE_URL);
    request.setMethod('GET');
    HttpResponse response = http.send(request);

```

```

    List<Product2> warehouseEq = new List<Product2>();

```

```

    if (response.getStatusCode() == 200) {
      List<Object> jsonResponse =
(List<Object>)JSON.deserializeUntyped(response.getBody());
      System.debug(response.getBody());
    }
  }
}

```

```

for (Object eq : jsonResponse){
    Map<String,Object> mapJson = (Map<String,Object>)eq;
    Product2 myEq = new Product2();
    myEq.Replacement_Part__c = (Boolean) mapJson.get('replacement');
    myEq.Name = (String) mapJson.get('name');
    myEq.Maintenance_Cycle__c = (Integer) mapJson.get('maintenanceperiod');
    myEq.Lifespan_Months__c = (Integer) mapJson.get('lifespan');
    myEq.Cost__c = (Decimal) mapJson.get('lifespan');
    myEq.Warehouse_SKU__c = (String) mapJson.get('sku');
    myEq.Current_Inventory__c = (Double) mapJson.get('quantity');
    warehouseEq.add(myEq);
}

if (warehouseEq.size() > 0){
    upsert warehouseEq;
    System.debug('Your equipment was synced with the warehouse one');
    System.debug(warehouseEq);
}

}
}
}

```

WarehouseCalloutServiceTest.apxc :-

@isTest

```

private class WarehouseCalloutServiceTest {
    @isTest
    static void testWareHouseCallout(){
        Test.startTest();
        // implement mock callout test here
        Test.setMock(HTTPCalloutMock.class, new WarehouseCalloutServiceMock());
        WarehouseCalloutService.runWarehouseEquipmentSync();
        Test.stopTest();
    }
}

```

```

        System.assertEquals(1, [SELECT count() FROM Product2]);
    }
}

```

WarehouseCalloutServiceMock.apxc :-

```

@isTest
global class WarehouseCalloutServiceMock implements HttpCalloutMock {
    // implement http mock callout
    global static HttpResponse respond(HttpRequest request){

        System.assertEquals('https://th-superbadge-apex.herokuapp.com/equipment',
request.getEndpoint());
        System.assertEquals('GET', request.getMethod());

        // Create a fake response
        HttpResponse response = new HttpResponse();
        response.setHeader('Content-Type', 'application/json');

        response.setBody('[{ "_id": "55d66226726b611100aaf741", "replacement": false, "quantity": 5
, "name": "Generator 1000
kW", "maintenanceperiod": 365, "lifespan": 120, "cost": 5000, "sku": "100003" }]');
        response.setStatusCode(200);
        return response;
    }
}

```

WarehouseSyncSchedule.apxc :-

```

global class WarehouseSyncSchedule implements Schedulable {
    global void execute(SchedulableContext ctx) {

        WarehouseCalloutService.runWarehouseEquipmentSync();
    }
}

```

```
}  
}
```

WarehouseSyncScheduleTest.apxc :-

```
@isTest  
public class WarehouseSyncScheduleTest {  
  
    @isTest static void WarehousescheduleTest(){  
        String scheduleTime = '00 00 01 * * ?';  
        Test.startTest();  
        Test.setMock(HttpCalloutMock.class, new WarehouseCalloutServiceMock());  
        String jobID=System.schedule('Warehouse Time To Schedule to Test', scheduleTime,  
new WarehouseSyncSchedule());  
        Test.stopTest();  
        //Contains schedule information for a scheduled job. CronTrigger is similar to a cron  
job on UNIX systems.  
        // This object is available in API version 17.0 and later.  
        CronTrigger a=[SELECT Id FROM CronTrigger where NextFireTime > today];  
        System.assertEquals(jobID, a.Id,'Schedule ');  
  
    }  
}
```