

Apex Triggers :

https://trailhead.salesforce.com/content/learn/modules/apex_triggers?trailmix_creator_id=trailblazerconnect&trailmix_slug=salesforce-developer-catalyst

1. Get Started with Apex Trigger

AccountAddressTrigger Code :

```
trigger AccountAddressTrigger on Account (before insert, before update) {
```

```
    for(Account a : Trigger.new){
        if( !String.isBlank(a.BillingPostalCode) && a.Match_Billing_Address__c ){
            a.ShippingPostalCode = a.BillingPostalCode;
        }
    }
}
```

2. Bulk Apex Triggers Unit

ClosedOpportunityTriggerCode :

```
trigger ClosedOpportunityTrigger on Opportunity (before insert, before update) {
```

```
List<Task> newTask = new List <Task>();
```

```
    //Grab the Opportunity Id's from Opps that are Closed Won from the Context Variable
    and store them in opp
```

```
    for(Opportunity opp : [SELECT Id FROM Opportunity
                           WHERE StageName = 'Closed Won' IN :Trigger.New]){
```

```
    //Create a Follow Up Task against Id's that are stored in the variable opp
```

```
    newTask.add(new Task(Subject = 'Follow Up Test Task',
```

```
                        Priority = 'High',
```

```
                        WhatId = opp.Id));
```

```
    //Insert new Tasks
```

```
        {insert newTask;
```

```
    }
```

```
}
```

```
}
```

Apex Testing : https://trailhead.salesforce.com/content/learn/modules/apex_testing?trailmix_creator_id=trailblazerconnect&trailmix_slug=salesforce-developer-catalyst

1. Get Started with Apex Unit

Testing VerifyDate Code :

```
@isTest
private class VerifyDateTest {
    @isTest static void CheckDatesTesttrue() {
        Date date1=date.today();
        Date date2=date1.addDays(29);
        Date t = VerifyDate.CheckDates(date1, date2);
        System.assertEquals(t, date2);
    }
    @isTest static void DateOver() {
        Date date1=date.today();
        Date date2=date1.addDays(31);
        Date t = VerifyDate.CheckDates(date1, date2);
        System.assertNotEquals(t, date1);
    }
}
```

TestVerifyDate Code :

```
@isTest
public class TestVerifyDate {
    @isTest static void Test_CheckDates_case1(){
        Date D = VerifyDate.CheckDates(date.parse('01/01/2020'),
date.parse('01/05/2020'));
        System.assertEquals(date.parse('01/05/2020'), D);
    }
    @isTest static void Test_CheckDates_case2(){
        Date D = VerifyDate.CheckDates(date.parse('01/01/2020'),
date.parse('05/05/2020'));
```

```

        System.assertEquals(date.parse('01/31/2020'), D);
    }
    @isTest static void Test_DateWithin30Days_case1(){
        Boolean flag = VerifyDate.DateWithin30Days(date.parse('01/01/2020'),
date.parse('12/30/2019'));
        System.assertEquals(false, flag);
    }
    @isTest static void Test_DateWithin30Days_case2(){
        Boolean flag = VerifyDate.DateWithin30Days(date.parse('01/01/2020'),
date.parse('02/02/2019'));
        System.assertEquals(false, flag);
    }
    @isTest static void Test_DateWithin30Days_case3(){
        Boolean flag = VerifyDate.DateWithin30Days(date.parse('01/01/2020'),
date.parse('02/02/2020'));
        System.assertEquals(true, flag);
    }
    @isTest static void Test_SetEndOfMonthDate(){
        Date returndate = VerifyDate.SetEndOfMonthDate(date.parse('01/01/2020'));
    }
}

```

2. TestApex Triggers Unit

RestrictContactByName Code :

trigger RestrictContactByName on Contact (before insert, before update) {

```

    //check contacts prior to insert or update for invalid data
    For (Contact c : Trigger.New) {
        if(c.LastName == 'INVALIDNAME') {      //invalidname is invalid
            c.AddError('The Last Name "'+c.LastName+'" is not allowed for
DML');
        }
    }
}

```

```
}
```

TestRestrictContactByName Code :

```
@isTest
public class TestRestrictContactByName {
    @isTest static void Test_insertupdateContact(){
        Contact cnt = new Contact();
        cnt.LastName = 'INVALIDNAME';
        Test.startTest();
        Database.SaveResult result = Database.insert(cnt, false);
        Test.stopTest();
        System.assert(!result.isSuccess());
        System.assert(result.getErrors().size() > 0);
        System.assertEquals('The Last Name "INVALIDNAME" is not allowed for DML',
result.getErrors()[0].getMessage());
    }
}
```

3. Create Test Data for Apex Tests:

RandomContactFactory Code :

```
public class RandomContactFactory {
    public static List<Contact> generateRandomContacts(Integer numcnt, string
lastname){
        List<Contact> contacts = new List<Contact>();
        for(Integer i=0;i<numcnt;i++){
            Contact cnt = new Contact(FirstName = 'Test '+i, LastName = lastname);
            contacts.add(cnt);
        }
        return contacts;
    }
}
```

Asynchronous Apex :

https://trailhead.salesforce.com/content/learn/modules/asynchronous_apex?trailmix_creator_id=trailblazerconnect&trailmix_slug=salesforce-developer-catalyst

1. Quiz

2. Use Future Methods

AccountProcessor Code :

```
public class AccountProcessor {
    @future
    public static void countContacts(List<Id> accountIds){

        List<Account> accountsToUpdate= new List<Account>();

        List<Account> accounts = [Select Id, Name, (Select Id from Contacts) from Account
Where Id in :accountIds];

        For (Account acc:accounts) {
            List<Contact> contactList = acc.Contacts;
            acc.Number_Of_Contacts__c= contactList.size();
            accountsToUpdate.add(acc);

        }
        update accountsToUpdate;

    }
}
```

AccountProcessorTest Code :

```
@IsTest
public class AccountProcessorTest {
    @IsTest
    private static void testCountContacts(){
        Account newAccount = new Account(Name='Test Account');
        insert newAccount;
    }
}
```

```

        Contact newContact1 = new Contact(FirstName='John',LastName='Doe',AccountId
= newAccount.Id);
        insert newContact1;
        Contact newContact2 = new Contact(FirstName='Jane',LastName='Doe',AccountId
= newAccount.Id);
        insert newContact2;
        List<Id> accountIds = new List<Id>();
        accountIds.add(newAccount.Id);
        Test.startTest();
        AccountProcessor.countContacts(accountIds);
        Test.stopTest();
    }

}

```

3. Use Batch Apex

LeadProcessor Code :

```

global class LeadProcessor implements Database.Batchable<sObject> {
    global Integer count = 0;
    global Database.QueryLocator start(Database.BatchableContext bc){
        return Database.getQueryLocator('SELECT ID, LeadSource FROM Lead');
    }

    global void execute (Database.BatchableContext bc, List<Lead> L_list){
        List<lead> L_list_new = new List<lead>();
        for(lead L:L_list){
            L.leadsource = 'Dreamforce';
            L_list_new.add(L);
            count +=1;
        }
        update L_list_new;
    }
    global void finish(Database.BatchableContext bc){
        system.debug('count = ' + count );
    }
}

```

```
}
```

LeadProcessorTest Code :

```
@isTest
public class LeadProcessorTest {
    @isTest
    public static void testit(){
        List<lead> L_list = new List<lead>();
        for(Integer i=0; i<200; i++){
            Lead L = new lead();
            L.LastName = 'name' + i;
            L.Company = 'Company';
            L.Status = 'Random Status';
            L_list.add(L);
        }
        insert L_list;
        Test.startTest();
        LeadProcessor lp = new LeadProcessor();
        Id batchId = Database.executeBatch(lp);
        Test.stopTest();
    }
}
```

4. Controp Processes with Queueable Apex

AddPrimaryContact Code :

```
public class AddPrimaryContact implements Queueable{
    private Contact con;
    private String state;
    public AddPrimaryContact(Contact con, String state){
        this.con = con;
        this.state = state;
    }
    public void execute(QueueableContext context){
```

```

        List<Account> accounts = [Select Id, Name, (Select FirstName, LastName, Id from
contacts)
                                from Account where BillingState = :state Limit 200];
    List<Contact> primaryContacts = new List<Contact>();
    for(Account acc:accounts){
        Contact c = con.clone();
        c.AccountId = acc.Id;
        primaryContacts.add(c);
    }
    if(primaryContacts.size() > 0){
        insert primaryContacts;
    }
}
}

```

AddPrimaryContactTest Code :

```

@isTest
public class AddPrimaryContactTest {
    static testmethod void testQueueable(){
        List<Account> testAccounts = new List<Account>();
        for(Integer i=0;i<50;i++){
            testAccounts.add(new Account(Name='Account '+i,BillingState='CA'));
        }
        for(Integer j=0;j<50;j++){
            testAccounts.add(new Account(Name='Account '+j,BillingState='NY'));
        }
        insert testAccounts;
        Contact testContact = new Contact(FirstName = 'John', LastName = 'Doe');
        insert testContact;
        AddPrimaryContact addit = new addPrimaryContact(testContact, 'CA');
        Test.startTest();
        system.enqueueJob(addit);
        Test.stopTest();
        System.assertEquals(50,[Select count()from Contact where accountId in (Select Id
from Account where BillingState='CA')]);
    }
}

```



```
}  
  
}
```

5. Schedule Jobs Using the Apex Scheduler

DailyLeadProcessor Code :

```
public class DailyLeadProcessor implements Schedulable{  
    public void execute(SchedulableContext ctx){  
        List<lead> leads = [Select Id From Lead Where LeadSource = NULL LIMIT 200];  
        for(Lead l:leads){  
            l.LeadSource = 'Dreamforce';  
            update l;  
        }  
    }  
}
```

DailyLeadProcessorTestCode :

```
@isTest  
private class DailyLeadProcessorTest {  
    static testMethod void testDailyLeadProcessor(){  
        String CRON_EXP = '0 0 1 * * ?';  
        List<Lead> IList = new List<lead>();  
        for(Integer i=0; i<200; i++){  
            IList.add(new Lead(LastName='Dreamforce'+i, Company='Test1 Inc.',  
Status='Open - Not Contacted'));  
        }  
        insert IList;  
        Test.startTest();  
        String jobId = System.schedule('DailyLeadProcessor', CRON_EXP, new  
DailyLeadProcessor());  
    }  
}
```

Apex Integration Services

https://trailhead.salesforce.com/content/learn/modules/apex_integration_services?trailmix_creator_id=trailblazerconnect&trailmix_slug=salesforcedeveloper-catalyst

1. Quiz

2. Apex REST Callouts

AnimalLocatorCode :

```
public class AnimalLocator{
    public static String getAnimalNameById(Integer x){
        Http http = new Http();
        HttpRequest req = new HttpRequest();
        req.setEndpoint('https://th-apex-http-callout.herokuapp.com/animals/' + x);
        req.setMethod('GET');
        Map<String, Object> animal= new Map<String, Object>();
        HttpResponse res = http.send(req);
        if (res.getStatusCode() == 200) {
            Map<String, Object> results =(Map<String, Object>)JSON.deserializeUntyped
(res.getBody());
            animal = (Map<String, Object>) results.get('animal');
        }
        return (String)animal.get('name');
    }
}
```

AnimalLocatorTest Code :

@isTest

```
private class AnimalLocatorTest{
    @isTest static void AnimalLocatorMock1() {
        Test.setMock(HttpCalloutMock.class, new AnimalLocatorMock());
        String result = AnimalLocator.getAnimalNameById(3);
        String expectedResult = 'chicken';
        System.assertEquals(result,expectedResult );
    }
}
```

```
}  
}
```

AnimalLocatorMock Code :

```
@isTest  
global class AnimalLocatorMock implements HttpCalloutMock {  
    // Implement this interface method  
    global HTTPResponse respond(HTTPRequest request) {  
        // Create a fake response  
        HttpResponse response = new HttpResponse();  
        response.setHeader('Content-Type','application/json');  
        response.setBody('{"animals":["majestic badger", "fluffy bunny", "scary bear",  
"chicken", "mighty moose"]}');  
        response.setStatusCode(200);  
        return response;  
    }  
  
}
```

2)Apex SOAP Callouts

ParkService Code :

//Generated by wsdl2apex

```
public class AsyncParkService {  
    public class byCountryResponseFuture extends System.WebServiceCalloutFuture {  
        public String[] getValue() {  
            parkService.byCountryResponse response =  
(parkService.byCountryResponse)System.WebServiceCallout.endInvoke(this);  
            return response.return_x;  
        }  
    }  
}  
public class AsyncParksImplPort {
```

```

        public String endpoint_x = 'https://th-apex-soap-
service.herokuapp.com/service/parks';
        public Map<String,String> inputHttpHeaders_x;
        public String clientCertName_x;
        public Integer timeout_x;
        private String[] ns_map_type_info = new String[]{'http://parks.services/',
'parkService'};
        public AsyncParkService.byCountryResponseFuture
beginByCountry(System.Continuation continuation,String arg0) {
        parkService.byCountry request_x = new parkService.byCountry();
        request_x.arg0 = arg0;
        return (AsyncParkService.byCountryResponseFuture)
System.WebServiceCallout.beginInvoke(
        this,
        request_x,
        AsyncParkService.byCountryResponseFuture.class,
        continuation,
        new String[]{endpoint_x,
        "",
        'http://parks.services/',
        'byCountry',
        'http://parks.services/',
        'byCountryResponse',
        'parkService.byCountryResponse'}
        );
    }
}
}
}

```

ParkLocator Code :

```

public class ParkLocator {
    public static String[] country(String theCountry) {
        ParkService.ParksImplPort parkSvc = new ParkService.ParksImplPort();
        return parkSvc.byCountry(theCountry);
    }
}

```

ParkLocatorTest Code :

```
@isTest
private class ParkLocatorTest {
    @isTest static void testCallout() {
        // This causes a fake response to be generated
        Test.setMock(WebServiceMock.class, new ParkServiceMock());
        // Call the method that invokes a callout
        //Double x = 1.0;
        //Double result = AwesomeCalculator.add(x, y);
        String country = 'Germany';
        String[] result = ParkLocator.Country(country);
        // Verify that a fake result is returned
        System.assertEquals(new List<String>{'Hamburg Wadden Sea National Park',
'Hainich National Park', 'Bavarian Forest National Park'}, result);
    }
}
```

ParkServiceMock Code :

```
@isTest
global class ParkServiceMock implements WebServiceMock {
    global void doInvoke(
        Object stub,
        Object request,
        Map<String, Object> response,
        String endpoint,
        String soapAction,
        String requestName,
        String responseNS,
        String responseName,
        String responseType) {
        // start - specify the response you want to send
        parkService.byCountryResponse response_x = new
parkService.byCountryResponse();
        response_x.return_x = new List<String>{'Hamburg Wadden Sea National Park',
'Hainich National Park', 'Bavarian Forest National Park'};
```

```

        //calculatorServices.doAddResponse response_x = new
calculatorServices.doAddResponse();
        //response_x.return_x = 3.0;
        // end
        response.put('response_x', response_x);
    }
}

```

4) Apex Web Services

AccountManager Code :

```

@RestResource(urlMapping = '/Accounts/*/contacts')
global with sharing class AccountManager {
    @HttpGet
    global static Account getAccount(){
        RestRequest request = RestContext.request;
        string accountId = request.requestURI.substringBetween('Accounts/','/contacts');
        Account result = [SELECT Id, Name, (Select Id, Name from Contacts) from Account
where Id=:accountId Limit 1];
        return result;
    }
}

```

AccountManagerTest Code :

```

@IsTest
public class AccountManagerTest {
    @isTest static void testGetContactsByAccountId(){
        Id recordId = createTestRecord();
        RestRequest request = new RestRequest();
        request.requestUri =
'https://yoursInstance.my.salesforce.com/services/apexrest/Accounts/'+
        recordId+'/contacts';
        request.httpMethod = 'GET';
        RestContext.request = request;
    }
}

```

```

    Account thisAccount = AccountManager.getAccount();
    System.assert(thisAccount != null);
    System.assertEquals('Test record', thisAccount.Name);
}
static Id createTestRecord(){
    Account accountTest = new Account(
        Name = 'Test record');
    insert accountTest;
    Contact contactTest = new Contact(
        FirstName='John',
        LastName = 'Doe',
        AccountId = accountTest.Id
    );
    insert contactTest;
    return accountTest.Id;
}
}

```

APEX SPECIALIST SUPERBADGE :

https://trailhead.salesforce.com/content/learn/modules/apex_integration_services?trailmix_creator_id=trailblazerconnect&trailmix_slug=salesforce-developercatalyst

1. Quiz
2. Automate RecordCreation

MaintenanceRequestHelperCode :

```

public with sharing class MaintenanceRequestHelper {
    public static void updateWorkOrders(List<Case> updWorkOrders, Map<Id,Case>
nonUpdCaseMap) {
        Set<Id> validIds = new Set<Id>();
        For (Case c : updWorkOrders){
            if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
                if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){

```

```

        validIds.add(c.Id);
    }
}
}

//When an existing maintenance request of type Repair or Routine Maintenance is
closed,
//create a new maintenance request for a future routine checkup.
if (!validIds.isEmpty()){
    Map<Id,Case> closedCases = new Map<Id,Case>([SELECT Id, Vehicle_c,
Equipmentc, Equipmentr.Maintenance_Cycle_c,
                                (SELECT Id,Equipment_c,Quantityc FROM
Equipment_Maintenance_Items_r)
                                FROM Case WHERE Id IN :validIds]);
    Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
    //calculate the maintenance request due dates by using the maintenance cycle
defined on the related equipment records.
    AggregateResult[] results = [SELECT Maintenance_Request__c,
                                MIN(Equipment_r.Maintenance_Cycle_c)cycle
                                FROM Equipment_Maintenance_Item__c
                                WHERE Maintenance_Request_c IN :ValidIds GROUP BY
Maintenance_Request_c];
    for (AggregateResult ar : results){
        maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal)
ar.get('cycle'));
    }
    List<Case> newCases = new List<Case>();
    for(Case cc : closedCases.values()){
        Case nc = new Case (
            ParentId = cc.Id,
            Status = 'New',
            Subject = 'Routine Maintenance',
            Type = 'Routine Maintenance',
            Vehicle_c = cc.Vehicle_c,
            Equipment_c =cc.Equipment_c,
            Origin = 'Web',
            Date_Reported__c = Date.Today()
        );
    }
}

```



```

        //If multiple pieces of equipment are used in the maintenance request,
        //define the due date by applying the shortest maintenance cycle to today's
date.
        //If (maintenanceCycles.containsKey(cc.Id)){
            nc.Date_Due__c = Date.today().addDays((Integer)
maintenanceCycles.get(cc.Id));
        //} else {
            // nc.Date_Due__c = Date.today().addDays((Integer)
cc.Equipmenttr.maintenance_Cycle_c);
        //}
        newCases.add(nc);
    }
    insert newCases;
    List<Equipment_Maintenance_Item_c> clonedList = new
List<Equipment_Maintenance_Item_c>();
    for (Case nc : newCases){
        for (Equipment_Maintenance_Item_c clonedListItem :
closedCases.get(nc.ParentId).Equipment_Maintenance_Items_r){
            Equipment_Maintenance_Item__c item = clonedListItem.clone();
            item.Maintenance_Request__c = nc.Id;
            clonedList.add(item);
        }
    }
    insert clonedList;
}
}
}

```

MaintenanceRequest Code :

```

trigger MaintenanceRequest on Case (before update, after update) {
    if(Trigger.isUpdate && Trigger.isAfter){
        MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);
    }
}

```

3. Synchronize Salesforce Data

WarehouseCalloutServiceCode :

```
public with sharing class WarehouseCalloutService implements Queueable {
    private static final String WAREHOUSE_URL = 'https://th-superbadge-
apex.herokuapp.com/equipment';
    //Write a class that makes a REST callout to an external warehouse system to get a
list of equipment that needs to be updated.
    //The callout's JSON response returns the equipment records that you upsert in
Salesforce.
    @future(callout=true)
    public static void runWarehouseEquipmentSync(){
        System.debug('go into runWarehouseEquipmentSync');
        Http http = new Http();
        HttpRequest request = new HttpRequest();
        request.setEndpoint(WAREHOUSE_URL);
        request.setMethod('GET');
        HttpResponse response = http.send(request);
        List<Product2> product2List = new List<Product2>();
        System.debug(response.getStatusCode());
        if (response.getStatusCode() == 200){
            List<Object> jsonResponse =
(List<Object>)JSON.deserializeUntyped(response.getBody());
            System.debug(response.getBody());
            //class maps the following fields:
            //warehouse SKU will be external ID for identifying which equipment records to
update within Salesforce
            for (Object jR : jsonResponse){
                Map<String,Object> mapJson = (Map<String,Object>)jR;
                Product2 product2 = new Product2();
                //replacement part (always true),
                product2.Replacement_Part__c = (Boolean) mapJson.get('replacement');
                //cost
                product2.Cost__c = (Integer) mapJson.get('cost');
                //current inventory
                product2.Current_Inventory__c = (Double) mapJson.get('quantity');
```

```

        //lifespan
        product2.Lifespan_Months__c = (Integer) mapJson.get('lifespan');
        //maintenance cycle
        product2.Maintenance_Cycle__c = (Integer)
mapJson.get('maintenanceperiod');
        //warehouse SKU
        product2.Warehouse_SKU__c = (String) mapJson.get('sku');
        product2.Name = (String) mapJson.get('name');
        product2.ProductCode = (String) mapJson.get('_id');
        product2List.add(product2);
    }
    if (product2List.size() > 0){
        upsert product2List;
        System.debug('Your equipment was synced with the warehouse one');
    }
}
}
}
public static void execute (QueueableContext context){
    System.debug('start runWarehouseEquipmentSync');
    runWarehouseEquipmentSync();
    System.debug('end runWarehouseEquipmentSync');
}
}
}

```

4. Schedule Synchronization

WarehouseSyncSchedule Code :

```

global with sharing class WarehouseSyncSchedule implements Schedulable {
    // implement scheduled code here
    global void execute (SchedulableContext ctx){
        System.enqueueJob(new WarehouseCalloutService());
    }
}

```

5. Test AutomaticLogic

MaintenanceRequestHelperTest Code :

@isTest

public with sharing class MaintenanceRequestHelperTest {

 // createVehicle

 private static Vehicle__c createVehicle(){

 Vehicle__c vehicle = new Vehicle__C(name = 'Testing Vehicle');

 return vehicle;

 }

 // createEquipment

 private static Product2 createEquipment(){

 product2 equipment = new product2(name = 'Testing equipment',

 lifespan_months__c = 10,

 maintenance_cycle__c = 10,

 replacement_part__c = true);

 return equipment;

 }

 // createMaintenanceRequest

 private static Case createMaintenanceRequest(id vehicleId, id equipmentId){

 case cse = new case(Type='Repair',

 Status='New',

 Origin='Web',

 Subject='Testing subject',

 Equipment__c=equipmentId,

 Vehicle__c=vehicleId);

 return cse;

 }

 // createEquipmentMaintenanceItem

 private static Equipment_Maintenance_Item__c createEquipmentMaintenanceItem(id equipmentId, id requestId){

 Equipment_Maintenance_Item__c equipmentMaintenanceItem = new
Equipment_Maintenance_Item__c(

 Equipment__c = equipmentId,

```

        Maintenance_Request__c = requestId);
    return equipmentMaintenanceltem;
}

```

@isTest

```

private static void testPositive(){
    Vehicle__c vehicle = createVehicle();
    insert vehicle;
    id vehicleId = vehicle.Id;

```

```

    Product2 equipment = createEquipment();
    insert equipment;
    id equipmentId = equipment.Id;

```

```

    case createdCase = createMaintenanceRequest(vehicleId,equipmentId);
    insert createdCase;

```

```

    Equipment_Maintenance_Item__c equipmentMaintenanceltem =
createEquipmentMaintenanceltem(equipmentId,createdCase.id);
    insert equipmentMaintenanceltem;

```

```

test.startTest();
createdCase.status = 'Closed';
update createdCase;
test.stopTest();

```

```

Case newCase = [Select id,
                    subject,
                    type,
                    Equipment__c,
                    Date_Reported__c,
                    Vehicle__c,
                    Date_Due__c
                from case
                where status ='New'];

```

```

Equipment_Maintenance_Item__c workPart = [select id

```

```

        from Equipment_Maintenance_Item__c
        where Maintenance_Request__c =:newCase.Id];
list<case> allCase = [select id from case];
system.assert(allCase.size() == 2);

system.assert(newCase != null);
system.assert(newCase.Subject != null);
system.assertEquals(newCase.Type, 'Routine Maintenance');
SYSTEM.assertEquals(newCase.Equipment__c, equipmentId);
SYSTEM.assertEquals(newCase.Vehicle__c, vehicleId);
SYSTEM.assertEquals(newCase.Date_Reported__c, system.today());
}

```

@isTest

```

private static void testNegative(){
    Vehicle__C vehicle = createVehicle();
    insert vehicle;
    id vehicleId = vehicle.Id;

    product2 equipment = createEquipment();
    insert equipment;
    id equipmentId = equipment.Id;

    case createdCase = createMaintenanceRequest(vehicleId,equipmentId);
    insert createdCase;

    Equipment_Maintenance_Item__c workP =
createEquipmentMaintenanceItem(equipmentId, createdCase.Id);
    insert workP;

    test.startTest();
    createdCase.Status = 'Working';
    update createdCase;
    test.stopTest();

    list<case> allCase = [select id from case];

```

```
Equipment_Maintenance_Item__c equipmentMaintenanceltem = [select id
                    from Equipment_Maintenance_Item__c
                    where Maintenance_Request__c = :createdCase.Id];
```

```
system.assert(equipmentMaintenanceltem != null);
system.assert(allCase.size() == 1);
}
```

@isTest

```
private static void testBulk(){
    list<Vehicle__C> vehicleList = new list<Vehicle__C>();
    list<Product2> equipmentList = new list<Product2>();
    list<Equipment_Maintenance_Item__c> equipmentMaintenanceltemList = new
list<Equipment_Maintenance_Item__c>();
    list<case> caseList = new list<case>();
    list<id> oldCaseIds = new list<id>();

    for(integer i = 0; i < 300; i++){
        vehicleList.add(createVehicle());
        equipmentList.add(createEquipment());
    }
    insert vehicleList;
    insert equipmentList;

    for(integer i = 0; i < 300; i++){
        caseList.add(createMaintenanceRequest(vehicleList.get(i).id,
equipmentList.get(i).id));
    }
    insert caseList;

    for(integer i = 0; i < 300; i++){

equipmentMaintenanceltemList.add(createEquipmentMaintenanceltem(equipmentList.
get(i).id, caseList.get(i).id));
    }
    insert equipmentMaintenanceltemList;
```

```

test.startTest();
for(case cs : caseList){
    cs.Status = 'Closed';
    oldCaseIds.add(cs.Id);
}
update caseList;
test.stopTest();

list<case> newCase = [select id
                      from case
                      where status ='New'];

list<Equipment_Maintenance_Item__c> workParts = [select id
                                                  from Equipment_Maintenance_Item__c
                                                  where Maintenance_Request__c in: oldCaseIds];

system.assert(newCase.size() == 300);

list<case> allCase = [select id from case];
system.assert(allCase.size() == 600);
}
}

```

MaintenanceRequestHelper.apxc :-

```

public with sharing class MaintenanceRequestHelper {
    public static void updateWorkOrders(List<Case> updWorkOrders, Map<Id,Case>
nonUpdCaseMap) {
        Set<Id> validIds = new Set<Id>();
        For (Case c : updWorkOrders){
            if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
                if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
                    validIds.add(c.Id);
                }
            }
        }
    }
}

```



```

    }
  }
}

```

//When an existing maintenance request of type Repair or Routine Maintenance is closed,

//create a new maintenance request for a future routine checkup.

```
if (!validIds.isEmpty()){
```

```
    Map<Id,Case> closedCases = new Map<Id,Case>([SELECT Id, Vehicle__c,
Equipment__c, Equipment__r.Maintenance_Cycle__c,
```

```
                (SELECT Id,Equipment__c,Quantity__c FROM
Equipment_Maintenance_Items__r)
```

```
                FROM Case WHERE Id IN :validIds]);
```

```
    Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
```

//calculate the maintenance request due dates by using the maintenance cycle defined on the related equipment records.

```
    AggregateResult[] results = [SELECT Maintenance_Request__c,
```

```
        MIN(Equipment__r.Maintenance_Cycle__c)cycle
```

```
        FROM Equipment_Maintenance_Item__c
```

```
        WHERE Maintenance_Request__c IN :ValidIds GROUP BY
Maintenance_Request__c];
```

```
    for (AggregateResult ar : results){
```

```
        maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal)
ar.get('cycle'));
    }
```

```
List<Case> newCases = new List<Case>();
```

```
for(Case cc : closedCases.values()){
```

```
    Case nc = new Case (
```

```
        ParentId = cc.Id,
```

```
        Status = 'New',
```

```
        Subject = 'Routine Maintenance',
```

```
        Type = 'Routine Maintenance',
```

```
        Vehicle__c = cc.Vehicle__c,
```

```
        Equipment__c =cc.Equipment__c,
```

```

        Origin = 'Web',
        Date_Reported__c = Date.Today()
    );

    //If multiple pieces of equipment are used in the maintenance request,
    //define the due date by applying the shortest maintenance cycle to today's
date.
    //If (maintenanceCycles.containsKey(cc.Id)){
        nc.Date_Due__c = Date.today().addDays((Integer)
maintenanceCycles.get(cc.Id));
    //} else {
    //    nc.Date_Due__c = Date.today().addDays((Integer)
cc.Equipment__r.maintenance_Cycle__c);
    //}

    newCases.add(nc);
}

insert newCases;

List<Equipment_Maintenance_Item__c> clonedList = new
List<Equipment_Maintenance_Item__c>();
for (Case nc : newCases){
    for (Equipment_Maintenance_Item__c clonedListItem :
closedCases.get(nc.ParentId).Equipment_Maintenance_Items__r){
        Equipment_Maintenance_Item__c item = clonedListItem.clone();
        item.Maintenance_Request__c = nc.Id;
        clonedList.add(item);
    }
}
insert clonedList;
}
}
}

```

MaintenanceRequest Code :

```

trigger MaintenanceRequest on Case (before update, after update) {
    if(Trigger.isUpdate && Trigger.isAfter){
        MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);
    }
}

```

6. TestCallout Logic

WarehouseCalloutServiceCode :

```

public with sharing class WarehouseCalloutService implements Queueable {
    private static final String WAREHOUSE_URL = 'https://th-superbadge-
apex.herokuapp.com/equipment';

```

//Write a class that makes a REST callout to an external warehouse system to get a list of equipment that needs to be updated.

//The callout's JSON response returns the equipment records that you upsert in Salesforce.

```

@future(callout=true)
public static void runWarehouseEquipmentSync(){
    System.debug('go into runWarehouseEquipmentSync');
    Http http = new Http();
    HttpRequest request = new HttpRequest();

    request.setEndpoint(WAREHOUSE_URL);
    request.setMethod('GET');
    HttpResponse response = http.send(request);

    List<Product2> product2List = new List<Product2>();
    System.debug(response.getStatusCode());
    if (response.getStatusCode() == 200){
        List<Object> jsonResponse =
(List<Object>)JSON.deserializeUntyped(response.getBody());
        System.debug(response.getBody());
    }
}

```

```

//class maps the following fields:
//warehouse SKU will be external ID for identifying which equipment records to
update within Salesforce
for (Object jR : jsonResponse){
    Map<String,Object> mapJson = (Map<String,Object>)jR;
    Product2 product2 = new Product2();
    //replacement part (always true),
    product2.Replacement_Part__c = (Boolean) mapJson.get('replacement');
    //cost
    product2.Cost__c = (Integer) mapJson.get('cost');
    //current inventory
    product2.Current_Inventory__c = (Double) mapJson.get('quantity');
    //lifespan
    product2.Lifespan_Months__c = (Integer) mapJson.get('lifespan');
    //maintenance cycle
    product2.Maintenance_Cycle__c = (Integer)
mapJson.get('maintenanceperiod');
    //warehouse SKU
    product2.Warehouse_SKU__c = (String) mapJson.get('sku');

    product2.Name = (String) mapJson.get('name');
    product2.ProductCode = (String) mapJson.get('_id');
    product2List.add(product2);
}

if (product2List.size() > 0){
    upsert product2List;
    System.debug('Your equipment was synced with the warehouse one');
}
}
}

public static void execute (QueueableContext context){
    System.debug('start runWarehouseEquipmentSync');
    runWarehouseEquipmentSync();
    System.debug('end runWarehouseEquipmentSync');
}

```

```
}
```

WarehouseCalloutServiceTest.apxc :-

```
@IsTest
private class WarehouseCalloutServiceTest {
    // implement your mock callout test here
    @isTest
    static void testWarehouseCallout() {
        test.startTest();
        test.setMock(HttpCalloutMock.class, new WarehouseCalloutServiceMock());
        WarehouseCalloutService.execute(null);
        test.stopTest();

        List<Product2> product2List = new List<Product2>();
        product2List = [SELECT ProductCode FROM Product2];

        System.assertEquals(3, product2List.size());
        System.assertEquals('55d66226726b611100aaf741',
product2List.get(0).ProductCode);
        System.assertEquals('55d66226726b611100aaf742',
product2List.get(1).ProductCode);
        System.assertEquals('55d66226726b611100aaf743',
product2List.get(2).ProductCode);
    }
}
```

WarehouseCalloutServiceMock Code :

```
@IsTest
global class WarehouseCalloutServiceMock implements HttpCalloutMock {
    // implement http mock callout
    global static HttpResponse respond(HttpRequest request) {

        HttpResponse response = new HttpResponse();
        response.setHeader('Content-Type', 'application/json');
```

```

response.setBody([{"_id":"55d66226726b611100aaf741","replacement":false,"quantity":5
,"name":"Generator 1000
kW","maintenanceperiod":365,"lifespan":120,"cost":5000,"sku":"100003"},{"_id":"55d66226
726b611100aaf742","replacement":true,"quantity":183,"name":"Cooling
Fan","maintenanceperiod":0,"lifespan":0,"cost":300,"sku":"100004"},{"_id":"55d66226726b6
11100aaf743","replacement":true,"quantity":143,"name":"Fuse
20A","maintenanceperiod":0,"lifespan":0,"cost":22,"sku":"100005"}]);
    response.setStatusCode(200);

    return response;
}
}

```

7. Test Scheduling Logic

WarehouseSyncSchedule Code :

```

global with sharing class WarehouseSyncSchedule implements Schedulable {
    // implement scheduled code here
    global void execute (SchedulableContext ctx){
        System.enqueueJob(new WarehouseCalloutService());
    }
}

```

WarehouseSyncScheduleTest Code

```

@isTest
public with sharing class WarehouseSyncScheduleTest {
    // implement scheduled code here
    //
    @isTest static void test() {
        String scheduleTime = '00 00 00 * * ? *';
    }
}

```

```
Test.startTest();
Test.setMock(HttpCalloutMock.class, new WarehouseCalloutServiceMock());
String jobId = System.schedule('Warehouse Time to Schedule to test',
scheduleTime, new WarehouseSyncSchedule());
CronTrigger c = [SELECT State FROM CronTrigger WHERE Id =: jobId];
System.assertEquals('WAITING', String.valueOf(c.State), 'JobId does not match');

Test.stopTest();
}
}
```