Salesforce Developer Catalyst

AccountManager:

```
@RestResource(urlMapping='/Accounts/*/contacts')
global with sharing class AccountManager {
  @HttpGet
  global static Account getAccount() {
    RestRequest request = RestContext.request;
    String accountld =
request.requestURI.substringBetween('/Accounts/','/contacts');
    Account result = [SELECT Id, Name, (SELECT Id, Name from contacts) from
Account where Id=:accountId];
                return result;
 }
}
AccountManagerTest:
@IsTest
private class AccountManagerTest {
  @isTest static void testGetContactsByAccountId() {
    Id recordId = createTestRecord();
    // Set up a test request
    RestRequest request = new RestRequest();
    request.requestUri =
'https://yourInstance.salesforce.com/services/apexrest/Accounts/'+recordId+'/cont
acts';
    request.httpMethod = 'GET';
    RestContext.request = request;
    // Call the method to test
    Account this Account = Account Manager.get Account();
    // Verify results
    System.assert(thisAccount != null);
    System.assertEquals('Test record', thisAccount.Name);
  }
```

```
// Helper method
  static Id createTestRecord() {
    // Create test record
    Account accountTest = new Account(
      Name='Test record');
      insert accountTest;
    Contact contactTest = new Contact(
    FirstName = 'John',
    LastName = 'Doe',
    AccountId = accountTest.Id);
    insert contactTest;
    return accountTest.ld;
 }
}
AccountProcessor:
public class AccountProcessor {
@future
  public static void countContacts(List<Id> accountIds){
    List<Account> accountsToUpdate = new List<Account>();
    List<Account> account = [Select Id, Name, (Select Id from Contacts) from
Account Where Id in :accountIds];
    For(Account acc:account){
      List<Contact> contactList =acc.Contacts;
      acc.Number_of_contacts__c = contactList.size();
      accountsToUpdate.add(acc);
    }
    update accountsToUpdate;
 }
```

AccountProcessorTest:

```
@IsTest
public class AccountProcessorTest {
@lsTest
  private static void testCountContacts(){
    Account newAccount = new Account(Name='Test Account');
    insert newAccount;
    Contact newContact1 = new
Contact(FirstName='John',LastName='Doe',AccountId = newAccount.Id);
    insert newContact1:
    Contact newContact2 = new
Contact(FirstName='John',LastName='Doe',AccountId = newAccount.Id);
    insert newContact2;
    List<ld> accountlds = new List<ld>();
    accountIds.add(newAccount.Id);
    Test.startTest();
    AccountProcessor.countContacts(accountIds);
    Test.stopTest();
  }
}
AddPrimaryContact:
public class AddPrimaryContact implements Queueable{
     private Contact con;
     private String state;
     public AddPrimaryContact(Contact con, String state){
      this.con = con;
      this.state = state;
    }
     public void execute (QueueableContext context) {
      List<Account> accounts = [Select Id, Name, (Select FirstName, LastName, Id
from contacts)
```

```
from Account where BillingState = :state Limit 200];
      List<Contact > primaryContacts = new List<Contact>();
      for (Account acc:accounts) {
      Contact c = con.clone();
      c.AccountId = acc.Id;
      primaryContacts.add(c);
   }
}
AddPrimaryContactTest:
@isTest
public class AddPrimaryContactTest {
    static testmethod void testQueueable() {
      List<Account> testAccounts = new List<Account>();
      for(Integer i=0;i<50; i++) {
        testAccounts.add(new Account (Name='Account '+i, BillingState='CA'));
       }
       for (Integer j=0; j<50; j++){
           testAccounts.add(new Account (Name = ' Account '+j, BillingState=
'NY'));
        insert testAccounts;
         Contact testContact = new Contact(FirstName = 'John', LastName = 'Doe');
         insert testContact;
         AddPrimaryContact addit = new addPrimaryContact(testContact, 'CA');
         Test.startTest();
         system.enqueueJob(addit);
         Test.stopTest();
         system.assertEquals(50,[select count() from Contact where accountld in
(select Id from Account where Billingstate='CA')]);
      }
```

```
}
AnimalLocator:
public class AnimalLocator {
  public static String getAnimalNameById(Integer ID) {
    String animal = '';
    Http http = new Http();
    HttpRequest request = new HttpRequest();
    String s = string.valueOf(ID);
    request.setEndpoint('https://th-apex-http-callout.herokuapp.com/animals/'+ ID);
    request.setMethod('GET');
    HttpResponse response = http.send(request);
    Map<String,Object> animals = new Map<String,Object>();
    if(response.getStatusCode() == 200) {
      Map<String,Object> results =
(Map<String,Object>)JSON.deserializeUntyped(response.getBody());
      animals = (Map<String,Object>) results.get('animal');
      animal = String.valueOf(animals.get('name'));
    } else {
      system.debug(response.getBody());
    }
    Return animal;
```

}

}

AnimalLocatorMock:

```
@isTest
global class AnimalLocatorMock implements HttpCalloutMock {
  // Implement this interface method
  global HTTPResponse respond(HTTPRequest request) {
    // Create a fake response
    HttpResponse response = new HttpResponse();
    response.setHeader('Content-Type', 'application/json');
    response.setBody('{"animal":{"id":1,"name":"chicken","eats":"chicken
food","says":"cluck cluck"}}');
    response.setStatusCode(200);
    return response;
 }
}
AnimalLocatorTest:
@isTest
private class AnimalLocatorTest {
  @isTest
  static void testGetCallout() {
    Test.setMock(HttpCalloutMock.class, new AnimalLocatorMock());
    String animalName = AnimalLocator.getAnimalNameByld(1);
    system.debug('AnimalName : ' + animalName);
    System.assertEquals(animalName, 'chicken');
  }
}
AsyncParkService:
public class AsyncParkService {
  public class byCountryResponseFuture extends System.WebServiceCalloutFuture {
    public String[] getValue() {
      ParkService.byCountryResponse response =
```

```
(ParkService.byCountryResponse)System.WebServiceCallout.endInvoke(this);
      return response.return_x;
    }
  }
  public class AsyncParksImplPort {
    public String endpoint_x = 'https://th-apex-soap-
service.herokuapp.com/service/parks';
    public Map<String,String> inputHttpHeaders_x;
    public String clientCertName_x;
    public Integer timeout_x;
    private String[] ns_map_type_info = new String[]{'http://parks.services/',
'ParkService'};
    public AsyncParkService.byCountryResponseFuture
beginByCountry(System.Continuation continuation,String arg0) {
      ParkService.byCountry request_x = new ParkService.byCountry();
      request_x.arg0 = arg0;
      return (AsyncParkService.byCountryResponseFuture)
System.WebServiceCallout.beginInvoke(
       this.
       request_x,
       AsyncParkService.byCountryResponseFuture.class,
       continuation,
       new String[]{endpoint_x,
       'http://parks.services/',
       'byCountry',
       'http://parks.services/',
       'byCountryResponse',
       'ParkService.byCountryResponse'}
      );
    }
  }
}
ContactsTodayController:
public class ContactsTodayController {
  @AuraEnabled
  public static List<Contact> getContactsForToday() {
```

List<Task> my_tasks = [SELECT Id, Subject, Whold FROM Task WHERE OwnerId = :UserInfo.getUserId() AND IsClosed = false AND Whold != null];

List<Event> my_events = [SELECT Id, Subject, Whold FROM Event WHERE OwnerId = :UserInfo.getUserId() AND StartDateTime >= :Date.today() AND Whold != null];

List<Case> my_cases = [SELECT ID, ContactId, Status, Subject FROM Case WHERE OwnerId = :UserInfo.getUserId() AND IsClosed = false AND ContactId != null];

```
Set<Id> contactIds = new Set<Id>();
for(Task tsk : my_tasks) {
   contactIds.add(tsk.Whold);
}
for(Event evt : my_events) {
   contactIds.add(evt.Whold);
}
for(Case cse : my_cases) {
   contactIds.add(cse.ContactId);
}
```

List<Contact> contacts = [SELECT Id, Name, Phone, Description FROM Contact WHERE Id IN :contactIds];

```
for(Contact c : contacts) {
    c.Description = ";
    for(Task tsk : my_tasks) {
        if(tsk.Whold == c.ld) {
            c.Description += 'Because of Task ""+tsk.Subject+""\n';
        }
    }
    for(Event evt : my_events) {
        if(evt.Whold == c.ld) {
            c.Description += 'Because of Event ""+evt.Subject+""\n';
        }
    }
    for(Case cse : my_cases) {
        if(cse.ContactId == c.ld) {
            c.Description += 'Because of Case ""+cse.Subject+""\n';
        }
    }
}
```

```
}
    return contacts;
  }
}
ContactsTodayControllerTest:
@lsTest
public class ContactsTodayControllerTest {
  @IsTest
  public static void testGetContactsForToday() {
    Account acct = new Account(
      Name = 'Test Account'
    insert acct;
    Contact c = new Contact(
      AccountId = acct.Id,
      FirstName = 'Test',
      LastName = 'Contact'
    );
    insert c;
    Task tsk = new Task(
      Subject = 'Test Task',
      Whold = c.ld,
      Status = 'Not Started'
    );
    insert tsk;
    Event evt = new Event(
      Subject = 'Test Event',
      Whold = c.Id,
      StartDateTime = Date.today().addDays(5),
      EndDateTime = Date.today().addDays(6)
    );
```

```
insert evt;
  Case cse = new Case(
    Subject = 'Test Case',
    ContactId = c.Id
  );
  insert cse:
  List<Contact> contacts = ContactsTodayController.getContactsForToday();
  System.assertEquals(1, contacts.size());
  System.assert(contacts[0].Description.containsIgnoreCase(tsk.Subject));
  System.assert(contacts[0].Description.containsIgnoreCase(evt.Subject));
  System.assert(contacts[0].Description.containsIgnoreCase(cse.Subject));
}
@IsTest
public static void testGetNoContactsForToday() {
  Account acct = new Account(
    Name = 'Test Account'
  );
  insert acct;
  Contact c = new Contact(
    AccountId = acct.Id,
    FirstName = 'Test',
    LastName = 'Contact'
  );
  insert c;
  Task tsk = new Task(
    Subject = 'Test Task',
    Whold = c.ld,
    Status = 'Completed'
  );
  insert tsk;
  Event evt = new Event(
    Subject = 'Test Event',
```

```
Whold = c.Id,
      StartDateTime = Date.today().addDays(-6),
      EndDateTime = Date.today().addDays(-5)
    );
    insert evt;
    Case cse = new Case(
      Subject = 'Test Case',
      ContactId = c.Id,
      Status = 'Closed'
    );
    insert cse;
    List<Contact> contacts = ContactsTodayController.getContactsForToday();
    System.assertEquals(0, contacts.size());
 }
}
DailyLeadProcessor:
global class DailyLeadProcessor implements Schedulable{
  global void execute(SchedulableContext ctx){
    List<Lead> leads = [SELECT Id, LeadSource FROM Lead WHERE LeadSource = "];
    if(leads.size() > 0){
      List<Lead> newLeads = new List<Lead>();
      for(Lead lead : leads){
        lead.LeadSource = 'DreamForce';
        newLeads.add(lead);
      }
      update newLeads;
    }
 }
}
```

DailyLeadProcessorTest

```
@isTest
private class DailyLeadProcessorTest{
  //Seconds Minutes Hours Day_of_month Month Day_of_week optional_year
  public static String CRON_EXP = '0 0 0 2 6 ? 2022';
  static testmethod void testScheduledJob(){
    List<Lead> leads = new List<Lead>();
    for(Integer i = 0; i < 200; i++){
      Lead lead = new Lead(LastName = 'Test ' + i, LeadSource = ", Company = 'Test
Company ' + i, Status = 'Open - Not Contacted');
      leads.add(lead);
    }
    insert leads;
    Test.startTest();
    // Schedule the test job
    String jobId = System.schedule('Update LeadSource to DreamForce', CRON_EXP,
new DailyLeadProcessor());
    // Stopping the test will run the job synchronously
    Test.stopTest();
  }
}
NewCaseListController:
public class NewCaseListController {
  public List<Case> getNewCases(){
    List<Case> filterList = [Select Id, CaseNumber from case where status = 'New'];
    return filterList;
  }
}
```

PagedResult:

```
public with sharing class PagedResult {
  @AuraEnabled
  public Integer pageSize { get; set; }
  @AuraEnabled
  public Integer pageNumber { get; set; }
  @AuraEnabled
  public Integer totalItemCount { get; set; }
  @AuraEnabled
  public Object[] records { get; set; }
}
ParkLocator:
public class ParkLocator {
  public static string[] country(String country) {
    parkService.parksImplPort park = new parkService.parksImplPort();
    return park.byCountry(country);
 }
}
ParkLocatorTest:
@isTest
private class ParkLocatorTest {
  @isTest static void testCallout() {
    // This causes a fake response to be generated
    Test.setMock(WebServiceMock.class, new ParkServiceMock());
    // Call the method that invokes a callout
    //Double x = 1.0;
    //Double result = AwesomeCalculator.add(x, y);
    String country = 'Germany';
    String[] result = ParkLocator.Country(country);
```

```
// Verify that a fake result is returned
    System.assertEquals(new List<String>{'Hamburg Wadden Sea National Park',
'Hainich National Park', 'Bavarian Forest National Park'}, result);
}
ParkService:
public class ParkService {
  public class byCountryResponse {
    public String[] return_x;
    private String[] return_x_type_info = new
String[]{'return','http://parks.services/',null,'0','-1','false'};
    private String[] apex_schema_type_info = new
String[]{'http://parks.services/','false','false'};
    private String[] field_order_type_info = new String[]{'return_x'};
  }
  public class byCountry {
    public String arg0;
    private String[] arg0_type_info = new
String[]{'arg0','http://parks.services/',null,'0','1','false'};
    private String[] apex_schema_type_info = new
String[]{'http://parks.services/','false','false'};
    private String[] field_order_type_info = new String[]{'arg0'};
  }
  public class ParksImplPort {
    public String endpoint_x = 'https://th-apex-soap-
service.herokuapp.com/service/parks';
    public Map<String,String> inputHttpHeaders_x;
    public Map<String,String> outputHttpHeaders_x;
    public String clientCertName_x;
    public String clientCert_x;
    public String clientCertPasswd_x;
    public Integer timeout_x;
    private String[] ns_map_type_info = new String[]{'http://parks.services/',
'ParkService'};
    public String[] byCountry(String arg0) {
       ParkService.byCountry request_x = new ParkService.byCountry();
```

```
request_x.arg0 = arg0;
      ParkService.byCountryResponse response_x;
      Map<String, ParkService.byCountryResponse> response_map_x = new
Map<String, ParkService.byCountryResponse>();
      response_map_x.put('response_x', response_x);
      WebServiceCallout.invoke(
       this.
       request_x,
       response_map_x,
       new String[]{endpoint_x,
       'http://parks.services/',
       'byCountry',
       'http://parks.services/',
       'byCountryResponse',
       'ParkService.byCountryResponse'}
      );
      response_x = response_map_x.get('response_x');
      return response_x.return_x;
    }
  }
}
ParkServiceMock:
@isTest
global class ParkServiceMock implements WebServiceMock {
 global void dolnvoke(
      Object stub,
      Object request,
      Map<String, Object> response,
      String endpoint,
      String soapAction,
      String requestName,
      String responseNS,
      String responseName,
      String responseType) {
    // start - specify the response you want to send
    parkService.byCountryResponse response_x = new
parkService.byCountryResponse();
```

```
response_x.return_x = new List<String>{'Hamburg Wadden Sea National Park',
'Hainich National Park', 'Bavarian Forest National Park');
    //calculatorServices.doAddResponse response_x = new
calculatorServices.doAddResponse();
    //response_x.return_x = 3.0;
    // end
    response.put('response_x', response_x);
 }
}
PropertyController:
public with sharing class PropertyController {
  private static final Decimal DEFAULT_MAX_PRICE = 9999999;
  private static final Integer DEFAULT_PAGE_SIZE = 9;
  /**
  * Endpoint that retrieves a paged and filtered list of properties
  * @param searchKey String used for searching on property title, city and tags
  * @param maxPrice Maximum price
  * @param minBedrooms Minimum number of bedrooms
  * @param minBathrooms Minimum number of bathrooms
  * @param pageSize Number of properties per page
  * @param pageNumber Page number
  * @return PagedResult object holding the paged and filtered list of properties
  */
  @AuraEnabled(cacheable=true)
  public static PagedResult getPagedPropertyList(
    String searchKey,
    Decimal maxPrice,
    Integer minBedrooms,
    Integer minBathrooms,
    Integer pageSize,
    Integer pageNumber
  ) {
    // Normalize inputs
    Decimal safeMaxPrice = (maxPrice == null
      ? DEFAULT_MAX_PRICE
      : maxPrice);
```

```
Integer safeMinBedrooms = (minBedrooms == null ? 0 : minBedrooms);
Integer safeMinBathrooms = (minBathrooms == null ? 0 : minBathrooms);
Integer safePageSize = (pageSize == null
  ? DEFAULT_PAGE_SIZE
  : pageSize);
Integer safePageNumber = (pageNumber == null ? 1 : pageNumber);
String searchPattern = '%' + searchKey + '%';
Integer offset = (safePageNumber - 1) * safePageSize;
PagedResult result = new PagedResult();
result.pageSize = safePageSize;
result.pageNumber = safePageNumber;
result.totalItemCount = [
  SELECT COUNT()
  FROM Property_c
  WHERE
    (Name LIKE: searchPattern
    OR City_c LIKE :searchPattern
    OR Tags_c LIKE :searchPattern)
    AND Price_c <= :safeMaxPrice
    AND Beds_c >= :safeMinBedrooms
    AND Baths_c >= :safeMinBathrooms
];
result.records = [
  SELECT
    ld,
    Address__c,
    City__c,
    State__c,
    Description__c,
    Price__c,
    Baths_c.
    Beds__c,
    Thumbnail__c,
    Location__Latitude__s,
    Location__Longitude__s
  FROM Property_c
  WHERE
    (Name LIKE: searchPattern
```

```
OR City_c LIKE :searchPattern
      OR Tags_c LIKE :searchPattern)
      AND Price__c <= :safeMaxPrice
      AND Beds__c >= :safeMinBedrooms
      AND Baths_c >= :safeMinBathrooms
    WITH SECURITY_ENFORCED
    ORDER BY Price c
    LIMIT :safePageSize
    OFFSET:offset
 ];
  return result;
}
/**
* Endpoint that retrieves pictures associated with a property
* @param propertyld Property Id
* @return List of ContentVersion holding the pictures
*/
@AuraEnabled(cacheable=true)
public static List<ContentVersion> getPictures(Id propertyId) {
  List<ContentDocumentLink> links = [
    SELECT Id, LinkedEntityId, ContentDocumentId
    FROM ContentDocumentLink
    WHERE
      LinkedEntityId = :propertyId
      AND ContentDocument.FileType IN ('PNG', 'JPG', 'GIF')
    WITH SECURITY_ENFORCED
  1:
  if (links.isEmpty()) {
    return null;
  }
  Set<Id> contentIds = new Set<Id>();
  for (ContentDocumentLink link: links) {
    contentIds.add(link.ContentDocumentId);
  }
  return [
```

```
SELECT Id, Title
      FROM ContentVersion
      WHERE ContentDocumentId IN :contentIds AND IsLatest = TRUE
      WITH SECURITY_ENFORCED
      ORDER BY CreatedDate
    ];
  }
}
AccountAddressTrigger:
trigger AccountAddressTrigger on Account (before insert,before update) {
  for (account account:trigger.new){
    if(account.Match_Billing_Address__c == true){
      account.ShippingPostalCode = account.BillingPostalCode;
    }
 }
}
ClosedOpportunityTrigger:
trigger ClosedOpportunityTrigger on Opportunity (before insert,after update) {
  list<Task> tasklist = new list<Task>();
  for(opportunity opp: trigger.new){
    if(opp.stagename == 'closed won'){
      tasklist.add(new task(subject ='follow up test task',whatid =opp.Id));
    }
  if (tasklist.size()>0){
    insert tasklist;
  }
}
RestrictContactByName:
trigger RestrictContactByName on Contact (before insert, before update) {
```

```
For (Contact c : Trigger.New) {
             if(c.LastName == 'INVALIDNAME') { //invalidname is invalid
                   c.AddError('The Last Name "+c.LastName+" is not allowed for
DML');
            }
      }
}
CreateDefaultData:
public with sharing class CreateDefaultData{
  Static Final String TYPE_ROUTINE_MAINTENANCE = 'Routine Maintenance';
  //gets value from custom metadata How_We_Roll_Settings__mdt to know if
Default data was created
  @AuraEnabled
  public static Boolean isDataCreated() {
    How_We_Roll_Settings__c customSetting =
How_We_Roll_Settings__c.getOrgDefaults();
    return customSetting.ls_Data_Created__c;
  }
  //creates Default Data for How We Roll application
  @AuraEnabled
  public static void createDefaultData(){
    List<Vehicle_c> vehicles = createVehicles();
    List<Product2> equipment = createEquipment();
    List<Case> maintenanceRequest = createMaintenanceRequest(vehicles);
    List<Equipment_Maintenance_Item__c> joinRecords =
createJoinRecords(equipment, maintenanceRequest);
    updateCustomSetting(true);
  }
  public static void updateCustomSetting(Boolean isDataCreated){
    How_We_Roll_Settings__c customSetting =
```

```
How_We_Roll_Settings__c.getOrgDefaults();
    customSetting.ls_Data_Created__c = isDataCreated;
    upsert customSetting;
  }
  public static List<Vehicle__c> createVehicles(){
    List<Vehicle_c> vehicles = new List<Vehicle_c>();
    vehicles.add(new Vehicle_c(Name = 'Toy Hauler RV', Air_Conditioner_c = true,
Bathrooms_c = 1, Bedrooms_c = 1, Model_c = 'Toy Hauler RV'));
    vehicles.add(new Vehicle__c(Name = 'Travel Trailer RV', Air_Conditioner__c =
true, Bathrooms_c = 2, Bedrooms_c = 2, Model_c = 'Travel Trailer RV'));
    vehicles.add(new Vehicle__c(Name = 'Teardrop Camper', Air_Conditioner__c =
true, Bathrooms_c = 1, Bedrooms_c = 1, Model_c = 'Teardrop Camper'));
    vehicles.add(new Vehicle_c(Name = 'Pop-Up Camper', Air_Conditioner_c =
true, Bathrooms_c = 1, Bedrooms_c = 1, Model_c = 'Pop-Up Camper'));
    insert vehicles;
    return vehicles;
  }
  public static List<Product2> createEquipment(){
    List<Product2> equipments = new List<Product2>();
    equipments.add(new Product2(Warehouse_SKU__c =
'55d66226726b611100aaf741',name = 'Generator 1000 kW', Replacement_Part__c =
true,Cost_c = 100,Maintenance_Cycle_c = 100));
    equipments.add(new Product2(name = 'Fuse 20B',Replacement_Part__c =
true,Cost_c = 1000, Maintenance_Cycle_c = 30 ));
    equipments.add(new Product2(name = 'Breaker 13C',Replacement_Part__c =
true,Cost_c = 100, Maintenance_Cycle_c = 15));
    equipments.add(new Product2(name = 'UPS 20 VA',Replacement_Part__c =
true,Cost_c = 200 , Maintenance_Cycle_c = 60));
    insert equipments;
    return equipments;
 }
  public static List<Case> createMaintenanceRequest(List<Vehicle_c> vehicles){
    List<Case> maintenanceRequests = new List<Case>();
    maintenanceRequests.add(new Case(Vehicle__c = vehicles.get(1).ld, Type =
TYPE_ROUTINE_MAINTENANCE, Date_Reported__c = Date.today()));
    maintenanceRequests.add(new Case(Vehicle__c = vehicles.get(2).ld, Type =
```

```
TYPE_ROUTINE_MAINTENANCE, Date_Reported__c = Date.today()));
    insert maintenanceRequests;
    return maintenanceRequests;
 }
  public static List<Equipment_Maintenance_Item__c>
createJoinRecords(List<Product2> equipment, List<Case> maintenanceRequest){
    List<Equipment_Maintenance_Item__c> joinRecords = new
List<Equipment_Maintenance_Item__c>();
    joinRecords.add(new Equipment_Maintenance_Item__c(Equipment__c =
equipment.get(0).ld, Maintenance_Request__c = maintenanceRequest.get(0).ld));
    joinRecords.add(new Equipment_Maintenance_Item__c(Equipment__c =
equipment.get(1).ld, Maintenance_Request__c = maintenanceRequest.get(0).ld));
    joinRecords.add(new Equipment_Maintenance_Item__c(Equipment__c =
equipment.get(2).ld, Maintenance_Request__c = maintenanceRequest.get(0).ld));
    joinRecords.add(new Equipment_Maintenance_Item__c(Equipment__c =
equipment.get(0).ld, Maintenance_Request__c = maintenanceRequest.get(1).ld));
    joinRecords.add(new Equipment_Maintenance_Item__c(Equipment__c =
equipment.get(1).ld, Maintenance_Request__c = maintenanceRequest.get(1).ld));
    joinRecords.add(new Equipment_Maintenance_Item__c(Equipment__c =
equipment.get(2).ld, Maintenance_Request__c = maintenanceRequest.get(1).ld));
    insert joinRecords;
    return joinRecords;
 }
CreateDefaultDataTest:
@isTest
private class CreateDefaultDataTest {
  @isTest
  static void createData_test(){
    Test.startTest();
    CreateDefaultData.createDefaultData();
    List<Vehicle_c> vehicles = [SELECT Id FROM Vehicle_c];
    List<Product2> equipment = [SELECT Id FROM Product2];
    List<Case> maintenanceRequest = [SELECT Id FROM Case];
    List<Equipment_Maintenance_Item__c> joinRecords = [SELECT Id FROM
Equipment_Maintenance_Item__c];
```

```
System.assertEquals(4, vehicles.size(), 'There should have been 4 vehicles
created');
    System.assertEquals(4, equipment.size(), 'There should have been 4 equipment
    System.assertEquals(2, maintenanceRequest.size(), 'There should have been 2
maintenance request created');
    System.assertEquals(6, joinRecords.size(), 'There should have been 6
equipment maintenance items created');
  }
  @isTest
  static void updateCustomSetting_test(){
    How_We_Roll_Settings__c customSetting =
How_We_Roll_Settings__c.getOrgDefaults();
    customSetting.ls_Data_Created__c = false;
    upsert customSetting;
    System.assertEquals(false, CreateDefaultData.isDataCreated(), 'The custom
setting How_We_Roll_Settings__c.ls_Data_Created__c should be false');
    customSetting.ls_Data_Created__c = true;
    upsert customSetting;
    System.assertEquals(true, CreateDefaultData.isDataCreated(), 'The custom
setting How_We_Roll_Settings__c.ls_Data_Created__c should be true');
 }
}
MaintenanceRequestHelper:
public with sharing class MaintenanceRequestHelper {
  public static void updateworkOrders(List<Case> updWorkOrders, Map<Id,Case>
nonUpdCaseMap) {
    Set<Id> validIds = new Set<Id>();
    For (Case c: updWorkOrders){
```

```
if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
        if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
          validIds.add(c.Id);
        }
      }
    }
    if (!validIds.isEmpty()){
      List<Case> newCases = new List<Case>();
      Map<Id,Case> closedCasesM = new Map<Id,Case>([SELECT Id, Vehicle__c,
Equipment_c, Equipment_r.Maintenance_Cycle_c,(SELECT
Id,Equipment_c,Quantity_c FROM Equipment_Maintenance_Items_r)
                              FROM Case WHERE Id IN :validIds]);
      Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
      AggregateResult[] results = [SELECT Maintenance_Request__c,
MIN(Equipment_r.Maintenance_Cycle__c)cycle FROM
Equipment_Maintenance_Item_c WHERE Maintenance_Request_c IN: ValidIds
GROUP BY Maintenance_Request__c];
    for (AggregateResult ar : results){
      maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal)
ar.get('cycle'));
    }
      for(Case cc : closedCasesM.values()){
        Case nc = new Case (
          ParentId = cc.Id,
        Status = 'New',
          Subject = 'Routine Maintenance',
          Type = 'Routine Maintenance',
          Vehicle_c = cc.Vehicle_c,
          Equipment_c = cc. Equipment_c,
          Origin = 'Web',
          Date_Reported__c = Date.Today()
        );
        If (maintenanceCycles.containskey(cc.ld)){
```

```
nc.Date_Due__c = Date.today().addDays((Integer)
maintenanceCycles.get(cc.ld));
        }
        newCases.add(nc);
      }
     insert newCases;
      List<Equipment_Maintenance_Item__c> clonedWPs = new
List<Equipment_Maintenance_Item__c>();
      for (Case nc : newCases){
        for (Equipment_Maintenance_Item__c wp:
closedCasesM.get(nc.ParentId).Equipment_Maintenance_Items__r){
          Equipment_Maintenance_Item__c wpClone = wp.clone();
           wpClone.Maintenance_Request__c = nc.ld;
           ClonedWPs.add(wpClone);
        }
      insert ClonedWPs:
    }
  }
}
class MaintenanceRequestHelperTest:
@istest
public with sharing class MaintenanceRequestHelperTest {
  private static final string STATUS_NEW = 'New';
  private static final string WORKING = 'Working';
  private static final string CLOSED = 'Closed';
  private static final string REPAIR = 'Repair';
  private static final string REQUEST_ORIGIN = 'Web';
  private static final string REQUEST_TYPE = 'Routine Maintenance';
  private static final string REQUEST_SUBJECT = 'Testing subject';
  PRIVATE STATIC Vehicle_c createVehicle(){
    Vehicle_c Vehicle = new Vehicle_C(name = 'SuperTruck');
```

```
return Vehicle;
  }
  PRIVATE STATIC Product2 createEq(){
    product2 equipment = new product2(name = 'SuperEquipment',
                     lifespan_months__C = 10,
                     maintenance_cycle__C = 10,
                     replacement_part__c = true);
    return equipment;
  }
  PRIVATE STATIC Case createMaintenanceRequest(id vehicleId, id equipmentId){
    case cs = new case(Type=REPAIR,
             Status=STATUS_NEW,
             Origin=REQUEST_ORIGIN,
             Subject=REQUEST_SUBJECT,
             Equipment_c=equipmentId,
             Vehicle_c=vehicleId);
    return cs:
  }
  PRIVATE STATIC Equipment_Maintenance_Item__c createWorkPart(id
equipmentId,id requestId){
    Equipment_Maintenance_Item__c wp = new
Equipment_Maintenance_Item__c(Equipment__c = equipmentId,
                                        Maintenance_Request__c = requestId);
    return wp;
  }
  @istest
  private static void testMaintenanceRequestPositive(){
    Vehicle__c vehicle = createVehicle();
    insert vehicle:
    id vehicleId = vehicle.Id;
    Product2 equipment = createEq();
    insert equipment;
    id equipmentId = equipment.Id;
```

```
case somethingToUpdate = createMaintenanceRequest(vehicleId,equipmentId);
    insert somethingToUpdate;
    Equipment_Maintenance_Item__c workP =
createWorkPart(equipmentId,somethingToUpdate.id);
    insert workP;
    test.startTest();
    somethingToUpdate.status = CLOSED;
    update somethingToUpdate;
    test.stopTest();
    Case newReq = [Select id, subject, type, Equipment_c, Date_Reported_c,
Vehicle_c, Date_Due_c
           from case
           where status =:STATUS_NEW];
    Equipment_Maintenance_Item__c workPart = [select id
                         from Equipment_Maintenance_Item__c
                         where Maintenance_Request__c =:newReq.Id];
    system.assert(workPart != null);
    system.assert(newReq.Subject != null);
    system.assertEquals(newReg.Type, REQUEST_TYPE);
    SYSTEM.assertEquals(newReq.Equipment_c, equipmentId);
    SYSTEM.assertEquals(newReq.Vehicle_c, vehicleId);
    SYSTEM.assertEquals(newReq.Date_Reported__c, system.today());
  }
  @istest
  private static void testMaintenanceRequestNegative(){
    Vehicle__C vehicle = createVehicle();
    insert vehicle:
    id vehicleId = vehicle.Id;
    product2 equipment = createEq();
    insert equipment;
    id equipmentId = equipment.Id;
    case emptyReg = createMaintenanceRequest(vehicleId,equipmentId);
```

```
insert emptyReq;
    Equipment_Maintenance_Item_c workP = createWorkPart(equipmentId,
emptyReq.ld);
    insert workP;
    test.startTest();
    emptyReq.Status = WORKING;
    update emptyReq;
    test.stopTest();
    list<case> allRequest = [select id
                  from casel;
    Equipment_Maintenance_Item__c workPart = [select id
                           from Equipment_Maintenance_Item__c
                           where Maintenance_Request__c = :emptyReq.Id];
    system.assert(workPart != null);
    system.assert(allRequest.size() == 1);
  }
  @istest
  private static void testMaintenanceRequestBulk(){
    list<Vehicle_C> vehicleList = new list<Vehicle_C>();
    list<Product2> equipmentList = new list<Product2>();
    list<Equipment_Maintenance_Item__c> workPartList = new
list<Equipment_Maintenance_Item__c>();
    list<case> requestList = new list<case>();
    list<id> oldRequestIds = new list<id>();
    for(integer i = 0; i < 300; i++){
     vehicleList.add(createVehicle());
      equipmentList.add(createEq());
    insert vehicleList;
    insert equipmentList;
    for(integer i = 0; i < 300; i++){
      requestList.add(createMaintenanceRequest(vehicleList.get(i).id,
```

```
equipmentList.get(i).id));
    insert requestList;
    for(integer i = 0; i < 300; i++){
      workPartList.add(createWorkPart(equipmentList.get(i).id,
requestList.get(i).id));
    }
    insert workPartList;
    test.startTest();
    for(case req : requestList){
      req.Status = CLOSED;
      oldRequestIds.add(req.ld);
    }
    update requestList;
    test.stopTest();
    list<case> allRequests = [select id
                  from case
                  where status =: STATUS_NEW];
    list<Equipment_Maintenance_Item__c> workParts = [select id
                               from Equipment_Maintenance_Item__c
                               where Maintenance_Request_c in: oldRequestIds];
    system.assert(allRequests.size() == 300);
  }
}
WarehouseCalloutService:
public with sharing class WarehouseCalloutService {
  private static final String WAREHOUSE_URL = 'https://th-superbadge-
apex.herokuapp.com/equipment';
  //@future(callout=true)
```

```
public static void runWarehouseEquipmentSync(){
    Http http = new Http();
    HttpRequest request = new HttpRequest();
    request.setEndpoint(WAREHOUSE_URL);
    request.setMethod('GET');
    HttpResponse response = http.send(request);
    List<Product2> warehouseEq = new List<Product2>();
    if (response.getStatusCode() == 200){
      List<Object> isonResponse =
(List<Object>)JSON.deserializeUntyped(response.getBody());
      System.debug(response.getBody());
      for (Object eq: jsonResponse){
        Map<String,Object> mapJson = (Map<String,Object>)eg;
        Product2 myEq = new Product2();
        myEq.Replacement_Part__c = (Boolean) mapJson.get('replacement');
        myEq.Name = (String) mapJson.get('name');
        myEq.Maintenance_Cycle__c = (Integer) mapJson.get('maintenanceperiod');
        myEq.Lifespan_Months__c = (Integer) mapJson.get('lifespan');
        myEq.Cost_c = (Decimal) mapJson.get('lifespan');
        myEq.Warehouse_SKU__c = (String) mapJson.get('sku');
        myEq.Current_Inventory_c = (Double) mapJson.get('quantity');
        warehouseEq.add(myEq);
      }
      if (warehouseEq.size() > 0){
        upsert warehouseEq;
        System.debug('Your equipment was synced with the warehouse one');
        System.debug(warehouseEq);
      }
 }
```

WarehouseCalloutServiceMock:

}

```
@isTest
global class WarehouseCalloutServiceMock implements HttpCalloutMock {
  // implement http mock callout
  global static HttpResponse respond(HttpRequest request){
    System.assertEquals('https://th-superbadge-apex.herokuapp.com/equipment',
request.getEndpoint());
    System.assertEquals('GET', request.getMethod());
    // Create a fake response
    HttpResponse response = new HttpResponse();
    response.setHeader('Content-Type', 'application/json');
response.setBody('[{"_id":"55d66226726b611100aaf741","replacement":false,"quantit
y":5,"name":"Generator 1000
kW","maintenanceperiod":365,"lifespan":120,"cost":5000,"sku":"100003"}]');
    response.setStatusCode(200);
    return response;
 }
}
WarehouseCalloutServiceTest:
@isTest
private class WarehouseCalloutServiceTest {
  @isTest
  static void testWareHouseCallout(){
    Test.startTest();
    // implement mock callout test here
    Test.setMock(HTTPCalloutMock.class, new WarehouseCalloutServiceMock());
    WarehouseCalloutService.runWarehouseEquipmentSync();
    Test.stopTest();
    System.assertEquals(1, [SELECT count() FROM Product2]);
 }
```

WarehouseSyncSchedule:

```
global with sharing class WarehouseSyncSchedule implements Schedulable{
  global void execute(SchedulableContext ctx){
    System.enqueueJob(new WarehouseCalloutService());
  }
}
WarehouseSyncScheduleTest:
@isTest
public class WarehouseSyncScheduleTest {
  @isTest static void WarehousescheduleTest(){
    String scheduleTime = '00 00 01 * * ?';
    Test.startTest();
    Test.setMock(HttpCalloutMock.class, new WarehouseCalloutServiceMock());
    String jobID=System.schedule('Warehouse Time To Schedule to Test',
scheduleTime, new WarehouseSyncSchedule());
    Test.stopTest();
    //Contains schedule information for a scheduled job. CronTrigger is similar to a
cron job on UNIX systems.
    // This object is available in API version 17.0 and later.
    CronTrigger a=[SELECT Id FROM CronTrigger where NextFireTime > today];
    System.assertEquals(jobID, a.Id,'Schedule');
 }
}
trigger MaintenanceRequest:
trigger MaintenanceRequest on Case (before update, after update) {
  if(Trigger.isUpdate && Trigger.isAfter){
    MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);
  }
}
```