Module: Apex Triggers

Get Started with Apex Triggers

```
trigger AccountAddressTrigger on Account (before insert, before update) {
    for(Account account:Trigger.New){
        if(account.Match_Billing_Address__c == True) {
            account.ShippingPostalCode = account.BillingPostalCode;
        }
    }
}
```

Bulk Apex Triggers

```
trigger ClosedOpportunityTrigger on Opportunity (after insert, after update) {
   List<Task> tasklist = new List<Task>();

for(Opportunity opp: Trigger.New){
   if(opp.StageName == 'Closed Won'){
     tasklist.add(new Task(Subject = 'Follow Up Test Task', WhatId = opp.Id));
   }
}

if(tasklist.size()>0){
   insert tasklist;
}
```

Module: Apex Testing

Get Started with Apex Unit Tests

VerifyDate

```
public class VerifyDate {
```

```
//method to handle potential checks against two dates
       public static Date CheckDates(Date date1, Date date2) {
             //if date2 is within the next 30 days of date1, use date2. Otherwise use
the end of the month
             if(DateWithin30Days(date1,date2)) {
                    return date2:
             } else {
                    return SetEndOfMonthDate(date1);
             }
      }
       //method to check if date2 is within the next 30 days of date1
       @TestVisible private static Boolean DateWithin30Days(Date date1, Date date2) {
             //check for date2 being in the past
       if( date2 < date1) { return false; }</pre>
       //check that date2 is within (>=) 30 days of date1
       Date date30Days = date1.addDays(30); //create a date 30 days away from date1
             if( date2 >= date30Days ) { return false; }
             else { return true; }
      }
       //method to return the end of the month of a given date
@TestVisible private static Date SetEndOfMonthDate(Date date1) {
             Integer totalDays = Date.daysInMonth(date1.year(), date1.month());
             Date lastDay = Date.newInstance(date1.year(), date1.month(), totalDays);
             return lastDay;
      }
}
<u>TestVerifyDate</u>
@isTest
private class TestVerifyDate {
```

```
@isTest static void Test_CheckDates_case1(){
    Date D = VerifyDate.CheckDates(date.parse('01/01/2020'),
date.parse('01/05/2020'));
    System.assertEquals(date.parse('01/05/2020'), D);
 }
  @isTest static void Test_CheckDates_case2(){
    Date D = VerifyDate.CheckDates(date.parse('01/01/2020'),
date.parse('05/05/2020'));
    System.assertEquals(date.parse('01/31/2020'), D);
  }
  @isTest static void Test_DateWithin30Days_case1(){
    Boolean flag = VerifyDate.DateWithin30Days(date.parse('01/01/2020'),
date.parse('12/30/2019'));
             System.assertEquals(false, flag);
  }
  @isTest static void Test_DateWithin30Days_case2(){
    Boolean flag = VerifyDate.DateWithin30Days(date.parse('01/01/2020'),
date.parse('02/02/2020'));
             System.assertEquals(false, flag);
      }
  @isTest static void Test_DateWithin30Days_case3(){
    Boolean flag = VerifyDate.DateWithin30Days(date.parse('01/01/2020'),
date.parse('01/15/2020'));
             System.assertEquals(true, flag);
      }
  @isTest static void Test_SetEndOfMonthDate(){
    Date returndate = VerifyDate.SetEndOfMonthDate(date.parse('01/01/2020'));
}
```

Test Apex Triggers

<u>RestrictContactByName</u>

```
trigger RestrictContactByName on Contact (before insert, before update) {
      //check contacts prior to insert or update for invalid data
       For (Contact c : Trigger.New) {
             if(c.LastName == 'INVALIDNAME') {
                                                     //invalidname is invalid
                    c.AddError('The Last Name "'+c.LastName+" is not allowed for
DML');
             }
      }
}
<u>TestRestrictContactByName</u>
@isTest
public class TestRestrictContactByName {
  @isTest static void Test_insertupdateContact(){
    Contact cnt = new Contact();
    cnt.LastName = 'INVALIDNAME';
    Test.startTest();
    Database.SaveResult result = Database.insert(cnt, false);
    Test.stopTest();
    System.assert(!result.isSuccess());
    System.assert(result.getErrors().size() > 0);
    System.assertEquals('The Last Name "INVALIDNAME" is not allowed for DML',
result.getErrors()[0].getMessage());
}
```

Create Test Data for Apex Tests

<u>RandomContactFactory</u>

```
public class RandomContactFactory {
    public static List<Contact> generateRandomContacts(Integer numcnt, string
lastname){
    List<Contact> contacts = new List<Contact>();
    for(Integer i=0;i<numcnt;i++){
        Contact cnt = new Contact(FirstName = 'Test '+i, LastName = lastname);
        contacts.add(cnt);
    }
    return contacts;
}</pre>
```

Module: Asynchronous Apex

Use Future Methods

<u>AccountProcessor</u>

```
public class AccountProcessor {
    @future
    public static void countContacts(List<Id> accountIds){
        List<Account> accountsToUpdate = new List<Account>();
        List<Account> accounts = [Select Id, Name, (Select Id from Contacts) from Account
Where Id in : accountIds];
    For(account acc:accounts){
        List<Contact> contactList = acc.Contacts;
        acc.Number_Of_Contacts__c = contactList.size();
        accountsToUpdate.add(acc);
    }
    update accountsToUpdate;
}
```

AccountProcessorTest

```
@IsTest
private class AccountProcessorTest {
      @IsTest
  private static void testCountContacts(){
    Account newAccount = new Account(Name = 'Test Account');
    insert newAccount:
    Contact newContact1 = new Contact(FirstName = 'John', LastName = 'Doe',
accountId = newAccount.Id);
    insert newContact1;
    Contact newContact2 = new Contact(FirstName = 'Jane', LastName = 'Doe',
accountId = newAccount.Id);
    insert newContact2;
    List<ld> accountIds = new List<ld>();
    accountIds.add(newAccount.Id);
    Test.startTest();
    AccountProcessor.countContacts(accountIds);
    Test.stopTest();
 }
```

Use Batch Apex

<u>LeadProcessor</u>

```
global class LeadProcessor implements Database.Batchable<sObject> {
    global Integer count = 0;
    global Database.QueryLocator start(Database.BatchableContext bc) {
        return Database.getQueryLocator('SELECT ID, LeadSource FROM Lead');
    }
    global void execute(Database.BatchableContext bc, List<Lead> L_list) {
```

```
List<lead> L_list_new = new List<lead>();
    for(lead L:L_list){
      L.leadsource = 'Dreamforce';
      L_list_new.add(L);
      count +=1;
    update L_list_new;
  global void finish(Database.BatchableContext bc){
    system.debug('count = ' + count);
  }
}
LeadProcessorTest
@isTest
public class LeadProcessorTest {
  @isTest
  public static void testit(){
    List<lead> L_list = new List<lead>();
    for(Integer i=0; i<200; i++){
      Lead L = new lead();
      L.LastName = 'name' + i;
      L.Company = 'Company';
      L.Status = 'Random Status';
      L_list.add(L);
    insert L_list;
    Test.startTest();
    LeadProcessor();
    Id batchId = Database.executeBatch(lp);
    Test.stopTest();
  }
```

}

Control Processes with Queueable Apex

<u>AddPrimaryContact</u>

```
public class AddPrimaryContact implements Queueable {
  private Contact con;
  private String state;
  public AddPrimaryContact(Contact con, String state){
    this.con = con;
    this.state = state;
  public void execute(QueueableContext context){
    List<Account> accounts = [Select Id, Name, (select FirstName, LastName, Id from
contacts)
                  from Account where BillingState = :state Limit 200];
    List<Contact> primaryContacts = new List<Contact>();
    for(Account acc:accounts){
      contact c = con.clone();
      c.AccountId = acc.Id;
      primaryContacts.add(c);
    if(primaryContacts.size()> 0){
      insert primaryContacts;
  }
}
AddPrimaryContactTest
```

```
@isTest
public class AddPrimaryContactTest {
    static testmethod void testQueueable(){
        List<Account> testAccounts = new List<Account>();
        for(Integer i=0;i<50;i++){
```

```
testAccounts.add(new Account(Name = 'Account '+i,BillingState='CA'));
}
for(Integer i=0;i<50;i++){
    testAccounts.add(new Account(Name = 'Account '+i,BillingState='NY'));
}
insert testAccounts;
Contact testContact = new Contact(FirstName = 'John', LastName = 'Doe');
insert testContact;
AddPrimaryContact addit = new addPrimaryContact(testContact, 'CA');
Test.startTest();
system.enqueueJob(addit);
Test.stopTest();
System.assertEquals(50,[Select count() from Contact where accountId in (Select ID from Account where BillingState='CA')]);
}
</pre>
```

Schedule Jobs Using the Apex Scheduler

DailyLeadProcessor

DailyLeadProcessorTest

```
@isTest
private class DailyLeadProcessorTest {
  public static String CRON_EXP = '0 0 0 15 3 ? 2023';
  static testmethod void testScheduledJob(){
    List<Lead> leads = new List<lead>();
    for(Integer i = 0; i < 200; i++){
      Lead I = new Lead(
      FirstName = 'First ' + i,
      LastName = 'LastName',
         Company = 'The Inc'
        );
      leads.add(I);
    insert leads:
    Test.startTest();
    string jobId= System.schedule('ScheduledApexTest',
                     CRON_EXP,
                     new DailyLeadProcessor());
    Test.stopTest();
    List<Lead> checkleads = new List<Lead>();
    checkleads = [Select Id from Lead Where LeadSource = 'Dreamforce' and Company
= 'The Inc'];
    System.assertEquals(200,checkleads.size(), 'Leads were not created');
  }
}
```

MODULE: APEX INTEGRATION SERVICES Apex REST Callouts

AnimalLocator

```
public class AnimalLocator {
  public static String getAnimalNameById(Integer x){
    Http http = new Http();
```

```
HttpRequest req = new HttpRequest();
             req.setEndpoint('https://th-apex-http-callout.herokuapp.com/animals/' +
x);
             req.setMethod('GET');
    Map<String, Object> animal = new Map <String, Object>();
    HttpResponse res = http.send(reg);
    if(res.getStatusCode() == 200) {
    Map<String, Object> results = (Map<String, Object>)
JSON.deserializeUntyped(res.getBody());
             animal = (Map<String, Object>) results.get('animal');
    }
    return (String)animal.get('name');
 }
}
AnimalLocatorMock
@isTest
global class AnimalLocatorMock implements HttpCalloutMock {
  // Implement this interface method
  global HTTPResponse respond(HTTPRequest request) {
    // Create a fake response
    HttpResponse response = new HttpResponse();
    response.setHeader('Content-Type', 'application/json');
    response.setBody('{"animals": ["majestic badger", "fluffy bunny", "scary bear",
"chicken", "mighty moose"]}');
    response.setStatusCode(200);
    return response;
 }
}
AnimalLocatorTest
@isTest
private class AnimalLocatorTest {
  @isTest static void AnimalLocatorMock1() {
    Test.setMock(HttpCalloutMock.class, new AnimalLocatorMock());
```

```
string result = AnimalLocator.getAnimalNameById(3);
   String expectedResult = 'chicken';
   system.assertEquals(result,expectedResult);
}
```

Apex SOAP Callouts

ParkService

```
public class ParkService {
  public class byCountryResponse {
    public String∏ return_x;
    private String[] return_x_type_info = new
String[]{'return','http://parks.services/',null,'0','-1','false'};
    private String[] apex_schema_type_info = new
String[]{'http://parks.services/','false','false'};
    private String[] field_order_type_info = new String[]{'return_x'};
  public class byCountry {
    public String arg0;
    private String[] arg0_type_info = new
String[]{'arg0','http://parks.services/',null,'0','1','false'};
    private String[] apex_schema_type_info = new
String[]{'http://parks.services/','false','false'};
    private String[] field_order_type_info = new String[]{'arg0'};
  }
  public class ParksImplPort {
    public String endpoint_x = 'https://th-apex-soap-
service.herokuapp.com/service/parks';
    public Map<String,String> inputHttpHeaders_x;
    public Map<String,String> outputHttpHeaders_x;
    public String clientCertName_x;
    public String clientCert_x;
    public String clientCertPasswd_x;
    public Integer timeout_x;
    private String[] ns_map_type_info = new String[]{'http://parks.services/',
```

```
'ParkService'};
    public String[] byCountry(String arg0) {
      ParkService.byCountry request_x = new ParkService.byCountry();
      request_x.arg0 = arg0;
      ParkService.byCountryResponse response_x;
      Map<String, ParkService.byCountryResponse> response_map_x = new
Map<String, ParkService.byCountryResponse>();
      response_map_x.put('response_x', response_x);
      WebServiceCallout.invoke(
       this.
       request_x,
       response_map_x,
       new String[]{endpoint_x,
       'http://parks.services/',
       'byCountry',
       'http://parks.services/',
       'byCountryResponse',
       'ParkService.byCountryResponse'}
      );
      response_x = response_map_x.get('response_x');
      return response_x.return_x;
 }
}
ParkLocator
public class ParkLocator {
  public static List<String>country(String country)
    ParkService.ParksImplPort parkservice = new parkService.ParksImplport();
    return parkservice.byCountry(country);
 }
}
```

ParkLocatorTest

```
@isTest
private class ParkLocatorTest {
    @isTest static void testCallout() {

    Test.setMock(WebServiceMock.class, new ParkServiceMock());

    String country = 'United States';
    List<String> result = ParkLocator.country(country);
    List<String> parks = new List<String>();
        parks.add('Yosemite');
        parks.add('Yellowstone');
        parks.add('Another Park');
        System.assertEquals(parks, result);
    }
}
```

Apex Web Services

AccountManager

```
@RestResource(urlMapping = '/Accounts/*/contacts')
global with sharing class AccountManager {

    @HttpGet
    global static Account getAccount(){
        RestRequest request = RestContext.request;
        string accountId = request.requestURI.substringBetween('Accounts/','/contacts');
        account result = [SELECT Id, Name, (Select Id, Name from Contacts) from Account
where Id =:accountId Limit 1];
        return result;
    }
}
```

<u>AccountManagerTest</u>

```
@IsTest
private class AccountManagerTest {
  @isTest static void testGetContactsByAccountId(){
    Id recordId = createTestRecord();
    RestRequest request = new RestRequest();
    request.requestUri =
'https://yourInstance.my.salesforce.com/services/apexrest/Accounts/'+ recordId +
'/contacts';
    request.httpMethod = 'GET';
    RestContext.request = request;
    account this Account = Account Manager.get Account();
    System.assert(thisAccount != null);
    System.assertEquals('Test record', thisAccount.Name);
  static Id createTestRecord(){
    Account accountTest = new Account(
    Name = 'Test record');
    insert accountTest:
    Contact contactTest = new Contact(
    FirstName = 'John',
    LastName = 'Doe',
    AccountId = accountTest.Id
    insert contactTest;
    return accountTest.ld;
}
```

APEX SPECIALIST SUPERBADGE:

Automate Record Creation

MaintenanceRequest

```
trigger MaintenanceRequest on Case (before update, after update) {
  if(Trigger.isUpdate && Trigger.isAfter){
    MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);
 }
}
<u>MaintenanceRequestHelper</u>
public with sharing class MaintenanceRequestHelper {
  public static void updateworkOrders(List<Case> updWorkOrders, Map<Id,Case>
nonUpdCaseMap) {
    Set<Id> validIds = new Set<Id>();
    For (Case c : updWorkOrders){
      if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
        if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
          validIds.add(c.Id);
        }
     }
    }
    //When an existing maintenance request of type Repair or Routine Maintenance is
closed.
    //create a new maintenance request for a future routine checkup.
    if (!validIds.isEmpty()){
      Map<ld,Case> closedCases = new Map<ld,Case>([SELECT Id, Vehicle__c,
Equipment_c, Equipment_r.Maintenance_Cycle_c,
                               (SELECT Id, Equipment_c, Quantity_c FROM
Equipment_Maintenance_Items__r)
                               FROM Case WHERE Id IN :validIds]);
```

//calculate the maintenance request due dates by using the maintenance cycle defined on the related equipment records.

Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();

```
AggregateResult[] results = [SELECT Maintenance_Request__c,
                      MIN(Equipment__r.Maintenance_Cycle__c)cycle
                      FROM Equipment_Maintenance_Item__c
                      WHERE Maintenance_Request__c IN :ValidIds GROUP BY
Maintenance_Request__c];
      for (AggregateResult ar : results){
        maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal)
ar.get('cycle'));
      }
      List<Case> newCases = new List<Case>();
      for(Case cc : closedCases.values()){
        Case nc = new Case (
          ParentId = cc.Id.
          Status = 'New'.
          Subject = 'Routine Maintenance',
          Type = 'Routine Maintenance',
          Vehicle_c = cc.Vehicle_c,
          Equipment_c = cc.Equipment_c,
          Origin = 'Web',
          Date_Reported__c = Date.Today()
        );
        //If multiple pieces of equipment are used in the maintenance request,
        //define the due date by applying the shortest maintenance cycle to today's
date.
        //If (maintenanceCycles.containskey(cc.ld)){
          nc.Date_Due__c = Date.today().addDays((Integer)
maintenanceCycles.get(cc.ld));
        //} else {
        // nc.Date_Due__c = Date.today().addDays((Integer)
cc.Equipment__r.maintenance_Cycle__c);
        //}
        newCases.add(nc);
```

```
insert newCases;

List<Equipment_Maintenance_Item__c> clonedList = new
List<Equipment_Maintenance_Item__c>();
    for (Case nc : newCases){
        for (Equipment_Maintenance_Item__c clonedListItem :
closedCases.get(nc.ParentId).Equipment_Maintenance_Items__r){
            Equipment_Maintenance_Item__c item = clonedListItem.clone();
            item.Maintenance_Request__c = nc.Id;
            clonedList.add(item);
        }
    }
    insert clonedList;
}
```

Synchronization Salesforce Data with an External System

WarehouseCalloutService

public with sharing class WarehouseCalloutService implements Queueable {
 private static final String WAREHOUSE_URL = 'https://th-superbadgeapex.herokuapp.com/equipment';

//Write a class that makes a REST callout to an external warehouse system to get a list of equipment that needs to be updated.

//The callout's JSON response returns the equipment records that you upsert in Salesforce.

```
@future(callout=true)
public static void runWarehouseEquipmentSync(){
   System.debug('go into runWarehouseEquipmentSync');
   Http http = new Http();
```

```
HttpRequest request = new HttpRequest();
    request.setEndpoint(WAREHOUSE_URL);
    request.setMethod('GET');
    HttpResponse response = http.send(request);
    List<Product2> product2List = new List<Product2>();
    System.debug(response.getStatusCode());
    if (response.getStatusCode() == 200){
      List<Object> jsonResponse =
(List<Object>)JSON.deserializeUntyped(response.getBody());
      System.debug(response.getBody());
      //class maps the following fields:
      //warehouse SKU will be external ID for identifying which equipment records to
update within Salesforce
      for (Object jR : jsonResponse){
        Map<String,Object> mapJson = (Map<String,Object>)jR;
        Product2 product2 = new Product2();
        //replacement part (always true),
        product2.Replacement_Part__c = (Boolean) mapJson.get('replacement');
        //cost
        product2.Cost__c = (Integer) mapJson.get('cost');
        //current inventory
        product2.Current_Inventory__c = (Double) mapJson.get('quantity');
        //lifespan
        product2.Lifespan_Months__c = (Integer) mapJson.get('lifespan');
        //maintenance cycle
        product2.Maintenance_Cycle__c = (Integer)
mapJson.get('maintenanceperiod');
        //warehouse SKU
        product2.Warehouse_SKU__c = (String) mapJson.get('sku');
        product2.Name = (String) mapJson.get('name');
        product2.ProductCode = (String) mapJson.get('_id');
        product2List.add(product2);
      }
```

```
if (product2List.size() > 0){
    upsert product2List;
    System.debug('Your equipment was synced with the warehouse one');
    }
}

public static void execute (QueueableContext context){
    System.debug('start runWarehouseEquipmentSync');
    runWarehouseEquipmentSync();
    System.debug('end runWarehouseEquipmentSync');
}
```

Schedule Synchronization using apex code

<u>WarehouseSyncSchedule</u>

```
global with sharing class WarehouseSyncSchedule implements Schedulable{
   global void execute(SchedulableContext ctx){
     System.enqueueJob(new WarehouseCalloutService());
   }
}
```

Test Automation Logic

MaintenanceRequestHelperTest

```
@isTest
public with sharing class MaintenanceRequestHelperTest {
    // createVehicle
    private static Vehicle_c createVehicle(){
        Vehicle_c vehicle = new Vehicle_C(name = 'Testing Vehicle');
    }
}
```

```
return vehicle;
  }
  // createEquipment
  private static Product2 createEquipment(){
    product2 equipment = new product2(name = 'Testing equipment',
                      lifespan_months__c = 10,
                      maintenance_cycle__c = 10,
                      replacement_part__c = true);
    return equipment;
 }
  // createMaintenanceRequest
  private static Case createMaintenanceRequest(id vehicleId, id equipmentId){
    case cse = new case(Type='Repair',
              Status='New',
              Origin='Web',
              Subject='Testing subject',
               Equipment_c=equipmentId,
               Vehicle_c=vehicleId);
    return cse;
 }
  // createEquipmentMaintenanceItem
  private static Equipment_Maintenance_Item_c createEquipmentMaintenanceItem(id
equipmentId,id requestId){
    Equipment_Maintenance_Item__c equipmentMaintenanceItem = new
Equipment_Maintenance_Item__c(
      Equipment_c = equipmentId,
      Maintenance_Request__c = requestId);
    return equipmentMaintenanceItem;
  }
  @isTest
  private static void testPositive(){
    Vehicle__c vehicle = createVehicle();
    insert vehicle:
```

```
id vehicleId = vehicle.Id:
    Product2 equipment = createEquipment();
    insert equipment;
    id equipmentId = equipment.Id;
    case createdCase = createMaintenanceRequest(vehicleId,equipmentId);
    insert createdCase:
    Equipment_Maintenance_Item__c equipmentMaintenanceItem =
createEquipmentMaintenanceItem(equipmentId,createdCase.id);
    insert equipmentMaintenanceItem;
    test.startTest();
    createdCase.status = 'Closed';
    update createdCase;
    test.stopTest();
    Case newCase = [Select id,
            subject,
            type,
            Equipment__c,
            Date_Reported__c,
            Vehicle__c,
            Date_Due__c
            from case
            where status ='New'];
    Equipment_Maintenance_Item__c workPart = [select id
                          from Equipment_Maintenance_Item__c
                          where Maintenance_Request__c =:newCase.ld];
    list<case> allCase = [select id from case];
    system.assert(allCase.size() == 2);
    system.assert(newCase != null);
    system.assert(newCase.Subject != null);
    system.assertEquals(newCase.Type, 'Routine Maintenance');
```

```
SYSTEM.assertEquals(newCase.Equipment_c, equipmentId);
    SYSTEM.assertEquals(newCase.Vehicle_c, vehicleId);
    SYSTEM.assertEquals(newCase.Date_Reported__c, system.today());
  }
  @isTest
  private static void testNegative(){
    Vehicle__C vehicle = createVehicle();
    insert vehicle:
    id vehicleId = vehicle.Id;
    product2 equipment = createEquipment();
    insert equipment;
    id equipmentId = equipment.Id;
    case createdCase = createMaintenanceRequest(vehicleId,equipmentId);
    insert createdCase;
    Equipment_Maintenance_Item__c workP =
createEquipmentMaintenanceItem(equipmentId, createdCase.Id);
    insert workP;
    test.startTest();
    createdCase.Status = 'Working';
    update createdCase;
    test.stopTest();
    list<case> allCase = [select id from case];
    Equipment_Maintenance_Item__c equipmentMaintenanceItem = [select id
                          from Equipment_Maintenance_Item__c
                          where Maintenance_Request__c = :createdCase.ld];
    system.assert(equipmentMaintenanceItem != null);
    system.assert(allCase.size() == 1);
  }
```

```
@isTest
  private static void testBulk(){
    list<Vehicle_C> vehicleList = new list<Vehicle_C>();
    list<Product2> equipmentList = new list<Product2>();
    list<Equipment_Maintenance_Item__c> equipmentMaintenanceItemList = new
list<Equipment_Maintenance_Item__c>();
    list<case> caseList = new list<case>();
    list<id> oldCaseIds = new list<id>();
    for(integer i = 0; i < 300; i++){
      vehicleList.add(createVehicle());
      equipmentList.add(createEquipment());
    insert vehicleList;
    insert equipmentList;
    for(integer i = 0; i < 300; i++){
      caseList.add(createMaintenanceRequest(vehicleList.get(i).id,
equipmentList.get(i).id));
    insert caseList;
    for(integer i = 0; i < 300; i++){
equipmentMaintenanceItemList.add(createEquipmentMaintenanceItem(equipmentList.
get(i).id, caseList.get(i).id));
    insert equipmentMaintenanceItemList;
    test.startTest();
    for(case cs : caseList){
      cs.Status = 'Closed';
      oldCaseIds.add(cs.Id);
    update caseList;
    test.stopTest();
```

```
list<case> newCase = [select id
                  from case
                  where status ='New'];
    list<Equipment_Maintenance_Item__c> workParts = [select id
                               from Equipment_Maintenance_Item__c
                               where Maintenance_Request__c in: oldCaseIds];
    system.assert(newCase.size() == 300);
    list<case> allCase = [select id from case];
    system.assert(allCase.size() == 600);
}
<u>MaintenanceRequestHelper</u>
public with sharing class MaintenanceRequestHelper {
  public static void updateworkOrders(List<Case> updWorkOrders, Map<Id,Case>
nonUpdCaseMap) {
    Set<Id> validIds = new Set<Id>();
    For (Case c : updWorkOrders){
      if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
        if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
          validIds.add(c.Id);
        }
      }
    }
    //When an existing maintenance request of type Repair or Routine Maintenance is
closed,
    //create a new maintenance request for a future routine checkup.
    if (!validIds.isEmpty()){
      Map<Id,Case> closedCases = new Map<Id,Case>([SELECT Id, Vehicle__c,
Equipment__c, Equipment__r.Maintenance_Cycle__c,
```

```
(SELECT Id,Equipment_c,Quantity_c FROM
Equipment_Maintenance_Items__r)
                               FROM Case WHERE Id IN :validIds]);
      Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
      //calculate the maintenance request due dates by using the maintenance cycle
defined on the related equipment records.
      AggregateResult[] results = [SELECT Maintenance_Request__c,
                      MIN(Equipment__r.Maintenance_Cycle__c)cycle
                      FROM Equipment_Maintenance_Item__c
                      WHERE Maintenance_Request__c IN :ValidIds GROUP BY
Maintenance_Request__c];
      for (AggregateResult ar : results){
        maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal)
ar.get('cycle'));
      }
      List<Case> newCases = new List<Case>();
      for(Case cc : closedCases.values()){
        Case nc = new Case (
          ParentId = cc.Id.
          Status = 'New',
          Subject = 'Routine Maintenance',
          Type = 'Routine Maintenance',
          Vehicle_c = cc.Vehicle_c,
          Equipment_c = cc.Equipment_c,
          Origin = 'Web',
          Date_Reported__c = Date.Today()
        );
        //If multiple pieces of equipment are used in the maintenance request,
        //define the due date by applying the shortest maintenance cycle to today's
date.
        //If (maintenanceCycles.containskey(cc.ld)){
          nc.Date_Due__c = Date.today().addDays((Integer)
maintenanceCycles.get(cc.ld));
```

```
//} else {
        // nc.Date_Due__c = Date.today().addDays((Integer)
cc.Equipment__r.maintenance_Cycle__c);
        //}
        newCases.add(nc);
      }
      insert newCases;
      List<Equipment_Maintenance_Item__c> clonedList = new
List<Equipment_Maintenance_Item__c>();
      for (Case nc : newCases){
        for (Equipment_Maintenance_Item__c clonedListItem:
closedCases.get(nc.ParentId).Equipment_Maintenance_Items__r){
          Equipment_Maintenance_Item__c item = clonedListItem.clone();
          item.Maintenance_Request__c = nc.ld;
          clonedList.add(item);
        }
      }
      insert clonedList;
}
MaintenanceRequest
trigger MaintenanceRequest on Case (before update, after update) {
  if(Trigger.isUpdate && Trigger.isAfter){
    MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);
 }
}
```

Test Callout Logic

WarehouseCalloutService

```
public with sharing class WarehouseCalloutService implements Queueable {
   private static final String WAREHOUSE_URL = 'https://th-superbadge-
   apex.herokuapp.com/equipment';
```

//Write a class that makes a REST callout to an external warehouse system to get a list of equipment that needs to be updated.

//The callout's JSON response returns the equipment records that you upsert in Salesforce.

```
@future(callout=true)
  public static void runWarehouseEquipmentSync(){
    System.debug('go into runWarehouseEquipmentSync');
    Http http = new Http();
    HttpRequest request = new HttpRequest();
    request.setEndpoint(WAREHOUSE_URL);
    request.setMethod('GET');
    HttpResponse response = http.send(request);
    List<Product2> product2List = new List<Product2>();
    System.debug(response.getStatusCode());
    if (response.getStatusCode() == 200){
      List<Object> isonResponse =
(List<Object>)JSON.deserializeUntyped(response.getBody());
      System.debug(response.getBody());
      //class maps the following fields:
      //warehouse SKU will be external ID for identifying which equipment records to
update within Salesforce
      for (Object iR: jsonResponse){
        Map<String,Object> mapJson = (Map<String,Object>)jR;
        Product2 product2 = new Product2();
        //replacement part (always true),
        product2.Replacement_Part__c = (Boolean) mapJson.get('replacement');
        //cost
        product2.Cost__c = (Integer) mapJson.get('cost');
```

```
//current inventory
        product2.Current_Inventory__c = (Double) mapJson.get('quantity');
        //lifespan
        product2.Lifespan_Months__c = (Integer) mapJson.get('lifespan');
        //maintenance cycle
        product2.Maintenance_Cycle__c = (Integer)
mapJson.get('maintenanceperiod');
        //warehouse SKU
        product2.Warehouse_SKU__c = (String) mapJson.get('sku');
        product2.Name = (String) mapJson.get('name');
        product2.ProductCode = (String) mapJson.get('_id');
        product2List.add(product2);
      }
      if (product2List.size() > 0){
        upsert product2List;
        System.debug('Your equipment was synced with the warehouse one');
      }
    }
  }
  public static void execute (QueueableContext context){
    System.debug('start runWarehouseEquipmentSync');
    runWarehouseEquipmentSync();
    System.debug('end runWarehouseEquipmentSync');
  }
}
WarehouseCalloutServiceTest
@IsTest
private class WarehouseCalloutServiceTest {
```

// implement your mock callout test here

static void testWarehouseCallout() {

@isTest

```
test.startTest();
    test.setMock(HttpCalloutMock.class, new WarehouseCalloutServiceMock());
    WarehouseCalloutService.execute(null);
    test.stopTest();
    List<Product2> product2List = new List<Product2>();
    product2List = [SELECT ProductCode FROM Product2];
    System.assertEquals(3, product2List.size());
    System.assertEquals('55d66226726b611100aaf741',
product2List.get(0).ProductCode);
    System.assertEquals('55d66226726b611100aaf742',
product2List.get(1).ProductCode);
    System.assertEquals('55d66226726b611100aaf743'.
product2List.get(2).ProductCode);
 }
}
WarehouseCalloutServiceMock
@isTest
global class WarehouseCalloutServiceMock implements HttpCalloutMock {
  // implement http mock callout
  global static HttpResponse respond(HttpRequest request) {
    HttpResponse response = new HttpResponse();
    response.setHeader('Content-Type', 'application/json');
response.setBody('[{"_id":"55d66226726b611100aaf741","replacement":false,"quantity":5
"name": "Generator 1000
kW","maintenanceperiod":365,"lifespan":120,"cost":5000,"sku":"100003"},{"_id":"55d66226
726b611100aaf742","replacement":true,"quantity":183,"name":"Cooling
Fan","maintenanceperiod":0,"lifespan":0,"cost":300,"sku":"100004"},{"_id":"55d66226726b6
11100aaf743","replacement":true,"quantity":143,"name":"Fuse
20A","maintenanceperiod":0,"lifespan":0,"cost":22,"sku":"100005"}]');
    response.setStatusCode(200);
```

```
return response;
}
}
```

Test Scheduling Logic

WarehouseSyncSchedule

```
global with sharing class WarehouseSyncSchedule implements Schedulable{
  global void execute(SchedulableContext ctx){
    System.enqueueJob(new WarehouseCalloutService());
  }
}
```

<u>WarehouseSyncScheduleTest</u>

```
@isTest
public with sharing class WarehouseSyncScheduleTest {
    // implement scheduled code here
    //
    @isTest static void test() {
        String scheduleTime = '00 00 00 **? *';
        Test.startTest();
        Test.setMock(HttpCalloutMock.class, new WarehouseCalloutServiceMock());
        String jobId = System.schedule('Warehouse Time to Schedule to test',
        scheduleTime, new WarehouseSyncSchedule());
        CronTrigger c = [SELECT State FROM CronTrigger WHERE Id =: jobId];
        System.assertEquals('WAITING', String.valueOf(c.State), 'JobId does not match');
        Test.stopTest();
    }
}
```