# **APEX TRIGGERS**

### AccountAddressTrigger:

```
trigger AccountAddressTrigger on Account (before insert, before update) {
  for(Account account:Trigger.New){
    if(account.Match_Billing_Address__c == True){
      account.ShippingPostalCode = account.BillingPostalCode;
    }
}
```

### ClosedOpportunityTrigger:

```
trigger ClosedOpportunityTrigger on Opportunity (after insert, after update) {
   List<Task> tasklist = new List<Task>();
   for(Opportunity opp: Trigger.New){
      if(opp.StageName == 'Closed Won'){
        tasklist.add(new Task(Subject = 'Follow Up Test Task', WhatId = opp.Id));
    }
   }
   if(tasklist.size()>0){
      insert tasklist;
   }
}
```

# **APEX TESTING**

# VerifyDate:

```
public class VerifyDate {
  //method to handle potential checks against two dates
  public static Date CheckDates(Date date1, Date date2) {
     //if date2 is within the next 30 days of date1, use date2. Otherwise use the end of the
  month
     if(DateWithin30Days(date1,date2)) {
        return date2;
     } else {
```

```
return SetEndOfMonthDate(date1);
 }
 //method to check if date2 is within the next 30 days of date1
 private static Boolean DateWithin30Days(Date date1, Date date2) {
  //check for date2 being in the past
     if( date2 < date1) { return false; }</pre>
     //check that date2 is within (>=) 30 days of date1
     Date date30Days = date1.addDays(30); //create a date 30 days away from date1
  if( date2 >= date30Days ) { return false; }
  else { return true; }
 //method to return the end of the month of a given date
 private static Date SetEndOfMonthDate(Date date1) {
  Integer totalDays = Date.daysInMonth(date1.year(), date1.month());
  Date lastDay = Date.newInstance(date1.year(), date1.month(), totalDays);
  return lastDay;
 }
TestVerifyDate:
@isTest
public class TestVerifyDate
  static testMethod void testMethod1()
    Date d = VerifyDate.CheckDates(System.today(),System.today()+1);
    Date d1 = VerifyDate.CheckDates(System.today(),System.today()+60);
 }
RestrictContactByName:
trigger RestrictContactByName on Contact (before insert, before update) {
      //check contacts prior to insert or update for invalid data
      For (Contact c : Trigger.New) {
```

### TestRestrictContactByName:

```
@isTest
public class TestRestrictContactByName {
  @isTest static void testInvalidName() {
    //try inserting a Contact with INVALIDNAME
    Contact myConact = new Contact(LastName='INVALIDNAME');
    insert myConact;
    // Perform test
    Test.startTest();
    Database.SaveResult result = Database.insert(myConact, false);
    Test.stopTest();
    // Verify
    // In this case the creation should have been stopped by the trigger,
    // so verify that we got back an error.
    System.assert(!result.isSuccess());
    System.assert(result.getErrors().size() > 0);
    System.assertEquals('Cannot create contact with invalid last name.',
                result.getErrors()[0].getMessage());
 }
```

## RandomContactFactory

```
}
return con;
}
```

# **ASYNCHRONOUS APEX**

### AccountProcessor:

```
public class AccountProcessor{
    @future
    public static void countContacts(List<Id> accountIds){
        List<Account> accountsToUpdate = new List<Account>();
        List<Account> accounts = [Select Id, Name, (Select Id from Contacts) from Account
Where Id in :accountIds];
    For(Account acc:accounts){
        List<Contact> contactList = acc.Contacts;
        acc.Number_Of_Contacts__c = contactList.size();
        accountsToUpdate.add(acc);
    }
    update accountsToUpdate;
}
```

# AccountProcessorTest:

```
@lsTest
private class AccountProcessorTest {
    @lsTest
    private static void testCountContacts(){
        Account newAccount = new Account(Name='Test Account');
        insert newAccount;
        Contact newContact1 = new Contact (FirstName='John',LastName='Doe',AccountId = newAccount.Id);
        insert newContact1;
        Contact newContact2 = new Contact (FirstName='Jane',LastName='Doe',AccountId = newAccount.Id);
        insert newContact2;
```

```
List<Id> accountIds = new List<Id>();
accountIds.add(newAccount.Id);
Test.startTest();
AccountProcessor.countContacts(accountIds);
Test.stopTest();
}
```

#### LeadProcessor:

```
global class LeadProcessor implements Database.Batchable<sObject> {
    global Integer count = 0;
    global Database.QueryLocator start(Database.BatchableContext bc) {
        return Database.getQueryLocator('SELECT ID, LeadSource FROM Lead');
    }
    global void execute (Database.BatchableContext bc, List<Lead> L_list) {
        List<lead> L_list_new = new List<lead>();
        for(lead L:L_list) {
        L.leadsource = 'Dreamforce';
        L_list_new.add(L);
        count += 1;
     }
        update L_list_new;
    }
    global void finish(Database.BatchableContext bc) {
        system.debug('count = ' + count);
    }
}
```

#### LeadProcessorTest:

```
@isTest
public class LeadProcessorTest {
    @isTest
    public static void testit(){
        List<lead> L_list = new List<lead>();
        for(Integer i=0; i<200; i++){
        Lead L = new lead();
        L.LastName = 'name' + i;
        L.Company = 'Company';</pre>
```

```
L.Status = 'Random Status';
L_list.add(L);
}
insert L_list;
Test.startTest();
LeadProcessor lp = new LeadProcessor();
Id batchId = Database.executeBatch(lp);
Test.stopTest();
}
```

# ${\bf AddPrimary Contact:}$

```
public class AddPrimaryContact implements Queueable {
  private Contact con;
  private String state;
  public AddPrimaryContact(Contact con, String state){
    this.con = con;
    this.state = state:
  public void execute(QueueableContext context){
    List<Account> accounts = [Select Id, Name, (Select FirstName, LastName, Id from
contacts)
                 from Account where BillingState = :state Limit 200];
    List<Contact> primaryContacts = new List<Contact>();
    for (Account acc:accounts){
      Contact c = con.clone();
      c.AccountId = acc.Id;
      primaryContacts.add(c);
    if(primaryContacts.size() > 0){
      insert primaryContacts;
  }
```

# Add Primary Contact Test

@isTest

```
public class AddPrimaryContactTest {
  static testmethod void testQueueable(){
    List<Account> testAccounts = new List<Account>();
    for(Integer i=0;i<50;i++){
      testAccounts.add(new Account(Name='Account ' +i,BillingState='CA'));
    for(Integer j=0;j<50;j++){
      testAccounts.add(new Account(Name='Account '+j,BillingState='NY'));
    insert testAccounts;
    Contact testContact = new Contact(FirstName = 'John', LastName = 'Doe');
    insert testContact;
    AddPrimaryContact addit = new addPrimaryContact(testContact, 'CA');
    Test.startTest();
    system.enqueueJob(addit);
    Test.stopTest();
    System.assertEquals(50,[Select count() from Contact where accounted in (Select Id
from Account where BillingState='CA')]);
  }
DailyLeadProcessor
public class DailyLeadProcessor implements Schedulable {
  Public void execute (SchedulableContext SC) {
    List<Lead> LeadObj = [SELECT Id from Lead Where LeadSource = null limit 200];
    for(Lead I : LeadObj ) {
      I.LeadSource = 'Dreamforce';
      update I;
    }
  }
DailyLeadProcessorTest:
@isTest
```

private class DailyLeadProcessorTest {

String CRON\_EXP = '0 0 1 \* \* ?';

static testMethod void testDailyLeadProcessor() {

# **APEX INTEGRATION**

### AnimalLocator:

#### AnimalLocatorTest:

```
@isTest
private class AnimalLocatorTest{
    @isTest static void AnimalLocatorMock1() {
```

```
Test.setMock(HttpCalloutMock.class, new AnimalLocatorMock());
    string result = AnimalLocator.getAnimalNameById(3);
    String expectedResult = 'chicken';
    System.assertEquals(result,expectedResult);
  }
}
AnimalLocatorMock:
@isTest
global class AnimalLocatorMock implements HttpCalloutMock {
  // Implement this interface method
  global HTTPResponse respond(HTTPRequest request) {
    // Create a fake response
    HttpResponse response = new HttpResponse();
    response.setHeader('Content-Type', 'application/json');
    response.setBody('{"animals": ["majestic badger", "fluffy bunny", "scary bear",
"chicken", "mighty moose"]}');
    response.setStatusCode(200);
    return response;
  }
}
ParkLocator:
public class ParkLocator {
  public static string[] country(string theCountry) {
    ParkService.ParksImplPort parkSvc = new ParkService.ParksImplPort(); // remove
space
    return parkSvc.byCountry(theCountry);
  }
ParkLocatorTest:
@isTest
private class ParkLocatorTest {
  @isTest static void testCallout() {
    Test.setMock(WebServiceMock.class, new ParkServiceMock ());
```

String country = 'United States';

```
List<String> result = ParkLocator.country(country);
    List<String> parks = new List<String>{'Yellowstone', 'Mackinac National Park',
'Yosemite'}:
    System.assertEquals(parks, result);
 }
}
AccountManager:
@RestResource(urlMapping = '/Accounts/*/contacts')
global with sharing class AccountManager {
  @HttpGet
  global static Account getAccount(){
    RestRequest request = RestContext.request;
    string accountId = request.requestURI.substringBetween('Accounts/','/contacts');
    Account result = [SELECT Id, Name, (Select Id, Name from Contacts) from Account
where Id=:accountId Limit 1];
    return result;
 }
```

### AccountManagerTest:

```
Name ='Test record');
insert accountTest;
Contact contactTest = new Contact(
FirstName='John',
LastName = 'Doe',
AccountId = accountTest.Id
);
insert contactTest;
return accountTest.Id;
}
```

# **APEX SPECIALIST**

### CreateDefaultData:

```
public with sharing class CreateDefaultData{
  Static Final String TYPE_ROUTINE_MAINTENANCE = 'Routine Maintenance';
  //gets value from custom metadata How_We_Roll_Settings__mdt to know if Default
data was created
  @AuraEnabled
  public static Boolean isDataCreated() {
    How_We_Roll_Settings_c customSetting =
How_We_Roll_Settings_c.getOrgDefaults();
    return customSetting.Is_Data_Created__c;
 }
  //creates Default Data for How We Roll application
  @AuraEnabled
  public static void createDefaultData(){
    List<Vehicle_c> vehicles = createVehicles();
    List<Product2> equipment = createEquipment();
    List<Case> maintenanceRequest = createMaintenanceRequest(vehicles);
    List<Equipment_Maintenance_Item__c> joinRecords =
createJoinRecords(equipment, maintenanceRequest);
    updateCustomSetting(true);
```

```
public static void updateCustomSetting(Boolean isDataCreated){
    How_We_Roll_Settings_c customSetting =
How_We_Roll_Settings_c.getOrgDefaults();
    customSetting.ls_Data_Created__c = isDataCreated;
    upsert customSetting;
 }
  public static List<Vehicle__c> createVehicles(){
    List<Vehicle_c> vehicles = new List<Vehicle_c>();
    vehicles.add(new Vehicle_c(Name = 'Toy Hauler RV', Air_Conditionerc = true,
Bathroomsc = 1, Bedroomsc = 1, Model_c = 'Toy Hauler RV'));
    vehicles.add(new Vehicle_c(Name = 'Travel Trailer RV', Air_Conditionerc = true,
Bathroomsc = 2, Bedroomsc = 2, Model_c = 'Travel Trailer RV'));
    vehicles.add(new Vehicle_c(Name = 'Teardrop Camper', Air_Conditionerc = true,
Bathroomsc = 1, Bedroomsc = 1, Model_c = 'Teardrop Camper'));
    vehicles.add(new Vehicle_c(Name = 'Pop-Up Camper', Air_Conditionerc = true,
Bathroomsc = 1, Bedroomsc = 1, Model_c = 'Pop-Up Camper'));
    insert vehicles:
    return vehicles:
  }
  public static List<Product2> createEquipment(){
    List<Product2> equipments = new List<Product2>();
    equipments.add(new Product2(Warehouse_SKU_c =
'55d66226726b611100aaf741',name = 'Generator 1000 kW', Replacement_Partc =
true,Costc = 100,Maintenance_Cycle_c = 100));
    equipments.add(new Product2(name = 'Fuse 20B',Replacement_Part_c = true,Costc
= 1000, Maintenance_Cycle_c = 30 ));
    equipments.add(new Product2(name = 'Breaker 13C',Replacement_Part_c =
true,Costc = 100 , Maintenance_Cycle_c = 15));
    equipments.add(new Product2(name = 'UPS 20 VA',Replacement_Part_c =
true,Costc = 200 , Maintenance_Cycle_c = 60));
    insert equipments;
    return equipments;
  }
```

```
public static List<Case> createMaintenanceRequest(List<Vehicle__c> vehicles){
    List<Case> maintenanceRequests = new List<Case>();
    maintenanceRequests.add(new Case(Vehicle_c = vehicles.get(1).ld, Type =
TYPE_ROUTINE_MAINTENANCE, Date_Reported_c = Date.today()));
    maintenanceRequests.add(new Case(Vehicle_c = vehicles.get(2).ld, Type =
TYPE_ROUTINE_MAINTENANCE, Date_Reported_c = Date.today()));
    insert maintenanceRequests;
    return maintenanceRequests;
 }
  public static List<Equipment_Maintenance_Item__c>
createJoinRecords(List<Product2> equipment, List<Case> maintenanceRequest){
    List<Equipment_Maintenance_Item_c> joinRecords = new
List<Equipment_Maintenance_Item_c>();
    joinRecords.add(new Equipment_Maintenance_Item_c(Equipmentc =
equipment.get(0).ld, Maintenance_Request_c = maintenanceRequest.get(0).ld));
    joinRecords.add(new Equipment_Maintenance_Item_c(Equipmentc =
equipment.get(1).ld, Maintenance_Request_c = maintenanceRequest.get(0).ld));
    joinRecords.add(new Equipment_Maintenance_Item_c(Equipmentc =
equipment.get(2).ld, Maintenance_Request_c = maintenanceRequest.get(0).ld));
    joinRecords.add(new Equipment_Maintenance_Item_c(Equipmentc =
equipment.get(0).ld, Maintenance_Request_c = maintenanceRequest.get(1).ld));
    joinRecords.add(new Equipment_Maintenance_Item_c(Equipmentc =
equipment.get(1).ld, Maintenance_Request_c = maintenanceRequest.get(1).ld));
    joinRecords.add(new Equipment_Maintenance_Item_c(Equipmentc =
equipment.get(2).ld, Maintenance_Request_c = maintenanceRequest.get(1).ld));
    insert joinRecords;
    return joinRecords;
 }
```

#### CreateDefaultDataTest:

```
@isTest
private class CreateDefaultDataTest {
  @isTest
  static void createData_test(){
```

```
Test.startTest();
    CreateDefaultData.createDefaultData();
    List<Vehicle_c> vehicles = [SELECT Id FROM Vehicle_c];
    List<Product2> equipment = [SELECT Id FROM Product2];
    List<Case> maintenanceRequest = [SELECT Id FROM Case];
    List<Equipment_Maintenance_Item_c> joinRecords = [SELECT Id FROM]
Equipment_Maintenance_Item_c];
    System.assertEquals(4, vehicles.size(), 'There should have been 4 vehicles
created');
    System.assertEquals(4, equipment.size(), 'There should have been 4 equipment
created');
    System.assertEquals(2, maintenanceRequest.size(), 'There should have been 2
maintenance request created');
    System.assertEquals(6, joinRecords.size(), 'There should have been 6 equipment
maintenance items created');
 }
  @isTest
  static void updateCustomSetting_test(){
    How_We_Roll_Settings_c customSetting =
How_We_Roll_Settings_c.getOrgDefaults();
    customSetting.ls_Data_Created__c = false;
    upsert customSetting;
    System.assertEquals(false, CreateDefaultData.isDataCreated(), 'The custom setting
How_We_Roll_Settings_c.ls_Data_Created_c should be false');
    customSetting.ls_Data_Created__c = true;
    upsert customSetting;
    System.assertEquals(true, CreateDefaultData.isDataCreated(), 'The custom setting
How_We_Roll_Settings_c.ls_Data_Created_c should be true');
 }
```

MaintenanceRequest:

```
trigger MaintenanceRequest on Case (before update, after update) {
  if(Trigger.isUpdate && Trigger.isAfter){
    MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);
  }
}
```

### MaintenanceRequestHelper:

```
public with sharing class MaintenanceRequestHelper {
  public static void updateworkOrders(List<Case> updWorkOrders, Map<Id,Case>
nonUpdCaseMap) {
    Set<Id> validIds = new Set<Id>();
    For (Case c : updWorkOrders){
      if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
        if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
          validIds.add(c.Id);
        }
      }
    //When an existing maintenance request of type Repair or Routine Maintenance is
closed.
    //create a new maintenance request for a future routine checkup.
    if (!validIds.isEmpty()){
      Map<Id,Case> closedCases = new Map<Id,Case>([SELECT Id, Vehicle_c,
Equipmentc, Equipmentr. Maintenance_Cycle_c,
                               (SELECT Id,Equipment_c,Quantityc FROM
Equipment_Maintenance_Items_r)
                               FROM Case WHERE Id IN :validIds]);
      Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
      //calculate the maintenance request due dates by using the maintenance cycle
defined on the related equipment records.
      AggregateResult[] results = [SELECT Maintenance_Request__c,
                      MIN(Equipment_r.Maintenance_Cycle_c)cycle
                      FROM Equipment_Maintenance_Item__c
                      WHERE Maintenance_Request_c IN :ValidIds GROUP BY
Maintenance_Request_c];
      for (AggregateResult ar : results){
        maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal)
```

```
ar.get('cycle'));
      List<Case> newCases = new List<Case>();
      for(Case cc : closedCases.values()){
        Case nc = new Case (
          ParentId = cc.Id,
          Status = 'New'.
          Subject = 'Routine Maintenance',
          Type = 'Routine Maintenance',
          Vehicle_c = cc.Vehicle_c,
          Equipment_c =cc.Equipment_c,
          Origin = 'Web',
          Date_Reported__c = Date.Today()
        );
        //If multiple pieces of equipment are used in the maintenance request,
        //define the due date by applying the shortest maintenance cycle to today's
date.
        //If (maintenanceCycles.containskey(cc.ld)){
          nc.Date_Due__c = Date.today().addDays((Integer)
maintenanceCycles.get(cc.ld));
        //} else {
        // nc.Date_Due_c = Date.today().addDays((Integer)
cc.Equipmentr.maintenance_Cycle_c);
        //}
        newCases.add(nc);
      }
      insert newCases:
      List<Equipment_Maintenance_Item_c> clonedList = new
List<Equipment_Maintenance_Item_c>();
      for (Case nc : newCases){
        for (Equipment_Maintenance_Item_c clonedListItem:
closedCases.get(nc.ParentId).Equipment_Maintenance_Items_r){
          Equipment_Maintenance_Item__c item = clonedListItem.clone();
          item.Maintenance_Request__c = nc.ld;
          clonedList.add(item);
      }
```

```
insert clonedList;
}
}
```

## MaintenanceRequestHelperTest:

```
@isTest
public with sharing class MaintenanceRequestHelperTest {
  // createVehicle
  private static Vehicle__c createVehicle(){
    Vehicle_c vehicle = new Vehicle_C(name = 'Testing Vehicle');
    return vehicle;
  }
  // createEquipment
  private static Product2 createEquipment(){
    product2 equipment = new product2(name = 'Testing equipment',
                      lifespan_months__c = 10,
                      maintenance_cycle__c = 10,
                      replacement_part__c = true);
    return equipment;
  // createMaintenanceRequest
  private static Case createMaintenanceRequest(id vehicleId, id equipmentId){
    case cse = new case(Type='Repair',
              Status='New',
               Origin='Web',
              Subject='Testing subject',
               Equipment_c=equipmentId,
              Vehicle_c=vehicleId);
    return cse;
  }
  // createEquipmentMaintenanceItem
  private static Equipment_Maintenance_Item__c createEquipmentMaintenanceItem(id
equipmentId,id requestId){
    Equipment_Maintenance_Item_c equipmentMaintenanceItem = new
Equipment_Maintenance_Item_c(
      Equipment_c = equipmentId,
```

```
Maintenance_Request__c = requestId);
    return equipmentMaintenanceItem;
  }
  @isTest
  private static void testPositive(){
    Vehicle__c vehicle = createVehicle();
    insert vehicle:
    id vehicleId = vehicle.Id:
    Product2 equipment = createEquipment();
    insert equipment;
    id equipmentId = equipment.Id;
    case createdCase = createMaintenanceRequest(vehicleId,equipmentId);
    insert createdCase;
    Equipment_Maintenance_Item__c equipmentMaintenanceItem =
createEquipmentMaintenanceItem(equipmentId,createdCase.id);
    insert equipmentMaintenanceItem;
    test.startTest();
    createdCase.status = 'Closed';
    update createdCase;
    test.stopTest();
    Case newCase = [Select id,
             subject,
             type,
             Equipment__c,
             Date_Reported__c,
             Vehicle__c,
             Date_Due__c
            from case
            where status ='New'];
    Equipment_Maintenance_Item__c workPart = [select id
                          from Equipment_Maintenance_Item__c
                          where Maintenance_Request__c =:newCase.ld];
    list<case> allCase = [select id from case];
    system.assert(allCase.size() == 2);
    system.assert(newCase != null);
    system.assert(newCase.Subject != null);
    system.assertEquals(newCase.Type, 'Routine Maintenance');
```

```
SYSTEM.assertEquals(newCase.Equipment_c, equipmentId);
    SYSTEM.assertEquals(newCase.Vehicle_c, vehicleId);
    SYSTEM.assertEquals(newCase.Date_Reported__c, system.today());
  }
  @isTest
  private static void testNegative(){
    Vehicle__C vehicle = createVehicle();
    insert vehicle:
    id vehicleId = vehicle.Id:
    product2 equipment = createEquipment();
    insert equipment;
    id equipmentId = equipment.Id;
    case createdCase = createMaintenanceRequest(vehicleId,equipmentId);
    insert createdCase:
    Equipment_Maintenance_Item__c workP =
createEquipmentMaintenanceItem(equipmentId, createdCase.Id);
    insert workP;
    test.startTest();
    createdCase.Status = 'Working';
    update createdCase;
    test.stopTest();
    list<case> allCase = [select id from case];
    Equipment_Maintenance_Item__c equipmentMaintenanceItem = [select id
                           from Equipment_Maintenance_Item__c
                           where Maintenance_Request__c = :createdCase.Id];
    system.assert(equipmentMaintenanceItem != null);
    system.assert(allCase.size() == 1);
  }
  @isTest
  private static void testBulk(){
    list<Vehicle_C> vehicleList = new list<Vehicle_C>();
    list<Product2> equipmentList = new list<Product2>();
    list<Equipment_Maintenance_Item_c> equipmentMaintenanceItemList = new
list<Equipment_Maintenance_Item_c>();
    list<case> caseList = new list<case>();
    list<id> oldCaseIds = new list<id>();
    for(integer i = 0; i < 300; i++){
```

```
vehicleList.add(createVehicle());
      equipmentList.add(createEquipment());
    }
    insert vehicleList;
    insert equipmentList;
    for(integer i = 0; i < 300; i++){
      caseList.add(createMaintenanceRequest(vehicleList.get(i).id,
equipmentList.get(i).id));
    }
    insert caseList:
    for(integer i = 0; i < 300; i++){
equipmentMaintenanceItemList.add(createEquipmentMaintenanceItem(equipmentList.
get(i).id, caseList.get(i).id));
    insert equipmentMaintenanceItemList;
    test.startTest();
    for(case cs : caseList){
      cs.Status = 'Closed';
      oldCaseIds.add(cs.Id);
    update caseList;
    test.stopTest();
    list<case> newCase = [select id
                   from case
                   where status ='New'];
    list<Equipment_Maintenance_Item__c> workParts = [select id
                                from Equipment_Maintenance_Item__c
                                where Maintenance_Request__c in: oldCaseIds];
    system.assert(newCase.size() == 300);
    list<case> allCase = [select id from case];
    system.assert(allCase.size() == 600);
}
```

### WarehouseCalloutService:

public with sharing class WarehouseCalloutService implements Queueable {

```
private static final String WAREHOUSE_URL = 'https://th-superbadge-
apex.herokuapp.com/equipment';
  //Write a class that makes a REST callout to an external warehouse system to get a
list of equipment that needs to be updated.
  //The callout's JSON response returns the equipment records that you upsert in
Salesforce.
  @future(callout=true)
  public static void runWarehouseEquipmentSync(){
    System.debug('go into runWarehouseEquipmentSync');
    Http http = new Http();
    HttpRequest request = new HttpRequest();
    request.setEndpoint(WAREHOUSE_URL);
    request.setMethod('GET');
    HttpResponse response = http.send(request);
    List<Product2> product2List = new List<Product2>();
    System.debug(response.getStatusCode());
    if (response.getStatusCode() == 200){
      List<Object> jsonResponse =
(List<Object>)JSON.deserializeUntyped(response.getBody());
      System.debug(response.getBody());
      //class maps the following fields:
      //warehouse SKU will be external ID for identifying which equipment records to
update within Salesforce
      for (Object jR : jsonResponse){
        Map<String,Object> mapJson = (Map<String,Object>)jR;
        Product2 product2 = new Product2();
        //replacement part (always true),
        product2.Replacement_Part__c = (Boolean) mapJson.get('replacement');
        product2.Cost__c = (Integer) mapJson.get('cost');
        //current inventory
        product2.Current_Inventory__c = (Double) mapJson.get('quantity');
        //lifespan
        product2.Lifespan_Months__c = (Integer) mapJson.get('lifespan');
        //maintenance cycle
        product2.Maintenance_Cycle__c = (Integer)
mapJson.get('maintenanceperiod');
```

```
product2.Warehouse_SKU__c = (String) mapJson.get('sku');
        product2.Name = (String) mapJson.get('name');
        product2.ProductCode = (String) mapJson.get('_id');
        product2List.add(product2);
      }
      if (product2List.size() > 0){
        upsert product2List;
        System.debug('Your equipment was synced with the warehouse one');
      }
    }
  public static void execute (QueueableContext context){
    System.debug('start runWarehouseEquipmentSync');
    runWarehouseEquipmentSync();
    System.debug('end runWarehouseEquipmentSync');
 }
WarehouseCalloutServiceMock:
@isTest
global class WarehouseCalloutServiceMock implements HttpCalloutMock {
  // implement http mock callout
  global static HttpResponse respond(HttpRequest request) {
    HttpResponse response = new HttpResponse();
    response.setHeader('Content-Type', 'application/json');
response.setBody('[{"_id":"55d66226726b611100aaf741","replacement":false,"quantity":5
,"name":"Generator 1000
kW","maintenanceperiod":365,"lifespan":120,"cost":5000,"sku":"100003"},{"_id":"55d66226
726b611100aaf742","replacement":true,"quantity":183,"name":"Cooling
Fan","maintenanceperiod":0,"lifespan":0,"cost":300,"sku":"100004"},{"_id":"55d66226726b6
11100aaf743","replacement":true,"quantity":143,"name":"Fuse
20A","maintenanceperiod":0,"lifespan":0,"cost":22,"sku":"100005"}]');
    response.setStatusCode(200);
    return response;
```

//warehouse SKU

}

#### WarehouseCalloutServiceTest:

```
@lsTest
private class WarehouseCalloutServiceTest {
  // implement your mock callout test here
 @isTest
  static void testWarehouseCallout() {
    test.startTest();
    test.setMock(HttpCalloutMock.class, new WarehouseCalloutServiceMock());
    WarehouseCalloutService.execute(null);
    test.stopTest();
    List<Product2> product2List = new List<Product2>();
    product2List = [SELECT ProductCode FROM Product2];
    System.assertEquals(3, product2List.size());
    System.assertEquals('55d66226726b611100aaf741',
product2List.get(0).ProductCode);
    System.assertEquals('55d66226726b611100aaf742',
product2List.get(1).ProductCode);
    System.assertEquals('55d66226726b611100aaf743',
product2List.get(2).ProductCode);
WarehouseSyncSchedule:
global with sharing class WarehouseSyncSchedule implements Schedulable {
  // implement scheduled code here
  global void execute (SchedulableContext ctx){
    System.enqueueJob(new WarehouseCalloutService());
 }
```

## WarehouseSyncScheduleTest:

```
@isTest
public with sharing class WarehouseSyncScheduleTest {
    // implement scheduled code here
    //
    @isTest static void test() {
```

```
String scheduleTime = '00 00 00 * * ? *';

Test.startTest();

Test.setMock(HttpCalloutMock.class, new WarehouseCalloutServiceMock());

String jobId = System.schedule('Warehouse Time to Schedule to test',

scheduleTime, new WarehouseSyncSchedule());

CronTrigger c = [SELECT State FROM CronTrigger WHERE Id =: jobId];

System.assertEquals('WAITING', String.valueOf(c.State), 'JobId does not match');

Test.stopTest();

}
```