

## APPEX TRIGGERS

### GET STARTED WITH APEX TRIGGERS:

1.AccountAddressTrigger.apxt

```
trigger AccountAddressTrigger on Account (before insert,before update) {
    for(Account account:Trigger.new){
        if(account.Match_Billing_Address__c==True)
        {
            account.ShippingPostalCode=account.BillingPostalCode;
        }
    }
}
```

### BULK APEX TRIGGERS:

1.ClosedOpportunityTrigger.apxt

```
trigger ClosedOpportunityTrigger on Opportunity (before insert,after update) {
    List<Task> tasklist = new List<Task>();
    for(Opportunity opp: Trigger.New){
        if(opp.StageName=='Closed Won'){
            tasklist.add(new Task(Subject='Follow Up Test Task',WhatId=opp.Id));
        }
    }
    if(tasklist.size(>0){
        insert tasklist;
    }
}
```

## APPEX TESTING

### GET STARTED WITH APEX UNIT TEST:

1.VerifyDate.apxc

```
public class VerifyDate {

    //method to handle potential checks against two dates
    public static Date CheckDates(Date date1, Date date2) {
        //if date2 is within the next 30 days of date1, use date2. Otherwise use the
end of the month
        if(DateWithin30Days(date1,date2)) {
            return date2;
        } else {
            return SetEndOfMonthDate(date1);
        }
    }

    //method to check if date2 is within the next 30 days of date1
    @TestVisible private static Boolean DateWithin30Days(Date date1, Date date2) {
        //check for date2 being in the past
        if( date2 < date1) { return false; }

        //check that date2 is within (>=) 30 days of date1
        Date date30Days = date1.addDays(30); //create a date 30 days away from date1
        if( date2 >= date30Days ) { return false; }
        else { return true; }
    }

    //method to return the end of the month of a given date
    @TestVisible private static Date SetEndOfMonthDate(Date date1) {
        Integer totalDays = Date.daysInMonth(date1.year(), date1.month());
        Date lastDay = Date.newInstance(date1.year(), date1.month(), totalDays);
        return lastDay;
    }
}
```

```

    }
}
2.TestVerifyDate.apxc
@isTest
public class TestVerifyDate {
    @isTest static void Test_CheckDates_case1(){
        Date D= VerifyDate.CheckDates(date.parse('01/01/2020'),date.parse('01/05/2020'));
        System.assertEquals(date.parse('01/05/2020'),D);
    }
    @isTest static void Test_CheckDates_case2(){
        Date D= VerifyDate.CheckDates(date.parse('01/01/2020'),date.parse('05/05/2020'));
        System.assertEquals(date.parse('01/31/2020'),D);
    }
    @isTest static void Test_DateWithin30Days_case1(){
        Boolean flag =
VerifyDate.DateWithin30Days(date.parse('01/01/2020'),date.parse('12/30/2019'));
        System.assertEquals(false, flag);
    }
    @isTest static void Test_DateWithin30Days_case2(){
        Boolean flag =
VerifyDate.DateWithin30Days(date.parse('01/01/2020'),date.parse('02/02/2020'));
        System.assertEquals(false, flag);
    }
    @isTest static void Test_DateWithin30Days_case3(){
        Boolean flag =
VerifyDate.DateWithin30Days(date.parse('01/01/2020'),date.parse('01/15/2020'));
        System.assertEquals(true, flag);
    }
    @isTest static void Test_SetEndOfMonthDate(){
        Date returndate = VerifyDate.SetEndOfMonthDate(date.parse('01/01/2020'));
    }
}

```

### TEST APEX TRIGGERS:

#### 1.RestrictContactByName.apxt

trigger RestrictContactByName on Contact (before insert, before update) {

```

    //check contacts prior to insert or update for invalid data
    For (Contact c : Trigger.New) {
        if(c.LastName == 'INVALIDNAME') { //invalidname is invalid
            c.AddError('The Last Name "' + c.LastName + '" is not allowed for DML');
        }
    }
}

```

### CREATE TEST DATA FOR APEX TESTS:

#### 1.RandomContactFactory.apxc

```

public class RandomContactFactory {
    public static List<Contact> generateRandomContacts(Integer numcnt,string lastname){
        List<Contact> contacts = new List<Contact>();
        for(Integer i=0;i<numcnt;i++)
        {
            Contact cnt = new Contact(FirstName = 'Test ' + i,LastName = lastname);
            contacts.add(cnt);
        }
        return contacts;
    }
}

```

```
}  
}
```

## ASYNCHRONOUS APEX

### USE FUTURE METHODS:

#### 1.AccountProcessor.apxc

```
public class AccountProcessor {  
    @future  
    public static void countContacts(List<Id> accountIds){  
        List<Account> accounts = [Select Id, Name from Account Where Id IN : accountIds];  
        List<Account> updatedAccounts = new List<Account>();  
        for(Account account : accounts){  
            account.Number_of_Contacts__c = [Select count() from Contact Where AccountId =:  
account.Id];  
            System.debug('No Of Contacts = ' + account.Number_of_Contacts__c);  
            updatedAccounts.add(account);  
        }  
        update updatedAccounts;  
    }  
}
```

#### 2.AccountProcessorTest.apxc

```
@isTest  
public class AccountProcessorTest {  
    @isTest  
    public static void testNoOfContacts(){  
        Account a = new Account();  
        a.Name = 'Test Account';  
        Insert a;  
  
        Contact c = new Contact();  
        c.FirstName = 'Bob';  
        c.LastName = 'Willie';  
        c.AccountId = a.Id;  
        Contact c2 = new Contact();  
        c2.FirstName = 'Tom';  
        c2.LastName = 'Cruise';  
        c2.AccountId = a.Id;  
        List<Id> acctIds = new List<Id>();  
        acctIds.add(a.Id);  
        Test.startTest();  
        AccountProcessor.countContacts(acctIds);  
        Test.stopTest();  
    }  
}
```

### USE BATCH APEX:

#### 1.LeadProcessor.apxc

```
public class LeadProcessor implements Database.Batchable<sObject> {  
    public Database.QueryLocator start(Database.BatchableContext bc) {  
        // collect the batches of records or objects to be passed to execute  
        return Database.getQueryLocator([Select LeadSource From Lead ]);  
    }  
    public void execute(Database.BatchableContext bc, List<Lead> leads){  
        // process each batch of records  
        for (Lead Lead : leads) {  
            lead.LeadSource = 'Dreamforce';  
        }  
    }  
}
```

```

    }
    update leads;
}
public void finish(Database.BatchableContext bc){
}
}
2.LeadProcessorTest.apxc
@isTest
public class LeadProcessorTest {
    @testSetup
    static void setup() {
        List<Lead> leads = new List<Lead>();
        for(Integer counter=0 ;counter <200;counter++){
            Lead lead = new Lead();
            lead.FirstName ='FirstName';
            lead.LastName ='LastName'+counter;
            lead.Company ='demo'+counter;
            leads.add(lead);
        }
        insert leads;
    }

    @isTest static void test() {
        Test.startTest();
        LeadProcessor leadProcessor = new LeadProcessor();
        Id batchId = Database.executeBatch(leadProcessor);
        Test.stopTest();
    }
}

```

### CONTROL PROCESSES WITH QUEUEABLE APEX:

#### 1.AddPrimaryContact.apxc

```

public class AddPrimaryContact implements Queueable
{
    private Contact c;
    private String state;
    public AddPrimaryContact(Contact c, String state)
    {
        this.c = c;
        this.state = state;
    }
    public void execute(QueueableContext context)
    {
        List<Account> ListAccount = [SELECT ID, Name ,(Select id,FirstName,LastName from
contacts ) FROM ACCOUNT WHERE BillingState = :state LIMIT 200];
        List<Contact> lstContact = new List<Contact>();
        for (Account acc:ListAccount)
        {
            Contact cont = c.clone(false,false,false,false);
            cont.AccountId = acc.id;
            lstContact.add( cont );
        }
        if(lstContact.size() >0 )
        {
            insert lstContact;
        }
    }
}

```

```

    }
}
}
2.AddPrimaryContactTest.apxc
@isTest
public class AddPrimaryContactTest
{
    @isTest static void TestList()
    {
        List<Account> Teste = new List <Account>();
        for(Integer i=0;i<50;i++)
        {
            Teste.add(new Account(BillingState = 'CA', name = 'Test'+i));
        }
        for(Integer j=0;j<50;j++)
        {
            Teste.add(new Account(BillingState = 'NY', name = 'Test'+j));
        }
        insert Teste;
        Contact co = new Contact();
        co.FirstName='demo';
        co.LastName = 'demo';
        insert co;
        String state = 'CA';

        AddPrimaryContact apc = new AddPrimaryContact(co, state);
        Test.startTest();
        System.enqueueJob(apc);
        Test.stopTest();
    }
}

```

### SCHEDULE JOBS USING APEX SCHEDULER:

```

1.DailyLeadProcessor.apxc
public class DailyLeadProcessor implements Schedulable {
    Public void execute(SchedulableContext SC){
        List<Lead> LeadObj=[SELECT Id from Lead where LeadSource=null limit 200];
        for(Lead l:LeadObj){
            l.LeadSource='Dreamforce';
            update l;
        }
    }
}
2.DailyLeadProcessorTest.apxc
@isTest
private class DailyLeadProcessorTest {
    static testMethod void testDailyLeadProcessor() {
        String CRON_EXP = '0 0 1 * * ?';
        List<Lead> IList = new List<Lead>();
        for (Integer i = 0; i < 200; i++) {
            IList.add(new Lead(LastName='Dreamforce'+i, Company='Test1 Inc.',
Status='Open - Not Contacted'));
        }
        insert IList;
        Test.startTest();
    }
}

```

```

        String jobId = System.schedule('DailyLeadProcessor', CRON_EXP, new
DailyLeadProcessor());
    }
}

```

## APEX INTEGRATION SERVICES

### APEX REST CALLOUTS:

#### 1. AnimalLocator.apxc

```

public class AnimalLocator{
    public static String getAnimalNameById(Integer x){
        Http http = new Http();
        HttpRequest req = new HttpRequest();
        req.setEndpoint('https://th-apex-http-callout.herokuapp.com/animals/' + x);
        req.setMethod('GET');
        Map<String, Object> animal= new Map<String, Object>();
        HttpResponse res = http.send(req);
        if (res.getStatusCode() == 200) {
            Map<String, Object> results = (Map<String,
Object>)JSON.deserializeUntyped(res.getBody());
            animal = (Map<String, Object>) results.get('animal');
        }
        return (String)animal.get('name');
    }
}

```

#### 2. AnimalLocatorMock.apxc

@isTest

global class AnimalLocatorMock implements HttpCalloutMock {

// Implement this interface method

global HTTPResponse respond(HTTPRequest request) {

// Create a fake response

HttpResponse response = new HttpResponse();

response.setHeader('Content-Type', 'application/json');

response.setBody("{\"animals\": [\"majestic badger\", \"fluffy bunny\", \"scary bear\", \"chicken\", \"mighty moose\"]}");

response.getStatusCode(200);

return response;

}

}

#### 3. AnimalLocatorTest.apxc

@isTest

private class AnimalLocatorTest{

@isTest static void AnimalLocatorMock1() {

Test.setMock(HttpCalloutMock.class, new AnimalLocatorMock());

String result = AnimalLocator.getAnimalNameById(3);

String expectedResult = 'chicken';

System.assertEquals(result, expectedResult );

}

}

### APEX SOAP CALLOUTS:

#### 1. ParkService.apxc

public class ParkService {

public class byCountryResponse {

public String[] return\_x;

```

        private String[] return_x_type_info = new String[]{'return','http://parks.services/',null,'0','-
1','false'};
        private String[] apex_schema_type_info = new
String[]{'http://parks.services/','false','false'};
        private String[] field_order_type_info = new String[]{'return_x'};
    }
    public class byCountry {
        public String arg0;
        private String[] arg0_type_info = new
String[]{'arg0','http://parks.services/',null,'0','1','false'};
        private String[] apex_schema_type_info = new
String[]{'http://parks.services/','false','false'};
        private String[] field_order_type_info = new String[]{'arg0'};
    }
    public class ParksImplPort {
        public String endpoint_x = 'https://th-apex-soap-service.herokuapp.com/service/parks';
        public Map<String,String> inputHttpHeaders_x;
        public Map<String,String> outputHttpHeaders_x;
        public String clientCertName_x;
        public String clientCert_x;
        public String clientCertPasswd_x;
        public Integer timeout_x;
        private String[] ns_ma_ptype_info = new String[]{'http://parks.services/', 'ParkService'};
        public String[] byCountry(String arg0) {
            ParkService.byCountry request_x = new ParkService.byCountry();
            request_x.arg0 = arg0;
            ParkService.byCountryResponse response_x;
            Map<String, ParkService.byCountryResponse> response_map_x = new Map<String,
ParkService.byCountryResponse>();
            response_map_x.put('response_x', response_x);
            WebServiceCallout.invoke(
                this,
                request_x,
                response_map_x,
                new String[]{endpoint_x,
                "",
                'http://parks.services/',
                'byCountry',
                'http://parks.services/',
                'byCountryResponse',
                'ParkService.byCountryResponse'}
            );
            response_x = response_map_x.get('response_x');
            return response_x.return_x;
        }
    }
}

```

2.ParkServiceMock.apxc

@isTest

global class ParkServiceMock implements WebServiceMock {

global void doInvoke(

Object stub,

Object request,

Map<String, Object> response,

String endpoint,

```

        String soapAction,
        String requestName,
        String responseNS,
        String responseName,
        String responseType) {
    // start - specify the response you want to send
    ParkService.byCountryResponse response_x = new
ParkService.byCountryResponse();
    response_x.return_x = new List<String>{'Yellowstone', 'Mackinac National Park',
'Yosemite'};
    // end
    response.put('response_x', response_x);
}
}
3.ParkLocator.apxc
public class ParkLocator {
    public static string[] country(string theCountry) {
        ParkService.ParksImplPort parkSvc = new ParkService.ParksImplPort(); // remove
space
        return parkSvc.byCountry(theCountry);
    }
}
4.ParkLocatorTest.apxc
@isTest
private class ParkLocatorTest {
    @isTest static void testCallout() {
        Test.setMock(WebServiceMock.class, new ParkServiceMock ());
        String country = 'United States';
        List<String> result = ParkLocator.country(country);
        List<String> parks = new List<String>{'Yellowstone', 'Mackinac National Park',
'Yosemite'};
        System.assertEquals(parks, result);
    }
}

```

### APEX WEB SERVICES:

```

1.AccountManager.apxc
@RestResource(urlMapping='/Accounts/*/contacts')
global class AccountManager {
    @HttpGet
    global static Account getAccount() {
        RestRequest req = RestContext.request;
        String accId = req.requestURI.substringBetween('Accounts/', '/contacts');
        Account acc = [SELECT Id, Name, (SELECT Id, Name FROM Contacts)
            FROM Account WHERE Id = :accId];
        return acc;
    }
}
2.AccountManagerTest.apxc
@isTest
private class AccountManagerTest {
    private static testMethod void getAccountTest1() {
        Id recordId = createTestRecord();
        // Set up a test request
        RestRequest request = new RestRequest();
    }
}

```



```

        request.requestUri = 'https://na1.salesforce.com/services/apexrest/Accounts/' + recordId
        + '/contacts' ;
        request.httpMethod = 'GET';
        RestContext.request = request;
        // Call the method to test
        Account thisAccount = AccountManager.getAccount();
        // Verify results
        System.assert(thisAccount != null);
        System.assertEquals('Test record', thisAccount.Name);
    }
    // Helper method
    static Id createTestRecord() {
        // Create test record
        Account TestAcc = new Account(
            Name='Test record');
        insert TestAcc;
        Contact TestCon= new Contact(
            LastName='Test',
            AccountId = TestAcc.id);
        return TestAcc.Id;
    }
}

```

## APEX SPECIALIST SUPERBADGE

### AUTOMATE RECORD CREATION:

#### 1.MaintenanceRequest.apxt

```

trigger MaintenanceRequest on Case (before update, after update) {
    if (Trigger.isUpdate && Trigger.isAfter){
        MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);
    }
}

```

#### 2.MaintenanceRequestHelper.apxc

```

public with sharing class MaintenanceRequestHelper {
    public static void updateWorkOrders(List<Case> updWorkOrders, Map<Id,Case>
nonUpdCaseMap) {
        Set<Id> validIds = new Set<Id>();

        For (Case c : updWorkOrders){
            if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
                if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
                    validIds.add(c.Id);
                }
            }
        }

        if (!validIds.isEmpty()){
            List<Case> newCases = new List<Case>();
            Map<Id,Case> closedCasesM = new Map<Id,Case>([SELECT Id, Vehicle__c,
Equipment__c, Equipment__r.Maintenance_Cycle__c,(SELECT
Id,Equipment__c,Quantity__c FROM Equipment_Maintenance_Items__r)

```

```

FROM Case WHERE Id IN :validIds]);
Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
AggregateResult[] results = [SELECT Maintenance_Request__c,
MIN(Equipment__r.Maintenance_Cycle__c)cycle FROM Equipment_Maintenance_Item__c
WHERE Maintenance_Request__c IN :ValidIds GROUP BY Maintenance_Request__c];
for (AggregateResult ar : results){
    maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal)
ar.get('cycle'));
}
for(Case cc : closedCasesM.values()){
    Case nc = new Case (
        ParentId = cc.Id,
        Status = 'New',
        Subject = 'Routine Maintenance',
        Type = 'Routine Maintenance',
        Vehicle__c = cc.Vehicle__c,
        Equipment__c =cc.Equipment__c,
        Origin = 'Web',
        Date_Reported__c = Date.Today()
    );
    If (maintenanceCycles.containsKey(cc.Id)){
        nc.Date_Due__c = Date.today().addDays((Integer)
maintenanceCycles.get(cc.Id));
    }
    newCases.add(nc);
}
insert newCases;
List<Equipment_Maintenance_Item__c> clonedWPs = new
List<Equipment_Maintenance_Item__c>();
for (Case nc : newCases){
    for (Equipment_Maintenance_Item__c wp :
closedCasesM.get(nc.ParentId).Equipment_Maintenance_Items__r){
        Equipment_Maintenance_Item__c wpClone = wp.clone();
        wpClone.Maintenance_Request__c = nc.Id;
        ClonedWPs.add(wpClone);
    }
}
insert ClonedWPs;
}
}
}

```

## SYNCHRONIZATION SALESFORCE DATA WITH AN EXTERNAL SYSTEM:

1.WarehouseCalloutService.apxc

```

public with sharing class WarehouseCalloutService {
    private static final String WAREHOUSE_URL = 'https://th-superbadge-
apex.herokuapp.com/equipment';

```

```

//@future(callout=true)
public static void runWarehouseEquipmentSync(){
    Http http = new Http();
    HttpRequest request = new HttpRequest();
    request.setEndpoint(WAREHOUSE_URL);
    request.setMethod('GET');

```

```

    HttpResponse response = http.send(request);
    List<Product2> warehouseEq = new List<Product2>();
    if (response.getStatusCode() == 200){
        List<Object> jsonResponse =
        (List<Object>)JSON.deserializeUntyped(response.getBody());
        System.debug(response.getBody());

        for (Object eq : jsonResponse){
            Map<String,Object> mapJson = (Map<String,Object>)eq;
            Product2 myEq = new Product2();
            myEq.Replacement_Part__c = (Boolean) mapJson.get('replacement');
            myEq.Name = (String) mapJson.get('name');
            myEq.Maintenance_Cycle__c = (Integer) mapJson.get('maintenanceperiod');
            myEq.Lifespan_Months__c = (Integer) mapJson.get('lifespan');
            myEq.Cost__c = (Decimal) mapJson.get('lifespan');
            myEq.Warehouse_SKU__c = (String) mapJson.get('sku');
            myEq.Current_Inventory__c = (Double) mapJson.get('quantity');
            warehouseEq.add(myEq);
        }
        if (warehouseEq.size() > 0){
            upsert warehouseEq;
            System.debug('Your equipment was synced with the warehouse one');
            System.debug(warehouseEq);
        }
    }
}

```

#### SCHEDULE SYNCHRONIZATION USING APEX CODE:

```

1.WarehouseSyncSchedule.apxc
global class WarehouseSyncSchedule implements Schedulable {
    global void execute(SchedulableContext ctx) {

        WarehouseCalloutService.runWarehouseEquipmentSync();
    }
}

```

#### TEST AUTOMATION LOGIC:

```

1.MaintenanceRequestHelperTest.apxc
@istest
public with sharing class MaintenanceRequestHelperTest {
    private static final string STATUS_NEW = 'New';
    private static final string WORKING = 'Working';
    private static final string CLOSED = 'Closed';
    private static final string REPAIR = 'Repair';
    private static final string REQUEST_ORIGIN = 'Web';
    private static final string REQUEST_TYPE = 'Routine Maintenance';
    private static final string REQUEST_SUBJECT = 'Testing subject';
    PRIVATE STATIC Vehicle__c createVehicle(){
        Vehicle__c Vehicle = new Vehicle__C(name = 'SuperTruck');
        return Vehicle;
    }
    PRIVATE STATIC Product2 createEq(){
        product2 equipment = new product2(name = 'SuperEquipment',
            lifespan_months__C = 10,

```

```

        maintenance_cycle__C = 10,
        replacement_part__c = true);
    return equipment;
}
PRIVATE STATIC Case createMaintenanceRequest(id vehicleId, id equipmentId){
    case cs = new case(Type=REPAIR,
        Status=STATUS_NEW,
        Origin=REQUEST_ORIGIN,
        Subject=REQUEST_SUBJECT,
        Equipment__c=equipmentId,
        Vehicle__c=vehicleId);
    return cs;
}
PRIVATE STATIC Equipment_Maintenance_Item__c createWorkPart(id equipmentId,id
requestId){
    Equipment_Maintenance_Item__c wp = new
Equipment_Maintenance_Item__c(Equipment__c = equipmentId,
        Maintenance_Request__c = requestId);
    return wp;
}
@istest
private static void testMaintenanceRequestPositive(){
    Vehicle__c vehicle = createVehicle();
    insert vehicle;
    id vehicleId = vehicle.Id;
    Product2 equipment = createEq();
    insert equipment;
    id equipmentId = equipment.Id;

    case somethingToUpdate = createMaintenanceRequest(vehicleId,equipmentId);
    insert somethingToUpdate;
    Equipment_Maintenance_Item__c workP =
createWorkPart(equipmentId,somethingToUpdate.id);
    insert workP;
    test.startTest();
    somethingToUpdate.status = CLOSED;
    update somethingToUpdate;
    test.stopTest();
    Case newReq = [Select id, subject, type, Equipment__c, Date_Reported__c,
Vehicle__c, Date_Due__c
        from case
        where status =:STATUS_NEW];
    Equipment_Maintenance_Item__c workPart = [select id
        from Equipment_Maintenance_Item__c
        where Maintenance_Request__c =:newReq.Id];
    system.assert(workPart != null);
    system.assert(newReq.Subject != null);
    system.assertEquals(newReq.Type, REQUEST_TYPE);
    SYSTEM.assertEquals(newReq.Equipment__c, equipmentId);
    SYSTEM.assertEquals(newReq.Vehicle__c, vehicleId);
    SYSTEM.assertEquals(newReq.Date_Reported__c, system.today());
}
@istest
private static void testMaintenanceRequestNegative(){
    Vehicle__C vehicle = createVehicle();

```

```

insert vehicle;
id vehicleId = vehicle.Id;
product2 equipment = createEq();
insert equipment;
id equipmentId = equipment.Id;
case emptyReq = createMaintenanceRequest(vehicleId,equipmentId);
insert emptyReq;
Equipment_Maintenance_Item__c workP = createWorkPart(equipmentId,
emptyReq.Id);
insert workP;
test.startTest();
emptyReq.Status = WORKING;
update emptyReq;
test.stopTest();

list<case> allRequest = [select id
                        from case];
Equipment_Maintenance_Item__c workPart = [select id
                                           from Equipment_Maintenance_Item__c
                                           where Maintenance_Request__c = :emptyReq.Id];
system.assert(workPart != null);
system.assert(allRequest.size() == 1);
}
@istest
private static void testMaintenanceRequestBulk(){
    list<Vehicle__C> vehicleList = new list<Vehicle__C>();
    list<Product2> equipmentList = new list<Product2>();
    list<Equipment_Maintenance_Item__c> workPartList = new
list<Equipment_Maintenance_Item__c>();
    list<case> requestList = new list<case>();
    list<id> oldRequestIds = new list<id>();

    for(integer i = 0; i < 300; i++){
        vehicleList.add(createVehicle());
        equipmentList.add(createEq());
    }
    insert vehicleList;
    insert equipmentList;
    for(integer i = 0; i < 300; i++){
        requestList.add(createMaintenanceRequest(vehicleList.get(i).id,
equipmentList.get(i).id));
    }
    insert requestList;
    for(integer i = 0; i < 300; i++){
        workPartList.add(createWorkPart(equipmentList.get(i).id, requestList.get(i).id));
    }
    insert workPartList;
    test.startTest();
    for(case req : requestList){
        req.Status = CLOSED;
        oldRequestIds.add(req.Id);
    }
    update requestList;
    test.stopTest();

```

```

        list<case> allRequests = [select id
                                from case
                                where status =: STATUS_NEW];
        list<Equipment_Maintenance_Item__c> workParts = [select id
                                                         from Equipment_Maintenance_Item__c
                                                         where Maintenance_Request__c in: oldRequestIds];
        system.assert(allRequests.size() == 300);
    }
}
2.MaintenanceRequestHelper.apxc

public with sharing class MaintenanceRequestHelper {
    public static void updateWorkOrders(List<Case> updWorkOrders, Map<Id,Case>
nonUpdCaseMap) {
        Set<Id> validIds = new Set<Id>();

        For (Case c : updWorkOrders){
            if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
                if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
                    validIds.add(c.Id);
                }
            }
        }

        if (!validIds.isEmpty()){
            List<Case> newCases = new List<Case>();
            Map<Id,Case> closedCasesM = new Map<Id,Case>([SELECT Id, Vehicle__c,
Equipment__c, Equipment__r.Maintenance_Cycle__c,(SELECT
Id,Equipment__c,Quantity__c FROM Equipment_Maintenance_Items__r)
FROM Case WHERE Id IN :validIds]);
            Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
            AggregateResult[] results = [SELECT Maintenance_Request__c,
MIN(Equipment__r.Maintenance_Cycle__c)cycle FROM Equipment_Maintenance_Item__c
WHERE Maintenance_Request__c IN :ValidIds GROUP BY Maintenance_Request__c];

            for (AggregateResult ar : results){
                maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal)
ar.get('cycle'));
            }

            for(Case cc : closedCasesM.values()){
                Case nc = new Case (
                    ParentId = cc.Id,
                    Status = 'New',
                    Subject = 'Routine Maintenance',
                    Type = 'Routine Maintenance',
                    Vehicle__c = cc.Vehicle__c,
                    Equipment__c =cc.Equipment__c,
                    Origin = 'Web',
                    Date_Reported__c = Date.Today()

```

```

    );
    If (maintenanceCycles.containsKey(cc.Id)){
        nc.Date_Due__c = Date.today().addDays((Integer)
maintenanceCycles.get(cc.Id));
    }
    newCases.add(nc);
}
insert newCases;

List<Equipment_Maintenance_Item__c> clonedWPs = new
List<Equipment_Maintenance_Item__c>();
for (Case nc : newCases){
    for (Equipment_Maintenance_Item__c wp :
closedCasesM.get(nc.ParentId).Equipment_Maintenance_Items__r){
        Equipment_Maintenance_Item__c wpClone = wp.clone();
        wpClone.Maintenance_Request__c = nc.Id;
        ClonedWPs.add(wpClone);
    }
}
insert ClonedWPs;
}
}
}

```

### 3.MaintenanceRequest.apxt

```

trigger MaintenanceRequest on Case (before update, after update) {
    if (Trigger.isUpdate && Trigger.isAfter){
        MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);
    }
}

```

## TEST CALLOUT LOGIC:

### 1.WarehouseCalloutService.apxc

```

public with sharing class WarehouseCalloutService {
    private static final String WAREHOUSE_URL = 'https://th-superbadge-
apex.herokuapp.com/equipment';
    //@future(callout=true)
    public static void runWarehouseEquipmentSync(){
        Http http = new Http();
        HttpRequest request = new HttpRequest();
        request.setEndpoint(WAREHOUSE_URL);
        request.setMethod('GET');
        HttpResponse response = http.send(request);
        List<Product2> warehouseEq = new List<Product2>();
        if (response.getStatusCode() == 200){
            List<Object> jsonResponse =
(List<Object>)JSON.deserializeUntyped(response.getBody());
            System.debug(response.getBody());
            for (Object eq : jsonResponse){
                Map<String,Object> mapJson = (Map<String,Object>)eq;
                Product2 myEq = new Product2();
                myEq.Replacement_Part__c = (Boolean) mapJson.get('replacement');
                myEq.Name = (String) mapJson.get('name');
                myEq.Maintenance_Cycle__c = (Integer) mapJson.get('maintenanceperiod');
            }
        }
    }
}

```

```

        myEq.Lifespan_Months__c = (Integer) mapJson.get('lifespan');
        myEq.Cost__c = (Decimal) mapJson.get('lifespan');
        myEq.Warehouse_SKU__c = (String) mapJson.get('sku');
        myEq.Current_Inventory__c = (Double) mapJson.get('quantity');
        warehouseEq.add(myEq);
    }
    if (warehouseEq.size() > 0){
        upsert warehouseEq;
        System.debug('Your equipment was synced with the warehouse one');
        System.debug(warehouseEq);
    }
}
}
}
}
2.WarehouseCalloutServiceTest.apxc

```

```

@isTest
private class WarehouseCalloutServiceTest {
    @isTest
    static void testWareHouseCallout(){
        Test.startTest();
        // implement mock callout test here
        Test.setMock(HTTPCalloutMock.class, new WarehouseCalloutServiceMock());
        WarehouseCalloutService.runWarehouseEquipmentSync();
        Test.stopTest();
        System.assertEquals(1, [SELECT count() FROM Product2]);
    }
}

```

```

3.WarehouseCalloutServiceMock.apxc
@isTest
global class WarehouseCalloutServiceMock implements HttpCalloutMock {
    // implement http mock callout
    global static HttpResponse respond(HttpRequest request){
        System.assertEquals('https://th-superbadge-apex.herokuapp.com/equipment',
request.getEndpoint());
        System.assertEquals('GET', request.getMethod());
        // Create a fake response
        HttpResponse response = new HttpResponse();
        response.setHeader('Content-Type',
'application/json');
        response.setBody('{"_id":"55d66226726b611100aaf741","replacement":false,"quantity":5,"name":"Generator 1000 kW","maintenanceperiod":365,"lifespan":120,"cost":5000,"sku":"100003"}');
        response.setStatusCode(200);
        return response;
    }
}

```

### TEST SCHEDULING LOGIC:

```

1.WarehouseSyncSchedule.apxc
global class WarehouseSyncSchedule implements Schedulable {
    global void execute(SchedulableContext ctx) {

```



```

        WarehouseCalloutService.runWarehouseEquipmentSync();
    }
}

```

## 2.WarehouseSyncScheduleTest.apxc

```

@isTest
public class WarehouseSyncScheduleTest {
    @isTest static void WarehousescheduleTest(){
        String scheduleTime = '00 00 01 * * ?';
        Test.startTest();
        Test.setMock(HttpCalloutMock.class, new WarehouseCalloutServiceMock());
        String jobId=System.schedule('Warehouse Time To Schedule to Test', scheduleTime,
new WarehouseSyncSchedule());
        Test.stopTest();
        //Contains schedule information for a scheduled job. CronTrigger is similar to a cron job
on UNIX systems.
        // This object is available in API version 17.0 and later.
        CronTrigger a=[SELECT Id FROM CronTrigger where NextFireTime > today];
        System.assertEquals(jobID, a.Id,'Schedule ');
    }
}

```