

SALESFORCE DEVELOPER CATALYST

APEX TRIGGERS >

1. Get Started with Apex Triggers

AccountAddressTrigger

```
trigger AccountAddressTrigger on Account (before insert,before update) {
    for (Account account:Trigger.new){
        if(account.Match_Billing_Address__c == True){
            account.ShippingPostalCode = account.BillingPostalCode;
        }
    }
}
```

2. Bulk Apex Triggers

ClosedOpportunityTrigger

```
trigger ClosedOpportunityTrigger on Opportunity (after insert, after update) {
    List<Task> taskList = new List<Task>();

    for(Opportunity opp : Trigger.New){
        if(opp.StageName == 'Closed Won'){
            taskList.add(new Task(Subject = 'Follow Up Test Task', WhatId = opp.ID));
        }
    }
    if(taskList.size()>0){
        insert taskList;
    }
}
```

//

Apex Testing >

1. Get Started With Apex Unit Tests

VerifyDate

```
public class VerifyDate {  
  
    //method to handle potential checks against two dates  
    public static Date CheckDates(Date date1, Date date2) {  
        //if date2 is within the next 30 days of date1, use date2. Otherwise use  
the end of the month  
        if(DateWithin30Days(date1,date2)) {  
            return date2;  
        } else {  
            return SetEndOfMonthDate(date1);  
        }  
    }  
  
    //method to check if date2 is within the next 30 days of date1  
    @TestVisible private static Boolean DateWithin30Days(Date date1, Date date2) {  
        //check for date2 being in the past  
        if( date2 < date1) { return false; }  
  
        //check that date2 is within (>=) 30 days of date1  
        Date date30Days = date1.addDays(30); //create a date 30 days away from date1  
        if( date2 >= date30Days ) { return false; }  
        else { return true; }  
    }  
  
    //method to return the end of the month of a given date  
    @TestVisible private static Date SetEndOfMonthDate(Date date1) {  
        Integer totalDays = Date.daysInMonth(date1.year(), date1.month());  
        Date lastDay = Date.newInstance(date1.year(), date1.month(), totalDays);  
        return lastDay;  
    }  
}
```

TestVerifyDate

```

@isTest
public class TestVerifyDate {
    @isTest static void Test_CheckDates_case1(){
        Date D = VerifyDate.CheckDates(date.parse('01/01/2020'),
date.parse('01/05/2020'));
        System.assertEquals(date.parse('01/05/2020'), D);
    }
    @isTest static void Test_CheckDates_case2(){
        Date D = VerifyDate.CheckDates(date.parse('01/01/2020'),
date.parse('05/05/2020'));
        System.assertEquals(date.parse('01/31/2020'), D);
    }
    @isTest static void Test_DateWithin30Days_case1(){
        Boolean flag = VerifyDate.DateWithin30Days(date.parse('01/01/2020'),
date.parse('12/30/2019'));
        System.assertEquals(false, flag);
    }
    @isTest static void Test_DateWithin30Days_case2(){
        Boolean flag = VerifyDate.DateWithin30Days(date.parse('01/01/2020'),
date.parse('02/02/2020'));
        System.assertEquals(false, flag);
    }
    @isTest static void Test_DateWithin30Days_case3(){
        Boolean flag = VerifyDate.DateWithin30Days(date.parse('01/01/2020'),
date.parse('01/15/2020'));
        System.assertEquals(false, flag);
    }
    @isTest static void Test_SetEndOfMonthDate(){
        Date returndate = VerifyDate.SetEndOfMonthDate(date.parse('01/01/2020'));
    }
}

```

2. Test Apex Triggers

RestrictContactByName

```
trigger RestrictContactByName on Contact (before insert, before update) {

    //check contacts prior to insert or update for invalid data
    For (Contact c : Trigger.New) {
        if(c.LastName == 'INVALIDNAME') {      //invalidname is invalid
            c.AddError('The Last Name "'+c.LastName+'" is not allowed for
DML');
        }
    }
}
```

TestRestrictContactByName

@isTest

public class TestRestrictContactByName {

@isTest static void Test_insertupdateContact(){

Contact cnt = new Contact();

cnt.LastName = 'INVALIDNAME';

Test.startTest();

Database.SaveResult result = Database.insert(cnt, false);

Test.stopTest();

System.assert(!result.isSuccess());

System.assert(result.getErrors().size() > 0);

System.assertEquals('The Last Name "INVALIDNAME" is not allowed for DML',
result.getErrors()[0].getMessage());
 }

3. Create Test Data for Apex Tests

RandomContactFactory

public class RandomContactFactory {

```

    public static List<Contact> generateRandomContacts(Integer numcnt, string
lastname){
        List<Contact> contacts = new List<Contact>();
        for(Integer i=0;i<numcnt;i++){
            Contact cnt = new Contact(FirstName = 'Test'+i, LastName = lastname);
            contacts.add(cnt);
        }
        return contacts;
    }
}

```

//

Asynchronous Apex>

1.Use Future Methods

AccountProcessor

```

public class AccountProcessor {
    @future
    public static void countContacts(List<Id> accountIds){

        List<Account> accountsToUpdate = new List<Account>();

        List<Account> accounts = [Select Id, Name, (Select Id from Contacts) from Account
Where Id in :accountIds];

        For(Account acc:accounts){
            List<Contact> contactList = acc.Contacts;
            acc.Number_Of_Contacts__c = contactList.size();
            accountsToUpdate.add(acc);
        }
        update accountsToUpdate;
    }
}

```

AccountProcessorTest

```

@IsTest
private class AccountProcessorTest {
    @IsTest
    private static void testcountContacts(){
        Account newAccount = new Account(Name='Test Account');
        insert newAccount;

        Contact newContact1 = new Contact(FirstName='John',LastName='Doe',AccountId
= newAccount.Id);
        insert newContact1;

        Contact newContact2 = new Contact(FirstName='Jane',LastName='Doe',AccountId
= newAccount.Id);
        insert newContact2;

        List<Id> accountIds = new List<Id>();
        accountIds.add(newAccount.Id);

        Test.startTest();
        AccountProcessor.countContacts(accountIds);
        Test.stopTest();
    }
}

```

2.Use Batch Apex

LeadProcessor

```

global class LeadProcessor implements Database.Batchable<sObject> {
    global Integer count = 0;

    global Database.QueryLocator start(Database.BatchableContext bc){
        return Database.getQueryLocator('SELECT ID, LeadSource FROM Lead');
    }

    global void execute (Database.BatchableContext bc, List<Lead> L_list){
        List<lead> L_list_new = new List<lead>();
    }
}

```

```

        for(lead L:L_list){
            L.leadsource = 'Dreamforce';
            L_list_new.add(L);
            count +=1;
        }
        update L_list_new;
    }
    global void finish(Database.BatchableContext bc){
        system.debug('count = ' + count);
    }
}

```

LeadProcessorTest

```

@Test
public class LeadProcessorTest {

    @Test
    public static void testit(){
        List<lead> L_list = new List<lead>();

        for(Integer i=0; i<200; i++){
            Lead L = new lead();
            L.LastName = 'name' +i;
            L.Company = 'Company';
            L.Status = 'Random Status';
            L_list.add(L);
        }
        insert L_list;

        Test.startTest();
        LeadProcessor lp = new LeadProcessor();
        Id batchId = Database.executeBatch(lp);
        Test.stopTest();
    }
}

```

3.Control Processes With Queueable Apex

AddPrimaryContact

```
public class AddPrimaryContact implements Queueable{

    private Contact con;
    private String state;

    public AddPrimaryContact(Contact con, String state){
        this.con = con;
        this.state = state;
    }

    public void execute(QueueableContext context){
        List<Account> accounts = [Select Id, Name, (Select FirstName, LastName, Id from
contacts) from Account where BillingState = :state Limit 200];
        List<Contact> primaryContacts= new List<Contact>();

        for(Account acc:accounts){
            Contact c = con.clone();
            c.AccountId = acc.Id;
            primaryContacts.add(c);
        }
        if(primaryContacts.size() > 0){
            insert primaryContacts;
        }
    }
}
```

AddPrimaryContactTest

```
@isTest
public class AddPrimaryContactTest {
```



```

static testmethod void testQueueable(){
    List<Account> testAccounts = new List<Account>();
    for(Integer i=0;i<500;i++){
        testAccounts.add(new Account(Name = 'Account'+i,Billingstate='CA'));
    }
    for(Integer j=0;j<50;j++){
        testAccounts.add(new Account(Name='Account '+j,BillingState='NY'));
    }
    insert testAccounts;

    Contact testContact = new Contact(FirstName = 'John',LastName = 'Doe');
    insert testContact;

    AddPrimaryContact addit = new addPrimaryContact(testContact,'CA');

    Test.startTest();
    system.enqueueJob(addit);
    Test.stopTest();

    System.assertEquals(50,[Select count() from Contact where accountId in (Select Id
from Account where BillingState='CA')]);
}

```

4.Schedule Jods Using The Apex Scheduler

DailyLeadProcessor

```

global class DailyLeadProcessor implements Schedulable{
    global void execute(SchedulableContext ctx){
        List<lead> leadstoupdate = new List<lead>();
        List<Lead> leads = [Select id from Lead Where LeadSource = NULL Limit 200];

        for(Lead l:leads){
            l.LeadSource = 'Dreamforce';
            leadstoupdate.add(l);
        }
        update leadstoupdate;
    }
}

```

```
}  
}
```

DailyLeadProcessorTest

@isTest

private class DailyLeadProcessorTest {

public static String CRON_EXP = '0 0 0 15 7 ? 2022';

static testmethod void testScheduledJob(){

List<Lead> leads = new List<lead>();

for (Integer i=0; i<200; i++){

Lead l = new Lead(

FirstName = 'First '+i,

LastName = 'LastName',

Company = 'The Inc'

);

leads.add(l);

}

insert leads;

Test.startTest();

String jobId = System.schedule('ScheduledApexTest', CRON_EXP, new
DailyLeadProcessor());

Test.stopTest();

List<Lead> checkleads = new List<Lead>();

checkleads = [Select Id From Lead Where LeadSource = 'Dreamforce' and Company
= 'The Inc'];

System.assertEquals(200, checkleads.size(), 'Leads were not created');

}

}

////////////////////////////////////

Apex Integration Services>

1. Apex Rest Callouts

AnimalLocator

```
public class AnimalLocator {  
    public static String getAnimalNameById(Integer animalId) {  
        String animalName;  
        Http http = new Http();  
        HttpRequest request = new HttpRequest();  
        request.setEndpoint('https://th-apex-http-  
callout.herokuapp.com/animals/'+animalId);  
        request.setMethod('GET');  
        HttpResponse response = http.send(request);  
        if (response.getStatusCode() == 200){  
            Map<String, Object> r = (Map<String, Object>)  
                JSON.deserializeUntyped(response.getBody());  
            Map<String, Object> animal= (Map<String, Object>)r.get('animal');  
            animalName = string.valueOf(animal.get('name'));  
        }  
        return animalName;  
    }  
}
```

AnimalLocatorTest

```
@isTest  
private class AnimalLocatorTest {  
    @isTest static void getAnimalNameByIdTest() {  
        Test.setMock(HttpCalloutMock.class, new AnimalLocatorMock());  
        string response = AnimalLocator.getAnimalNameById(1);  
        System.assertEquals('chicken', response);  
    }  
}
```

AnimalLocatorMock

@isTest

```
global class AnimalLocatorMock implements HttpCalloutMock {  
    // Implement this interface method  
    global HTTPResponse respond(HTTPRequest request) {  
        // Create a fake response  
        HttpResponse response = new HttpResponse();  
        response.setHeader('Content-Type', 'application/json');  
        response.setBody('{"animal":{"id":1,"name":"chicken","eats":"chicken  
food","says":"cluck cluck"}}');  
        response.setStatusCode(200);  
        return response;  
    }  
}
```

2. Apex SOAP Callouts

ParkLocator

```
public class ParkLocator {  
    public static List<String> country(String country) {  
        ParkService.ParksImplPort parkservice =  
            new parkService.ParksImplPort();  
        return parkservice.byCountry(country);  
    }  
}
```

ParkLocatorTest

@isTest

```
private class ParkLocatorTest {  
    @isTest static void testCallout() {  
        // This causes a fake response to be generated
```

```

Test.setMock(WebServiceMock.class, new ParkServiceMock());
// Call the method that invokes a callout
String country = 'United States';
List<String> result = ParkLocator.country(country);
List<String> parks = new List<String>();
    parks.add('Yosemite');
    parks.add('Yellowstone');
    parks.add('Another Park');
// Verify that a fake result is returned
System.assertEquals(parks, result);
}
}

```

ParkServiceMock

```

@Test
global class ParkServiceMock implements WebServiceMock {
    global void doInvoke(
        Object stub,
        Object request,
        Map<String, Object> response,
        String endpoint,
        String soapAction,
        String requestName,
        String responseNS,
        String responseName,
        String responseType) {
        // start - specify the response you want to send
        List<String> parks = new List<string>();
            parks.add('Yosemite');
            parks.add('Yellowstone');
            parks.add('Another Park');
        ParkService.byCountryResponse response_x =
            new ParkService.byCountryResponse();
        response_x.return_x = parks;
        // end
        response.put('response_x', response_x);
    }
}

```

```
}  
}
```

ParkService

//Generated by wsdl2apex

```
public class ParkService {  
    public class byCountryResponse {  
        public String[] return_x;  
        private String[] return_x_type_info = new  
String[]{'return','http://parks.services/',null,'0','-1','false'};  
        private String[] apex_schema_type_info = new  
String[]{'http://parks.services/',false,false'};  
        private String[] field_order_type_info = new String[]{'return_x'};  
    }  
    public class byCountry {  
        public String arg0;  
        private String[] arg0_type_info = new  
String[]{'arg0','http://parks.services/',null,'0','1','false'};  
        private String[] apex_schema_type_info = new  
String[]{'http://parks.services/',false,false'};  
        private String[] field_order_type_info = new String[]{'arg0'};  
    }  
    public class ParksImplPort {  
        public String endpoint_x = 'https://th-apex-soap-  
service.herokuapp.com/service/parks';  
        public Map<String,String> inputHttpHeaders_x;  
        public Map<String,String> outputHttpHeaders_x;  
        public String clientCertName_x;  
        public String clientCert_x;  
        public String clientCertPasswd_x;  
        public Integer timeout_x;  
        private String[] ns_map_type_info = new String[]{'http://parks.services/',  
'ParkService'};  
        public String[] byCountry(String arg0) {  
            ParkService.byCountry request_x = new ParkService.byCountry();
```

```

        request_x.arg0 = arg0;
        ParkService.byCountryResponse response_x;
        Map<String, ParkService.byCountryResponse> response_map_x = new
Map<String, ParkService.byCountryResponse>();
        response_map_x.put('response_x', response_x);
        WebServiceCallout.invoke(
            this,
            request_x,
            response_map_x,
            new String[]{endpoint_x,
                ",
                'http://parks.services/',
                'byCountry',
                'http://parks.services/',
                'byCountryResponse',
                'ParkService.byCountryResponse'}
        );
        response_x = response_map_x.get('response_x');
        return response_x.return_x;
    }
}
}

```

3. Apex Web Services

AccountManager

```

@RestResource(urlMapping = '/Accounts/*/contacts')
global with sharing class AccountManager {

```

```

    @HttpGet
    global static Account getAccount(){
        RestRequest request = RestContext.request;
        String accountId = request.requestURI.substringBetween('Accounts/', '/contacts');
        Account result = [SELECT Id, Name, (Select Id, Name from Contacts) from Account
where Id=:accountId Limit 1];
        return result;
    }
}

```

```
}  
}
```

AccountManagerTest

@IsTest

```
private class AccountManagerTest {  
    @isTest static void testGetContactsByAccountId(){  
        Id recordId = createTestRecord();  
        RestRequest request = new RestRequest();  
        request.requestUri =  
'https://yourInstance.my.salesforce.com/services/apexrest/Accounts/'  
            + recordId+'/contacts';  
        request.httpMethod = 'GET';  
        RestContext.request = request;  
        Account thisAccount = AccountManager.getAccount();  
        System.assert(thisAccount != null);  
        System.assertEquals('Test record', thisAccount.Name);  
    }  
  
    static Id createTestRecord(){  
        Account accountTest = new Account(  
            Name ='Test record');  
        insert accountTest;  
  
        Contact contactTest = new Contact(  
            FirstName='John',  
            LastName='Doe',  
            AccountId=accountTest.Id  
        );  
        insert contactTest;  
  
        return accountTest.Id;  
    }  
}
```

```
////////////////////////////////////
```


Apex Specialist SuperBadge>

1. Automates Record Creation

MaintenanceRequest

```
trigger MaintenanceRequest on Case (before update, after update) {  
    if (Trigger.isUpdate && Trigger.isAfter) {  
        MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);  
    }  
}
```

MaintenanceRequestHelper

```
public with sharing class MaintenanceRequestHelper {  
    public static void updateWorkOrders(List<Case> updWorkOrders, Map<Id,Case>  
nonUpdCaseMap) {  
        Set<Id> validIds = new Set<Id>();  
        For (Case c : updWorkOrders) {  
            if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed') {  
                if (c.Type == 'Repair' || c.Type == 'Routine Maintenance') {  
                    validIds.add(c.Id);  
                }  
            }  
        }  
    }  
}
```

//When an existing maintenance request of type Repair or Routine Maintenance is closed,

//create a new maintenance request for a future routine checkup.

```
if (!validIds.isEmpty()) {  
    Map<Id,Case> closedCases = new Map<Id,Case>([SELECT Id, Vehicle__c,  
Equipment__c, Equipment__r.Maintenance_Cycle__c,  
                (SELECT Id,Equipment__c,Quantity__c FROM  
Equipment_Maintenance_Items__r)  
                FROM Case WHERE Id IN :validIds]);  
    Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
```

//calculate the maintenance request due dates by using the maintenance cycle defined on the related equipment records.

```
AggregateResult[] results = [SELECT Maintenance_Request__c,  
    MIN(Equipment__r.Maintenance_Cycle__c)cycle  
    FROM Equipment_Maintenance_Item__c  
    WHERE Maintenance_Request__c IN :ValidIds GROUP BY  
Maintenance_Request__c];
```

```
for (AggregateResult ar : results){  
    maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal)  
ar.get('cycle'));  
}
```

```
List<Case> newCases = new List<Case>();
```

```
for(Case cc : closedCases.values()){
```

```
    Case nc = new Case (  
        ParentId = cc.Id,  
        Status = 'New',  
        Subject = 'Routine Maintenance',  
        Type = 'Routine Maintenance',  
        Vehicle__c = cc.Vehicle__c,  
        Equipment__c =cc.Equipment__c,  
        Origin = 'Web',  
        Date_Reported__c = Date.Today()  
    );
```

//If multiple pieces of equipment are used in the maintenance request,
//define the due date by applying the shortest maintenance cycle to today's
date.

```
    //If (maintenanceCycles.containsKey(cc.Id)){  
        nc.Date_Due__c = Date.today().addDays((Integer)  
maintenanceCycles.get(cc.Id));  
    //} else {  
        // nc.Date_Due__c = Date.today().addDays((Integer)  
cc.Equipment__r.maintenance_Cycle__c);  
    //}
```

```

        newCases.add(nc);
    }

    insert newCases;

    List<Equipment_Maintenance_Item__c> clonedList = new
List<Equipment_Maintenance_Item__c>();
    for (Case nc : newCases){
        for (Equipment_Maintenance_Item__c clonedListItem :
closedCases.get(nc.ParentId).Equipment_Maintenance_Items__r){
            Equipment_Maintenance_Item__c item = clonedListItem.clone();
            item.Maintenance_Request__c = nc.Id;
            clonedList.add(item);
        }
    }
    insert clonedList;
}
}
}
}

```

2.Synchronize Salesforce data with an external system

WarehouseCalloutService

```

public with sharing class WarehouseCalloutService implements Queueable {
    private static final String WAREHOUSE_URL = 'https://th-superbadge-
apex.herokuapp.com/equipment';

```

system to get a list of equipment that needs to be updated.

```

@future(callout=true)
public static void runWarehouseEquipmentSync(){
    System.debug('go into runWarehouseEquipmentSync');
    Http http = new Http();
    HttpRequest request = new HttpRequest();

    request.setEndpoint(WAREHOUSE_URL);
    request.setMethod('GET');

```

```

HttpResponse response = http.send(request);

List<Product2> product2List = new List<Product2>();
System.debug(response.getStatusCode());
if (response.getStatusCode() == 200){
    List<Object> jsonResponse =
(List<Object>)JSON.deserializeUntyped(response.getBody());
    System.debug(response.getBody());

    for (Object jR : jsonResponse){
        Map<String,Object> mapJson = (Map<String,Object>)jR;
        Product2 product2 = new Product2();

        product2.Replacement_Part__c = (Boolean) mapJson.get('replacement');

        product2.Cost__c = (Integer) mapJson.get('cost');

        product2.Current_Inventory__c = (Double) mapJson.get('quantity');

        product2.Lifespan_Months__c = (Integer) mapJson.get('lifespan');

        product2.Maintenance_Cycle__c = (Integer)
mapJson.get('maintenanceperiod');

        product2.Warehouse_SKU__c = (String) mapJson.get('sku');

        product2.Name = (String) mapJson.get('name');
        product2.ProductCode = (String) mapJson.get('_id');
        product2List.add(product2);
    }

    if (product2List.size() > 0){
        upsert product2List;
        System.debug('Your equipment was synced with the warehouse one');
    }
}

```

```

    }

    public static void execute (QueueableContext context){
        System.debug('start runWarehouseEquipmentSync');
        runWarehouseEquipmentSync();
        System.debug('end runWarehouseEquipmentSync');
    }
}

```

3.Schedule synchronization using Apex code

WarehouseSyncSchedule

```

global with sharing class WarehouseSyncSchedule implements Schedulable{
    global void execute(SchedulableContext ctx){
        System.enqueueJob(new WarehouseCalloutService());
    }
}

```

4.Test Automation Logic

MaintenanceRequestHelperTest

```

@isTest
public with sharing class MaintenanceRequestHelperTest {

    // createVehicle
    private static Vehicle__c createVehicle(){
        Vehicle__c vehicle = new Vehicle__C(name = 'Testing Vehicle');
        return vehicle;
    }

    // createEquipment
    private static Product2 createEquipment(){
        product2 equipment = new product2(name = 'Testing equipment',
            lifespan_months__c = 10,
            maintenance_cycle__c = 10,
            replacement_part__c = true);
    }
}

```

```

        return equipment;
    }

    // createMaintenanceRequest
    private static Case createMaintenanceRequest(id vehicleId, id equipmentId){
        case cse = new case(Type='Repair',
            Status='New',
            Origin='Web',
            Subject='Testing subject',
            Equipment__c=equipmentId,
            Vehicle__c=vehicleId);
        return cse;
    }

    // createEquipmentMaintenanceItem
    private static Equipment_Maintenance_Item__c createEquipmentMaintenanceItem(id
equipmentId,id requestId){
        Equipment_Maintenance_Item__c equipmentMaintenanceItem = new
Equipment_Maintenance_Item__c(
            Equipment__c = equipmentId,
            Maintenance_Request__c = requestId);
        return equipmentMaintenanceItem;
    }

    @isTest
    private static void testPositive(){
        Vehicle__c vehicle = createVehicle();
        insert vehicle;
        id vehicleId = vehicle.Id;

        Product2 equipment = createEquipment();
        insert equipment;
        id equipmentId = equipment.Id;

        case createdCase = createMaintenanceRequest(vehicleId,equipmentId);
        insert createdCase;

        Equipment_Maintenance_Item__c equipmentMaintenanceItem =

```

```

createEquipmentMaintenanceItem(equipmentId,createdCase.id);
    insert equipmentMaintenanceItem;

test.startTest();
createdCase.status = 'Closed';
update createdCase;
test.stopTest();

Case newCase = [Select id,
                subject,
                type,
                Equipment__c,
                Date_Reported__c,
                Vehicle__c,
                Date_Due__c
                from case
                where status ='New'];

Equipment_Maintenance_Item__c workPart = [select id
                                           from Equipment_Maintenance_Item__c
                                           where Maintenance_Request__c =:newCase.Id];
list<case> allCase = [select id from case];
system.assert(allCase.size() == 2);

system.assert(newCase != null);
system.assert(newCase.Subject != null);
system.assertEquals(newCase.Type, 'Routine Maintenance');
SYSTEM.assertEquals(newCase.Equipment__c, equipmentId);
SYSTEM.assertEquals(newCase.Vehicle__c, vehicleId);
SYSTEM.assertEquals(newCase.Date_Reported__c, system.today());
}

@isTest
private static void testNegative(){
    Vehicle__C vehicle = createVehicle();
    insert vehicle;
    id vehicleId = vehicle.Id;

```

```

product2 equipment = createEquipment();
insert equipment;
id equipmentId = equipment.Id;

case createdCase = createMaintenanceRequest(vehicleId,equipmentId);
insert createdCase;

Equipment_Maintenance_Item__c workP =
createEquipmentMaintenanceItem(equipmentId, createdCase.Id);
insert workP;

test.startTest();
createdCase.Status = 'Working';
update createdCase;
test.stopTest();

list<case> allCase = [select id from case];

Equipment_Maintenance_Item__c equipmentMaintenanceItem = [select id
                    from Equipment_Maintenance_Item__c
                    where Maintenance_Request__c = :createdCase.Id];

system.assert(equipmentMaintenanceItem != null);
system.assert(allCase.size() == 1);
}

@isTest
private static void testBulk(){
    list<Vehicle__C> vehicleList = new list<Vehicle__C>();
    list<Product2> equipmentList = new list<Product2>();
    list<Equipment_Maintenance_Item__c> equipmentMaintenanceItemList = new
list<Equipment_Maintenance_Item__c>();
    list<case> caseList = new list<case>();
    list<id> oldCaseIds = new list<id>();

    for(integer i = 0; i < 300; i++){
        vehicleList.add(createVehicle());
        equipmentList.add(createEquipment());
    }
}

```



```

    }
    insert vehicleList;
    insert equipmentList;

    for(integer i = 0; i < 300; i++){
        caseList.add(createMaintenanceRequest(vehicleList.get(i).id,
equipmentList.get(i).id));
    }
    insert caseList;

    for(integer i = 0; i < 300; i++){

equipmentMaintenanceItemlist.add(createEquipmentMaintenanceItem(equipmentList.
get(i).id, caseList.get(i).id));
    }
    insert equipmentMaintenanceItemlist;

    test.startTest();
    for(case cs : caseList){
        cs.Status = 'Closed';
        oldCaseIds.add(cs.Id);
    }
    update caseList;
    test.stopTest();

    list<case> newCase = [select id
                        from case
                        where status ='New'];

    list<Equipment_Maintenance_Item__c> workParts = [select id
                                                    from Equipment_Maintenance_Item__c
                                                    where Maintenance_Request__c in: oldCaseIds];

    system.assert(newCase.size() == 300);

    list<case> allCase = [select id from case];

```

```

        system.assert(allCase.size() == 600);
    }
}

```

MaintenanceRequestHelper

```

public with sharing class MaintenanceRequestHelper {
    public static void updateWorkOrders(List<Case> updWorkOrders, Map<Id,Case>
nonUpdCaseMap) {
        Set<Id> validIds = new Set<Id>();
        For (Case c : updWorkOrders){
            if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
                if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
                    validIds.add(c.Id);
                }
            }
        }
    }
}

```

//When an existing maintenance request of type Repair or Routine Maintenance is closed,

//create a new maintenance request for a future routine checkup.

```

if (!validIds.isEmpty()){
    Map<Id,Case> closedCases = new Map<Id,Case>([SELECT Id, Vehicle__c,
Equipment__c, Equipment__r.Maintenance_Cycle__c,
                (SELECT Id,Equipment__c,Quantity__c FROM
Equipment_Maintenance_Items__r)
                FROM Case WHERE Id IN :validIds]);
    Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();

```

//calculate the maintenance request due dates by using the maintenance cycle defined on the related equipment records.

```

    AggregateResult[] results = [SELECT Maintenance_Request__c,
                MIN(Equipment__r.Maintenance_Cycle__c)cycle
                FROM Equipment_Maintenance_Item__c
                WHERE Maintenance_Request__c IN :ValidIds GROUP BY
Maintenance_Request__c];

```

```

        for (AggregateResult ar : results){
            maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal)
ar.get('cycle'));
        }

List<Case> newCases = new List<Case>();
for(Case cc : closedCases.values()){
    Case nc = new Case (
        ParentId = cc.Id,
        Status = 'New',
        Subject = 'Routine Maintenance',
        Type = 'Routine Maintenance',
        Vehicle__c = cc.Vehicle__c,
        Equipment__c =cc.Equipment__c,
        Origin = 'Web',
        Date_Reported__c = Date.Today()
    );

    //If multiple pieces of equipment are used in the maintenance request,
    //define the due date by applying the shortest maintenance cycle to today's
date.
    //If (maintenanceCycles.containsKey(cc.Id)){
        nc.Date_Due__c = Date.today().addDays((Integer)
maintenanceCycles.get(cc.Id));
    //} else {
        // nc.Date_Due__c = Date.today().addDays((Integer)
cc.Equipment__r.maintenance_Cycle__c);
    //}

    newCases.add(nc);
}

insert newCases;

List<Equipment_Maintenance_Item__c> clonedList = new
List<Equipment_Maintenance_Item__c>();
for (Case nc : newCases){
    for (Equipment_Maintenance_Item__c clonedListItem :

```

```

closedCases.get(nc.ParentId).Equipment_Maintenance_Items__r){
    Equipment_Maintenance_Item__c item = clonedListItem.clone();
    item.Maintenance_Request__c = nc.Id;
    clonedList.add(item);
}
}
insert clonedList;
}
}
}

```

MaintenanceRequest

```

trigger MaintenanceRequest on Case (before update, after update) {
    if(Trigger.isUpdate && Trigger.isAfter){
        MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);
    }
}

```

5. Test Callout Logic

WarehouseCalloutService

```

public with sharing class WarehouseCalloutService implements Queueable {
    private static final String WAREHOUSE_URL = 'https://th-superbadge-
apex.herokuapp.com/equipment';

```

//Write a class that makes a REST callout to an external warehouse system to get a list of equipment that needs to be updated.

//The callout's JSON response returns the equipment records that you upsert in Salesforce.

```

@future(callout=true)
public static void runWarehouseEquipmentSync(){
    System.debug('go into runWarehouseEquipmentSync');
    Http http = new Http();
    HttpRequest request = new HttpRequest();

```

```

request.setEndpoint(WAREHOUSE_URL);
request.setMethod('GET');
HttpResponse response = http.send(request);

List<Product2> product2List = new List<Product2>();
System.debug(response.getStatusCode());
if (response.getStatusCode() == 200){
    List<Object> jsonResponse =
(List<Object>)JSON.deserializeUntyped(response.getBody());
    System.debug(response.getBody());

    //class maps the following fields:
    //warehouse SKU will be external ID for identifying which equipment records to
update within Salesforce
    for (Object jR : jsonResponse){
        Map<String,Object> mapJson = (Map<String,Object>)jR;
        Product2 product2 = new Product2();
        //replacement part (always true),
        product2.Replacement_Part__c = (Boolean) mapJson.get('replacement');
        //cost
        product2.Cost__c = (Integer) mapJson.get('cost');
        //current inventory
        product2.Current_Inventory__c = (Double) mapJson.get('quantity');
        //lifespan
        product2.Lifespan_Months__c = (Integer) mapJson.get('lifespan');
        //maintenance cycle
        product2.Maintenance_Cycle__c = (Integer)
mapJson.get('maintenanceperiod');
        //warehouse SKU
        product2.Warehouse_SKU__c = (String) mapJson.get('sku');

        product2.Name = (String) mapJson.get('name');
        product2.ProductCode = (String) mapJson.get('_id');
        product2List.add(product2);
    }
    if (product2List.size() > 0){
        upsert product2List;
    }
}

```

```

        System.debug('Your equipment was synced with the warehouse one');
    }
}
}
public static void execute (QueueableContext context){
    System.debug('start runWarehouseEquipmentSync');
    runWarehouseEquipmentSync();
    System.debug('end runWarehouseEquipmentSync');
}
}

```

WarehouseCalloutServiceTest

```

@IsTest
private class WarehouseCalloutServiceTest {
    // implement your mock callout test here
    @isTest
    static void testWarehouseCallout() {
        test.startTest();
        test.setMock(HttpCalloutMock.class, new WarehouseCalloutServiceMock());
        WarehouseCalloutService.execute(null);
        test.stopTest();

        List<Product2> product2List = new List<Product2>();
        product2List = [SELECT ProductCode FROM Product2];

        System.assertEquals(3, product2List.size());
        System.assertEquals('55d66226726b611100aaf741',
product2List.get(0).ProductCode);
        System.assertEquals('55d66226726b611100aaf742',
product2List.get(1).ProductCode);
        System.assertEquals('55d66226726b611100aaf743',
product2List.get(2).ProductCode);
    }
}

```

WarehouseCalloutServiceMock

```

@isTest
global class WarehouseCalloutServiceMock implements HttpCalloutMock {
    // implement http mock callout
    global static HttpResponse respond(HttpRequest request) {

        HttpResponse response = new HttpResponse();
        response.setHeader('Content-Type', 'application/json');

        response.setBody('[{ "_id": "55d66226726b611100aaf741", "replacement": false, "quantity": 5, "name": "Generator 1000 kW", "maintenanceperiod": 365, "lifespan": 120, "cost": 5000, "sku": "100003" }, { "_id": "55d66226726b611100aaf742", "replacement": true, "quantity": 183, "name": "Cooling Fan", "maintenanceperiod": 0, "lifespan": 0, "cost": 300, "sku": "100004" }, { "_id": "55d66226726b611100aaf743", "replacement": true, "quantity": 143, "name": "Fuse 20A", "maintenanceperiod": 0, "lifespan": 0, "cost": 22, "sku": "100005" } ]');
        response.setStatusCode(200);

        return response;
    }
}

```

6. Test Scheduling Logic

WarehouseSyncSchedule

```

global with sharing class WarehouseSyncSchedule implements Schedulable{
    global void execute(SchedulableContext ctx){
        System.enqueueJob(new WarehouseCalloutService());
    }
}

```

WarehouseSyncScheduleTest

```

@isTest
public with sharing class WarehouseSyncScheduleTest {
    // implement scheduled code here
    //

```

```
@isTest static void test() {
    String scheduleTime = '00 00 00 * * ? *';
    Test.startTest();
    Test.setMock(HttpCalloutMock.class, new WarehouseCalloutServiceMock());
    String jobId = System.schedule('Warehouse Time to Schedule to test',
scheduleTime, new WarehouseSyncSchedule());
    CronTrigger c = [SELECT State FROM CronTrigger WHERE Id =: jobId];
    System.assertEquals('WAITING', String.valueOf(c.State), 'JobId does not match');

    Test.stopTest();
}
}
```

////////////////////////////////////THE END////////////////////////////////////