

APEX SPECIALIST SUPERBADGE -1

Appex Triggers

1.RandomContactFactory.apxc

```
public class RandomContactFactory {  
    public static List<Contact> generateRandomContacts(Integer num,String lastName){  
        List<Contact> contactList=new List<Contact>();  
        for(Integer i=1;i<=num;i++){  
            Contact ct=new Contact(FirstName='Test'+i,LastName=lastName);  
            contactList.add(ct);  
        }  
        return contactList;  
    }  
}
```

2.AccountAddressTrigger.apxt

```
trigger AccountAddressTrigger on Account (before insert,before update) {  
    for (Account account : trigger.new){  
        if(account.Match_Billing_Address__c==true){  
            account.ShippingPostalCode=account.BillingPostalCode;  
        }  
    }  
}
```

Bulk Apex Triggers

1.ClosedOpportunityTrigger.apxt

```
trigger ClosedOpportunityTrigger on Opportunity (after insert,after update) {  
    List<Task> taskList=new List<Task>();  
    for(Opportunity opp : Trigger.New){  
        if(opp.StageName == 'Closed Won'){  
            taskList.add(new Task(Subject='Follow Up Test Task',WhatId=opp.Id));  
        }  
    }  
    if(taskList.size()>0){  
        insert taskList;  
    }  
}
```

Apex Testings

1.VerifyDate.apxc

```
public class VerifyDate {

    //method to handle potential checks against two dates
    public static Date CheckDates(Date date1, Date date2) {
        //if date2 is within the next 30 days of date1, use date2. Otherwise use the end
of the month
        if(DateWithin30Days(date1,date2)) {
            return date2;
        } else {
            return SetEndOfMonthDate(date1);
        }
    }

    //method to check if date2 is within the next 30 days of date1
    private static Boolean DateWithin30Days(Date date1, Date date2) {
        //check for date2 being in the past
        if( date2 < date1) { return false; }

        //check that date2 is within (>=) 30 days of date1
        Date date30Days = date1.addDays(30); //create a date 30 days away from date1
        if( date2 >= date30Days ) { return false; }
        else { return true; }
    }

    //method to return the end of the month of a given date
    private static Date SetEndOfMonthDate(Date date1) {
        Integer totalDays = Date.daysInMonth(date1.year(), date1.month());
        Date lastDay = Date.newInstance(date1.year(), date1.month(), totalDays);
        return lastDay;
    }
}
```

2.TestVerifyDate.apxc

```
@isTest
public class TestVerifyDate
{
    static testMethod void testMethod1()
    {
        Date d = VerifyDate.CheckDates(System.today(),System.today()+1);
    }
}
```

```

        Date d1 = VerifyDate.CheckDates(System.today(),System.today()+60);
    }
}

```

TextApexTriggers

1.RestrictContactByName.apxt

```

trigger RestrictContactByName on Contact (before insert, before update) {

    //check contacts prior to insert or update for invalid data
    For (Contact c : Trigger.New) {
        if(c.LastName == 'INVALIDNAME') { //invalidname is invalid
            c.AddError('The Last Name "'+c.LastName+'" is not allowed for DML');
        }
    }

}

```

2.TestRestrictContactByName.apxc

```

@IsTest
public class TestRestrictContactByName {
    @IsTest static void createBadContact(){

        Contact c=new Contact(Firstname='John',LastName='INVALIDNAME');

        Test.startTest();
        Database.SaveResult result = Database.insert(c, false);
        Test.stopTest();

        System.assert(!result.isSuccess());
    }
}

```

Create Test Data For Apex Tests

1.RandomContactFactory.apxc

```

public class RandomContactFactory {
    public static List<Contact> generateRandomContacts(Integer num,String lastName){
        List<Contact> contactList=new List<Contact>();
        for(Integer i=1;i<=num;i++){

```

```

        Contact ct=new Contact(FirstName='Test'+i,LastName=lastName);
        contactList.add(ct);
    }
    return contactList;
}
}

```

ASYNCHRONOUS APEX

Use Future Methods

1.AccountProcessor.apxc

```

public class AccountProcessor {
    @future
    public static void countContacts(List<Id> accountIds){
        List<Account> accounts = [Select Id, Name from Account Where Id IN : accountIds];
        List<Account> updatedAccounts = new List<Account>();
        for(Account account : accounts){
            account.Number_of_Contacts__c = [Select count() from Contact Where AccountId =:
account.Id];
            System.debug('No Of Contacts = ' + account.Number_of_Contacts__c);
            updatedAccounts.add(account);
        }
        update updatedAccounts;
    }
}

```

2.AccountProcessorTest.apxc

```

@isTest
public class AccountProcessorTest {
    @isTest
    public static void testNoOfContacts(){
        Account a = new Account();
        a.Name = 'Test Account';
        Insert a;

        Contact c = new Contact();
        c.FirstName = 'Bob';
        c.LastName = 'Willie';
        c.AccountId = a.Id;

        Contact c2 = new Contact();
    }
}

```

```

        c2.FirstName = 'Tom';
        c2.LastName = 'Cruise';
        c2.AccountId = a.Id;

        List<Id> acctIds = new List<Id>();
        acctIds.add(a.Id);

        Test.startTest();
        AccountProcessor.countContacts(acctIds);
        Test.stopTest();
    }
}

```

Use Batch Apex

1.LeadProcessor.apxc

```

public class LeadProcessor implements Database.Batchable<sObject> {

    public Database.QueryLocator start(Database.BatchableContext bc) {
        // collect the batches of records or objects to be passed to execute
        return Database.getQueryLocator([Select LeadSource From Lead ]);
    }

    public void execute(Database.BatchableContext bc, List<Lead> leads){
        // process each batch of records
        for (Lead Lead : leads) {
            lead.LeadSource = 'Dreamforce';
        }
        update leads;
    }

    public void finish(Database.BatchableContext bc){
    }

}

```

2.LeadProcessorTest.apxc

@isTest

```

public class LeadProcessorTest {

    @testSetup
    static void setup() {
        List<Lead> leads = new List<Lead>();
    }
}

```

```

    for(Integer counter=0 ;counter <200;counter++){
        Lead lead = new Lead();
        lead.FirstName ='FirstName';
        lead.LastName ='LastName'+counter;
        lead.Company ='demo'+counter;
        leads.add(lead);
    }
    insert leads;
}

@isTest static void test() {
    Test.startTest();
    LeadProcessor leadProcessor = new LeadProcessor();
    Id batchId = Database.executeBatch(leadProcessor);
    Test.stopTest();
}

}

```

Control Processes with Queueable Apex

1.AddPrimaryContact.apxc

public class AddPrimaryContact implements Queueable

```

{
    private Contact c;
    private String state;
    public AddPrimaryContact(Contact c, String state)
    {
        this.c = c;
        this.state = state;
    }
    public void execute(QueueableContext context)
    {
        List<Account> ListAccount = [SELECT ID, Name ,(Select id,FirstName,LastName from
contacts ) FROM ACCOUNT WHERE BillingState = :state LIMIT 200];
        List<Contact> lstContact = new List<Contact>();
        for (Account acc:ListAccount)
        {
            Contact cont = c.clone(false,false,false,false);
            cont.AccountId = acc.id;
            lstContact.add( cont );
        }
    }
}

```

```

        if(lstContact.size() >0 )
        {
            insert lstContact;
        }

    }

}

```

2.AddPrimaryContactTest.apxc

```

@isTest
public class AddPrimaryContactTest
{
    @isTest static void TestList()
    {
        List<Account> Teste = new List <Account>();
        for(Integer i=0;i<50;i++)
        {
            Teste.add(new Account(BillingState = 'CA', name = 'Test'+i));
        }
        for(Integer j=0;j<50;j++)
        {
            Teste.add(new Account(BillingState = 'NY', name = 'Test'+j));
        }
        insert Teste;

        Contact co = new Contact();
        co.FirstName='demo';
        co.LastName ='demo';
        insert co;
        String state = 'CA';

        AddPrimaryContact apc = new AddPrimaryContact(co, state);
        Test.startTest();
        System.enqueueJob(apc);
        Test.stopTest();
    }
}

```

Schedule Jobs using the Apex scheduler

1.DailyLeadProcessor.apxc

```
public class DailyLeadProcessor implements Schedulable {
    Public void execute(SchedulableContext SC){
        List<Lead> LeadObj=[SELECT Id from Lead where LeadSource=null limit 200];
        for(Lead l:LeadObj){
            l.LeadSource='Dreamforce';
            update l;
        }
    }
}
```

2.DailyLeadProcessorTest.apxc

```
@isTest
private class DailyLeadProcessorTest {
    static testMethod void testDailyLeadProcessor() {
        String CRON_EXP = '0 0 1 * * ?';
        List<Lead> lList = new List<Lead>();
        for (Integer i = 0; i < 200; i++) {
            lList.add(new Lead(LastName='Dreamforce'+i, Company='Test1 Inc.',
Status='Open - Not Contacted'));
        }
        insert lList;

        Test.startTest();
        String jobId = System.schedule('DailyLeadProcessor', CRON_EXP, new
DailyLeadProcessor());
    }
}
```

Apex Integration Services

Apex REST Callouts

1.AnimalLocator.apxc

```
public class AnimalLocator{
    public static String getAnimalNameById(Integer x){
        Http http = new Http();
        HttpRequest req = new HttpRequest();
        req.setEndpoint('https://th-apex-http-callout.herokuapp.com/animals/' + x);
        req.setMethod('GET');
        Map<String, Object> animal= new Map<String, Object>();
        HttpResponse res = http.send(req);
        if (res.getStatusCode() == 200) {
```



```

        Map<String, Object> results = (Map<String,
Object>)JSON.deserializeUntyped(res.getBody());
        animal = (Map<String, Object>) results.get('animal');
    }
    return (String)animal.get('name');
}
}

```

2. AnimalLocatorTest.apxc

@isTest

```

private class AnimalLocatorTest{
    @isTest static void AnimalLocatorMock1() {
        Test.setMock(HttpCalloutMock.class, new AnimalLocatorMock());
        string result = AnimalLocator.getAnimalNameById(3);
        String expectedResult = 'chicken';
        System.assertEquals(result,expectedResult );
    }
}

```

3. AnimalLocatorMock.apxc

@isTest

```

global class AnimalLocatorMock implements HttpCalloutMock {
    // Implement this interface method
    global HTTPResponse respond(HTTPRequest request) {
        // Create a fake response
        HttpResponse response = new HttpResponse();
        response.setHeader('Content-Type', 'application/json');
        response.setBody('{"animals": ["majestic badger", "fluffy bunny", "scary bear", "chicken",
"mighty moose"]}');
        response.setStatusCode(200);
        return response;
    }
}

```

Apex SOAP Callouts

1. ParkLocator.apxc

```

public class ParkLocator {
    public static string[] country(string theCountry) {
        ParkService.ParksImplPort parkSvc = new ParkService.ParksImplPort(); // remove space
        return parkSvc.byCountry(theCountry);
    }
}

```

2.ParkLocatorTest.apxc

@isTest

```
private class ParkLocatorTest {
    @isTest static void testCallout() {
        Test.setMock(WebServiceMock.class, new ParkServiceMock ());
        String country = 'United States';
        List<String> result = ParkLocator.country(country);
        List<String> parks = new List<String>{'Yellowstone', 'Mackinac National Park', 'Yosemite'};
        System.assertEquals(parks, result);
    }
}
```

3.ParkServiceMock.apxc

@isTest

```
global class ParkServiceMock implements WebServiceMock {
    global void doInvoke(
        Object stub,
        Object request,
        Map<String, Object> response,
        String endpoint,
        String soapAction,
        String requestName,
        String responseNS,
        String responseName,
        String responseType) {
        // start - specify the response you want to send
        ParkService.byCountryResponse response_x = new ParkService.byCountryResponse();
        response_x.return_x = new List<String>{'Yellowstone', 'Mackinac National Park', 'Yosemite'};
        // end
        response.put('response_x', response_x);
    }
}
```

4.AsyncParkService.apxc

//Generated by wsdl2apex

```
public class AsyncParkService {
    public class byCountryResponseFuture extends System.WebServiceCalloutFuture {
        public String[] getValue() {
            ParkService.byCountryResponse response =
(ParkService.byCountryResponse)System.WebServiceCallout.endInvoke(this);
```

```

        return response.return_x;
    }
}

public class AsyncParksImplPort {
    public String endpoint_x = 'https://th-apex-soap-service.herokuapp.com/service/parks';
    public Map<String,String> inputHttpHeaders_x;
    public String clientCertName_x;
    public Integer timeout_x;
    private String[] ns_map_type_info = new String[]{'http://parks.services/', 'ParkService'};
    public AsyncParkService.byCountryResponseFuture beginByCountry(System.Continuation
continuation,String arg0) {
        ParkService.byCountry request_x = new ParkService.byCountry();
        request_x.arg0 = arg0;
        return (AsyncParkService.byCountryResponseFuture)
System.WebServiceCallout.beginInvoke(
            this,
            request_x,
            AsyncParkService.byCountryResponseFuture.class,
            continuation,
            new String[]{endpoint_x,
            ",
            'http://parks.services/',
            'byCountry',
            'http://parks.services/',
            'byCountryResponse',
            'ParkService.byCountryResponse'}
            );
        }
    }
}
}

```

Apex Web Services

1.AccountManager.apxc

```
@RestResource(urlMapping='/Accounts/*/contacts')
```

```
global class AccountManager {
```

```
    @HttpGet
```

```
    global static Account getAccount() {
```

```
        RestRequest req = RestContext.request;
```

```
        String accId = req.requestURI.substringBetween('Accounts/', '/contacts');
```

```
        Account acc = [SELECT Id, Name, (SELECT Id, Name FROM Contacts)
```

```
            FROM Account WHERE Id = :accId];
```

```

        return acc;
    }
}

```

2.AccountManagerTest.apxc

@isTest

```
private class AccountManagerTest {
```

```

    private static testMethod void getAccountTest1() {
        Id recordId = createTestRecord();
        // Set up a test request
        RestRequest request = new RestRequest();
        request.requestUri = 'https://na1.salesforce.com/services/apexrest/Accounts/'+ recordId
+ '/contacts';
        request.httpMethod = 'GET';
        RestContext.request = request;
        // Call the method to test
        Account thisAccount = AccountManager.getAccount();
        // Verify results
        System.assert(thisAccount != null);
        System.assertEquals('Test record', thisAccount.Name);
    }
}

```

```

// Helper method
static Id createTestRecord() {
    // Create test record
    Account TestAcc = new Account(
        Name='Test record');
    insert TestAcc;
    Contact TestCon= new Contact(
        LastName='Test',
        AccountId = TestAcc.id);
    return TestAcc.Id;
}
}

```

APEX SPECIALIST

Step2:Automate Record Creation

1.MaintainanceRequest.apxt

```
trigger MaintenanceRequest on Case (before update, after update) {
```

```

if(Trigger.isUpdate && Trigger.isAfter){

    MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);

}

}

2.MaintainanceRequestHelper.apxc
public with sharing class MaintenanceRequestHelper {
    public static void updateworkOrders(List<Case> updWorkOrders, Map<Id,Case>
nonUpdCaseMap) {
        Set<Id> validIds = new Set<Id>();

        For (Case c : updWorkOrders){
            if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
                if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
                    validIds.add(c.Id);
                }
            }
        }

        if (!validIds.isEmpty()){
            List<Case> newCases = new List<Case>();
            Map<Id,Case> closedCasesM = new Map<Id,Case>([SELECT Id, Vehicle__c,
Equipment__c, Equipment__r.Maintenance_Cycle__c,(SELECT Id,Equipment__c,Quantity__c
FROM Equipment_Maintenance_Items__r)
FROM Case WHERE Id IN :validIds]);
            Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
            AggregateResult[] results = [SELECT Maintenance_Request__c,
MIN(Equipment__r.Maintenance_Cycle__c)cycle FROM Equipment_Maintenance_Item__c
WHERE Maintenance_Request__c IN :ValidIds GROUP BY Maintenance_Request__c];

            for (AggregateResult ar : results){
                maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal) ar.get('cycle'));
            }
        }
    }
}

```

```

for(Case cc : closedCasesM.values()){
    Case nc = new Case (
        ParentId = cc.Id,
        Status = 'New',
        Subject = 'Routine Maintenance',
        Type = 'Routine Maintenance',
        Vehicle__c = cc.Vehicle__c,
        Equipment__c =cc.Equipment__c,
        Origin = 'Web',
        Date_Reported__c = Date.Today()

    );

    If (maintenanceCycles.containsKey(cc.Id)){
        nc.Date_Due__c = Date.today().addDays((Integer) maintenanceCycles.get(cc.Id));
    }

    newCases.add(nc);
}

insert newCases;

List<Equipment_Maintenance_Item__c> clonedWPs = new
List<Equipment_Maintenance_Item__c>();
for (Case nc : newCases){
    for (Equipment_Maintenance_Item__c wp :
closedCasesM.get(nc.ParentId).Equipment_Maintenance_Items__r){
        Equipment_Maintenance_Item__c wpClone = wp.clone();
        wpClone.Maintenance_Request__c = nc.Id;
        ClonedWPs.add(wpClone);

    }
}
insert ClonedWPs;
}
}
}

```

3.MaintainanceRequestHelperTest.apxc

```

public with sharing class MaintenanceRequestHelper {
    public static void updateworkOrders(List<Case> updWorkOrders, Map<Id,Case>

```

```

nonUpdCaseMap) {
    Set<Id> validIds = new Set<Id>();

    For (Case c : updWorkOrders){
        if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
            if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
                validIds.add(c.Id);
            }
        }
    }

    if (!validIds.isEmpty()){
        List<Case> newCases = new List<Case>();
        Map<Id,Case> closedCasesM = new Map<Id,Case>([SELECT Id, Vehicle__c,
Equipment__c, Equipment__r.Maintenance_Cycle__c,(SELECT Id,Equipment__c,Quantity__c
FROM Equipment_Maintenance_Items__r)
                                FROM Case WHERE Id IN :validIds]);
        Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
        AggregateResult[] results = [SELECT Maintenance_Request__c,
MIN(Equipment__r.Maintenance_Cycle__c)cycle FROM Equipment_Maintenance_Item__c
WHERE Maintenance_Request__c IN :ValidIds GROUP BY Maintenance_Request__c];

        for (AggregateResult ar : results){
            maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal) ar.get('cycle'));
        }

        for(Case cc : closedCasesM.values()){
            Case nc = new Case (
                ParentId = cc.Id,
                Status = 'New',
                Subject = 'Routine Maintenance',
                Type = 'Routine Maintenance',
                Vehicle__c = cc.Vehicle__c,
                Equipment__c =cc.Equipment__c,
                Origin = 'Web',
                Date_Reported__c = Date.Today()

            );

```

```

        If (maintenanceCycles.containsKey(cc.Id)){
            nc.Date_Due__c = Date.today().addDays((Integer) maintenanceCycles.get(cc.Id));
        }

        newCases.add(nc);
    }

    insert newCases;

    List<Equipment_Maintenance_Item__c> clonedWPs = new
    List<Equipment_Maintenance_Item__c>();
    for (Case nc : newCases){
        for (Equipment_Maintenance_Item__c wp :
        closedCasesM.get(nc.ParentId).Equipment_Maintenance_Items__r){
            Equipment_Maintenance_Item__c wpClone = wp.clone();
            wpClone.Maintenance_Request__c = nc.Id;
            ClonedWPs.add(wpClone);

        }
    }
    insert ClonedWPs;
}
}
}
}

```

Step 3 :Synchronize Salesforce Data With an External Organisation

1.WarehouseCalloutService.apxc

public with sharing class WarehouseCalloutService{

private static final String WAREHOUSE_URL = 'https://th-superbadge-
apex.herokuapp.com/equipment';

//@future(callout=true)
public static void runWarehouseEquipmentSync(){

Http http = new Http();
HttpRequest request = new HttpRequest();

request.setEndpoint(WAREHOUSE_URL);
request.setMethod('GET');


```

HttpResponse response = http.send(request);

List<Product2> warehouseEq = new List<Product2>();

if (response.getStatusCode() == 200){
    List<Object> jsonResponse =
(List<Object>)JSON.deserializeUntyped(response.getBody());
    System.debug(response.getBody());

    for (Object eq : jsonResponse){
        Map<String,Object> mapJson = (Map<String,Object>)eq;
        Product2 myEq = new Product2();
        myEq.Replacement_Part__c = (Boolean) mapJson.get('replacement');
        myEq.Name = (String) mapJson.get('name');
        myEq.Maintenance_Cycle__c = (Integer) mapJson.get('maintenanceperiod');
        myEq.Lifespan_Months__c = (Integer) mapJson.get('lifespan');
        myEq.Cost__c = (Decimal) mapJson.get('lifespan');
        myEq.Warehouse_SKU__c = (String) mapJson.get('sku');
        myEq.Current_Inventory__c = (Double) mapJson.get('quantity');
        warehouseEq.add(myEq);
    }

    if (warehouseEq.size() > 0){
        upsert warehouseEq;
        System.debug('Your equipment was synced with the warehouse one');
        System.debug(warehouseEq);
    }

}
}
}

```

Step 4 :Schedule Synchronization

1.WarehouseSyncSchedule.apxc

```

global class WarehouseSyncSchedule implements Schedulable {
    global void execute(SchedulableContext ctx) {

        WarehouseCalloutService.runWarehouseEquipmentSync();
    }
}

```

```
}
```

2.MaintainanceRequestHelper.apxc

```
public with sharing class MaintenanceRequestHelper {  
    public static void updateWorkOrders(List<Case> updWorkOrders, Map<Id,Case>  
nonUpdCaseMap) {  
        Set<Id> validIds = new Set<Id>();  
  
        For (Case c : updWorkOrders){  
            if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){  
                if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){  
                    validIds.add(c.Id);  
  
                }  
            }  
        }  
  
        if (!validIds.isEmpty()){  
            List<Case> newCases = new List<Case>();  
            Map<Id,Case> closedCasesM = new Map<Id,Case>([SELECT Id, Vehicle__c,  
Equipment__c, Equipment__r.Maintenance_Cycle__c,(SELECT Id,Equipment__c,Quantity__c  
FROM Equipment_Maintenance_Items__r)  
FROM Case WHERE Id IN :validIds]);  
            Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();  
            AggregateResult[] results = [SELECT Maintenance_Request__c,  
MIN(Equipment__r.Maintenance_Cycle__c)cycle FROM Equipment_Maintenance_Item__c  
WHERE Maintenance_Request__c IN :ValidIds GROUP BY Maintenance_Request__c];  
  
            for (AggregateResult ar : results){  
                maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal) ar.get('cycle'));  
            }  
  
            for(Case cc : closedCasesM.values()){  
                Case nc = new Case (  
                    ParentId = cc.Id,  
                    Status = 'New',  
                    Subject = 'Routine Maintenance',  
                    Type = 'Routine Maintenance',  
                    Vehicle__c = cc.Vehicle__c,
```

```

        Equipment__c =cc.Equipment__c,
        Origin = 'Web',
        Date_Reported__c = Date.Today()

    );

    If (maintenanceCycles.containsKey(cc.Id)){
        nc.Date_Due__c = Date.today().addDays((Integer) maintenanceCycles.get(cc.Id));
    }

    newCases.add(nc);
}

insert newCases;

List<Equipment_Maintenance_Item__c> clonedWPs = new
List<Equipment_Maintenance_Item__c>();
for (Case nc : newCases){
    for (Equipment_Maintenance_Item__c wp :
closedCasesM.get(nc.ParentId).Equipment_Maintenance_Items__r){
        Equipment_Maintenance_Item__c wpClone = wp.clone();
        wpClone.Maintenance_Request__c = nc.Id;
        ClonedWPs.add(wpClone);
    }
}
insert ClonedWPs;
}
}
}
}

```

3.MaintainanceRequestHelperTest.apxc

@istest

public with sharing class MaintenanceRequestHelperTest {

```

    private static final string STATUS_NEW = 'New';
    private static final string WORKING = 'Working';
    private static final string CLOSED = 'Closed';
    private static final string REPAIR = 'Repair';
    private static final string REQUEST_ORIGIN = 'Web';
    private static final string REQUEST_TYPE = 'Routine Maintenance';

```

```

private static final string REQUEST_SUBJECT = 'Testing subject';

PRIVATE STATIC Vehicle__c createVehicle(){
    Vehicle__c Vehicle = new Vehicle__C(name = 'SuperTruck');
    return Vehicle;
}

PRIVATE STATIC Product2 createEq(){
    product2 equipment = new product2(name = 'SuperEquipment',
        lifespan_months__C = 10,
        maintenance_cycle__C = 10,
        replacement_part__c = true);
    return equipment;
}

PRIVATE STATIC Case createMaintenanceRequest(id vehicleId, id equipmentId){
    case cs = new case(Type=REPAIR,
        Status=STATUS_NEW,
        Origin=REQUEST_ORIGIN,
        Subject=REQUEST_SUBJECT,
        Equipment__c=equipmentId,
        Vehicle__c=vehicleId);
    return cs;
}

PRIVATE STATIC Equipment_Maintenance_Item__c createWorkPart(id equipmentId,id
requestId){
    Equipment_Maintenance_Item__c wp = new
Equipment_Maintenance_Item__c(Equipment__c = equipmentId,
        Maintenance_Request__c = requestId);
    return wp;
}

@istest
private static void testMaintenanceRequestPositive(){
    Vehicle__c vehicle = createVehicle();
    insert vehicle;
    id vehicleId = vehicle.Id;

    Product2 equipment = createEq();

```

```
insert equipment;  
id equipmentId = equipment.Id;
```

```
case somethingToUpdate = createMaintenanceRequest(vehicleId,equipmentId);  
insert somethingToUpdate;
```

```
Equipment_Maintenance_Item__c workP =  
createWorkPart(equipmentId,somethingToUpdate.id);  
insert workP;
```

```
test.startTest();  
somethingToUpdate.status = CLOSED;  
update somethingToUpdate;  
test.stopTest();
```

```
Case newReq = [Select id, subject, type, Equipment__c, Date_Reported__c, Vehicle__c,  
Date_Due__c  
from case  
where status =:STATUS_NEW];
```

```
Equipment_Maintenance_Item__c workPart = [select id  
from Equipment_Maintenance_Item__c  
where Maintenance_Request__c =:newReq.Id];
```

```
system.assert(workPart != null);  
system.assert(newReq.Subject != null);  
system.assertEquals(newReq.Type, REQUEST_TYPE);  
SYSTEM.assertEquals(newReq.Equipment__c, equipmentId);  
SYSTEM.assertEquals(newReq.Vehicle__c, vehicleId);  
SYSTEM.assertEquals(newReq.Date_Reported__c, system.today());  
}
```

```
@istest  
private static void testMaintenanceRequestNegative(){  
    Vehicle__C vehicle = createVehicle();  
    insert vehicle;  
    id vehicleId = vehicle.Id;  
  
    product2 equipment = createEq();  
    insert equipment;  
    id equipmentId = equipment.Id;
```

```
case emptyReq = createMaintenanceRequest(vehicleId,equipmentId);
insert emptyReq;
```

```
Equipment_Maintenance_Item__c workP = createWorkPart(equipmentId, emptyReq.Id);
insert workP;
```

```
test.startTest();
emptyReq.Status = WORKING;
update emptyReq;
test.stopTest();
```

```
list<case> allRequest = [select id
                        from case];
```

```
Equipment_Maintenance_Item__c workPart = [select id
                                           from Equipment_Maintenance_Item__c
                                           where Maintenance_Request__c = :emptyReq.Id];
```

```
system.assert(workPart != null);
system.assert(allRequest.size() == 1);
}
```

```
@istest
private static void testMaintenanceRequestBulk(){
    list<Vehicle__C> vehicleList = new list<Vehicle__C>();
    list<Product2> equipmentList = new list<Product2>();
    list<Equipment_Maintenance_Item__c> workPartList = new
list<Equipment_Maintenance_Item__c>();
    list<case> requestList = new list<case>();
    list<id> oldRequestIds = new list<id>();

    for(integer i = 0; i < 300; i++){
        vehicleList.add(createVehicle());
        equipmentList.add(createEq());
    }
    insert vehicleList;
    insert equipmentList;

    for(integer i = 0; i < 300; i++){
        requestList.add(createMaintenanceRequest(vehicleList.get(i).id, equipmentList.get(i).id));
```

```

    }
    insert requestList;

    for(integer i = 0; i < 300; i++){
        workPartList.add(createWorkPart(equipmentList.get(i).id, requestList.get(i).id));
    }
    insert workPartList;

    test.startTest();
    for(case req : requestList){
        req.Status = CLOSED;
        oldRequestIds.add(req.Id);
    }
    update requestList;
    test.stopTest();

    list<case> allRequests = [select id
                            from case
                            where status =: STATUS_NEW];

    list<Equipment_Maintenance_Item__c> workParts = [select id
                                                    from Equipment_Maintenance_Item__c
                                                    where Maintenance_Request__c in: oldRequestIds];

    system.assert(allRequests.size() == 300);
}
}

```

Step 6 :Test Callout Logic

1.WarehouseCalloutServiceMock.apxc

@isTest

global class WarehouseCalloutServiceMock implements HttpCalloutMock {

// implement http mock callout

global static HttpResponse respond(HttpRequest request){

System.assertEquals('https://th-superbadge-apex.herokuapp.com/equipment',
request.getEndpoint());

System.assertEquals('GET', request.getMethod());

// Create a fake response

```

        HttpResponse response = new HttpResponse();
        response.setHeader('Content-Type', 'application/json');

        response.setBody('{"_id":"55d66226726b611100aaf741","replacement":false,"quantity":5,"name":
        "Generator 1000 kW","maintenanceperiod":365,"lifespan":120,"cost":5000,"sku":"100003"}');
        response.setStatusCode(200);
        return response;
    }
}

```

2. WarehouseCalloutServiceTest.apxc

@isTest

```

private class WarehouseCalloutServiceTest {
    @isTest
    static void testWareHouseCallout(){
        Test.startTest();
        // implement mock callout test here
        Test.setMock(HTTPCalloutMock.class, new WarehouseCalloutServiceMock());
        WarehouseCalloutService.runWarehouseEquipmentSync();
        Test.stopTest();
        System.assertEquals(1, [SELECT count() FROM Product2]);
    }
}

```

Step 7 :Test Scheduling Logic

1. WarehouseSyncScheduleTest.apxc

@isTest

public class WarehouseSyncScheduleTest {

```

    @isTest static void WarehousescheduleTest(){
        String scheduleTime = '00 00 01 * * ?';
        Test.startTest();
        Test.setMock(HttpCalloutMock.class, new WarehouseCalloutServiceMock());
        String jobId=System.schedule('Warehouse Time To Schedule to Test', scheduleTime, new
        WarehouseSyncSchedule());
        Test.stopTest();
        //Contains schedule information for a scheduled job. CronTrigger is similar to a cron job on
        UNIX systems.
        // This object is available in API version 17.0 and later.
    }
}

```



```
CronTrigger a=[SELECT Id FROM CronTrigger where NextFireTime > today];  
System.assertEquals(jobID, a.Id,'Schedule ');
```

```
}  
}
```