

Apex Specialist Superbadge :

APEX SPECIALIST :

Challenge 2 : Automate record creation

Maintenance Request.cls

```
trigger MaintenanceRequest on Case (before update, after update) {
    if(Trigger.isUpdate && Trigger.isAfter){
        MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);
    }
}
```

MaintenanceRequestHelper.cls

```
public with sharing class MaintenanceRequestHelper {
    public static void updateWorkOrders(List<Case> updWorkOrders, Map<Id,Case>
nonUpdCaseMap) {
        Set<Id> validIds = new Set<Id>();
        For (Case c : updWorkOrders){
            if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
                if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
                    validIds.add(c.Id);
                }
            }
        }
    }
}
```

```
        //When an existing maintenance request of type Repair or Routine Maintenance is closed,
        //create a new maintenance request for a future routine checkup.
        if (!validIds.isEmpty()){
            Map<Id,Case> closedCases = new Map<Id,Case>([SELECT Id, Vehicle__c,
Equipment__c, Equipment__r.Maintenance_Cycle__c,
                (SELECT Id,Equipment__c,Quantity__c FROM
Equipment_Maintenance_Items__r)
                FROM Case WHERE Id IN :validIds]);
            Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
```

```
        //calculate the maintenance request due dates by using the maintenance cycle defined on
        the related equipment records.
        AggregateResult[] results = [SELECT Maintenance_Request__c,
                MIN(Equipment__r.Maintenance_Cycle__c)cycle
                FROM Equipment_Maintenance_Item__c
```

```
WHERE Maintenance_Request__c IN :ValidIds GROUP BY  
Maintenance_Request__c];
```

```
for (AggregateResult ar : results){  
    maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal)  
ar.get('cycle'));  
}
```

```
List<Case> newCases = new List<Case>();  
for(Case cc : closedCases.values()){  
    Case nc = new Case (  
        ParentId = cc.Id,  
        Status = 'New',  
        Subject = 'Routine Maintenance',  
        Type = 'Routine Maintenance',  
        Vehicle__c = cc.Vehicle__c,  
        Equipment__c =cc.Equipment__c,  
        Origin = 'Web',  
        Date_Reported__c = Date.Today()  
    );
```

```
    //If multiple pieces of equipment are used in the maintenance request,  
    //define the due date by applying the shortest maintenance cycle to today's date.  
    If (maintenanceCycles.containsKey(cc.Id)){  
        nc.Date_Due__c = Date.today().addDays((Integer) maintenanceCycles.get(cc.Id));  
    } else {  
        nc.Date_Due__c = Date.today().addDays((Integer)  
cc.Equipment__r.maintenance_Cycle__c);  
    }
```

```
        newCases.add(nc);  
    }
```

```
insert newCases;
```

```
List<Equipment_Maintenance_Item__c> clonedList = new  
List<Equipment_Maintenance_Item__c>();  
for (Case nc : newCases){  
    for (Equipment_Maintenance_Item__c clonedListItem :  
closedCases.get(nc.ParentId).Equipment_Maintenance_Items__r){  
        Equipment_Maintenance_Item__c item = clonedListItem.clone();  
        item.Maintenance_Request__c = nc.Id;  
        clonedList.add(item);  
    }  
}  
insert clonedList;
```

```

    }
}
}public with sharing class MaintenanceRequestHelper {
    public static void updateWorkOrders(List<Case> updWorkOrders, Map<Id,Case>
nonUpdCaseMap) {
    Set<Id> validIds = new Set<Id>();
    For (Case c : updWorkOrders){
        if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
            if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
                validIds.add(c.Id);
            }
        }
    }
}
}
}

```

```

//When an existing maintenance request of type Repair or Routine Maintenance is closed,
//create a new maintenance request for a future routine checkup.

```

```

if (!validIds.isEmpty()){
    Map<Id,Case> closedCases = new Map<Id,Case>([SELECT Id, Vehicle__c,
Equipment__c, Equipment__r.Maintenance_Cycle__c,
(SELECT Id,Equipment__c,Quantity__c FROM
Equipment_Maintenance_Items__r)
FROM Case WHERE Id IN :validIds]);
    Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
}

```

```

//calculate the maintenance request due dates by using the maintenance cycle defined on
the related equipment records.

```

```

AggregateResult[] results = [SELECT Maintenance_Request__c,
MIN(Equipment__r.Maintenance_Cycle__c)cycle
FROM Equipment_Maintenance_Item__c
WHERE Maintenance_Request__c IN :ValidIds GROUP BY
Maintenance_Request__c];

```

```

for (AggregateResult ar : results){
    maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal)
ar.get('cycle'));
}

```

```

List<Case> newCases = new List<Case>();
for(Case cc : closedCases.values()){
    Case nc = new Case (
        ParentId = cc.Id,
        Status = 'New',
        Subject = 'Routine Maintenance',
        Type = 'Routine Maintenance',
        Vehicle__c = cc.Vehicle__c,
        Equipment__c = cc.Equipment__c,

```

```

        Origin = 'Web',
        Date_Reported__c = Date.Today()
    );

    //If multiple pieces of equipment are used in the maintenance request,
    //define the due date by applying the shortest maintenance cycle to today's date.
    If (maintenanceCycles.containsKey(cc.Id)){
        nc.Date_Due__c = Date.today().addDays((Integer) maintenanceCycles.get(cc.Id));
    } else {
        nc.Date_Due__c = Date.today().addDays((Integer)
cc.Equipment__r.maintenance_Cycle__c);
    }

    newCases.add(nc);
}

insert newCases;

List<Equipment_Maintenance_Item__c> clonedList = new
List<Equipment_Maintenance_Item__c>();
for (Case nc : newCases){
    for (Equipment_Maintenance_Item__c clonedListItem :
closedCases.get(nc.ParentId).Equipment_Maintenance_Items__r){
        Equipment_Maintenance_Item__c item = clonedListItem.clone();
        item.Maintenance_Request__c = nc.Id;
        clonedList.add(item);
    }
}
insert clonedList;
}
}
}
}

```

Challenge-3 : Synchronize Salesforce data with an external system

WarehouseCalloutService.cls

```

public with sharing class WarehouseCalloutService implements Queueable {
    private static final String WAREHOUSE_URL = 'https://th-superbadge-
apex.herokuapp.com/equipment';

```

```

    //Write a class that makes a REST callout to an external warehouse system to get a list of
    equipment that needs to be updated.

```

//The callout's JSON response returns the equipment records that you upsert in Salesforce.

```
@future(callout=true)
public static void runWarehouseEquipmentSync(){
    System.debug('go into runWarehouseEquipmentSync');
    Http http = new Http();
    HttpRequest request = new HttpRequest();

    request.setEndpoint(WAREHOUSE_URL);
    request.setMethod('GET');
    HttpResponse response = http.send(request);

    List<Product2> product2List = new List<Product2>();
    System.debug(response.getStatusCode());
    if (response.getStatusCode() == 200){
        List<Object> jsonResponse =
(List<Object>)JSON.deserializeUntyped(response.getBody());
        System.debug(response.getBody());

        //class maps the following fields:
        //warehouse SKU will be external ID for identifying which equipment records to update
        within Salesforce
        for (Object jR : jsonResponse){
            Map<String,Object> mapJson = (Map<String,Object>)jR;
            Product2 product2 = new Product2();
            //replacement part (always true),
            product2.Replacement_Part__c = (Boolean) mapJson.get('replacement');
            //cost
            product2.Cost__c = (Integer) mapJson.get('cost');
            //current inventory
            product2.Current_Inventory__c = (Double) mapJson.get('quantity');
            //lifespan
            product2.Lifespan_Months__c = (Integer) mapJson.get('lifespan');
            //maintenance cycle
            product2.Maintenance_Cycle__c = (Integer) mapJson.get('maintenanceperiod');
            //warehouse SKU
            product2.Warehouse_SKU__c = (String) mapJson.get('sku');

            product2.Name = (String) mapJson.get('name');
            product2.ProductCode = (String) mapJson.get('_id');
            product2List.add(product2);
        }

        if (product2List.size() > 0){
            upsert product2List;
            System.debug('Your equipment was synced with the warehouse one');
```

```

    }
  }
}

public static void execute (QueueableContext context){
    System.debug('start runWarehouseEquipmentSync');
    runWarehouseEquipmentSync();
    System.debug('end runWarehouseEquipmentSync');
}
}

```

Challenge 4 : Schedule synchronization

WarehouseSyncShedule.cls

```

global with sharing class WarehouseSyncSchedule implements Schedulable{
    global void execute(SchedulableContext ctx){
        System.enqueueJob(new WarehouseCalloutService());
    }
}

```

Challenge 5 : Test automation logic

MaintenanceRequest.cls

```

trigger MaintenanceRequest on Case (before update, after update) {
    if(Trigger.isUpdate && Trigger.isAfter){
        MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);
    }
}

```

MaintenanceRequestHelper.cls

```

public with sharing class MaintenanceRequestHelper {
    public static void updateworkOrders(List<Case> updWorkOrders, Map<Id,Case>
nonUpdCaseMap) {
        Set<Id> validIds = new Set<Id>();
        For (Case c : updWorkOrders){
            if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
                if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
                    validIds.add(c.Id);
                }
            }
        }
    }
}

```

```

    }
}

//When an existing maintenance request of type Repair or Routine Maintenance is closed,
//create a new maintenance request for a future routine checkup.
if (!validIds.isEmpty()){
    Map<Id,Case> closedCases = new Map<Id,Case>([SELECT Id, Vehicle__c,
Equipment__c, Equipment__r.Maintenance_Cycle__c,
                                (SELECT Id,Equipment__c,Quantity__c FROM
Equipment_Maintenance_Items__r)
                                FROM Case WHERE Id IN :validIds]);
    Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();

    //calculate the maintenance request due dates by using the maintenance cycle defined on
the related equipment records.
    AggregateResult[] results = [SELECT Maintenance_Request__c,
                                MIN(Equipment__r.Maintenance_Cycle__c)cycle
                                FROM Equipment_Maintenance_Item__c
                                WHERE Maintenance_Request__c IN :ValidIds GROUP BY
Maintenance_Request__c];

    for (AggregateResult ar : results){
        maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal)
ar.get('cycle'));
    }

    List<Case> newCases = new List<Case>();
    for(Case cc : closedCases.values()){
        Case nc = new Case (
            ParentId = cc.Id,
            Status = 'New',
            Subject = 'Routine Maintenance',
            Type = 'Routine Maintenance',
            Vehicle__c = cc.Vehicle__c,
            Equipment__c =cc.Equipment__c,
            Origin = 'Web',
            Date_Reported__c = Date.Today()
        );

        //If multiple pieces of equipment are used in the maintenance request,
        //define the due date by applying the shortest maintenance cycle to today's date.
        //If (maintenanceCycles.containsKey(cc.Id)){
            nc.Date_Due__c = Date.today().addDays((Integer) maintenanceCycles.get(cc.Id));
        //} else {
            // nc.Date_Due__c = Date.today().addDays((Integer)
cc.Equipment__r.maintenance_Cycle__c);

```

```

        //}

        newCases.add(nc);
    }

    insert newCases;

    List<Equipment_Maintenance_Item__c> clonedList = new
List<Equipment_Maintenance_Item__c>();
    for (Case nc : newCases){
        for (Equipment_Maintenance_Item__c clonedListItem :
closedCases.get(nc.ParentId).Equipment_Maintenance_Items__r){
            Equipment_Maintenance_Item__c item = clonedListItem.clone();
            item.Maintenance_Request__c = nc.Id;
            clonedList.add(item);
        }
    }
    insert clonedList;
}
}
}
}

```

MaintenanceRequestHelperTest.cls

```

@isTest
public with sharing class MaintenanceRequestHelperTest {

    // createVehicle
    private static Vehicle__c createVehicle(){
        Vehicle__c vehicle = new Vehicle__C(name = 'Testing Vehicle');
        return vehicle;
    }

    // createEquipment
    private static Product2 createEquipment(){
        product2 equipment = new product2(name = 'Testing equipment',
            lifespan_months__c = 10,
            maintenance_cycle__c = 10,
            replacement_part__c = true);

        return equipment;
    }

    // createMaintenanceRequest
    private static Case createMaintenanceRequest(id vehicleId, id equipmentId){

```



```

        case cse = new case(Type='Repair',
                            Status='New',
                            Origin='Web',
                            Subject='Testing subject',
                            Equipment__c=equipmentId,
                            Vehicle__c=vehicleId);
    return cse;
}

```

```

// createEquipmentMaintenanceItem
private static Equipment_Maintenance_Item__c createEquipmentMaintenanceItem(id
equipmentId,id requestId){
    Equipment_Maintenance_Item__c equipmentMaintenanceItem = new
Equipment_Maintenance_Item__c(
    Equipment__c = equipmentId,
    Maintenance_Request__c = requestId);
    return equipmentMaintenanceItem;
}

```

```

@isTest
private static void testPositive(){
    Vehicle__c vehicle = createVehicle();
    insert vehicle;
    id vehicleId = vehicle.Id;

```

```

    Product2 equipment = createEquipment();
    insert equipment;
    id equipmentId = equipment.Id;

```

```

    case createdCase = createMaintenanceRequest(vehicleId,equipmentId);
    insert createdCase;

```

```

    Equipment_Maintenance_Item__c equipmentMaintenanceItem =
createEquipmentMaintenanceItem(equipmentId,createdCase.id);
    insert equipmentMaintenanceItem;

```

```

    test.startTest();
    createdCase.status = 'Closed';
    update createdCase;
    test.stopTest();

```

```

    Case newCase = [Select id,
                      subject,
                      type,
                      Equipment__c,
                      Date_Reported__c,

```

```
Vehicle__c,  
Date_Due__c  
from case  
where status ='New'];
```

```
Equipment_Maintenance_Item__c workPart = [select id  
                                             from Equipment_Maintenance_Item__c  
                                             where Maintenance_Request__c =:newCase.Id];  
list<case> allCase = [select id from case];  
system.assert(allCase.size() == 2);
```

```
system.assert(newCase != null);  
system.assert(newCase.Subject != null);  
system.assertEquals(newCase.Type, 'Routine Maintenance');  
SYSTEM.assertEquals(newCase.Equipment__c, equipmentId);  
SYSTEM.assertEquals(newCase.Vehicle__c, vehicleId);  
SYSTEM.assertEquals(newCase.Date_Reported__c, system.today());  
}
```

```
@isTest  
private static void testNegative(){  
    Vehicle__C vehicle = createVehicle();  
    insert vehicle;  
    id vehicleId = vehicle.Id;
```

```
product2 equipment = createEquipment();  
insert equipment;  
id equipmentId = equipment.Id;
```

```
case createdCase = createMaintenanceRequest(vehicleId,equipmentId);  
insert createdCase;
```

```
Equipment_Maintenance_Item__c workP =  
createEquipmentMaintenanceItem(equipmentId, createdCase.Id);  
insert workP;
```

```
test.startTest();  
createdCase.Status = 'Working';  
update createdCase;  
test.stopTest();
```

```
list<case> allCase = [select id from case];
```

```
Equipment_Maintenance_Item__c equipmentMaintenanceItem = [select id  
                                                             from Equipment_Maintenance_Item__c  
                                                             where Maintenance_Request__c = :createdCase.Id];
```

```

    system.assert(equipmentMaintenanceItem != null);
    system.assert(allCase.size() == 1);
}

```

```
@isTest
```

```

private static void testBulk(){
    list<Vehicle__C> vehicleList = new list<Vehicle__C>();
    list<Product2> equipmentList = new list<Product2>();
    list<Equipment_Maintenance_Item__c> equipmentMaintenanceItemList = new
list<Equipment_Maintenance_Item__c>();
    list<case> caseList = new list<case>();
    list<id> oldCaseIds = new list<id>();

    for(integer i = 0; i < 300; i++){
        vehicleList.add(createVehicle());
        equipmentList.add(createEquipment());
    }
    insert vehicleList;
    insert equipmentList;

    for(integer i = 0; i < 300; i++){
        caseList.add(createMaintenanceRequest(vehicleList.get(i).id, equipmentList.get(i).id));
    }
    insert caseList;

    for(integer i = 0; i < 300; i++){
        equipmentMaintenanceItemList.add(createEquipmentMaintenanceItem(equipmentList.get(i).id, caseList.get(i).id));
    }
    insert equipmentMaintenanceItemList;

    test.startTest();
    for(case cs : caseList){
        cs.Status = 'Closed';
        oldCaseIds.add(cs.Id);
    }
    update caseList;
    test.stopTest();

    list<case> newCase = [select id
                        from case
                        where status = 'New'];
}

```

```

list<Equipment_Maintenance_Item__c> workParts = [select id
                                                    from Equipment_Maintenance_Item__c
                                                    where Maintenance_Request__c in: oldCaseIds];

system.assert(newCase.size() == 300);

list<case> allCase = [select id from case];
system.assert(allCase.size() == 600);
}
}

```

Challenge-6 : Test callout logic

WarehouseCalloutService.cls

```

public with sharing class WarehouseCalloutService implements Queueable {
    private static final String WAREHOUSE_URL = 'https://th-superbadge-
apex.herokuapp.com/equipment';

```

//Write a class that makes a REST callout to an external warehouse system to get a list of equipment that needs to be updated.

//The callout's JSON response returns the equipment records that you upsert in Salesforce.

```

    @future(callout=true)
    public static void runWarehouseEquipmentSync(){
        System.debug('go into runWarehouseEquipmentSync');
        Http http = new Http();
        HttpRequest request = new HttpRequest();

        request.setEndpoint(WAREHOUSE_URL);
        request.setMethod('GET');
        HttpResponse response = http.send(request);

        List<Product2> product2List = new List<Product2>();
        System.debug(response.getStatusCode());
        if (response.getStatusCode() == 200){
            List<Object> jsonResponse =
(List<Object>)JSON.deserializeUntyped(response.getBody());
            System.debug(response.getBody());

            //class maps the following fields:
            //warehouse SKU will be external ID for identifying which equipment records to update
            within Salesforce
            for (Object jR : jsonResponse){
                Map<String,Object> mapJson = (Map<String,Object>)jR;
                Product2 product2 = new Product2();

```

```

        //replacement part (always true),
        product2.Replacement_Part__c = (Boolean) mapJson.get('replacement');
        //cost
        product2.Cost__c = (Integer) mapJson.get('cost');
        //current inventory
        product2.Current_Inventory__c = (Double) mapJson.get('quantity');
        //lifespan
        product2.Lifespan_Months__c = (Integer) mapJson.get('lifespan');
        //maintenance cycle
        product2.Maintenance_Cycle__c = (Integer) mapJson.get('maintenanceperiod');
        //warehouse SKU
        product2.Warehouse_SKU__c = (String) mapJson.get('sku');

        product2.Name = (String) mapJson.get('name');
        product2.ProductCode = (String) mapJson.get('_id');
        product2List.add(product2);
    }

    if (product2List.size() > 0){
        upsert product2List;
        System.debug('Your equipment was synced with the warehouse one');
    }
}

public static void execute (QueueableContext context){
    System.debug('start runWarehouseEquipmentSync');
    runWarehouseEquipmentSync();
    System.debug('end runWarehouseEquipmentSync');
}
}

```

WarehouseCalloutServiceMock.cls

```

@isTest
global class WarehouseCalloutServiceMock implements HttpCalloutMock {
    // implement http mock callout
    global static HttpResponse respond(HttpRequest request) {

        HttpResponse response = new HttpResponse();
        response.setHeader('Content-Type', 'application/json');
        response.setBody('[{"_id":"55d66226726b611100aaf741","replacement":false,"quantity":5,
"name":"Generator 1000
kW","maintenanceperiod":365,"lifespan":120,"cost":5000,"sku":"100003"},{"_id":"55d6622672
6b611100aaf742","replacement":true,"quantity":183,"name":"Cooling

```

```

Fan","maintenanceperiod":0,"lifespan":0,"cost":300,"sku":"100004"},{"_id":"55d66226726b611
100aaf743","replacement":true,"quantity":143,"name":"Fuse
20A","maintenanceperiod":0,"lifespan":0,"cost":22,"sku":"100005"}]]);
    response.setStatusCode(200);

    return response;
}
}

```

WarehouseCalloutServiceTest.cls

```

@IsTest
private class WarehouseCalloutServiceTest {
    // implement your mock callout test here
    @isTest
    static void testWarehouseCallout() {
        test.startTest();
        test.setMock(HttpCalloutMock.class, new WarehouseCalloutServiceMock());
        WarehouseCalloutService.execute(null);
        test.stopTest();

        List<Product2> product2List = new List<Product2>();
        product2List = [SELECT ProductCode FROM Product2];

        System.assertEquals(3, product2List.size());
        System.assertEquals('55d66226726b611100aaf741', product2List.get(0).ProductCode);
        System.assertEquals('55d66226726b611100aaf742', product2List.get(1).ProductCode);
        System.assertEquals('55d66226726b611100aaf743', product2List.get(2).ProductCode);
    }
}

```

Challenge 7 : Test scheduling logic

WarehouseCalloutServiceMock.cls

```

@isTest
global class WarehouseCalloutServiceMock implements HttpCalloutMock {
    // implement http mock callout
    global static HttpResponse respond(HttpRequest request) {

        HttpResponse response = new HttpResponse();
        response.setHeader('Content-Type', 'application/json');
        response.setBody(['{"_id":"55d66226726b611100aaf741","replacement":false,"quantity":5,
"name":"Generator 1000
kW","maintenanceperiod":365,"lifespan":120,"cost":5000,"sku":"100003"},{"_id":"55d6622672

```

```

6b611100aaf742","replacement":true,"quantity":183,"name":"Cooling
Fan","maintenanceperiod":0,"lifespan":0,"cost":300,"sku":"100004"},{"_id":"55d66226726b611
100aaf743","replacement":true,"quantity":143,"name":"Fuse
20A","maintenanceperiod":0,"lifespan":0,"cost":22,"sku":"100005"}]]);
    response.setStatusCode(200);

    return response;
}
}

```

WarehouseSyncShedule.cls

```

global with sharing class WarehouseSyncSchedule implements Schedulable {
    // implement scheduled code here
    global void execute (SchedulableContext ctx){
        System.enqueueJob(new WarehouseCalloutService());
    }
}

```

WarehouseSyncSheduleTest.cls

```

@isTest
public with sharing class WarehouseSyncScheduleTest {
    // implement scheduled code here
    //
    @isTest static void test() {
        String scheduleTime = '00 00 00 * * ? *';
        Test.startTest();
        Test.setMock(HttpCalloutMock.class, new WarehouseCalloutServiceMock());
        String jobId = System.schedule('Warehouse Time to Schedule to test', scheduleTime, new
WarehouseSyncSchedule());
        CronTrigger c = [SELECT State FROM CronTrigger WHERE Id =: jobId];
        System.assertEquals('WAITING', String.valueOf(c.State), 'JobId does not match');

        Test.stopTest();
    }
}

```

Apex Testing

Challenge : Get Started with Apex Unit Tests

VerifyDate.cls

```
public class VerifyDate {

    //method to handle potential checks against two dates
    public static Date CheckDates(Date date1, Date date2) {
        //if date2 is within the next 30 days of date1, use date2. Otherwise use the end of
the month
        if(DateWithin30Days(date1,date2)) {
            return date2;
        } else {
            return SetEndOfMonthDate(date1);
        }
    }

    //method to check if date2 is within the next 30 days of date1
    @TestVisible private static Boolean DateWithin30Days(Date date1, Date date2) {
        //check for date2 being in the past
        if( date2 < date1) { return false; }
        if( date2 < date1) { return false; }

        //check that date2 is within (>=) 30 days of date1
        Date date30Days = date1.addDays(30); //create a date 30 days away from date1
        //check that date2 is within (>=) 30 days of date1
        // Date date30Days = date1.addDays(30); //create a date 30 days away from date1
        if( date2 >= date30Days ) { return false; }
        else { return true; }
    }

    //method to return the end of the month of a given date
    @TestVisible private static Date SetEndOfMonthDate(Date date1) {
        Integer totalDays = Date.daysInMonth(date1.year(), date1.month());
        Date lastDay = Date.newInstance(date1.year(), date1.month(), totalDays);
        return lastDay;
    }
}
```

TestVerifyDate .cls


```

@isTest
private class TestVerifyDate {

    @isTest static void Test_CheckDates_case1(){
        Date D = VerifyDate.CheckDates(date.parse('01/01/2020'), date.parse('01/05/2020'));
        System.assertEquals(date.parse('01/05/2020'), D);
    }
    @isTest static void Test_CheckDates_case2(){
        Date D = VerifyDate.CheckDates(date.parse('01/01/2020'), date.parse('05/05/2020'));
        System.assertEquals(date.parse('01/31/2020'), D);
    }
    @isTest static void Test_DateWithin30Days_case1(){
        Boolean flag = VerifyDate.DateWithin30Days(date.parse('01/01/2020'),
date.parse('12/30/2019'));
        System.assertEquals(false, flag);
    }
    @isTest static void Test_DateWithin30Days_case2(){
        Boolean flag = VerifyDate.DateWithin30Days(date.parse('01/01/2020'),
date.parse('02/02/2019'));
        System.assertEquals(false, flag);
    }
    @isTest static void Test_DateWithin30Days_case3(){
        Boolean flag = VerifyDate.DateWithin30Days(date.parse('01/01/2020'),
date.parse('01/15/2019'));
        System.assertEquals(false, flag);
    }
    @isTest static void Test_SetEndOfMonthDate(){
        Date returndate = VerifyDate.SetEndOfMonthDate(date.parse('01/01/2020'));
    }
}

```

Challenge : Test Apex Triggers

RestrictContactByName.cls

```

trigger RestrictContactByName on Contact (before insert, before update) {

    //check contacts prior to insert or update for invalid data
    For (Contact c : Trigger.New) {
        if(c.LastName == 'INVALIDNAME') { //invalidname is invalid
            c.AddError("The Last Name '"+c.LastName+"' is not allowed for DML");
        }
    }
}

```

```
}
```

TestRestrictContactByName .cls

```
@isTest
public class TestRestrictContactByName {

    @isTest static void Test_insertupdateContact(){
        Contact cnt = new Contact();
        cnt.LastName = 'INVALIDNAME';

        Test.startTest();
        Database.SaveResult result = Database.insert(cnt,false);
        Test.stopTest();

        System.assert(!result.isSuccess());
        System.assert(result.getErrors().size() > 0);
        System.assertEquals('The Last Name "INVALIDNAME" is not allowed for DML',
result.getErrors()[0].getMessage());
    }
}
```

Challenge : Create Test Data for Apex Tests

RandomContactFactory .cls

```
public class RandomContactFactory {

    public static List<Contact> generateRandomContacts(Integer numcnt, string lastname){
        List<Contact> contacts = new List<Contact>();
        for(Integer i=0;i<numcnt;i++){
            Contact cnt = new Contact(FirstName = 'Test' +i, LastName = lastname);
            contacts.add(cnt);
        }
        return contacts;
    }
}
```

Apex Triggers

Challenge : Get Started with Apex Triggers

AccountAddressTrigger.cls

```
trigger AccountAddressTrigger on Account (before insert,before update) {  
  
    for(Account account:Trigger.New){  
        if(account.Match_Billing_Address__c == True){  
            account.ShippingPostalCode = account.BillingPostalCode;  
        }  
    }  
}
```

Challenge : Bulk Apex Triggers

ClosedOpportunityTrigger.cls

```
trigger ClosedOpportunityTrigger on Opportunity (after insert, after update) {  
    List<Task> taskList = new List<Task>();  
  
    for(Opportunity opp: Trigger.New){  
        if(opp.StageName == 'Closed Won'){  
            taskList.add(new Task(Subject = 'Follow Up Test Task', WhatId = opp.Id));  
        }  
    }  
    if(taskList.size()>0){  
        insert taskList;  
    }  
}
```

Asynchronous Apex :

Challenge : Use Future Methods

AccountProcessor .cls

```

public class AccountProcessor {
    @future
    public static void countContacts(List<Id> accountIds){
        List<Account> accountsToUpdate = new List<Account>();
        List<Account> accounts = [Select Id, Name, (Select Id from Contacts) from Account Where Id in :accountIds];

        for(Account acc:accounts){
            List<Contact> contactList = acc.Contacts;
            acc.Number_Of_Contacts__c = contactList.size();
            accountsToUpdate.add(acc);
        }
        update accountsToUpdate;
    }
}

```

AccountProcessorTest .cls

```

@IsTest
private class AccountProcessorTest {
    @IsTest
    private static void testCountContacts(){
        Account newAccount = new Account(Name='Test Account');
        insert newAccount;

        Contact newContact1 = new Contact(FirstName='John',LastName='Doe',AccountId =
newAccount.Id);
        insert newContact1;

        Contact newContact2 = new Contact(FirstName='Jane',LastName='Doe',AccountId =
newAccount.Id);
        insert newContact2;

        List<Id> accountIds = new List<Id>();
        accountIds.add(newAccount.Id);

        Test.startTest();
        AccountProcessor.countContacts(accountIds);
        Test.stopTest();
    }
}

```

Challenge : Use Batch Apex

LeadProcessor .cls

```

global class LeadProcessor implements Database.Batchable<sObject>{
    global Integer count = 0;

    global Database.QueryLocator start(Database.BatchableContext bc){
        return Database.getQueryLocator('SELECT ID, LeadSource FROM Lead');
    }
    global void execute (Database.BatchableContext bc, List<Lead> L_list){
        List<Lead> L_List_new = new List<Lead>();

        for(lead L:L_list){
            L.leadsource = 'Dreamforce';
            L_list_new.add(L);
            count += 1;
        }
        update L_list_new;
    }
    global void finish(Database.BatchableContext bc){
        system.debug('count = ' +count);
    }
}

```

LeadProcessorTest.cls

```

@isTest
public class LeadProcessorTest {

    @isTest
    public static void testify(){
        List<lead> L_list = new List<lead>();

        for(Integer i=0; i<200; i++){
            Lead L = new lead();
            L.LastName = 'name' +i;
            L.Company = 'Company';
            L.Status = 'Random Status';
            L_list.add(L);
        }
        insert L_list;

        Test.startTest();
        LeadProcessor lp = new LeadProcessor();
        Id batchId = Database.executeBatch(lp);
        Test.stopTest();
    }
}

```

```
}  
}
```

Challenge : Control Processes with Queueable Apex

AddPrimaryContact.cls

```
public class AddPrimaryContact implements Queueable {  
  
    private Contact con;  
    private String state;  
  
    public AddPrimaryContact(Contact con, String state){  
        this.con = con;  
        this.state = state;  
    }  
    public void execute(QueueableContext context){  
        List<Account> accounts = [Select Id, Name, (Select FirstName, LastName, Id from  
contacts)  
                                from Account where BillingState = :state Limit 200];  
        List<Contact> primaryContacts = new List<Contact>();  
  
        for(Account acc:accounts){  
            Contact c = con.clone();  
            c.AccountId = acc.Id;  
            primaryContacts.add(c);  
        }  
        if(primaryContacts.size() > 0){  
            insert primaryContacts;  
        }  
    }  
}
```

AddPrimaryContactTest.cls

```

@isTest
public class AddPrimaryContactTest {

    static testmethod void testQueueable(){
        List<Account> testAccounts = new List<Account>();
        for(Integer i=0;i<50;i++){
            testAccounts.add(new Account(Name='Account '+i,BillingState='CA'));
        }
        for(Integer j=0;j<50;j++){
            testAccounts.add(new Account(Name='Account '+j,BillingState='NY'));
        }
        insert testAccounts;

        Contact testContact = new Contact(FirstName = 'John', LastName = 'Doe');
        insert testContact;

        AddPrimaryContact addit = new addPrimaryContact(testContact, 'CA');

        Test.startTest();
        system.enqueueJob(addit);
        Test.stopTest();

        System.assertEquals(50,[Select count() from Contact where accountId in (Select Id from
Account Where BillingState='CA')]);
    }
}

```

Challenge : Schedule Jobs Using the Apex Scheduler

DailyLeadProcessor .cls

```

global class DailyLeadProcessor implements Schedulable {
    global void execute(SchedulableContext ctx) {
        List<lead> leadstoupdate = new List<lead>();
        List<Lead> leads = [Select id From Lead Where LeadSource = NULL Limit 200];

        for(Lead l:leads){
            l.LeadSource = 'Dreamforce';
            leadstoupdate.add(l);
        }
        update leadstoupdate;
    }
}

```

DailyLeadProcessorTest .cls

@isTest

private class DailyLeadProcessorTest {

public static String CRON_EXP = '0 0 0 15 3 ? 2022';

static testmethod void testScheduledJob(){

List<Lead> leads = new List<lead>();

for (Integer i=0; i<200; i++){

Lead l = new Lead(

FirstName = 'First ' + i,

LastName = 'LastName',

Company = 'The Inc'

);

leads.add(l);

}

insert leads;

Test.startTest();

DailyLeadProcessor ab = new DailyLeadProcessor();

String jobId = System.schedule('jobName', '0 5 * * * ?', ab);

Test.stopTest();

List<Lead> checkleads = new List<Lead>();

checkleads = [select Id From Lead Where LeadSource = 'Dreamforce' and Company = 'The Inc'];

System.assertEquals(200, checkleads.size(), 'Leads were not created');

}

}

Apex Integration Services

Challenge : Apex REST Callouts

AnimalLocator .cls

```
public class AnimalLocator {
    public static string getAnimalNameById(Integer id) {
        Http http = new Http();
        HttpRequest req = new HttpRequest();
        req.setEndpoint('https://th-apex-http-callout.herokuapp.com/animals/'+id);
        req.setMethod('GET');
        Map<String,Object> animals = new Map<String,Object>();
        HttpResponse res = http.send(req);
        // If the request is successful, parse the JSON response.
        if(res.getStatusCode() == 200) {
            Map<String,Object> results = (Map<String,Object>)
            JSON.deserializeUntyped(res.getBody());
            animals = (Map<String,Object>)results.get('animal');
        }
        else{
            System.debug("The status code returned was not
            expected: '"+res.getStatusCode()+"'+res.getStatus());
        }
        return (string)animals.get('name');
    }
}
```

AnimalLocatorTest .cls

```
@isTest
private class AnimalLocatorTest{
    @isTest static void AnimalsCalloutsTest(){
        Test.setMock(HttpCalloutMock.class, new AnimalLocatorMock());
        String result = AnimalLocator.getAnimalNameById(1);
        String expectedValue = 'chicken';
        System.assertEquals(result,expectedValue);
    }
}
```

AnimalLocatorMock .cls

```

@Test
global class AnimalLocatorMock implements HttpCalloutMock{
    // Implement this interface method
    global HTTPResponse respond(HTTPRequest request) {
        // Create a fake response
        HTTPResponse response = new HTTPResponse();
        response.setHeader('Content-Type', 'application/json');
        response.setBody('{"animals":{"id":1,"name":"chicken","eats":"chicken
food","says":"cluck cluck"}}');
        //response.setBody('{"animals":{"id":1,"name":"chicken"}}');
        response.setStatusCode(200);
        return response;
    }
}

```

AnimalsHttpCalloutMock .cls

```

@Test
global class AnimalsHttpCalloutMock implements HttpCalloutMock {
    // Implement this interface method
    global HTTPResponse respond(HTTPRequest request) {
        // Create a fake response
        HTTPResponse response = new HTTPResponse();
        response.setHeader('Content-Type', 'application/json');
        response.setBody('{"animals": ["majestic badger", "fluffy bunny", "scary bear",
"chicken", "mighty moose"]}');
        response.setStatusCode(200);
        return response;
    }
}

```

Challenge : Apex SOAP Callouts

ParkService.cls

//Generated by wsdl2apex

```

public class ParkService {
    public class byCountryResponse {
        public String[] return_x;
        private String[] return_x_type_info = new String[] {'return','http://parks.services/',null,'0','-
1','false'};
    }
}

```

```

        private String[] apex_schema_type_info = new
String[] { 'http://parks.services/', 'false', 'false' };
        private String[] field_order_type_info = new String[] { 'return_x' };
    }
    public class byCountry {
        public String arg0;
        private String[] arg0_type_info = new
String[] { 'arg0', 'http://parks.services/', null, '0', '1', 'false' };
        private String[] apex_schema_type_info = new
String[] { 'http://parks.services/', 'false', 'false' };
        private String[] field_order_type_info = new String[] { 'arg0' };
    }
    public class ParksImplPort {
        public String endpoint_x = 'https://th-apex-soap-service.herokuapp.com/service/parks';
        public Map<String,String> inputHttpHeaders_x;
        public Map<String,String> outputHttpHeaders_x;
        public String clientCertName_x;
        public String clientCert_x;
        public String clientCertPasswd_x;
        public Integer timeout_x;
        private String[] ns_map_type_info = new String[] { 'http://parks.services/', 'ParkService' };
        public String[] byCountry(String arg0) {
            ParkService.byCountry request_x = new ParkService.byCountry();
            request_x.arg0 = arg0;
            ParkService.byCountryResponse response_x;
            Map<String, ParkService.byCountryResponse> response_map_x = new Map<String,
ParkService.byCountryResponse>();
            response_map_x.put('response_x', response_x);
            WebServiceCallout.invoke(
                this,
                request_x,
                response_map_x,
                new String[] { endpoint_x,
                    "",
                    'http://parks.services/',
                    'byCountry',
                    'http://parks.services/',
                    'byCountryResponse',
                    'ParkService.byCountryResponse' }
            );
            response_x = response_map_x.get('response_x');
            return response_x.return_x;
        }
    }
}

```

ParkLocator.cls

```
public class ParkLocator {  
    public static List<String> country(String country){  
        ParkService.ParksImplPort parkservice =  
            new parkService.ParksImplPort();  
        return parkservice.byCountry(country);  
    }  
}
```

ParkLocatorTest.cls

```
@isTest  
private class ParkLocatorTest {  
    @isTest static void testCallout() {  
        // This causes a fake response to be generated  
        Test.setMock(WebServiceMock.class, new ParkServiceMock());  
        // Call the method that invokes a callout  
        String country = 'United States';  
        List<String> result = ParkLocator.country(country);  
        List<String> parks = new List<String>();  
        parks.add('yosemite');  
        parks.add('Yellowstone');  
        parks.add('Another Park');  
        // Verify that a fake result is returned  
        System.assertEquals(parks, result);  
    }  
}
```

ParkServiceMock.cls

```
@isTest  
global class ParkServiceMock implements WebServiceMock {  
    global void doInvoke(  
        Object stub,  
        Object request,  
        Map<String, Object> response,  
        String endpoint,  
        String soapAction,  
        String requestName,  
        String responseNS,  
        String responseName,  
        String responseType) {  
        // start - specify the response you want to send  
        List<String> parks = new List<String>();
```

```

        parks.add('yosemite');
        parks.add('Yellowstone');
        parks.add('Another Park');
    ParkService.byCountryResponse response_x =
        new ParkService.byCountryResponse();
    response_x.return_x = parks;
    // end
    response.put('response_x', response_x);
}
}

```

Challenge : Apex Web Services

AccountManager .cls

```

@RestResource(urlMapping = '/Accounts/*/contacts')
global with sharing class AccountManager {
    @HttpGet
    global static Account getAccount(){
        RestRequest request = RestContext.request;
        string accountId = request.requestURI.substringBetween('Accounts/', '/contacts');
        Account result = [SELECT Id, Name, (Select Id, Name from Contacts) from Account where
        Id=:accountId Limit 1];
        return result;
    }
}

```

AccountManagerTest .cls

```

@isTest
public class AccountManagerTest {
    @isTest static void testGetContactByAccountId(){
        Id recordId = createTestRecord();
        RestRequest request = new RestRequest();
        request.requestUri = 'https://yourInstance.my.salesforce.com/services/apexrest/Accounts/'
            + recordId + '/contacts';
        request.httpMethod = 'GET';
        RestContext.request = request;
        Account thisAccount = AccountManager.getAccount();
        System.assert(thisAccount != null);
        System.assertEquals('Test record', thisAccount.Name);
    }
}

```

```
static Id createTestRecord(){
    Account accountTest = new Account(
        Name = 'Test record');
    insert accountTest;

    Contact contactTest = new Contact(
        FirstName = 'John',
        LastName = 'Doe',
        AccountId = accountTest.Id
    );
    insert contactTest;

    return accountTest.Id;
}
}
```


